



# TEST REPORT

**Report Reference No.** : TRE1610003903      **R/C** : 97667

**FCC ID** : 2AAA6-S130

**Applicant's name** : SENWA MEXICO,S.A.D.E C.V

**Address** : Av. Javier Barros Sierra 540,Torre I, Piso 5; COL. LOMAS DE SANTA FE DELEGACION ALVARO OBREGON C.P. 01210 MEXICO,DISTRITO FEDERAL

**Manufacturer** : Senwa Mobile HK Ltd

**Address** : Room 910, International Trade Centre 11-19 Sha Tsui Road, Tsuen Wan, NT, HK

**Test item description** : Mobile Phone

**Trade Mark** : SENWA

**Model/Type reference** : S130

**Listed Model(s)** : -

**Standard** : FCC CFR Title 47 Part 15 Subpart C Section 15.247

**Date of receipt of test sample** : Oct. 17, 2016

**Date of testing** : Oct. 18, 2016 - Nov. 01, 2016

**Date of issue** : Nov. 01, 2016

**Result** : PASS

Compiled by  
(position+printedname+signature) : File administrators Becky Liang

Supervised by  
(position+printedname+signature) : Project Engineer Lion Cai

Approved by  
(position+printedname+signature) : RF Manager Hans Hu

**Testing Laboratory Name** : Shenzhen Huatongwei International Inspection Co., Ltd.

**Address** : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

**Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

## Contents

|           |  |           |
|-----------|--|-----------|
| <u>1.</u> | <u>TEST STANDARDS AND TEST DESCRIPTION</u>     | <u>3</u>  |
| 1.1.      | Test Standards                                 | 3         |
| 1.2.      | Test Description                               | 3         |
| <u>2.</u> | <u>SUMMARY</u>                                 | <u>4</u>  |
| 2.1.      | Client Information                             | 4         |
| 2.2.      | Product Description                            | 4         |
| 2.3.      | Operation state                                | 5         |
| 2.4.      | EUT configuration                              | 5         |
| 2.5.      | Modifications                                  | 5         |
| <u>3.</u> | <u>TEST ENVIRONMENT</u>                        | <u>6</u>  |
| 3.1.      | Address of the test laboratory                 | 6         |
| 3.2.      | Test Facility                                  | 6         |
| 3.3.      | Environmental conditions                       | 7         |
| 3.4.      | Statement of the measurement uncertainty       | 7         |
| 3.5.      | Equipments Used during the Test                | 8         |
| <u>4.</u> | <u>TEST CONDITIONS AND RESULTS</u>             | <u>9</u>  |
| 4.1.      | Antenna requirement                            | 9         |
| 4.2.      | Conducted Emission (AC Main)                   | 10        |
| 4.3.      | Conducted Peak Output Power                    | 13        |
| 4.4.      | 20dB Emission Bandwidth                        | 16        |
| 4.5.      | Carrier Frequencies Separation                 | 19        |
| 4.6.      | Hopping Channel Number                         | 21        |
| 4.7.      | Dwell Time                                     | 23        |
| 4.8.      | Pseudorandom Frequency Hopping Sequence        | 26        |
| 4.9.      | Restricted band (radiated)                     | 27        |
| 4.10.     | Bandedge and Spurious Emission (conducted)     | 29        |
| 4.11.     | Spurious Emission (radiated)                   | 36        |
| <u>5.</u> | <u>TEST SETUP PHOTOS OF THE EUT</u>            | <u>41</u> |
| <u>6.</u> | <u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u> | <u>42</u> |

## 1. **TEST STANDARDS AND TEST DESCRIPTION**

### 1.1. **Test Standards**

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

### 1.2. **Test Description**

| ReportSection | Test Item                               | Section in CFR 47                             | Result |
|---------------|---|---|--------|
| 4.1           | Antenna Requirement                     | 15.203/15.247 (c)                             | Pass   |
| 4.2           | AC Power Line Conducted Emission        | 15.207  | Pass   |
| 4.3           | Conducted Peak Output Power             | 15.247 (b)(1)                                 | Pass   |
| 4.4           | 20dB Occupied Bandwidth                 | 15.247 (a)(1)                                 | Pass   |
| 4.5           | Carrier Frequencies Separation          | 15.247 (a)(1)                                 | Pass   |
| 4.6           | Hopping Channel Number                  | 15.247 (a)(1)                                 | Pass   |
| 4.7           | Dwell Time                              | 15.247 (a)(1)                                 | Pass   |
| 4.8           | Pseudorandom Frequency Hopping Sequence | 15.247(b)(4)&TCB Exclusion List (7 July 2002) | Pass   |
| 4.9           | Restricted band                         | 15.247(d)/15.205                              | Pass   |
| 4.10/4.11     | Radiated Emission                       | 15.247(d)/15.209                              | Pass   |

Remark: The measurement uncertainty is not included in the test result.

## 2. SUMMARY

### 2.1. Client Information

|               |   |
|---------------|---|
| Applicant:    | SENWA MEXICO,S.A.DE C.V   |
| Address:      | Av. Javier Barros Sierra 540,Torre I, Piso 5; COL. LOMAS DE SANTA FE DELEGACION ALVARO OBREGON C.P. 01210 MEXICO,DISTRITO FEDERAL |
| Manufacturer: | Senwa Mobile HK Ltd   |
| Address:      | Room 910, International Trade Centre 11-19 Sha Tsui Road, Tsuen Wan, NT, HK   |

### 2.2. Product Description

|                      |   |
|----------------------|---|
| Name of EUT          | Mobile Phone  |
| Trade Mark:          | SENWA   |
| Model No.:           | S130  |
| Listed Model(s):     | -   |
| IMEI 1:              | 359432070000445   |
| Power supply:        | DC 3.7V From internal battery   |
| Adapter information: | Model: S130<br>Input: 100-240V a.c., 50-60Hz, 0.15A<br>Output: 5V d.c., 500mA |
| <b>Bluetooth</b>     |   |
| Version:             | Supported BT2.1+ EDR compatibility  |
| Modulation:          | GFSK, π/4DQPSK, 8DPSK   |
| Operation frequency: | 2402MHz~2480MHz   |
| Channel number:      | 79  |
| Channel separation:  | 1MHz  |
| Antenna type:        | Internal Antenna  |
| Antenna gain:        | 1.4dBi  |

## 2.3. Operation state

### ◆ Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channel which were tested. the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

| Channel | Frequency (MHz) |
|---------|-----------------|
| 0       | 2402            |
| 1       | 2403            |
| :       | :               |
| 39      | 2441            |
| :       | :               |
| 77      | 2479            |
| 78      | 2480            |

### ◆ Test mode

For RF test items:

the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions:

the EUT was set to connect with the Bluetooth under large package sizes transmission.

## 2.4. EUT configuration

**The following peripheral devices and interface cables were connected during the measurement:**

- - supplied by the manufacturer
- - supplied by the lab

|  |                |   |
|--|----------------|---|
|  | Length (m) :   | / |
|  | Shield :       | / |
|  | Detachable :   | / |
|  | Manufacturer : | / |
|  | Model No. :    | / |

## 2.5. Modifications

No modifications were implemented to meet testing criteria.

### **3. TEST ENVIRONMENT**

#### **3.1. Address of the test laboratory**

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Phone: 86-755-26748019 Fax: 86-755-26748089

#### **3.2. Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

##### **CNAS-Lab Code: L1225**

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories, Date of Registration: February 28, 2015. Valid time is until February 27, 2018.

##### **A2LA-Lab Cert. No. 3902.01**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing. Valid time is until December 31, 2016.

##### **FCC-Registration No.: 317478**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 317478, Renewal date Jul. 18, 2014, valid time is until Jul. 18, 2017.

##### **IC-Registration No.: 5377A&5377B**

The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377A on Dec. 31, 2013, valid time is until Dec. 31, 2016.

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377B on Dec.03, 2014, valid time is until Dec.03, 2017.

##### **ACA**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

##### **VCCI**

The 3m Semi-

anechoic chamber (12.2m×7.95m×6.7m) of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2484. Date of Registration: Dec. 20, 2012. Valid time is until Dec. 29, 2015.

Radiated disturbance above 1GHz measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-292. Date of Registration: Dec. 24, 2013. Valid time is until Dec. 23, 2016.

Main Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: C-2726. Date of Registration: Dec. 20, 2012. Valid time is until Dec. 19, 2015.

Telecommunication Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: T-1837. Date of Registration: May 07, 2013. Valid time is until May 06, 2016.

##### **DNV**

Shenzhen Huatongwei International Inspection Co., Ltd. has been found to comply with the requirements of DNV towards subcontractor of EMC and safety testing services in conjunction with the EMC and Low voltage Directives and in the voluntary field. The acceptance is based on a formal quality Audit and follow-ups according to relevant parts of ISO/IEC Guide 17025 (2005), in accordance with the requirements of the DNV Laboratory Quality Manual towards subcontractors. Valid time is until Aug. 24, 2016.

### 3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

|                    |             |
|--------------------|-------------|
| Temperature:       | 15~35°C     |
| Relative Humidity: | 30~60 %     |
| Air Pressure:      | 950~1050mba |

### 3.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

| Test Items                              | Measurement Uncertainty | Notes |
|---|-------------------------|-------|
| Transmitter power conducted             | 0.57 dB                 | (1)   |
| Transmitter power Radiated              | 2.20 dB                 | (1)   |
| Conducted spurious emission 9KHz-40 GHz | 1.60 dB                 | (1)   |
| Radiated spurious emission 9KHz-40 GHz  | 2.20 dB                 | (1)   |
| Conducted Emission 9KHz-30MHz           | 3.39 dB                 | (1)   |
| Radiated Emission 30~1000MHz            | 4.24 dB                 | (1)   |
| Radiated Emissio 1~18GHz                | 5.16 dB                 | (1)   |
| Radiated Emissio 18-40GHz               | 5.54 dB                 | (1)   |
| Occupied Bandwidth                      | -----                   | (1)   |

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=1.96$ .

### 3.5. Equipments Used during the Test

| Conducted Emission (AC Main) |                   |               |             |            |            |
|------------------------------|-------------------|---------------|-------------|------------|------------|
| Item                         | Test Equipment    | Manufacturer  | Model No.   | Serial No. | Last Cal   |
| 1                            | Artificial Mains  | Rohde&Schwarz | ESH2-Z5     | 100028     | 2015/11/02 |
| 2                            | EMI Test Receiver | Rohde&Schwarz | ESCI3       | 100038     | 2015/11/02 |
| 3                            | Pulse Limiter     | Rohde&Schwarz | ESHSZ2      | 100044     | 2015/11/02 |
| 4                            | EMI Test Software | Rohde&Schwarz | ES-K1 V1.71 | N/A        | N/A        |

| Radiated Emission |                         |                              |                    |            |            |
|-------------------|-------------------------|------------------------------|--------------------|------------|------------|
| Item              | Test Equipment          | Manufacturer                 | Model No.          | Serial No. | Last Cal   |
| 1                 | Ultra-Broadband Antenna | ShwarzBeck                   | VULB9163           | 538        | 2015/11/02 |
| 2                 | EMI TEST RECEIVER       | Rohde&Schwarz                | ESI 26             | 100009     | 2015/11/02 |
| 3                 | EMI TEST Software       | Audix                        | E3                 | N/A        | N/A        |
| 4                 | TURNTABLE               | ETS                          | 2088               | 2149       | N/A        |
| 5                 | ANTENNA MAST            | ETS                          | 2075               | 2346       | N/A        |
| 6                 | EMI TEST Software       | Rohde&Schwarz                | ESK1               | N/A        | N/A        |
| 7                 | HORNANTENNA             | ShwarzBeck                   | 9120D              | 1011       | 2015/11/02 |
| 8                 | Amplifier               | Sonoma                       | 310N               | E009-13    | 2015/11/02 |
| 9                 | JS amplifier            | Rohde&Schwarz                | JS4-00101800-28-5A | F201504    | 2015/11/02 |
| 10                | High pass filter        | Compliance Direction systems | BSU-6              | 34202      | 2015/11/02 |
| 11                | HORNANTENNA             | ShwarzBeck                   | 9120D              | 1012       | 2015/11/02 |
| 12                | Amplifier               | Compliance Direction systems | PAP1-4060          | 120        | 2015/11/02 |
| 13                | Loop Antenna            | Rohde&Schwarz                | HFH2-Z2            | 100020     | 2015/11/02 |
| 14                | TURNTABLE               | MATURO                       | TT2.0              | ----       | N/A        |
| 15                | ANTENNA MAST            | MATURO                       | TAM-4.0-P          | ----       | N/A        |
| 16                | Horn Antenna            | SCHWARZBECK                  | BBHA9170           | 25841      | 2015/11/02 |
| 17                | ULTRA-BROADBAND ANTENNA | Rohde&Schwarz                | HL562              | 100015     | 2015/11/02 |

Maximum Peak Output Power / Power Spectral Density / 6dB Bandwidth / Band Edge Compliance of RF Emission / Spurious RF Conducted Emission

| Item | Test Equipment    | Manufacturer  | Model No. | Serial No.   | Last Cal   |
|------|-------------------|---------------|-----------|--------------|------------|
| 1    | Spectrum Analyzer | Rohde&Schwarz | FSP       | 1164.4391.40 | 2015/11/02 |

The Cal.Interval was one year

## 4. **TEST CONDITIONS AND RESULTS**

### 4.1. Antenna requirement

#### Requirement

##### **FCC CFR Title 47 Part 15 Subpart C Section 15.203:**


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

##### **FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):**

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

#### Test Result:

The antenna is integral antenna, the best case gain of the antenna is 1.4dBi



## 4.2. Conducted Emission (AC Main)


### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

| Frequency range (MHz) | Limit (dBuV) |           |
|-----------------------|--------------|-----------|
|                       | Quasi-peak   | Average   |
| 0.15-0.5              | 66 to 56*    | 56 to 46* |
| 0.5-5                 | 56           | 46        |
| 5-30                  | 60           | 50        |

\* Decreases with the logarithm of the frequency.


### TEST CONFIGURATION



### TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.

### TEST RESULTS


**MEASUREMENT RESULT: "GM1608035003\_fin"**


10/19/2016 10:33AM

| Frequency<br>MHz | Level<br>dB $\mu$ V | Transd<br>dB | Limit<br>dB $\mu$ V | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------------|--------------|---------------------|--------------|----------|------|-----|
| 0.159000         | 45.70               | 10.3         | 66                  | 19.8         | QP       | L1   | GND |
| 0.483000         | 42.40               | 10.2         | 56                  | 13.9         | QP       | L1   | GND |
| 0.928500         | 36.70               | 10.3         | 56                  | 19.3         | QP       | L1   | GND |
| 1.990500         | 35.40               | 10.3         | 56                  | 20.6         | QP       | L1   | GND |
| 4.218000         | 37.30               | 10.4         | 56                  | 18.7         | QP       | L1   | GND |
| 5.289000         | 36.40               | 10.5         | 60                  | 23.6         | QP       | L1   | GND |

**MEASUREMENT RESULT: "GM1608035003\_fin2"**

10/19/2016 10:33AM

| Frequency<br>MHz | Level<br>dB $\mu$ V | Transd<br>dB | Limit<br>dB $\mu$ V | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------------|--------------|---------------------|--------------|----------|------|-----|
| 0.159000         | 35.80               | 10.3         | 56                  | 19.7         | AV       | L1   | GND |
| 0.276000         | 30.70               | 10.2         | 51                  | 20.2         | AV       | L1   | GND |
| 0.483000         | 37.50               | 10.2         | 46                  | 8.8          | AV       | L1   | GND |
| 0.937500         | 31.60               | 10.3         | 46                  | 14.4         | AV       | L1   | GND |
| 2.080500         | 30.90               | 10.3         | 46                  | 15.1         | AV       | L1   | GND |
| 3.183000         | 30.80               | 10.4         | 46                  | 15.2         | AV       | L1   | GND |


**MEASUREMENT RESULT: "GM1608035004\_fin"**

10/19/2016 10:36AM

| Frequency<br>MHz | Level<br>dB $\mu$ V | Transd<br>dB | Limit<br>dB $\mu$ V | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------------|--------------|---------------------|--------------|----------|------|-----|
| 0.159000         | 44.20               | 10.3         | 66                  | 21.3         | QP       | N    | GND |
| 0.478500         | 36.40               | 10.2         | 56                  | 20.0         | QP       | N    | GND |
| 0.906000         | 29.70               | 10.2         | 56                  | 26.3         | QP       | N    | GND |
| 1.320000         | 29.90               | 10.3         | 56                  | 26.1         | QP       | N    | GND |
| 4.263000         | 30.60               | 10.4         | 56                  | 25.4         | QP       | N    | GND |
| 5.190000         | 30.90               | 10.5         | 60                  | 29.1         | QP       | N    | GND |

**MEASUREMENT RESULT: "GM1608035004\_fin2"**

10/19/2016 10:36AM

| Frequency<br>MHz | Level<br>dB $\mu$ V | Transd<br>dB | Limit<br>dB $\mu$ V | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------------|--------------|---------------------|--------------|----------|------|-----|
| 0.159000         | 30.40               | 10.3         | 56                  | 25.1         | AV       | N    | GND |
| 0.478500         | 26.00               | 10.2         | 46                  | 20.4         | AV       | N    | GND |
| 0.928500         | 21.20               | 10.3         | 46                  | 24.8         | AV       | N    | GND |
| 4.330500         | 20.70               | 10.4         | 46                  | 25.3         | AV       | N    | GND |
| 5.140500         | 20.90               | 10.5         | 50                  | 29.1         | AV       | N    | GND |
| 29.238000        | 25.70               | 10.9         | 50                  | 24.3         | AV       | N    | GND |


Remark: Transd=Cable loss+ PULSE LIMITER factor+ ARTIFICIAL MAINS factor; Margin= Limit -Level

### 4.3. Conducted Peak Output Power

#### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): **30dBm**

#### TEST CONFIGURATION




#### TEST PROCEDURE

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum.

#### TEST RESULTS

| Modulation type | Channel | Output power (dBm) | Limit (dBm) | Result |
|-----------------|---------|--------------------|-------------|--------|
| GFSK            | 00      | -9.93              | 30.00       | Pass   |
|                 | 39      | -11.44             |             |        |
|                 | 78      | -11.46             |             |        |
| $\pi/4$ DQPSK   | 00      | -10.44             | 21.00       | Pass   |
|                 | 39      | -11.72             |             |        |
|                 | 78      | -11.70             |             |        |
| 8DPSK           | 00      | -10.55             | 21.00       | Pass   |
|                 | 39      | -11.93             |             |        |
|                 | 78      | -12.02             |             |        |

Test plot as follows:






## 4.4. 20dB Emission Bandwidth

### LIMIT

N/A

### TEST CONFIGURATION




### TEST PROCEDURE


1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. The bandwidth of the fundamental frequency was measured by spectrum analyzer with  $RBW \geq 1\%$  of the 20 dB bandwidth and  $VBW \geq RBW$ .
3. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

### TEST RESULTS

| Modulation type | Channel | 20dB Bandwidth (MHz) | Limit (MHz) | Result |
|-----------------|---------|----------------------|-------------|--------|
| GFSK            | 00      | 0.845                | /           | Pass   |
|                 | 39      | 0.880                |             |        |
|                 | 78      | 0.880                |             |        |
| $\pi/4$ DQPSK   | 00      | 1.132                | /           | Pass   |
|                 | 39      | 1.136                |             |        |
|                 | 78      | 1.132                |             |        |
| 8DPSK           | 00      | 1.147                | /           | Pass   |
|                 | 39      | 1.147                |             |        |
|                 | 78      | 1.140                |             |        |

Test plot as follows:






## 4.5. Carrier Frequencies Separation

### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the  $2/3 \times 20$ dB bandwidth of the hopping channel, whichever is greater.

### TEST CONFIGURATION




### TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. The bandwidth of the fundamental frequency was measured by spectrum analyzer with  $RBW=30$  KHz and  $VBW=100$  KHz.

### TEST RESULTS

| Modulation type | Channel | Carrier Frequencies Separation (MHz) | Limit (MHz) | Result |
|-----------------|---------|--------------------------------------|-------------|--------|
| GFSK            | 39      | 1.001                                | 0.845       | Pass   |
| $\pi/4$ DQPSK   | 39      | 1.001                                | 0.757       | Pass   |
| 8DPSK           | 39      | 1.001                                | 0.760       | Pass   |

Test plot as follows:




## 4.6. Hopping Channel Number

### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least **15** channels.

### TEST CONFIGURATION



### TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=1MHz and VBW=3MHz.

### TEST RESULTS

| Modulation type | Channel number | Limit (MHz) | Result |
|-----------------|----------------|-------------|--------|
| GFSK            | 79             | 15          | Pass   |
| $\pi/4$ DQPSK   | 79             |             |        |
| 8DPSK           | 79             |             |        |

Test plot as follows:




## 4.7. Dwell Time

### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

*The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.*

### TEST CONFIGURATION



### TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. Set center frequency of spectrum analyzer=operating frequency with RBW=1MHz and VBW=1MHz,Span=0Hz.


### TEST RESULTS

| Modulation type | Channel | Dwell time (Second) | Limit (Second) | Result |
|-----------------|---------|---------------------|----------------|--------|
| GFSK            | DH1     | 0.413               | 0.40           | Pass   |
|                 | DH3     | 1.667               |                |        |
|                 | DH5     | 2.920               |                |        |
| $\pi/4$ DQPSK   | 2-DH1   | 0.420               | 0.40           | Pass   |
|                 | 2-DH3   | 1.674               |                |        |
|                 | 2-DH5   | 2.928               |                |        |
| 8DPSK           | 3-DH1   | 0.431               | 0.40           | Pass   |
|                 | 3-DH3   | 1.667               |                |        |
|                 | 3-DH5   | 2.717               |                |        |


Note:

1. We have tested all mode at high,middle and low channel, and recorded worst case at middle channel.
2. Dwell time=Pulse time (ms)  $\times$   $(1600 \div 2 \div 79) \times 31.6$  Second for DH1, 2-DH1, 3-DH1  
Dwell time=Pulse time (ms)  $\times$   $(1600 \div 4 \div 79) \times 31.6$  Second for DH3, 2-DH3, 3-DH3  
Dwell time=Pulse time (ms)  $\times$   $(1600 \div 6 \div 79) \times 31.6$  Second for DH5, 2-DH5, 3-DH5


Test plot as follows:




## 8DPSK



## 3-DH1



## 3-DH3



## 3-DH5

## 4.8. Pseudorandom Frequency Hopping Sequence

### LIMIT


FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

### TEST RESULTS


The pseudorandom frequency hopping sequence may be generated in a nine-stage shift register whose 5<sup>th</sup> and 9<sup>th</sup> stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence:  $2^9 - 1 = 511$  bits
- Longest sequence of zeros: 8 (non-inverted signal)



*Linear Feedback Shift Register for Generation of the PRBS sequence*

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally on the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.


## 4.9. Restricted band (radiated)

### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209

| Frequency  | Limit (dBuV/m @3m) | Value   |
|------------|--------------------|---------|
| Above 1GHz | 54.00              | Average |
|            | 74.00              | Peak    |

### TEST CONFIGURATION



### TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. The receiver set as follow:  
RBW=1MHz, VBW=3MHz for Peak value  
RBW=1MHz, VBW=10Hz for Average value.
6. The frequency range from 2310MHz to 2483.5MHz harmonic is checked.

### TEST RESULTS

| CH00            |                   |                       |                 |                    |                |                     |                   |              |            |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-------------------|--------------|------------|
| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Margin Limit (dB) | Polarization | Test value |
| 2389.02         | 46.42             | 27.53                 | 6.81            | 37.24              | 43.52          | 74                  | -30.48            | Vertical     | Peak       |
| 2389.35         | 45.48             | 27.53                 | 6.81            | 37.24              | 42.58          | 74                  | -31.42            | Horizontal   |            |
| 2386.47         | 41.64             | 27.53                 | 6.81            | 37.24              | 38.74          | 54                  | -15.26            | Vertical     | Average    |
| 2386.29         | 40.55             | 27.53                 | 6.81            | 37.24              | 37.65          | 54                  | -16.35            | Horizontal   |            |

| CH78            |                   |                       |                 |                    |                |                     |                   |              |            |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-------------------|--------------|------------|
| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Margin Limit (dB) | Polarization | Test value |
| 2485.68         | 47.87             | 27.85                 | 6.96            | 37.92              | 44.76          | 74                  | -29.24            | Vertical     | Peak       |
| 2482.75         | 45.8              | 27.85                 | 6.96            | 37.92              | 42.69          | 74                  | -31.31            | Horizontal   |            |
| 2482.97         | 42.86             | 27.85                 | 6.96            | 37.92              | 39.75          | 54                  | -14.25            | Vertical     | Average    |
| 2482.36         | 40.97             | 27.85                 | 6.96            | 37.92              | 37.86          | 54                  | -16.14            | Horizontal   |            |

Note: 1. Level= Read+ Antenna Factor+ Cable Loss- Preamp Factor

2. Have pre-scan all modulation mode, found the GFSK modulation which it was worst case, so only the worst case's data on the test report.


## 4.10. Bandedge and Spurious Emission (conducted)

### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

*In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.*

### TEST CONFIGURATION




### TEST PROCEDURE


1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. Conducted spurious emission the bandwidth of the fundamental frequency was measured by spectrum analyzer with  $RBW=100$  KHz and  $VBW=300$  KHz.
3. Below -20dB of the highest emission level in operating band.


### TEST RESULTS

Test plot as follows:














## 4.11. Spurious Emission (radiated)


### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209


| Frequency     | Limit (dBuV/m @3m) | Value      |
|---------------|--------------------|------------|
| 30MHz-88MHz   | 40.00              | Quasi-peak |
| 88MHz-216MHz  | 43.50              | Quasi-peak |
| 216MHz-960MHz | 46.00              | Quasi-peak |
| 960MHz-1GHz   | 54.00              | Quasi-peak |
| Above 1GHz    | 54.00              | Average    |
|               | 74.00              | Peak       |

### TEST CONFIGURATION


- ◆ Below 30MHz



- ◆ 30MHz~1000MHz



- ◆ Above 1GHz



## TEST PROCEDURE

1. The EUT was placed on the top of a rotating table 0.8 meter above ground for below 1GHz, and 1.5m for above 1GHz at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable was turned from 0 degrees to 360 degrees to find the maximum reading.
5. Use the following spectrum analyzer settings
  - a) Span shall be wide enough to fully capture the emission being measured;
  - b) Below 1GHz, RBW=120KHz, VBW=300KHz, Sweep=auto, Detector function=peak, Trace=max hold;  
*If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.*
  - c) Above 1GHz, RBW=1MHz, VBW=3MHz for Peak value  
RBW=1MHz, VBW=10Hz for Average value.

## TEST RESULTS

### *Noted:*

### *Below 1GHz*

*Have pre-scan all modulation mode, found the GFSK modulation middle channel which it was worst case, so only the worst case's data on the test report.*

### *Above 1GHz*


*Have pre-scan all modulation mode, found the GFSK modulation which it was worst case, so only the worst case's data on the test report.*

### **Measurement data:**

#### **■ 9kHz ~ 30MHz**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.


## ■ 30MHz ~ 1GHz



## MEASUREMENT RESULT: "GM1610256126\_red"

10/25/2016 11:22PM

| Frequency<br>MHz | Level<br>dB $\mu$ V/m | Transd<br>dB | Limit<br>dB $\mu$ V/m | Margin<br>dB | Det. | Height<br>cm | Azimuth<br>deg | Polarization |
|------------------|-----------------------|--------------|-----------------------|--------------|------|--------------|----------------|--------------|
| 47.460000        | 12.50                 | -16.3        | 40.0                  | 27.5         | QP   | 300.0        | 196.00         | HORIZONTAL   |
| 55.220000        | 11.00                 | -16.7        | 40.0                  | 29.0         | QP   | 300.0        | 359.00         | HORIZONTAL   |
| 101.780000       | 11.10                 | -17.5        | 43.5                  | 32.4         | QP   | 100.0        | 221.00         | HORIZONTAL   |
| 210.420000       | 13.50                 | -15.6        | 43.5                  | 30.0         | QP   | 300.0        | 74.00          | HORIZONTAL   |
| 551.860000       | 21.80                 | -6.2         | 46.0                  | 24.2         | QP   | 100.0        | 321.00         | HORIZONTAL   |
| 930.160000       | 30.20                 | 1.4          | 46.0                  | 15.8         | QP   | 300.0        | 159.00         | HORIZONTAL   |



## MEASUREMENT RESULT: "GM1610256127\_red"

10/25/2016 11:24PM

| Frequency<br>MHz | Level<br>dB $\mu$ V/m | Transd<br>dB | Limit<br>dB $\mu$ V/m | Margin<br>dB | Det. | Height<br>cm | Azimuth<br>deg | Polarization |
|------------------|-----------------------|--------------|-----------------------|--------------|------|--------------|----------------|--------------|
| 35.820000        | 11.40                 | -17.6        | 40.0                  | 28.6         | QP   | 100.0        | 66.00          | VERTICAL     |
| 57.160000        | 10.70                 | -16.9        | 40.0                  | 29.3         | QP   | 100.0        | 0.00           | VERTICAL     |
| 115.360000       | 10.00                 | -18.1        | 43.5                  | 33.5         | QP   | 100.0        | 292.00         | VERTICAL     |
| 284.140000       | 14.90                 | -13.4        | 46.0                  | 31.1         | QP   | 100.0        | 160.00         | VERTICAL     |
| 555.740000       | 21.20                 | -6.0         | 46.0                  | 24.8         | QP   | 100.0        | 219.00         | VERTICAL     |
| 916.580000       | 30.00                 | 1.3          | 46.0                  | 16.0         | QP   | 100.0        | 329.00         | VERTICAL     |

Remark: Transd=Cable loss+ Antenna factor- Pre-amplifier; Margin=Limit -Level

## ■ Above 1GHz

| CH00 for GFSK   |                   |                       |                 |                    |                |                     |                   |              |            |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-------------------|--------------|------------|
| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Margin Limit (dB) | Polarization | Test value |
| 4804.00         | 38.01             | 31.28                 | 5.66            | 35.29              | 39.66          | 74.00               | -34.34            | Vertical     | Peak       |
| 7206.00         | 34.64             | 36.22                 | 6.87            | 35.15              | 42.58          | 74.00               | -31.42            | Vertical     |            |
| 9608.00         | 34.75             | 37.85                 | 8.80            | 35.55              | 45.85          | 74.00               | -28.15            | Vertical     |            |
| 11264.26        | *                 |                       |                 |                    |                |                     |                   | Vertical     |            |
| 4804.00         | 38.01             | 31.28                 | 5.66            | 35.29              | 39.66          | 74.00               | -34.34            | Horizontal   |            |
| 7206.00         | 34.53             | 36.22                 | 6.87            | 35.15              | 42.47          | 74.00               | -31.53            | Horizontal   |            |
| 9608.00         | 34.28             | 37.85                 | 8.80            | 35.55              | 45.38          | 74.00               | -28.62            | Horizontal   |            |
| 11264.26        | *                 |                       |                 |                    |                |                     |                   | Horizontal   |            |
| 4804.00         | 32.87             | 31.28                 | 5.66            | 35.29              | 34.52          | 54.00               | -19.48            | Vertical     | Average    |
| 7206.00         | 29.31             | 36.22                 | 6.87            | 35.15              | 37.25          | 54.00               | -16.75            | Vertical     |            |
| 9608.00         | 28.74             | 37.85                 | 8.80            | 35.55              | 39.84          | 54.00               | -14.16            | Vertical     |            |
| 11264.26        | *                 |                       |                 |                    |                |                     |                   | Vertical     |            |
| 4804.00         | 32.68             | 31.28                 | 5.66            | 35.29              | 34.33          | 54.00               | -19.67            | Horizontal   |            |
| 7206.00         | 29.70             | 36.22                 | 6.87            | 35.15              | 37.64          | 54.00               | -16.36            | Horizontal   |            |
| 9608.00         | 28.75             | 37.85                 | 8.80            | 35.55              | 39.85          | 54.00               | -14.15            | Horizontal   |            |
| 11264.26        | *                 |                       |                 |                    |                |                     |                   | Horizontal   |            |
| CH39 for GFSK   |                   |                       |                 |                    |                |                     |                   |              |            |
| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Margin Limit (dB) | Polarization | Test value |
| 4882.00         | 38.15             | 30.88                 | 5.70            | 35.27              | 39.46          | 74.00               | -34.54            | Vertical     | Peak       |
| 7323.00         | 34.92             | 35.82                 | 6.91            | 35.13              | 42.52          | 74.00               | -31.48            | Vertical     |            |
| 9764.00         | 35.59             | 37.45                 | 8.84            | 35.53              | 46.35          | 74.00               | -27.65            | Vertical     |            |
| 12247.62        | *                 |                       |                 |                    |                |                     |                   | Vertical     |            |
| 4882.00         | 38.37             | 30.88                 | 5.70            | 35.27              | 39.68          | 74.00               | -34.32            | Horizontal   |            |
| 7323.00         | 34.92             | 35.82                 | 6.91            | 35.13              | 42.52          | 74.00               | -31.48            | Horizontal   |            |
| 9764.00         | 35.61             | 37.45                 | 8.84            | 35.53              | 46.37          | 74.00               | -27.63            | Horizontal   |            |
| 12247.62        | *                 |                       |                 |                    |                |                     |                   | Horizontal   |            |
| 4882.00         | 33.21             | 30.88                 | 5.70            | 35.27              | 34.52          | 54.00               | -19.48            | Vertical     | Average    |
| 7323.00         | 30.25             | 35.82                 | 6.91            | 35.13              | 37.85          | 54.00               | -16.15            | Vertical     |            |
| 9764.00         | 29.49             | 37.45                 | 8.84            | 35.53              | 40.25          | 54.00               | -13.75            | Vertical     |            |
| 12247.62        | *                 |                       |                 |                    |                |                     |                   | Vertical     |            |
| 4882.00         | 33.12             | 30.88                 | 5.70            | 35.27              | 34.43          | 54.00               | -19.57            | Horizontal   |            |
| 7323.00         | 29.76             | 35.82                 | 6.91            | 35.13              | 37.36          | 54.00               | -16.64            | Horizontal   |            |
| 9764.00         | 30.08             | 37.45                 | 8.84            | 35.53              | 40.84          | 54.00               | -13.16            | Horizontal   |            |
| 12247.62        | *                 |                       |                 |                    |                |                     |                   | Horizontal   |            |

## Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- “\*”, means this data is the too weak instrument of signal is unable to test.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

| CH78 for GFSK   |                   |                       |                 |                    |                |                     |                   |              |            |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-------------------|--------------|------------|
| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Margin Limit (dB) | Polarization | Test value |
| 4960.00         | 38.95             | 30.98                 | 5.73            | 35.32              | 40.34          | 74.00               | -33.66            | Vertical     | Peak       |
| 7440.00         | 34.90             | 35.92                 | 6.94            | 35.18              | 42.58          | 74.00               | -31.42            | Vertical     |            |
| 9920.00         | 35.22             | 37.55                 | 8.87            | 35.58              | 46.06          | 74.00               | -27.94            | Vertical     |            |
| 13214.26        | *                 |                       |                 |                    |                |                     |                   | Vertical     |            |
| 4960.00         | 38.34             | 30.98                 | 5.73            | 35.32              | 39.73          | 74.00               | -34.27            | Horizontal   |            |
| 7440.00         | 34.84             | 35.92                 | 6.94            | 35.18              | 42.52          | 74.00               | -31.48            | Horizontal   |            |
| 9920.00         | 35.53             | 37.55                 | 8.87            | 35.58              | 46.37          | 74.00               | -27.63            | Horizontal   |            |
| 13214.26        | *                 |                       |                 |                    |                |                     |                   | Horizontal   |            |
| 4960.00         | 32.94             | 30.98                 | 5.73            | 35.32              | 34.33          | 54.00               | -19.67            | Vertical     | Average    |
| 7440.00         | 30.17             | 35.92                 | 6.94            | 35.18              | 37.85          | 54.00               | -16.15            | Vertical     |            |
| 9920.00         | 29.79             | 37.55                 | 8.87            | 35.58              | 40.63          | 54.00               | -13.37            | Vertical     |            |
| 13214.26        | *                 |                       |                 |                    |                |                     |                   | Vertical     |            |
| 4960.00         | 33.13             | 30.98                 | 5.73            | 35.32              | 34.52          | 54.00               | -19.48            | Horizontal   |            |
| 7440.00         | 29.68             | 35.92                 | 6.94            | 35.18              | 37.355         | 54.00               | -16.65            | Horizontal   |            |
| 9920.00         | 29.63             | 37.55                 | 8.87            | 35.58              | 40.47          | 54.00               | -13.53            | Horizontal   |            |
| 13214.26        | *                 |                       |                 |                    |                |                     |                   | Horizontal   |            |

## Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

## 5. Test Setup Photos of the EUT

Radiated Emission



Conducted Emission (AC Mains)



## **6. External and Internal Photos of the EUT**

Reference to Test Report No.: TRE1610003901.

.....***End of Report***.....