



### **TEST REPORT**

Applicant	ZONDA HOBBY TECHNOLOGIES ELECTRONIC LIMITED
Address	SUITE NO.2011 20 FLOOR EXCHANGE TOWER 33WANG CHIU ROAD KOWLOON BAY KL IN HONGKONG

Manufacturer or Supplier	ZONDA HOBBY TECHNOLOGIES ELECTRONIC LIMITED	
Address	SUITE NO.2011 20 FLOOR EXCHANGE TOWER 33WANG CHIU ROAD KOWLOON BAY KL IN HONGKONG	
Product	2.4G wireless remote-controlled plane	
Brand Name	ESKY	
Model	ESKY005437	
Additional Model & Model Difference	N/A	
Date of tests	Aug. 01, 2013 ~ Aug. 08, 2013	

The submitted sample of the above equipment has been tested according to the requirements of the following standards:

#### CONCLUSION: The submitted sample was found to **COMPLY** with the test requirement

Manager / EMC Department
Date: Aug. 08, 2013

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



# **TABLE OF CONTENTS**

R	ELEA	ASE	CONTROL RECORD	3
1	s	UMN	MARY OF TEST RESULTS	4
2	N	/IEAS	SUREMENT UNCERTAINTY	4
3	G	ENE	RAL INFORMATION	5
	3.1	GE	NERAL DESCRIPTION OF EUT	5
	3.2	DE	SCRIPTION OF TEST MODES	6
	3.3	GE	NERAL DESCRIPTION OF APPLIED STANDARDS	7
	3.4	DE	SCRIPTION OF SUPPORT UNITS	7
4	Т	EST	TYPES AND RESULTS	8
	4.1	RA	DIATED EMISSION MEASUREMENT	8
	4.	1.1	LIMITS OF RADIATED EMISSION MEASUREMENT	8
	4.	1.2	TEST INSTRUMENTS	9
	4.	1.3	TEST PROCEDURES	. 10
	4.	1.4	DEVIATION FROM TEST STANDARD	. 10
	4.	1.5	TEST SETUP	11
	4.	1.6	EUT OPERATING CONDITIONS	11
	4.	1.7	TEST RESULTS	. 12
	4.2	200	IB BANDWIDTH MEASUREMENT	. 17
	4	.3.1	LIMITS OF 20dB BANDWIDTH MEASUREMENT	. 17
	4	.3.2	TEST INSTRUMENTS	. 17
	4	.3.3	TEST PROCEDURE	. 18
	4	.3.4	DEVIATION FROM TEST STANDARD	. 18
	4	.3.5	TEST SETUP	. 18
	4	.3.6	EUT OPERATING CONDITIONS	. 19
	4	.3.7	TEST RESULTS	. 19
5	Р	нот	OGRAPHS OF THE TEST CONFIGURATION	. 21
6	AF	PPEN	NDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE	
	Εl	JT B	Y THE LAB	. 22



# **RELEASE CONTROL RECORD**

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF130801N001	Original release	Aug. 08, 2013

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

 $\textbf{Email:} \ \underline{\text{customerservice.dg@cn.bureauveritas.com}}$ 



#### 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.249)						
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK			
§15.203	Antenna Requirement	PASS	Compliant			
§15.207 (a)	Conducted Emission	N/A	EUT is powered by battery			
§15.205	Restricted Band of Operation	PASS	Compliant			
§15.209 §15.249(a)	Radiated Emission	PASS	Compliant			
§15.215I	20dB Bandwidth Test	PASS	Compliant			

#### **2 MEASUREMENT UNCERTAINTY**

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.67dB
	30MHz ~1GHz	4.81dB
Radiated emissions	1GHz ~ 18GHz	4.3dB
	18GHz ~ 40GHz	1.94dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



## **3 GENERAL INFORMATION**

#### 3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	2.4G wireless remote-controlled plane
TEST MODEL	ESKY005437
FCC ID	2AAB6-HK0002
NOMINAL VOLTAGE	6V DC (Battery)
MODULATION TYPE	GFSK
OPERATING FREQUENCY	2406-2477MHz
ANTENNA TYPE	Wire Antenna with 0dBi gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	N/A

#### NOTE:

- 1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- 2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

Fax: +86 769 8593 1080 Email: <u>customerservice.dg@cn.bureauveritas.com</u>

Tel: +86 769 8593 5656

Page 5 of 22



#### 3.2 DESCRIPTION OF TEST MODES

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and packet type. The EUT was tested under the following modes, and the final worst is marked in boldface and recorded in the report.

EUT CONFIGURE	APPLICABLE TO				DESCRIPTION
MODE	RE<1G	RE≥1G	PLC	BW	DESCRIPTION
Α	<b>√</b>	√	-	<b>√</b>	Powered by battery

Where **RE<1G:** Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

PLC: Power Line Conducted Emission

BW: 20db bandwidth

Following channel(s) was (were) selected for the test as listed below.

TESTED CHANNEL	TESTED FREQUENCY
Low	2406 MHz
Middle	2444 MHz
High	2477 MHz

Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com

Tel: +86 769 8593 5656

Page 6 of 22



#### **GENERAL DESCRIPTION OF APPLIED STANDARDS**

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.249)** ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

NOTE: It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Verification). The test report has been issued separately.

#### 3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together without any other necessary accessories or support units.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



#### 4 TEST TYPES AND RESULTS

#### 4.1 RADIATED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field strength of fundamental (milli-volts/meter)	Field strength of harmonics (micro-volts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply.

#### NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level  $(dBuV/m) = 20 \log Emission level (uV/m)$ .
- 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



#### 4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Spectrum Analyzer	Agilent	E4446A	MY46180622	Apr. 24,13	Apr. 23,14
EMI Test Receiver	Rohde&Schwarz	ESVD	847398/003	May 14,13	May 13,14
Bilog Antenna (25MHz-2GHz)	Teseq	CBL 6111D	25757	Nov. 22,12	Nov. 21,13
Bilog Antenna	Teseq	CBL 6111D	25757	Nov. 22,12	Nov. 21,13
Horn Antenna (1GHz -18GHz)	ЕМСО	3117	00062558	Oct.18,12	Oct.17,13
Pre-Amplifier (20MHz-3GHz)	EMCI	EMC 330	980095	Nov. 02,12	Nov.01,13
Pre-Amplifier (100MHz-26.5GHz)	Agilent	8449B		May 14,13	May 13,14
10m Semi-anechoic Chamber	CHANGLING	21.4m*12.1m*8 .8m	NSEMC006	Mar. 24,13	Mar. 23,14
Digital Multimeter	FLUKE	15B	A1220010D G	Oct. 31,12	Oct. 30,13
Test Software	ADT	ADT_Radiated _V7.6.15	N/A	N/A	N/A

#### NOTE:

- 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
- 2. The test was performed in 10m Chamber
- 3. The FCC Site Registration No. is 502831

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver/spectrum system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

#### NOTE:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
- 4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation

Fax: +86 769 8593 1080


Tel: +86 769 8593 5656

Email: <a href="mailto:customerservice.dg@cn.bureauveritas.com">customerservice.dg@cn.bureauveritas.com</a>

Page 10 of 22



#### 4.1.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT OPERATING CONDITIONS

Set the EUT under transmission condition continuously at specific channel frequency.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



#### 4.1.7 TEST RESULTS


#### **BELOW 1GHz WORST-CASE DATA:**

CHANNEL	Low Channel	DETECTOR	Ougai Book (OD)
FREQUENCY RANGE	30MHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)			
1	34.75	15.6 QP	40.0	-24.4	1.00 H	215	-1.77	17.36			
2	374.32	14.6 QP	46.0	-31.4	1.00 H	276	-2.83	17.40			
3	400.19	15.2 QP	46.0	-30.8	1.00 H	327	-3.14	18.36			
4	456.79	18.7 QP	46.0	-27.3	1.00 H	344	-1.12	19.85			
5	474.57	18.7 QP	46.0	-27.3	1.00 H	258	-1.62	20.35			
6	600.70	20.6 QP	46.0	-25.4	1.00 H	308	-2.62	23.25			

#### **REMARKS:**

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.



Tel: +86 769 8593 5656 Fax: +86 769 8593 1080




CHANNEL	Low Channel	DETECTOR	Ougoi Pook (OP)
FREQUENCY RANGE	30MHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)

	ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)			
1	37.98	13.8 QP	40.0	-26.2	1.00 V	245	-1.77	15.56			
2	156.03	9.1 QP	43.5	-34.4	1.00 V	221	-2.95	12.06			
3	384.02	14.5 QP	46.0	-31.5	1.00 V	293	-3.12	17.65			
4	456.79	17.9 QP	46.0	-28.1	1.00 V	313	-1.94	19.85			
5	474.57	20.2 QP	46.0	-25.9	1.00 V	202	-0.20	20.35			
6	548.96	18.6 QP	46.0	-27.4	1.00 V	267	-4.03	22.59			

#### **REMARKS:**

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.



Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



#### **ABOVE 1GHz WORST-CASE DATA:**

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Low Channel	FREQUENCY RANGE 1 ~ 25GHz		
TEST VOLTAGE	I 6 V by Battery	DETECTOR FUNCTION	Peak (PK) Average (AV)	

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)		
1	2400.00	70.6 PK	74	-3.4	1.76 H	155	33.33	37.27		
2	2400.00	50.8 AV	54	-3.2	1.76 H	155	13.53	37.27		
3	*2406.00	98.4 PK	114	-15.6	1.76 H	155	61.12	37.28		
4	*2406.00	59.4 AV	94	-34.6	1.76 H	155	22.12	37.28		
5	4812.00	59.6 PK	74.0	-14.4	1.00 H	204	17.98	41.62		
6	4812.00	40.4 AV	54.0	-13.6	1.00 H	204	-1.22	41.62		
		ANTENNA	POLARITY	/ & TEST DI	STANCE: V	ERTICAL A	T 3 M			
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)		
1	2400.00	68.1 PK	74	-5.9	1.50 V	87	30.83	37.27		
2	2400.00	51.1 AV	54	-2.9	1.50 V	87	13.83	37.27		
3	*2406.00	97.5 PK	114	-16.5	1.50 V	87	60.22	37.28		
4	*2406.00	60.7 AV	94	-33.3	1.50 V	87	23.42	37.28		
5	4812.00	61.9 PK	74.0	-12.1	1.03 V	355	20.28	41.62		
6	4812.00	39.6 AV	54.0	-14.4	1.03 V	355	-2.02	41.62		

#### **REMARKS:**

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.
- 5. " \* ": Fundamental frequency.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: <a href="mailto:customerservice.dg@cn.bureauveritas.com">customerservice.dg@cn.bureauveritas.com</a>

Report Version 1



EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Middle Channel	FREQUENCY RANGE 1 ~ 25GHz		
TEST VOLTAGE	6V by Battery		Peak (PK) Average (AV)	

		ANTENNA	DOL ADITY	P TEST DIS	TANCE: HO	DIZONTAL	AT 2 M	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2444.00	100.2 PK	114.0	-13.8	1.80 H	222	62.86	37.34
2	*2444.00	62.3 AV	94	-31.7	1.80 H	222	24.96	37.34
3	4888.00	60.4 PK	74.0	-13.6	1.00 H	194	18.69	41.71
4	4888.00	40.6 AV	54.0	-13.4	1.00 H	194	-1.11	41.71
5	7332.00	61.1 PK	74.0	-12.9	1.00 H	312	15.30	45.80
6	7332.00	45.7 AV	54.0	-8.3	1.00 H	312	-0.10	45.80
		ANTENNA	POLARITY	/ & TEST DI	STANCE: V	ERTICAL A	T 3 M	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2444.00	98.1 PK	114.0	-15.9	1.00 V	64	60.76	37.34
2	*2444.00	65.7 AV	94	-28.3	1.00 V	64	28.36	37.34
3	4888.00	63.5 PK	74.0	-10.5	1.00 V	5	21.79	41.71
4	4888.00	40.6 AV	54.0	-13.4	1.00 V	5	-1.11	41.71
5	7332.00	64.9 PK	74.0	-9.1	1.00 V	193	19.10	45.80
6	7332.00	46.8 AV	54.0	-7.2	1.00 V	193	1.00	45.80

#### **REMARKS:**

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.
- 5. " \* ": Fundamental frequency.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	High Channel	FREQUENCY RANGE 1 ~ 25GHz		
TEST VOLTAGE	6V by Battery		Peak (PK) Average (AV)	

		ANTENNA	POLARITY &	& TEST DIS	TANCE: HO	RIZONTAL	AT 3 M	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2477.00	97.7 PK	114	-16.3	1.70 H	162	60.3	37.4
2	*2477.00	57.2 AV	94	-36.8	1.70 H	162	19.8	37.4
3	2483.50	66.9 PK	74	-7.1	1.70 H	162	29.49	37.41
4	2483.50	40.5 AV	54	-13.5	1.70 H	162	3.09	37.41
5	4954.00	61.2 PK	74	-12.8	1.00 H	200	19.41	41.79
6	4954.00	41.5 AV	54	-12.5	1.00 H	200	-0.29	41.79
7	7431.00	62.9 PK	74	-11.1	1.59 H	316	17.08	45.82
8	7431.00	46.5 AV	54	-7.5	1.59 H	316	0.68	45.82
		ANTENNA	POLARITY	/ & TEST DI	STANCE: V	ERTICAL A	T 3 M	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2477.00	98.4 PK	114	-15.6	1.00 V	42	61	37.4
2	*2477.00	58.9 AV	94	-35.1	1.00 V	42	21.5	37.4
3	2483.50	66.7 PK	74	-7.3	1.00 V	42	29.29	37.41
4	2483.50	41.4 AV	54	-12.6	1.00 V	42	3.99	37.41
5	4954.00	66.3 PK	74	-7.7	1.00 V	241	24.51	41.79
6	4954.00	41.7 AV	54	-12.3	1.00 V	241	-0.09	41.79
7	7431.00	65.4 PK	74	-8.6	1.00 V	180	19.58	45.82
8	7431.00	46.4 AV	54	-7.6	1.00 V	180	0.58	45.82

#### **REMARKS:**

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.
- 5. " \* ": Fundamental frequency.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



#### 4.2 20dB BANDWIDTH MEASUREMENT

#### 4.3.1 LIMITS OF 20dB BANDWIDTH MEASUREMENT

According to FCC 15.215(c), must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

#### 4.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Spectrum Analyzer	Agilent	E4446A	MY46180622	Apr. 24,13	Apr. 23,14
EMI Test Receiver	Rohde&Schwarz	ESVD	847398/003	May 14,13	May 13,14
Bilog Antenna (25MHz-2GHz)	Teseq	CBL 6111D	25757	Nov. 22,12	Nov. 21,13
Bilog Antenna	Teseq	CBL 6111D	25757	Nov. 22,12	Nov. 21,13
Horn Antenna (1GHz -18GHz)	ЕМСО	3117	00062558	Oct.18,12	Oct.17,13
Pre-Amplifier (20MHz-3GHz)	EMCI	EMC 330	980095	Nov. 02,12	Nov.01,13
Pre-Amplifier (100MHz-26.5GHz)	Agilent	8449B	3008A00409	May 14,13	May 13,14
10m Semi-anechoic Chamber	CHANGLING	21.4m*12.1m*8 .8m	NSEMC006	Mar. 24,13	Mar. 23,14
Digital Multimeter	FLUKE	15B	A1220010D G	Oct. 31,12	Oct. 30,13
Test Software	ADT	ADT_Radiated _V7.6.15	N/A	N/A	N/A

#### NOTE:

- 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
- 2. The test was performed in 10m Chamber
- 3. The FCC Site Registration No. is 502831

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080




#### 4.3.3 TEST PROCEDURE

The EUT was placed on a turn table which was 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna which was mounted on a antenna tower. The measuring antenna moved up and down to find out the maximum emission level. It moved from 1 to 4 m for horizontal and vertical polarizations. The spectrum analyzer was receiving the maximum emission level. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

#### 4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.3.5 TEST SETUP



Tel: +86 769 8593 5656 Fax: +86 769 8593 1080




#### 4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.3.7 TEST RESULTS

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
Low	2406	2.171
Middle	2444	2.200
High	2477	2.026


#### **Test Data: Low channel**




Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



#### **Test Data: Middle channel**



#### **Test Data: High channel**



Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com

Tel: +86 769 8593 5656

Page 21 of 22



# 6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---

Fax: +86 769 8593 1080 Email: <u>customerservice.dg@cn.bureauveritas.com</u>

Report Version 1

Tel: +86 769 8593 5656

Page 22 of 22