

Lead Engineer

#### **TEST REPORT**

Report No.: 14080673HKG-001R1

Underground Toys LLC

**Application** For Certification (Original Grant) (FCC ID: 2AAB905447T)

#### **Transmitter**

This report supersedes previous report with report number(s) 14080673HKG-001R1 dated September 03, 2014.

Prepared and Checked by: Approved by: Signed On File Wong Kwok Yeung, Kenneth Chan Chi Hung, Terry

Supervisor

Date: October 16, 2014

Intertek's standard Terms and Conditions can be obtained at our website http://www.intertek.com/terms/

Intertek's standard Terms and Conditions can be obtained at our website http://www.intertek.com/terms/.

The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

## **GENERAL INFORMATION**

Grantee:	Underground Toys LLC
Grantee Address:	8685 Miralani Drive,
	Suite 300 San Diego,
	CA 92126, USA
Contact Person:	Rita Lam
Tel:	+1-619-702-2023
Fax:	+1-619-702-2021
e-mail:	rita.lam@underground-toys.com
Manufacturer:	Toy Options (Far East) Ltd.
Manufacturer Address:	Room 1005-1007A, 10/F., Empire Centre, 68 Mody
	Road, Tsim Sha Tsui East, Kowloon, Hong Kong.
Brand Name:	N/A
Model:	05447
Type of EUT:	Transmitter
Description of EUT:	Doctor Who: 1/4 Scale Radio Control K9
Serial Number:	N/A
FCC ID:	2AAB905447T
Date of Sample Submitted:	August 19, 2014
Date of Test:	August 19, 2014 to August 29, 2014
Report No.:	14080673HKG-001R1
Report Date:	October 16, 2014
Environmental Conditions:	Temperature: +10 to 40°C
	Humidity: 10 to 90%

i

Report No.: 14080673HKG-001R1

#### **SUMMARY OF TEST RESULT**

TEST SPECIFICATION	REFERENCE	RESULTS
Transmitter Field Strength and Bandedge Requirement	15.249	Pass

The equipment under test is found to be complying with the following standards: FCC Part 15, October 1, 2012 Edition

ii

Report No.: 14080673HKG-001R1

Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the pervisions of this section.

<sup>2.</sup> Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

## **Table of Contents**

1.0	General Description	1
1.1	Product Description	1
1.2	Related Submittal(s) Grants	1
1.3	Test Methodology	1
1.4	Test Facility	1
		_
2.0	System Test Configuration	. 2
2.1	Justification	
2.2	EUT Exercising Software	
2.3	Special Accessories	
2.4	Measurement Uncertainty	
2.5	Support Equipment List and Description	. 2
3.0	Emission Results	3
3.0 3.1	Field Strength Calculation	
3.1		
3.2	Radiated Emission Configuration Photograph Radiated Emission Data	
3.3	Radiated Ethission Data	. 4
4.0	Equipment Photographs	. 6
	<b>-</b>	_
5.0	Product Labelling	. 6
6.0	Technical Specifications	. 6
7.0	Instruction Manual	. 6
8.0	Miscellaneous Information	7
8.1	Measured Bandwidth / Radiated Emission on the Bandedge	
8.2	Discussion of Pulse Desensitization	
8.3	Calculation of Average Factor	
8.4	Emissions Test Procedures	
0.4	LIIIISSIOIIS TEST FIOCEURIES	10
9.0	Equipment List	12

Report No.: 14080673HKG-001R1

#### 1.0 **General Description**

#### 1.1 Product Description

The Equipment Under Test (EUT) is a transmitter for a RC car, which is operating at 2478MHz. It is powered by a 9V alkaline battery. The EUT consists of five sound buttons and two directional keys. After switching ON the EUT and the corresponding car (Receiver), When you press the sound buttons, the corresponding receiver will send out different sounds and if you activate the directional keys on the EUT, you can control the car moving forward, backward, left and right.

Antenna Type: Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

#### 1.2 Related Submittal(s) Grants

This is a single application for certification of a transmitter.

#### 1.3 Test Methodology

Radiated emission measurements was performed according to the procedures in ANSI C63.4 (2009). All radiated measurements were performed in an Open Area Test Site. Preliminary scans were performed in the Open Area Test Site only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application.

#### 1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Workshop No. 3, G/F., World-Wide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Sha Tin, N.T., Hong Kong. This test facility and site measurement data have been placed on file with the FCC and IC.

Report No.: 14080673HKG-001R1 1

#### 2.0 **System Test Configuration**

#### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2009).

The device was powered by new 1 x 9.0V Alkaline Battery.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

#### 2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

#### 2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

#### 2.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

#### 2.5 Support Equipment List and Description

N/A.

Report No.: 14080673HKG-001R1 2

#### 3.0 **Emission Results**

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

#### 3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CF - AG - AV

where FS = Field Strength in  $dB\mu V/m$ 

RA = Receiver Amplitude (including preamplifier) in dBµV

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB AG = Amplifier Gain in dB AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

FS = RR + LF

where  $FS = Field Strength in dB\mu V/m$ 

 $RR = RA - AG - AV in dB\mu V$ 

LF = CF + AF in dB

Assume a receiver reading of 52.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 32 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

 $RA = 52.0 dB\mu V/m$ 

AF = 7.4 dB RR = 18.0 dB $\mu$ V

AG = 29.0 dBAV = 5.0 dB

FS = RR + LF

 $FS = 18 + 9 = 27 \, dB\mu V/m$ 

Level in  $\mu$ V/m = Common Antilogarithm [(27 dB $\mu$ V/m)/20] = 22.4  $\mu$ V/m

Report No.: 14080673HKG-001R1

### 3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 2483.500 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

#### 3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 6.9 dB

Report No.: 14080673HKG-001R1

Applicant: Underground Toys LLC Date of Test: August 29, 2014

Model: 05447

Worst-Case Operating Mode: Transmitting

Table 1

# Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

			Pre-Amp	Antenna	Net at	Average	Calculated	Average Limit	
Polari-	Frequency	Reading	Gain	Factor	3m - Peak	Factor	at 3m	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
Н	2400.000	61.6	33	29.4	58.0	31.3	26.7	54.0	-27.3
Ι	2478.000	98.6	33	29.4	95.0	31.3	63.7	94.0	-30.3
Н	2483.500	70.7	33	29.4	67.1	31.3	35.8	54.0	-18.2
Н	4956.000	47.1	33	34.9	49.0	31.3	17.7	54.0	-36.3
Н	7434.000	46.2	33	37.9	51.1	31.3	19.8	54.0	-34.2
Н	9912.000	47.6	33	40.4	55.0	31.3	23.7	54.0	-30.3
Н	12390.000	50.7	33	40.5	58.2	31.3	26.9	54.0	-27.1
Н	14868.000	54.6	33	38.4	60.0	31.3	28.7	54.0	-25.3

			Pre-Amp	Antenna	Net at	Peak Limit	
Polari-	Frequency	Reading	Gain	Factor	3m - Peak	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
Н	2400.000	61.6	33	29.4	58.0	74.0	-16.0
Н	2478.000	98.6	33	29.4	95.0	114.0	-19.0
Н	2483.500	70.7	33	29.4	67.1	74.0	-6.9
Н	4956.000	47.1	33	34.9	49.0	74.0	-25.0
Н	7434.000	46.2	33	37.9	51.1	74.0	-22.9
Н	9912.000	47.6	33	40.4	55.0	74.0	-19.0
Н	12390.000	50.7	33	40.5	58.2	74.0	-15.8
Н	14868.000	54.6	33	38.4	60.0	74.0	-14.0

NOTES: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative sign in the column shows value below limit.
- 4. Horn antenna is used for the emission over 1000MHz.
- 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.

Report No.: 14080673HKG-001R1 5

### 4.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

#### 5.0 **Product Labelling**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

### 6.0 <u>Technical Specifications</u>

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

## 7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

Report No.: 14080673HKG-001R1 6

#### 8.0 **Miscellaneous Information**

The miscellaneous information includes details of the test procedure and measured bandwidth / calculation of factor such as pulse desensitization and averaging factor (calculation and timing diagram).

#### 8.1 Radiated Emission on the Bandedge

From the following plots, they show that the fundamental emissions are confined in the specified band (2400MHz to 2483.5MHz). In case of the fundamental emissions are within two standard bandwidths from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.4 (2009) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50dB below the level of the fundamental or to the general radiated emissions limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).

#### **Peak Measurement**

The resultant field strength meets the general radiated emission limit in Section 15.209, which does not exceed 74 dB $\mu$ V/m (Peak Limit) and 54 dB $\mu$ V/m (Average Limit).

Report No.: 14080673HKG-001R1 7

#### 8.2 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period (Teff) is approximately 0.68ms for a digital "1" bit which illustrated on technical specification, with a resolution bandwidth (3dB) of 1MHz, so the pulse desensitivity factor is 0dB.

### 8.3 Calculation of Average Factor

The duty cycle is simply the on-time divided by the period:


The duration of one cycle = 100ms


Effective period of the cycle = 4\*0.68 = 2.72ms

DC = 2.72/100 = 0.0272

Therefore, the averaging factor is found by  $20\log 0.0272 = -31.3dB$ .

Report No.: 14080673HKG-001R1





Report No.: 14080673HKG-001R1

#### 8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

Report No.: 14080673HKG-001R1 10

#### 8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.4 (2009).

The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.

Report No.: 14080673HKG-001R1 11

#### 9.0 **Equipment List**

#### 1) **Radiated Emissions Test**

Equipment	EMI Test Receiver	Spectrum Analyzer	Log Periodic Antenna
Registration No.	EW-2666	EW-2253	EW-0572
Manufacturer	R&S	R&S	EMCO
Model No.	ESCI7	FSP40	3146
Calibration Date	Jun. 20, 2013	May 08, 2014	Jun. 26, 2013
Calibration Due Date	Sep. 20, 2014	May 08, 2015	Dec. 26, 2014

Equipment	Double Ridged Guide Antenna	Biconical Antenna
Registration No.	EW-1015	EW-0571
Manufacturer	EMCO	EMCO
Model No.	3115	3104C
Calibration Date	Mar. 05, 2013	Nov. 01, 2013
Calibration Due Date	Sep. 05, 2014	May 01, 2015

#### 2) Bandedge Measurement

Equipment	Spectrum Analyzer
Registration No.	EW-2329
Manufacturer	R&S
Model No.	FSP3
Calibration Date	Jun. 19, 2014
Calibration Due Date	Jun. 19, 2015

**END OF TEST REPORT** 

Report No.: 14080673HKG-001R1 12