



# A Test Lab Techno Corp.

Changan Lab : No. 140 -1, Changan Street, Bade City, Taoyuan County, Taiwan R.O.C.  
Tel : 886-3-271-0188 / Fax : 886-3-271-0190



## MPE Report

Test Report No.	: 1305FS18
Applicant	: SHANG CHUEN WEIGHTING MACHINE CO., LTD.
Manufacturer	: SHANG CHUEN WEIGHTING MACHINE CO., LTD.
Product Type	: BLUETOOTH BATHROOM SCALE
Trade Name	: SATRUE
Model Number	: WBT-168,WBT-168A
Dates of Receive	: Apr. 03, 2013
Dates of Test	: May 17, 2013
Issued Date	: May 27, 2013
Test Specification	: 47 CFR § 2.1091 47 CFR §1.1310 ANSI / IEEE Std.C95.1-1992
Location of Test Lab.	: Chang-an Lab.

1. The test operations have to be performed with cautious behavior, the test results are as attached.
2. The test results are under chamber environment of A Test Lab Techno Corp. A Test Lab Techno Corp. does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples.
3. The measurement report has to be written approval of A Test Lab Techno Corp. It may only be reproduced or published in full. This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp.
4. This document may be altered or revised by A Test Lab Techno. Corp. personnel only, and shall be noted in the revision section of the document.

Approved By :  Tested By :   
(Yung Tan Tsai) (Bill Hu)



## Contents

1. Description of Equipment under Test (EUT).....	3
2. Human Exposure Assessment .....	4
3. RF Output Power.....	5
4. Test Result.....	5



## 1. **Description of Equipment under Test (EUT)**

Applicant	SHANG CHUEN WEIGHTING MACHINE CO., LTD.
Applicant Address	No. 53, Liao-Yang 4th St. Taichung City, Taiwan, R.O.C.
Manufacturer	SHANG CHUEN WEIGHTING MACHINE CO., LTD.
Manufacturer Address	No. 53, Liao-Yang 4th St. Taichung City, Taiwan, R.O.C.
Product Type	BLUETOOTH BATHROOM SCALE
Trade Name	SATRUE
Model Number	WBT-168, WBT-168A
Model Different Description	The two model numbers differ from each other in selling region.
FCC ID	2AABU-WBT168
Frequency Range	Bluetooth: 2402 ~ 2480MHz
Avg. Transmit Power (conducted power)	Bluetooth: 0.002 W / 3.75 dBm
Antenna Designation	PCB Antenna
Antenna Specification	-0.59 dBi
Temperature Range	-30 ~ +70°C

The above equipment was tested by A Test Lab Techno Corp. For compliance with the requirements set forth in 47 CFR § 2.1091 & 47 CFR § 1.1310. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties



## 2. Human Exposure Assessment

Due to the design and installation of this product, it is not possible to conduct SAR evaluation. This is because client either manufactures or supplies the antenna(s) that will be used in the installation of this product. Therefore, this product will be evaluated as a mobile device per 47 CFR §1.1310 titled "Radiofrequency radiation exposure limits", generally referred to as MPE limits.

In 47 CFR § 2.1091, paragraph (b) defines a mobile device as "a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 cm is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons." This product is intended to be installed into a vehicle such that the unit is physically secured at one location. In the installation guide supplied with the product,

Client has made the following statement: "IMPORTANT: To meet the FCC's RF Exposure Guidelines, the antenna should be installed so there is at least 20 cm of separation between the body of the user and nearby persons and the antenna". Based on the installation of the transceiver and the antenna, the transmitters radiating structure is more than 20 cm from the user. Thus, this product is a "mobile device" as defined in section § 2.1091 paragraph (b).

### Exposure evaluation

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna.



### 3. RF Output Power

Band	CH	Frequency (MHz)	Packet Type	Average Conducted Output Power (dBm)
Bluetooth (GFSK)	0	2402	DH1	-3.09
			DH3	0.31
			DH5	1.01
	39	2441	DH1	-2.05
			DH3	1.27
			DH5	2.00
	78	2480	DH1	-0.30
			DH3	3.06
			DH5	3.75
Bluetooth ( $\pi/4$ -DQPSK)	0	2402	DH1	-5.26
			DH3	-2.46
			DH5	-1.84
	39	2441	DH1	-4.26
			DH3	-1.48
			DH5	-0.87
	78	2480	DH1	-2.51
			DH3	0.29
			DH5	0.91
Bluetooth (8DPSK)	0	2402	DH1	-5.24
			DH3	-2.42
			DH5	-1.71
	39	2441	DH1	-4.21
			DH3	-1.46
			DH5	-0.83
	78	2480	DH1	-2.48
			DH3	0.34
			DH5	0.96

### 4. Test Result

Band	Packet Type	Frequency (MHz)	Limit (mw)	Distance [R] (cm)	Max0 tune-up Power (upper limit) [P] (dBm)	ANT Gain [G] (dBi)	Duty Cycle	[P]+[G] with Duty cycle [TP] (W)	Power Density [S] (mw)/cm <sup>2</sup>
Bluetooth (GFSK)	DH5	2402.0	1.000	20	4	-0.59	1	0.002	0.0004
		2441.0	1.000	20	4	-0.59	1	0.002	0.0004
		2480.0	1.000	20	4	-0.59	1	0.002	0.0004