

Radiofrequency radiation exposure evaluation: mobile devices

RESULT :

Pass

Test Specification

| | | |
|---------------------------|---|---|
| Test item | : | Video Light |
| Identification / Type No. | : | STORM 400x |
| FCC ID | : | 2AABZ-STORM400X |
| IC | : | 28850-STORM400X |
| Test standard | : | CFR47 FCC Part 2: Section 2.1091 CFR47 FCC Part 1: Section 1.1310 FCC KDB Publication 447498 D04 RSS-102 Issue 6 |

➤ FCC requirements

FCC requirement: Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 20cm normally can be maintained between the user and the device.

MPE Calculation Method according to KDB 447498 D04

TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES
SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

| RF Source Frequency | | Minimum Distance | | Threshold ERP | |
|---------------------|-----------|--------------------|--------------------|---------------|--|
| f_L MHz | f_H MHz | $\lambda_L / 2\pi$ | $\lambda_H / 2\pi$ | W | |
| 0.3 | — | 1.34 | 159 m | — | 35.6 m 1,920 R ² |
| 1.34 | — | 30 | 35.6 m | — | 1.6 m 3,450 R ² /f ² |
| 30 | — | 300 | 1.6 m | — | 159 mm 3.83 R ² |
| 300 | — | 1,500 | 159 mm | — | 31.8 mm 0.0128 R ² f |
| 1,500 | — | 100,000 | 31.8 mm | — | 0.5 mm 19.2R ² |

Subscripts L and H are low and high; λ is wavelength.
From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

a) EUT RF Exposure Evaluation operations, Worst Case mode

| Test Mode | Measured Power (dBm) | Measured Power (mW) | Minimum Separation Distances (cm) | Limit (mW) |
|-----------|----------------------|---------------------|-----------------------------------|------------|
| BLE | 2.92 | 1.958 | 20 | 3060 |

➤ **IC requirements:** The EUT shall comply with the requirement of RSS-102 section 6.6 Exposure Limits.

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz⁶ and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

a) EUT RF Exposure Evaluation standalone operations, Worst Case mode

| Test Mode | Maximum e.i.r.p (dBm) | Maximum e.i.r.p (W) | Limit (W) |
|-----------|-----------------------|---------------------|-----------|
| BLE | 4.60 | 0.00288 | 2.68 |

“RF Radiation Exposure Statement Caution: This Transmitter must be installed to provide a separation distance of at least 20 cm from all persons.”