



## FCC TEST REPORT

**FCC ID: 2AAC4-POWERDISCV1**

On Behalf of

**Case-Mate, Inc.**

**Power Disc Wireless Charger**

**Model No.: CM044810, CM044886**

Prepared for : Case-Mate, Inc.  
Address : 7000 Central Pkwy., Ste. 1050, Atlanta, GA 30328, U.S.A.

Prepared By : Shenzhen Alpha Product Testing Co., Ltd.  
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District,  
518103, Shenzhen, Guangdong, China

Report Number	: A2009021-C01-R02
Date of Receipt	: September 9, 2020
Date of Test	: September 9, 2020-September 15, 2020
Date of Report	: September 15, 2020
Version Number	: V0

## **TABLE OF CONTENTS**

<b>1. Test Result Summary .....</b>	<b>5</b>
<b>2. EUT Description.....</b>	<b>6</b>
2.1. DESCRIPTION OF DEVICE (EUT).....	6
2.2. ACCESSORIES OF DEVICE (EUT).....	8
2.3. TESTED SUPPORTING SYSTEM DETAILS .....	8
2.4. BLOCK DIAGRAM OF CONNECTION BETWEEN EUT AND SIMULATORS .....	8
2.5. DESCRIPTION OF TEST MODES.....	8
2.6. TEST CONDITIONS .....	8
2.7. TEST FACILITY .....	9
2.8. MEASUREMENT UNCERTAINTY .....	9
<b>3. Test Results and Measurement Data .....</b>	<b>10</b>
3.1. RF EXPOSURE TEST.....	10
<b>4. Photos of test setup .....</b>	<b>13</b>
<b>5. Photographs of EUT .....</b>	<b>14</b>

## TEST REPORT DECLARATION

Applicant : Case-Mate, Inc.  
Address : 7000 Central Pkwy., Ste. 1050, Atlanta, GA 30328, U.S.A.  
Manufacturer : Case-Mate, Inc.C  
Address : 7000 Central Pkwy., Ste. 1050, Atlanta, GA 30328, U.S.A.  
EUT Description : Power Disc Wireless Charger  
(A) Model No. : CM044810, CM044886  
(B) Trademark : N/A

Measurement Standard Used:

**FCC CFR Title 47 Part 15 Subpart C**

**FCC KDB 680106 D01 RF Exposure Wireless Charging Apps v03**

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed full responsibility for the accuracy and completeness test. Also, this report shows that the EUT is technically compliant with the KDB 680106 D01 requirements.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....: Lucas Pang  
Project Engineer



Approved by (name + signature).....: Simple Guan  
Project Manager



Date of issue.....: September 15, 2020

**Revision History**

Revision	Issue Date	Revisions	Revised By
V0	September 15, 2020	Initial released Issue	Lucas Pang

## 1. Test Result Summary

Requirement	CFR 47 Section	Result
RF EXPOSURE	§1.1307(b)(1) & KDB680106	PASS

**Note:**

1. *PASS: Test item meets the requirement.*
2. *Fail: Test item does not meet the requirement.*
3. *N/A: Test case does not apply to the test object.*
4. *The test result judgment is decided by the limit of test standard.*

## 2. EUT Description

### 2.1. Description of Device (EUT)

EUT Name : Power Disc Wireless Charger

Model No. : CM044810, CM044886

DIFF. : There is no difference except for the appearance, shape and model name. So all the test were performed on the model CM044810.

Trademark : N/A

Power supply : Type-C Input: DC 5V/2A, DC 9V/2A, Wireless Output: 5W, 7.5W, 10W(Max).

Operation frequency : 125~200KHz

Modulation : MSK

Antenna Type : Coil Antenna, Maximum Gain is 0dBi(This value is supplied by applicant).

Connector cable loss : 0.5dB (This value is supplied by applicant).

Conditions requirement	Answers
Power transfer frequency is less than 1 MHz.	After measuring the product the transfer frequency is 125-200KHz
Output power from each primary coil is less than or equal to 15 watts.	After measuring the product the each primary coil power is 10 watts
The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.	The transfer system includes only single primary.
Client device is placed directly in contact with the transmitter.	Client device is placed directly in contact with the transmitter.
Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	Mobile exposure conditions only.
The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.	After measuring the product the Max H-field Strength is <b>0.3608A/m</b> Far less than 50% of the MPE limit.


## 2.2. Accessories of Device (EUT)

Accessories1	:	Power Supply
Manufacturer	:	SHENZHEN DISHENGHUI ELECTRONICS CO., LTD
Model	:	DBS15Q
Ratings	:	Input: AC 100-240V 50/60Hz 500mA, Output: DC 5V/3A, 9V/2A, 12V/1.5A

## 2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or SDOC
1	Wireless load	--	--	--	N/A
2	USB cable	--	--	--	N/A

## 2.4. Block Diagram of connection between EUT and simulators



## 2.5. Description of Test Modes

Channel	Frequency (KHz)
1	139

## 2.6. Test Conditions

Items	Required	Actual
Temperature range:	15-35°C	24°C
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	98kPa

## 2.7. Test Facility

Shenzhen Alpha Product Testing Co., Ltd

Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103, Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission  
Registration Number: 293961

July 15, 2019 Certificated by IC  
Registration Number: CN0085

## 2.8. Measurement Uncertainty


(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for H-Field	2.39dB
Uncertainty for E-Field	2.45dB
Uncertainty for conducted RF Power	0.65dB
Uncertainty for temperature	0.2°C
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

### 3. Test Results and Measurement Data

#### 3.1. RF EXPOSURE TEST

##### 3.1.1. Test Specification

Test Requirement:	FCC Rules and Regulations KDB680106
Test Method:	§1.1307(b)(1) & KDB680106
Limits:	According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. According to §1.1310 and §2.1093 RF exposure is calculated. According KDB680106 D01v03: RF Exposure Wireless Charging.
Test Setup:	 <p>E to position is 20cm.</p>
Test Mode:	Transmitting Mode
Test Procedure:	<ol style="list-style-type: none"> <li>1. The RF exposure test was performed on 360 degree turn table in anechoic chamber.</li> <li>2. The measurement probe was placed at test distance (15cm) which is between the edge of the charger and the geometric centre of probe.</li> <li>3. The turn table was rotated 360d degree to search of highest strength.</li> <li>4. The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.</li> <li>5. The EUT were measured according to the dictates of KDB 680106D01v03.</li> </ol>
Test Result:	PASS

### 3.1.2. Test Instruments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Exposure Level Tester	narda	ELT-400	N-0231	2020.09.02	1 Year
2	Magnetic field probe 100cm <sup>2</sup>	narda	ELT probe 100cm <sup>2</sup>	M0675	2020.09.02	1 Year
3	Isotropic Electric Field Probe	narda	EP-601	511WX60706	2020.09.02	1 Year

### 3.1.3. Test data

For Full load mode:

E-Field Strength at 15 cm for position A, B, C, D 20cm for position E from the edges surrounding the EUT (V/m)

Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Limit (50%) (V/m)	Limits Test (V/m)
0.125-0.200	2.564	2.483	2.316	2.480	2.081	307	614

H-Field Strength at 15 cm for position A, B, C, D 20cm for position E from the edges surrounding the EUT (A/m)

Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Limit (50%) (A/m)	Limits Test (A/m)
0.125-0.200	<b>0.3608</b>	0.3586	0.3482	0.3256	0.3215	0.815	1.63

For Half load mode:

E-Field Strength at 15 cm for position A, B, C, D 20cm for position E from the edges surrounding the EUT (V/m)

Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Limit (50%) (V/m)	Limits Test (V/m)
0.125-0.200	1.815	1.745	1.664	1.725	1.655	307	614

H-Field Strength at 15 cm for position A, B, C, D 20cm for position E from the edges surrounding the EUT (A/m)

Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Limit (50%) (A/m)	Limits Test (A/m)
0.125-0.200	0.2654	0.2230	0.2642	0.2781	0.2197	0.815	1.63

For Null load mode:

E-Field Strength at 15 cm for position A, B, C, D 20cm for position E from the edges surrounding the EUT (V/m)

Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Limit (50%) (V/m)	Limits Test (V/m)
0.125-0.200	1.256	1.264	1.235	1.117	1.262	307	614

H-Field Strength at 15 cm for position A, B, C, D 20cm for position E from the edges surrounding the EUT (A/m)

Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Limit (50%) (A/m)	Limits Test (A/m)
0.125-0.200	0.1832	0.1724	0.1824	0.1785	0.1735	0.815	1.63

## 4. Photos of test setup

For Full load mode



For No load mode



## 5. Photographs of EUT

Refer to test report A2009021-C01-R01.

-----End-----