



FCC COMPLIANCE TEST REPORT

Technical Statement of Conformity in accordance with 47 CFR Part 15 Subpart C

The product

Equipment Under Test : powerlineECCO+

Model Number : powerlineECCO+

Product Series : N/A

Report Number : HA150774-RA
Issue Date : 01-Oct-2015
Test Result : Compliance

is produced by advanced PANMOBIL Systems GmbH & Co. KG Hansestrasse 91, D-51149 Koeln, Germany



HongAn TECHNOLOGY CO., LTD.

NO.15-1, CWEISHUH KENG, CWEIPIN VILLAGE, **TEL**: +886-2-26030362 LINKOU, TAIPEI COUNTY, **FAX**: +886-2-26019259

TAIWAN, R. O. C. E-mail: hatlab@ms19.hinet.net

BSMI Registration No.: SL2-IN-E-0023, SL2-A1-E-0023, FCC Designation No.: TW1071

SL2-IS-E-0023, SL2-R1-E-0023, **TAF Accreditation No.:** 1163

SL2-R2-E-0023, SL2-L1-E-0023 **VCCI Registration No.:** R-2156, C-2329, T-219

FCC Test Report Page 1 of 49

Contents

| 1 | General Description | 5 |
|------|--|----|
| 1.1 | Description of EUT | 5 |
| 1.2 | Test Instruments | 6 |
| 1.3 | Auxiliary Equipments | 7 |
| 1.4 | EUT SETUP | 7 |
| 1.5 | Identifying the Final Test Mode | 7 |
| 1.6 | Final Test Mode | 7 |
| 1.7 | Condition of Power Supply | 8 |
| 1.8 | EUT Configuration | 8 |
| 1.9 | Test Methodology | 8 |
| 1.10 | General Test Procedures | 8 |
| 1.11 | Modification | 8 |
| 1.12 | FCC Part 15.205 restricted bands of operations | 9 |
| 1.13 | Qualification of Test Facility | 10 |
| 2 | Power line Conducted Emission Measurement | 11 |
| 2.1 | Test Instruments | 11 |
| 2.2 | Test Arrangement and Procedure | 11 |
| 2.3 | Limit (§ 15.207) | 11 |
| 2.4 | Test Result | 11 |
| 3 | Radiated Emission Test | 12 |
| 3.1 | Test Instruments | 16 |
| 3.2 | Test Arrangement and Procedure | 16 |
| 3.3 | Limit of Field Strength of Fundamental (§ 15.249(a)) | 17 |
| 3.4 | Limit (§ 15.205 & § 15.209 & § 15.249(d)) | 17 |
| 3.5 | Test Result | 19 |
| 4 | Antenna requirement | 36 |
| 4.1 | Limit (§ 15.203) | 36 |
| 4.2 | Test Result | 36 |
| 5 | Photographs of the Tests | 37 |
| 5.1 | Radiated Disturbances Emission Test | 37 |
| 6 | Photographs of the EUT | 38 |

FCC Test Report Page 2 of 49

Test Result Certification

Report No.: HA150774-RA

| Applicant : advanced PANMOBIL Systems GmbH & Co. KG | | | | | | |
|---|---|--|--|--|--|--|
| Address of Applicant | : Hansestrasse 91, D-51149 Koeln, Germany | | | | | |
| Manufacturer | : advanced PANMOBIL Systems GmbH & Co. KG | | | | | |
| Address of Manufacturer | : Hansestrasse 91, D-51149 Koeln, Germany | | | | | |
| Trade Name | : ECCO+ | | | | | |
| Equipment Under Test | : powerlineECCO+ | | | | | |
| Model Number | : powerlineECCO+ | | | | | |
| Product Series | : N/A | | | | | |
| FCC ID | : 2AACD-EECCOPLUS | | | | | |
| Filing Type | : Certification | | | | | |
| Sample Received Date | : 28-Jul-2015 | | | | | |
| Test Standard : | | | | | | |
| ⊠ FC | C Part 15 Subpart C §15.249 | | | | | |
| Deviations from standard test methods & any other specifications : NONE | | | | | | |

Remark:

- 1. This report details the results of the test carried out on one sample.
- 2. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in both ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.203, 15.207, 15.209, 15.249.
- 3. This report applies to the above sample only and shall not be reproduced in part without written approval of HongAn Technology Co., Ltd.

| | Kaghang | | |
|----------------|--------------------------------|---------|------------|
| Documented by: | 0 | <u></u> | 2015-10-01 |
| | Kay Wang/ ADM. Dept Staff | | |
| Tested by: | Bason . Hsieh | | 2015-09-07 |
| | Eason Hsieh / ENG. Dept. Staff | | |
| | Peter Chin | | |
| Approved by: | 140 | Date: | 2015-10-01 |
| | Peter Chin / Section Manager | | |

FCC Test Report Page 3 of 49

Summary of Test Result

| | Test Item | Applicable Standard | Test Result |
|---|--------------------------|-------------------------------|----------------|
| 1 | Antenna Requirement | FCC part 15 subpart C §203 | Compliance |
| 2 | Conducted limits | FCC part 15 subpart C §207 | Not applicable |
| 3 | Radiated emission limits | FCC part 15 subpart C §209 | Compliance |
| 4 | 20dB Bandwidth | FCC part 15 subpart C §215 | Compliance |
| 5 | Field Strength | FCC part 15 subpart C §249(a) | Compliance |
| | Emissions Radiated | | |
| 6 | outside of the specified | FCC part 15 subpart C §249(d) | Compliance |
| | frequency bands | | |

FCC Test Report Page 4 of 49



1 General Description

1.1 Description of EUT

| Equipment Under Test | : | powerlineECCO+ | | | | | | | |
|-----------------------------------|---|---|---|--|---|--|---|----------------------------------|--|
| Model Number of EUT | : | powerlin | powerlineECCO+ | | | | | | |
| Product Series | : | N/A | | | | | | | |
| Power Supply | : | Li-Ploymer Battery DC 3.7 V, 1500mAh | | | | | | | |
| Frequency Range | : | 902~928 | 8 MHz | | | | | | |
| Transmit Power | : | 62.46 dE | BuV/m @ | 902 MH | z | | | | |
| Number of Channels | : | 27 Chan | nels | | | | | | |
| Carrier Frequency of Each Channel | : | 00 01 02 03 04 05 06 | 902 903 904 905 906 907 908 | 07 08 09 10 11 12 13 | 909 910 911 912 913 914 915 | 14 15 16 17 18 19 20 | 916 917 918 919 920 921 922 | 21 22 23 24 25 26 | 923 924 925 926 927 928 |
| Antenna Specification | : | Loop PC | B Anten | na/ Gain | : 0 dBi | | | | |
| Modulation Technique | : | ASK | | | | | | | |
| Specification | : | Dimensions: 87 mm (L) X 48 mm (W) X 26 mm (H) Weight: 90g Function: The EUT is an UHF RFID reader. **For more detail specification, please refer to the User Manual. | | | | | | | |

FCC Test Report Page 5 of 49

1.2 Test Instruments

HA2

| Instrument Name | Manufacture Mode | Model Number | Serial Number | Last Cal. Date | Next Cal. Date |
|------------------------------------|---------------------------------------|-----------------|---------------|----------------|----------------|
| RF Amplifier | Schaffner | CPA9231A | 0405 | 01-JUN-2015 | 31-MAY-2016 |
| EMI Receiver | R&S | ESCI | 100931 | 25-JUL-2015 | 24-JUL-2016 |
| Spectrum Analyzer | R&S | FSV | 101629 | 27-JAN-2015 | 26-JAN-2016 |
| Preamplifier | HD | HD17187 | 004 | 01-JUN-2015 | 31-MAY-2016 |
| Bilog Antenna | TESEQ | CBL6111D | 38521 | 04-JUN-2015 | 03-JUN-2016 |
| Double-Ridged Waveguide Horn | EMCO | 3115 | 9912-5992 | 01-JUN-2015 | 31-MAY-2016 |
| Horn Antenna (18-40GHz) | Com-Power | AH-840 | 101042 | 02-JUN-2015 | 01-JUN-2016 |
| Microwave Preamplifier | Com-Power | PAM-840 | 461269 | 04-JUN-2015 | 03-JUN-2016 |
| L.I.S.N. | Rolf Heine Hochfrequenzte chnik | NNB-4/32T | 00001 | 18-MAR-2015 | 17-MAR-2016 |
| L.I.S.N. | EMCO | 3810/2NM | 9702-1818 | 20-MAR-2015 | 19-MAR-2016 |

Report No.: HA150774-RA

FCC Test Report Page 6 of 49

The test equipments used are calibrated and can be traced to National ITRI and International Standards.

1.3 Auxiliary Equipments

1.3.1. Provided by HongAn Technology Co., Ltd. for Emission Test.

N/A

1.3.2. Provided by the Manufacturer

N/A

1.4 EUT SETUP



Report No.: HA150774-RA

Note: Main Test Sample: powerlineECCO+

1.5 Identifying the Final Test Mode

- 1. Mode 1: TX CH 00 (902MHz).
- 2. Mode 2: TX CH 13 (915MHz).
- 3. Mode 3: TX CH 26 (928MHz).
- 4. Mode 4: RX mode.

Note:

- 1. After pre-test, we identified that the TX (Mode 3) was most likely to cause maximum disturbance and most likely to be susceptible to disturbance. Therefore, the Final Assessment was performed for the worst case.
- 2. The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.
- 3. Channel Low (902 MHz), Mid (915 MHz) and High (928 MHz) were chosen for full testing.
- According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.207, 15.209 and 15.249 under the FCC Rules Part 15 Subpart C.
- 5. Fully charged Li-polymer Battery has been used during all testing.

1.6 Final Test Mode

Conducted Emission: N/A. Field Strength: All Mode.

Radiated Emission (30~1000 MHz): Mode 3. Radiated Emission (1~26.5GHz): All Mode.

FCC Test Report Page 7 of 49

1.7 Condition of Power Supply

Li-polymer battery x1, DC 3.7 V, 1500 mAh.

1.8 EUT Configuration

- 1. Setup the EUT as shown in Sec.1.4 Block Diagram.
- 2. Turn on the power of all equipments.
- 3. Activate the selected Final Test Mode.

1.9 Test Methodology

The tests documented in this report were performed in accordance with ANSI C63.10 (2013) and FCC CFR 47 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057, 15.203, 15.207, 15.209 and 15.249.

Report No.: HA150774-RA

1.10 General Test Procedures

Conducted Emissions

The EUT is set according to the requirements in Section 6.2 of ANSI C63.10 (2013).

Radiated Emissions

The EUT is set according to the requirements in Section 6.3 of ANSI C63.10 (2013).

1.11 Modification

N/A

FCC Test Report Page 8 of 49

1.12 FCC Part 15.205 restricted bands of operations

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

Report No.: HA150774-RA

| MHz | MHz | MHz | GHz |
|--------------------------|---------------------|---------------|-------------|
| 0.090-0.110 | 16.42-16.423 | 399.9-410 | 4.5-5.15 |
| ¹ 0.495-0.505 | 16.69475-16.69525 | 608-614 | 5.35-5.46 |
| 2.1735-2.1905 | 16.80425-16.80475 | 960-1240 | 7.25-7.75 |
| 4.125-4.128 | 25.5-25.67 | 1300-1427 | 8.025-8.5 |
| 4.17725-4.17775 | 37.5-38.25 | 1435-1626.5 | 9.0-9.2 |
| 4.20725-4.20775 | 73-74.6 | 1645.5-1646.5 | 9.3-9.5 |
| 6.215-6.218 | 74.8-75.2 | 1660-1710 | 10.6-12.7 |
| 6.26775-6.26825 | 108-121.94 | 1718.8-1722.2 | 13.25-13.4 |
| 6.31175-6.31225 | 123-138 | 2200-2300 | 14.47-14.5 |
| 8.291-8.294 | 149.9-150.05 | 2310-2390 | 15.35-16.2 |
| 8.362-8.366 | 156.52475-156.52525 | 2483.5-2500 | 17.7-21.4 |
| 8.37635-8.38675 | 156.7-156.9 | 2690-2900 | 22.01-23.12 |
| 8.41425-8.41475 | 162.0125-167.17 | 3260-3267 | 23.6-24.0 |
| 12.29-12.293 | 167.72-173.2 | 3332-3339 | 31.2-31.8 |
| 12.51975-12.52025 | 240-285 | 3345.8-3358 | 36.43-36.5 |
| 12.57675-12.57725 | 322-335.4 | 3600-4400 | (2) |
| 13.36-13.41 | | | |

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

FCC Test Report Page 9 of 49

² Above 38.6

⁽b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

1.13 Qualification of Test Facility

SL2-IS-E-0023, SL2-IN-E-0023, SL2-R1-E-0023, SL2-R2-E-0023, :

Report No.: HA150774-RA

SL2-A1-E-0023, SL2-L1-E-0023.

FCC Designation No. : TW1071

TAF Accreditation No. : 1163

VCCI Certificate No. : R-2156, C-2329, T-219

FCC Test Report Page 10 of 49

2 Power line Conducted Emission Measurement

2.1 Test Instruments

Refer to Sec. 1.2 Test Instruments.

2.2 Test Arrangement and Procedure

- 1. The EUT was placed on a table, which is 0.8m above ground plane.
- 2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.

Report No.: HA150774-RA

3. Repeat above procedures until all frequency measured were complete.

2.3 Limit (§ 15.207)

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

| Frequency (MHz) | Limits (dBuV) | | |
|-----------------|-------------------|----------------|--|
| Frequency (MHZ) | Q.P. (Quasi-Peak) | A.V. (Average) | |
| 0.15 to 0.50 | 66 to 56 | 56 to 46 | |
| 0.50 to 5.0 | 56 | 46 | |
| 5.0 to 30 | 60 | 50 | |

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

2.4 Test Result

Not applicable.


FCC Test Report Page 11 of 49

3 20 dB Bandwidth of the Emission

3.1 Test Instruments

Refer to Sec. 1.2 Test Instruments.

3.2 Test Arrangement and Procedure



3.3 Test Result

| Channel | Frequency (MHz) | 20 dB Bandwidth (kHz) | |
|---------|-----------------|-----------------------|--|
| 00 | 902 | 254.7 | |
| 13 | 915 | 289.4 | |
| 26 | 928 | 285.1 | |

Report No.: HA150774-RA

Note: if the 20 dB Bandwidths are over 1MHz, the RBW setting of measuring Field strength of Fundamental should be at 3 MHz, and VBW should be at 10 MHz.


The final test data are shown on the following page(s).

FCC Test Report Page 12 of 49

Temperature : 28.1° C Humidity : 35%

Test Date : 07-Sep-2015 Tested by : Eason Hsieh

Channel: CH00 (902MHz)




FCC Test Report Page 13 of 49

Temperature : 28.1° C Humidity : 35%

Test Date : 07-Sep-2015 Tested by : Eason Hsieh

Channel: CH13 (915MHz)




FCC Test Report Page 14 of 49

Temperature : 28.1° C Humidity : 35%

Test Date : 07-Sep-2015 Tested by : Eason Hsieh

Channel: CH26 (928MHz)




FCC Test Report Page 15 of 49


4 Radiated Emission Test

4.1 Test Instruments

Refer to Sec. 1.2 Test Instruments.

4.2 Test Arrangement and Procedure





- 1. The EUT is placed on a turntable, which is 0.8 m (below 1GHz) and 1.5m (above 1GHz) above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3 m away from the receiving antenna, which is varied from 1 m to 4 m to find out the highest emissions.
- 4. Maxium procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Set the spectrum analyzer in the following setting as:
 - (a) Below 1 GHz: RBW =100 kHz/ VBW = 1 MHz/ Sweep = AUTO.

FCC Test Report Page 16 of 49



(b) Above 1 GHz: Peak: RBW = VBW = 1MHz/ Sweep = AUTO; Average: RBW = 1MHz/ VBW = 10Hz/ Sweep = AUTO.

Report No.: HA150774-RA

7. Repeat above procedures until the meausreemnts for all frequencies are complete.

4.3 Limit of Field Strength of Fundamental (§ 15.249(a))

(a) Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

| Fundamental frequency | Field strength of fundamental (millivolts/meter) | Field strength of harmonics (microvolts/meter) |
|-----------------------|--|--|
| 902-928 MHz | 50 | 500 |
| 2400-2483.5 MHz | 50 | 500 |
| 5725-5875 MHz | 50 | 500 |
| 24.0-24.25 GHz | 250 | 2500 |

4.4 Limit (§ 15.205 & § 15.209 & § 15.249(d))

- 4.4.1. Limit of Restricted Band of Operation (§ 15.205)
 - (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| | Frequency Band | | | | | | |
|--------------------------|-------------------|---------------|------------|--|--|--|--|
| MHz | MHz | MHz | GHz | | | | |
| 0.090-0.110 | 16.42-16.423 | 399.9-410 | 4.5-5.15 | | | | |
| ¹ 0.495-0.505 | 16.69475-16.69525 | 608-614 | 5.35-5.46 | | | | |
| 2.1735-2.1905 | 16.80425-16.80475 | 960-1240 | 7.25-7.75 | | | | |
| 4.125-4.128 | 25.5-25.67 | 1300-1427 | 8.025-8.5 | | | | |
| 4.17725-4.17775 | 37.5-38.25 | 1435-1626.5 | 9.0-9.2 | | | | |
| 4.20725-4.20775 | 73-74.6 | 1645.5-1646.5 | 9.3-9.5 | | | | |
| 6.215-6.218 | 74.8-75.2 | 1660-1710 | 10.6-12.7 | | | | |
| 6.26775-6.26825 | 108-121.94 | 1718.8-1722.2 | 13.25-13.4 | | | | |
| 6.31175-6.31225 | 123-138 | 2200-2300 | 14.47-14.5 | | | | |
| 8.291-8.294 | 149.9-150.05 | 2310-2390 | 15.35-16.2 | | | | |

FCC Test Report Page 17 of 49

| 8.362-8.366 | 156.52475-156.52525 | 2483.5-2500 | 17.7-21.4 |
|-------------------|---------------------|-------------|-------------|
| 8.37625-8.38675 | 156.7-156.9 | 2690-2900 | 22.01-23.12 |
| 8.41425-8.41475 | 162.0125-167.17 | 3260-3267 | 23.6-24.0 |
| 12.29-12.293 | 167.72-173.2 | 3332-3339 | 31.2-31.8 |
| 12.51975-12.52025 | 240-285 | 3345.8-3358 | 36.43-36.5 |
| 12.57675-12.57725 | 322-335.4 | 3600-4400 | |
| 13.36-13.41 | | | |

FCC Test Report Page 18 of 49



4.4.2. Limit of Spurious Emission (§ 15.209)

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is lesser attenuation.

Report No.: HA150774-RA

| Frequency | Field strength | Measurement distance |
|-------------|---------------------|----------------------|
| (MHz) | (microvolts/ meter) | (meters) |
| 0.009-0.490 | 2400/F(kHz) | 300 |
| 0.490-1.705 | 24000/F(kHz) | 30 |
| 1.705-30.0 | 30 | 30 |
| 30-88 | 100** | 3 |
| 88-216 | 150** | 3 |
| 216-960 | 200** | 3 |
| Above 960 | 500 | 3 |

^{**} Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g.§§ 15.231 and 15.241.

4.4.3. Limit of Spurious Emission (§ 15.249(d))

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation.

4.5 Test Result

Compliance

The final test data are shown on the following page(s).

FCC Test Report Page 19 of 49

Radiated Emission Test Data (Field Strength of Fundamental)


Report No.: HA150774-RA

Temperature : 28.1℃ Humidity : 35%

Test Date 07-Sep-2015 Tested by : Eason Hsieh

Polarization : Vertical Channel : CH 00, 13, 26 (902, 915,928 MHz)

Test Mode Mode 1



| Freq | Reading | C.F | Result | Limit | Margin | A/pos | T/pos | Remark |
|---------------------------------------|-------------------------|-------------------------|-------------------------|-------------------------|----------------------------|-------|-------|--------|
| MHz | dBuY | dB | dBuV/m | dBuY/m | dB | | | |
| 1 @ 902.000 2 915.000 3 928.000 | 66.86 62.93 65.17 | -4.40 -4.22 -4.02 | 62.46 58.71 61.15 | 94.00 94.00 94.00 | -31.54 -35.29 -32.85 | | | |

C.F = Antenna Factor + Cable Loss - Preamp gain Result = Reading + C.F ; Margin = Result - Limit

@ :Maximum Data x:Over Limit

Remark:

1. All readings are Peak values. None of the peak value reading exceeds the A.V. limit. Hence, A.V. reading was not measured.

2. Spectrum setting: Peak Setting, RBW = 100kHz, VBW = 300kHz

FCC Test Report Page 20 of 49

A H

Radiated Emission Test Data (Field Strength of Fundamental)


Report No.: HA150774-RA

Temperature : 28.1° C Humidity : 35%

Test Date : 07-Sep-2015 Tested by : Eason Hsieh

Polarization : Horizontal : CH 00, 13, 26 (902, 915,928 MHz)

Test Mode : Mode 1



C.F = Antenna Factor + Cable Loss - Preamp gain Result = Reading + C.F ; Margin = Result - Limit

@:Maximum Data x:Over Limit

Remark:

1. All readings are Peak values. None of the peak value reading exceeds the A.V. limit. Hence, A.V. reading was not measured.

2. Spectrum setting: Peak Setting, RBW = 100kHz, VBW = 300kHz

FCC Test Report Page 21 of 49

Radiated Emission Test Data (Below 1 GHz)


Report No.: HA150774-RA

Temperature : 28.1° C Humidity : 35%

Test Date : 07-Sep-2015 Tested by : Eason Hsieh

Polarization : Vertical : CH26 (928MHz)

EUT Position : Vertical



| | Freq | Reading | C.F | Result | Limit | Margin | A/pos | T/pos | Remark |
|-----|---------|---------|--------|--------|--------|--------|-------|-------|--------|
| | MHz | dBuV | dB | dBuY/m | dBuY/m | dB | | | |
| 1 | 51.340 | 45.43 | -15.53 | 29.90 | 40.00 | -10.10 | | | |
| 2 | 134.760 | 56.49 | -23.30 | 33.19 | 43.50 | -10.31 | | | |
| 3 @ | 272.500 | 59.01 | -20.27 | 38.74 | 46.00 | -7.26 | | | |
| 4 | 398.600 | 46.65 | -15.39 | 31.26 | 46.00 | -14.74 | | | |
| 5 | 532.460 | 46.43 | -12.42 | 34.01 | 46.00 | -11.99 | | | |
| 6 | 662.440 | 38.19 | -9.51 | 28.68 | 46.00 | -17.32 | | | |

C.F = Antenna Factor + Cable Loss - Preamp gain
Result = Reading + C.F ; Margin = Result - Limit

@ :Maximum Data x :Over Limit

Remark:

- 1. Measuring frequencies from 30 MHz to 1 GHz.
- 2. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Peak detector mode.
- 3. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
- 4. All readings are Peak values. None of the peak value reading exceeds the Q.P. limit. Hence, Q.P. reading was not measured.
- 5. The IF bandwidth of SPA between 30 MHz to 1 GHz was 100 kHz.

FCC Test Report Page 22 of 49

600

Radiated Emission Test Data (Below 1 GHz)


Report No.: HA150774-RA

Temperature : 28.1° C Humidity : 35%

Test Date : 07-Sep-2015 Tested by : Eason Hsieh

Polarization : Horizontal Channel : CH26 (928MHz)

EUT Position : Vertical



| | Freq | Reading | C.F | Result | Limit | Margin | A/pos | T/pos | Remark |
|-----|---------|---------|--------|--------|--------|--------|-------|-------|--------|
| | MHz | dBuY | dB | dBuV/m | dBuY/m | dB | | | |
| 1 | 51.340 | 44.88 | -15.53 | 29.35 | 40.00 | -10.65 | | | |
| 2 | 134.760 | 54.08 | -23.30 | 30.78 | 43.50 | -12.72 | | | |
| 3 | 194.900 | 51.08 | -19.02 | 32.06 | 43.50 | -11.44 | | | |
| 4 @ | 272.500 | 64.16 | -20.27 | 43.89 | 46.00 | -2.11 | | | |
| 5 | 458.740 | 49.77 | -14.64 | 35.13 | 46.00 | -10.87 | | | |
| 6 | 532.460 | 46.24 | -12.42 | 33.82 | 46.00 | -12.18 | | | |
| | | | | | | | | | |

C.F = Antenna Factor + Cable Loss - Preamp gain Result = Reading + C.F ; Margin = Result - Limit

@:Maximum Data x:Over Limit

Remark:

- 1. Measuring frequencies from 30 MHz to 1 GHz.
- 2. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Peak detector mode.
- 3. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
- 4. All readings are Peak values. None of the peak value reading exceeds the Q.P. limit. Hence, Q.P. reading was not measured.
- 5. The IF bandwidth of SPA between 30 MHz to 1 GHz was 100 kHz.

FCC Test Report Page 23 of 49


Report No.: HA150774-RA

Temperature : 28.1° C Humidity : 35%

Test Date : 07-Sep-2015 Tested by : Eason Hsieh

Polarization : Vertical : CH00 (902MHz)

EUT Position : Vertical



C.F = Antenna Factor + Cable Loss - Preamp gain

Result = Reading + C.F ; Margin = Result - Limit

@:Maximum Data x:Over Limit

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode.
- 4. All readings are Peak values. None of the peak value reading exceeds the A.V. limit. Hence, A.V. reading was not measured.
- 5. Spectrum setting:
 - (a) Peak Setting 1GHz to 10th harmonics of fundamental, RBW = VBW = 1MHz, Sweep = AUTO.

FCC Test Report Page 24 of 49


Report No.: HA150774-RA

Temperature : 28.1° C Humidity : 35%

Test Date : 07-Sep-2015 Tested by : Eason Hsieh

Polarization : Horizontal : CH00 (902MHz)

EUT Position : Vertical



C.F = Antenna Factor + Cable Loss - Preamp gain Result = Reading + C.F ; Margin = Result - Limit

nesair - newallig . G.I) Halgill - nesair r

@:Maximum Data x:Over Limit

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode.
- 4. All readings are Peak values. None of the peak value reading exceeds the A.V. limit. Hence, A.V. reading was not measured.
- 5. Spectrum setting:
 - (a) Peak Setting 1GHz to 10th harmonics of fundamental, RBW = VBW = 1MHz, Sweep = AUTO.

FCC Test Report Page 25 of 49


Report No.: HA150774-RA

28.1℃ Temperature 35% Humidity

Test Date 07-Sep-2015 Eason Hsieh Tested by

Polarization Vertical Channel CH13 (915MHz)





C.F = Antenna Factor + Cable Loss - Preamp gain Result = Reading + C.F Margin = Result

x:Over Limit @ :Maximum Data

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode.
- 4. All readings are Peak values. None of the peak value reading exceeds the A.V. limit. Hence, A.V. reading was not measured.
- 5. Spectrum setting:
 - (a) Peak Setting 1GHz to 10th harmonics of fundamental, RBW = VBW = 1MHz, Sweep = AUTO.

FCC Test Report Page 26 of 49


Report No.: HA150774-RA

Temperature : 28.1° C Humidity : 35%

Test Date : 07-Sep-2015 Tested by : Eason Hsieh

Polarization : Horizontal Channel : CH13 (915MHz)

EUT Position : Vertical



C.F = Antenna Factor + Cable Loss - Preamp gain

Result = Reading + C.F ; Margin = Result - Limit

@:Maximum Data x:Over Limit

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode.
- 4. All readings are Peak values. None of the peak value reading exceeds the A.V. limit. Hence, A.V. reading was not measured.
- 5. Spectrum setting:
 - (a) Peak Setting 1GHz to 10th harmonics of fundamental, RBW = VBW = 1MHz, Sweep = AUTO.

FCC Test Report Page 27 of 49


Report No.: HA150774-RA

Temperature : 28.1° C Humidity : 35%

Test Date : 07-Sep-2015 Tested by : Eason Hsieh

Polarization : Vertical : CH26 (928MHz)

EUT Position : Vertical



C.F = Antenna Factor + Cable Loss - Preamp gain

Result = Reading + C.F ; Margin = Result

0 : Maximum Data \times : Over Limit

Remark:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode.
- 4. All readings are Peak values. None of the peak value reading exceeds the A.V. limit. Hence, A.V. reading was not measured.
- 5. Spectrum setting:
 - (a) Peak Setting 1GHz to 10th harmonics of fundamental, RBW = VBW = 1MHz, Sweep = AUTO.

FCC Test Report Page 28 of 49


Report No.: HA150774-RA

Humidity Temperature 28.1℃ 35%

Test Date 07-Sep-2015 Eason Hsieh Tested by

Polarization Horizontal Channel CH26 (928MHz)

EUT Position Vertical



Result = Reading + C.F ; Margin = Result - Limit

x:Over Limit @ :Maximum Data

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode.
- 4. All readings are Peak values. None of the peak value reading exceeds the A.V. limit. Hence, A.V. reading was not measured.
- 5. Spectrum setting:
 - (a) Peak Setting 1GHz to 10th harmonics of fundamental, RBW = VBW = 1MHz, Sweep = AUTO

FCC Test Report Page 29 of 49


Report No.: HA150774-RA

Temperature **28.1**℃ Humidity 35%

Test Date 07-Sep-2015 Tested by Eason Hsieh

Polarization Horizontal Channel CH00 (902MHz)

EUT Position Vertical



| | Freq | Reading | C.F | Result | Limit | Margin | A/pos | T/pos | Remark |
|-------------|-------------------------------|-------------------------|---------------------------|-------------------------|-------------------------|----------------------------|-------|-------|----------------------|
| - | MHz | dBuV | dB | dBuY/m | dBuV/m | dB | | | |
| 1 2 3 | 608.060 614.000 900.000 | 30.03 28.86 26.52 | -10.75 -10.63 -4.42 | 19.28 18.23 22.10 | 46.00 46.00 46.00 | -26.72 -27.77 -23.90 | | | Peak Peak Peak |

C.F = Antenna Factor + Cable Loss - Preamp gain Result = Reading + C.F ; Margin = Result - Limit

@ :Maximum Data x:Over Limit

Remark:

1.All readings are Peak values. None of the peak value reading exceeds the A.V. limit. Hence, A.V. reading was not measured.

2.Spectrum setting: Peak Setting, RBW = 100kHz, VBW = 300kHz

FCC Test Report Page 30 of 49


Report No.: HA150774-RA

Temperature : 28.1℃ Humidity : 35%

Test Date 07-Sep-2015 Tested by : Eason Hsieh

Polarization Vertical Channel : CH00 (902MHz)

EUT Position Vertical



| Freq | Reading | C.F | Result | Limit | Margin | A/pos | T/pos | Remark |
|---------------------------------------|---------|---------------------------|-------------------------|-------------------------|----------------------------|-------|-------|----------------------|
| MHz | dBuV | dB | dBuY/m | dBuV/m | dB | | | |
| 1 608.060 2 614.000 3 @ 900.000 | 28.59 | -10.75 -10.63 -4.42 | 19.77 17.96 22.87 | 46.00 46.00 46.00 | -26.23 -28.04 -23.13 | | | Peak Peak Peak |

C.F = Antenna Factor + Cable Loss - Preamp gain Result = Reading + C.F ; Margin = Result - Limit

@ :Maximum Data x:Over Limit

Remark:

1.All readings are Peak values. None of the peak value reading exceeds the A.V. limit. Hence, A.V. reading was not measured.

2.Spectrum setting: Peak Setting, RBW = 100kHz, VBW = 300kHz

FCC Test Report Page 31 of 49


Report No.: HA150774-RA

Temperature Humidity 35% : 28.1℃

Test Date 07-Sep-2015 Tested by Eason Hsieh

Polarization Horizontal Channel CH26 (928MHz)

EUT Position Vertical



C.F = Antenna Factor + Cable Loss - Preamp gain Result = Reading + C.F ; Margin = Result - Limit Result = Reading + C.F ;

@ :Maximum Data x:Over Limit

Remark:

1.All readings are Peak values. None of the peak value reading exceeds the A.V. limit. Hence, A.V. reading was not measured.

2.Spectrum setting: Peak Setting, RBW = 100kHz, VBW = 300kHz

FCC Test Report Page 32 of 49


Report No.: HA150774-RA

Temperature : 28.1°C Humidity : 35%

Test Date : 07-Sep-2015 Tested by : Eason Hsieh

Polarization : Vertical Channel : CH26 (928MHz)

EUT Position : Vertical



C.F = Antenna Factor + Cable Loss - Preamp gain Result = Reading + C.F ; Margin = Result - Limit

@:Maximum Data x:Over Limit

Remark:

1.All readings are Peak values. None of the peak value reading exceeds the A.V. limit. Hence, A.V. reading was not measured.

2.Spectrum setting: Peak Setting, RBW = 100kHz, VBW = 300kHz

FCC Test Report Page 33 of 49


Report No.: HA150774-RA

Temperature : 28.1° C Humidity : 35%

Test Date : 07-Sep-2015 Tested by : Eason Hsieh

Polarization : Horizontal Channel : CH26 (928MHz)

EUT Position : Vertical



C.F = Antenna Factor + Cable Loss - Preamp gain Result = Reading + C.F ; Margin = Result - Limit

@:Maximum Data x:Over Limit

Remark:

1.All readings are Peak values. None of the peak value reading exceeds the A.V. limit. Hence, A.V. reading was not measured.

2.Spectrum setting: Peak Setting, RBW = VBW = 1MHz

FCC Test Report Page 34 of 49


Report No.: HA150774-RA

Temperature : 28.1°C Humidity : 35%

Test Date : 07-Sep-2015 Tested by : Eason Hsieh

Polarization : Vertical Channel : CH26 (928MHz)

EUT Position : Vertical



C.F = Antenna Factor + Cable Loss - Preamp gain Result = Reading + C.F ; Margin = Result - Limit

@:Maximum Data x:Over Limit

Remark:

1.All readings are Peak values. None of the peak value reading exceeds the A.V. limit. Hence, A.V. reading was not measured.

2.Spectrum setting: Peak Setting, RBW = VBW = 1MHz

FCC Test Report Page 35 of 49

5 Antenna requirement

5.1 Limit (§ 15.203)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a uniue coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

Report No.: HA150774-RA

5.2 Test Result

The EUT applies a Loop PCB antenna.

-----End Of Test Report-----

FCC Test Report Page 36 of 49