FCC TEST REPORT(GSM)

for

MC MOBILE E.U.

GSM Mobile Phone

Model Number: Aerox

FCC ID: 2AACKAEROX

Prepared for : MC MOBILE E.U.

Address : CRA 112F# 72C-03 TO1 APT 301, BOGOTA, Colombia

Prepared by: Keyway Testing Technology Co., Ltd.

Address : Baishun Industrial Zone, Zhangmutou Town,

Dongguan, Guangdong, China

Tel: 86-769-8718 2258 Fax: 86-769-8718 1058

Report No. : 14KWE08178501F Date of Test : Aug. 1~5, 2014 Date of Report : Aug. 5, 2014

TABLE OF CONTENTS

Test	Report Declaration	Page
1. 7	EST SUMMARY	4
2. (GENERAL PRODUCT INFORMATION	5
2.1	Product Function	5
2.2		
2.3		
2.4	Test Supporting System	5
2.5	Independent Operation Modes	6
3.	EST SITES	7
3.1	Test Facilities	7
3.2	List of Test and Measurement Instruments	8
4. 7	EST SET-UP AND OPERATION MODES	9
4.1	Principle of Configuration Selection	9
4.2	Block Diagram of Test Set-up	9
4.3	·	
4.4	- 1	
4.5		
5. E	EMISSION TEST RESULTS	10
5.1	Conducted Emission at the Mains Terminals Test	10
5.2		
5.3		
5.4	- 1 7 7	
5.5		
5.6		
5.7 5.8	,	
	PHOTOGRAPHS OF TEST SET-UP	
7. F	PHOTOGRAPHS OF THE EUT	36

Keyway Testing Technology Co., Ltd.

Applicant: MC MOBILE E.U.

Address: CRA 112F# 72C-03 TO1 APT 301, BOGOTA, Colombia

Manufacturer: Shenzhen Leed Electronic Co.,LTD

Address:

Room 29A1,Block A, Zhonghangbeiyuan Building,Zhenhua

Road, Futian District Shenzhen China

E.U.T: GSM Mobile Phone

Model Number: Aerox

Trade Name: MC MOBILE Serial No.: -----

Date of Receipt: Jul. 31, 2014 Date of Test: Aug. 1~5, 2014

Test Specification: FCC CFR Title 47 Part 2: 2013

FCC CFR Title 47 Part22 Subpart H: 2013 FCC CFR Title 47 Part24 Subpart E: 2013

Test Result: The equipment under test was found to be compliance with the

requirements of the standards applied.

Issue Date: Aug. 5, 2014

Tested by:

Reviewed by:

Approved by:

Andy Gao / Engineer

Jade Yang/ Supervisor

Chris Du / Manager

Other Aspects:

None.

Abbreviations: OK/P=passed

fail/F=failed

n.a/N=not applicable

E.U.T=equipment under tested

This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Keyway Testing Technology Co., Ltd.

1.TEST SUMMARY

Test Items	Test Requirement	Result
Conducted Emission at the Mains Terminals	15.207	PASS
555 (0.15)	Part 1.1307	
RF Exposure (SAR)	Part 2.1093	(Please refer to SAR Report)
Conducted RF Output Power	2.1046	PASS
	2.1049,	
99% & -26 dB Occupied Bandwidth	22.917	PASS
	24.238,	
	2.1055,	
Frequency Stability	22.355	PASS
	24.235,	
	2.1051,2.1057	
Conducted Out of Band Emissions	22.917,	PASS
	24.238	
	2.1051,2.1057	
Band Edge	22.917,	PASS
	24.238	
Transporter Dadieted Davies (FIDD/FDD)	22.913,	DACC
Transmitter Radiated Power (EIPR/ERP)	24.232	PASS
	2.1053,2.1057	
Radiated Out of Band Emissions	22.917,	PASS
	24.238	

2.GENERAL PRODUCT INFORMATION

2.1. Product Function

Refer to Technical Construction Form and User Manual.

2.2. Description of Device (EUT)

Product Name:	GSM Mobile Phone
Model No.:	Aerox
	Bluetooth:2402~2480MHz
	GSM 850MHz:
	Tx: 824.20 - 848.80MHz (at intervals of 200kHz);
Operation Frequency:	Rx: 869.20 - 893.80MHz (at intervals of 200kHz)
	GSM 1900MHz:
	Tx: 1850.20 - 1909.80MHz (at intervals of 200kHz);
	Rx: 1930.20 - 1989.80MHz (at intervals of 200kHz)
Channel numbers:	Bluetooth:79 Channels
Channel separation:	Bluetooth:1M
Modulation technology:	Bluetooth: FHSS(GFSK 1Mbps)
	GSM/GPRS Mode with GMSK Modulation
Antenna Type:	Integral Antenna
Antenna gain:	1.0dBi (BT),0.5dBi (GSM)
Device events	DC 5V from adapter
Power supply:	Rechargeable lithium-ion battery 3.7V
GPRS Class:	10

2.3. Difference between Model Numbers

None.

2.4. Test Supporting System

2.4.1. AC Adapter:

Provide: Shenzhen Leed Electronic Co.,LTD

M/N: Aerox

I/P: AC 100~240V 50/60Hz

O/P: DC 5V 500mA FCC Approve: FCC VOC

2.5. Independent Operation Modes

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

	Test modes						
Band	Band Radiated Conducted						
GSM 850	■ GSM link	■ GSM link					
PCS 1900	■ GSM link	■ GSM link					

Note: The maximum power levels are GSM mode for GMSK link,

The conducted power tables are as follows:

Conducted Power average (dBm)							
Band	GSM850 PCS1900						
Channel	128	190	251	512	661	810	
Frequency	824.20	836.60	848.80	1850.20	1880.00	1909.80	
GSM (SIM1)	32.03	32.15	32.04	29.34	29.28	29.31	
GSM (SIM2)	31.98	32.02	31.89	29.12	29.31	29.07	

Note: The worst mode was in SIM1, all test data in SIM1 mode in this report..

3. TEST SITES

3.1. Test Facilities

Lab Qualifications: 944 Shielded Room built by ETS-Lindgren, USA

Date of completion: March 28, 2011

966 Chamber built by ETS-Lindgren, USA

Date of completion: March 28, 2011

Certificated by TUV Rheinland, Germany.

Registration No.: UA 50207153 Date of registration: July 13, 2011

Certificated by UL, USA Registration No.: 100567-237

Date of registration: September 1, 2011

Certificated by Intertek

Registration No.: 2011-RTL-L1-31 Date of registration: October 11, 2011

Certificated by Industry Canada

Registration No.: 9868A

Date of registration: December 8, 2011

Certificated by FCC, USA Registration No.: 370994

Date of registration: February 21, 2012

Certificated by CNAS China Registration No.: CNAS L5783 Date of registration: August 8, 2012

Name of Firm : Keyway Testing Technology Co., Ltd.

Site Location : Baishun Industrial Zone, Zhangmutou Town,

Dongguan, Guangdong, China

3.2. List of Test and Measurement Instruments

3.2.1. For conducted emission at the mains terminals test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESCI	101156	Apr. 27,14	Apr. 27,15
Artificial Mains Network	Rohde&Schwarz	ENV216	101315	Apr. 27,14	Apr. 27,15
Artificial Mains Network (AUX)	Rohde&Schwarz	ENV216	101314	Apr. 27,14	Apr. 27,15
RF Cable	FUJIKURA	3D-2W	944 Cable	Apr. 27,14	Apr. 27,15

3.2.2. For radiated emission test

	1	I		1	1
Equipment	Equipment Manufacturer Mo		Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESCI	101156	Apr. 27,14	Apr. 27,15
System Simulator	Agilent	E5515C	GB43130245	Apr. 30,14	Apr. 30,15
Power Splitter	Weinschel	1506A	NW425	Apr. 30,14	Apr. 30,15
Bilog Antenna	ETS-LINDGREEN	3142D	135452	Apr. 27,14	Apr. 27,15
Spectrum Analyzer	Agilent	E4411B	MY4511304	Apr. 27,14	Apr. 27,15
3m Semi-anechoic Chamber	ETS-LINDGREEN	966	KW01	Apr. 27,14	Apr. 27,15
Signal Amplifier	SONOMA	310	187016	Apr. 27,14	Apr. 27,15
Signal Amplifier	Agilent	8449B	3008A00251	Apr. 27,14	Apr. 27,15
RF Cable	IMRO	IMRO-400	966 Cable 1#	N/A	N/A
MULTI-DEVICE Controller	ETS-LINDGREEN	2090	126913	N/A	N/A
Horn Antenna	DAZE	ZN30701	11003	Apr. 27,14	Apr. 27,15
Horn Antenna	SCHWARZBECK	BBHA9170	9170-068	Apr. 27,14	Apr. 27,15
Spectrum Analyzer	Agilent	8593E	3911A04271	Apr. 27,14	Apr. 27,15
Spectrum Analyzer	Agilent	E4408B	MY44211125	Apr. 30,14	Apr. 30,15
Signal Amplifier	DAZE	ZN3380C	11001	Apr. 27,14	Apr. 27,15
High Pass filter	Micro	HPM50111	324216	Apr. 30,14	Apr. 30,15
Filter	COM-MW	ZBSF-C836.5-25-X	KW032	Apr. 30,14	Apr. 30,15
Filter	COM-MW	ZBSF-C1747.5-75-X2	KW035	Apr. 30,14	Apr. 30,15
Filter	COM-MW	ZBSF-C1880-60-X2	KW037	Apr. 30,14	Apr. 30,15
DC Power Supply	LongWei	PS-305D	010964729	Apr. 27,14	Apr. 27,15
Constant temperature and humidity box	GF	GTH-800-40-1P	MAA9906-005	Apr. 27,14	Apr. 27,15
Universal radio communication tester	Rohde&Schwarz	CMU200	3215420	Apr. 27,14	Apr. 27,15
Splitter	Agilent	11636B	0025164	Apr. 27,14	Apr. 27,15

FCC ID: 2AACKAEROX

4. TEST SET-UP AND OPERATION MODES

4.1. Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the Operating Instructions.

- 4.2. Block Diagram of Test Set-up See item 6.
- 4.3. Test Operation Mode and Test Software None.
- 4.4. Special Accessories and Auxiliary Equipment None.
- 4.5. Countermeasures to Achieve EMC Compliance None.

5. EMISSION TEST RESULTS

5.1. Conducted Emission at the Mains Terminals Test

5.1.1. Limit 15.207 limits

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBµV)		
	Quasi-peak	Average	
0.15-0.5 0.5-5 5-30	66 to 56 56 60	56 to 46 46 50	

5.1.2. Test Setup

The EUT was put on a wooden table which was 0.8 m high above the ground and connected to the AC mains through the Artificial Mains Network (AMN). Where the mains cable supplied by the manufacture was longer than 0.8 m, the excess was folded back and forth parallel to the cable at the centre so as to form a bundle no longer than 0.4 m.


The EUT was kept 0.4 m from any other earthed conducting surface. Both sides of AC line were checked to find out the maximum conducted emission levels according to the test procedure during the conducted emission test.

The frequency range from 150 kHz to 30 MHz was investigated.

The bandwidth of the test receiver was set at 9 kHz.


Pretest for all mode, The test data of the worst case condition(s) was reported on the following page.

Measurement Uncertainty: ±2.6 dB.




5.1.3. Test Mode

Refer to section 2.5 for details



			Limit	Over	
	Freq	Level	Line	Limit	Remark
· ·	MHz	dBuV	dBuV	dB	
1	0.176	35.83	54.68	-18.85	Average
2	0.176	50.36	64.68	-14.32	QP
3	0.277	28.21	50.90	-22.69	Average
4	0.277	41.10	60.90	-19.80	QP
5	0.375	36.90	58.39	-21.49	QP
6	0.375	27.56	48.39	-20.83	Average
7	0.499	37.20	56.02	-18.82	QP
8	0.499	25.32	46.01	-20.69	Average
9	0.657	33.70	56.00	-22.30	QP
10	0.658	24.36	46.00	-21.64	Average
11	1.480	21.42	46.00	-24.58	Average
12	1.480	31.30	56.00	-24.70	QP

Neutral



			Limit	Over	
	Freq	Level	Line	Limit	Remark
-	MHz	dBuV	dBuV	dB	
1	0.174	30.91	54.77	-23.86	Average
2	0.174	44.29	64.77	-20.48	QP
3	0.199	29.61	53.67	-24.06	Average
4	0.199	41.70	63.67	-21.97	QP
5	0.256	40.30	61.56	-21.26	QP
6	0.256	21.70	51.56	-29.86	Average
7	0.432	32.30	57.21	-24.91	QP
8	0.433	23.73	47.20	-23.47	Average
9	0.541	30.10	56.00	-25.90	QP
10	0.541	22.32	46.00	-23.68	Average
11	1.725	17.25	46.00	-28.75	Average
12	1.725	28.60	56.00	-27.40	QP

Page 12 of 36

5.2. Conducted RF Output Power

5.2.1. Limit

According to FCC section 2.1046(a), FCC part22.913(a) and FCC part24.232(b), for transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in FCC section 2.1033(c)(8).

5.2.2. Test Setup

The EUT, which is powered by the adapter, is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 500hm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power.

5.2.3. Test Result

Here the lowest, middle and highest channels are selected to perform testing to verify the conducted RF output power of the EUT.

Measurement data

Conducted Power average (dBm)						
Band		GSM	850		PCS1900	
Channel	128	190	251	512	661	810
Frequency	824.20	836.60	848.80	1850.20	1880.00	1909.80
GSM (GMSK, 1 TX slot)	32.03	32.15	32.04	29.34	29.28	29.31
GPRS (GMSK, 1 TX slot)	31.12	31.16	31.05	28.26	28.18	28.21
GPRS (GMSK, 2 TX slot)	30.26	30.18	30.22	27.12	27.06	27.09
Limit	38.45				33.01	
Result	Pass					

Note: Measurement Uncertainty: ±2.6 dB.

Page 13 of 36

5.3. 99% & -26 dB Occupied Bandwidth

5.3.1. Limit

According to FCC section 2.1049 and FCC part22.913(a) and FCC part24.232(b), the occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission.

Occupied bandwidth is also known as the 99% emission bandwidth,

5.3.2. Test Setup

The EUT, which is powered by the adapter, is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 500hm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power.

5.3.3. Test Result


Measurement Data

EUT Mode	Channel	Frequency (MHz)	99% Occupy bandwidth (KHz)	-26dB bandwidth (KHz)
0011.050	128	824.20	244.0	318.0
GSM 850 (GSM link)	190	836.60	242.0	316.0
(CON IIIIK)	251	848.80	242.0	316.0
200 4000	512	1850.20	252.0	320.0
PCS 1900 (GSM link)	661	1880.00	246.0	316.0
(33)	810	1909.80	250.0	320.0


Note: Measurement Uncertainty: ±20Hz.

Test plot as follows: 99% Occupy bandwidth


GSM 850MHz Lowest channel



GSM 850MHz Middle channel




GSM 850MHz Highest channel:




-26dB bandwidth




GSM 850MHz Middle channel



GSM 850MHz Highest channel:



-26dB bandwidth







PCS 1900 (GSM link) Middle channel



PCS 1900 (GSM link) Highest channel



99% Occupy bandwidth






PCS 1900 (GSM link) Middle channel



PCS 1900 (GSM link) Highest channel




5.4. Frequency Stability

5.4.1. Limit

According to FCC section 22.355 and FCC section 24.235, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. According to FCC section 2.1055, the test conditions are:

- (a) The temperature is varied from -30°C to +50°C at intervals of not more than 10°C.
- (b) For hand carried battery powered equipment, the primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacture. The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided.

5.4.2. Test Setup



Note: Measurement setup for testing on Antenna connector

The EUT, which is powered by the DC Power Supply directly, is located in the Temperature Chamber.

The EUT is commanded by the System Simulator (SS) to operate at the maximum output power

5.4.3. Test Result

The nominal, highest and lowest extreme voltages are separately 3.7VDC, 4.2VDC and 3.6VDC which are specified by the applicant; the normal temperature here used is 25°C. The frequency deviation limit of 850MHz band is ±2.5ppm, and 1900MHz is ±1ppm

Page 19 of 36

Normal

Т	est Conditions		Frequ	Frequency Deviation		
Band	Power(Vdc)	Temperatu re(°C)	Frequency Error(Hz)	ppm	Limit	Result
	3.7	-30	27	0.0323		
	3.7	-20	33	0.0394		
	3.7	-10	42	0.0502		
GSM850	3.7	0	37	0.0442		
(GSM link)	3.7	10	36	0.0430		
Middle	3.7	20	32	0.0383	±2.5	PASS
channel=190	3.7	30	28	0.0335	±2.5	PASS
channel=836.	3.7	40	32	0.0383		
6MHz	3.7	50	19	0.0227		
	4.25	25	48	0.0574		
	3.70	25	54	0.0645		
	3.40	25	36	0.0430		
	3.7	-30	53	0.0282		
	3.7	-20	59	0.0314		
	3.7	-10	76	0.0404		
PCS1900	3.7	0	64	0.0340		
(GSM link)	3.7	10	48	0.0255		
Middle	3.7	20	55	0.0293	. 1	PASS
channel=661	3.7	30	37	0.0197	±1	PASS
channel=188	3.7	40	41	0.0218		
0MHz	3.7	50	62	0.0330		
	4.25	25	83	0.0441		
	3.70	25	72	0.0383		
	3.40	25	59	0.0314		


Note: Measurement Uncertainty: ±20Hz.

5.5. Conducted Out of Band Emissions

5.5.1. Limit

According to FCC section 22.917(a) and FCC section 24.238(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43+10*log(P)dB. This calculated to be -13dBm.

5.5.2. Test Setup



Note: Measurement setup for testing on Antenna connector

5.5.3. Measurement Procedure

The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz, sufficient scans were taken to show the out of band Emissions if any up to 10th harmonic.

For the out of band: Set the RBW, VBW = 100KHz, Start=30MHz, Stop= 10th harmonic.

Limit = -13dBm


Note: used 5001 sweep points for each plots.

5.5.4. Test Result


The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the out of band emissions.


Test plot as follows:


GSM 850MHz Lowest channel





GSM 850MHz Middle channel






























5.6. Conducted Out of Band Emissions

5.6.1. Limit

According to FCC section 22.917(b) and FCC section 24.238(b), 27.53(g)(h) in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth (26dB emission bandwidth) of the fundamental emission of the transmitter may be employed.

5.6.2. Test Setup



Note: Measurement setup for testing on Antenna connector


5.6.3. Measurement Procedure


The EUT, which is powered by the adapter, is coupled to the Spectrum Analyzer and the System Simulator with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the System Simulator to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the System Simulator.

5.6.4. Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the out of band emissions.

Test plot as follows:






5.7. Transmitter Radiated Power (EIRP/ERP)

5.7.1. Limit


According to FCC section 22.913, the Effective Radiated Power (ERP) of mobile transmitters and auxiliary test transmitters must not exceed 7Watts, and FCC section 24.232, the broadband PCS mobile station is limited to 2 Watts e.i.r.p. peak power.

5.7.2. Test Setup


Below 1GHz



Above 1GHz



Substituted method:



Page 27 of 36

5.7.3. Measurement Procedure

The EUT was placed on an non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer. all test in Full-Anechoic Chamber.

During the measurement, the EUT was communication with the station. The highest emission was recorded with the rotation of the turntable and the lowering of the test antenna from 4m to 1m. The reading was recorded and the field strength (E in dBuV/m) was calculated.

ERP in frequency band 824.2 –848.80.8MHz were measured using a substitution method. The EUT was replaced by dipole antenna connected, the S.G. output was recorded and ERP was calculated as follows:

EIRP in frequency band 1850.2 –1909.8MHz were measured using a substitution method. The EUT was replaced by or horn antenna connected, the S.G. output was recorded and EIRP was calculated as follows:

ERP = S.G. output (dBm) + Antenna Gain (dBd) – Cable Loss (dB)

EIRP = S.G. output (dBm) + Antenna Gain (dBi) - Cable Loss (dB)

5.7.4. Test Result

EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
		Н	V	32.11		
		П	Н	30.48		
	Lawaat	E1	V	29.96	20.45	
	Lowest		Н	29.65	38.45	Pass
		E2	V	28.29		
		E2	Н	27.99		
		Н	V	31.99		Pass
	Middle	П	Н	29.77	38.45	
GSM850		E1	V	27.41		
(GSM link)			Н	28.24		
		E2	V	27.68		
			Н	28.82		
		Н	V	32.08		
		П	Н	29.67		
	∐ighost	E1	V	27.77	20 45	Pass
	Highest	LI	Н	28.21	38.45	F855
		E2	V	26.51		
		LZ	Н	27.86		

EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP (dBm)	Limit (dBm)	Result
		Н	V	29.23		
		П	Н	27.04		
	Laurant	- 4	V	26.56		
	Lowest	E1	Н	25.13	33.01	Pass
		Fo	V	24.68		
		E2	Н	23.55		
		Н	V	29.48		Pass
	Middle	П	Н	27.16	33.01	
PCS1900		E1	V	25.81		
(GSM link)			Н	24.17		
		E2	V	25.48		
			Н	24.50		
		Н	V	29.40		
		П	Н	27.77	33.01	
	Llighoot	E1	V	26.13		Door
	Highest	E'I	Н	24.26		Pass
		E2	V	24.80		
		E2	Н	23.61		

5.8. Radiated Out of Band Emissions

5.8.1. Limit


According to FCC section 22.917(a) and section 24.238(a), 27.53(g) the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power

(P) by a factor of at least 43+10*log(P)dB. This calculated to be -13dBm.


The spurious emission with frequency band 1900 according to FCC section 2.1057.

5.8.2. Test Setup


Below 1GHz



Above 1GHz



Substituted method:



5.8.3. Measurement Procedure

The EUT was placed on a non-conductive, The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations. all test in Full-Anechoic Chamber.

The frequency range up to tenth harmonic was investigated for each of three fundamental frequency

(low, middle and high channels). Once spurious emission was identified, the power of the emission was determined using the substitution method.

The spurious emissions attenuation was calculated as the difference between radiated power at the fundamental frequency and the spurious emissions frequency.

EIRP = S.G. output (dBm) + Antenna Gain(dBi) - Cable Loss (dB)

Note: Measurement Uncertainty: ±3.6 dB.

Band	Frequency	Spurio	ous Emission	Limit	Result
Dallu	(MHz)	Polarization	Level(dBm)	(dBm)	Result
	742.95	Vertical	-70.27		
	1648.40	Vertical	-27.50		
	2472.60	Vertical	-33.19		
	3296.80	Vertical	-34.92		
	4121.00	Vertical	-43.03		
GSM 850	4945.20	Vertical	-37.47	-13	PASS
Lowest	493.66	Horizontal	-70.76	-13	PASS
	2472.60	Horizontal	-30.96		
	3296.80	Horizontal	-35.20		
	4121.00	Horizontal	-40.91		
	4945.20	Horizontal	-43.13		
	5769.40	Horizontal	-39.49		

Band	Frequency	Spurio	ous Emission	Limit	Result
Бапа	(MHz)	Polarization	Level(dBm)	(dBm)	Result
	741.89	Vertical	-70.30		
	1673.20	Vertical	-31.44		
	2509.80	Vertical	-30.49		PASS
	3346.40	Vertical	-37.64	-13	
	4183.00	Vertical	-42.46		
GSM 850	5019.60	Vertical	-40.41		
Middle	492.89	Horizontal	-70.17		
	1673.20	Horizontal	-27.48		
	2509.80	Horizontal	-30.22		
	3346.40	Horizontal	-42.46		
	4183.00	Horizontal	-45.75		
	5019.60	Horizontal	-40.46		

Band	Frequency	Spurio	ous Emission	Limit	Result
Бапа	(MHz)	Polarization	Level(dBm)	(dBm)	Result
	743.23	Vertical	-70.47		
	1697.60	Vertical	-26.51		
	2546.40	Vertical	-27.50		
	3395.20	Vertical	-34.02		
	4244.00	Vertical	-43.35		
GSM 850	5092.80	Vertical	-40.47	10	PASS
Highest	493.02	Horizontal	-73.29	-13	PASS
	1697.60	Horizontal	-26.86		
	2546.40	Horizontal	-28.77		
	3395.20	Horizontal	-36.05		
	4244.00	Horizontal	-42.40		
	5092.80	Horizontal	-40.66		

Band	Frequency	Spuri	ous Emission	Limit	Result
Dallu	(MHz)	Polarization	Level(dBm)	(dBm)	Result
	742.26	Vertical	-71.05		
	3700.40	Vertical	-44.62		
	5550.60	Vertical	-43.84		PASS
	7400.80	Vertical	-41.44	-13	
	9251.00	Vertical	-43.74		
PCS1900	11101.20	Vertical	-40.41		
Lowest	494.15	Horizontal	-71.37		
	3700.40	Horizontal	-46.49		
	5550.60	Horizontal	-45.71		
	7400.80	Horizontal	-40.41		
	9251.00	Horizontal	-44.74		
	11101.20	Horizontal	-41.75		


Band	Frequency	Spurio	ous Emission	Limit	Desuit
Band	(MHz)	Polarization	Level(dBm)	(dBm)	Result
	743.53	Vertical	-71.27		
	3760.00	Vertical	-42.46		
	5640.00	Vertical	-44.05		
	7520.00	Vertical	-40.09		
	9400.00	Vertical	-39.75		
PCS1900	11280.00	Vertical	-38.15	-13	PASS
Middle	493.93	Horizontal	-71.37	-13	PASS
	3760.00	Horizontal	-44.62		
	5640.00	Horizontal	-42.13	1	
	7520.00	Horizontal	-36.84		
	9400.00	Horizontal	-40.46		
	11280.00	Horizontal	-38.39		

Band	Frequency	Spurio	ous Emission	Limit	Result
Бапа	(MHz)	Polarization	Level(dBm)	(dBm)	Result
	741.78	Vertical	-71.15		
	3819.60	Vertical	-42.71		
	5729.40	Vertical	-39.73		PASS
	7639.20	Vertical	-35.48	-13	
	9549.00	Vertical	-39.75		
PCS1900	11458.80	Vertical	-39.09		
Highest	492.79	Horizontal	-71.12		
	3819.60	Horizontal	-42.34		
	5729.40	Horizontal	-37.73		
	7639.20	Horizontal	-34.19		
	9549.00	Horizontal	-39.75		
	11458.80	Horizontal	-37.90		

6. PHOTOGRAPHS OF TEST SET-UP

Conducted Emission







7. PHOTOGRAPHS OF THE EUT

Reference to the test report No. 14KWE08178502F

END.