

SAR evaluation
FCC ID: 2AACS-INF431

MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d$$

$$\text{Power Density: } P_d \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well

as the gain of the used antenna, the RF power density can be obtained.

Calculated WIFI Result and Limit (WORSE CASE IS AS BELOW)

Antenna Gain (Numeric)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
4.40 dBi (2.754)	145.21116 (21.62dBm)	0.08	1	Compiles

Note:

Antenna Gain: 1.39dBi (2.4G Band)

Assembly Antenna Gain: 4.40dBi

Assembly Antenna Gain (Numeric): 2.754dBi

$$\text{ERP} = 21.62 + 4.40 - 2.15 = 23.87 \text{ dBm} (243.7811 \text{ mW})$$

WIFI 2.4G band and 5G band cannot transmit Simultaneously

Calculated Bluetooth Result and Limit (WORSE CASE IS AS BELOW)

$$\text{eirp} = p_t \times g_t = (E \cdot d)^2 / 30$$

where:

p_t = transmitter output power in watts,

g_t = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- $10^{((\text{dBuV/m})/20)/10^6}$

d = measurement distance in meters (m)---3m

$$\text{So } p_t = (E \cdot d)^2 / (30 \times g_t)$$

Ant gain =1.39dBi so Ant numeric gain= 1.377

Field strength =85.73dBμV/m @3m@2480MHz

So Pt=85.73-95.2=-9.47dBm

Antenna Gain (Numeric)	Peak Output Power (mW)	Power Density (S) (mW/cm2)	Limit of Power Density (S) (mW/cm2)	Test Result
1.39 dBi (1.377)	0.113 (-9.47dBm)	0.000031	1	Compiles

Note:

Antenna Gain: 1.39dBi (2.4G Band)

Assembly Antenna Gain (Numeric): 1.377

ERP=-9.47dBm-2.15=-11.62 dBm(0.07mW)

BT BDR/EDR and BLE cannot transmit Simultaneously

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} = 145.21116/3060 + 0.113/3060 = 0.0475$$

$$\sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} = (243.7811 + 0.07) / 3060 = 0.08$$

$$\sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} = (0.08 + 0.000031) / 1 = 0.080031$$

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

$$0.0475 + 0.08 + 0.080031 = 0.21 < 1$$