

# FCC Test Report

Product Name	Remote Control
Model No	KWR174002/01BR, KWR174002/01BRS, KWR174002/01BRU, KWR174003/01BR, KWR174003/01BRS, KWR174003/01BRU
FCC ID.	2AADIKWR17B

Applicant	Home Control Singapore Pte. Ltd.
Address	620A Lorong 1 Toa Payoh Singapore 319762.

Date of Receipt	Aug. 25, 2014
Issue Date	Sep. 30, 2014
Report No.	1480545R-RFUSP01V00
Report Version	V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of Quietek Corporation.

# Test Report

Issue Date: Sep. 30, 2014

Report No.: 1480545R-RFUSP01V00



Product Name	Remote Control
Applicant	Home Control Singapore Pte. Ltd.
Address	620A Lorong 1 Toa Payoh Singapore 319762.
Manufacturer	Wujiang Century Billion Electronic Technology Co., Ltd.
Model No.	KWR174002/01BR, KWR174002/01BRS, KWR174002/01BRU, KWR174003/01BR, KWR174003/01BRS, KWR174003/01BRU
FCC ID.	2AADIKWR17B
EUT Rated Voltage	DC 3V (Powered by 2 pieces of AAA battery in series connection with option 1 pair in parallel connection)
EUT Test Voltage	DC 3V (Powered by 2 pieces of AAA battery in series connection with option 1 pair in parallel connection)
Trade Name	Engel, ATS
Applicable Standard	FCC CFR Title 47 Part 15 Subpart C: 2013 ANSI C63.10: 2009, KDB 558074 D01 DTS Meas Guidance v03r02
Test Result	Complied

Documented By : Jinn Chen  
( Senior Adm. Specialist / Jinn Chen )

Tested By : Nova Chu  
( Assistant Engineer / Nova Chu )

Approved By : Vincent Lin  
( Director / Vincent Lin )

## TABLE OF CONTENTS

Description	Page
<b>1. GENERAL INFORMATION .....</b>	<b>5</b>
1.1. EUT Description.....	5
1.2. Operational Description .....	7
1.3. Tested System Details.....	8
1.4. Configuration of Tested System .....	8
1.5. EUT Exercise Software .....	8
1.6. Test Facility .....	9
<b>2. Conducted Emission.....</b>	<b>10</b>
2.1. Test Equipment.....	10
2.2. Test Setup .....	10
2.3. Limits .....	11
2.4. Test Procedure .....	11
2.5. Uncertainty .....	11
2.6. Test Result of Conducted Emission.....	12
<b>3. Peak Power Output .....</b>	<b>13</b>
3.1. Test Equipment.....	13
3.2. Test Setup .....	13
3.3. Limits .....	13
3.4. Test Procedure .....	13
3.5. Uncertainty .....	13
3.6. Test Result of Peak Power Output.....	14
<b>4. Radiated Emission .....</b>	<b>15</b>
4.1. Test Equipment.....	15
4.2. Test Setup .....	16
4.3. Limits .....	17
4.4. Test Procedure .....	18
4.5. Uncertainty .....	18
4.6. Test Result of Radiated Emission.....	19
<b>5. RF antenna conducted test.....</b>	<b>23</b>
5.1. Test Equipment.....	23
5.2. Test Setup .....	23
5.3. Limits .....	23
5.4. Test Procedure .....	23
5.5. Uncertainty .....	24
5.6. Test Result of RF antenna conducted test.....	25
<b>6. Band Edge .....</b>	<b>26</b>
6.1. Test Equipment.....	26
6.2. Test Setup .....	26
6.3. Limits .....	27
6.4. Test Procedure .....	27
6.5. Uncertainty .....	27
6.6. Test Result of Band Edge .....	28

---

<b>7.</b>	<b>Occupied Bandwidth .....</b>	<b>32</b>
7.1.	Test Equipment.....	32
7.2.	Test Setup .....	32
7.3.	Limits .....	32
7.4.	Test Procedure .....	32
7.5.	Uncertainty .....	32
7.6.	Test Result of Occupied Bandwidth .....	33
<b>8.</b>	<b>Power Density .....</b>	<b>36</b>
8.1.	Test Equipment.....	36
8.2.	Test Setup .....	36
8.3.	Limits .....	36
8.4.	Test Procedure .....	36
8.5.	Uncertainty .....	36
8.6.	Test Result of Power Density .....	37
<b>9.</b>	<b>EMI Reduction Method During Compliance Testing .....</b>	<b>40</b>

Attachment 1: EUT Test Photographs

Attachment 2: EUT Detailed Photographs

## 1. GENERAL INFORMATION

### 1.1. EUT Description

Product Name	Remote Control
Trade Name	Engel, ATS
Model No.	KWR174002/01BR, KWR174002/01BRS, KWR174002/01BRU, KWR174003/01BR, KWR174003/01BRS, KWR174003/01BRU
FCC ID.	2AADIKWR17B
Frequency Range	2425~2475MHz
Channel Separation	5 MHz
Channel Number	3
Type of Modulation	O-QPSK
Antenna Type	Print on PCB
Antenna Gain	Refer to the table "Antenna List"
Channel Control	Auto

#### Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	Wujiang	N/A	Print on PCB	0.13 dBi for 2.4 GHz

Note: The antenna of EUT is conform to FCC 15.203.

## Center Frequency of Each Channel:

Channel Frequency Channel Frequency Channel Frequency

Channel 15: 2425MHz Channel 20: 2450MHz Channel 25: 2475 MHz

## Note:

1. The EUT is a Remote Control with a built-in 2.4GHz ZigBee transceiver.
2. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.
3. These tests are conducted on a sample for the purpose of demonstrating compliance of ZigBee transmitter with Part 15 Subpart C Paragraph 15.247 of spread spectrum devices.
4. The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.
5. The EUT is including six models for different is listed as below:
  - Different cosmetic printing on top part and keymat.
  - Different firmware (key code).
  - The KWR174002 (Engel) support infrared function but the KWR174003 (ATS) does not support it although both of them sharing same hardware.

No.	Model Number	Brand	Description
1	KWR174002/01BR	Engel	Bundled with batteries. Packed with carton box.
2	KWR174002/01BRS	Engel	Bundled with batteries and dongle. Packed with carton box.
3	KWR174002/01BRU	Engel	Bundled with batteries. Without any carton box packaging.
4	KWR174003/01BR	ATS	Bundled with batteries. Packed with carton box.
5	KWR174003/01BRS	ATS	Bundled with batteries and dongle. Packed with carton box.
6	KWR174003/01BRU	ATS	Bundled with batteries. Without any carton box packaging.

Test Mode:	Mode 1: Transmit
------------	------------------


### 1.3. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	Power Cord
N/A				

Signal Cable Type	Signal cable Description
N/A	

### 1.4. Configuration of Tested System



### 1.5. EUT Exercise Software

- (1) Setup the EUT as shown in section 1.4.
- (2) Press and hold the button of EUT.
- (3) Start transmits continually.
- (4) Verify that the EUT works properly.

## 1.6. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

The related certificate for our laboratories about the test site and management system can be downloaded from

Quietek Corporation's Web Site: <http://www.quietek.com/tw/ctg/cts/accreditations.htm>

The address and introduction of Quietek Corporation's laboratories can be founded in our Web site:

<http://www.quietek.com/>

Site Description: File on  
Federal Communications Commission  
FCC Engineering Laboratory  
7435 Oakland Mills Road  
Columbia, MD 21046  
Registration Number: 92195

Site Name: Quietek Corporation  
Site Address: No.5-22, Ruishukeng,  
Linkou Dist. New Taipei City 24451,  
Taiwan, R.O.C.  
TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789  
E-Mail : [service@quietek.com](mailto:service@quietek.com)

FCC Accreditation Number: TW1014

## 2. Conducted Emission


### 2.1. Test Equipment

	Equipment	Manufacturer	Model No. / Serial No.	Last Cal.	Remark
X	Test Receiver	R & S	ESCS 30 / 825442/018	Sep., 2014	
X	Artificial Mains Network	R & S	ENV4200 / 848411/10	Feb., 2014	Peripherals
X	LISN	R & S	ESH3-Z5 / 825562/002	Feb., 2014	EUT
	DC LISN	Schwarzbeck	8226 / 176	Mar, 2014	EUT
X	Pulse Limiter	R & S	ESH3-Z2 / 357.8810.52	Feb., 2014	
	No.1 Shielded Room				

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked by "X" are used to measure the final test results.

### 2.2. Test Setup



### 2.3. Limits

<b>FCC Part 15 Subpart C Paragraph 15.207 (dB<math>\mu</math>V) Limit</b>		
Frequency MHz	Limits	
	QP	AVG
0.15 - 0.50	66-56	56-46
0.50-5.0	56	46
5.0 - 30	60	50

### 2.4. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2009 on conducted measurement.

Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

### 2.5. Uncertainty

± 2.26 dB

## **2.6. Test Result of Conducted Emission**

Owing to the DC operation of EUT, this test item is not performed.

### 3. Peak Power Output


#### 3.1. Test Equipment

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X Power Meter	Anritsu	ML2495A/6K00003357	May, 2014
X Power Sensor	Anritsu	MA2411B/0738448	Jun., 2014

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with “X” are used to measure the final test results.

#### 3.2. Test Setup



#### 3.3. Limits

The maximum peak power shall be less 1 Watt.

#### 3.4. Test Procedure

The EUT was tested according to DTS test procedure of KDB 558074 for compliance to FCC 47CFR 15.247 requirements. The maximum peak conducted output power using KDB 558074 D01 DTS Meas Guidance v03r02 section 9.1.2 PKPM1 Peak power meter method.

#### 3.5. Uncertainty

± 1.27 dB

### 3.6. Test Result of Peak Power Output

Product : Remote Control  
Test Item : Peak Power Output Data  
Test Site : No.3 OATS  
Test Mode : Mode 1: Transmit

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
15	2425	0.45	<30dBm	Pass
20	2450	0.82	<30dBm	Pass
25	2475	1.14	<30dBm	Pass

Note: Peak Power Output Value =Reading value on power meter + cable loss

## 4. Radiated Emission

### 4.1. Test Equipment

The following test equipment are used during the radiated emission test:


Test Site	Equipment		Manufacturer	Model No./Serial No.	Last Cal.
☒ Site # 3	X	Loop Antenna	Teseq	HLA6120 / 26739	Jul., 2014
	X	Bilog Antenna	Schaffner Chase	CBL6112B/2673	Sep., 2014
	X	Horn Antenna	Schwarzbeck	BBHA9120D/D305	Sep., 2014
	X	Horn Antenna	Schwarzbeck	BBHA9170/208	Jul., 2014
	X	Pre-Amplifier	Agilent	8447D/2944A09549	Sep., 2014
	X	Spectrum Analyzer	Agilent	E4407B / US39440758	May, 2014
	X	Test Receiver	R & S	ESCS 30/ 825442/018	Sep., 2014
	X	Coaxial Cable	QuieTek	QTK-CABLE/ CAB5	Feb., 2014
	X	Controller	QuieTek	QTK-CONTROLLER/ CTRL3	N/A
	X	Coaxial Switch	Anritsu	MP59B/6200265729	N/A

Note: 1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.


2. The test instruments marked with “X” are used to measure the final test results.

## 4.2. Test Setup

### Radiated Emission Below 1GHz



### Radiated Emission Above 1GHz



#### 4.3. Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

<b>FCC Part 15 Subpart C Paragraph 15.209(a) Limits</b>		
Frequency MHz	Field strength (microvolts/meter)	Measurement distance (meter)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remarks: E field strength (dB $\mu$ V/m) = 20 log E field strength (uV/m)

#### **4.4. Test Procedure**

The EUT was setup according to ANSI C63.10: 2009 and tested according to DTS test procedure of KDB558074 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned between 1 meter and 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10: 2009 on radiated measurement.

The resolution bandwidth below 30MHz setting on the field strength meter is 9kHz and 30MHz~1GHz is 120kHz and above 1GHz is 1MHz.

Radiated emission measurements below 30MHz are made using Loop Antenna and 30MHz~1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas.

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB bandwidth of the antenna.

The worst radiated emission is measured in the Open Area Test Site on the Final Measurement.

The frequency range from 9kHz to 10th harmonics is checked.

#### **4.5. Uncertainty**

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

#### 4.6. Test Result of Radiated Emission

Product : Remote Control  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2425MHz)

Frequency MHz	Correct Factor dB	Reading Level dB $\mu$ V	Measurement Level dB $\mu$ V/m	Margin dB	Limit dB $\mu$ V/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4850.000	2.239	47.575	49.814	-24.186	74.000
7275.000	9.154	48.945	58.099	-15.901	74.000
9700.000	9.586	36.385	45.971	-28.029	74.000
<b>Average Detector:</b>					
7275.000	9.154	42.035	51.189	-2.811	54.000
<b>Vertical</b>					
<b>Peak Detector:</b>					
4850.000	2.671	46.631	49.302	-24.698	74.000
7275.000	9.154	44.024	53.178	-20.822	74.000
9700.000	9.586	36.030	45.616	-28.384	74.000

#### Average Detector:

--

#### Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Remote Control  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2450 MHz)

Frequency MHz	Correct Factor dB	Reading Level dB $\mu$ V	Measurement Level dB $\mu$ V/m	Margin dB	Limit dB $\mu$ V/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4900.000	1.984	46.151	48.135	-25.865	74.000
7350.000	10.934	48.282	59.216	-14.784	74.000
9800.000	9.822	36.054	45.876	-28.124	74.000
<b>Average Detector:</b>					
7350.000	10.238	40.529	50.767	-3.233	54.000
<b>Vertical</b>					
<b>Peak Detector:</b>					
4900.000	2.482	44.817	47.299	-26.701	74.000
7350.000	10.238	42.272	52.510	-21.490	74.000
9800.000	9.822	36.775	46.597	-27.403	74.000

**Average Detector:**

--

**Note:**

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Remote Control  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2475 MHz)

Frequency MHz	Correct Factor dB	Reading Level dB $\mu$ V	Measurement Level dB $\mu$ V/m	Margin dB	Limit dB $\mu$ V/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4950.000	2.483	43.529	46.012	-27.988	74.000
7425.000	10.496	43.794	54.290	-19.710	74.000
9900.000	10.163	37.061	47.223	-26.777	74.000
<b>Average Detector:</b>					
7425.000	10.496	36.446	46.942	-7.058	54.000
<b>Vertical</b>					
<b>Peak Detector:</b>					
4950.000	3.243	41.467	44.710	-29.290	74.000
7425.000	11.225	38.708	49.934	-24.066	74.000
9900.000	11.202	37.367	48.568	-25.432	74.000

**Average Detector:**

--

**Note:**

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Remote Control  
 Test Item : General Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2450 MHz)

Frequency	Correct Factor	Reading Level	Measurement Level	Margin	Limit
MHz	dB	dB $\mu$ V	dB $\mu$ V/m	dB	dB $\mu$ V/m
<b>Horizontal</b>					
40.670	-4.780	38.116	33.336	-6.664	40.000
82.380	-13.063	43.105	30.042	-9.958	40.000
191.990	-9.887	36.704	26.817	-16.683	43.500
458.740	3.298	24.742	28.040	-17.960	46.000
610.060	3.657	23.947	27.604	-18.396	46.000
845.770	6.523	23.741	30.264	-15.736	46.000
<b>Vertical</b>					
53.280	-11.767	46.351	34.584	-5.416	40.000
87.230	-4.069	36.651	32.582	-7.418	40.000
384.050	-0.122	24.675	24.553	-21.447	46.000
614.910	1.701	27.936	29.637	-16.363	46.000
780.780	2.769	25.872	28.641	-17.359	46.000
948.590	3.198	24.196	27.395	-18.605	46.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.
8. No emission found between lowest internal used/generated frequency to 30MHz.

## 5. RF antenna conducted test


### 5.1. Test Equipment

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2014
Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2014
X Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2014

Note: 1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.  
2. The test instruments marked with "X" are used to measure the final test results.

### 5.2. Test Setup

#### RF antenna Conducted Measurement:



### 5.3. Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

### 5.4. Test Procedure

The EUT was tested according to DTS test procedure of KDB558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 100 kHz, Set VBW > RBW, scan up through 10th harmonic.


## 5.5. Uncertainty

The measurement uncertainty  
Conducted is defined as  $\pm 1.27\text{dB}$


## 5.6. Test Result of RF antenna conducted test

Product : Remote Control  
Test Item : RF antenna conducted test  
Test Site : No.3 OATS  
Test Mode : Mode 1: Transmit


**Channel 15 (2425MHz)**



**Channel 20 (2450MHz)**



**Channel 25 (2475MHz)**



Note: The above test pattern is synthesized by multiple of the frequency range.

## 6. Band Edge

### 6.1. Test Equipment

#### RF Radiated Measurement:

The following test equipments are used during the band edge tests:


Test Site	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Site # 3	Bilog Antenna	Schaffner Chase	CBL6112B/2673	Sep., 2014
	X Horn Antenna	Schwarzbeck	BBHA9120D/D305	Sep., 2014
	Horn Antenna	Schwarzbeck	BBHA9170/208	Jul., 2014
	X Pre-Amplifier	Agilent	8447D/2944A09549	Sep., 2014
	X Spectrum Analyzer	Agilent	E4407B / US39440758	May, 2014
	Test Receiver	R & S	ESCS 30/ 825442/018	Sep., 2014
	X Coaxial Cable	Quietek	QTK-CABLE/ CAB5	Feb., 2014
	X Controller	Quietek	QTK-CONTROLLER/ CTRL3	N/A
	X Coaxial Switch	Anritsu	MP59B/6200265729	N/A

Note:

1. All instruments are calibrated every one year.
2. The test instruments marked by "X" are used to measure the final test results.

### 6.2. Test Setup

#### RF Radiated Measurement:



### **6.3. Limits**

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

### **6.4. Test Procedure**

The EUT was setup according to ANSI C63.10: 2009 and tested according to DTS test procedure of KDB558074 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10: 2009 on radiated measurement.

### **6.5. Uncertainty**

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

## 6.6. Test Result of Band Edge

Product : Remote Control  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit

### RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
15 (Peak)	2362.200	31.400	25.866	57.266	74.00	54.00	Pass
15 (Peak)	2390.000	31.509	23.634	55.143	74.00	54.00	Pass
15 (Peak)	2400.000	31.561	23.195	54.756	74.00	54.00	Pass
15 (Peak)	2425.400	31.741	64.403	96.144	--	--	Pass
15 (Average)	2363.400	31.405	14.873	46.277	74.00	54.00	Pass
15 (Average)	2390.000	31.509	14.486	45.995	74.00	54.00	Pass
15 (Average)	2400.000	31.561	14.162	45.723	74.00	54.00	Pass
15 (Average)	2425.200	31.740	62.140	93.879	--	--	Pass

Figure Channel 15:

Horizontal (Peak)





Figure Channel 15:

Horizontal (Average)





Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “\*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : Remote Control  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit

**RF Radiated Measurement (Vertical):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
15 (Peak)	2370.400	31.006	25.605	56.611	74.00	54.00	Pass
15 (Peak)	2390.000	30.915	24.437	55.352	74.00	54.00	Pass
15 (Peak)	2400.000	30.912	25.943	56.855	74.00	54.00	Pass
15 (Peak)	2424.400	31.034	59.826	90.859	--	--	Pass
15 (Average)	2381.800	30.953	14.303	45.256	74.00	54.00	Pass
15 (Average)	2390.000	30.915	13.996	44.911	74.00	54.00	Pass
15 (Average)	2400.000	30.912	14.289	45.201	74.00	54.00	Pass
15 (Average)	2425.200	31.039	59.072	90.111	--	--	Pass

**Figure Channel15:**
**Vertical (Peak)**

**Figure Channel15:**
**Vertical (Average)**


Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “\*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : Remote Control  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit

#### RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
25 (Peak)	2474.300	32.113	66.203	98.315	--	--	Pass
25 (Peak)	2483.500	32.182	24.458	56.640	74.00	54.00	Pass
25 (Peak)	2496.300	32.276	25.533	57.809	74.00	54.00	Pass
25 (Average)	2474.900	32.117	64.388	96.505	--	--	Pass
25 (Average)	2483.500	32.182	15.848	48.030	74.00	54.00	Pass

Figure Channel 25:

Horizontal (Peak)





Figure Channel 25:

Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “\*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.


Product : Remote Control  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit

**RF Radiated Measurement (Vertical):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
25 (Peak)	2474.300	31.373	60.741	92.114	--	--	Pass
25 (Peak)	2483.500	31.435	23.999	55.434	74.00	54.00	Pass
25 (Peak)	2489.700	31.477	24.832	56.309	74.00	54.00	Pass
25 (Average)	2474.900	31.378	59.309	90.686	--	--	Pass
25 (Average)	2483.500	31.435	14.143	45.578	74.00	54.00	Pass
25 (Average)	2488.900	31.472	14.354	45.826	74.00	54.00	Pass


**Figure Channel 25:**

**Vertical (Peak)**



**Figure Channel 25:**

**Vertical (Average)**



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “\*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

## 7. Occupied Bandwidth


### 7.1. Test Equipment

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2014
Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2014
X Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2014

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with “X” are used to measure the final test results.

### 7.2. Test Setup



### 7.3. Limits

The minimum bandwidth shall be at least 500 kHz.

### 7.4. Test Procedure

The EUT was setup according to ANSI C63.10: 2009; tested according to DTS test procedure of KDB558074 for compliance to FCC 47CFR 15.247 requirements.

### 7.5. Uncertainty


± 150Hz

## 7.6. Test Result of Occupied Bandwidth

Product : Remote Control  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2425MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
15	2425	1490	>500	Pass


**Figure Channel 15:**



Product : Remote Control  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2450MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
20	2450	1680	>500	Pass

Figure Channel 20:



Product : Remote Control  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2475MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
25	2475	1540	>500	Pass

Figure Channel 25:



## 8. Power Density


### 8.1. Test Equipment

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2014
Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2014
X Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2014

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with “X” are used to measure the final test results.

### 8.2. Test Setup



### 8.3. Limits

The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3kHz bandwidth.

### 8.4. Test Procedure

The EUT was setup according to ANSI C63.10, 2009; tested according to DTS test procedure of KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

The maximum power spectral density using KDB 558074 section 10.2 PKPSD (peak PSD) method.

### 8.5. Uncertainty


± 1.27 dB

## 8.6. Test Result of Power Density

Product : Remote Control  
 Test Item : Power Density Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2425MHz)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
15	2425	-1.057	< 8dBm	Pass


**Figure Channel 15:**



Product : Remote Control  
 Test Item : Power Density Data  
 Test Site : No.3OATS  
 Test Mode : Mode 1: Transmit (2450MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
20	2450	-0.559	< 8dBm	Pass


**Figure Channel 20:**



Product : Remote Control  
 Test Item : Power Density Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2475MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
25	2475	-0.323	< 8dBm	Pass

**Figure Channel 25:**



**9. EMI Reduction Method During Compliance Testing**

No modification was made during testing.