#### FCC 47 CFR PART 15 SUBPART C

Report No.: T130802W02-RP1

### **TEST REPORT**

For

Remote controller + dongle

MODEL / Serial Number: KWR800003/01BS / 3139 228 12501

**Trade Name: Google** 

Issued to

Home Control Singapore Pte Ltd 620A Lorong 1 Toa Payoh Singapore 319762.

Issued by

Compliance Certification Services Inc.
No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City 24891, Taiwan. (R.O.C.)
http://www.ccsrf.com
service@ccsrf.com
Issued Date: August 28, 2013





Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.

Page 1 / 32 Rev.00

# **Revision History**

Report No.: T130802W02-RP1

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	August 28, 2013	Initial Issue	ALL	Kelly Cheng

Page 2 Rev.00

# TABLE OF CONTENTS

1. TI	EST RESULT CERTIFICATION	4
2. E	UT DESCRIPTION	5
3. Tl	EST METHODOLOGY	6
3.1	EUT CONFIGURATION	6
3.2	EUT EXERCISE	
3.3	GENERAL TEST PROCEDURES	6
3.4	FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS	7
3.5	DESCRIPTION OF TEST MODES	8
4. IN	NSTRUMENT CALIBRATION	9
4.1	MEASURING INSTRUMENT CALIBRATION	9
4.2	MEASUREMENT EQUIPMENT USED	
4.3	MEASUREMENT UNCERTAINTY	10
5. F	ACILITIES AND ACCREDITATIONS	11
5.1	FACILITIES	11
5.2	EQUIPMENT	11
5.3	TABLE OF ACCREDITATIONS AND LISTINGS	12
6. SI	ETUP OF EQUIPMENT UNDER TEST	13
6.1	SETUP CONFIGURATION OF EUT	13
6.2	SUPPORT EQUIPMENT	
7. F0	CC PART 15.249 REQUIREMENTS	14
7.1	20 DB BANDWIDTH	14
7.2	BAND EDGES MEASUREMENT	
7.3	SPURIOUS EMISSION	23
7.4	POWERLINE CONDUCTED EMISSIONS	
APPE	NDIX I PHOTOGRAPHS OF TEST SETUP	32
APPE	NDIX 1 - PHOTOGRAPHS OF EUT	

### 1. TEST RESULT CERTIFICATION

**Applicant:** Home Control Singapore Pte Ltd

620A Lorong 1 Toa Payoh Singapore 319762.

**Equipment Under Test:** Remote controller + dongle

**Trade Name:** Google

**Model / Serial Number:** KWR800003/01BS / 3139 228 12501

**Date of Test:** August 15 ~ 22, 2013

APPLICABLE STANDARDS				
STANDARD	TEST RESULT			
FCC 47 CFR Part 15 Subpart C	No non-compliance noted			

## We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in **ANSI C63.4: 2009** and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements emission limits of FCC Rules Part 15.207, 15.209 and 15.249.

The test results of this report relate only to the tested sample identified in this report.

Approved by:

Reviewed by:

Miller Lee

Section Manager

Compliance Certification Services Inc.

Willer Los

Angel Cheng Section Manager

Compliance Certification Services Inc.

Angel Chent

Report No.: T130802W02-RP1

Page 4 Rev.00

# 2. EUT DESCRIPTION

Product	Remote controller + dongle			
Trade Name	Google			
Model / Serial Number	KWR800003/01BS / 3	3139 228 12:	501	
<b>Model Discrepancy</b>	N/A			
Received Date	August 6, 2013			
Power Supply	Remote controller: Battery: LITHIUM(DC 3V)			
		Channel	Frequency (MHz)	
1				
Fraguency Dange		5	2405	
Frequency Range		25	2425	
Frequency Range		25 42	2425 2442	
Frequency Range		25 42 63	2425 2442 2463	
Frequency Range		25 42	2425 2442	
Frequency Range  Modulation Technique	GFSK	25 42 63	2425 2442 2463	
	GFSK 0.88dBi	25 42 63	2425 2442 2463	

### Remark:

- 1. The sample selected for test was production product and was provided by manufacturer.
- 2. This submittal(s) (test report) is intended for FCC ID: <u>2AADIOVU81H7</u> filing to comply with Section 15.107, 15.109, 15.207, 15.209, 15.249 (FCC Part 15, Subpart C Rules.)

Page 5 Rev.00

## 3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4: 2009 and FCC CFR 47 Part 15.207, 15.209, 15.247 and DA00-705.

Report No.: T130802W02-RP1

### 3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

#### 3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209,15.249 under the FCC Rules Part 15 Subpart C.

#### 3.3 GENERAL TEST PROCEDURES

#### **Conducted Emissions**

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4: 2009 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

#### **Radiated Emissions**

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4: 2009.

Page 6 Rev.00

## 3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

Report No.: T130802W02-RP1

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	$\binom{2}{}$
13.36 - 13.41	322 - 335.4		

<sup>&</sup>lt;sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

Page 7 Rev.00

<sup>&</sup>lt;sup>2</sup> Above 38.6

<sup>(</sup>b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

### 3.5 DESCRIPTION OF TEST MODES

The EUT (model: KWR800003/01BU) had been tested under operating condition.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only.

Report No.: T130802W02-RP1

Channel Low(2405MHz), Channel Mid(2442MHz) and Channel High(2477MHz) were chosen for the final testing.

The field strength of spurious emission was measured in the following position: EUT stand-up position (Z mode), lie-down position (X, Y mode). The worst emission was found in lie-down position (Y axis) and the worst case was recorded.

Page 8 Rev.00

# 4. INSTRUMENT CALIBRATION

### 4.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

Report No.: T130802W02-RP1

# 4.2 MEASUREMENT EQUIPMENT USED

### **Equipment Used for Emissions Measurement**

**Remark:** Each piece of equipment is scheduled for calibration once a year and Loop Antenna is scheduled for calibration once three years.

Conducted Emissions Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due	
Spectrum Analyzer	Agilent	E4446A	MY43360131	03/20/2014	

	3M Chamber Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due		
Spectrum Analyzer	Agilent	E4446A	US42510268	11/06/2013		
EMI Test Receiver	R&S	ESCI	100064	02/28/2014		
Pre-Amplifier	Mini-Circults	ZFL-1000LN	SF350700823	01/12/2014		
Pre-Amplifier	MITEQ	AFS44-00102650- 42-10P-44	1415367	11/19/2013		
Bilog Antenna	Sunol Sciences	JB3	A030105	10/02/2013		
Horn Antenna	EMCO	3117	00055165	02/13/2014		
Horn Antenna	EMCO	3116	2487	10/10/2013		
Loop Antenna	EMCO	6502	8905/2356	06/09/2014		
Turn Table	CCS	CC-T-1F	N/A	N.C.R		
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R		
Controller	CCS	CC-C-1F	N/A	N.C.R		
Site NSA	CCS	N/A	N/A	12/22/2013		
Test S/W	Test S/W EZ-EMC (CCS-3A1RE)					

Page 9 Rev.00

# 4.3 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
3M Semi Anechoic Chamber / <200M	+/- 4.0138
3M Semi Anechoic Chamber / 200M~1000M	+/- 3.9483
3M Semi Anechoic Chamber / 1G~8G	+/- 2.5975
3M Semi Anechoic Chamber / 8G~18G	+/- 2.6112
3M Semi Anechoic Chamber / 18G~26G	+/- 2.7389
3M Semi Anechoic Chamber / 26G~40G	+/- 2.9683

**Remark**: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Page 10 Rev.00

### 5. FACILITIES AND ACCREDITATIONS

### **5.1 FACILITIES**

All measurement facilities used to collect the measurement data are located at
No.199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.
Tel: 886-2-2217-0894 / Fax: 886-2-2217-1029
No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.) Tel: 886-2-2299-9720 / Fax: 886-2-2298-4045
<ul> <li>No.81-1, Lane 210, Bade 2nd Rd., Lujhu Township, Taoyuan County 33841, TAIWAN, R.O.C.</li> <li>Tel: 886-3-324-0332 / Fax: 886-3-324-5235</li> </ul>
The sites are constructed in conformance with the requirements of ANSI C62.7. ANSI C62.4 or

Report No.: T130802W02-RP1

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

## 5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

Page 11 Rev.00

# 5.3 TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
III \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		3M Semi Anechoic Chamber (FCC MRA: TW1039) to perform FCC Part 15 measurements	FCC MRA: TW1039
Taiwan	TAF	LP0002, RTTE01, FCC Method-47 CFR Part 15 Subpart C, D, E, RSS-210, RSS-310  IDA TS SRD, AS/NZS 4268, AS/NZS 4771, TS 12.1 & 12,2, ETSI EN 300 440-1, ETSI EN 300 440-2, ETSI EN 300 328, ETSI EN 300 220-1, ETSI EN 300 220-2, ETSI EN 301 893, ETSI EN 301 489-1/3/7/17  FCC OET Bulletin 65 + Supplement C, EN 50360, EN 50361, EN 50371, RSS 102, EN 50383, EN 50385, EN 50392, IEC 62209, CNS 14958-1, CNS 14959  FCC Method -47 CFR Part 15 Subpart B  IEC / EN 61000-3-2, IEC / EN 61000-3-3, IEC / EN 61000-4-2/3/4/5/6/8/11	Testing Laboratory 1309
Canada Industry Canada 3M Sem		3M Semi Anechoic Chamber (IC 2324G-1 / IC 2324G-2) to perform	Canada IC 2324G-1 IC 2324G-2

Report No.: T130802W02-RP1

Page 12 Rev.00

<sup>\*</sup> No part of this report may be used to claim or imply product endorsement by A2LA or any agency of the US Government.

# 6. SETUP OF EQUIPMENT UNDER TEST

# **6.1 SETUP CONFIGURATION OF EUT**

See test photographs attached in Appendix I for the actual connections between EUT and support equipment.

Report No.: T130802W02-RP1

# **6.2 SUPPORT EQUIPMENT**

No	Equipment	Model	Serial No.	FCC ID	Trade Name	Data Cable	Power Cord
	N/A						

#### Remark:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

Page 13 Rev.00


# 7. FCC PART 15.249 REQUIREMENTS

## 7.1 20 DB BANDWIDTH

### **LIMIT**

None; for reporting purposes only.

#### **Test Configuration**



## **TEST PROCEDURE**

- 1. Place the EUT on the table and set it in the transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as RBW=100kHz, VBW = 100kHz, Span = 10MHz, Sweep = auto.
- 4. Mark the peak frequency and 20dB (upper and lower) frequency.
- 5. Repeat until all the rest channels are investigated.

### **TEST RESULTS**

No non-compliance noted


### **Test Data**

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
Low 2405		1.95
Mid	2442	1.95
High	2447	1.95


Page 14 Rev.00

### **Test Plot**

#### **CH Low**




#### **CH Mid**



Page 15 Rev.00

CH High



Page 16 Rev.00



### 7.2 BAND EDGES MEASUREMENT


#### LIMIT

1. In the above emission table, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (μV/m at 3-meter)	Field Strength (dBµV/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

2. As shown in Section 15.35(b), for frequencies above 1000 MHz, the above field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.

### **Test Configuration**



Page 17 Rev.00

## **TEST PROCEDURE**

- 1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.

Report No.: T130802W02-RP1

- 4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
  - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
  - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
- 5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

### **TEST RESULTS**


Refer to attach spectrum analyzer data chart.

Page 18 Rev.00


Report No.: T130802W02-RP1

### **Band Edges (CH Low)**

#### **Detector mode: Peak Polarity: Vertical**




**Polarity: Vertical Detector mode: Average** 




Page 19 Rev.00



#### **Detector mode: Peak Polarity: Horizontal**




#### **Detector mode: Average Polarity: Horizontal**




Page 20 Rev.00 Report No.: T130802W02-RP1

### **Band Edges (CH High)**

#### **Detector mode: Peak Polarity: Vertical**




**Polarity: Vertical Detector mode: Average** 




Page 21 Rev.00



#### **Detector mode: Peak Polarity: Horizontal**



#### **Detector mode: Average Polarity: Horizontal**



Page 22 Rev.00

## 7.3 SPURIOUS EMISSION

### **LIMIT**

1. In the section 15.249(a):

Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Report No.: T130802W02-RP1

Fundamental Frequency (MHz)	Field Strength of Fundamental Field Strength (mV/m)	Field Strength of Harmonics (μV/m)
902-928 MHz	50	500
2400 - 2483.5 MHz	50	500
5725 - 5875 MHz	50	500
24.0 - 24.25 GHz	250	2500

2. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

**Remark:** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.


3. In the above emission table, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (μV/m at 3-meter)	Field Strength (dBμV/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54


Page 23 Rev.00

### **Test Configuration**

### $9kHz \sim 30MHz$




### 30MHz~1GHz



Page 24 Rev.00

## **Above 1 GHz**



Page 25 Rev.00

## **TEST PROCEDURE**

- 1. The EUT is placed on a turntable, which is 0.8m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.

Report No.: T130802W02-RP1

- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Set the spectrum analyzer in the following setting as:

Below 1GHz:

RBW=100kHz / VBW=300kHz / Sweep=AUTO

Above 1GHz:

- (a) PEAK: RBW=1MHz / VBW=3MHz / Sweep=AUTO
- (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
- 7. Repeat above procedures until the measurements for all frequencies are complete.

Page 26 Rev.00

### **Below 1 GHz**

**Operation Mode:** Normal Link **Test Date:** August 22, 2013

Report No.: T130802W02-RP1

**Temperature:** 27°C **Tested by:** Rex Huang

Humidity: 53% RH Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit 3m (dBuV/m)	Margin (dB)	Detector Mode (PK/QP)	Ant.Pol. (H/V)
31.6167	44.21	-21.64	22.57	40.00	-17.43	Peak	V
128.6167	44.36	-28.41	15.95	43.50	-27.55	Peak	V
191.6667	46.17	-29.37	16.80	43.50	-26.70	Peak	V
299.9833	44.47	-27.73	16.74	46.00	-29.26	Peak	V
448.7167	45.33	-24.24	21.09	46.00	-24.91	Peak	V
631.4000	41.02	-21.37	19.65	46.00	-26.35	Peak	V
31.6167	43.37	-21.64	21.73	40.00	-18.27	peak	Н
128.6167	42.73	-28.41	14.32	43.50	-29.18	peak	Н
191.6667	44.04	-29.37	14.67	43.50	-28.83	peak	Н
303.2167	46.91	-27.65	19.26	46.00	-26.74	peak	Н
319.3833	47.04	-27.28	19.76	46.00	-26.24	peak	Н
631.4000	41.76	-21.37	20.39	46.00	-25.61	peak	Н

### Remark:

- 1. No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz).
- 2. Radiated emissions measured were made with an instrument using peak/quasi-peak detector mode.
- 3. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit or as required by the applicant.
- 4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 5. Margin(dB) = Remark result(dBuV/m) Quasi-peak limit(dBuV/m).

Page 27 Rev.00

### **Above 1 GHz**

**Operation Mode:** Tx / CH Low **Test Date:** August 22, 2013

Report No.: T130802W02-RP1

**Temperature:** 27°C **Tested by:** Rex Huang

**Humidity:** 53% RH **Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
2405	94.73	0.00	94.73	114.00	-19.27	peak	V
2405	90.35	0.00	90.35	94.00	-3.65	AVG	V
2260.000	51.75	-0.33	51.42	74.00	-22.58	peak	V
4808.333	50.77	5.39	56.16	74.00	-17.84	peak	V
4808.333	45.55	5.39	50.94	54.00	-3.06	AVG	V
N/A							
2405	96.77	0.00	96.77	114.00	-17.23	peak	Н
2405	91.75	0.00	91.75	94.00	-2.25	AVG	Н
2246.667	51.74	-0.37	51.37	74.00	-22.63	peak	Н
N/A							

#### Remark:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6.  $Margin(dB) = Remark\ result\ (dBuV/m) Average\ limit\ (dBuV/m)$ . Peak detector mode and average detector mode of the emission shown in Result column.

Page 28 Rev.00

**Operation Mode:** Tx / CH Mid **Test Date:** August 22, 2013

Report No.: T130802W02-RP1

**Temperature:** 27°C **Tested by:** Rex Huang

**Humidity:** 53% RH **Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
2442	95.46	0.27	95.73	114.00	-18.27	peak	V
2442	91.06	0.27	91.33	94.00	-2.67	AVG	V
2236.667	51.59	-0.41	51.18	74.00	-22.82	peak	V
4883.333	49.31	5.49	54.80	74.00	-19.20	peak	V
4883.333	46.16	5.49	51.65	54.00	-2.35	AVG	V
N/A							
2442	95.98	0.27	96.25	114.00	-17.75	peak	Н
2442	91.69	0.27	91.96	94.00	-2.04	AVG	Н
2210.000	51.67	-0.49	51.18	74.00	-22.82	peak	Н
N/A							

#### Remark:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6.  $Margin(dB) = Remark\ result\ (dBuV/m) Average\ limit\ (dBuV/m)$ . Peak detector mode and average detector mode of the emission shown in Result column.

Page 29 Rev.00

**Operation Mode:** Tx / CH High **Test Date:** August 22, 2013

Report No.: T130802W02-RP1

**Temperature:** 27°C **Tested by:** Rex Huang

**Humidity:** 53% RH **Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
2477	95.63	0.51	96.14	114.00	-17.86	peak	V
2477	91.08	0.51	91.59	94.00	-2.41	AVG	V
2306.667	51.93	-0.19	51.74	74.00	-22.26	peak	V
4950.000	51.34	5.58	56.92	74.00	-17.08	peak	V
4950.000	46.40	5.58	51.98	54.00	-2.02	AVG	V
N/A							
2477	97.10	0.51	97.61	114.00	-16.39	peak	Н
2477	92.61	0.51	93.12	94.00	-0.88	AVG	Н
2193.333	52.27	-0.55	51.72	74.00	-22.28	peak	Н
4958.333	42.67	5.59	48.26	74.00	-25.74	peak	Н
N/A							

#### Remark:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6.  $Margin(dB) = Remark\ result\ (dBuV/m) Average\ limit\ (dBuV/m)$ . Peak detector mode and average detector mode of the emission shown in Result column.

Page 30 Rev.00

#### 7.4 POWERLINE CONDUCTED EMISSIONS

### **LIMIT**

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Report No.: T130802W02-RP1

Frequency Range (MHz)	Limits (dBμV)				
(MITZ)	Quasi-peak	Average			
0.15 to 0.50	66 to 56*	56 to 46*			
0.50 to 5	56	46			
5 to 30	60	50			

<sup>\*</sup> Decreases with the logarithm of the frequency.

#### **Test Configuration**

See test photographs attached in Appendix I for the actual connections between EUT and support equipment.

#### TEST PROCEDURE

- 1. The EUT was placed on a table, which is 0.8m above ground plane.
- 2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 3. Repeat above procedures until all frequency measured were complete.

### **TEST RESULTS**

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

#### **Test Data**

Not applicable, because EUT not connect to AC Main Source direct.

Page 31 Rev.00