

FCC SAR EVALUATION REPORT

**In accordance with the requirements of
FCC 47 CFR Part 2(2.1093), ANSI/IEEE C95.1-1992 and
IEEE Std 1528-2013**

Product Name : Mobile Phone

Trademark : CellAllure

Model Name : Earn2 CL

Family Model : N/A

Report No. : STR191009001001E

FCC ID : 2AAE9CAPHG58

Prepared for

GNJ Manufacturing Inc.

5811 West Hallandale Beach Blvd. West Park, FL 33023 Hallandale, FL 33023,
United States

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an District,
Shenzhen, Guangdong, China

Tel.: +86-755-6115 6588 Fax.: +86-755-6115 6599

Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION**Applicant's name**: GNJ Manufacturing Inc.Address.....: 5811 West Hallandale Beach Blvd. West Park, FL 33023 Hallandale,
FL 33023, United States**Manufacturer's Name**.....: GNJ Manufacturing Inc. ChinaAddress.....: 4/F, Building A, No.45 Industrial Park, ZhongKai HiTech Zone,
HuiZhou City, GuangDong Province. 516006, China**Product description**

Product name.....: Mobile Phone

Trademark: CellAllure

Model Name: Earn2 CL

Family Model.....: N/A

FCC 47 CFR Part 2(2.1093)

ANSI/IEEE C95.1-1992

Standards: IEEE Std 1528-2013

Published RF exposure KDB procedures


This device described above has been tested by Shenzhen NTEK. In accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 and KDB 865664 D01. Testing has shown that this device is capable of compliance with localized specific absorption rate (SAR) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992. The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK, this document may be altered or revised by Shenzhen NTEK, personal only, and shall be noted in the revision of the document.


Date of Test

Date (s) of performance of tests: Oct. 14, 2019 ~ Nov. 11, 2019

Date of Issue: Nov. 13, 2019

Test Result.....: **Pass**Prepared By
(Test Engineer): 

(Cheng Jiawen)

Approved By
(Lab Manager): 

(Sam Chen)

※ ※ Revision History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	Nov. 13, 2019	Cheng Jiawen

TABLE OF CONTENTS

1. General Information	6
1.1. RF exposure limits	6
1.2. Statement of Compliance.....	7
1.3. EUT Description	7
1.4. Test specification(s)	10
1.5. Ambient Condition	10
2. SAR Measurement System	11
2.1. SATIMO SAR Measurement Set-up Diagram	11
2.2. Robot	12
2.3. E-Field Probe	13
2.3.1. E-Field Probe Calibration.....	13
2.4. SAM phantoms	14
2.4.1. Technical Data	15
2.5. Device Holder	16
2.6. Test Equipment List	17
3. SAR Measurement Procedures	19
3.1. Power Reference.....	19
3.2. Area scan & Zoom scan	19
3.3. Description of interpolation/extrapolation scheme	21
3.4. Volumetric Scan	21
3.5. Power Drift	21
4. System Verification Procedure.....	22
4.1. Tissue Verification.....	22
4.1.1. Tissue Dielectric Parameter Check Results	23
4.2. System Verification Procedure	24
4.2.1. System Verification Results	25
5. SAR Measurement variability and uncertainty	26
5.1. SAR measurement variability	26
5.2. SAR measurement uncertainty.....	26
6. RF Exposure Positions	27
6.1. Ear and handset reference point.....	27
6.2. Definition of the cheek position	27
6.3. Definition of the tilt position.....	29
6.4. Body Worn Accessory	29
6.5. Wireless Router Devices.....	30
7. RF Output Power	31
7.1. GSM Conducted Power	31
7.2. WCDMA Conducted Power.....	31
7.3. LTE Conducted Power.....	33

7.4. WLAN & Bluetooth Output Power	45
7.4.1. Output Power Results Of WLAN	45
7.4.2. Output Power Results Of Bluetooth	45
8. Antenna Location.....	46
9. Stand-alone SAR test exclusion	47
10. SAR Results	48
10.1. SAR measurement results	48
10.1.1. SAR measurement Result of GSM850.....	48
10.1.2. SAR measurement Result of GSM1900.....	49
10.1.3. SAR measurement Result of WCDMA Band 2.....	50
10.1.4. SAR measurement Result of WCDMA Band 4.....	50
10.1.5. SAR measurement Result of WCDMA Band 5.....	51
10.1.6. SAR measurement Result of LTE Band 2	52
10.1.7. SAR measurement Result of LTE Band 4	54
10.1.8. SAR measurement Result of LTE Band 5	57
10.1.9. SAR measurement Result of LTE Band 7	58
10.1.10. SAR measurement Result of LTE Band 12	60
10.1.11. SAR measurement Result of LTE Band 17	62
10.1.12. SAR measurement Result of WLAN 2.4G.....	64
10.2. SAR Summation Scenario	65
11. Appendix A. Photo documentation.....	74
12. Appendix B. System Check Plots	74
13. Appendix C. Plots of High SAR Measurement	99
14. Appendix D. Calibration Certificate.....	148

1. General Information

1.1. RF exposure limits

(A).Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B).Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

NOTE
 HEAD AND TRUNK LIMIT
 1.6 W/kg
 APPLIED TO THIS EUT

1.2. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for Earn2 CL are as follows.

Band	Max Reported SAR Value(W/kg)			
	1-g Head	1-g Body-Worn (Separation distance of 10mm)	1-g Hotspot (Separation distance of 10mm)	Max Simultaneous Tx
GSM 850	0.702	1.094	1.094	1.371
GSM 1900	0.093	0.383	0.383	
WCDMA Band 2	0.070	0.701	0.701	
WCDMA Band 4	0.122	1.128	1.128	
WCDMA Band 5	0.614	0.782	0.782	
LTE Band 2	0.079	1.197	1.197	
LTE Band 4	0.084	1.197	1.197	
LTE Band 5	0.713	0.796	0.796	
LTE Band 7	0.414	0.184	0.184	
LTE Band 12	0.371	0.644	0.644	
LTE Band 17	0.343	0.457	0.457	
WLAN 2.4G	0.169	0.174	0.174	

Note: The Max Simultaneous Tx is calculated based on the same configuration and test position. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 & KDB 865664 D01.

1.3. EUT Description

Device Information	
Product Name	Mobile Phone
Trade Name	CellAllure
Model Name	Earn2 CL
Family Model	N/A
FCC ID	2AAE9CAPHG58
Device Phase	Identical Prototype
Exposure Category	General population / Uncontrolled environment
Antenna	PIFA Antenna
Battery Information	DC 3.8V, 2400mAh, 9.12Wh
Device Operating Configurations	
Supporting Mode(s)	GSM 850/1900, WCDMA Band 2/4/5, LTE Band 2/4/5/7/12/17,

	WLAN 2.4G, Bluetooth		
Test Modulation	GSM(GMSK/8PSK), WCDMA(QPSK), LTE(QPSK/16QAM), WLAN(DSSS/OFDM), Bluetooth(GFSK, $\pi/4$ -DQPSK, 8DPSK)		
Device Class	B		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM 850	824-849	869-894
	GSM 1900	1850-1910	1930-1990
	WCDMA Band 2	1850-1910	1930-1990
	WCDMA Band 4	1710-1755	2110-2155
	WCDMA Band 5	824-849	869-894
	LTE Band 2	1850-1910	1930-1990
	LTE Band 4	1710-1755	2110-2155
	LTE Band 5	824-849	869-894
	LTE Band 7	2500-2570	2620-2690
	LTE Band 12	699-716	729-746
	LTE Band 17	704-716	734-746
	WLAN 2.4G	2412-2462	
	Bluetooth	2402-2480	
GPRS Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
EDGE Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
Power Class	4, tested with power level 5(GSM 850)		
	1, tested with power level 0(GSM 1900)		
	3, tested with power control "all 1"(WCDMA Band 2)		
	3, tested with power control "all 1"(WCDMA Band 4)		
	3, tested with power control "all 1"(WCDMA Band 5)		
	3, tested with power control all Max.(LTE Band 2)		
	3, tested with power control all Max.(LTE Band 4)		
	3, tested with power control all Max.(LTE Band 5)		
	3, tested with power control all Max.(LTE Band 7)		
	3, tested with power control all Max.(LTE Band 12)		
	3, tested with power control all Max.(LTE Band 17)		
Test Channels (low-mid-high)	128-189-251(GSM 850)		
	512-661-810(GSM 1900)		
	9262-9400-9538(WCDMA Band 2)		
	1312-1413-1513(WCDMA Band 4)		
	4132-4182-4233(WCDMA Band 5)		

18607-18900-19193(LTE Band 2 BW=1.4MHz)
18615-18900-19185(LTE Band 2 BW=3MHz)
18625-18900-19175(LTE Band 2 BW=5MHz)
18650-18900-19150(LTE Band 2 BW=10MHz)
18675-18900-19125(LTE Band 2 BW=15MHz)
18700-18900-19100(LTE Band 2 BW=20MHz)
19957-20175-20393(LTE Band 4 BW=1.4MHz)
19965-20175-20385(LTE Band 4 BW=3MHz)
19975-20175-20375(LTE Band 4 BW=5MHz)
20000-20175-20350(LTE Band 4 BW=10MHz)
20025-20175-20325(LTE Band 4 BW=15MHz)
20050-20175-20300(LTE Band 4 BW=20MHz)
20407-20525-20643(LTE Band 5 BW=1.4MHz)
20415-20525-20635(LTE Band 5 BW=3MHz)
20425-20525-20625(LTE Band 5 BW=5MHz)
20450-20525-20600(LTE Band 5 BW=10MHz)
20775-21100-21425(LTE Band 7 BW=5MHz)
20800-21100-21400(LTE Band 7 BW=10MHz)
20825-21100-21375(LTE Band 7 BW=15MHz)
20850-21100-21350(LTE Band 7 BW=20MHz)
23017-23095-23173 (LTE Band 12 BW=1.4MHz)
23025-23095-23165 (LTE Band 12 BW=3MHz)
23035-23095-23155 (LTE Band 12 BW=5MHz)
23060-23095-23130 (LTE Band 12 BW=10MHz)
23755-23790-23825(LTE Band 17 BW=5MHz)
23780-23790-23800(LTE Band 17 BW=10MHz)
1-3-6-9-11(WLAN 2.4G)

1.4. Test specification(s)


FCC 47 CFR Part 2(2.1093)
ANSI/IEEE C95.1-1992
IEEE Std 1528-2013
KDB 865664 D01 SAR measurement 100 MHz to 6 GHz
KDB 865664 D02 RF Exposure Reporting
KDB 447498 D01 General RF Exposure Guidance
KDB 248227 D01 802.11 Wi-Fi SAR
KDB 941225 D01 3G SAR Procedures
KDB 941225 D05 SAR for LTE Devices
KDB 941225 D06 Hotspot SAR
KDB 648474 D04 Handset SAR

1.5. Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

2. SAR Measurement System

2.1. SATIMO SAR Measurement Set-up Diagram



These measurements were performed with the automated near-field scanning system OPENSAR from SATIMO. The system is based on a high precision robot (working range: 901 mm), which positions the probes with a positional repeatability of better than ± 0.03 mm. The SAR measurements were conducted with dosimetric probe (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation.

The first step of the field measurement is the evaluation of the voltages induced on the probe by the device under test. Probe diode detectors are nonlinear. Below the diode compression point, the output voltage is proportional to the square of the applied E-field; above the diode compression point, it is linear to the applied E-field. The compression point depends on the diode, and a calibration procedure is necessary for each sensor of the probe.

The Keithley multimeter reads the voltage of each sensor and send these three values to the PC. The corresponding E field value is calculated using the probe calibration factors, which are stored in the working directory. This evaluation includes linearization of the diode characteristics. The field calculation is done separately for each sensor. Each component of the E field is displayed on the "Dipole Area Scan Interface" and the total E field is displayed on the "3D Interface"

2.2. Robot

The SATIMO SAR system uses the high precision robots from KUKA. For the 6-axis controller system, the robot controller version (KUKA) from KUKA is used. The KUKA robot series have many features that are important for our application:



- High precision (repeatability ± 0.03 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

2.3. E-Field Probe

This E-field detection probe is composed of three orthogonal dipoles linked to special Schottky diodes with low detection thresholds. The probe allows the measurement of electric fields in liquids such as the one defined in the IEEE and CENELEC standards.

For the measurements the Specific Dosimetric E-Field Probe SN 41/18 EPGO330 with following specifications is used



- Dynamic range: 0.01-100 W/kg
 - Tip Diameter: 2.5 mm
 - Distance between probe tip and sensor center: 1 mm
 - Distance between sensor center and the inner phantom surface: 2 mm (repeatability better than ± 1 mm).
 - Probe linearity: ± 0.10 dB
 - Axial isotropy: 0.06 dB
 - Hemispherical Isotropy: 0.09 dB
 - Calibration range: 650MHz to 5900MHz for head & body simulating liquid.
 - Lower detection limit: 9mW/kg
- Angle between probe axis (evaluation axis) and surface normal line: less than 30° .

2.3.1. E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (Norm X, Norm Y, and Norm Z), the diode compression parameter (DCP) and the conversion factor (Conv F) of the probe are tested. The calibration data can be referred to appendix D of this report.

2.4. SAM phantoms


Photo of SAM phantom SN 16/15 SAM119



The SAM phantom is used to measure the SAR relative to people exposed to electro-magnetic field radiated by mobile phones.

2.4.1. Technical Data

Serial Number	Shell thickness	Filling volume	Dimensions	Positionner Material	Permittivity	Loss Tangent
SN 16/15 SAM119	2 mm $\pm$ 0.2 mm	27 liters	Length:1000 mm Width:500 mm Height:200 mm	Gelcoat with fiberglass	3.4	0.02




Serial Number	Left Head(mm)		Right Head(mm)		Flat Part(mm)	
SN 16/15 SAM119	2	2.02	2	2.08	1	2.09
	3	2.05	3	2.06	2	2.06
	4	2.07	4	2.07	3	2.08
	5	2.08	5	2.08	4	2.10
	6	2.05	6	2.07	5	2.10
	7	2.05	7	2.05	6	2.07
	8	2.07	8	2.06	7	2.07
	9	2.08	9	2.06	-	-

The test, based on ultrasonic system, allows measuring the thickness with an accuracy of 10 μ m.

2.5. Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1 degree.



Serial Number	Holder Material	Permittivity	Loss Tangent
SN 16/15 MSH100	Delrin	3.7	0.005

2.6. Test Equipment List

This table gives a complete overview of the SAR measurement equipment.

Devices used during the test described are marked ☒

	Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
					Last Cal.	Due Date
☒	MVG	E FIELD PROBE	SSE2	SN 41/18 EPG0330	May 21, 2019	May 20, 2020
☒	MVG	750 MHz Dipole	SID750	SN 03/15 DIP 0G750-355	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	835 MHz Dipole	SID835	SN 03/15 DIP 0G835-347	Apr. 19, 2018	Apr. 18, 2021
☐	MVG	900 MHz Dipole	SID900	SN 03/15 DIP 0G900-348	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	1800 MHz Dipole	SID1800	SN 03/15 DIP 1G800-349	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	1900 MHz Dipole	SID1900	SN 03/15 DIP 1G900-350	Apr. 19, 2018	Apr. 18, 2021
☐	MVG	2000 MHz Dipole	SID2000	SN 03/15 DIP 2G000-351	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	2450 MHz Dipole	SID2450	SN 03/15 DIP 2G450-352	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	2600 MHz Dipole	SID2600	SN 03/15 DIP 2G600-356	Apr. 19, 2018	Apr. 18, 2021
☐	MVG	5000 MHz Dipole	SWG5500	SN 13/14 WGA 33	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	Liquid measurement Kit	SCLMP	SN 21/15 OCPG 72	NCR	NCR
☒	MVG	Power Amplifier	N.A	AMPLISAR_28/14_003	NCR	NCR
☒	KEITHLEY	Millivoltmeter	2000	4072790	NCR	NCR
☒	R&S	Universal radio communication tester	CMU200	117858	Aug. 06, 2019	Aug. 05, 2020
☒	R&S	Wideband radio communication tester	CMW500	103917	Aug. 28, 2019	Aug. 27, 2020
☒	HP	Network Analyzer	8753D	3410J01136	Aug. 06, 2019	Aug. 05, 2020
☒	Agilent	PSG Analog Signal Generator	E8257D	MY51110112	Aug. 06, 2019	Aug. 05, 2020

☒	Agilent	Power meter	E4419B	MY45102538	Aug. 06, 2019	Aug. 05, 2020
☒	Agilent	Power sensor	E9301A	MY41495644	Aug. 06, 2019	Aug. 05, 2020
☒	Agilent	Power sensor	E9301A	US39212148	Aug. 06, 2019	Aug. 05, 2020
☒	MCLI/USA	Directional Coupler	CB11-20	0D2L51502	Aug. 06, 2019	Aug. 05, 2020

3. SAR Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/Bluetooth power measurement, use engineering software to configure EUT WLAN/Bluetooth continuously transmission, at maximum RF power in each supported wireless interface and frequency band.
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/Bluetooth output power.

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/Bluetooth continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix A demonstrates.
- (c) Set scan area, grid size and other setting on the OPENSAR software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band.
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

3.1. Power Reference

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

3.2. Area scan & Zoom scan

The area scan is a 2D scan to find the hot spot location on the DUT. The zoom scan is a 3D scan above the hot spot to calculate the 1g and 10g SAR value.

Measurement of the SAR distribution with a grid of 8 to 16 mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8 * 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that will not be within the zoom scan of other peaks; additional peaks shall be measured only when the primary peak is within 2 dB of the SAR compliance limit (e.g., 1 W/kg for 1,6 W/kg 1 g limit, or 1,26 W/kg for 2 W/kg, 10 g limit).

Area scan & Zoom scan scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	≤ 1.5 · $\Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the reported SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

3.3. Description of interpolation/extrapolation scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1 mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.

3.4. Volumetric Scan

The volumetric scan consists to a full 3D scan over a specific area. This 3D scan is useful form multi Tx SAR measurement. Indeed, it is possible with OpenSAR to add, point by point, several volumetric scan to calculate the SAR value of the combined measurement as it is define in the standard IEEE1528 and IEC62209.

3.5. Power Drift

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In OpenSAR measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in V/m. If the power drifts more than $\pm 5\%$, the SAR will be retested.


4. System Verification Procedure

4.1. Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% of weight)	Head Tissue									
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	34.40	34.40	34.40	55.36	55.36	57.87	57.87	57.87	65.53	65.53
NaCl	0.79	0.79	0.79	0.35	0.35	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	64.81	64.81	64.81	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	30.45	30.45	19.97	19.97	19.97	24.24	24.24
DGBE	0.00	0.00	0.00	13.84	13.84	22.00	22.00	22.00	10.23	10.23
Ingredients (% of weight)	Body Tissue									
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	50.30	50.30	50.30	69.91	69.91	71.88	71.88	71.88	79.54	79.54
NaCl	0.60	0.60	0.60	0.13	0.13	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	49.10	49.10	49.10	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	9.99	9.99	19.97	19.97	19.97	11.24	11.24
DGBE	0.00	0.00	0.00	19.97	19.97	7.99	7.99	7.99	9.22	9.22

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid depth from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm.

Photo of Liquid depth for Head Position	Photo of Liquid depth for Body Position
	

4.1.1. Tissue Dielectric Parameter Check Results

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.


Tissue Type	Measured Frequency (MHz)	Target Tissue		Measured Tissue		Liquid Temp.	Test Date
		ϵ_r ($\pm 5\%$)	σ (S/m) ($\pm 5\%$)	ϵ_r	σ (S/m)		
Head 750	750	41.96 (39.86~44.06)	0.89 (0.85~0.93)	41.08	0.91	21.3 °C	Oct. 25, 2019
Body 750	750	55.55 (52.77~58.33)	0.96 (0.91~1.01)	55.31	0.97	21.5 °C	Oct. 14, 2019
Head 850	835	41.50 (39.43~43.58)	0.90 (0.86~0.95)	40.55	0.93	21.8 °C	Oct. 26, 2019
Body 850	835	55.20 (52.44~57.96)	0.97 (0.92~1.02)	54.28	1.00	21.1 °C	Oct. 26, 2019
Head 1800	1800	40.00 (38.00~42.00)	1.40 (1.33~1.47)	38.65	1.40	21.3 °C	Oct. 26, 2019
Body 1800	1800	53.30 (50.64~55.97)	1.52 (1.44~1.60)	53.19	1.57	21.6 °C	Nov. 11, 2019
Head 1900	1900	40.00 (38.00~42.00)	1.40 (1.33~1.47)	40.98	1.45	21.4 °C	Oct. 27, 2019
Body 1900	1900	53.30 (50.64~55.97)	1.52 (1.44~1.60)	52.52	1.58	21.5 °C	Nov. 11, 2019
Head 2450	2450	39.20 (37.24~41.16)	1.80 (1.71~1.89)	38.78	1.85	21.6 °C	Oct. 25, 2019
Body 2450	2450	52.70 (50.07~55.34)	1.95 (1.85~2.05)	52.09	2.03	21.5 °C	Oct. 25, 2019
Head 2600	2600	39.01 (37.06~40.96)	1.96 (1.86~2.06)	38.46	2.02	21.5 °C	Oct. 27, 2019
Body 2600	2600	52.51 (49.88~55.14)	2.16 (2.05~2.27)	52.67	2.22	21.3 °C	Oct. 27, 2019

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

4.2. System Verification Procedure

The system verification is performed for verifying the accuracy of the complete measurement system and performance of the software. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 100mW (below 5GHz) or 100mW (above 5GHz). To adjust this power a power meter is used. The power sensor is connected to the cable before the system verification to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system verification to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

The system verification is shown as below picture:



4.2.1. System Verification Results

Comparing to the original SAR value provided by SATIMO, the verification data should be within its specification of $\pm 10\%$. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance verification can meet the variation criterion and the plots can be referred to Appendix B of this report.

System Verification	Target SAR (1W) ($\pm 10\%$)		Measured SAR (Normalized to 1W)		Liquid Temp.	Test Date
	1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)		
750MHz Head	8.56 (7.70~9.42)	5.55 (5.00~6.11)	8.52	5.53	21.3 °C	Oct. 25, 2019
750MHz Body	8.85 (7.97~9.74)	5.91 (5.32~6.50)	8.81	5.88	21.5 °C	Oct. 14, 2019
835MHz Head	9.55 (8.60~10.51)	6.10 (5.49~6.71)	9.51	6.08	21.8 °C	Oct. 26, 2019
835MHz Body	9.83 (8.85~10.81)	6.45 (5.81~7.10)	9.81	6.41	21.1 °C	Oct. 26, 2019
1800MHz Head	38.11 (34.30~41.92)	20.05 (18.05~22.06)	38.09	20.01	21.3 °C	Oct. 26, 2019
1800MHz Body	38.13 (34.32~41.94)	20.65 (18.59~22.72)	38.18	20.49	21.6 °C	Nov. 11, 2019
1900MHz Head	38.92 (35.03~42.81)	20.09 (18.08~22.10)	38.95	20.63	21.4 °C	Oct. 27, 2019
1900MHz Body	39.02 (35.12~42.92)	20.57 (18.51~22.63)	39.22	20.41	21.5 °C	Nov. 11, 2019
2450MHz Head	53.76 (48.38~59.14)	24.12 (21.71~26.53)	53.71	24.09	21.6 °C	Oct. 25, 2019
2450MHz Body	52.90 (47.61~58.19)	24.09 (21.68~26.50)	52.93	24.03	21.5 °C	Oct. 25, 2019
2600MHz Head	55.60 (50.04~61.16)	24.60 (22.14~27.06)	55.65	24.55	21.5 °C	Oct. 27, 2019
2600MHz Body	52.49 (47.24~57.74)	23.74 (21.37~26.11)	52.43	23.78	21.3 °C	Oct. 27, 2019

5. SAR Measurement variability and uncertainty

5.1. SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

5.2. SAR measurement uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

6. RF Exposure Positions

6.1. Ear and handset reference point

Figure 6.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M”, the left ear reference point (ERP) is marked “LE”, and the right ERP is marked “RE”.



Fig 6.1.1 Front, back, and side views of SAM phantom

6.2. Definition of the cheek position

1. Define two imaginary lines on the handset, the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset: the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 6.2.1 and Figure 6.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 6.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 6.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
2. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
3. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP
4. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
5. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.

6. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 6.2.3. The actual rotation angles should be documented in the test report.




Fig 6.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 6.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 6.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

6.3. Definition of the tilt position

1. While maintaining the orientation of the handset, retract the handset parallel to the reference plane far enough away from the phantom to enable a rotation of the device by 15 degree.
2. Rotate the Handset around the horizontal line by 15 degree (see Figure 6.3.1).
3. While maintaining the orientation of the handset, move the handset towards the phantom on a line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, e.g., the antenna with the back of the phantom head, the angle of the handset shall be reduced. In this case, the tilt position is obtained if any part of the handset is in contact with the pinna as well as a second part of the handset is in contact with the phantom, e.g., the antenna with the back of the head.




Figure 6.3.1 – Tilt position of the wireless device on the left side of SAM

6.4. Body Worn Accessory

1. Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6.4.1). Per KDB 648474 D04, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $< 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a handset attached to the handset.
2. Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest

spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Figure 6.4.1 – Test positions for body-worn devices

6.5. Wireless Router Devices

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WLAN simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WLAN transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WLAN transmitter according to FCC KDB Publication 447498 D01 publication procedures. The “Portable Hotspot” feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

7. RF Output Power

7.1. GSM Conducted Power

Band GSM850	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	128	189	251	Tune-up	128	189	251
Frequency (MHz)	(dBm)	824.2	836.4	848.8	(dBm)	824.2	836.4	848.8
GSM (GMSK)	34.00	33.55	33.66	33.71	24.97	24.52	24.63	24.68
GPRS(GMSK, 1 TS)	34.00	33.56	33.69	33.74	24.97	24.53	24.66	24.71
GPRS(GMSK, 2 TS)	33.00	32.55	32.72	32.76	26.98	26.53	26.70	26.74
GPRS(GMSK, 3 TS)	31.00	30.40	30.55	30.61	26.74	26.14	26.29	26.35
GPRS(GMSK, 4 TS)	30.00	29.23	29.40	29.42	26.99	26.22	26.39	26.41
EDGE(8PSK, 1 TS)	34.00	33.52	33.64	33.75	24.97	24.49	24.61	24.72
EDGE(8PSK, 2 TS)	33.00	32.49	32.65	32.74	26.98	26.47	26.63	26.72
EDGE(8PSK, 3 TS)	31.00	30.35	30.49	30.60	26.74	26.09	26.23	26.34
EDGE(8PSK, 4 TS)	30.00	29.18	29.34	29.41	26.99	26.17	26.33	26.40
Band GSM1900	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	512	661	810	Tune-up	512	661	810
Frequency (MHz)	(dBm)	1850.2	1880.0	1909.8	(dBm)	1850.2	1880.0	1909.8
GSM (GMSK)	29.50	29.17	29.16	29.17	20.47	20.14	20.13	20.14
GPRS(GMSK, 1 TS)	29.50	29.19	29.17	29.19	20.47	20.16	20.14	20.16
GPRS(GMSK, 2 TS)	28.50	28.18	28.18	28.22	22.48	22.16	22.16	22.20
GPRS(GMSK, 3 TS)	26.50	26.03	26.03	26.09	22.24	21.77	21.77	21.83
GPRS(GMSK, 4 TS)	25.50	24.91	24.94	25.01	22.49	21.90	21.93	22.00
EDGE(8PSK, 1 TS)	29.50	29.19	29.20	29.19	20.47	20.16	20.17	20.16
EDGE(8PSK, 2 TS)	28.50	28.21	28.21	28.22	22.48	22.19	22.19	22.20
EDGE(8PSK, 3 TS)	26.50	26.03	26.05	26.09	22.24	21.77	21.79	21.83
EDGE(8PSK, 4 TS)	25.50	24.92	24.97	25.02	22.49	21.91	21.96	22.01

Note: The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.
The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 TS) - 9.03 dB

Frame-averaged power = Maximum burst averaged power (2 TS) - 6.02 dB

Frame-averaged power = Maximum burst averaged power (3 TS) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 TS) - 3.01 dB

7.2. WCDMA Conducted Power

Band	WCDMA Band 2			
Tx Channel	Tune-up	9262	9400	9538
Frequency (MHz)		1852.4	1880	1907.6

RMC 12.2Kbps	23.00	22.66	22.68	22.77
HSDPA Subtest-1	22.00	21.70	21.75	21.83
HSDPA Subtest-2	22.00	21.05	21.15	21.28
HSDPA Subtest-3	21.00	20.15	20.02	20.48
HSDPA Subtest-4	21.00	20.09	20.27	20.33
HSUPA Subtest-1	22.00	21.36	21.52	21.43
HSUPA Subtest-2	22.00	21.67	21.73	21.72
HSUPA Subtest-3	21.00	20.40	20.53	20.56
HSUPA Subtest-4	22.00	21.72	21.75	21.82
HSUPA Subtest-5	22.00	20.86	21.14	21.17
Band	WCDMA Band 4			
Tx Channel	Tune-up	1312	1413	1513
Frequency (MHz)		1712.4	1732.6	1752.6
RMC 12.2Kbps	23.50	23.23	23.43	23.36
HSDPA Subtest-1	23.50	22.54	22.48	22.38
HSDPA Subtest-2	22.50	22.06	21.90	21.66
HSDPA Subtest-3	21.50	21.01	21.02	20.49
HSDPA Subtest-4	21.50	20.92	21.12	21.01
HSUPA Subtest-1	22.50	22.07	22.14	22.04
HSUPA Subtest-2	22.50	22.45	22.33	22.36
HSUPA Subtest-3	21.50	21.39	21.25	20.83
HSUPA Subtest-4	23.50	22.56	22.51	22.40
HSUPA Subtest-5	22.50	21.78	21.73	21.77
Band	WCDMA Band 5			
Tx Channel	Tune-up	4132	4182	4233
Frequency (MHz)		826.4	836.4	846.6
RMC 12.2Kbps	24.50	23.92	24.07	24.22
HSDPA Subtest-1	23.50	23.02	23.09	23.26
HSDPA Subtest-2	23.50	22.43	22.74	22.59
HSDPA Subtest-3	22.50	21.73	21.91	21.76
HSDPA Subtest-4	22.50	21.62	21.58	21.96
HSUPA Subtest-1	23.50	22.70	22.57	22.70
HSUPA Subtest-2	23.50	22.93	22.99	23.19
HSUPA Subtest-3	22.50	21.85	21.86	22.06
HSUPA Subtest-4	23.50	23.00	23.09	23.25
HSUPA Subtest-5	22.50	22.24	22.12	22.32

7.3. LTE Conducted Power

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18607/1850.7	18900/1880	19193/1909.3
LTE Band 2	1.4MHz	QPSK	1	0	23.00	22.71	22.20	22.30
			1	2	23.00	22.88	22.35	22.44
			1	5	23.00	22.68	22.19	22.29
			3	0	23.00	22.71	22.28	22.35
			3	1	23.00	22.72	22.31	22.35
			3	2	23.00	22.71	22.30	22.34
			6	0	22.00	21.69	21.43	21.42
		16QAM	1	0	22.00	21.48	21.38	21.15
			1	2	22.00	21.67	21.50	21.30
			1	5	22.00	21.30	21.39	21.17
			3	0	22.00	21.38	21.51	21.52
			3	1	22.00	21.36	21.51	21.49
			3	2	22.00	21.35	21.50	21.55
			6	0	21.00	20.32	20.43	20.54
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18615/1851.5	18900/1880	19185/1908.5
LTE Band 2	3MHz	QPSK	1	0	23.00	22.12	22.22	22.32
			1	7	23.00	22.39	22.57	22.61
			1	14	23.00	22.07	22.19	22.25
			8	0	22.00	21.17	21.30	21.39
			8	4	22.00	21.18	21.30	21.36
			8	7	22.00	21.20	21.28	21.29
			15	0	22.00	21.12	21.23	21.28
		16QAM	1	0	22.00	21.47	21.39	21.22
			1	7	22.00	21.81	21.62	21.44
			1	14	22.00	21.49	21.35	21.18
			8	0	21.00	20.17	20.24	20.32
			8	4	21.00	20.19	20.27	20.34
			8	7	21.00	20.16	20.21	20.28
			15	0	21.00	20.15	20.16	20.35
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		

			RB Size	RB Offset		18625/1852.5	18900/1880	19175/1907.5
LTE Band 2	5MHz	QPSK	1	0	23.00	22.03	22.16	22.23
			1	12	23.00	22.57	22.49	22.66
			1	24	23.00	22.10	22.11	22.17
			12	0	22.00	21.21	21.30	21.41
			12	6	22.00	21.22	21.28	21.37
			12	11	22.00	21.14	21.17	21.26
			25	0	22.00	21.20	21.24	21.38
		16QAM	1	0	23.00	21.48	21.44	21.52
			1	12	23.00	22.03	21.79	21.81
			1	24	23.00	21.62	21.39	21.48
			12	0	21.00	20.17	20.22	20.42
			12	6	21.00	20.19	20.24	20.43
			12	11	21.00	20.12	20.09	20.24
			25	0	21.00	20.13	20.21	20.29
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18650/1855	18900/1880	19150/1905
LTE Band 2	10MHz	QPSK	1	0	23.00	22.05	22.27	22.40
			1	24	23.00	22.27	22.29	22.44
			1	49	23.00	22.24	22.17	22.27
			25	0	22.00	21.29	21.37	21.49
			25	12	22.00	21.25	21.31	21.40
			25	24	22.00	21.35	21.20	21.25
			50	0	22.00	21.33	21.27	21.34
		16QAM	1	0	22.00	21.42	21.45	21.24
			1	24	22.00	21.75	21.45	21.34
			1	49	22.00	21.70	21.33	21.15
			25	0	21.00	20.30	20.35	20.43
			25	12	21.00	20.28	20.26	20.39
			25	24	21.00	20.31	20.12	20.25
			50	0	21.00	20.27	20.31	20.35
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18675/1857.5	18900/1880	19125/1902.5
LTE Band	15MHz	QPSK	1	0	23.00	22.04	22.20	22.33
			1	37	23.00	22.55	22.38	22.54

2			1	74	23.00	22.20	22.06	22.19
			36	0	22.00	21.35	21.44	21.41
			36	18	22.00	21.37	21.40	21.48
			36	37	22.00	21.42	21.24	21.36
			75	0	22.00	21.40	21.34	21.44
		16QAM	1	0	23.00	21.21	21.38	21.76
			1	37	23.00	21.77	21.39	22.07
			1	74	23.00	21.42	21.24	21.57
			36	0	21.00	20.38	20.37	20.40
			36	18	21.00	20.41	20.33	20.48
			36	37	21.00	20.46	20.15	20.35
			75	0	21.00	20.33	20.30	20.39
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18700/1860	18900/1880	19100/1900
LTE Band 2	20MHz	QPSK	1	0	23.00	21.89	22.08	22.12
			1	49	23.00	22.39	22.30	22.53
			1	99	23.00	22.01	21.95	22.03
			50	0	22.00	21.30	21.31	21.34
			50	24	22.00	21.36	21.28	21.44
			50	49	22.00	21.47	21.08	21.23
			100	0	22.00	21.40	21.21	21.30
		16QAM	1	0	22.00	21.20	21.38	21.35
			1	49	22.00	21.70	21.47	21.77
			1	99	22.00	21.42	21.23	21.30
			50	0	21.00	20.36	20.27	20.40
			50	24	21.00	20.42	20.26	20.46
			50	49	21.00	20.53	20.07	20.29
			100	0	21.00	20.38	20.16	20.29

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		19957/1710.7	20175/1732.5	20393/1754.3
LTE Band 4	1.4MHz	QPSK	1	0	24.00	23.63	23.51	23.07
			1	2	24.00	23.79	23.71	23.08
			1	5	24.00	23.65	23.52	23.01
			3	0	24.00	23.44	23.53	22.90
			3	1	24.00	23.48	23.47	22.95

			3	2	24.00	23.42	23.36	22.90
			6	0	23.00	22.82	22.45	22.11
		16QAM	1	0	23.00	22.25	22.33	21.98
			1	2	23.00	22.43	22.45	22.08
			1	5	23.00	22.23	22.33	21.98
			3	0	23.00	22.54	22.52	22.04
			3	1	23.00	22.55	22.35	22.10
			3	2	23.00	22.54	22.28	22.09
			6	0	22.00	21.73	21.36	21.11
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		19965/1711.5	20175/1732.5	20385/1753.5
LTE Band 4	3MHz	QPSK	1	0	24.00	23.61	23.02	22.96
			1	7	24.00	23.95	23.36	23.33
			1	14	24.00	23.56	22.90	23.00
			8	0	23.00	22.66	22.03	22.04
			8	4	23.00	22.67	22.05	22.08
			8	7	23.00	22.61	21.98	22.00
			15	0	23.00	22.50	21.95	21.91
		16QAM	1	0	23.00	22.59	22.11	21.64
			1	7	23.00	22.71	22.43	22.02
			1	14	23.00	22.46	22.08	21.65
			8	0	22.00	21.27	20.98	20.89
			8	4	22.00	21.18	21.01	20.92
			8	7	22.00	21.05	20.95	20.87
			15	0	22.00	21.13	20.90	20.91
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		19975/1712.5	20175/1732.5	20375/1752.5
LTE Band 4	5MHz	QPSK	1	0	24.00	23.50	22.84	22.85
			1	12	24.00	23.96	23.29	23.27
			1	24	24.00	23.40	22.84	22.86
			12	0	23.00	22.47	21.93	21.87
			12	6	23.00	22.39	22.01	21.98
			12	11	23.00	22.18	21.92	21.88
			25	0	23.00	22.10	21.96	21.91
		16QAM	1	0	23.00	22.08	22.39	21.99
			1	12	23.00	22.38	22.75	22.35

			1	24	23.00	22.08	22.34	22.01
			12	0	22.00	21.05	20.99	20.80
			12	6	22.00	21.02	21.03	20.88
			12	11	22.00	20.94	20.94	20.80
			25	0	21.00	20.88	20.94	20.83
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20000/1715	20175/1732.5	20350/1750
LTE Band 4	10MHz	QPSK	1	0	24.00	23.61	22.95	22.87
			1	24	24.00	23.38	23.01	22.98
			1	49	24.00	23.13	22.90	22.95
			25	0	23.00	22.08	22.03	21.94
			25	12	23.00	22.09	21.99	21.90
			25	24	23.00	22.06	22.02	21.92
			50	0	23.00	22.02	22.03	21.88
		16QAM	1	0	23.00	21.76	22.36	21.92
			1	24	23.00	21.88	22.40	21.97
			1	49	23.00	21.80	22.27	21.95
			25	0	22.00	20.98	21.02	20.86
			25	12	22.00	20.97	21.03	20.79
			25	24	22.00	21.00	21.01	20.84
			50	0	22.00	20.98	21.02	20.85
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20025/1717.5	20175/1732.5	20325/1747.5
LTE Band 4	15MHz	QPSK	1	0	24.00	23.37	22.85	22.75
			1	37	24.00	23.29	23.21	23.09
			1	74	24.00	22.96	22.77	22.84
			36	0	23.00	22.24	22.09	22.08
			36	18	23.00	22.17	22.13	22.11
			36	37	23.00	22.15	22.11	22.04
			75	0	23.00	22.24	22.13	22.06
		16QAM	1	0	23.00	22.01	22.04	22.11
			1	37	23.00	22.33	22.35	22.31
			1	74	23.00	22.08	21.87	22.09
			36	0	22.00	21.18	21.04	21.01
			36	18	22.00	21.17	21.03	21.00
			36	37	22.00	21.18	21.00	20.99

			75	0	22.00	21.10	21.07	20.94
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20050/1720	20175/1732.5	20300/1745
LTE Band 4	20MHz	QPSK	1	0	24.00	22.90	22.73	22.66
			1	49	24.00	23.20	23.06	23.05
			1	99	24.00	22.75	22.64	22.73
			50	0	23.00	22.03	22.01	21.86
			50	24	23.00	22.08	22.05	21.97
			50	49	23.00	22.03	21.97	21.82
			100	0	23.00	22.04	21.99	21.87
		16QAM	1	0	23.00	21.93	22.06	21.92
			1	49	23.00	22.31	22.38	22.11
			1	99	23.00	22.02	21.91	21.81
			50	0	22.00	21.05	21.02	20.83
			50	24	22.00	21.10	21.09	20.87
			50	49	22.00	21.05	21.00	20.79
			100	0	22.00	21.02	21.01	20.79

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20407/824.7	20525/836.5	20643/848.3
LTE Band 5	1.4MHz	QPSK	1	0	25.00	24.27	23.74	23.71
			1	2	25.00	24.42	23.85	23.86
			1	5	25.00	24.22	23.69	23.70
			3	0	25.00	24.32	23.80	23.81
			3	1	25.00	24.33	23.79	23.82
			3	2	25.00	24.29	23.79	23.78
			6	0	24.00	23.19	22.71	22.76
		16QAM	1	0	24.00	23.29	22.89	22.62
			1	2	24.00	23.43	22.98	22.75
			1	5	24.00	23.27	22.87	22.62
			3	0	24.00	23.43	23.02	22.94
			3	1	24.00	23.30	23.05	23.00
			3	2	24.00	23.12	23.01	23.02
			6	0	23.00	22.26	21.90	21.95
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		

			RB Size	RB Offset		20415/825.5	20525/836.5	20635/847.5
LTE Band 5	3MHz	QPSK	1	0	25.00	24.13	23.72	23.75
			1	7	25.00	24.24	24.02	24.11
			1	14	25.00	23.76	23.74	23.80
			8	0	23.00	22.70	22.72	22.74
			8	4	23.00	22.74	22.73	22.79
			8	7	23.00	22.73	22.73	22.71
			15	0	23.00	22.67	22.73	22.78
		16QAM	1	0	24.00	23.11	22.89	22.60
			1	7	24.00	23.50	23.22	23.02
			1	14	24.00	23.02	22.90	22.63
			8	0	22.00	21.76	21.82	21.75
			8	4	22.00	21.78	21.84	21.77
			8	7	22.00	21.77	21.81	21.72
			15	0	22.00	21.79	21.78	21.82
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20425/826.5	20525/836.5	20625/846.5
LTE Band 5	5MHz	QPSK	1	0	25.00	23.63	23.66	23.62
			1	12	25.00	24.02	24.09	24.09
			1	24	25.00	23.62	23.65	23.65
			12	0	23.00	22.60	22.71	22.84
			12	6	23.00	22.70	22.79	22.76
			12	11	23.00	22.54	22.82	22.62
			25	0	23.00	22.61	22.83	22.74
		16QAM	1	0	24.00	23.11	22.93	22.91
			1	12	24.00	23.45	23.50	23.40
			1	24	24.00	23.09	22.92	23.03
			12	0	22.00	21.64	21.77	21.88
			12	6	22.00	21.79	21.83	21.80
			12	11	22.00	21.64	21.88	21.71
			25	0	22.00	21.63	21.90	21.76
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20450/829	20525/836.5	20600/844
LTE Band	10MHz	QPSK	1	0	24.00	23.67	23.70	23.74
			1	24	24.00	23.77	23.86	23.81

5			1	49	24.00	23.73	23.74	23.75
			25	0	24.00	22.64	22.80	22.65
			25	12	24.00	22.69	22.77	22.71
			25	24	24.00	22.51	23.09	22.53
			50	0	23.00	22.63	22.94	22.59
		16QAM	1	0	24.00	22.80	22.62	23.06
			1	24	24.00	22.91	22.67	23.14
			1	49	24.00	22.90	22.54	23.17
			25	0	23.00	21.71	21.88	21.70
			25	12	23.00	21.70	21.78	21.78
			25	24	23.00	21.59	22.12	21.51
			50	0	22.00	21.72	21.95	21.65

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20775/2502.5	21100/2535	21425/2567.5
LTE Band 7	5MHz	QPSK	1	0	23.00	22.08	21.98	22.04
			1	12	23.00	22.51	22.35	22.42
			1	24	23.00	21.91	22.00	22.07
			12	0	22.00	20.88	21.05	21.10
			12	6	22.00	20.96	21.04	21.14
			12	11	22.00	20.96	21.00	21.02
			25	0	22.00	20.97	21.06	21.10
		16QAM	1	0	22.00	21.12	21.41	21.26
			1	12	22.00	21.54	21.67	21.62
			1	24	22.00	21.15	21.47	21.29
			12	0	21.00	19.99	20.05	20.05
			12	6	21.00	20.04	20.04	20.09
			12	11	21.00	20.04	20.02	19.96
			25	0	21.00	19.95	20.01	20.10
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20800/2505	21100/2535	21400/2565
LTE Band 7	10MHz	QPSK	1	0	23.00	21.92	22.07	22.13
			1	24	23.00	22.14	22.23	22.26
			1	49	23.00	21.99	22.12	22.13
			25	0	22.00	20.95	21.14	21.14
			25	12	22.00	21.02	21.11	21.16

			25	24	22.00	21.09	21.10	21.08
			50	0	22.00	21.02	21.08	21.11
		16QAM	1	0	22.00	21.07	20.89	21.40
			1	24	22.00	21.22	21.00	21.55
			1	49	22.00	21.14	20.90	21.43
			25	0	21.00	19.99	20.12	20.10
			25	12	21.00	20.08	20.03	20.11
			25	24	21.00	20.14	20.05	20.10
			50	0	21.00	20.10	20.04	20.05
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20825/2507.5	21100/2535	21375/2562.5
LTE Band 7	15MHz	QPSK	1	0	23.00	21.86	22.03	22.04
			1	37	23.00	22.15	22.32	22.33
			1	74	23.00	21.89	22.02	22.05
			36	0	22.00	20.96	21.18	21.17
			36	18	22.00	21.04	21.13	21.23
			36	37	22.00	21.15	21.11	21.18
			75	0	22.00	21.09	21.16	21.21
		16QAM	1	0	22.00	20.98	21.35	21.12
			1	37	22.00	21.33	21.60	21.46
			1	74	22.00	21.01	21.36	21.16
			36	0	21.00	19.96	20.13	20.16
			36	18	21.00	20.04	20.12	20.24
			36	37	21.00	20.07	20.08	20.21
			75	0	21.00	20.12	20.08	20.13
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20850/2510	21100/2535	21350/2560
LTE Band 7	20MHz	QPSK	1	0	23.00	21.74	21.88	21.84
			1	49	23.00	22.14	22.25	22.26
			1	99	23.00	21.86	21.90	21.92
			50	0	22.00	20.90	21.10	21.01
			50	24	22.00	21.06	21.08	21.13
			50	49	22.00	21.05	20.99	21.06
			100	0	22.00	20.96	21.05	21.06
		16QAM	1	0	22.00	20.92	21.02	21.08
			1	49	22.00	21.32	21.45	21.44

			1	99	22.00	21.01	21.04	21.18
			50	0	21.00	19.93	20.11	20.02
			50	24	21.00	20.03	20.09	20.16
			50	49	21.00	20.05	20.00	20.08
			100	0	21.00	19.99	20.01	20.00

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23017/699.7	23095/707.5	23173/715.3
LTE Band 12	1.4MHz	QPSK	1	0	24.00	23.31	23.27	23.06
			1	2	24.00	23.47	23.39	23.18
			1	5	24.00	23.34	23.25	23.05
			3	0	24.00	23.38	23.36	23.13
			3	1	24.00	23.41	23.39	23.11
			3	2	24.00	23.41	23.36	23.10
		16QAM	6	0	23.00	22.36	22.34	22.18
			1	0	23.00	22.40	22.49	21.90
			1	2	23.00	22.56	22.58	22.06
			1	5	23.00	22.50	22.50	21.91
			3	0	23.00	22.54	22.63	22.31
			3	1	23.00	22.56	22.62	22.29
			3	2	23.00	22.53	22.61	22.33
			6	0	22.00	21.53	21.48	21.30
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23025/700.5	23095/707.5	23165/714.5
LTE Band 12	3MHz	QPSK	1	0	24.00	23.30	23.31	23.09
			1	7	24.00	23.45	23.77	23.41
			1	14	24.00	23.30	23.25	23.08
			8	0	23.00	22.31	22.35	22.18
			8	4	23.00	22.38	22.39	22.15
			8	7	23.00	22.37	22.32	22.10
			15	0	23.00	22.35	22.33	22.09
		16QAM	1	0	23.00	22.70	22.55	21.98
			1	7	23.00	22.99	22.70	22.24
			1	14	23.00	22.73	22.53	21.95
			8	0	22.00	21.33	21.37	21.09
			8	4	22.00	21.41	21.36	21.14

			8	7	22.00	21.39	21.33	21.12
			15	0	22.00	21.39	21.32	21.16
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23035/701.5	23095/707.5	23155/713.5
LTE Band 12	5MHz	QPSK	1	0	24.00	23.24	23.28	23.05
			1	12	24.00	23.65	23.51	23.33
			1	24	24.00	23.29	23.25	23.01
			12	0	23.00	22.35	22.38	22.20
			12	6	23.00	22.43	22.40	22.18
			12	11	23.00	22.33	22.35	22.05
			25	0	23.00	22.37	22.38	22.18
		16QAM	1	0	24.00	22.76	22.64	22.42
			1	12	24.00	23.12	22.95	22.68
			1	24	24.00	22.80	22.59	22.35
			12	0	22.00	21.32	21.32	21.21
			12	6	22.00	21.43	21.35	21.27
			12	11	22.00	21.36	21.29	21.12
			25	0	22.00	21.27	21.43	21.15
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23060/704	23095/707.5	23130/711
LTE Band 12	10MHz	QPSK	1	0	24.00	23.31	23.30	23.29
			1	24	24.00	23.43	23.43	23.34
			1	49	24.00	23.31	23.17	23.09
			25	0	23.00	22.42	22.45	22.34
			25	12	23.00	22.40	22.37	22.27
			25	24	23.00	22.44	22.42	22.13
			50	0	23.00	22.42	22.44	22.27
		16QAM	1	0	23.00	22.18	22.69	22.50
			1	24	23.00	22.31	22.85	22.52
			1	49	23.00	22.24	22.59	22.30
			25	0	22.00	21.41	21.46	21.39
			25	12	22.00	21.41	21.43	21.27
			25	24	22.00	21.43	21.43	21.15
			50	0	22.00	21.41	21.40	21.29

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23755/706.5	23790/710	23825/713.5
LTE Band 17	5MHz	QPSK	1	0	24.00	23.68	23.75	23.67
			1	12	24.00	23.98	23.90	23.95
			1	24	24.00	23.75	23.68	23.56
			12	0	23.00	22.87	22.82	22.86
			12	6	23.00	22.91	22.91	22.81
			12	11	23.00	22.92	22.74	22.65
			25	0	23.00	22.92	22.84	22.78
		16QAM	1	0	24.00	23.08	23.26	23.03
			1	12	24.00	23.46	23.57	23.28
			1	24	24.00	23.11	23.17	22.89
			12	0	22.00	21.90	21.86	21.82
			12	6	22.00	21.95	21.91	21.78
			12	11	22.00	21.90	21.78	21.61
			25	0	22.00	21.87	21.77	21.83
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23780/709	23790/710	23800/711
LTE Band 17	10MHz	QPSK	1	0	24.00	23.77	23.81	23.82
			1	24	24.00	23.99	23.91	23.91
			1	49	24.00	23.65	23.66	23.68
			25	0	23.00	22.89	22.91	22.88
			25	12	23.00	22.92	22.88	22.87
			25	24	23.00	22.83	22.75	22.66
			50	0	23.00	22.91	22.86	22.80
		16QAM	1	0	24.00	23.22	23.01	22.68
			1	24	24.00	23.40	23.08	22.77
			1	49	24.00	23.07	22.84	22.55
			25	0	22.00	21.95	21.91	21.88
			25	12	22.00	21.93	21.89	21.87
			25	24	22.00	21.86	21.78	21.69
			50	0	22.00	21.87	21.85	21.76

7.4. WLAN & Bluetooth Output Power

7.4.1. Output Power Results Of WLAN

Mode	Channel	Frequency (MHz)	Tune-up	Output Power (dBm)
802.11b	1	2412	16.00	15.38
	6	2437	16.00	15.53
	11	2462	16.00	15.52
802.11g	1	2412	14.00	13.99
	6	2437	14.00	13.73
	11	2462	14.00	13.33
802.11n HT20	1	2412	14.00	13.95
	6	2437	14.00	13.66
	11	2462	14.00	13.30
802.11n HT40	3	2422	14.00	13.43
	6	2437	14.00	13.08
	9	2452	14.00	12.89


NOTE: Power measurement results of WLAN 2.4G.

7.4.2. Output Power Results Of Bluetooth

BR+EDR	Output Power (dBm)				
	Channel	Tune-up	Data Rates		
			1M	2M	3M
	0CH	1.000	0.782	0.386	0.502
	39CH	-1.000	-1.006	-1.568	-1.498
	78CH	2.000	1.397	0.740	0.774

BLE	Channel	Tune-up	Output Power (dBm)
	0CH	1.000	0.968
	19CH	-1.000	-0.986
	39CH	2.000	1.366

8. Antenna Location



Distance of the Antenna to the EUT surface/edge						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main	≤ 25mm	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	≤ 25mm
WLAN & Bluetooth	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	>25mm
Positions for SAR tests						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main	Yes	Yes	Yes	Yes	NO	Yes
WLAN & Bluetooth	Yes	Yes	Yes	NO	Yes	NO

9. Stand-alone SAR test exclusion

Refer to FCC KDB 447498D01, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	P_{max} (dBm)	P_{max} (mW)	Distance (mm)	f (GHz)	Calculation Result	SAR Exclusion threshold	SAR test exclusion
Bluetooth	2.000	1.585	5	2.48	0.5	3.0	Yes

NOTE: Standalone SAR test exclusion for Bluetooth

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}/x}] \text{ W/kg}$ for test separation distances $\leq 50\text{mm}$, where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	Position	P_{max} (dBm)	P_{max} (mW)	Distance (mm)	f (GHz)	x	Estimated SAR (W/Kg)
Bluetooth	Head	2.000	1.585	5	2.48	7.5	0.067
Bluetooth	Body	2.000	1.585	10	2.48	7.5	0.033
Bluetooth	Hotspot	2.000	1.585	10	2.48	7.5	0.033

NOTE: Estimated SAR calculation for Bluetooth

10. SAR Results

10.1. SAR measurement results

10.1.1. SAR measurement Result of GSM850

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	189/836.4	GPRS(GMSK 2TS)	0.658	0.495	2.16	32.72	33.00	0.702
Left Tilt 15 Degree	189/836.4	GPRS(GMSK 2TS)	0.476	0.107	4.01	32.72	33.00	0.508
Right Cheek	189/836.4	GPRS(GMSK 2TS)	0.566	0.230	-3.16	32.72	33.00	0.604
Right Tilt 15 Degree	189/836.4	GPRS(GMSK 2TS)	0.423	0.122	4.55	32.72	33.00	0.451

NOTE: Head SAR test results of GSM850.

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	189/836.4	GPRS(GMSK 2TS)	0.705	0.550	3.21	32.72	33.00	0.752
Back Side	189/836.4	GPRS(GMSK 2TS)	1.026	0.903	-1.75	32.72	33.00	1.094
Back Side Repeated	189/836.4	GPRS(GMSK 2TS)	1.002	0.883	0.01	32.72	33.00	1.069
Back Side	128/824.2	GPRS(GMSK 2TS)	0.766	0.433	-0.10	32.55	33.00	0.850
Back Side	251/848.8	GPRS(GMSK 2TS)	0.661	0.394	0.39	32.76	33.00	0.699

NOTE: Body-Worn SAR test results of GSM850

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	189/836.4	GPRS(GMSK 2TS)	0.705	0.550	3.21	32.72	33.00	0.752
Back Side	189/836.4	GPRS(GMSK 2TS)	1.026	0.903	-1.75	32.72	33.00	1.094
Back Side Repeated	189/836.4	GPRS(GMSK 2TS)	1.002	0.883	0.01	32.72	33.00	1.069

Left Side	189/836.4	GPRS(GMSK 2TS)	0.562	0.415	3.52	32.72	33.00	0.599
Right Side	189/836.4	GPRS(GMSK 2TS)	0.604	0.443	-1.32	32.72	33.00	0.644
Bottom Side	189/836.4	GPRS(GMSK 2TS)	0.664	0.589	4.05	32.72	33.00	0.708
Back Side	128/824.2	GPRS(GMSK 2TS)	0.766	0.433	-0.10	32.55	33.00	0.850
Back Side	251/848.8	GPRS(GMSK 2TS)	0.661	0.394	0.39	32.76	33.00	0.699

NOTE: Hotspot SAR test results of GSM850

10.1.2. SAR measurement Result of GSM1900

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	661/1880	GPRS(GMSK 2TS)	0.086	0.057	0.99	28.18	28.50	0.093
Left Tilt 15 Degree	661/1880	GPRS(GMSK 2TS)	0.044	0.024	-2.97	28.18	28.50	0.047
Right Cheek	661/1880	GPRS(GMSK 2TS)	0.063	0.044	-3.38	28.18	28.50	0.068
Right Tilt 15 Degree	661/1880	GPRS(GMSK 2TS)	0.030	0.016	-1.34	28.18	28.50	0.032

NOTE: Head SAR test results of GSM1900

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	661/1880	GPRS(GMSK 2TS)	0.288	0.145	0.08	28.18	28.50	0.310
Back Side	661/1880	GPRS(GMSK 2TS)	0.356	0.181	1.83	28.18	28.50	0.383

NOTE: Body-Worn SAR test results of GSM1900

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	661/1880	GPRS(GMSK 2TS)	0.288	0.145	0.08	28.18	28.50	0.310
Back Side	661/1880	GPRS(GMSK 2TS)	0.356	0.181	1.83	28.18	28.50	0.383

		2TS)						
Left Side	661/1880	GPRS(GMSK 2TS)	0.261	0.137	2.53	28.18	28.50	0.281
Right Side	661/1880	GPRS(GMSK 2TS)	0.244	0.121	-2.18	28.18	28.50	0.263
Bottom Side	661/1880	GPRS(GMSK 2TS)	0.301	0.153	1.38	28.18	28.50	0.324

NOTE: Hotspot SAR test results of GSM1900

10.1.3. SAR measurement Result of WCDMA Band 2

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	9400/1880	RMC12.2K	0.065	0.039	3.30	22.68	23.00	0.070
Left Tilt 15 Degree	9400/1880	RMC12.2K	0.039	0.024	-4.54	22.68	23.00	0.042
Right Cheek	9400/1880	RMC12.2K	0.051	0.036	-4.49	22.68	23.00	0.055
Right Tilt 15 Degree	9400/1880	RMC12.2K	0.023	0.018	0.17	22.68	23.00	0.025

NOTE: Head SAR test results of WCDMA Band 2

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	9400/1880	RMC12.2K	0.513	0.304	-2.33	22.68	23.00	0.552
Back Side	9400/1880	RMC12.2K	0.651	0.383	-1.56	22.68	23.00	0.701

NOTE: Body-Worn SAR test results of WCDMA Band 2

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	9400/1880	RMC12.2K	0.513	0.304	-2.33	22.68	23.00	0.552
Back Side	9400/1880	RMC12.2K	0.651	0.383	-1.56	22.68	23.00	0.701
Left Side	9400/1880	RMC12.2K	0.466	0.277	-1.90	22.68	23.00	0.502
Right Side	9400/1880	RMC12.2K	0.351	0.205	-2.91	22.68	23.00	0.378
Bottom Side	9400/1880	RMC12.2K	0.520	0.307	-0.53	22.68	23.00	0.560

NOTE: Hotspot SAR test results of WCDMA Band 2

10.1.4. SAR measurement Result of WCDMA Band 4

Test Position	Test	Test Mode	SAR Value	Power	Conducted	Tune-up	Scaled
---------------	------	-----------	-----------	-------	-----------	---------	--------

of Head	channel /Freq.		(W/kg)		Drift (±5%)	power (dBm)	power (dBm)	SAR 1g (W/Kg)
			1g	10g				
Left Cheek	1413/1732.6	RMC12.2K	0.120	0.057	-0.22	23.43	23.50	0.122
Left Tilt 15 Degree	1413/1732.6	RMC12.2K	0.057	0.025	-4.58	23.43	23.50	0.058
Right Cheek	1413/1732.6	RMC12.2K	0.105	0.045	-3.19	23.43	23.50	0.107
Right Tilt 15 Degree	1413/1732.6	RMC12.2K	0.055	0.025	0.04	23.43	23.50	0.056

NOTE: Head SAR test results of WCDMA Band 4

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	1413/1732.6	RMC12.2K	0.723	0.361	-2.71	23.43	23.50	0.735
Back Side	1413/1732.6	RMC12.2K	1.000	0.446	0.79	23.43	23.50	1.016
Back Side	1312/1712.4	RMC12.2K	0.957	0.428	-0.54	23.23	23.50	1.018
Back Side	1513/1752.6	RMC12.2K	1.092	0.485	-0.51	23.36	23.50	1.128
Back Side - Repeated	1513/1752.6	RMC12.2K	0.996	0.428	0.04	23.36	23.50	1.028

NOTE: Body-Worn SAR test results of WCDMA Band 4

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	1413/1732.6	RMC12.2K	0.723	0.361	-2.71	23.43	23.50	0.735
Back Side	1413/1732.6	RMC12.2K	1.000	0.446	0.79	23.43	23.50	1.016
Left Side	1413/1732.6	RMC12.2K	0.687	0.349	-0.89	23.43	23.50	0.698
Right Side	1413/1732.6	RMC12.2K	0.617	0.313	-2.57	23.43	23.50	0.627
Bottom Side	1413/1732.6	RMC12.2K	0.755	0.387	3.33	23.43	23.50	0.767
Back Side	1312/1712.4	RMC12.2K	0.957	0.428	-0.54	23.23	23.50	1.018
Back Side	1513/1752.6	RMC12.2K	1.092	0.485	-0.51	23.36	23.50	1.128
Back Side Repeated	1513/1752.6	RMC12.2K	0.996	0.428	0.04	23.36	23.50	1.028

NOTE: Hotspot SAR test results of WCDMA Band 4

10.1.5. SAR measurement Result of WCDMA Band 5

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	4182/836.4	RMC12.2K	0.556	0.422	-0.06	24.07	24.50	0.614

Left Tilt 15 Degree	4182/836.4	RMC12.2K	0.268	0.205	3.59	24.07	24.50	0.296
Right Cheek	4182/836.4	RMC12.2K	0.445	0.334	-4.21	24.07	24.50	0.491
Right Tilt 15 Degree	4182/836.4	RMC12.2K	0.219	0.167	-0.07	24.07	24.50	0.242

NOTE: Head SAR test results of WCDMA Band 5

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	4182/836.4	RMC12.2K	0.426	0.327	2.46	24.07	24.50	0.470
Back Side	4182/836.4	RMC12.2K	0.708	0.538	-0.55	24.07	24.50	0.782

NOTE: Body-Worn SAR test results of WCDMA Band 5

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	4182/836.4	RMC12.2K	0.426	0.327	2.46	24.07	24.50	0.470
Back Side	4182/836.4	RMC12.2K	0.708	0.538	-0.55	24.07	24.50	0.782
Left Side	4182/836.4	RMC12.2K	0.334	0.253	-0.83	24.07	24.50	0.369
Right Side	4182/836.4	RMC12.2K	0.359	0.272	-0.49	24.07	24.50	0.396
Bottom Side	4182/836.4	RMC12.2K	0.531	0.402	2.99	24.07	24.50	0.586

NOTE: Hotspot SAR test results of WCDMA Band 5

10.1.6. SAR measurement Result of LTE Band 2

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	18900/1880	20M QPSK(1,49)	0.067	0.048	-4.18	22.30	23.00	0.079
Left Tilt 15 Degree	18900/1880	20M QPSK(1,49)	0.033	0.021	2.50	22.30	23.00	0.039
Right Cheek	18900/1880	20M QPSK(1,49)	0.051	0.038	2.91	22.30	23.00	0.060
Right Tilt 15 Degree	18900/1880	20M QPSK(1,49)	0.020	0.012	-1.47	22.30	23.00	0.023

50%RB								
Left Cheek	18900/1880	1.4M QPSK(3,1)	0.033	0.021	1.40	22.31	23.00	0.039
Left Tilt 15 Degree	18900/1880	1.4M QPSK(3,1)	0.019	0.015	-0.53	22.31	23.00	0.022
Right Cheek	18900/1880	1.4M QPSK(3,1)	0.027	0.019	2.62	22.31	23.00	0.032
Right Tilt 15 Degree	18900/1880	1.4M QPSK(3,1)	0.010	0.004	2.18	22.31	23.00	0.012

NOTE: Head SAR test results of LTE Band 2

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	18900/1880	20M QPSK(1,49)	0.601	0.343	1.79	22.30	23.00	0.706
Back Side	18900/1880	20M QPSK(1,49)	1.019	0.526	0.26	22.30	23.00	1.197
Back Side	18700/1860	20M QPSK(1,49)	1.040	0.556	-0.70	22.39	23.00	1.197
Back Side Repeated	18700/1860	20M QPSK(1,49)	1.001	0.531	0.06	22.39	23.00	1.152
Back Side	19100/1900	20M QPSK(1,49)	1.033	0.528	-1.66	22.53	23.00	1.151
50%RB								
Front Side	18900/1880	1.4M QPSK(3,1)	0.564	0.333	-1.46	22.31	23.00	0.661
Back Side	18900/1880	1.4M QPSK(3,1)	1.008	0.507	-0.79	22.31	23.00	1.182
Back Side	18607/1850.7	1.4M QPSK(3,1)	0.989	0.483	-0.79	22.72	23.00	1.055
Back Side	19193/1909.3	1.4M QPSK(3,1)	0.973	0.431	0.53	22.35	23.00	1.130
100%RB								
Back Side	18900/1880	20M QPSK(100,0)	0.647	0.411	-0.01	21.21	22.00	0.776

NOTE: Body-Worn SAR test results of LTE Band 2

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				

1RB								
Front Side	18900/1880	20M QPSK(1,49)	0.601	0.343	1.79	22.30	23.00	0.706
Back Side	18900/1880	20M QPSK(1,49)	1.019	0.526	0.26	22.30	23.00	1.197
Left Side	18900/1880	20M QPSK(1,49)	0.486	0.244	-3.87	22.30	23.00	0.571
Right Side	18900/1880	20M QPSK(1,49)	0.494	0.243	-3.63	22.30	23.00	0.580
Bottom Side	18900/1880	20M QPSK(1,49)	0.453	0.277	-3.06	22.30	23.00	0.532
Back Side	18700/1860	20M QPSK(1,49)	1.040	0.556	-0.70	22.39	23.00	1.197
Back Side Repeated	18700/1860	20M QPSK(1,49)	1.001	0.531	0.06	22.39	23.00	1.152
Back Side	19100/1900	20M QPSK(1,49)	1.033	0.528	-1.66	22.53	23.00	1.151
50%RB								
Front Side	18900/1880	1.4M QPSK(3,1)	0.564	0.333	-1.46	22.31	23.00	0.661
Back Side	18900/1880	1.4M QPSK(3,1)	1.008	0.507	-0.79	22.31	23.00	1.182
Left Side	18900/1880	1.4M QPSK(3,1)	0.474	0.285	2.53	22.31	23.00	0.556
Right Side	18900/1880	1.4M QPSK(3,1)	0.463	0.287	-3.44	22.31	23.00	0.543
Bottom Side	18900/1880	1.4M QPSK(3,1)	0.404	0.207	0.77	22.31	23.00	0.474
Back Side	18607/1850.7	1.4M QPSK(3,1)	0.989	0.483	-0.79	22.72	23.00	1.055
Back Side	19193/1909.3	1.4M QPSK(3,1)	0.973	0.431	0.53	22.35	23.00	1.130
100%RB								
Back Side	18900/1880	20M QPSK(100,0)	0.647	0.411	-0.01	21.21	22.00	0.776

NOTE: Hotspot SAR test results of LTE Band 2

10.1.7. SAR measurement Result of LTE Band 4

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left	20175/1732.5	20M QPSK(1,49)	0.068	0.047	-0.10	23.06	24.00	0.084

Cheek								
Left Tilt 15 Degree	20175/1732.5	20M QPSK(1,49)	0.033	0.028	-2.36	23.06	24.00	0.041
Right Cheek	20175/1732.5	20M QPSK(1,49)	0.058	0.046	-3.43	23.06	24.00	0.072
Right Tilt 15 Degree	20175/1732.5	20M QPSK(1,49)	0.020	0.017	0.10	23.06	24.00	0.025
50%RB								
Left Cheek	20175/1732.5	1.4M QPSK(3,0)	0.051	0.035	-0.71	23.53	24.00	0.057
Left Tilt 15 Degree	20175/1732.5	1.4M QPSK(3,0)	0.023	0.014	-0.75	23.53	24.00	0.026
Right Cheek	20175/1732.5	1.4M QPSK(3,0)	0.043	0.021	0.02	23.53	24.00	0.048
Right Tilt 15 Degree	20175/1732.5	1.4M QPSK(3,0)	0.022	0.012	-1.99	23.53	24.00	0.025

NOTE: Head SAR test results of LTE Band 4

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tuned power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20175/1732.5	20M QPSK(1,49)	0.455	0.185	0.03	23.06	24.00	0.565
Back Side	20175/1732.5	20M QPSK(1,49)	0.922	0.580	-1.23	23.06	24.00	1.145
Back Side	20050/1720	20M QPSK(1,49)	0.955	0.550	-0.85	23.20	24.00	1.148
Back Side	20300/1745	20M QPSK(1,49)	0.962	0.629	0.01	23.05	24.00	1.197
Back Side Repeated	20300/1745	20M QPSK(1,49)	0.959	0.623	0.13	23.05	24.00	1.193
50%RB								
Front Side	20175/1732.5	1.4M QPSK(3,0)	0.361	0.199	-2.38	23.53	24.00	0.402
Back Side	20175/1732.5	1.4M QPSK(3,0)	0.716	0.549	-3.73	23.53	24.00	0.798
100%RB								

Back Side	20175/1732. 5	20M QPSK(100,0)	0.633	0.506	3.97	21.99	23.00	0.799
-----------	------------------	--------------------	-------	-------	------	-------	-------	-------

NOTE: Body-Worn SAR test results of LTE Band 4

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conduc ted power (dBm)	Tune-u p power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20175/1732. 5	20M QPSK(1,49)	0.455	0.185	0.03	23.06	24.00	0.565
Back Side	20175/1732. 5	20M QPSK(1,49)	0.922	0.580	-1.23	23.06	24.00	1.145
Left Side	20175/1732. 5	20M QPSK(1,49)	0.340	0.172	3.58	23.06	24.00	0.422
Right Side	20175/1732. 5	20M QPSK(1,49)	0.332	0.175	-0.18	23.06	24.00	0.412
Bottom Side	20175/1732. 5	20M QPSK(1,49)	0.577	0.301	2.50	23.06	24.00	0.716
Back Side	20050/1720	20M QPSK(1,49)	0.955	0.550	-0.85	23.20	24.00	1.148
Back Side	20300/1745	20M QPSK(1,49)	0.962	0.629	0.01	23.05	24.00	1.197
Back Side Repeated	20300/1745	20M QPSK(1,49)	0.959	0.623	0.13	23.05	24.00	1.193
50%RB								
Front Side	20175/1732. 5	1.4M QPSK(3,0)	0.361	0.199	-2.38	23.53	24.00	0.402
Back Side	20175/1732. 5	1.4M QPSK(3,0)	0.716	0.549	-3.73	23.53	24.00	0.798
Left Side	20175/1732. 5	1.4M QPSK(3,0)	0.339	0.174	0.96	23.53	24.00	0.378
Right Side	20175/1732. 5	1.4M QPSK(3,0)	0.403	0.211	-4.75	23.53	24.00	0.449
Bottom Side	20175/1732. 5	1.4M QPSK(3,0)	0.412	0.216	-4.66	23.53	24.00	0.459
100%RB								
Back Side	20175/1732. 5	20M QPSK(100,0)	0.633	0.506	3.97	21.99	23.00	0.799

NOTE: Hotspot SAR test results of LTE Band 4

10.1.8. SAR measurement Result of LTE Band 5

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	20525/836.5	1.4M QPSK(1,2)	0.547	0.419	1.45	23.85	25.00	0.713
Left Tilt 15 Degree	20525/836.5	1.4M QPSK(1,2)	0.247	0.183	-3.54	23.85	25.00	0.322
Right Cheek	20525/836.5	1.4M QPSK(1,2)	0.484	0.374	4.20	23.85	25.00	0.631
Right Tilt 15 Degree	20525/836.5	1.4M QPSK(1,2)	0.231	0.176	0.16	23.85	25.00	0.301
50%RB								
Left Cheek	20525/836.5	1.4M QPSK(3,1)	0.489	0.374	-3.88	23.79	25.00	0.646
Left Tilt 15 Degree	20525/836.5	1.4M QPSK(3,1)	0.233	0.176	-1.07	23.79	25.00	0.308
Right Cheek	20525/836.5	1.4M QPSK(3,1)	0.432	0.333	-2.22	23.79	25.00	0.571
Right Tilt 15 Degree	20525/836.5	1.4M QPSK(3,1)	0.220	0.164	4.19	23.79	25.00	0.291

NOTE: Head SAR test results of LTE Band 5

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20525/836.5	1.4M QPSK(1,2)	0.236	0.176	-3.44	23.85	25.00	0.308
Back Side	20525/836.5	1.4M QPSK(1,2)	0.611	0.516	-0.05	23.85	25.00	0.796
50%RB								
Front Side	20525/836.5	1.4M QPSK(3,1)	0.201	0.153	1.58	23.79	25.00	0.266
Back Side	20525/836.5	1.4M QPSK(3,1)	0.556	0.426	-0.44	23.79	25.00	0.735

NOTE: Body-Worn SAR test results of LTE Band 5

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20525/836.5	1.4M QPSK(1,2)	0.236	0.176	-3.44	23.85	25.00	0.308
Back Side	20525/836.5	1.4M QPSK(1,2)	0.611	0.516	-0.05	23.85	25.00	0.796
Left Side	20525/836.5	1.4M QPSK(1,2)	0.257	0.193	4.01	23.85	25.00	0.335
Right Side	20525/836.5	1.4M QPSK(1,2)	0.284	0.214	-1.46	23.85	25.00	0.370
Bottom Side	20525/836.5	1.4M QPSK(1,2)	0.335	0.253	-0.79	23.85	25.00	0.437
50%RB								
Front Side	20525/836.5	1.4M QPSK(3,1)	0.201	0.153	1.58	23.79	25.00	0.266
Back Side	20525/836.5	1.4M QPSK(3,1)	0.556	0.426	-0.44	23.79	25.00	0.735
Left Side	20525/836.5	1.4M QPSK(3,1)	0.224	0.164	4.81	23.79	25.00	0.296
Right Side	20525/836.5	1.4M QPSK(3,1)	0.208	0.153	0.33	23.79	25.00	0.275
Bottom Side	20525/836.5	1.4M QPSK(3,1)	0.255	0.196	2.07	23.79	25.00	0.337

NOTE: Hotspot SAR test results of LTE Band 5

10.1.9. SAR measurement Result of LTE Band 7

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	21100/2535	20M QPSK(1,49)	0.348	0.186	4.68	22.25	23.00	0.414
Left Tilt 15 Degree	21100/2535	20M QPSK(1,49)	0.170	0.093	2.79	22.25	23.00	0.202

Right Cheek	21100/2535	20M QPSK(1,49)	0.314	0.167	3.25	22.25	23.00	0.373
Right Tilt 15 Degree	21100/2535	20M QPSK(1,49)	0.155	0.089	-1.07	22.25	23.00	0.184
50%RB								
Left Cheek	21100/2535	20M QPSK(50,24)	0.287	0.158	-1.28	21.08	22.00	0.355
Left Tilt 15 Degree	21100/2535	20M QPSK(50,24)	0.164	0.081	2.35	21.08	22.00	0.203
Right Cheek	21100/2535	20M QPSK(50,24)	0.274	0.149	-3.86	21.08	22.00	0.339
Right Tilt 15 Degree	21100/2535	20M QPSK(50,24)	0.180	0.091	0.93	21.08	22.00	0.222

NOTE: Head SAR test results of LTE Band 7

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	21100/2535	20M QPSK(1,49)	0.134	0.075	2.88	22.25	23.00	0.159
Back Side	21100/2535	20M QPSK(1,49)	0.155	0.087	0.56	22.25	23.00	0.184
50%RB								
Front Side	21100/2535	20M QPSK(50,24)	0.080	0.046	-2.51	21.08	22.00	0.099
Back Side	21100/2535	20M QPSK(50,24)	0.064	0.033	-3.12	21.08	22.00	0.079

NOTE: Body-Worn SAR test results of LTE Band 7

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conduc ted power (dBm)	Tune-u p power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	21100/2535	20M QPSK(1,49)	0.134	0.075	2.88	22.25	23.00	0.159
Back Side	21100/2535	20M	0.155	0.087	0.56	22.25	23.00	0.184

		QPSK(1,49)						
Left Side	21100/2535	20M QPSK(1,49)	0.120	0.064	-2.56	22.25	23.00	0.143
Right Side	21100/2535	20M QPSK(1,49)	0.117	0.065	2.35	22.25	23.00	0.139
Bottom Side	21100/2535	20M QPSK(1,49)	0.097	0.056	3.42	22.25	23.00	0.115
50%RB								
Front Side	21100/2535	20M QPSK(50,24)	0.080	0.046	-2.51	21.08	22.00	0.099
Back Side	21100/2535	20M QPSK(50,24)	0.064	0.033	-3.12	21.08	22.00	0.079
Left Side	21100/2535	20M QPSK(50,24)	0.051	0.029	-1.39	21.08	22.00	0.063
Right Side	21100/2535	20M QPSK(50,24)	0.050	0.023	-0.96	21.08	22.00	0.062
Bottom Side	21100/2535	20M QPSK(50,24)	0.066	0.036	1.20	21.08	22.00	0.082

NOTE: Hotspot SAR test results of LTE Band 7

10.1.10. SAR measurement Result of LTE Band 12

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	23095/707.5	10M QPSK(1,24)	0.325	0.265	1.08	23.43	24.00	0.371
Left Tilt 15 Degree	23095/707.5	10M QPSK(1,24)	0.166	0.131	-1.14	23.43	24.00	0.189
Right Cheek	23095/707.5	10M QPSK(1,24)	0.296	0.232	3.82	23.43	24.00	0.338
Right Tilt 15 Degree	23095/707.5	10M QPSK(1,24)	0.147	0.114	-1.98	23.43	24.00	0.168
50%RB								
Left Cheek	23095/707.5	1.4M QPSK(3,1)	0.302	0.233	3.59	23.39	24.00	0.348
Left Tilt	23095/707.5	1.4M QPSK(3,1)	0.158	0.125	0.83	23.39	24.00	0.182

15 Degree								
Right Cheek	23095/707.5	1.4M QPSK(3,1)	0.277	0.216	-1.12	23.39	24.00	0.319
Right Tilt 15 Degree	23095/707.5	1.4M QPSK(3,1)	0.122	0.093	2.91	23.39	24.00	0.140

NOTE: Head SAR test results of LTE Band 12

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	23095/707.5	10M QPSK(1,24)	0.206	0.161	-0.19	23.43	24.00	0.235
Back Side	23095/707.5	10M QPSK(1,24)	0.565	0.445	-1.66	23.43	24.00	0.644
50%RB								
Front Side	23095/707.5	1.4M QPSK(3,1)	0.200	0.157	-1.47	23.39	24.00	0.230
Back Side	23095/707.5	1.4M QPSK(3,1)	0.544	0.423	-2.15	23.39	24.00	0.626

NOTE: Body-Worn SAR test results of LTE Band 12

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	23095/707.5	10M QPSK(1,24)	0.206	0.161	-0.19	23.43	24.00	0.235
Back Side	23095/707.5	10M QPSK(1,24)	0.565	0.445	-1.66	23.43	24.00	0.644
Left Side	23095/707.5	10M QPSK(1,24)	0.221	0.173	3.58	23.43	24.00	0.252
Right Side	23095/707.5	10M QPSK(1,24)	0.213	0.166	-0.18	23.43	24.00	0.243
Bottom Side	23095/707.5	10M QPSK(1,24)	0.301	0.233	2.50	23.43	24.00	0.343
50%RB								
Front Side	23095/707.5	1.4M QPSK(3,1)	0.200	0.157	-1.47	23.39	24.00	0.230
Back	23095/707.5	1.4M QPSK(3,1)	0.544	0.423	-2.15	23.39	24.00	0.626

Side								
Left Side	23095/707.5	1.4M QPSK(3,1)	0.208	0.163	-3.31	23.39	24.00	0.239
Right Side	23095/707.5	1.4M QPSK(3,1)	0.203	0.156	-0.46	23.39	24.00	0.234
Bottom Side	23095/707.5	1.4M QPSK(3,1)	0.266	0.208	-2.98	23.39	24.00	0.306

NOTE: Hotspot SAR test results of LTE Band 12

10.1.11. SAR measurement Result of LTE Band 17

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	23790/710	10M QPSK(1,24)	0.336	0.274	1.00	23.91	24.00	0.343
Left Tilt 15 Degree	23790/710	10M QPSK(1,24)	0.166	0.132	4.48	23.91	24.00	0.169
Right Cheek	23790/710	10M QPSK(1,24)	0.308	0.250	-1.82	23.91	24.00	0.314
Right Tilt 15 Degree	23790/710	10M QPSK(1,24)	0.155	0.125	-4.17	23.91	24.00	0.158
50%RB								
Left Cheek	23790/710	10M QPSK(25,12)	0.301	0.244	-2.29	22.88	23.00	0.309
Left Tilt 15 Degree	23790/710	10M QPSK(25,12)	0.155	0.123	-3.80	22.88	23.00	0.159
Right Cheek	23790/710	10M QPSK(25,12)	0.288	0.233	-0.31	22.88	23.00	0.296
Right Tilt 15 Degree	23790/710	10M QPSK(25,12)	0.144	0.116	-1.41	22.88	23.00	0.148

NOTE: Head SAR test results of LTE Band 17

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g
			1g	10g				

								(W/Kg)
1RB								
Front Side	23790/710	10M QPSK(1,24)	0.199	0.155	-2.38	23.91	24.00	0.203
Back Side	23790/710	10M QPSK(1,24)	0.448	0.353	-1.22	23.91	24.00	0.457
50%RB								
Front Side	23790/710	10M QPSK(25,12)	0.188	0.147	0.46	22.88	23.00	0.193
Back Side	23790/710	10M QPSK(25,12)	0.420	0.331	3.20	22.88	23.00	0.432

NOTE: Body-Worn SAR test results of LTE Band 17

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	23790/710	10M QPSK(1,24)	0.199	0.155	-2.38	23.91	24.00	0.203
Back Side	23790/710	10M QPSK(1,24)	0.448	0.353	-1.22	23.91	24.00	0.457
Left Side	23790/710	10M QPSK(1,24)	0.156	0.127	-1.82	23.91	24.00	0.159
Right Side	23790/710	10M QPSK(1,24)	0.166	0.132	-4.17	23.91	24.00	0.169
Bottom Side	23790/710	10M QPSK(1,24)	0.213	0.166	4.76	23.91	24.00	0.217
50%RB								
Front Side	23790/710	10M QPSK(25,12)	0.188	0.147	0.46	22.88	23.00	0.193
Back Side	23790/710	10M QPSK(25,12)	0.420	0.331	3.20	22.88	23.00	0.432
Left Side	23790/710	10M QPSK(25,12)	0.142	0.114	-3.67	22.88	23.00	0.146
Right Side	23790/710	10M QPSK(25,12)	0.123	0.097	3.61	22.88	23.00	0.126
Bottom Side	23790/710	10M QPSK(25,12)	0.198	0.153	3.94	22.88	23.00	0.204

NOTE: Hotspot SAR test results of LTE Band 17

10.1.12. SAR measurement Result of WLAN 2.4G

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	6/2437	802.11 b	0.152	0.097	0.22	15.53	16.00	0.169
Left Tilt 15 Degree	6/2437	802.11 b	0.077	0.049	-0.23	15.53	16.00	0.086
Right Cheek	6/2437	802.11 b	0.112	0.071	4.22	15.53	16.00	0.125
Right Tilt 15 Degree	6/2437	802.11 b	0.053	0.033	3.55	15.53	16.00	0.059

NOTE: Head SAR test results of WLAN 2.4G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	6/2437	802.11 b	0.086	0.049	2.45	15.53	16.00	0.096
Back Side	6/2437	802.11 b	0.156	0.090	-1.26	15.53	16.00	0.174

NOTE: Body-Worn SAR test results of WLAN 2.4G

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	6/2437	802.11 b	0.086	0.049	2.45	15.53	16.00	0.096
Back Side	6/2437	802.11 b	0.156	0.090	-1.26	15.53	16.00	0.174
Left Side	6/2437	802.11 b	0.096	0.054	1.77	15.53	16.00	0.107
Top Side	6/2437	802.11 b	0.101	0.057	2.15	15.53	16.00	0.113

NOTE: Hotspot SAR test results of WLAN 2.4G

10.2. SAR Summation Scenario

Per KDB 447498 D01, simultaneous transmission SAR is compliant if,

- 1) Scalar SAR summation $< 1.6\text{W/kg}$.
- 2) $\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan. If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 850	WLAN 2.4G			
Head	Left Cheek	0.702	0.169	0.871	N/A	N/A
	Left Tilt 15 Degree	0.508	0.086	0.594	N/A	N/A
	Right Cheek	0.604	0.125	0.728	N/A	N/A
	Right Tilt 15 Degree	0.451	0.059	0.510	N/A	N/A
Body-Worn	Front Side	0.752	0.096	0.848	N/A	N/A
	Back Side	1.094	0.174	1.268	N/A	N/A
Hotspot	Front Side	0.752	0.096	0.848	N/A	N/A
	Back Side	1.094	0.174	1.268	N/A	N/A
	Left Side	0.599	0.107	0.706	N/A	N/A
	Right Side	0.644	N/A	0.644	N/A	N/A
	Top Side	N/A	0.113	0.113	N/A	N/A
	Bottom Side	0.708	N/A	0.708	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM850 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 1900	WLAN 2.4G			
Head	Left Cheek	0.093	0.169	0.262	N/A	N/A
	Left Tilt 15 Degree	0.047	0.086	0.133	N/A	N/A
	Right Cheek	0.068	0.125	0.193	N/A	N/A
	Right Tilt 15 Degree	0.032	0.059	0.091	N/A	N/A
Body-Worn	Front Side	0.310	0.096	0.406	N/A	N/A
	Back Side	0.383	0.174	0.557	N/A	N/A
Hotspot	Front Side	0.310	0.096	0.406	N/A	N/A
	Back Side	0.383	0.174	0.557	N/A	N/A
	Left Side	0.281	0.107	0.388	N/A	N/A
	Right Side	0.263	N/A	0.263	N/A	N/A
	Top Side	N/A	0.113	0.113	N/A	N/A
	Bottom Side	0.324	N/A	0.324	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM1900 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 2	WLAN 2.4G			
Head	Left Cheek	0.070	0.169	0.239	N/A	N/A
	Left Tilt 15 Degree	0.042	0.086	0.128	N/A	N/A
	Right Cheek	0.055	0.125	0.180	N/A	N/A
	Right Tilt 15 Degree	0.025	0.059	0.084	N/A	N/A
Body-Worn	Front Side	0.552	0.096	0.648	N/A	N/A
	Back Side	0.701	0.174	0.875	N/A	N/A
Hotspot	Front Side	0.552	0.096	0.648	N/A	N/A
	Back Side	0.701	0.174	0.875	N/A	N/A
	Left Side	0.502	0.107	0.609	N/A	N/A
	Right Side	0.378	N/A	0.378	N/A	N/A
	Top Side	N/A	0.113	0.113	N/A	N/A
	Bottom Side	0.560	N/A	0.560	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 2 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 4	WLAN 2.4G			
Head	Left Cheek	0.122	0.169	0.291	N/A	N/A
	Left Tilt 15 Degree	0.058	0.086	0.144	N/A	N/A
	Right Cheek	0.107	0.125	0.232	N/A	N/A
	Right Tilt 15 Degree	0.056	0.059	0.115	N/A	N/A
Body-Worn	Front Side	0.735	0.096	0.831	N/A	N/A
	Back Side	1.128	0.174	1.302	N/A	N/A
Hotspot	Front Side	0.735	0.096	0.831	N/A	N/A
	Back Side	1.128	0.174	1.302	N/A	N/A
	Left Side	0.698	0.107	0.805	N/A	N/A
	Right Side	0.627	N/A	0.627	N/A	N/A
	Top Side	N/A	0.113	0.113	N/A	N/A
	Bottom Side	0.767	N/A	0.767	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 4 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 5	WLAN 2.4G			
Head	Left Cheek	0.614	0.169	0.783	N/A	N/A
	Left Tilt 15	0.296	0.086	0.382	N/A	N/A

	Degree					
	Right Cheek	0.491	0.125	0.616	N/A	N/A
	Right Tilt 15 Degree	0.242	0.059	0.301	N/A	N/A
Body-Worn	Front Side	0.470	0.096	0.566	N/A	N/A
	Back Side	0.782	0.174	0.956	N/A	N/A
Hotspot	Front Side	0.470	0.096	0.566	N/A	N/A
	Back Side	0.782	0.174	0.956	N/A	N/A
	Left Side	0.369	0.107	0.476	N/A	N/A
	Right Side	0.396	N/A	0.396	N/A	N/A
	Top Side	N/A	0.113	0.113	N/A	N/A
	Bottom Side	0.586	N/A	0.586	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 5 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 2	WLAN 2.4G			
Head	Left Cheek	0.079	0.169	0.248	N/A	N/A
	Left Tilt 15 Degree	0.039	0.086	0.125	N/A	N/A
	Right Cheek	0.060	0.125	0.185	N/A	N/A
	Right Tilt 15 Degree	0.023	0.059	0.083	N/A	N/A
Body-Worn	Front Side	0.706	0.096	0.802	N/A	N/A
	Back Side	1.197	0.174	1.371	N/A	N/A
Hotspot	Front Side	0.706	0.096	0.802	N/A	N/A
	Back Side	1.197	0.174	1.371	N/A	N/A
	Left Side	0.571	0.107	0.678	N/A	N/A
	Right Side	0.580	N/A	0.580	N/A	N/A
	Top Side	N/A	0.113	0.113	N/A	N/A
	Bottom Side	0.532	N/A	0.532	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 2 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 4	WLAN 2.4G			
Head	Left Cheek	0.084	0.169	0.254	N/A	N/A
	Left Tilt 15 Degree	0.041	0.086	0.127	N/A	N/A
	Right Cheek	0.072	0.125	0.197	N/A	N/A
	Right Tilt 15 Degree	0.025	0.059	0.084	N/A	N/A
Body-Worn	Front Side	0.565	0.096	0.661	N/A	N/A
	Back Side	1.197	0.174	1.371	N/A	N/A
Hotspot	Front Side	0.565	0.096	0.661	N/A	N/A
	Back Side	1.197	0.174	1.371	N/A	N/A

	Left Side	0.422	0.107	0.529	N/A	N/A
	Right Side	0.449	N/A	0.449	N/A	N/A
	Top Side	N/A	0.113	0.113	N/A	N/A
	Bottom Side	0.716	N/A	0.716	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 4 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 5	WLAN 2.4G			
Head	Left Cheek	0.713	0.169	0.882	N/A	N/A
	Left Tilt 15 Degree	0.322	0.086	0.408	N/A	N/A
	Right Cheek	0.631	0.125	0.756	N/A	N/A
	Right Tilt 15 Degree	0.301	0.059	0.360	N/A	N/A
Body-Worn	Front Side	0.308	0.096	0.403	N/A	N/A
	Back Side	0.796	0.174	0.970	N/A	N/A
Hotspot	Front Side	0.308	0.096	0.403	N/A	N/A
	Back Side	0.796	0.174	0.970	N/A	N/A
	Left Side	0.335	0.107	0.442	N/A	N/A
	Right Side	0.370	N/A	0.370	N/A	N/A
	Top Side	N/A	0.113	0.113	N/A	N/A
	Bottom Side	0.437	N/A	0.437	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 5 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 7	WLAN 2.4G			
Head	Left Cheek	0.414	0.169	0.583	N/A	N/A
	Left Tilt 15 Degree	0.203	0.086	0.289	N/A	N/A
	Right Cheek	0.373	0.125	0.498	N/A	N/A
	Right Tilt 15 Degree	0.222	0.059	0.281	N/A	N/A
Body-Worn	Front Side	0.159	0.096	0.255	N/A	N/A
	Back Side	0.184	0.174	0.358	N/A	N/A
Hotspot	Front Side	0.159	0.096	0.255	N/A	N/A
	Back Side	0.184	0.174	0.358	N/A	N/A
	Left Side	0.143	0.107	0.250	N/A	N/A
	Right Side	0.139	N/A	0.139	N/A	N/A
	Top Side	N/A	0.113	0.113	N/A	N/A
	Bottom Side	0.115	N/A	0.115	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 7 and WLAN 2.4G.

Test Position	Scaled SAR _{MAX}		Σ 1-g SAR	SPLSR	Remark
---------------	---------------------------	--	------------------	-------	--------

		LTE Band 12	WLAN 2.4G	(W/Kg)		
Head	Left Cheek	0.371	0.169	0.540	N/A	N/A
	Left Tilt 15 Degree	0.189	0.086	0.275	N/A	N/A
	Right Cheek	0.338	0.125	0.462	N/A	N/A
	Right Tilt 15 Degree	0.168	0.059	0.227	N/A	N/A
Body-Worn	Front Side	0.235	0.096	0.331	N/A	N/A
	Back Side	0.644	0.174	0.818	N/A	N/A
Hotspot	Front Side	0.235	0.096	0.331	N/A	N/A
	Back Side	0.644	0.174	0.818	N/A	N/A
	Left Side	0.252	0.107	0.359	N/A	N/A
	Right Side	0.243	N/A	0.243	N/A	N/A
	Top Side	N/A	0.113	0.113	N/A	N/A
	Bottom Side	0.343	N/A	0.343	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 12 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 17	WLAN 2.4G			
Head	Left Cheek	0.343	0.169	0.512	N/A	N/A
	Left Tilt 15 Degree	0.169	0.086	0.255	N/A	N/A
	Right Cheek	0.314	0.125	0.439	N/A	N/A
	Right Tilt 15 Degree	0.158	0.059	0.217	N/A	N/A
Body-Worn	Front Side	0.203	0.096	0.299	N/A	N/A
	Back Side	0.457	0.174	0.631	N/A	N/A
Hotspot	Front Side	0.203	0.096	0.299	N/A	N/A
	Back Side	0.457	0.174	0.631	N/A	N/A
	Left Side	0.159	0.107	0.266	N/A	N/A
	Right Side	0.169	N/A	0.169	N/A	N/A
	Top Side	N/A	0.113	0.113	N/A	N/A
	Bottom Side	0.217	N/A	0.217	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 17 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 850	Bluetooth			
Head	Left Cheek	0.702	0.067	0.768	N/A	N/A
	Left Tilt 15 Degree	0.508	0.067	0.574	N/A	N/A
	Right Cheek	0.604	0.067	0.670	N/A	N/A

	Right Tilt 15 Degree	0.451	0.067	0.518	N/A	N/A
Body-Worn	Front Side	0.752	0.033	0.785	N/A	N/A
	Back Side	1.094	0.033	1.128	N/A	N/A
Hotspot	Front Side	0.752	0.033	0.785	N/A	N/A
	Back Side	1.094	0.033	1.128	N/A	N/A
	Left Side	0.599	0.033	0.633	N/A	N/A
	Right Side	0.644	N/A	0.644	N/A	N/A
	Top Side	N/A	0.033	0.033	N/A	N/A
	Bottom Side	0.708	N/A	0.708	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM850 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 1900	Bluetooth			
Head	Left Cheek	0.093	0.067	0.159	N/A	N/A
	Left Tilt 15 Degree	0.047	0.067	0.114	N/A	N/A
	Right Cheek	0.068	0.067	0.134	N/A	N/A
	Right Tilt 15 Degree	0.032	0.067	0.099	N/A	N/A
Body-Worn	Front Side	0.310	0.033	0.343	N/A	N/A
	Back Side	0.383	0.033	0.417	N/A	N/A
Hotspot	Front Side	0.310	0.033	0.343	N/A	N/A
	Back Side	0.383	0.033	0.417	N/A	N/A
	Left Side	0.281	0.033	0.314	N/A	N/A
	Right Side	0.263	N/A	0.263	N/A	N/A
	Top Side	N/A	0.033	0.033	N/A	N/A
	Bottom Side	0.324	N/A	0.324	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM1900 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 2	Bluetooth			
Head	Left Cheek	0.070	0.067	0.137	N/A	N/A
	Left Tilt 15 Degree	0.042	0.067	0.109	N/A	N/A
	Right Cheek	0.055	0.067	0.121	N/A	N/A
	Right Tilt 15 Degree	0.025	0.067	0.091	N/A	N/A
Body-Worn	Front Side	0.552	0.033	0.586	N/A	N/A
	Back Side	0.701	0.033	0.734	N/A	N/A
Hotspot	Front Side	0.552	0.033	0.586	N/A	N/A
	Back Side	0.701	0.033	0.734	N/A	N/A
	Left Side	0.502	0.033	0.535	N/A	N/A

	Right Side	0.378	N/A	0.378	N/A	N/A
	Top Side	N/A	0.033	0.033	N/A	N/A
	Bottom Side	0.560	N/A	0.560	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 2 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 4	Bluetooth			
Head	Left Cheek	0.122	0.067	0.189	N/A	N/A
	Left Tilt 15 Degree	0.058	0.067	0.124	N/A	N/A
	Right Cheek	0.107	0.067	0.173	N/A	N/A
	Right Tilt 15 Degree	0.056	0.067	0.122	N/A	N/A
Body-Worn	Front Side	0.735	0.033	0.768	N/A	N/A
	Back Side	1.128	0.033	1.161	N/A	N/A
Hotspot	Front Side	0.735	0.033	0.768	N/A	N/A
	Back Side	1.128	0.033	1.161	N/A	N/A
	Left Side	0.698	0.033	0.731	N/A	N/A
	Right Side	0.627	N/A	0.627	N/A	N/A
	Top Side	N/A	0.033	0.033	N/A	N/A
	Bottom Side	0.767	N/A	0.767	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 4 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 5	Bluetooth			
Head	Left Cheek	0.614	0.067	0.680	N/A	N/A
	Left Tilt 15 Degree	0.296	0.067	0.362	N/A	N/A
	Right Cheek	0.491	0.067	0.558	N/A	N/A
	Right Tilt 15 Degree	0.242	0.067	0.308	N/A	N/A
Body-Worn	Front Side	0.470	0.033	0.504	N/A	N/A
	Back Side	0.782	0.033	0.815	N/A	N/A
Hotspot	Front Side	0.470	0.033	0.504	N/A	N/A
	Back Side	0.782	0.033	0.815	N/A	N/A
	Left Side	0.369	0.033	0.402	N/A	N/A
	Right Side	0.396	N/A	0.396	N/A	N/A
	Top Side	N/A	0.033	0.033	N/A	N/A
	Bottom Side	0.586	N/A	0.586	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 5 and Bluetooth.

Test Position	Scaled SAR _{MAX}		Σ 1-g SAR	SPLSR	Remark
---------------	---------------------------	--	------------------	-------	--------

		LTE Band 2	Bluetooth	(W/Kg)		
Head	Left Cheek	0.079	0.067	0.145	N/A	N/A
	Left Tilt 15 Degree	0.039	0.067	0.105	N/A	N/A
	Right Cheek	0.060	0.067	0.126	N/A	N/A
	Right Tilt 15 Degree	0.023	0.067	0.090	N/A	N/A
Body-Worn	Front Side	0.706	0.033	0.739	N/A	N/A
	Back Side	1.197	0.033	1.230	N/A	N/A
Hotspot	Front Side	0.706	0.033	0.739	N/A	N/A
	Back Side	1.197	0.033	1.230	N/A	N/A
	Left Side	0.571	0.033	0.604	N/A	N/A
	Right Side	0.580	N/A	0.580	N/A	N/A
	Top Side	N/A	0.033	0.033	N/A	N/A
	Bottom Side	0.532	N/A	0.532	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 2 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 4	Bluetooth			
Head	Left Cheek	0.084	0.067	0.151	N/A	N/A
	Left Tilt 15 Degree	0.041	0.067	0.108	N/A	N/A
	Right Cheek	0.072	0.067	0.139	N/A	N/A
	Right Tilt 15 Degree	0.025	0.067	0.091	N/A	N/A
Body-Worn	Front Side	0.565	0.033	0.598	N/A	N/A
	Back Side	1.197	0.033	1.231	N/A	N/A
Hotspot	Front Side	0.565	0.033	0.598	N/A	N/A
	Back Side	1.197	0.033	1.231	N/A	N/A
	Left Side	0.422	0.033	0.455	N/A	N/A
	Right Side	0.449	N/A	0.449	N/A	N/A
	Top Side	N/A	0.033	0.033	N/A	N/A
	Bottom Side	0.716	N/A	0.716	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 4 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 5	Bluetooth			
Head	Left Cheek	0.713	0.067	0.779	N/A	N/A
	Left Tilt 15 Degree	0.322	0.067	0.388	N/A	N/A
	Right Cheek	0.631	0.067	0.697	N/A	N/A
	Right Tilt 15 Degree	0.301	0.067	0.368	N/A	N/A

Body-Worn	Front Side	0.308	0.033	0.341	N/A	N/A
	Back Side	0.796	0.033	0.830	N/A	N/A
Hotspot	Front Side	0.308	0.033	0.341	N/A	N/A
	Back Side	0.796	0.033	0.830	N/A	N/A
	Left Side	0.335	0.033	0.368	N/A	N/A
	Right Side	0.370	N/A	0.370	N/A	N/A
	Top Side	N/A	0.033	0.033	N/A	N/A
	Bottom Side	0.437	N/A	0.437	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 5 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 7	Bluetooth			
Head	Left Cheek	0.414	0.067	0.480	N/A	N/A
	Left Tilt 15 Degree	0.203	0.067	0.270	N/A	N/A
	Right Cheek	0.373	0.067	0.440	N/A	N/A
	Right Tilt 15 Degree	0.222	0.067	0.289	N/A	N/A
Body-Worn	Front Side	0.159	0.033	0.193	N/A	N/A
	Back Side	0.184	0.033	0.217	N/A	N/A
Hotspot	Front Side	0.159	0.033	0.193	N/A	N/A
	Back Side	0.184	0.033	0.217	N/A	N/A
	Left Side	0.143	0.033	0.176	N/A	N/A
	Right Side	0.139	N/A	0.139	N/A	N/A
	Top Side	N/A	0.033	0.033	N/A	N/A
	Bottom Side	0.115	N/A	0.115	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 7 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 12	Bluetooth			
Head	Left Cheek	0.371	0.067	0.437	N/A	N/A
	Left Tilt 15 Degree	0.189	0.067	0.256	N/A	N/A
	Right Cheek	0.338	0.067	0.404	N/A	N/A
	Right Tilt 15 Degree	0.168	0.067	0.234	N/A	N/A
Body-Worn	Front Side	0.235	0.033	0.268	N/A	N/A
	Back Side	0.644	0.033	0.678	N/A	N/A
Hotspot	Front Side	0.235	0.033	0.268	N/A	N/A
	Back Side	0.644	0.033	0.678	N/A	N/A
	Left Side	0.252	0.033	0.285	N/A	N/A
	Right Side	0.243	N/A	0.243	N/A	N/A

	Top Side	N/A	0.033	0.033	N/A	N/A
	Bottom Side	0.343	N/A	0.343	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 12 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 17	Bluetooth			
Head	Left Cheek	0.343	0.067	0.410	N/A	N/A
	Left Tilt 15 Degree	0.169	0.067	0.236	N/A	N/A
	Right Cheek	0.314	0.067	0.381	N/A	N/A
	Right Tilt 15 Degree	0.158	0.067	0.225	N/A	N/A
Body-Worn	Front Side	0.203	0.033	0.236	N/A	N/A
	Back Side	0.457	0.033	0.491	N/A	N/A
Hotspot	Front Side	0.203	0.033	0.236	N/A	N/A
	Back Side	0.457	0.033	0.491	N/A	N/A
	Left Side	0.159	0.033	0.193	N/A	N/A
	Right Side	0.169	N/A	0.169	N/A	N/A
	Top Side	N/A	0.033	0.033	N/A	N/A
	Bottom Side	0.217	N/A	0.217	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 17 and Bluetooth.

11. Appendix A. Photo documentation

Refer to appendix Test Setup photo---SAR

12. Appendix B. System Check Plots

Table of contents
MEASUREMENT 1 System Performance Check - SID750 - Head
MEASUREMENT 2 System Performance Check - SID750 - Body
MEASUREMENT 3 System Performance Check - SID835 - Head
MEASUREMENT 4 System Performance Check - SID835 - Body
MEASUREMENT 5 System Performance Check - SID1800 - Head
MEASUREMENT 6 System Performance Check - SID1800 - Body
MEASUREMENT 7 System Performance Check - SID1900 - Head
MEASUREMENT 8 System Performance Check - SID1900 - Body
MEASUREMENT 9 System Performance Check - SID2450 - Head
MEASUREMENT 10 System Performance Check - SID2450 - Body
MEASUREMENT 11 System Performance Check - SID2600 - Head
MEASUREMENT 12 System Performance Check - SID2600 - Body

MEASUREMENT 1


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW750</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	750.000000
Relative permittivity (real part)	41.083162
Relative permittivity (imaginary part)	22.071263
Conductivity (S/m)	0.919583
Variation (%)	-3.910000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=3.00

SAR Peak: 1.30 W/Kg

SAR 10g (W/Kg)	0.553218
SAR 1g (W/Kg)	0.851962



MEASUREMENT 2


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW750</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	750.000000
Relative permittivity (real part)	55.310248
Relative permittivity (imaginary part)	23.273842
Conductivity (S/m)	0.972518
Variation (%)	1.280000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=3.00

SAR Peak: 1.30 W/kg

SAR 10g (W/Kg)	0.588281
SAR 1g (W/Kg)	0.881463



MEASUREMENT 3


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW835</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	40.553541
Relative permittivity (imaginary part)	20.110613
Conductivity (S/m)	0.931742
Variation (%)	3.190000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=3.00

SAR Peak: 1.30 W/kg

SAR 10g (W/Kg)	0.607966
SAR 1g (W/Kg)	0.951235



MEASUREMENT 4


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW835</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	54.281111
Relative permittivity (imaginary part)	21.783359
Conductivity (S/m)	1.001236
Variation (%)	-4.330000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 1.23 W/kg

SAR 10g (W/Kg)	0.641123
SAR 1g (W/Kg)	0.981356



MEASUREMENT 5


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1800.000000
Relative permittivity (real part)	38.651237
Relative permittivity (imaginary part)	13.963229
Conductivity (S/m)	1.402367
Variation (%)	-3.16000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 6.82 W/kg

SAR 10g (W/Kg)	2.001397
SAR 1g (W/Kg)	3.809451



MEASUREMENT 6


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1800.000000
Relative permittivity (real part)	53.193510
Relative permittivity (imaginary part)	15.674016
Conductivity (S/m)	1.573096
Variation (%)	3.220000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 6.82 W/kg

SAR 10g (W/Kg)	2.049379
SAR 1g (W/Kg)	3.818268



MEASUREMENT 7


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative permittivity (real part)	40.981287
Relative permittivity (imaginary part)	13.773008
Conductivity (S/m)	1.450336
Variation (%)	-1.430000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=2.00

SAR Peak: 6.70 W/kg

SAR 10g (W/Kg)	2.063456
SAR 1g (W/Kg)	3.895365



MEASUREMENT 8


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative permittivity (real part)	52.523335
Relative permittivity (imaginary part)	14.943503
Conductivity (S/m)	1.582566
Variation (%)	2.660000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=2.00

SAR Peak: 6.39 W/kg

SAR 10g (W/Kg)	2.041329
SAR 1g (W/Kg)	3.922402



MEASUREMENT 9


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2450</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2450.000000
Relative permittivity (real part)	38.781421
Relative permittivity (imaginary part)	13.612631
Conductivity (S/m)	1.852663
Variation (%)	-3.350000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=1.00

SAR Peak: 8.14 W/kg

SAR 10g (W/Kg)	2.409375
SAR 1g (W/Kg)	5.371435



MEASUREMENT 10


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2450</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2450.000000
Relative permittivity (real part)	52.091497
Relative permittivity (imaginary part)	14.993566
Conductivity (S/m)	2.039816
Variation (%)	3.420000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=1.00

SAR Peak: 8.46 W/kg

SAR 10g (W/Kg)	2.403285
SAR 1g (W/Kg)	5.293270



MEASUREMENT 11


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2600</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative permittivity (real part)	38.462638
Relative permittivity (imaginary part)	13.983997
Conductivity (S/m)	2.023631
Variation (%)	-4.040000

SURFACE SAR





VOLUME SAR



Maximum location: X=-1.00, Y=2.00

SAR Peak: 9.07 W/kg

SAR 10g (W/Kg)	2.455205
SAR 1g (W/Kg)	5.564867



MEASUREMENT 12


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2600</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative permittivity (real part)	52.672866
Relative permittivity (imaginary part)	15.340101
Conductivity (S/m)	2.223465
Variation (%)	-1.220000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=2.00

SAR Peak: 9.99 W/kg

SAR 10g (W/Kg)	2.378324
SAR 1g (W/Kg)	5.243188



13. Appendix C. Plots of High SAR Measurement

Table of contents
MEASUREMENT 1 GSM 850 Head
MEASUREMENT 2 GSM 850 Body
MEASUREMENT 3 GSM 1900 Head
MEASUREMENT 4 GSM 1900 Body
MEASUREMENT 5 WCDMA Band 2 Head
MEASUREMENT 6 WCDMA Band 2 Body
MEASUREMENT 7 WCDMA Band 4 Head
MEASUREMENT 8 WCDMA Band 4 Body
MEASUREMENT 9 WCDMA Band 5 Head
MEASUREMENT 10 WCDMA Band 5 Body
MEASUREMENT 11 WLAN 2.4G Head
MEASUREMENT 12 WLAN 2.4G Body
MEASUREMENT 13 LTE Band 2 Head
MEASUREMENT 14 LTE Band 2 Body
MEASUREMENT 15 LTE Band 4 Head
MEASUREMENT 16 LTE Band 4 Body
MEASUREMENT 17 LTE Band 5 Head
MEASUREMENT 18 LTE Band 5 Body
MEASUREMENT 19 LTE Band 7 Head
MEASUREMENT 20 LTE Band 7 Body
MEASUREMENT 21 LTE Band 12 Head
MEASUREMENT 22 LTE Band 12 Body
MEASUREMENT 23 LTE Band 17 Head
MEASUREMENT 24 LTE Band 17 Body

MEASUREMENT 1


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 4.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	40.460960
Relative permittivity (imaginary part)	20.131540
Conductivity (S/m)	0.935446
Variation (%)	2.160000

SURFACE SAR





VOLUME SAR



Maximum location: X=-51.00, Y=-22.00

SAR Peak: 1.20 W/kg

SAR 10g (W/Kg)	0.495334
SAR 1g (W/Kg)	0.657508



MEASUREMENT 2


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 4.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	54.289581
Relative permittivity (imaginary part)	21.772739
Conductivity (S/m)	1.011707
Variation (%)	-1.750000

SURFACE SAR






VOLUME SAR



Maximum location: X=3.00, Y=-3.00

SAR Peak: 1.70 W/kg

SAR 10g (W/Kg)	0.902898
SAR 1g (W/Kg)	1.025599



MEASUREMENT 3


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 4.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	40.964401
Relative permittivity (imaginary part)	13.848680
Conductivity (S/m)	1.469345
Variation (%)	0.990000

SURFACE SAR





VOLUME SAR



Maximum location: X=-52.00, Y=-48.00

SAR Peak: 0.12 W/kg

SAR 10g (W/Kg)	0.057061
SAR 1g (W/Kg)	0.085563



MEASUREMENT 4


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 4.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	52.648899
Relative permittivity (imaginary part)	14.957700
Conductivity (S/m)	1.562249
Variation (%)	1.830000

SURFACE SAR





VOLUME SAR



Maximum location: X=-12.00, Y=-26.00

SAR Peak: 0.60 W/kg

SAR 10g (W/Kg)	0.181059
SAR 1g (W/Kg)	0.355774



MEASUREMENT 5


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band2_WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	41.018200
Relative permittivity (imaginary part)	13.714300
Conductivity (S/m)	1.432382
Variation (%)	3.300000

SURFACE SAR





VOLUME SAR



Maximum location: X=-51.00, Y=-50.00

SAR Peak: 0.20 W/kg

SAR 10g (W/Kg)	0.039167
SAR 1g (W/Kg)	0.065171



MEASUREMENT 6


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band2_WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	52.648899
Relative permittivity (imaginary part)	14.957700
Conductivity (S/m)	1.562249
Variation (%)	-1.560000

SURFACE SAR





VOLUME SAR



Maximum location: X=-26.00, Y=-56.00

SAR Peak: 1.22 W/kg

SAR 10g (W/Kg)	0.383153
SAR 1g (W/Kg)	0.650804



MEASUREMENT 7


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band4_WCDMA1700</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1732.600000
Relative permittivity (real part)	39.107391
Relative permittivity (imaginary part)	13.915742
Conductivity (S/m)	1.339004
Variation (%)	-0.220000

SURFACE SAR





VOLUME SAR



Maximum location: X=-51.00, Y=-50.00

SAR Peak: 0.33 W/kg

SAR 10g (W/Kg)	0.057183
SAR 1g (W/Kg)	0.120427



MEASUREMENT 8


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band4_WCDMA1700</u>
<u>Channels</u>	<u>High</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1752.600000
Relative permittivity (real part)	53.436367
Relative permittivity (imaginary part)	15.654170
Conductivity (S/m)	1.523673
Variation (%)	-0.510000

SURFACE SAR





VOLUME SAR



Maximum location: X=2.00, Y=3.00

SAR Peak: 2.02 W/kg

SAR 10g (W/Kg)	0.484542
SAR 1g (W/Kg)	1.091732



MEASUREMENT 9


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band5 WCDMA850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	40.460960
Relative permittivity (imaginary part)	20.131540
Conductivity (S/m)	0.935446
Variation (%)	-0.060000

SURFACE SAR





VOLUME SAR



Maximum location: X=-51.00, Y=-34.00

SAR Peak: 0.67 W/kg

SAR 10g (W/Kg)	0.421631
SAR 1g (W/Kg)	0.555551



MEASUREMENT 10


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band5_WCDMA850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	54.289581
Relative permittivity (imaginary part)	21.772739
Conductivity (S/m)	1.011707
Variation (%)	-0.550000

SURFACE SAR





VOLUME SAR



Maximum location: X=-10.00, Y=49.00

SAR Peak: 0.84 W/kg

SAR 10g (W/Kg)	0.538017
SAR 1g (W/Kg)	0.707618



MEASUREMENT 11


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11b (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2437.000000
Relative permittivity (real part)	38.831001
Relative permittivity (imaginary part)	13.530300
Conductivity (S/m)	1.831852
Variation (%)	0.220000

SURFACE SAR





VOLUME SAR



Maximum location: X=-20.00, Y=-25.00

SAR Peak: 0.25 W/kg

SAR 10g (W/Kg)	0.097152
SAR 1g (W/Kg)	0.151777




MEASUREMENT 12

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11b (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	2437.000000
Relative permittivity (real part)	52.151600
Relative permittivity (imaginary part)	14.945620
Conductivity (S/m)	2.023471
Variation (%)	-1.260000



Maximum location: X=7.00, Y=0.00

SAR Peak: 0.35 W/kg

SAR 10g (W/Kg)	0.090349
SAR 1g (W/Kg)	0.155916



MEASUREMENT 13


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 2</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	41.063801
Relative permittivity (imaginary part)	13.708100
Conductivity (S/m)	1.431354
Variation (%)	-4.180000

SURFACE SAR





VOLUME SAR



Maximum location: X=-52.00, Y=-35.00

SAR Peak: 0.09 W/kg

SAR 10g (W/Kg)	0.048225
SAR 1g (W/Kg)	0.066943



MEASUREMENT 14


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 2</u>
<u>Channels</u>	<u>Low</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1860.000000
Relative permittivity (real part)	52.654251
Relative permittivity (imaginary part)	15.065600
Conductivity (S/m)	1.556360
Variation (%)	-0.700000

SURFACE SAR





VOLUME SAR



Maximum location: X=-10.00, Y=-12.00

SAR Peak: 2.41 W/kg

SAR 10g (W/Kg)	0.555598
SAR 1g (W/Kg)	1.040368



MEASUREMENT 15


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 4</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1732.500000
Relative permittivity (real part)	39.115292
Relative permittivity (imaginary part)	13.900592
Conductivity (S/m)	1.337932
Variation (%)	-0.100000

SURFACE SAR





VOLUME SAR



Maximum location: X=-51.00, Y=-50.00

SAR Peak: 0.11 W/kg

SAR 10g (W/Kg)	0.046664
SAR 1g (W/Kg)	0.068277



MEASUREMENT 16


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 4</u>
<u>Channels</u>	<u>High</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1745.000000
Relative permittivity (real part)	53.526318
Relative permittivity (imaginary part)	15.611020
Conductivity (S/m)	1.512968
Variation (%)	0.010000

SURFACE SAR





VOLUME SAR



Maximum location: X=-1.00, Y=-11.00

SAR Peak: 1.89 W/kg

SAR 10g (W/Kg)	0.628896
SAR 1g (W/Kg)	0.961818



MEASUREMENT 17


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 5</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.500000
Relative permittivity (real part)	40.463551
Relative permittivity (imaginary part)	20.130199
Conductivity (S/m)	0.935495
Variation (%)	1.450000

SURFACE SAR




VOLUME SAR



Maximum location: X=-51.00, Y=-26.00

SAR Peak: 0.64 W/kg

SAR 10g (W/Kg)	0.419286
SAR 1g (W/Kg)	0.546740



MEASUREMENT 18


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 5</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.500000
Relative permittivity (real part)	54.293499
Relative permittivity (imaginary part)	21.767000
Conductivity (S/m)	1.011561
Variation (%)	-0.050000

SURFACE SAR





VOLUME SAR



Maximum location: X=-10.00, Y=49.00

SAR Peak: 0.85 W/kg

SAR 10g (W/Kg)	0.516361
SAR 1g (W/Kg)	0.610595



MEASUREMENT 19


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 7</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2535.000000
Relative permittivity (real part)	38.795486
Relative permittivity (imaginary part)	13.851160
Conductivity (S/m)	1.950705
Variation (%)	4.680000

SURFACE SAR





VOLUME SAR



Maximum location: X=-49.00, Y=-49.00

SAR Peak: 0.57 W/kg

SAR 10g (W/Kg)	0.186481
SAR 1g (W/Kg)	0.348280



MEASUREMENT 20


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 7</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2535.000000
Relative permittivity (real part)	53.006947
Relative permittivity (imaginary part)	15.207840
Conductivity (S/m)	2.141771
Variation (%)	0.560000

SURFACE SAR





VOLUME SAR



Maximum location: X=6.00, Y=-41.00

SAR Peak: 0.20 W/kg

SAR 10g (W/Kg)	0.087443
SAR 1g (W/Kg)	0.155174



MEASUREMENT 21


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 12</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	707.500000
Relative permittivity (real part)	41.615509
Relative permittivity (imaginary part)	22.207029
Conductivity (S/m)	0.872860
Variation (%)	1.080000

SURFACE SAR




VOLUME SAR



Maximum location: X=-53.00, Y=-33.00

SAR Peak: 0.38 W/kg

SAR 10g (W/Kg)	0.264679
SAR 1g (W/Kg)	0.325304



MEASUREMENT 22


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 12</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	707.500000
Relative permittivity (real part)	55.817959
Relative permittivity (imaginary part)	23.631300
Conductivity (S/m)	0.928841
Variation (%)	-1.660000

SURFACE SAR



VOLUME SAR




Maximum location: X=-7.00, Y=-39.00


SAR Peak: 0.73 W/kg

SAR 10g (W/Kg)	0.445367
SAR 1g (W/Kg)	0.565185


Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.7007	0.4603	0.2695	0.1600	0.1010	0.0651	0.0458



3D screen shot



Hot spot position



MEASUREMENT 23


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 17</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	710.000000
Relative permittivity (real part)	41.586311
Relative permittivity (imaginary part)	22.267380
Conductivity (S/m)	0.878324
Variation (%)	1.000000

SURFACE SAR




VOLUME SAR



Maximum location: X=-53.00, Y=-34.00

SAR Peak: 0.39 W/kg

SAR 10g (W/Kg)	0.274275
SAR 1g (W/Kg)	0.336054



MEASUREMENT 24


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 17</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	710.000000
Relative permittivity (real part)	55.796711
Relative permittivity (imaginary part)	23.650499
Conductivity (S/m)	0.932881
Variation (%)	-1.220000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=38.00

SAR Peak: 0.55 W/kg

SAR 10g (W/Kg)	0.352726
SAR 1g (W/Kg)	0.448479



14. Appendix D. Calibration Certificate

Table of contents
E Field Probe - SN 41/18 EPGO330
750 MHz Dipole - SN 03/15 DIP 0G750-355
835 MHz Dipole - SN 03/15 DIP 0G835-347
1800 MHz Dipole - SN 03/15 DIP 1G800-349
1900 MHz Dipole - SN 03/15 DIP 1G900-350
2450 MHz Dipole - SN 03/15 DIP 2G450-352
2600 MHz Dipole - SN 03/15 DIP 2G600-356



COMOSAR E-Field Probe Calibration Report

Ref : ACR.142.2.19.SATU.B

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.
BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA
MVG COMOSAR DOSIMETRIC E-FIELD PROBE
SERIAL NO.: SN 41/18 EPGO330

Calibrated at MVG US
2105 Barrett Park Dr. - Kennesaw, GA 30144



Calibration Date: 05/21/19

Summary:

This document presents the method and results from an accredited COMOSAR Dosimetric E-Field Probe calibration performed in MVG USA using the CALISAR / CALIBAIR test bench, for use with a COMOSAR system only. All calibration results are traceable to national metrology institutions.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.142.2.19.SATU.B

	Name	Function	Date	Signature
Prepared by :	Jérôme LUC	Product Manager	5/22/2019	
Checked by :	Jérôme LUC	Product Manager	5/22/2019	
Approved by :	Kim RUTKOWSKI	Quality Manager	5/22/2019	

	Customer Name
Distribution :	CCIC SOUTHERN TESTING CO., LTD

Issue	Date	Modifications
A	5/22/2019	Initial release
B	5/27/2019	Change customer name and address