



FCC Test Report

Equipment : SharePod
Brand Name : wePresent
Model No. : WHE-100,WHE-200,WSP-100,
WSP-200,CSSP-100
FCC ID : 2AAEDWHE10016
Standard : 47 CFR FCC Part 15.407
Operating Band : 5150 MHz – 5250 MHz
5725 MHz – 5850 MHz
FCC Classification : NII
Applicant / Manufacturer : Barco NV
President Kennedypark 35,
8500 Kortrijk, Belgium
Function : Outdoor AP; Indoor AP;
 Fixed P2P AP; Portable Client

The product sample received on Aug. 13, 2015 and completely tested on Sep. 11, 2015. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Kevin Liang / Assistant Manager





Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Accessories and Support Equipment	7
1.3	Testing Applied Standards	7
1.4	Testing Location Information	7
1.5	Measurement Uncertainty	8
2	TEST CONFIGURATION OF EUT.....	9
2.1	The Worst Case Modulation Configuration	9
2.2	The Worst Case Power Setting Parameter.....	9
2.3	The Worst Case Measurement Configuration	10
2.4	Test Setup Diagram	11
3	TRANSMITTER TEST RESULT	13
3.1	AC Power-line Conducted Emissions	13
3.2	Emission Bandwidth	16
3.3	RF Output Power.....	19
3.4	Peak Power Spectral Density.....	23
3.5	Transmitter Bandedge Emissions	27
3.6	Transmitter Unwanted Emissions.....	31
3.7	Frequency Stability	68
4	TEST EQUIPMENT AND CALIBRATION DATA.....	70

APPENDIX A. TEST PHOTOS

APPENDIX B. PHOTOGRAPHS OF EUT



Summary of Test Result

Conformance Test Specifications			
Report Clause	Ref. Std. Clause	Description	Result
1.1.2	15.203	Antenna Requirement	Complied
3.1	15.207	AC Power-line Conducted Emissions	Complied
3.2	15.407(a)	Emission Bandwidth	Complied
3.3	15.407(a)	RF Output Power (Maximum Conducted Output Power)	Complied
3.4	15.407(a)	Peak Power Spectral Density	Complied
3.5	15.407(b)	Transmitter Bandedge Emissions	Complied
3.6	15.407(b)	Transmitter Unwanted Emissions	Complied
3.7	15.407(g)	Frequency Stability	Complied



Revision History



1 General Description

1.1 Information

All model numbers vary in different countries and regions.

1.1.1 RF General Information

RF General Information (5150-5250MHz band)					
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N _{TX})	RF Output Power (dBm)
5150-5250	a	5180-5240	36-48 [4]	2	23.02
5150-5250	n (HT20)	5180-5240	36-48 [4]	2	23.46
5150-5250	n (HT40)	5190-5230	38-46 [2]	2	20.26

Note 1: RF output power specifies that Maximum Conducted Output Power.
Note 2: 802.11a/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.

RF General Information (5725-5850MHz band)					
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N _{TX})	RF Output Power (dBm)
5725-5850	a	5745-5825	149-165 [5]	2	16.54
5725-5850	n (HT20)	5745-5825	149-165 [5]	2	16.15
5725-5850	n (HT40)	5755-5795	151-159 [2]	2	17.91

Note 1: RF output power specifies that Maximum Conducted Output Power.
Note 2: 802.11a/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.

1.1.2 Antenna Information

Antenna Category	
<input checked="" type="checkbox"/>	Integral antenna (antenna permanently attached)
<input checked="" type="checkbox"/>	Temporary RF connector provided
<input type="checkbox"/>	No temporary RF connector provided Transmit chains bypass antenna and soldered temporary RF connector provided for connected measurement. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator and correct for all losses in the RF path.

Antenna General Information			
No.	Ant. Cat.	Ant. Type	Gain (dBi)
1	Integral	FPC	1.0
2	Integral	FPC	1.0

Remark: This EUT only supports 2TX in modulation mode: 11a/n.



1.1.3 Type of EUT

Identify EUT	
EUT Serial Number	N/A
Presentation of Equipment	<input type="checkbox"/> Production ; <input checked="" type="checkbox"/> Pre-Production ; <input type="checkbox"/> Prototype
Type of EUT	
<input checked="" type="checkbox"/> Stand-alone	
<input type="checkbox"/> Combined (EUT where the radio part is fully integrated within another device) Combined Equipment - Brand Name / Model No.: ...	
<input type="checkbox"/> Plug-in radio (EUT intended for a variety of host systems) Host System - Brand Name / Model No.: ...	
<input type="checkbox"/> Other:	

1.1.4 Test Signal Duty Cycle

Operated Mode for Worst Duty Cycle	
<input type="checkbox"/> Operated normally mode for worst duty cycle	
<input checked="" type="checkbox"/> Operated test mode for worst duty cycle	
Test Signal Duty Cycle (x)	Power Duty Factor [dB] – (10 log 1/x)
<input checked="" type="checkbox"/> 100% - IEEE 802.11a	0
<input checked="" type="checkbox"/> 100% - IEEE 802.11n (HT20)	0
<input checked="" type="checkbox"/> 100% - IEEE 802.11n (HT40)	0

1.1.5 EUT Operational Condition

Supply Voltage	<input checked="" type="checkbox"/> AC mains	<input type="checkbox"/> DC	
Type of DC Source	<input type="checkbox"/> Internal DC supply	<input checked="" type="checkbox"/> External AC adapter	<input type="checkbox"/> From system



1.2 Accessories and Support Equipment

Accessories				
AC Adapter	Brand Name	ENG	Model Name	6A-061WP05
	Power Rating	I/P: 100-240V~50-60Hz 0.3A ; O/P: 5V === 1.2A		

Reminder: Regarding to more detail and other information, please refer to user manual.

Support Equipment - RF Conducted				
No.	Equipment	Brand Name	Model Name	FCC ID
1	Notebook	DELL	E5540	DoC
2	Adapter for Notebook	DELL	HA65NM130	DoC

1.3 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ◆ 47 CFR FCC Part 15
- ◆ ANSI C63.10-2013
- ◆ FCC KDB 789033 D02 v01
- ◆ FCC KDB 644545 D03 v01
- ◆ FCC-14-30A1-UNII
- ◆ FCC KDB 662911 D01 v02r01

1.4 Testing Location Information

Testing Location				
	HWA YA	ADD	: No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.	
		TEL	: 886-3-327-3456	FAX : 886-3-327-0973
Test Condition		Test Site No.	Test Engineer	Test Environment
AC Conduction		CO04-HY	Zeus	21°C / 58%
RF Conducted		TH01-HY	Leo	22.1°C / 64%
Radiated Emission		03CH09-HY	Thor	24.3°C / 64.8%
Test Site Registration Number				
213289				



1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty		
Test Item	Uncertainty	
AC power-line conducted emissions	±2.3 dB	
Emission bandwidth, 26dB bandwidth	±0.5%	
RF output power, conducted	±0.1 dB	
Power density, conducted	±0.5 dB	
Unwanted emissions, conducted	9 – 150 kHz	±0.4 dB
	0.15 – 30 MHz	±0.4 dB
	30 – 1000 MHz	±0.6 dB
	1 – 18 GHz	±0.5 dB
	18 – 40 GHz	±0.5 dB
	40 – 200 GHz	N/A
All emissions, radiated	9 – 150 kHz	±2.5 dB
	0.15 – 30 MHz	±2.3 dB
	30 – 1000 MHz	±2.6 dB
	1 – 18 GHz	±3.6 dB
	18 – 40 GHz	±3.8 dB
	40 – 200 GHz	N/A
Temperature	±0.8 °C	
Humidity	±5 %	
DC and low frequency voltages	±0.9%	
Time	±1.4 %	
Duty Cycle	±0.5 %	



2 Test Configuration of EUT

2.1 The Worst Case Modulation Configuration

Worst Modulation Used for Conformance Testing				
Modulation Mode	Transmit Chains (N _{TX})		Data Rate / MCS	Worst Data Rate / MCS
11a	2		6-54Mbps	6 Mbps
HT20	2		MCS 0-15	MCS 0
HT40	2		MCS 0-15	MCS 0

2.2 The Worst Case Power Setting Parameter

The Worst Case Power Setting Parameter (5150-5250MHz band)						
Test Software Version	RF Test_Ver 0.1					
Modulation Mode	N _{TX}	Test Frequency (MHz)				
		NCB: 20MHz			NCB: 40MHz	
		5180	5200	5240	5190	5230
11a	2	31	41	40	-	-
HT20	2	29	37	40	-	-
HT40	2	-	-	-	19	35

The Worst Case Power Setting Parameter (5725-5850MHz band)						
Test Software Version	RF Test_Ver 0.1					
Modulation Mode	N _{TX}	Test Frequency (MHz)				
		NCB: 20MHz			NCB: 40MHz	
		5745	5785	5825	5755	5795
11a	2	23	27	26	-	-
HT20	2	20	26	23	-	-
HT40	2	-	-	-	17	30




2.3 The Worst Case Measurement Configuration



The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
Operating Mode	Operating Mode Description
1	Transmit Mode (WLAN)

The Worst Case Mode for Following Conformance Tests	
Tests Item	RF Output Power, Peak Power Spectral Density, Emission Bandwidth, Peak Excursion, Transmitter Conducted Unwanted Emissions Transmitter Conducted Bandedge Emissions
Test Condition	Conducted measurement at transmit chains
Modulation Mode	11a, HT20, HT40

The Worst Case Mode for Following Conformance Tests							
Tests Item	Transmitter Radiated Unwanted Emissions Transmitter Radiated Bandedge Emissions						
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.						
User Position	<input type="checkbox"/> EUT will be placed in fixed position. <input checked="" type="checkbox"/> EUT will be placed in mobile position and operating multiple positions. EUT shall be performed three orthogonal planes. <input type="checkbox"/> EUT will be a hand-held or body-worn battery-powered devices and operating multiple positions.						
Operating Mode	Operating Mode Description						
1	Transmit Mode (WLAN)						
Modulation Mode	11a, HT20, HT40						
Orthogonal Planes of EUT	<table border="1"><thead><tr><th>X Plane</th><th>Y Plane</th><th>Z Plane</th></tr></thead><tbody><tr><td></td><td></td><td></td></tr></tbody></table>	X Plane	Y Plane	Z Plane			
X Plane	Y Plane	Z Plane					
Worst Planes of EUT	V						

2.4 Test Setup Diagram



Test Setup Diagram - Radiated Below 1GHz Test**Test Setup Diagram - Radiated Above 1GHz Test**

3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures


Test Method
<input checked="" type="checkbox"/> Refer as ANSI C63.10-2013, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup






3.1.5 Test Result of AC Power-line Conducted Emissions

AC Power-line Conducted Emissions Result							
Operating Mode	1	Power Phase	Neutral				
Operating Function	Transmit Mode (WLAN)						
Date: 2015-09-11							
							
Emissions Data (dBuV)							
Freq	Level	Over Limit	Limit	Read Line	LISN Level	Cable Factor	Cable Loss Remark
MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.1532130	34.19	-21.63	55.82	33.78	0.07	0.34 Average
2	0.1532130	48.17	-17.65	65.82	47.76	0.07	0.34 QP
3	0.1815220	45.21	-19.21	64.42	44.70	0.07	0.44 QP
4	0.1815220	28.13	-26.29	54.42	27.62	0.07	0.44 Average
5	0.4811910	45.00	-11.32	56.32	44.29	0.07	0.64 QP
6	0.4811910	36.23	-10.09	46.32	35.52	0.07	0.64 Average
7	0.9581900	38.22	-17.78	56.00	37.34	0.09	0.79 QP
8	0.9581900	26.82	-19.18	46.00	25.94	0.09	0.79 Average
9	1.180	35.84	-20.16	56.00	34.95	0.09	0.80 QP
10	1.180	25.49	-20.51	46.00	24.60	0.09	0.80 Average
11	3.530	31.80	-24.20	56.00	30.96	0.12	0.72 QP
12	3.530	20.02	-25.98	46.00	19.18	0.12	0.72 Average

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)





3.2 Emission Bandwidth

3.2.1 Emission Bandwidth Limit

Emission Bandwidth Limit	
UNII Devices	
<input checked="" type="checkbox"/>	For the 5.15-5.25 GHz band, N/A
<input type="checkbox"/>	For the 5.25-5.35 GHz band, the maximum conducted output power shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in MHz.
<input type="checkbox"/>	For the 5.47-5.725 GHz band, the maximum conducted output power shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in MHz.
<input checked="" type="checkbox"/>	For the 5.725-5.85 GHz band, 6 dB emission bandwidth \geq 500kHz.

3.2.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	For the emission bandwidth shall be measured using one of the options below:
<input checked="" type="checkbox"/>	Refer as FCC KDB 789033, clause C for EBW and clause D for OBW measurement.
<input type="checkbox"/>	Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.
<input type="checkbox"/>	Refer as IC RSS-Gen, clause 6.6 for bandwidth testing.
<input checked="" type="checkbox"/>	For conducted measurement.
<input type="checkbox"/>	The EUT supports single transmit chain and measurements performed on this transmit chain 1.
<input type="checkbox"/>	The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input checked="" type="checkbox"/>	The EUT supports multiple transmit chains using options given below:
	<input type="checkbox"/> Option 1: Multiple transmit chains measurements need to be performed on one of the active transmit chains (antenna outputs). All measurement had be performed on transmit chains 1.
	<input checked="" type="checkbox"/> Option 2: Multiple transmit chains measurements need to be performed on each transmit chains individually (antenna outputs). All measurement had be performed on all transmit chains.




3.2.4 Test Setup



3.2.5 Test Result of Emission Bandwidth

UNII Emission Bandwidth Result (5150-5250MHz band)						
Condition			Emission Bandwidth (MHz)			
Modulation Mode	N _{TX}	Freq. (MHz)	99% Bandwidth		26dB Bandwidth	
			Chain- Port 1	Chain- Port 2	Chain- Port 1	Chain- Port 2
11a	2	5180	16.69	16.71	24.10	26.32
11a	2	5200	24.03	22.96	37.87	35.10
11a	2	5240	26.53	24.68	38.55	38.80
HT20	2	5180	18.21	17.89	24.20	25.85
HT20	2	5200	18.66	19.29	34.65	35.62
HT20	2	5240	28.78	28.91	44.07	45.25
HT40	2	5190	36.26	36.22	44.08	43.56
HT40	2	5230	37.34	37.30	73.32	72.88
Result			Complied			

UNII Emission Bandwidth Result (5725-5850MHz band)						
Condition			Emission Bandwidth (MHz)			
Modulation Mode	N _{TX}	Freq. (MHz)	99% Bandwidth		6dB Bandwidth	
			Chain- Port 1	Chain- Port 2	Chain- Port 1	Chain- Port 2
11a	2	5745	16.47	16.43	16.42	16.44
11a	2	5785	16.59	16.55	16.42	16.47
11a	2	5825	16.53	16.55	16.48	16.44
HT20	2	5745	17.63	17.70	17.64	17.74
HT20	2	5785	17.81	17.73	17.80	17.71
HT20	2	5825	17.72	17.73	17.26	17.73
HT40	2	5755	35.90	35.98	32.64	35.08
HT40	2	5795	36.46	36.26	33.12	32.56
Limit			-		≥ 500 kHz	
Result			Complied			





3.3 RF Output Power

3.3.1 RF Output Power Limit

Maximum Conducted Output Power Limit	
UNII Devices	
<input checked="" type="checkbox"/> For the 5.15-5.25 GHz band:	
<input type="checkbox"/> Outdoor AP: the maximum conducted output power (P_{Out}) shall not exceed the lesser of 1 W. If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$. e.i.r.p. at any elevation angle above 30 degrees ≤ 125 mW [21dBm]	
<input type="checkbox"/> Indoor AP: the maximum conducted output power (P_{Out}) shall not exceed the lesser of 1 W. If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$	
<input type="checkbox"/> Point-to-point AP: the maximum conducted output power (P_{Out}) shall not exceed the lesser of 1 W If $G_{TX} > 23$ dBi, then $P_{Out} = 30 - (G_{TX} - 23)$.	
<input checked="" type="checkbox"/> Mobile or Portable Client: the maximum conducted output power (P_{Out}) shall not exceed the lesser of 250 mW. If $G_{TX} > 6$ dBi, then $P_{Out} = 24 - (G_{TX} - 6)$.	
<input type="checkbox"/> For the 5.25-5.35 GHz band, the maximum conducted output power (P_{Out}) shall not exceed the lesser of 250 mW or 11 dBm + $10 \log B$, where B is the 26 dB emission bandwidth in MHz. If $G_{TX} > 6$ dBi, then $P_{Out} = 24 - (G_{TX} - 6)$.	
<input type="checkbox"/> For the 5.47-5.725 GHz band, the maximum conducted output power (P_{Out}) shall not exceed the lesser of 250 mW or 11 dBm + $10 \log B$, where B is the 26 dB emission bandwidth in MHz. If $G_{TX} > 6$ dBi, then $P_{Out} = 24 - (G_{TX} - 6)$.	
<input checked="" type="checkbox"/> For the 5.725-5.85 GHz band:	
<input type="checkbox"/> Point-to-multipoint systems (P2M): the maximum conducted output power (P_{Out}) shall not exceed the lesser of 1 W. If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$.	
<input checked="" type="checkbox"/> Point-to-point systems (P2P): the maximum conducted output power (P_{Out}) shall not exceed the lesser of 1 W.	
P_{Out} = maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi.	

3.3.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.



3.3.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/> Maximum Conducted Output Power	
	[duty cycle \geq 98% or external video / power trigger]
<input checked="" type="checkbox"/>	Refer as FCC KDB 789033, clause E Method SA-1 (spectral trace averaging).
<input type="checkbox"/>	Refer as FCC KDB 789033, clause E Method SA-1 Alt. (RMS detection with slow sweep speed)
	duty cycle $<$ 98% and average over on/off periods with duty factor
<input type="checkbox"/>	Refer as FCC KDB 789033, clause E Method SA-2 (spectral trace averaging).
<input type="checkbox"/>	Refer as FCC KDB 789033, clause E Method SA-2 Alt. (RMS detection with slow sweep speed)
	Wideband RF power meter and average over on/off periods with duty factor
<input type="checkbox"/>	Refer as FCC KDB 789033, clause E Method PM (using an RF average power meter).
<input checked="" type="checkbox"/> For conducted measurement.	
<input type="checkbox"/>	The EUT supports single transmit chain and measurements performed on this transmit chain 1.
<input type="checkbox"/>	The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input checked="" type="checkbox"/>	The EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.
<input checked="" type="checkbox"/>	If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$

3.3.4 Test Setup






3.3.5 Test Result of Maximum Conducted Output Power

Maximum Conducted Output Power (5150-5250MHz band)							
Modulation Mode	N _{TX}	Freq. (MHz)	Chain Port 1	Chain Port 2	Sum Chain	Antenna Gain (dBi)	Power Limit
11a	2	5180	14.05	14.43	17.25	4.01	24.00
11a	2	5200	18.76	19.37	22.09	4.01	24.00
11a	2	5240	19.13	19.27	22.21	4.01	24.00
HT20	2	5180	13.85	13.37	16.63	4.01	24.00
HT20	2	5200	17.47	18.16	20.84	4.01	24.00
HT20	2	5240	19.26	19.35	22.32	4.01	24.00
HT40	2	5190	8.85	8.50	11.69	4.01	24.00
HT40	2	5230	17.50	16.98	20.26	4.01	24.00
Result		Complied					

Maximum Conducted Output Power (5725-5850MHz band)							
Modulation Mode	N _{TX}	Freq. (MHz)	Chain Port 1	Chain Port 2	Sum Chain	Antenna Gain (dBi)	Power Limit
11a	2	5745	10.62	10.92	13.78	4.01	30.00
11a	2	5785	13.22	13.81	16.54	4.01	30.00
11a	2	5825	13.05	13.23	16.15	4.01	30.00
HT20	2	5745	9.30	9.75	12.54	4.01	30.00
HT20	2	5785	12.76	13.49	16.15	4.01	30.00
HT20	2	5825	11.92	12.18	15.06	4.01	30.00
HT40	2	5755	7.97	8.09	11.04	4.01	30.00
HT40	2	5795	14.40	15.35	17.91	4.01	30.00
Result		Complied					





3.4 Peak Power Spectral Density

3.4.1 Peak Power Spectral Density Limit

Peak Power Spectral Density Limit	
UNII Devices	
<input checked="" type="checkbox"/> For the 5.15-5.25 GHz band:	
<input type="checkbox"/> Outdoor AP: the peak power spectral density (PPSD) shall not exceed the lesser of 17dBm/MHz. If $G_{TX} > 6$ dBi, then $P_{Out} = 17 - (G_{TX} - 6)$.	
<input type="checkbox"/> Indoor AP: the peak power spectral density (PPSD) shall not exceed the lesser of 17dBm/MHz. If $G_{TX} > 6$ dBi, then $P_{Out} = 17 - (G_{TX} - 6)$.	
<input type="checkbox"/> Point-to-point AP: the peak power spectral density (PPSD) shall not exceed the lesser of 17dBm/MHz. If $G_{TX} > 23$ dBi, then $P_{Out} = 17 - (G_{TX} - 23)$.	
<input checked="" type="checkbox"/> Mobile or Portable Client: the peak power spectral density (PPSD) ≤ 11 dBm/MHz. If $G_{TX} > 6$ dBi, then $PPSD = 11 - (G_{TX} - 6)$.	
<input type="checkbox"/> For the 5.25-5.35 GHz band, the peak power spectral density (PPSD) ≤ 11 dBm/MHz. If $G_{TX} > 6$ dBi, then $PPSD = 11 - (G_{TX} - 6)$.	
<input type="checkbox"/> For the 5.47-5.725 GHz band, the peak power spectral density (PPSD) ≤ 11 dBm/MHz. If $G_{TX} > 6$ dBi, then $PPSD = 11 - (G_{TX} - 6)$.	
<input checked="" type="checkbox"/> For the 5.725-5.85 GHz band:	
<input type="checkbox"/> Point-to-multipoint systems (P2M): the peak power spectral density (PPSD) ≤ 30 dBm/500kHz. If $G_{TX} > 6$ dBi, then $PPSD = 30 - (G_{TX} - 6)$.	
<input checked="" type="checkbox"/> Point-to-point systems (P2P): the peak power spectral density (PPSD) ≤ 30 dBm/500kHz.	
PPSD = peak power spectral density that the same method as used to determine the conducted output power shall be used to determine the power spectral density. And power spectral density in dBm/MHz G_{TX} = the maximum transmitting antenna directional gain in dBi.	


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/> Peak power spectral density procedures that the same method as used to determine the conducted output power shall be used to determine the peak power spectral density and use the peak search function on the spectrum analyzer to find the peak of the spectrum. For the peak power spectral density shall be measured using below options:	
<input type="checkbox"/> Refer as FCC KDB 789033, F)5) power spectral density can be measured using resolution bandwidths < 1 MHz provided that the results are integrated over 1 MHz bandwidth	[duty cycle \geq 98% or external video / power trigger]
<input checked="" type="checkbox"/> Refer as FCC KDB 789033, clause E Method SA-1 (spectral trace averaging).	
<input type="checkbox"/> Refer as FCC KDB 789033, clause E Method SA-1 Alt. (RMS detection with slow sweep speed)	duty cycle $<$ 98% and average over on/off periods with duty factor
<input type="checkbox"/> Refer as FCC KDB 789033, clause E Method SA-2 (spectral trace averaging).	
<input type="checkbox"/> Refer as FCC KDB 789033, clause E Method SA-2 Alt. (RMS detection with slow sweep speed)	
<input checked="" type="checkbox"/> For conducted measurement.	
<input type="checkbox"/> The EUT supports single transmit chain and measurements performed on this transmit chain 1.	
<input type="checkbox"/> The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.	
<input checked="" type="checkbox"/> The EUT supports multiple transmit chains using options given below:	
	<input checked="" type="checkbox"/> Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.
	<input type="checkbox"/> Option 2: Measure and add $10 \log(N)$ dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with $10 \log(N)$. Or each transmit chains shall be add $10 \log(N)$ to compared with the limit.
<input checked="" type="checkbox"/>	If multiple transmit chains, EIRP PPSD calculation could be following as methods: $PPSD_{total} = PPSD_1 + PPSD_2 + \dots + PPSD_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = PPSD_{total} + DG$
<input checked="" type="checkbox"/>	Each individually PPSD plots refer as test report clause 3.3.5 with each individually PPSD plots.

3.4.4 Test Setup






3.4.5 Test Result of Peak Power Spectral Density

Peak Power Spectral Density Result (5150-5250MHz band)					
Modulation Mode	N _{TX}	Freq. (MHz)	Peak Power Spectral Density (dBm)	PSD Limit	Antenna Gain (dBi)
11a	2	5180	6.31	11.00	4.01
11a	2	5200	10.89	11.00	4.01
11a	2	5240	10.72	11.00	4.01
HT20	2	5180	5.41	11.00	4.01
HT20	2	5200	9.25	11.00	4.01
HT20	2	5240	10.96	11.00	4.01
HT40	2	5190	-2.20	11.00	4.01
HT40	2	5230	6.15	11.00	4.01
Result		Complied			


Peak Power Spectral Density Result (5725-5850MHz band)					
Modulation Mode	N _{TX}	Freq. (MHz)	Peak Power Spectral Density (dBm)	PSD Limit (500kHz)	Antenna Gain (dBi)
11a	2	5745	7.17	30.00	4.01
11a	2	5785	9.37	30.00	4.01
11a	2	5825	9.09	30.00	4.01
HT20	2	5745	5.50	30.00	4.01
HT20	2	5785	8.47	30.00	4.01
HT20	2	5825	7.61	30.00	4.01
HT40	2	5755	0.23	30.00	4.01
HT40	2	5795	7.62	30.00	4.01
Result		Complied			



5150-5250MHz - Worst Power Spectral Density Plots





5725-5850MHz - Worst Power Spectral Density Plots



3.5 Transmitter Bandedge Emissions

3.5.1 Transmitter Radiated Bandedge Emissions Limit



3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.




3.5.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> The average emission levels shall be measured in [duty cycle \geq 98 or duty factor].
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.10 bandedge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.
<input type="checkbox"/> If EUT operate in adjacent contiguous bands, bandedge testing performed at the lowest frequency channel at lower-band and highest frequency channel at higher-band. Transmitter in-band emissions will consist of adjacent contiguous bands (e.g., IEEE 802.11ac VHT160 The lowest frequency channel at lower-band and highest frequency channel at higher-band in-band emissions will consist of two adjacent contiguous bands.) <input type="checkbox"/> Operating in 5.15-5.25 GHz band (lower-band) and 5.25-5.35 GHz band (higher-band). <input type="checkbox"/> Operating in 5.47-5.725 GHz band (lower-band) and 5.725-5.85 GHz band (higher-band).
<input type="checkbox"/> If EUT operate in individual non-contiguous bands, bandedge testing performed at the lowest frequency channel and highest frequency channel within lower-band and higher-band. (e.g., (e.g., IEEE 802.11ac VHT160) <input type="checkbox"/> Operating in 5.25-5.35 GHz band (lower-band) and 5.47-5.725 GHz band (higher-band). <input type="checkbox"/> Operating in 5.15-5.25 GHz band (lower-band) and 5.725-5.85 GHz band (higher-band).
<input checked="" type="checkbox"/> For the transmitter unwanted emissions shall be measured using following options below: <input checked="" type="checkbox"/> Refer as FCC KDB 789033, clause H)2) for unwanted emissions into non-restricted bands. <input checked="" type="checkbox"/> Refer as FCC KDB 789033, clause H)1) for unwanted emissions into restricted bands. <input checked="" type="checkbox"/> Refer as FCC KDB 789033, H)6) Method AD (Trace Averaging). <input type="checkbox"/> Refer as FCC KDB 789033, H)6) Method VB (Reduced VBW). <input type="checkbox"/> Refer as ANSI C63.10, clause 4.1.4.2.3 (Reduced VBW). VBW \geq 1/T, where T is pulse time. <input type="checkbox"/> Refer as ANSI C63.10, clause 4.1.4.2.4 average value of pulsed emissions. <input checked="" type="checkbox"/> Refer as FCC KDB 789033, clause H)5) measurement procedure peak limit. <input type="checkbox"/> Refer as ANSI C63.10, clause 4.1.4.2.2 measurement procedure peak limit.
<input checked="" type="checkbox"/> For the transmitter bandedge emissions shall be measured using following options below: <input type="checkbox"/> Refer as FCC KDB 789033, clause H)3)d) for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz). <input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.10 for band-edge testing. <input type="checkbox"/> Refer as ANSI C63.10, clause 6.10.6.2 for marker-delta method for band-edge measurements.
<input checked="" type="checkbox"/> For radiated measurement, refer as ANSI C63.10, clause 6.6. Test distance is 3m.
<input checked="" type="checkbox"/> Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements). Measurements in the bandedge are typically made at a closer distance 3m, because the instrumentation noise floor is typically close to the radiated emission limit.

3.5.4 Test Setup

Transmitter Radiated Bandedge Emissions



Electric field tests shall be performed in transmitter bandedge emissions using a calibrated horn antenna.



3.5.5 Transmitter Radiated Bandedge Emissions (with Antenna)

U-NII 5150-5250MHz Transmitter Radiated Bandedge (with Antenna)										
Modulation Mode	N _{TX}	Freq. (MHz)	Measure Distance (m)	Freq. (MHz) PK	Level (dBuV/m) PK	Limit (dBuV/m) PK	Freq. (MHz) AV	Level (dBuV/m) AV	Limit (dBuV/m) AV	Pol.
11a	2	5180	3	5149.90	71.13	74	5149.90	52.51	54	V
11a	2	5240	3	5121.60	58.35	74	5115.60	47.07	54	V
HT20	2	5180	3	5149.60	72.44	74	5149.90	50.63	54	V
HT20	2	5240	3	5133.60	62.03	74	5148.60	46.88	54	V
HT40	2	5190	3	5149.94	69.23	74	5149.94	52.67	54	V
HT40	2	5230	3	5149.80	65.65	74	5149.80	52.27	54	V

Note 1: Measurement worst emissions of receive antenna polarization.

U-NII 5725-5850MHz Transmitter Radiated Bandedge (with Antenna)							
Modulation Mode	N _{TX}	Freq. (MHz)	Measure Distance (m)	Freq. (MHz) PK	Level (dBuV/m) PK	Limit (dBuV/m) PK	Pol.
11a	2	5745	3	5724.97	76.32	78.20	V
11a	2	5825	3	5851.33	76.31	78.20	V
HT20	2	5745	3	5723.50	76.38	78.20	V
HT20	2	5825	3	5850.18	76.64	78.20	V
HT40	2	5755	3	5715.00	66.86	68.20	V
HT40	2	5795	3	5864.20	66.29	68.20	V

Note 1: Measurement worst emissions of receive antenna polarization.



3.6 Transmitter Unwanted Emissions

3.6.1 Transmitter Radiated Unwanted Emissions Limit

Unwanted emissions below 1 GHz and restricted band emissions above 1GHz limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Un-restricted band emissions above 1GHz Limit	
Operating Band	Limit
5.15 - 5.25 GHz	e.i.r.p. -27 dBm [68.2 dBuV/m@3m]
5.25 - 5.35 GHz	e.i.r.p. -27 dBm [68.2 dBuV/m@3m]
5.47 - 5.725 GHz	e.i.r.p. -27 dBm [68.2 dBuV/m@3m]
5.725 - 5.85 GHz	5.715 5.725 GHz: e.i.r.p. -17 dBm [78.2 dBuV/m@3m] 5.85 5.86 GHz: e.i.r.p. -17 dBm [78.2 dBuV/m@3m] Other un-restricted band: e.i.r.p. -27 dBm [68.2 dBuV/m@3m]

Note 1: Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

3.6.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.



3.6.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 m for frequencies above 30 MHz, unless it can be further demonstrated that measurements at a distance of 30 m or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).
<input checked="" type="checkbox"/> The average emission levels shall be measured in [duty cycle \geq 98 or duty factor].
<input checked="" type="checkbox"/> For the transmitter unwanted emissions shall be measured using following options below:
<input checked="" type="checkbox"/> Refer as FCC KDB 789033, clause G)2) for unwanted emissions into non-restricted bands.
<input checked="" type="checkbox"/> Refer as FCC KDB 789033, clause G)1) for unwanted emissions into restricted bands.
<input checked="" type="checkbox"/> Refer as FCC KDB 789033, G)6) Method AD (Trace Averaging).
<input type="checkbox"/> Refer as FCC KDB 789033, G)6) Method VB (Reduced VBW).
<input type="checkbox"/> Refer as ANSI C63.10, clause 4.1.4.2.3 (Reduced VBW). VBW \geq 1/T, where T is pulse time.
<input type="checkbox"/> Refer as ANSI C63.10, clause 4.1.4.2.4 average value of pulsed emissions.
<input checked="" type="checkbox"/> Refer as FCC KDB 789033, clause G)5) measurement procedure peak limit.
<input type="checkbox"/> Refer as ANSI C63.10, clause 4.1.4.2.2 measurement procedure peak limit.
<input checked="" type="checkbox"/> For radiated measurement.
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.4 for radiated emissions below 30 MHz and test distance is 3m.
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.5 for radiated emissions 30 MHz to 1 GHz and test distance is 3m.
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.6 for radiated emissions above 1GHz. For 1 GHz to 5 GHz, test distance is 3m; For 5 GHz to 40 GHz, test distance is 3m.
<input checked="" type="checkbox"/> The any unwanted emissions level shall not exceed the fundamental emission level.
<input checked="" type="checkbox"/> All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

3.6.4 Test Setup




3.6.5 Transmitter Radiated Unwanted Emissions-with Antenna (Below 30MHz)

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.



3.6.6 Transmitter Radiated Unwanted Emissions (Below 1GHz)


Transmitter Radiated Unwanted Emissions (Below 1GHz)											
Operating Mode	1	Polarization		V							
Operating Function	Transmit Mode (WLAN)										
Level (dBuV/m)									Date: 2015-09-07		
									NCC/C/IC/FCC-B -30dB		
Over Limit Read Antenna Cable Preamp											
Freq		Level	Over Limit	Line	Read Antenna	Cable	Preamp				
MHz		dBuV/m	dB	dBuV/m	dBuV	dB/m	dB				
<hr/>											
1	39.70	31.86	-8.14	40.00	54.51	14.20	0.38	37.23	Peak		
2	123.12	29.60	-13.90	43.50	53.70	11.89	0.67	36.66	Peak		
3	185.20	28.75	-14.75	43.50	54.98	9.40	0.80	36.43	Peak		
4	350.10	33.20	-12.80	46.00	53.31	15.20	1.18	36.49	Peak		
5	625.58	35.22	-10.78	46.00	50.86	19.95	1.66	37.25	Peak		
6	949.56	34.26	-11.74	46.00	44.96	24.67	2.05	37.42	Peak		

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical).


Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.






3.6.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 5150-5250MHz

Transmitter Radiated Unwanted Emissions (Above 1GHz)																																																																						
Modulation Mode	11a		Test Freq. (MHz)		5180																																																																	
N _{TX}	2		Polarization		V																																																																	
Level (dB _{uV/m})									Date: 2015-09-05																																																													
1	7128.00	48.56	-19.64	68.20	58.88	36.07	7.02	53.41	Peak																																																													
2	10360.00	54.06	-14.14	68.20	61.91	37.72	8.61	54.18	Peak																																																													
3	15540.00	41.72	-12.28	54.00	44.54	38.88	10.96	52.66	Average																																																													
4	15540.00	55.79	-18.21	74.00	58.61	38.88	10.96	52.66	Peak																																																													
<table border="1"> <thead> <tr> <th rowspan="2">Freq</th> <th rowspan="2">Level</th> <th>Over</th> <th>Limit</th> <th>Read</th> <th>Antenna</th> <th>Cable</th> <th>Preamp</th> <th rowspan="2">Remark</th> </tr> <tr> <th>Line</th> <th>Limit</th> <th>Antenna</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> </tr> <tr> <th>MHz</th> <th>dB_{uV/m}</th> <th>dB</th> <th>dB_{uV/m}</th> <th>dB_{uV}</th> <th>dB/m</th> <th>dB</th> <th>dB</th> <th></th> </tr> </thead> <tbody> <tr> <td>1</td> <td>7128.00</td> <td>48.56</td> <td>-19.64</td> <td>68.20</td> <td>58.88</td> <td>36.07</td> <td>7.02</td> <td>53.41 Peak</td> </tr> <tr> <td>2</td> <td>10360.00</td> <td>54.06</td> <td>-14.14</td> <td>68.20</td> <td>61.91</td> <td>37.72</td> <td>8.61</td> <td>54.18 Peak</td> </tr> <tr> <td>3</td> <td>15540.00</td> <td>41.72</td> <td>-12.28</td> <td>54.00</td> <td>44.54</td> <td>38.88</td> <td>10.96</td> <td>52.66 Average</td> </tr> <tr> <td>4</td> <td>15540.00</td> <td>55.79</td> <td>-18.21</td> <td>74.00</td> <td>58.61</td> <td>38.88</td> <td>10.96</td> <td>52.66 Peak</td> </tr> </tbody> </table>										Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark	Line	Limit	Antenna	Level	Factor	Loss	Factor	MHz	dB _{uV/m}	dB	dB _{uV/m}	dB _{uV}	dB/m	dB	dB		1	7128.00	48.56	-19.64	68.20	58.88	36.07	7.02	53.41 Peak	2	10360.00	54.06	-14.14	68.20	61.91	37.72	8.61	54.18 Peak	3	15540.00	41.72	-12.28	54.00	44.54	38.88	10.96	52.66 Average	4	15540.00	55.79	-18.21	74.00	58.61	38.88	10.96	52.66 Peak
Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark																																																														
		Line	Limit	Antenna	Level	Factor	Loss		Factor																																																													
MHz	dB _{uV/m}	dB	dB _{uV/m}	dB _{uV}	dB/m	dB	dB																																																															
1	7128.00	48.56	-19.64	68.20	58.88	36.07	7.02	53.41 Peak																																																														
2	10360.00	54.06	-14.14	68.20	61.91	37.72	8.61	54.18 Peak																																																														
3	15540.00	41.72	-12.28	54.00	44.54	38.88	10.96	52.66 Average																																																														
4	15540.00	55.79	-18.21	74.00	58.61	38.88	10.96	52.66 Peak																																																														
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.																																																																						
Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)																																																																						
Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)																																																																						
Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																						
Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.																																																																						
Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.																																																																						










Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (MHz)	5200				
N_{TX}	2	Polarization	H				
Level (dBuV/m)			Date: 2015-09-05				
Freq	Level	Over Limit	Read	Antenna	Cable	Preamp	Remark
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	
1	7818.00	49.30	-18.90	68.20	58.92	36.79	7.40 53.81 Peak
2	10400.00	60.33	-7.87	68.20	68.12	37.74	8.63 54.16 Peak
3	15600.00	49.63	-4.37	54.00	52.37	38.84	10.99 52.57 Average
4	15600.00	62.71	-11.29	74.00	65.45	38.84	10.99 52.57 Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.
Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.









Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	5180																																																												
N _{TX}	2	Polarization	H																																																												
Level (dBuV/m)			Date: 2015-09-05																																																												
<table border="1"> <thead> <tr> <th rowspan="2">Freq</th> <th rowspan="2">Level</th> <th>Over</th> <th>Limit</th> <th>Read</th> <th>Antenna</th> <th>Cable</th> <th>Preamp</th> </tr> <tr> <th>Line</th> <th>Limit</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> <th>Remark</th> </tr> </thead> <tbody> <tr> <td>MHz</td> <td>dBuV/m</td> <td>dB</td> <td>dBuV/m</td> <td>dBuV</td> <td>dB/m</td> <td>dB</td> <td>dB</td> <td></td> </tr> <tr> <td>1</td> <td>7926.00</td> <td>49.32</td> <td>-18.88</td> <td>68.20</td> <td>58.90</td> <td>36.85</td> <td>7.45</td> <td>53.88 Peak</td> </tr> <tr> <td>2</td> <td>10360.00</td> <td>53.68</td> <td>-14.52</td> <td>68.20</td> <td>61.53</td> <td>37.72</td> <td>8.61</td> <td>54.18 Peak</td> </tr> <tr> <td>3</td> <td>15540.00</td> <td>40.62</td> <td>-13.38</td> <td>54.00</td> <td>43.44</td> <td>38.88</td> <td>10.96</td> <td>52.66 Average</td> </tr> <tr> <td>4</td> <td>15540.00</td> <td>54.34</td> <td>-19.66</td> <td>74.00</td> <td>57.16</td> <td>38.88</td> <td>10.96</td> <td>52.66 Peak</td> </tr> </tbody> </table>	Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Line	Limit	Level	Factor	Loss	Factor	Remark	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		1	7926.00	49.32	-18.88	68.20	58.90	36.85	7.45	53.88 Peak	2	10360.00	53.68	-14.52	68.20	61.53	37.72	8.61	54.18 Peak	3	15540.00	40.62	-13.38	54.00	43.44	38.88	10.96	52.66 Average	4	15540.00	54.34	-19.66	74.00	57.16	38.88	10.96	52.66 Peak			
Freq			Level	Over	Limit	Read	Antenna	Cable	Preamp																																																						
	Line	Limit		Level	Factor	Loss	Factor	Remark																																																							
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB																																																								
1	7926.00	49.32	-18.88	68.20	58.90	36.85	7.45	53.88 Peak																																																							
2	10360.00	53.68	-14.52	68.20	61.53	37.72	8.61	54.18 Peak																																																							
3	15540.00	40.62	-13.38	54.00	43.44	38.88	10.96	52.66 Average																																																							
4	15540.00	54.34	-19.66	74.00	57.16	38.88	10.96	52.66 Peak																																																							

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.


Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.


Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

























3.6.8 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 5725-5850MHz






Transmitter Radiated Unwanted Emissions (Above 1GHz)










Transmitter Radiated Unwanted Emissions (Above 1GHz)


Modulation Mode	11a	Test Freq. (MHz)	5825																																																				
N _{TX}	2	Polarization	V																																																				
Level (dBuV/m)			Date: 2015-09-06																																																				
<table border="1"> <thead> <tr> <th>Freq</th> <th>Level</th> <th>Over Limit</th> <th>Line</th> <th>Read</th> <th>Antenna</th> <th>Cable</th> <th>Preamp</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV/m</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>8639.00</td> <td>50.34</td> <td>-17.86</td> <td>68.20</td> <td>59.19</td> <td>37.35</td> <td>7.80</td> <td>54.00 Peak</td> </tr> <tr> <td>2</td> <td>11650.00</td> <td>42.52</td> <td>-11.48</td> <td>54.00</td> <td>48.11</td> <td>38.72</td> <td>9.30</td> <td>53.61 Average</td> </tr> <tr> <td>3</td> <td>11650.00</td> <td>56.47</td> <td>-17.53</td> <td>74.00</td> <td>62.06</td> <td>38.72</td> <td>9.30</td> <td>53.61 Peak</td> </tr> <tr> <td>4</td> <td>17475.00</td> <td>65.14</td> <td>-3.06</td> <td>68.20</td> <td>63.13</td> <td>42.08</td> <td>11.28</td> <td>51.35 Peak</td> </tr> </tbody> </table>				Freq	Level	Over Limit	Line	Read	Antenna	Cable	Preamp	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	1	8639.00	50.34	-17.86	68.20	59.19	37.35	7.80	54.00 Peak	2	11650.00	42.52	-11.48	54.00	48.11	38.72	9.30	53.61 Average	3	11650.00	56.47	-17.53	74.00	62.06	38.72	9.30	53.61 Peak	4	17475.00	65.14	-3.06	68.20	63.13	42.08	11.28	51.35 Peak
Freq	Level	Over Limit	Line	Read	Antenna	Cable	Preamp																																																
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB																																																
1	8639.00	50.34	-17.86	68.20	59.19	37.35	7.80	54.00 Peak																																															
2	11650.00	42.52	-11.48	54.00	48.11	38.72	9.30	53.61 Average																																															
3	11650.00	56.47	-17.53	74.00	62.06	38.72	9.30	53.61 Peak																																															
4	17475.00	65.14	-3.06	68.20	63.13	42.08	11.28	51.35 Peak																																															
<p>Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.</p> <p>Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)</p> <p>Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)</p> <p>Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.</p> <p>Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.</p> <p>Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.</p>																																																							




Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (MHz)	5825																																																								
N _{TX}	2	Polarization	H																																																								
Level (dBuV/m)			Date: 2015-09-06																																																								
<table><thead><tr><th>Freq</th><th>Level</th><th>Over Limit</th><th>Read</th><th>Antenna</th><th>Cable</th><th>Preamp</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>Line</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th></tr></thead><tbody><tr><td>1</td><td>7884.00</td><td>50.48</td><td>-17.72</td><td>68.20</td><td>60.08</td><td>36.83</td><td>7.43</td><td>53.86</td><td>Peak</td></tr><tr><td>2</td><td>11650.00</td><td>43.54</td><td>-10.46</td><td>54.00</td><td>49.13</td><td>38.72</td><td>9.30</td><td>53.61</td><td>Average</td></tr><tr><td>3</td><td>11650.00</td><td>58.19</td><td>-15.81</td><td>74.00</td><td>63.78</td><td>38.72</td><td>9.30</td><td>53.61</td><td>Peak</td></tr><tr><td>4</td><td>17475.00</td><td>67.11</td><td>-1.09</td><td>68.20</td><td>65.10</td><td>42.08</td><td>11.28</td><td>51.35</td><td>Peak</td></tr></tbody></table>				Freq	Level	Over Limit	Read	Antenna	Cable	Preamp	Remark	MHz	dBuV/m	dB	Line	Level	Factor	Loss	Factor	1	7884.00	50.48	-17.72	68.20	60.08	36.83	7.43	53.86	Peak	2	11650.00	43.54	-10.46	54.00	49.13	38.72	9.30	53.61	Average	3	11650.00	58.19	-15.81	74.00	63.78	38.72	9.30	53.61	Peak	4	17475.00	67.11	-1.09	68.20	65.10	42.08	11.28	51.35	Peak
Freq	Level	Over Limit	Read	Antenna	Cable	Preamp	Remark																																																				
MHz	dBuV/m	dB	Line	Level	Factor	Loss	Factor																																																				
1	7884.00	50.48	-17.72	68.20	60.08	36.83	7.43	53.86	Peak																																																		
2	11650.00	43.54	-10.46	54.00	49.13	38.72	9.30	53.61	Average																																																		
3	11650.00	58.19	-15.81	74.00	63.78	38.72	9.30	53.61	Peak																																																		
4	17475.00	67.11	-1.09	68.20	65.10	42.08	11.28	51.35	Peak																																																		
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.																																																											
Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)																																																											
Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)																																																											
Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																											
Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.																																																											
Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.																																																											











Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	5785					
N_{TX}	2	Polarization	H					
Level (dBuV/m)			Date: 2015-09-06					
Freq	Level	Over Limit	Line Limit	Read	Antenna Factor	Cable Loss	Preamp Factor	Remark
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 8827.00	50.67	-17.53	68.20	59.40	37.43	7.90	54.06	Peak
2 11570.00	42.07	-11.93	54.00	47.87	38.61	9.29	53.70	Average
3 11570.00	56.85	-17.15	74.00	62.65	38.61	9.29	53.70	Peak
4 17355.00	66.85	-1.35	68.20	65.28	41.66	11.33	51.42	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
 Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.
 Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.










Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT40	Test Freq. (MHz)	5755					
N _{TX}	2	Polarization	V					
Level (dBuV/m)			Date: 2015-09-06					
Freq	Level	Over Limit	Limit	Read	Antenna	Cable	Preamp	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	Remark
1	7816.00	50.61	-17.59	68.20	60.23	36.79	7.40	53.81 Peak
2	11510.00	38.90	-15.10	54.00	44.96	38.47	9.28	53.81 Average
3	11510.00	53.11	-20.89	74.00	59.13	38.50	9.28	53.80 Peak
4	17265.00	58.13	-10.07	68.20	56.89	41.36	11.35	51.47 Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.
Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.







3.7 Frequency Stability

3.7.1 Frequency Stability Limit

Frequency Stability Limit	
UNII Devices	
<input checked="" type="checkbox"/> In-band emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.	
IEEE Std. 802.11n-2009	
<input checked="" type="checkbox"/> The transmitter center frequency tolerance shall be ± 20 ppm maximum for the 5 GHz band and ± 25 ppm maximum for the 2.4 GHz band.	


3.7.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.7.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.8 for frequency stability tests
<input checked="" type="checkbox"/>	Frequency stability with respect to ambient temperature
<input checked="" type="checkbox"/>	Frequency stability when varying supply voltage
<input checked="" type="checkbox"/>	For conducted measurement.
<input checked="" type="checkbox"/>	For conducted measurements on devices with multiple transmit chains: Measurements need only to be performed on one of the active transmit chains (antenna outputs)
<input type="checkbox"/>	For radiated measurement. The equipment to be measured and the test antenna shall be oriented to obtain the maximum emitted power level.

3.7.4 Test Setup





3.7.5 Test Result of Frequency Stability

Frequency Stability Result					
Mode		Frequency Stability (ppm)			
Condition	Freq. (MHz)	0 min	2 min	5 min	10 min
T _{20°C} Vmax	CW	-11.5385	-9.6154	-9.6154	-11.5385
T _{20°C} Vmin	CW	-7.6923	-5.7692	-5.7692	-7.6923
T _{50°C} Vnom	CW	-3.8462	3.8462	3.8462	3.8462
T _{40°C} Vnom	CW	-7.6923	-7.6923	-5.7692	-5.7692
T _{30°C} Vnom	CW	-9.6154	-7.6923	-7.6923	-7.6923
T _{20°C} Vnom	CW	-9.6154	-7.6923	-7.6923	-9.6154
T _{10°C} Vnom	CW	-7.6923	-7.6923	-7.6923	-7.6923
T _{0°C} Vnom	CW	-3.8462	-5.7692	-5.7692	-7.6923
T _{-10°C} Vnom	CW	-1.5385	-1.9231	-1.9231	-1.9231
T _{-20°C} Vnom	CW	0.0000	2.7885	0.0000	2.7885
Limit (ppm)		±20			
Result		Complied			

Note 1: Measure at 85 % [Vmin] and 115 % [Vmax] of the nominal voltage [Vnom].
Note 2: The nominal voltage refer test report clause 1.1.5 for EUT operational condition.



4 Test Equipment and Calibration Data

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz ~ 2.75GHz	Apr. 15. 2015	AC Conduction
LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	8127-477	9kHz ~ 30MHz	Jan. 22, 2015	AC Conduction
RF Cable-CON	HUBER+SUHNER	RG213/U	07611832020001	9kHz ~ 30MHz	Oct. 31, 2014	AC Conduction
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	NA	AC Conduction

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSV 40	101500	9KHz~40GHz	May. 06, 2015	RF Conducted
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Jul. 28, 2015	RF Conducted
Temp. and Humidity Chamber	Giant Force	GTH-225-20-SP-SD	MAA1112-007	-20 ~ 100 °C	Apr. 07, 2015	RF Conducted

Note: Calibration Interval of instruments listed above is one year.

<Radiation Emissions below 1GHz>

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
3m Semi Anechoic Chamber	TDK	SAC-3M	03CH09-HY	30MHz ~ 1GHz 3m	Jul. 01, 2015	Radiation
Amplifier	EMC	EMC9135	980232	9kHz ~ 1.0GHz	Jan 27, 2015	Radiation
Amplifier	EMC	EMC051845	980240	500MHz ~ 18GHz	Mar. 04, 2015	Radiation
Spectrum	KEYSIGHT	N9010A	MY54200885	10Hz ~ 44GHz	Jul. 15, 2015	Radiation
Bilog Antenna	TESEQ	CBL 6112D	35418	30MHz ~ 1GHz	Mar. 30, 2015	Radiation
Horn Antenna	AARONIA AG	POWERLOG 70180	05192	1GHz ~ 18GHz	Jan. 05, 2015	Radiation
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170614	18GHz ~ 40GHz	Dec. 29, 2014	Radiation
RF Cable-R03m	Jye Bao	RG142	CB021	9kHz ~ 1GHz	Jul. 23, 2015	Radiation
RF Cable-high	Jye Bao	RG142	03CH09-HY	1GHz ~ 40GHz	Jul. 23, 2015	Radiation
Turn Table	Chain Tek	T-200S	1308028	0 ~ 360 degree	N/A	Radiation
Antenna Mast	Chain Tek	MBS-400	1308049	1 ~ 4 m	N/A	Radiation

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Amplifier	MITEQ	JS44-18004000-33-8P	1840917	18GHz ~ 40GHz	Jun. 02.2015	Radiation
Loop Antenna	ROHDE&SCHWARZ	HFH2-Z2	100330	9 kHz~30 MHz	Nov. 05, 2014	Radiation

Note: Calibration Interval of instruments listed above is two years.