



FCC Part 1 Subpart I  
FCC Part 2 Subpart J  
INDUSTRY CANADA RSS 102 ISSUE 3

**RF EXPOSURE REPORT**

**FOR**

**Intelligent Backhaul Radio ISM 5.8GHz band**

**MODEL NUMBER: IBR-1A**

**FCC ID: 2AAEH-101**

**IC: 11158A-101**

**REPORT NUMBER: 13U14996-1**

**ISSUE DATE: 2013-11-22**

*Prepared for*  
**CBF NETWORKS, INC., DBA FASTBACK NETWORKS**  
**2460 N. FIRST STREET, SUITE 200**  
**SAN JOSE, CA 95131**

*Prepared by*  
**UL LLC**  
**1285 WALT WHITMAN RD.**  
**MELVILLE, NY 11747, U.S.A.**  
**TEL: (631) 271-6200**  
**FAX: (877) 854-3577**

**NVLAP**<sup>®</sup>

NVLAP LAB CODE 100255-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--	2013-10-22	Initial Issue	Joseph Danisi
--	2013-11-22	Corrected table page 10 , removed tables not applicable, added worst case tolerance to measured power readings, added power density table at 20cm	Joseph Danisi

## TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS .....	4
2. TEST METHODOLOGY .....	5
3. REFERENCES .....	5
4. FACILITIES AND ACCREDITATION .....	5
5. MAXIMUM PERMISSIBLE RF EXPOSURE .....	6
5.1. FCC RULES .....	6
5.2. IC RULES .....	7
5.3. EQUATIONS .....	8
5.4. LIMITS AND IC EXEMPTION .....	9
6. RF EXPOSURE RESULTS .....	10

## 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** CBF NETWORKS, INC., DBA FASTBACK NETWORKS  
2460 N. FIRST STREET, SUITE 200  
SAN JOSE, CA 95131

**EUT DESCRIPTION:** Intelligent Backhaul Radio ISM 5.8GHz band

**MODEL:** IBR-1A

**SERIAL NUMBER:** 53


**DATE TESTED:** 2013-05-02 to 2013-09-16

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 1 SUBPART I & PART 2 SUBPART J	Pass
INDUSTRY CANADA RSS 102 ISSUE 3	Pass

UL LLC calculated the RF Exposure of the above equipment in accordance with the requirements set forth in the above standards using test results reported in the test report documents referenced below and/or documentation furnished by the applicant. All indications of Pass/Fail in this report are opinions expressed by UL LLC based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL LLC and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL LLC will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For UL CCS By:



Calculated By:



---

Bob DeLisi  
WiSE Principal Engineer  
UL

---

Joseph Danisi  
WiSE Project Lead  
UL

## 2. TEST METHODOLOGY

All calculations were made in accordance with FCC OET Bulletin 65 Edition 97-01 and IC Safety Code 6.

## 3. REFERENCES

All measurements were made as documented in test report UL Document 13U14996 for operation in the 5 GHz bands.

Output power, Duty cycle and Antenna gain data is excerpted from the applicable test reports.

Antenna gain data is excerpted from product documentation provided by the applicant.

## 4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 1285 Walt Whitman Rd. Melville, NY 11747, USA.

UL LLC is accredited by NVLAP, Laboratory Code 100255-0. The full scope of accreditation can be viewed at <http://ts.nist.gov/standards/scopes/1002550.htm>.

## 5. MAXIMUM PERMISSIBLE RF EXPOSURE

### 5.1. FCC RULES

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

## 5.2. IC RULES

IC Safety Code 6, Section 2.2.1 (a) A person other than an RF and microwave exposed worker shall not be exposed to electromagnetic radiation in a frequency band listed in Column 1 of Table 5, if the field strength exceeds the value given in Column 2 or 3 of Table 5, when averaged spatially and over time, or if the power density exceeds the value given in Column 4 of Table 5, when averaged spatially and over time.

**Table 5**  
**Exposure Limits for Persons Not Classed As RF and Microwave Exposed Workers (Including the General Public)**

1 Frequency (MHz)	2 Electric Field Strength; rms (V/m)	3 Magnetic Field Strength; rms (A/m)	4 Power Density (W/m <sup>2</sup> )	5 Averaging Time (min)
0.003–1	280	2.19		6
1–10	280/ <i>f</i>	2.19/ <i>f</i>		6
10–30	28	2.19/ <i>f</i>		6
30–300	28	0.073	2*	6
300–1 500	1.585 <i>f</i> <sup>0.5</sup>	0.0042 <i>f</i> <sup>0.5</sup>	<i>f</i> /150	6
1 500–15 000	61.4	0.163	10	6
15 000–150 000	61.4	0.163	10	616 000/ <i>f</i> <sup>1.2</sup>
150 000–300 000	0.158 <i>f</i> <sup>0.5</sup>	4.21 × 10 <sup>-4</sup> <i>f</i> <sup>0.5</sup>	6.67 × 10 <sup>-5</sup> <i>f</i>	616 000/ <i>f</i> <sup>1.2</sup>

\* Power density limit is applicable at frequencies greater than 100 MHz.

**Notes:**

1. Frequency, *f*, is in MHz.
2. A power density of 10 W/m<sup>2</sup> is equivalent to 1 mW/cm<sup>2</sup>.
3. A magnetic field strength of 1 A/m corresponds to 1.257 microtesla (μT) or 12.57 milligauss (mG).

### 5.3. EQUATIONS

#### POWER DENSITY

Power density is given by:

$$S = \text{EIRP} / (4 * \text{Pi} * D^2)$$

Where

S = Power density in mW/cm<sup>2</sup>

EIRP = Equivalent Isotropic Radiated Power in mW

D = Separation distance in cm

Power density in units of mW/cm<sup>2</sup> is converted to units of W/m<sup>2</sup> by multiplying by 10.

#### DISTANCE

Distance is given by:

$$D = \text{SQRT} (\text{EIRP} / (4 * \text{Pi} * S))$$

Where

D = Separation distance in cm

EIRP = Equivalent Isotropic Radiated Power in mW

S = Power density in mW/cm<sup>2</sup>

#### SOURCE-BASED DUTY CYCLE

Where applicable (for example, multi-slot cell phone applications) a duty cycle factor may be applied.

$$\text{Source-based time-averaged EIRP} = (\text{DC} / 100) * \text{EIRP}$$

Where

DC = Duty Cycle in %, as applicable

EIRP = Equivalent Isotropic Radiated Power in W

### **MIMO AND COLOCATED TRANSMITTERS**

For multiple colocated transmitters operating simultaneously in frequency bands where different limits apply:

The Power Density at the specified separation distance is calculated for each transmitter chain or transmitter.

The fraction of the exposure limit is calculated for each chain or transmitter as  
(Power Density of chain or transmitter) / (Limit applicable to that chain or transmitter).

The fractions are summed.

Compliance is established if the sum of the fractions is less than or equal to one.

### **5.4. LIMITS AND IC EXEMPTION**

#### **FIXED LIMITS**

For operation in the 5 GHz band:

From FCC §1.1310 Table 1 (B), the maximum value of  $S = 1.0 \text{ mW/cm}^2$

From IC Safety Code 6, Section 2.2 Table 5 Column 4,  $S = 10 \text{ W/m}^2$

#### **INDUSTRY CANADA EXEMPTION**

RSS-102 Clause 2.5.2 RF exposure evaluation is required if the separation distance between the user and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 1.5 GHz and the maximum e.i.r.p. of the device is equal to or less than 2.5 W;
- at or above 1.5 GHz and the maximum e.i.r.p. of the device is equal to or less than 5 W.

## 6. RF EXPOSURE RESULTS

In the table(s) below, Power and Gain are entered in units of dBm and dBi respectively and conversions to linear forms are used for the calculations.

(Single chain transmitters, no colocation, 20 cm MPE distance)

Band	Mode	Separation Distance (cm)	Output Power (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	EIRP (mW)	FCC Power Density (mW/cm^2)	IC Density (W/m^2)
5 GHz 35MHz	WLAN	20	25.47	10.50	100.0	3953.7	0.787	7.87
5 GHz 18MHz	WLAN	20	25.10	10.50	100.0	3630.8	0.723	7.23
5 GHz 9MHz	WLAN	20	23.91	10.50	100.0	2760.6	0.549	5.49

Calculated using the worst case output power also a tolerance of 0.5 was added to output power.

(MIMO and/or Colocated transmitters all with same Power Density limit, MPE distance > 20 cm)

Multiple chain or colocated transmitters									
Band	Mode	Chain for MIMO	FCC Limit (mW/cm^2)	IC Limit (W/m^2)	Output Power (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	EIRP (mW)	Separatio Distance (cm)
5 GHz 35MHz	WLAN	0			22.68	10.50	100.0	2079.7	
5 GHz 35MHz	WLAN	1			21.91	10.50	100.0	1741.8	
Combined			1.00	10.0				3821.5	17.44

Multiple chain or colocated transmitters									
Band	Mode	Chain for MIMO	FCC Limit (mW/cm^2)	IC Limit (W/m^2)	Output Power (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	EIRP (mW)	Separatio Distance (cm)
5GHz 18MHz	WLAN	0			21.30	10.50	100.0	1513.6	
5 GHz 18MHz	WLAN	1			21.26	10.50	100.0	1499.7	
Combined			1.00	10.0				3013.2	15.49

Multiple chain or colocated transmitters									
Band	Mode	Chain for MIMO	FCC Limit (mW/cm^2)	IC Limit (W/m^2)	Output Power (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	EIRP (mW)	Separatio Distance (cm)
5 GHz 9MHz	WLAN	0			22.89	10.50	100.0	2182.7	
5 GHz 9MHz	WLAN	1			22.03	10.50	100.0	1790.6	
Combined			1.00	10.0				3973.3	17.79

Calculated using the worst case measured power also a tolerance of 0.5 was added to worst case measured power.

(MIMO and/or Colocated transmitters with different Power Density limits among bands)

**Notes:**

- 1) For MPE the new KDB 447498 requires the calculations to use the maximum rated power; that power should be declared by the manufacturer, and should not be lower than the measured power. If the power has a tolerance then we also need to check that the measured power is within the tolerance.
- 2) A tolerance value of +/- 0.5 dB was included in the output power values above to cover the output power tolerance of +/-0.5dB under extreme conditions in the real field as declared by the client.
- 3) The manufacturer configures output power so that the maximum power, after accounting for manufacturing tolerances, will never exceed the maximum power level measured.
- 4) The output power in the tables above is the maximum power per chain among various channels and various modes within the specific band.
- 5) The antenna gain in the tables above is the maximum antenna gain among various channels within the specified band.

**END OF REPORT**