



Report No.: AGC00634130501FE08

Page 1 of 47

---

# FCC Test Report

---

Report No.: AGC00634130501FE08

**FCC ID** : 2AAEELSWIPE9X

**APPLICATION PURPOSE** : Original Equipment

**PRODUCT DESIGNATION** : GSM Mobile Phone

**BRAND NAME** : Swipe

**MODEL NAME** : Swipe 9X

**CLIENT** : Swipe Telecom LLP

**DATE OF ISSUE** : May 28,2013

**STANDARD(S)** : FCC Part 15 Rules

**REPORT VERSION** : V1.0

**Attestation of Global Compliance (Shenzhen) Co., Ltd**

**CAUTION:**

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

**Report Revise Record**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	May 28,2013	Valid	Original Report

## TABLE OF CONTENTS

<b>1. VERIFICATION OF COMPLIANCE.....</b>	<b>5</b>
<b>2. GENERAL INFORMATION .....</b>	<b>6</b>
2.1 PRODUCT DESCRIPTION .....	6
2.2 RELATED SUBMITTAL(S)/GRANT(S).....	6
2.3 TEST METHODOLOGY .....	6
2.4 TEST FACILITY .....	6
2.5 SPECIAL ACCESSORIES.....	6
2.6 EQUIPMENT MODIFICATIONS.....	6
<b>3. SYSTEM TEST CONFIGURATION.....</b>	<b>7</b>
3.1 CONFIGURATION OF TESTED SYSTEM.....	7
3.2 EQUIPMENT USED IN TESTED SYSTEM .....	7
<b>4. SUMMARY OF TEST RESULTS.....</b>	<b>8</b>
<b>5. DESCRIPTION OF TEST MODES.....</b>	<b>8</b>
<b>6. ANTENNA REQUIREMENT .....</b>	<b>9</b>
6.1. STANDARD APPLICABLE .....	9
6.2. TEST RESULT .....	9
<b>7. RADIATED EMISSION.....</b>	<b>10</b>
7.1 MEASUREMENT PROCEDURE.....	10
7.2 TEST SETUP.....	11
7.3 LIMITS AND MEASUREMENT RESULT .....	12
7.4 TEST RESULT .....	12
<b>8. BAND EDGE EMISSION.....</b>	<b>25</b>
8.1. MEASUREMENT PROCEDURE .....	25
8.2. TEST SET-UP .....	25
8.3. TEST RESULT .....	26
<b>9. 6DB BANDWIDTH .....</b>	<b>30</b>
9.1. TEST EQUIPMENT LIST AND DETAILS.....	30
9.2. TEST PROCEDURE.....	30
9.3. SUMMARY OF TEST RESULTS/PLOTS .....	30
<b>10. CONDUCTED OUTPUT POWER .....</b>	<b>33</b>
10.1. MEASUREMENT PROCEDURE .....	33
10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	33
10.3. LIMITS AND MEASUREMENT RESULT .....	33
<b>11. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY .....</b>	<b>34</b>
11.1 MEASUREMENT PROCEDURE .....	34
11.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	34

11.3 MEASUREMENT EQUIPMENT USED.....	34
11.4 LIMITS AND MEASUREMENT RESULT.....	34
<b>12. FCC LINE CONDUCTED EMISSION TEST .....</b>	<b>37</b>
12.1 LIMITS .....	37
12.2 TEST SETUP.....	37
12.3 PRELIMINARY PROCEDURE .....	38
12.4 FINAL TEST PROCEDURE.....	38
12.5 TEST RESULT OF POWER LINE .....	39
<b>APPENDIX A: PHOTOGRAPHS OF TEST SETUP .....</b>	<b>41</b>
<b>APPENDIX B: PHOTOGRAPHS OF EUT .....</b>	<b>42</b>


## 1. VERIFICATION OF COMPLIANCE

<b>Applicant</b>	Swipe Telecom LLP
<b>Address</b>	Unit No. S-4, S-5, 2nd Floor, Metropole Building, Near Inox Theatre, Bundgarden Road, Pune -411001
<b>Manufacturer</b>	United Time Technology Co., Ltd.
<b>Address</b>	Room 1001 Microprofit Building, 6 Gaoxin south Road, High-Tech Park, Nanshan Shenzhen, China
<b>Product Designation</b>	GSM Mobile Phone
<b>Brand Name</b>	Swipe
<b>Test Model</b>	Swipe 9X
<b>Date of test</b>	May 17,2013 to May 27,2013
<b>Deviation</b>	None
<b>Condition of Test Sample</b>	Normal
<b>Report Template</b>	AGCRT-US-BLE/RF (2013-03-01)

### WE HEREBY CERTIFY THAT:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with requirement of FCC Part 15 Rules requirement.

Prepared By



Wall Huang May 28,2013

Checked By



Forrest Lei May 28,2013

Authorized By



Solger Zhang May 28,2013

## 2.GENERAL INFORMATION

### 2.1 PRODUCT DESCRIPTION

The EUT is a **GSM Mobile Phone** designed as a “Communication Device”. It is designed by way of utilizing the FHSS technology to achieve the system operation.

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz
Bluetooth Version	V4.0
Modulation	GFSK
Number of channels	40 Channel(37 Hopping Channel,3 advertising Channel)
Antenna Designation	Integral antenna
Antenna Gain	1.0dBi
Hardware Version	12G21_V02
Software Version	Swipe Fablet F9 ALPS.ICS.MP.V1.11
Power Supply	DC3.7V by Built-in Li-ion Battery

### 2.2 RELATED SUBMITTAL(S)/GRANT(S)

This submittal(s) (test report) is intended for **FCC ID: 2AAEELSWIPE9X** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

### 2.3 TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions. The EUT was tested in all three orthogonal planes and the worse case was showed.

### 2.4 TEST FACILITY

All measurement facilities used to collect the measurement data are located at  
Attestation of Global Compliance (Shenzhen) Co, Ltd

2/F., Building 2, No.1-No.4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen, Guangdong, China.

FCC register No.: 259865

### 2.5 SPECIAL ACCESSORIES

Refer to section 2.2.


### 2.6 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

### 3. SYSTEM TEST CONFIGURATION

#### 3.1 CONFIGURATION OF TESTED SYSTEM

Configuration:



#### 3.2 EQUIPMENT USED IN TESTED SYSTEM

Item	Equipment	Model No.	ID or Specification	Note
1	GSM Mobile Phone	Swipe 9X	FCC ID: 2AAEELSWIPE9X	EUT
2	Adapter	Swipe 9X	DC5.0V / 680mA	Accessory
3	Battery	Swipe 9X	DC3.7V/ 2000 mAh	Accessory
4	Earphone	Swipe 9X	N/A	Accessory
5	USB Cable	Swipe 9X	N/A	Accessory

#### 4. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§ 15.203	Antenna Requirement	Compliant
§15.209 §15.247(d)	Radiated Emission	Compliant
§15.247(d)	Band Edges	Compliant
§15.247	6 dB Bandwidth	Compliant
§15.247(b)	Conducted Power	Compliant
§15.247(e)	Maximum Conducted Output Power SPECTRAL Density	Compliant
§15.207	Line Conduction Emission	Compliant

#### 5. DESCRIPTION OF TEST MODES

The EUT has been operated in three modulations: GFSK independently.

NO.	TEST MODE DESCRIPTION
1	Low channel TX
2	Middle channel TX
3	High channel TX
4	Normal Operating (BT)

Note:

1. All the test modes can be supply by Built-in Li-ion battery, only the result of the worst case was recorded in the report if no any records.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

## **6. ANTENNA REQUIREMENT**

### **6.1. STANDARD APPLICABLE**

According to FCC 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

### **6.2. TEST RESULT**

This product has a permanent antenna, fulfill the requirement of this section.


## 7. RADIATED EMISSION

### 7.1 MEASUREMENT PROCEDURE


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.

## 7.2 TEST SETUP


### RADIATED EMISSION TEST SETUP BELOW 30MHz



### RADIATED EMISSION TEST SETUP 30MHz-1000MHz



### RADIATED EMISSION TEST SETUP ABOVE 1000MHz



### 7.3 LIMITS AND MEASUREMENT RESULT

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested For restricted band radiated emission,  
the test records reported below are the worst result compared to other modes.

### 7.4 TEST RESULT

#### RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

## RADIATED EMISSION BELOW 1GHZ

### RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1  
Limit: FCC Class B 3M Radiation  
EUT: GSM Mobile Phone  
M/N: Swipe 9X  
Mode: Low Channel TX  
Note:

Polarization: **Horizontal**

Power:

Distance: 3m


Temperature: 26

Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		97.9000	14.17	13.24	27.41	43.50	-16.09	peak			
2		169.0333	11.47	11.18	22.65	43.50	-20.85	peak			
3		261.1832	17.13	13.25	30.38	46.00	-15.62	peak			
4	*	367.8833	13.90	19.16	33.06	46.00	-12.94	peak			
5		560.2667	7.31	24.02	31.33	46.00	-14.67	peak			
6		844.8000	-1.78	30.81	29.03	46.00	-16.97	peak			

**RESULT: PASS**

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL -VERTICAL




Site: site #1  
 Limit: FCC Class B 3M Radiation  
 EUT: GSM Mobile Phone  
 M/N: Swipe 9X  
 Mode: Low Channel TX  
 Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna	Table	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		Height	Degree	
1	*	89.8167	23.22	8.37	31.59	43.50	-11.91	peak			
2		149.6333	10.45	14.15	24.60	43.50	-18.90	peak			
3		264.4167	15.73	14.67	30.40	46.00	-15.60	peak			
4		388.9000	13.27	19.06	32.33	46.00	-13.67	peak			
5		545.7166	8.78	23.60	32.38	46.00	-13.62	peak			
6		877.1333	-0.14	30.25	30.11	46.00	-15.89	peak			

RESULT: PASS

## RADIATED EMISSION TEST- (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1  
Limit: FCC Class B 3M Radiation  
EUT: GSM Mobile Phone  
M/N: Swipe 9X  
Mode: Middle Channel TX  
Note:

Polarization: *Horizontal*

Temperature: 26

## Power


Humidity: 60 %

Distance: 3m

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	89.8167	21.72	8.37	30.09	43.50	-13.41	peak			
2		146.4000	7.87	13.29	21.16	43.50	-22.34	peak			
3		257.9500	14.03	14.23	28.26	46.00	-17.74	peak			
4		375.9667	11.90	19.21	31.11	46.00	-14.89	peak			
5		557.0333	8.37	23.93	32.30	46.00	-13.70	peak			
6		877.1333	-0.14	30.25	30.11	46.00	-15.89	peak			

## RESULT: PASS

## RADIATED EMISSION TEST- (30MHZ-1GHZ)- MIDDLE CHANNEL -VERTICAL



Site: site #1  
Limit: FCC Class B 3M Radiation  
EUT: GSM Mobile Phone  
M/N: Swipe 9X  
Mode: Middle Channel TX  
Note:

Polarization: *Vertical*

Temperature: 26

Power:

Humidity: 60 %

FUT: GSM Mobile Phone

Distance: 3m

M/N: Swipe 9X

Mode: Middle Channel TX

Note:-

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		89.8167	19.72	8.37	28.09	43.50	-15.41	peak			
2		154.4833	13.21	12.18	25.39	43.50	-18.11	peak			
3		264.4167	15.73	14.67	30.40	46.00	-15.60	peak			
4	*	388.9000	14.77	19.06	33.83	46.00	-12.17	peak			
5		566.7333	8.58	24.23	32.81	46.00	-13.19	peak			
6		877.1333	-0.14	30.25	30.11	46.00	-15.89	peak			

## RESULT: PASS

## RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1 Polarization: *Horizontal* Temperature: 26  
Limit: FCC Class B 3M Radiation Power: Humidity: 60 %  
EUT: GSM Mobile Phone Distance: 3m  
M/N: Swipe 9X  
Mode: High Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		91.4333	13.57	16.56	30.13	43.50	-13.37	peak			
2		172.2666	14.16	11.18	25.34	43.50	-18.16	peak			
3		261.1832	15.13	13.25	28.38	46.00	-17.62	peak			
4	*	384.0500	15.28	18.55	33.83	46.00	-12.17	peak			
5		569.9666	6.72	24.33	31.05	46.00	-14.95	peak			
6		838.3333	-0.24	31.08	30.84	46.00	-15.16	peak			

## RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL




Site: site #1 Polarization: **Vertical** Temperature: 26  
 Limit: FCC Class B 3M Radiation Power: Humidity: 60 %  
 EUT: GSM Mobile Phone Distance: 3m  
 M/N: Swipe 9X  
 Mode: High Channel TX  
 Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		101.1333	14.34	12.17	26.51	43.50	-16.99	peak			
2		172.2666	18.16	11.18	29.34	43.50	-14.16	peak			
3		259.5667	18.47	12.56	31.03	46.00	-14.97	peak			
4	*	382.4332	14.74	18.83	33.57	46.00	-12.43	peak			
5		493.9833	5.45	22.57	28.02	46.00	-17.98	peak			
6		566.7333	5.95	24.23	30.18	46.00	-15.82	peak			

**RESULT: PASS**

## RADIATED EMISSION ABOVE 1GHZ



Site: site #1 Polarization: **Horizontal** Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %  
EUT: GSM Mobile Phone Distance: 3m  
M/N: Swipe 9X  
Mode: Low Channel TX  
Note:


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2402.085	72.63	0.00	72.63	74.00	-1.37	peak			
2		4133.333	44.23	0.00	44.23	74.00	-29.77	peak			
3		5091.667	44.99	0.00	44.99	74.00	-29.01	peak			

## RESULT: PASS

Note : Marker 1 is fundamental frequency.

6~25GHz at least have 20dB margin. No recording in the test report.

## RADIATED EMISSION TEST-(ABOVE 1GHZ)-LOW CHANNEL-VERTICAL



Site: site #1 Polarization: *Vertical* Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %  
EUT: GSM Mobile Phone Distance: 3m  
M/N: Swipe 9X  
Mode: Low Channel TX  
Note:


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2402.096	71.13	0.00	71.13	74.00	-2.87	peak			
2		4291.667	43.78	0.00	43.78	74.00	-30.22	peak			
3		4691.667	44.91	0.00	44.91	74.00	-29.09	peak			

**RESULT: PASS**

Note : Marker 1 is fundamental frequency.

6~25GHz at least have 20dB margin. No recording in the test report.

## RADIATED EMISSION TEST-(ABOVE 1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1 Polarization: *Horizontal* Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %  
EUT: GSM Mobile Phone Distance: 3m  
M/N: Swipe 9X  
Mode: Middle Channel TX  
Note:


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2442.071	72.80	0.00	72.80	74.00	-1.20	peak			
2		3883.333	39.86	0.00	39.86	74.00	-34.14	peak			
3		5766.667	41.31	0.00	41.31	74.00	-32.69	peak			

## RESULT: PASS

Note: Marker 1 fundamental frequency.

6~25GHz at least have 20dB margin. No recording in the test report.

RADIATED EMISSION TEST-(ABOVE 1GHZ)-MIDDLE CHANNEL-VERTICAL



Site: site #1 Polarization: **Vertical** Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %  
EUT: GSM Mobile Phone Distance: 3m  
M/N: Swipe 9X  
Mode: Middle Channel TX  
Note:


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2442.092	71.08	0.00	71.08	74.00	-2.92	peak			
2		3950.000	36.01	0.00	36.01	74.00	-37.99	peak			
3		4483.333	37.31	0.00	37.31	74.00	-36.69	peak			

**RESULT: PASS**

Note: Marker 1 is the fundamental frequency.

6~25GHz at least have 20dB margin. No recording in the test report.

## RADIATED EMISSION TEST-(ABOVE 1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1 Polarization: *Horizontal* Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %  
EUT: GSM Mobile Phone Distance: 3m  
M/N: Swipe 9X  
Mode: High Channel TX  
Note:


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.075	72.48	0.00	72.48	74.00	-1.52	peak			
2		3550.000	40.57	0.00	40.57	74.00	-33.43	peak			
3		4066.667	42.49	0.00	42.49	74.00	-31.51	peak			

## RESULT: PASS

Note: Marker 1 is the fundamental frequency.

6~25GHz at least have 20dB margin. No recording in the test report.

## RADIATED EMISSION TEST-(ABOVE 1GHZ)-HIGH CHANNEL-VERTICAL



Site: site #1 Polarization: **Vertical** Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %  
EUT: GSM Mobile Phone Distance: 3m  
M/N: Swipe 9X  
Mode: High Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.077	71.05	0.00	71.05	74.00	-2.95	peak			
2		3791.667	38.30	0.00	38.30	74.00	-35.70	peak			
3		4633.333	38.28	0.00	38.28	74.00	-35.72	peak			

## RESULT: PASS

Note: Marker 1 is the fundamental frequency.

6~25GHz at least have 20dB margin. No recording in the test report.

## **8. BAND EDGE EMISSION**

### **8.1. MEASUREMENT PROCEDURE**


1. Set the EUT Work on the top, the bottom operation frequency individually.
2. Set SPA Start or Stop Frequency = Operation Frequency, RBW $\geq$ 1%span, VBW $\geq$ RBW
3. The band edges was measured and recorded.

### **8.2. TEST SET-UP**

Radiated same as 6.2

### 8.3. TEST RESULT


## TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Horizontal



Site: site #1 Polarization: *Horizontal* Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %  
EUT: GSM Mobile Phone Distance: 3m  
M/N: Swipe 9X  
Mode: Low Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2390.000	24.97	-9.69	15.28	74.00	-58.72	peak			
2		2392.667	27.94	-9.69	18.25	74.00	-55.75	peak			
3		2398.000	28.79	-9.68	19.11	74.00	-54.89	peak			
4	*	2402.076	71.39	-9.68	61.71	74.00	-12.29	peak			

TEST PLOT OF BAND EDGE FOR LOW CHANNEL - Vertical




Site: site #1 Polarization: *Vertical* Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %  
EUT: GSM Mobile Phone Distance: 3m  
M/N: Swipe 9X  
Mode: Low Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2390.000	22.85	-9.69	13.16	74.00	-60.84	peak			
2		2396.625	26.89	-9.68	17.21	74.00	-56.79	peak			
3		2398.875	26.96	-9.68	17.28	74.00	-56.72	peak			
4	*	2402.105	71.16	-9.68	61.48	74.00	-12.52	peak			

## RESULT: PASS


## TEST PLOT OF BAND EDGE FOR HIGH CHANNEL –Horizontal



Site: site #1 Polarization: *Horizontal* Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %  
EUT: GSM Mobile Phone Distance: 3m  
M/N: Swipe 9X  
Mode: High Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.096	72.23	-9.59	62.64	74.00	-11.36	peak			
2		2483.500	21.86	-9.59	12.27	74.00	-61.73	peak			
3		2483.867	24.30	-9.59	14.71	74.00	-59.29	peak			
4		2490.540	23.86	-9.58	14.28	74.00	-59.72	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Vertical



Site: site #1 Polarization: **Vertical** Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %  
EUT: GSM Mobile Phone Distance: 3m  
M/N: Swipe 9X  
Mode: High Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.074	71.30	-9.59	61.71	74.00	-12.29	peak			
2		2483.500	26.74	-9.59	17.15	74.00	-56.85	peak			
3		2487.240	25.84	-9.58	16.26	74.00	-57.74	peak			
4		2491.053	24.78	-9.58	15.20	74.00	-58.80	peak			

## RESULT: PASS

## 9. 6DB BANDWIDTH

### 9.1. TEST EQUIPMENT LIST AND DETAILS

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
PSA SERIES SPECTRUM ANALYZER	AGILENT	E4440A	US41421290	07/18/2012	07/17/2013
RECEIVER ANTENNA	ETS	2175	57337	07/18/2012	07/17/2013


### 9.2. TEST PROCEDURE

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
3. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 KHz, VBW = RBW.
4. Set SPA Trace 1 Max hold, then View.

### 9.3. SUMMARY OF TEST RESULTS/PLOTS

Channel	6dB Bandwidth (KHz)	Minimum Limit (KHz)	Pass/Fail
Low	689.439	500KHz	Pass
Middle	693.776		Pass
High	693.185		Pass


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




## 10. CONDUCTED OUTPUT POWER

### 10.1. MEASUREMENT PROCEDURE

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Connect EUT RF output port to power meter through an RF attenuator
3. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
4. Set the RBW greater than 6DB bandwidth of emission.
5. Record the maximum power from the power meter.
6. The maximum peak power shall be less 1 Watt (30dBm).

**Note :** The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

### 10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)



### 10.3. LIMITS AND MEASUREMENT RESULT

Channel	Peak Power (dBm)	Applicable Limits (dBm)	Pass/Fail
Low Channel	2.32	20	Pass
Middle Channel	2.14	20	Pass
High Channel	1.98	20	Pass

## 11. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY

### 11.1 MEASUREMENT PROCEDURE

- (1). The EUT was placed on a turn table which is 0.8m above ground plane.
- (2). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (3). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (4). Set SPA Trace 1 Max hold, then View.

**Note:** The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

### 11.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)



Refer To Section 8.2

### 11.3 MEASUREMENT EQUIPMENT USED


Refer To Section 6.

### 11.4 LIMITS AND MEASUREMENT RESULT

Channel No.	PSD (dBm)	Limit (dBm)	Result
Low Channel	-18.66	8	Pass
Middle Channel	-20.68	8	Pass
High Channel	-17.67	8	Pass



TEST PLOT OF SPECTRAL DENSITY FOR HIGH CHANNEL




## 12. FCC LINE CONDUCTED EMISSION TEST

### 12.1 LIMITS

Frequency	Maximum RF Line Voltage	
	Q.P. ( dBuV)	Average ( dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

**\*\*Note:** 1. The lower limit shall apply at the transition frequency.  
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

### 12.2 TEST SETUP



A: Powered through filter

### 12.3 PRELIMINARY PROCEDURE

- 1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per ANSI C63.4.
- 3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4) All support equipments received AC120V/60Hz power from a LISN, if any.
- 5) The EUT received power by adapter which received power by a LISN.
- 6) The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7) Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8) During the above scans, the emissions were maximized by cable manipulation.
- 9) The following test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

### 12.4 FINAL TEST PROCEDURE

- 10) EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 11) 2) A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 12) 3) The test data of the worst case condition(s) was reported on the Summary Data page.

## 12.5 TEST RESULT OF POWER LINE


Line Conducted Emission Test Line 1-L



Site: Conduction Phase: **L1** Temperature: 26  
 Limit: FCC Class B Conduction(QP) Power: Humidity: 60 %  
 EUT: GSM Mobile Phone  
 M/N: Swipe 9X  
 Mode: Normal Operating(BT)  
 Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1737	35.61		20.73	10.19	45.80		30.92	64.78	54.78	-18.98	-23.86	P	
2	0.2058	35.38		18.87	10.22	45.60		29.09	63.37	53.37	-17.77	-24.28	P	
3	0.7419	30.35		11.44	10.32	40.67		21.76	56.00	46.00	-15.33	-24.24	P	
4	1.1737	27.13		10.13	10.37	37.50		20.50	56.00	46.00	-18.50	-25.50	P	
5	5.1139	24.62		9.52	10.24	34.86		19.76	60.00	50.00	-25.14	-30.24	P	
6	24.0180	24.12		16.75	10.11	34.23		26.86	60.00	50.00	-25.77	-23.14	P	

Line Conducted Emission Test Line 1-N



Site: Conduction Phase: *N* Temperature: 26  
 Limit: FCC Class B Conduction(QP) Power: Humidity: 60 %  
 EUT: GSM Mobile Phone  
 M/N: Swipe 9X  
 Mode: Normal Operating(BT)  
 Note:


No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	Avg		dB	Peak	QP	Avg	QP	Avg	QP	Avg	
1	0.1737	36.08		21.40	10.19	46.27		31.59	64.78	54.78	-18.51	-23.19	P	
2	0.6580	28.97		13.02	10.33	39.30		23.35	56.00	46.00	-16.70	-22.65	P	
3	1.2419	29.31		9.75	10.37	39.68		20.12	56.00	46.00	-16.32	-25.88	P	
4	1.8300	28.78		6.96	10.27	39.05		17.23	56.00	46.00	-16.95	-28.77	P	
5	4.7698	26.22		10.77	10.23	36.45		21.00	56.00	46.00	-19.55	-25.00	P	
6	18.6579	22.86		5.94	10.12	32.98		16.06	60.00	50.00	-27.02	-33.94	P	

## APPENDIX A: PHOTOGRAPHS OF TEST SETUP

### FCC LINE CONDUCTED EMISSION TEST SETUP



FCC RADIATED EMISSION TEST SETUP



## APPENDIX B: PHOTOGRAPHS OF EUT

### TOTAL VIEW OF EUT




TOP VIEW OF EUT



BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



BACK VIEW OF EUT



LEFT VIEW OF EUT



RIGHT VIEW OF EUT




OPEN VIEW OF EUT-1



OPEN VIEW OF EUT-2



INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



----END OF REPORT----