

MPE Analysis Report

Applicant: Deere & Company
Product Description: Deere & Company Instrument Cluster with Bluetooth LE (BLE)
Model No.: PH85239277
FCC ID: 2AAFX-M2H5BLE

The product, Deere & Company Instrument Cluster with Bluetooth LE (BLE), operates on Vehicle Battery (12VDC) & reads vehicle information from the CAN bus and convey that information to user's mobile device via BLE.

For Maximum Permissible Exposure (MPE) evaluation of the unit, the maximum power density at 20 cm from this transmitter shall be less than the General Population / Uncontrolled MPE limit in OET Bulletin 65 and meet the requirement listed in KDB447498.

For the 2.4GHz Bluetooth BLE portion of the unit, the measured powers among all the measured channels were within its production tolerance. The antenna gain is 0.3 dBi and its maximum source-based time-averaging duty factor is 100%. From these data and its operating configuration, the exposed power density at a distance (R) of 20 cm from the center of radiation of the antenna can be calculated according to OET Bulletin 65 as follow:

The EIRP radiated power
= conducted power (maximum) + antenna gain
= (16) dBm + 0.3 dBi
= 16.3 dBm (42.7 mW)

The radiated (EIRP) source-based time-averaging output power
= $(42.7 * 1)$ mW
= 42.7 mW

The power density at 20 cm from the antenna
= $EIRP / 4\pi R^2$
= 0.0085 mW cm⁻²

In the frequency range of 1,500 - 100,000MHz, the MPE limit is 1.0 mWcm⁻² for general population and uncontrolled exposure. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structures and body of the user or nearby persons.

The following RF exposure statement is proposed to be included in the user manual:

“ FCC RF Radiation Exposure Statement
Caution: To maintain compliance with the FCC’s RF exposure guidelines, place the unit at least 20cm from nearby persons.”