

Test report No:  
NIE: 71232RAN.001A1

## Assessment report RF EXPOSURE REPORT ACCORDING TO FCC 47 CFR Part 2.1091

(*) Identification of item under evaluation	LTE Cat-M Cellular communication module in SiP packaging
(*) Trademark	Sequans Communication
(*) Model and /or type reference	SKY66431
(*) Other identification of the product	HW version: V1 SW Version: LR8.0.6.1-56267 IMEI TAC: 01604700 FCC ID: 2AAGM66431 IC ID: 12732A-66431
(*) Features	LTE-M, 3GPP LTE Release 14
(*) Manufacturer	SEQUANS COMMUNICATIONS 55 Boulevard Charles de Gaulle, 92700 Colombes, France
Test method requested, standard	FCC 47 CFR Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices.
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Miguel Lacave Antennas Lab Manager
Date of issue	2024-04-22
Report template No	FAN36_01 (*) "Data provided by the client"

## Index

Competences and guarantees .....	3
General conditions .....	3
Data provided by the client.....	3
Identification of the client.....	3
Document history .....	3
Appendix A: FCC RF Exposure assessment result .....	4
General description of the equipment under evaluation .....	5
Maximum Antenna Gain determination for RF Exposure compliance .....	5
Appendix B: FCC RF Exposure information .....	7
FCC RF Exposure evaluation .....	8
FCC MPE Evaluation.....	9
FCC Cellular bands limits .....	9

## Competences and guarantees

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification, S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification, S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification, S.A.U. at the time of performance of the test.

DEKRA Testing and Certification, S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Assessment Report apply only to the particular item under test established in this document.

**IMPORTANT:** No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification, S.A.U.

## General conditions

1. This report is only referred to the item that has undergone the assessment.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification, S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification, S.A.U. and the Accreditation Bodies

## Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item under evaluation", "Trademark", "Model and/or type reference", "Other identification of the product", "Features", "Manufacturer" and "General description of the device").
2. Request for evaluation under mobile exposure conditions.

DEKRA Testing and Certification, S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

## Identification of the client

Company name: SEQUANS COMMUNICATIONS

Postal address: 55 Boulevard Charles de Gaulle, 92700 Colombes, France

Contact person: Sébastien Falgayrettes

Telephone / e-mail: 01 70 72 16 00 / sfalgayrettes@sequans.com

## Document history

Report number	Date	Description
71232RAN.001	2022-10-25	First release
71232RAN.001A1	2024-04-22	Second release. LTE Cat-M1 band 106 has been included. This modification test report cancels and replaces the test report 71232RAN.001.

## **Appendix A: FCC RF Exposure assessment result**

## General description of the equipment under evaluation

The equipment under evaluation consists of a most compact LTE modem and RF front-end in a single package:

- Same chipset as GM02S module i.e. SQN3430
- Integrated baseband, transceiver, RF front end, RAM memory, crystals and power management
- 8.8 x 11.3 x 1.585 (max.) mm BGA package, 0.5 and 1 mm pitch
- Compliant to 3GPP Rel-14, upgradeable to 3GPP Rel-15 & 16
- Optimized for half-duplex operation (HD-FDD) for LTE-M

As the equipment under evaluation is a module, a conservative evaluation distance of 20 cm has been used to perform the assessment.

As stated into DEKRA Testing and Certification, S.A.U. test reports num. 71232RRF.001, 71232RRF.002, 71232RRF.003 and 76225RRF.001, the maximum measured output power levels for each supported technology are:

Technology / Mode	Band	Frequency (MHz)	Maximum Conducted Output Power (Incl. Tune-Up) (dBm)
LTE Cat-M1	5	824 - 849	23.44
LTE Cat-M1	12	699 - 716	23.78
LTE Cat-M1	13	777 - 787	23.18
LTE Cat-M1	25	1850 - 1915	23.73
LTE Cat-M1	66	1710 - 1780	23.46
LTE Cat-M1	106	896 - 901	22.68

**Table 1:** Equipment specifications

## Maximum Antenna Gain determination for RF Exposure compliance

### Summary of maximum antenna gain values:

Maximum antenna gain for mobile operation to comply with MPE and EIRP limits (see Appendix B) shall not exceed the following values:

Technology / Mode	Band	Frequency (MHz)	Max Gain to comply with RF Exp Limits (dBi)	Max Gain to comply with EIRP Limits (dBi)	Maximum allowed Gain (worst case) (dBi)
LTE Cat-M1	5	824 - 849	10.90	17.16	10.90
LTE Cat-M1	12	699 - 716	9.90	13.14	9.90
LTE Cat-M1	13	777 - 787	10.90	13.74	10.90
LTE Cat-M1	25	1850 - 1915	13.20	9.27	9.27
LTE Cat-M1	66	1710 - 1780	13.50	6.54	6.54
LTE Cat-M1	106	896 - 901	12.00	14.24	12.00

**Table 2:** Maximum Antenna Gain values

**Maximum Gain to meet FCC Radiofrequency radiation exposure limits:**

Technology / Mode	Band	Frequency (MHz)	Distance (cm)	Power density for Gain = 0 dBi (mW/cm <sup>2</sup> )	FCC General Population Limit (mW/cm <sup>2</sup> )	Maximum Gain to comply with RF Exposure Limits (dBi)
LTE Cat-M1	5	824 - 849	20.00	0.04	0.55	10.90
LTE Cat-M1	12	699 - 716	20.00	0.05	0.47	9.90
LTE Cat-M1	13	777 - 787	20.00	0.04	0.52	10.90
LTE Cat-M1	25	1850 - 1915	20.00	0.05	1.00	13.20
LTE Cat-M1	66	1710 - 1780	20.00	0.04	1.00	13.50
LTE Cat-M1	106	896 - 901	20.00	0.04	0.60	12.00

**Table 3:** Maximum Antenna Gain values based on FCC MPE limits

**Maximum Gain to meet FCC EIRP limits**

Technology / Mode	Band	Frequency (MHz)	Maximum Output power (dBm)	EIRP Limits (dBm)	Maximum Gain to meet EIRP Limits (dBi)
LTE Cat-M1	5	824 - 849	23.44	40.60	17.16
LTE Cat-M1	12	699 - 716	23.78	36.92	13.14
LTE Cat-M1	13	777 - 787	23.18	36.92	13.74
LTE Cat-M1	25	1850 - 1915	23.73	33.00	9.27
LTE Cat-M1	66	1710 - 1780	23.46	30.00	6.54
LTE Cat-M1	106	896 - 901	22.68	36.92	14.24

**Table 4:** Maximum Antenna Gain values based on FCC EIRP limits

## Appendix B: FCC RF Exposure information

## FCC RF Exposure evaluation

Devices operating in standalone mobile device exposure conditions may contain a single transmitter or multiple transmitters that do not transmit simultaneously. A minimum test separation distance  $\geq 20$  cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be at least 20 cm and fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated. The minimum test separation distance required for a device to comply with mobile device exposure conditions must be clearly identified in the installation and operating instructions, for all installation and exposure conditions, to enable users and installers to comply with RF exposure requirements. For mobile devices that have the potential to operate in portable device exposure conditions, similar to the configurations described in § 2.1091(d)(4), a KDB inquiry is required to determine the SAR test requirements for demonstrating compliance.

When a device qualifies for the categorical exclusion provision of § 2.1091(c), the minimum test separation distance may be estimated, when applicable, by simple calculations according to plane-wave equivalent conditions, to ensure the transmitter and its antenna(s) can operate in manners that meet or exceed the estimated distance. The source-based time-averaged maximum radiated power, according to the maximum antenna gain, must be applied to calculate the field strength and power density required to establish the minimum test separation distance. When the estimated test separation distance becomes overly conservative and does not support compliance, MPE measurement or computational modeling may be used to determine the required minimum separation distance.

According to §1.1310 Radiofrequency radiation exposure limits, paragraph (e), the limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields are:

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3–3.0 .....	614	1.63	* 100	6
3.0–30 .....	1842/f	4.89/f	* 900/f <sup>2</sup>	6
30–300 .....	61.4	0.163	1.0	6
300–1,500 .....	.....	.....	f/300	6
1,500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	* 100	30
1.34–30 .....	824/f	2.19/f	* 180/f <sup>2</sup>	30
30–300 .....	27.5	0.073	0.2	30
300–1,500 .....	.....	.....	f/1500	30
1,500–100,000 .....	.....	.....	1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

## FCC MPE Evaluation

Each supported transmission technology will be evaluated to determine if it is in compliance with limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields.

In order to perform the assessment, the following equations have been used for the calculations; these equations are accurate in the far-field of an antenna and will over-predict power density in the near field, where they could be used for making a "worst-case" or conservative prediction:

$$\text{Power density: } S[mW / cm^2] = \frac{P_{\max} [mW]}{4\pi R[cm]^2}$$

Maximum gain to meet the MPE limit:  $G_{\max} [dBi] = (10 * \log[ S[mW / cm^2] * 4\pi R[cm]^2 ]) - P_{\max} [dBm]$

$S$  = power density

$P_{\max}$  = power input to the antenna

$R$  = distance to the center of radiation of the antenna (evaluation distance)

$G_{\max}$  = power gain of the antenna in the direction of interest relative to an isotropic radiator

## FCC Cellular bands limits

Maximum FCC EIRP limits are frequency-dependent and are stated into the FCC standards shown in the following table:

Standard	Frequency Band (MHz)	EIRP limit (W)	EIRP limit (dBm)
FCC 47 CFR §27.50 (c)	600-746	4.92	36.92
FCC 47 CFR §27.50 (b)	776-787	4.92	36.92
FCC Clause 90.542 (a) (7)	788-798	4.92	36.92
FCC 47 CFR §22.913	814-849	11.48	40.6
FCC 47 CFR §27.50 (d)	1710-1780	1.0	30.0
FCC 47 CFR §24.232	1850-1915	2.0	33.0
FCC 47 CFR §27.50 (a)	2305-2315	0.25 (average EIRP)	23.9
FCC 47 CFR §27.50 (h) (2)	2496-2690	2.0	33.0
FCC 47 CFR §96.41 (b)	3550-3700	0.2	23
FCC 47 CFR §27.5 (j)	3700-3980	1	30