

Maximum Permissible Exposure Evaluation

Test Report No: CSTS-A13-FCC0029-1

Equipment Name : WiFi Data Monitor

Model No. : S-checker

Applicant : CYCLOGIC. Inc

Address : L07, KETI, 68, Yatap, Bundang, Seongnam, Gyeonggi,

Korea, 463-816

This report applies only to the product named in the title of this report manufactured at the location indicated. Test results apply only to the particular equipment and functionality described in this test report.

Prepared by:

Young Goo, Kim / EMC Engineer

Date of Issue: June 10, 2013

Reviewed by:

Ik Seon, Jeong / Principle Engineer

Date of Issue: June 10, 2013

CERTIFICATION SERVICE TECHNOLOGY INC.

181, Manhaero, Danwan-gu, Ansan-city, Kyeonggi-do, 425-839, Korea Tel: +82 31 493 2001 Fax: +82 31 493 2055

http:www.cstlab.co.kr

Page Number:

Page 1 of 3

Test Report No : CSTPOC13-FCC0009-1

This report shall not be reproduced except in full, without the allowance of the test laboratory.



1. General Description of EUT


Item		Specification	note
Dimension		123 mm x 95 mm x 36 mm	
RF spec	Frequency Range	2412 MHz ~ 2462 MHz (802.11 b)	
	Channel	11	
	Modulation Type	CCK	
	Power	* It is maximum peak conducted power in band	
	Antenna Gain	1.99 dBi	
CPU		STM32F103ZC (ARM 32-bit Cortex [™] -M3)	
Power Source		AC 110V	

NOTE:

- This report is issued as a supplementary report of the original report.
 The EUT, operates in the 2.4GHz frequency range, lets you connect WiFi devices to the network.
 The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

2. General Information of Test

Certification Service Technology Inc. (CSTech)		
Test Site Location	1055, Singil-dong ,Danwon-gu ,Ansan-si, Gyeonggi-do,	
	Korea 425-839	
	TEL: +82-31-493-2001	
	FAX: +82-31-493-2055	





3. RF Exposure Measurement

3.1 Introduction & Standard

RF Exposure Requirements : 47 CFR §1.1307(b) RF Radiation Exposure Limits : 47 CFR §1.1310

RF Radiation Exposure Guidelines : FCC OST/OET Bulletin Number 65 EUT Frequency Band : 2412 MHz ~ 2462 MHz (WiFi) Limits for General Population/Uncontrolled Exposure in the band of : 1500 MHz ~ 100000 MHz

Power Density Limit : 1 mW/cm²

3.2 Compliance criteria

Evaluating for Power flux density

Equations are accurate in the far-field If antenna but will over-predict in the near field.

Under above describe specification of EUT and Antenna, Equivalent plane wave power density is calculated as below underlined quotation formula;

$$S_{eq} (W/m^2) = ExH = E^2/\eta = \sqrt{PG(\Phi)} / 4\pi r^2$$

Where:

- S_{eq} (W/m²) = Equivalent plane wave power density
- E(V/m) = Electric field strength
- H(A/m) = Magnetic field strength
- $\eta(\Omega)$ = Free space wave impedance = 120 $\pi \Omega$
- Φ = elevation and azimuth angles
- P(W) = Power input to the antenna
- G(dBi) = Antenna gain relative to an isotropic antenna
- r(m) = distance from observation point to the antenna

3.2.1 Accordingly as a result of calculated value

- -. P(W) = 100.4 mW
- -. G(dBi) = 1.99 dBi (Conversion 1.99 dBi to Linearity value is 1.58)
- -. r(m) = setting a distance (20cm) from the antenna to calibrated tuned receiving antenna in far field

 S_{eq} (W/m²) : $\sqrt{0.1004x1.58/4 \times 3.14 \times 0.2^2} = \underline{0.56191}$

So, above calculated 0.56191 W/m² is comply with the value required standard