



## OBW NVNT n40 2437MHz Ant1




Date: 2.NOV.2021 05:58:37

## OBW NVNT n40 2452MHz Ant1




Date: 2.NOV.2021 06:03:09

## -6dB Bandwidth NVNT b 2412MHz Ant1




Date: 2.NOV.2021 05:17:39

## -6dB Bandwidth NVNT b 2437MHz Ant1




Date: 2.NOV.2021 05:20:10

## -6dB Bandwidth NVNT b 2462MHz Ant1




Date: 2.NOV.2021 05:22:33

## -6dB Bandwidth NVNT g 2412MHz Ant1




Date: 2.NOV.2021 05:28:26

## -6dB Bandwidth NVNT g 2437MHz Ant1




Date: 2.NOV.2021 05:31:52

## -6dB Bandwidth NVNT g 2462MHz Ant1




Date: 2.NOV.2021 05:36:12

## -6dB Bandwidth NVNT n20 2412MHz Ant1




Date: 2.NOV.2021 05:40:56

## -6dB Bandwidth NVNT n20 2437MHz Ant1




Date: 2.NOV.2021 05:45:45

## -6dB Bandwidth NVNT n20 2462MHz Ant1




Date: 2.NOV.2021 05:50:32

## -6dB Bandwidth NVNT n40 2422MHz Ant1




Date: 2.NOV.2021 05:54:37

## -6dB Bandwidth NVNT n40 2437MHz Ant1



Date: 2.NOV.2021 05:58:54

## -6dB Bandwidth NVNT n40 2452MHz Ant1



Date: 2.NOV.2021 06:03:33

## 8. BAND EDGE CHECK

### 8.1. Test limits

Please refer RSS-GEN & FCC PART 15: 15.247

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits and RSS-GEN limits.

### 8.2. Test Procedure

Details see the KDB558074 D01 Meas Guidance v05r02

8.2.1 Put the EUT on a 1.5m high table, power on the EUT. Emissions were scanned and measured rotating the EUT to 360 degrees, Find the maximum Emission

8.2.2 Check the spurious emissions out of band.

8.2.3 RBW 1MHz, VBW 3MHz, peak detector for peak value , RBW 1MHz ,VBW 10Hz , RMS detector for AV value.

### 8.3. Test Setup


Same as 5.2.2.

### 8.4. Test Results




PASS.

Detailed information please see the following page.


## Test Mode: IEEE 802.11b-Low




## Test Mode: IEEE 802.11b-High

Test Mode: IEEE 802.11g-Low  
Polarization: VerticalTest Mode: IEEE 802.11g-High  
Polarization: Horizontal


Test Mode: IEEE 802.11n20-Low




Test Mode: IEEE 802.11n20-High




Test Mode: IEEE 802.11n40-Low




Test Mode: IEEE 802.11n40-High



## Test mode: 802.11b




Lowest channel




Highest channel

## Test mode: 802.11g




Lowest channel




Highest channel

## Test mode: 802.11n(HT20)




Lowest channel



Highest channel

## Test mode: 802.11n(HT40)



## 9. FREQUENCY STABILITY

### 9.1. Test limit


Please refer section RSS-Gen.

Regulation RSS-Gen If the frequency stability of the licence-exempt radio apparatus is not specified in the applicable RSS, the fundamental emissions of the radio apparatus should be kept within at least the central 80% of its permitted operating frequency band in order to minimize the possibility of out-of-band operation. In addition, its occupied bandwidth shall be entirely outside the restricted bands and the prohibited TV bands of 54-72 MHz, 76-88 MHz, 174-216 MHz, and 470-602 MHz, unless otherwise indicated.

### 9.2. Test Procedure

The following equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 9.3. Test Setup



### 9.4. Test Results

Not applicable.

## **10. ANTENNA REQUIREMENT**

### **10.1. Standard Requirement**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### **10.2. Antenna Connected Construction**


The antenna connector is unique antenna and no consideration of replacement. Please see EUT photo for details.

### **10.3. Results**

The EUT antenna is integrated antenna. It complies with the standard requirement.

## 11. TEST SETUP PHOTO

### 11.1. Photos of Radiated emission



### 11.2.Photos of Power Line Conducted Emission Test



## 12.PHOTOS OF EUT













