

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is an Mickey Mouse Clubhouse Track Set operating at 2.4G Band. The EUT can be powered by DC 4.5V (3 x 1.5V AAA batteries). For more details information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -6.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -6.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498 V06:

The Maximum peak radiated emission for the EUT is 89.8dB μ V/m at 3m in the frequency 2465MHz

The EIRP = $[(FS^*D)^2 / 30]$ mW = -5.43dBm
which is within the production variation.

The Minimum peak radiated emission for the EUT is 87.5dB μ V/m at 3m in the frequency 2445MHz

The EIRP = $[(FS^*D)^2 / 30]$ mW = -7.73dBm
which is within the production variation.

The maximum conducted output power specified is -3.0dBm= 0.501mW

The source- based time-averaging conducted output power
=0.501mW

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)
= 3.0 * 5 / sqrt (2.465) mW
= 9.55 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

FCC ID: 2AAIB3821201