

No. 1 Workshop, M-10, Middle section, Science & Technology Park,

Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Report No.: SZEM171001106303

Fax: +86 (0) 755 2671 0594 Page: 1 of 63

TEST REPORT

Application No.: SZEM1710011063CR

Applicant: ACOUSTMAX INTERNATIONAL CO., LTD.

Address of Applicant: Unit D16/F Cheuk Nang Plaza 250 Henessy Road Wanchai HongKong, China

Manufacturer: ACOUSTMAX INTERNATIONAL CO., LTD.

Address of Manufacturer: Unit D16/F Cheuk Nang Plaza 250 Henessy Road Wanchai HongKong, China

Factory: Arts Electronics Co., Ltd.

Address of Factory: NO. 1, SHANGXING LU, SHANGJIAO COMMUNITY, CHANGAN TOWN,

DONGGUAN CITY, GUANGDONG PROVINCE, CHINA

Equipment Under Test (EUT):

EUT Name: ROCKIN' ROLLER 4 SPEAKER

Model No.: ROCKIN ROLLER 4 (RR4), RR4-1, RR4 PRO, RR4 mini, RR4, RR5, RR6,

RR7, RR8 &

Please refer to section 2 of this report which indicates which model was

actually tested and which were electrically identical.

FCC ID: 2AAINYS1350

Trade mark: Monster

Standard(s): 47 CFR Part 15, Subpart C 15.247

Date of Receipt: 2017-10-30

Date of Test: 2017-11-13 to 2017-11-24

Date of Issue: 2017-11-29

Test Result: Pass*

Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEM171001106303

Page: 2 of 63

Revision Record							
Version Chapter Date Modifier Rema							
01		2017-11-29		Original			

Authorized for issue by:		
	1 Jombh	
	Harry Wu /Project Engineer	
	Eric Fu	
	Eric Fu /Reviewer	



Report No.: SZEM171001106303

Page: 3 of 63

2 Test Summary

Radio Spectrum Technical Requirement							
Item	Standard	Method	Requirement	Result			
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass			

Radio Spectrum Matter Part						
Item	Standard	Method	Requirement	Result		
Conducted Emissions at AC Power Line (150kHz- 30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass		
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass		
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass		
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass		
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass		
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass		
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass		
Radiated Spurious 47 CFR Part 15, Subpart C 15.247		ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass		

Remark:

Model No.: ROCKIN ROLLER 4 (RR4), RR4-1, RR4 PRO, RR4 mini, RR4, RR5, RR6, RR7, RR8 Only the model ROCKIN ROLLER 4 (RR4) was tested, since the electrical circuit design, layout, components used, internal wiring and functions were identical for all the above models, with only difference on model No. and enclosure colour.



Report No.: SZEM171001106303

Page: 4 of 63

3 Contents

			Page
1	COVER PAGE		1
2	TEST SUMMARY		3
3	CONTENTS		4
4		ΓΙΟΝ	6
7			
		UPPORT UNITS	
		CERTAINTY	
		TANDADDO	
		TANDARDSOM STANDARD CONDITIONS	
5	EQUIPMENT LIST		9
6	RADIO SPECTRUM T	ECHNICAL REQUIREMENT	13
	6.1 Antenna Require	MENT	13
		ent:	
	•		
7		ATTER TEST RESULTS	
-			
	7.1 CONDUCTED EMISS	SIONS AT AC POWER LINE (150kHz-30MHz)on	14
	•	gram	
		Procedure and Data	
		DWIDTH	
		on	
		gram	
		Procedure and Data	
		OUTPUT POWER	
	,	on	
		gram	
		Procedure and Data	
		1 DENSITY	
		ongram	
		Procedure and Data	
		EDGES MEASUREMENT	
		on	
	,	gramgram	
	,	Procedure and Data	
		IOUS EMISSIONS	
		on	
		gramgram	
		Procedure and Data	
		NS WHICH FALL IN THE RESTRICTED BANDS	
		on	
	7.7.2 Test Setup Dia	gram	27

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at https://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at https://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SZEM171001106303

Page: 5 of 63

	7.8 7.8.1 7.8.2	Measurement Procedure and Data	34 35 35
	7.8.3	Measurement Procedure and Data	36
8	РНО	TOGRAPHS	46
	8.1 8.2 8.3	CONDUCTED EMISSIONS AT AC POWER LINE (150KHz-30MHz) TEST SETUP	INED.
9	APP	ENDIX	47
	9.1	APPENDIX 15.247	1 7-68



Report No.: SZEM171001106303

Page: 6 of 63

4 General Information

4.1 Details of E.U.T.

Power supply:	Input: AC 120V 60Hz		
	Internal rechargeable battery: DC 12V 9Ah		
Cable:	AC Cable: 200cm, Unshielded		
	Microphone cable: 220cm unshielded		
Frequency Range:	2402MHz to 2480MHz		
Bluetooth Version:	V4.2 BLE mode		
Modulation Type:	GFSK		
Number of Channels:	40		
Antenna Type:	Integral		
Antenna Gain:	0dBi		

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle

frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2441MHz
The Highest channel	2480MHz



Report No.: SZEM171001106303

Page: 7 of 63

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Load Resistor	SGS	N/A	REF. No.SEA0600
Micro USB Cable	PHILIPS	SWR2101	REF. No.SEA0700
Aux In Cable	SAMZHE	YPH-8310	REF. No.SEA0800

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.25 x 10 ⁻⁸
2	Duty cycle	0.37%
3	Occupied Bandwidth	3%
4	RF conducted power	0.75dB
5	RF power density	2.84dB
6	Conducted Spurious emissions	0.75dB
7	DE Dadioted names	4.5dB (below 1GHz)
/	RF Radiated power	4.8dB (above 1GHz)
0	Dedicted Courieus emission test	4.5dB (30MHz-1GHz)
8	Radiated Spurious emission test	4.8dB (1GHz-18GHz)
9	Temperature test	1℃
10	Humidity test	3%
11	Supply voltages	1.5%
12	Time	3%



Report No.: SZEM171001106303

Page: 8 of 63

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

FCC –Designation Number: CN1178

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



Report No.: SZEM171001106303

Page: 9 of 63

5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)							
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date		
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2017-05-10	2018-05-09		
Measurement Software	AUDIX	e3 V5.4.1221d	N/A	N/A	N/A		
Coaxial Cable	SGS	N/A	SEM024-01	2017-07-13	2018-07-12		
LISN	Rohde & Schwarz	ENV216	SEM007-01	2017-09-27	2018-09-26		
LISN	ETS-LINDGREN	3816/2	SEM007-02	2017-04-14	2018-04-13		
EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2017-04-14	2018-04-13		

Minimum 6dB Bandwidth									
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date				
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26				
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2017-04-14	2018-04-13				
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A				
Coaxial Cable	SGS	N/A	SEM031-01	2017-07-13	2018-07-12				
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A				
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26				
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26				

Conducted Peak Output Power									
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date				
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26				
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2017-04-14	2018-04-13				
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A				
Coaxial Cable	SGS	N/A	SEM031-01	2017-07-13	2018-07-12				
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A				
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26				
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26				



Report No.: SZEM171001106303

Page: 10 of 63

Power Spectrum Density									
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date				
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26				
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2017-04-14	2018-04-13				
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A				
Coaxial Cable	SGS	N/A	SEM031-01	2017-07-13	2018-07-12				
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A				
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26				
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26				

Conducted Band Edges Measurement									
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date				
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26				
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2017-04-14	2018-04-13				
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A				
Coaxial Cable	SGS	N/A	SEM031-01	2017-07-13	2018-07-12				
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A				
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26				
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26				

Conducted Spurious Emissions									
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date				
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26				
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2017-04-14	2018-04-13				
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A				
Coaxial Cable	SGS	N/A	SEM031-01	2017-07-13	2018-07-12				
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A				
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26				
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26				



Report No.: SZEM171001106303

Page: 11 of 63

Radiated Emissions wh	Radiated Emissions which fall in the restricted bands						
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date		
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2017-05-02	2020-05-01		
Measurement Software	AUDIX	e3 V8.2014-6- 27	N/A	N/A	N/A		
Coaxial Cable	SGS	N/A	SEM026-01	2017-07-13	2018-07-12		
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2017-04-14	2018-04-13		
BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-01	2017-06-27	2020-06-26		
Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-13		
Horn Antenna (15GHz-40GHz)	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16		
Pre-amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2017-09-27	2018-09-26		
Low Noise Amplifier (100MHz-18GHz)	Black Diamond Series	BDLNA-0118- 352810	SEM005-05	2017-09-27	2018-09-27		
Pre-amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2017-11-20	2018-11-19		
Pre-amplifier (26GHz-40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2017-04-14	2018-04-13		
DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2017-09-27	2018-09-26		
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21		
Band filter	N/A	N/A	SEM023-01	N/A	N/A		

	RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm- dd)	Cal. Due date (yyyy-mm- dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2017-08-05	2020-08-04
2	MXE EMI Receiver (20Hz-8.4GHz)	Agilent Technologies	N9038A	SEM004-05	2017-09-27	2018-09-26
3	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEM003-01	2017-06-27	2020-06-26
4	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEM005-01	2017-04-14	2018-04-13
5	Measurement Software	AUDIX	e3 V8.2014-6- 27	N/A	N/A	N/A
6	Coaxial Cable	SGS	N/A	SEM025-01	2017-07-13	2018-07-12



Report No.: SZEM171001106303

Page: 12 of 63

Radiated Spurious Emissions								
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date			
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2017-05-02	2020-05-01			
Measurement Software	AUDIX	e3 V8.2014-6- 27	N/A	N/A	N/A			
Coaxial Cable	SGS	N/A	SEM026-01	2017-07-13	2018-07-12			
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2017-04-14	2018-04-13			
BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-01	2017-06-27	2020-06-26			
Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-13			
Horn Antenna (15GHz-40GHz)	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16			
Pre-amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2017-09-27	2018-09-26			
Low Noise Amplifier (100MHz-18GHz)	Black Diamond Series	BDLNA-0118- 352810	SEM005-05	2017-09-27	2018-09-27			
Pre-amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2017-11-20	2018-11-19			
Pre-amplifier (26GHz-40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2017-04-14	2018-04-13			
DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2017-09-27	2018-09-26			
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21			
Band filter	N/A	N/A	SEM023-01	N/A	N/A			

General used equipment								
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date			
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2017-09-29	2018-09-28			
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2017-09-29	2018-09-28			
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2017-09-29	2018-09-28			
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2017-04-18	2018-04-17			



Report No.: SZEM171001106303

Page: 13 of 63

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(c)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.



Report No.: SZEM171001106303

Page: 14 of 63

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207 Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Francisco (MALLE)	Conducted	d limit(dBµV)			
Frequency of emission(MHz)	Quasi-peak	Average			
0.15-0.5	66 to 56*	56 to 46*			
0.5-5	56	46			
5-30	60	50			
*Decreases with the logarithm of the frequency.					



Report No.: SZEM171001106303

Page: 15 of 63

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 45 % RH Atmospheric Pressure: 1015 mbar

Pretest these

h:Charge + TX mode_Keep the EUT in charging and continuously transmitting


mode to find the mode with GFSK modulation.

worst case:

The worst case h: Charge + TX mode Keep the EUT in charging and continuously transmitting

for final test: mode with GFSK modulation.

7.1.2 Test Setup Diagram



7.1.3 Measurement Procedure and Data


- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50µH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.Remark: LISN=Read Level+ Cable Loss+ LISN Factor



Report No.: SZEM171001106303

Page: 16 of 63

Mode:h; Line:Live Line



Site : Shielding Room

Condition: Line Job No. : 11063CR

Test mode: h

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.27	0.01	9.51	19.52	29.04	51.07	-22.03	Average
2	0.27	0.01	9.51	35.88	45.40	61.07	-15.67	QP
3	0.39	0.01	9.49	28.56	38.06	48.12	-10.06	Average
4	0.39	0.01	9.49	37.44	46.94	58.12	-11.18	QP
5	0.96	0.02	9.50	19.20	28.72	46.00	-17.28	Average
6	0.96	0.02	9.50	31.48	41.00	56.00	-15.00	QP
7	1.80	0.02	9.51	22.98	32.51	46.00	-13.49	Average
8	1.80	0.02	9.51	33.21	42.74	56.00	-13.26	QP
9	3.45	0.02	9.55	22.50	32.07	46.00	-13.93	Average
10	3.45	0.02	9.55	32.17	41.74	56.00	-14.26	QP
11	7.14	0.01	9.59	30.01	39.61	50.00	-10.39	Average
12	7.14	0.01	9.59	38.91	48.51	60.00	-11.49	QP


This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SZEM171001106303

Page: 17 of 63

Mode:h; Line:Neutral Line



Site : Shielding Room

Condition: Neutral Job No. : 11063CR

Test mode: h

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.46	0.01	9.60	20.19	29.80	46.63	-16.83	Average
2	0.46	0.01	9.60	33.70	43.31	56.63	-13.32	QP
3	0.69	0.02	9.62	20.55	30.19	46.00	-15.81	Average
4	0.69	0.02	9.62	31.89	41.53	56.00	-14.47	QP
5	0.97	0.02	9.62	19.20	28.84	46.00	-17.16	Average
6	0.97	0.02	9.62	30.73	40.37	56.00	-15.63	QP
7	2.66	0.02	9.64	23.86	33.52	46.00	-12.48	Average
8	2.66	0.02	9.64	32.30	41.96	56.00	-14.04	QP
9	6.91	0.01	9.72	30.96	40.69	50.00	-9.31	Average
10	6.91	0.01	9.72	38.47	48.20	60.00	-11.80	QP
11	7.29	0.01	9.73	29.14	38.88	50.00	-11.12	Average
12	7.29	0.01	9.73	37.45	47.19	60.00	-12.81	QP

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SZEM171001106303

Page: 18 of 63

7.2 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)
Test Method: ANSI C63.10 (2013) Section 11.8.1

Limit: ≥500 kHz

7.2.1 E.U.T. Operation

Operating Environment:


Temperature: 23 °C Humidity: 54 % RH Atmospheric Pressure: 1015 mbar

Pretest these e:TX mode_Keep the EUT in continuously transmitting mode with GFSK

mode to find the modulation.

worst case:

7.2.2 Test Setup Diagram



Ground Reference Plane

7.2.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247



Report No.: SZEM171001106303

Page: 19 of 63

7.3 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)
Test Method: ANSI C63.10 (2013) Section 11.9.1

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)			
	1 for ≥50 hopping channels			
902-928	0.25 for 25≤ hopping channels <50			
	1 for digital modulation			
	1 for ≥75 non-overlapping hopping channels			
2400-2483.5	0.125 for all other frequency hopping systems			
	1 for digital modulation			
5725-5850	1 for frequency hopping systems and digital modulation			



Report No.: SZEM171001106303

Page: 20 of 63

7.3.1 E.U.T. Operation

Operating Environment:


Temperature: 23 °C Humidity: 54 % RH Atmospheric Pressure: 1015 mbar

Pretest these e:TX mode_Keep the EUT in continuously transmitting mode with GFSK

mode to find the modulation.

worst case:

7.3.2 Test Setup Diagram



Ground Reference Plane

7.3.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247



Report No.: SZEM171001106303

Page: 21 of 63

7.4 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)
Test Method: ANSI C63.10 (2013) Section 11.10.2

Limit: ≤8dBm in any 3 kHz band during any time interval of continuous

transmission

7.4.1 E.U.T. Operation

Operating Environment:


Temperature: 23 °C Humidity: 54 % RH Atmospheric Pressure: 1015 mbar

Pretest these e:TX mode_Keep the EUT in continuously transmitting mode with GFSK

mode to find the modulation.

worst case:

7.4.2 Test Setup Diagram



Ground Reference Plane

7.4.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247



Report No.: SZEM171001106303

Page: 22 of 63

7.5 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit: In any 100 kHz bandwidth outside the frequ

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)



Report No.: SZEM171001106303

Page: 23 of 63

7.5.1 E.U.T. Operation

Operating Environment:


Temperature: 23 °C Humidity: 54 % RH Atmospheric Pressure: 1015 mbar

Pretest these e:TX mode_Keep the EUT in continuously transmitting mode with GFSK

mode to find the modulation.

worst case:

7.5.2 Test Setup Diagram



Ground Reference Plane

7.5.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247



Report No.: SZEM171001106303

Page: 24 of 63

7.6 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
Test Method: ANSI C63.10 (2013) Section 11.11

Limit: In any 100 kHz bandwidth outside the frequency band in which the spread

spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified

in §15.209(a) (see §15.205(c)



Report No.: SZEM171001106303

Page: 25 of 63

7.6.1 E.U.T. Operation

Operating Environment:


Temperature: 23 °C Humidity: 54 % RH Atmospheric Pressure: 1015 mbar

Pretest these e:TX mode_Keep the EUT in continuously transmitting mode with GFSK

mode to find the modulation.

worst case:

7.6.2 Test Setup Diagram



Ground Reference Plane

7.6.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247



Report No.: SZEM171001106303

Page: 26 of 63

7.7 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)		
0.009-0.490	2400/F(kHz)	300		
0.490-1.705	24000/F(kHz)	30		
1.705-30.0	30	30		
30-88	100	3		
88-216	150	3		
216-960	200	3		
Above 960	500	3		

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.



Report No.: SZEM171001106303

Page: 27 of 63

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: $\frac{50}{4}$ % RH Atmospheric Pressure: 1005 mbar

Pretest these mode to find the

h: Charge + TX mode_Keep the EUT in charging and continuously transmitting


mode with GFSK modulation.


worst case:

The worst case h: Charge + TX mode_Keep the EUT in charging and continuously transmitting

for final test: mode with GFSK modulation.

7.7.2 Test Setup Diagram





30MHz-1GHz Above 1GHz



Report No.: SZEM171001106303

Page: 28 of 63

7.7.3 Measurement Procedure and Data

a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor



Report No.: SZEM171001106303

Page: 29 of 63

Mode:h; Polarization:Horizontal; Modulation:GFSK; ; Channel:Low



Condition: 3m HORIZONTAL

Job No : 11063CR

1 2

Mode : 2402 Band edge


	- HOUGE								
	Cable	Ant	Preamp	Read		Limit	0ver		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		
2333.516	5.40	28.91	37.66	48.02	44.67	74.00	-29.33	peak	
2390.000	5.47	29.08	37.66	44.26	41.15	74.00	-32.85	peak	
pp 2402.250								•	



Report No.: SZEM171001106303

Page: 30 of 63

Mode:h; Polarization:Vertical; Modulation:GFSK; ; Channel:Low



Condition: 3m VERTICAL Job No : 11063CR

1 2

Mode : 2402 Band edge


	Cable	Ant	Preamp	Read		Limit	0ver	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
2333.121	5.40	28.90	37.66	48.19	44.83	74.00	-29.17	peak
2390.000								•
pp 2402.250								•



Report No.: SZEM171001106303

Page: 31 of 63

Mode:h; Polarization:Horizontal; Modulation:GFSK; ; Channel:High



Condition: 3m HORIZONTAL

Job No : 11063CR

Mode : 2480 Band edge


		Cable	Ant	Preamp	Read		Limit	0ver	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2476.300	5.59	29.33	37.65	99.95	97.22	74.00	23.22	peak
2	2483.500	5.60	29.35	37.65	44.28	41.58	74.00	-32.42	peak
3	2490.150	5.61	29.37	37.65	45.71	43.04	74.00	-30.96	peak



Report No.: SZEM171001106303

Page: 32 of 63

Mode:h; Polarization:Vertical; Modulation:GFSK; ; Channel:High



Condition: 3m VERTICAL Job No : 11063CR

Mode : 2480 Band edge

	Freq			Preamp Factor					Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
	2476.300 2483.500								•
3	2493.219	5.61	29.38	37.65	47.02	44.36	74.00	-29.64	peak



Report No.: SZEM171001106303

Page: 33 of 63

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

2) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.



Report No.: SZEM171001106303

Page: 34 of 63

7.8 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)		
0.009-0.490	2400/F(kHz)	300		
0.490-1.705	24000/F(kHz)	30		
1.705-30.0	30	30		
30-88	100	3		
88-216	150	3		
216-960	200	3		
Above 960	500	3		

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.



Report No.: SZEM171001106303

Page: 35 of 63

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 24 °C Humidity: 54 % RH Atmospheric Pressure: 1015 mbar

Pretest these e:TX mode_Keep the EUT in continuously transmitting mode with GFSK

mode to find the modulation.


worst case: f:Charge + TX mode_Keep the EUT in charging and continuously transmitting

mode with GFSK modulation.


The worst case f:Charge + TX mode_Keep the EUT in charging and continuously transmitting

for final test: mode with GFSK modulation.

7.8.2 Test Setup Diagram



Below 30MHz 30MHz-1GHz



Above 1GHz



Report No.: SZEM171001106303

Page: 36 of 63

7.8.3 Measurement Procedure and Data

a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel. i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor




Report No.: SZEM171001106303

Page: 37 of 63

 $30MHz{\scriptstyle \sim} 1GHz$

QP value:

Mode:f; Polarization:Horizontal;



Condition: 3m HORIZONTAL

Job No. : 11063CR

Test mode: f


		Cable	Ant	Preamp	Read		Limit	0ver
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	90.22	1.10	8.71	27.21	38.45	21.05	43.50	-22.45
2	180.65	1.37	9.91	26.77	47.88	32.39	43.50	-11.11
3	203.52	1.42	10.38	26.69	40.81	25.92	43.50	-17.58
4	446.41	2.40	16.83	27.42	41.51	33.32	46.00	-12.68
5 pp	468.88	2.49	17.58	27.54	44.86	37.39	46.00	-8.61
6	866.09	3.47	22.79	26.96	33.40	32.70	46.00	-13.30



Report No.: SZEM171001106303

Page: 38 of 63

Mode:f; Polarization:Vertical



Condition: 3m VERTICAL

Job No. : 11063CR

Test mode: f

		Cable	Ant	Preamp	Read		Limit	0ver
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	79.52	1.08	7.66	27.23	44.26	25.77	40.00	-14.23
2	112.52	1.23	8.42	27.11	46.95	29.49	43.50	-14.01
3 рр	180.65	1.37	9.91	26.77	52.11	36.62	43.50	-6.88
4	203.52	1.42	10.38	26.69	47.00	32.11	43.50	-11.39
5	423.54	2.30	16.39	27.27	44.21	35.63	46.00	-10.37
6	468.88	2.49	17.58	27.54	44.94	37.47	46.00	-8.53




Report No.: SZEM171001106303

Page: 39 of 63

Above 1GHz

Mode:f; Polarization:Horizontal; Modulation:GFSK; ; Channel:Low



Condition: 3m HORIZONTAL

Job No : 11063CR Mode : 2402 TX SE Note : BLE Module 1


ote	. DLL	HOUUT	е т							
		Cable	Ant	Preamp	Read		Limit	0ver		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		
1	1639.274	5.30	26.42	37.73	43.39	37.38	74.00	-36.62	peak	
2	4145.664	7.16	33.60	37.13	44.27	47.90	74.00	-26.10	peak	
3	4804.000	7.89	34.16	37.26	42.79	47.58	74.00	-26.42	peak	
4 p	p 6679.040	11.02	35.61	37.69	43.36	52.30	74.00	-21.70	peak	
5	7206.000	10.08	36.42	37.56	42.20	51.14	74.00	-22.86	peak	
6	9608.000	10.75	37.52	35.80	38.37	50.84	74.00	-23.16	peak	



Report No.: SZEM171001106303

Page: 40 of 63

Mode:f; Polarization:Vertical; Modulation:GFSK; ; Channel:Low



Condition: 3m VERTICAL

Job No : 11063CR Mode : 2402 TX SE

Note : BLE Module 1


		Freq			Preamp Factor					Remark
	-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1		1477.276	5.41	25.71	37.74	44.15	37.53	74.00	-36.47	peak
2		4392.376								-
3		4804.000	7.89	34.16	37.26	44.16	48.95	74.00	-25.05	peak
4	pp	6679.040	11.02	35.61	37.69	43.89	52.83	74.00	-21.17	peak
5		7206.000	10.08	36.42	37.56	43.39	52.33	74.00	-21.67	peak
6		9608.000	10.75	37.52	35.80	39.13	51.60	74.00	-22.40	peak



Report No.: SZEM171001106303

Page: 41 of 63

Mode:f; Polarization:Horizontal; Modulation:GFSK; ; Channel:middle



Condition: 3m HORIZONTAL

Job No : 11063CR Mode : 2440 TX SE Note : BLE Module 1


		Freq			Preamp Factor					Remark
	-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1		1601.804	5.35	26.26	37.73	43.07	36.95	74.00	-37.05	peak
2		4145.664								-
3		4880.000	7.97	34.29	37.28	44.42	49.40	74.00	-24.60	peak
4	pp	6679.040	11.02	35.61	37.69	44.05	52.99	74.00	-21.01	peak
5		7320.000	10.05	36.37	37.53	41.14	50.03	74.00	-23.97	peak
6		9760.000	10.82	37.55	35.68	39.01	51.70	74.00	-22.30	peak



Report No.: SZEM171001106303

Page: 42 of 63

Mode:f; Polarization:Vertical; Modulation:GFSK; ; Channel:middle



Condition: 3m VERTICAL

Job No : 11063CR Mode : 2440 TX

Mode : 2440 TX SE Note : BLE Module 1


			Cable	Ant	Preamp	Read		Limit	0ver	
		Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1		1583.392	5.37	26.18	37.73	43.00	36.82	74.00	-37.18	peak
2		4379.699	7.43	33.60	37.18	44.84	48.69	74.00	-25.31	peak
3		4880.000	7.97	34.29	37.28	44.46	49.44	74.00	-24.56	peak
4	pp	6815.551	10.64	36.00	37.65	43.18	52.17	74.00	-21.83	peak
5		7320.000	10.05	36.37	37.53	41.15	50.04	74.00	-23.96	peak
		9760.000								-



Report No.: SZEM171001106303

Page: 43 of 63

Mode:f; Polarization:Horizontal; Modulation:GFSK; ; Channel:High



Condition: 3m HORIZONTAL

Job No : 11063CR Mode : 2480 TX SE

Note : BLE Module 1


					Preamp					
		Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1		1658.337	5.28	26.50	37.73	43.58	37.63	74.00	-36.37	peak
2		4392.376	7.44	33.60	37.18	44.03	47.89	74.00	-26.11	peak
3		4960.000	8.05	34.43	37.29	42.70	47.89	74.00	-26.11	peak
4		6659.763	11.08	35.56	37.70	43.86	52.80	74.00	-21.20	peak
5		7440.000	10.02	36.32	37.51	41.81	50.64	74.00	-23.36	peak
6	pp	9920.000	10.90	37.58	35.56	40.07	52.99	74.00	-21.01	peak



Report No.: SZEM171001106303

Page: 44 of 63

Mode:f; Polarization:Vertical; Modulation:GFSK; ; Channel:High



Condition: 3m VERTICAL Job No : 11063CR Mode : 2480 TX SE

Note : BLE Module 1

	_		HOUGH							
			Cable	Ant	Preamp	Read		Limit	0ver	
		Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	-						ID 1//			
		MHz	dB	dB/m	dB	aBuV	dBuV/m	dBuV/m	dB	
1		1672.779	5.26	26.56	37.73	43.66	37.75	74.00	-36.25	peak
2		4254.921	7.28	33.60	37.16	44.34	48.06	74.00	-25.94	peak
3		4960.000	8.05	34.43	37.29	43.94	49.13	74.00	-24.87	peak
4		6545.263	11.41	35.23	37.73	43.79	52.70	74.00	-21.30	peak
5		7440.000	10.02	36.32	37.51	41.66	50.49	74.00	-23.51	peak
6	pp	9920.000	10.90	37.58	35.56	39.87	52.79	74.00	-21.21	peak



Report No.: SZEM171001106303

Page: 45 of 63

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

- 2) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.



Report No.: SZEM171001106303

Page: 46 of 63

8 Photographs

8.1 Test Setup

Refer to setup photos.

8.2 EUT Constructional Details

Refer to External photos and Internal photos.



Report No.: SZEM171001106303

Page: 47 of 63

9 Appendix

9.1 Appendix 15.247


1.6dB Bandwidth

Test Mode	Test	Ant	EBW[MHz]	Limit[MHz]	Verdict
BLE	2402	Ant1	0.564	>=0.5	PASS
BLE	2440	Ant1	0.582	>=0.5	PASS
BLE	2480	Ant1	0.582	>=0.5	PASS



Report No.: SZEM171001106303


Page: 48 of 63





Report No.: SZEM171001106303

Page: 49 of 63





Report No.: SZEM171001106303

Page: 50 of 63


2.Maximum peak conducted output power

Test Mode	Test Channel	Ant	Power[dBm]	Limit[dBm]	Verdict
BLE	2402	Ant1	1.82	<30	PASS
BLE	2440	Ant1	3.71	<30	PASS
BLE	2480	Ant1	4.84	<30	PASS



Report No.: SZEM171001106303


Page: 51 of 63





Report No.: SZEM171001106303

Page: 52 of 63





Report No.: SZEM171001106303

Page: 53 of 63


3. Maximum Peak power spectral density

Test Mode	Test Channel	Ant	PSD[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE	2402	Ant1	0.76	<8.00	PASS
BLE	2440	Ant1	2.49	<8.00	PASS
BLE	2480	Ant1	3.59	<8.00	PASS



Report No.: SZEM171001106303


Page: 54 of 63





Report No.: SZEM171001106303

Page: 55 of 63





Report No.: SZEM171001106303

Page: 56 of 63


4.Band-edge for RF Conducted Emissions

Test Mode	Test Channel	Ant	Carrier Power[dBm]	Max. Spurious Level [dBm]	Limit [dBm]	Verdict
BLE	2402	Ant1	1.870	-57.483	<-18.13	PASS
BLE	2480	Ant1	4.740	-50.617	<-15.26	PASS



Report No.: SZEM171001106303

Page: 57 of 63





Report No.: SZEM171001106303

Page: 58 of 63


5.RF Conducted Spurious Emissions

Test Mode	Test Channel	StartFre [MHz]	StopFre [MHz]	RBW [kHz]	VBW [kHz]	Pref[dBm]	Max. Level [dBm]	Limit [dBm]	Verdict
BLE	2402	30	10000	1000	3000	1.41	-42.370	<- 18.59	PASS
BLE	2402	10000	25000	1000	3000	1.41	-40.550	<- 18.59	PASS
BLE	2440	30	10000	1000	3000	3.85	-45.050	<- 16.15	PASS
BLE	2440	10000	25000	1000	3000	3.85	-39.330	<- 16.15	PASS
BLE	2480	30	10000	1000	3000	4.97	-44.760	<- 15.03	PASS
BLE	2480	10000	25000	1000	3000	4.97	-40.040	<- 15.03	PASS



Report No.: SZEM171001106303


Page: 59 of 63





Report No.: SZEM171001106303


Page: 60 of 63





Report No.: SZEM171001106303


Page: 61 of 63





Report No.: SZEM171001106303


Page: 62 of 63





Report No.: SZEM171001106303

Page: 63 of 63



- End of the Report -