

CENTRE OF TESTING SERVICE INTERNATIONAL

OPERATE ACCORDING TO ISO/IEC 17025

FCC ID TEST REPORT

TEST REPORT NUMBER: CGZ3140822-00945-EF



CENTRE OF TESTING SERVICE





TEST REPORT For FCC				
	47 CFR PART 15 OCT, 2013			
Report Reference No	•			
Date of issue	12 September 2014			
Testing Laboratory Name	CENTRE OF TESTING SERVICE CO., LTD.			
Address	A101, No.65, Zhuji Highway, Tianhe District, Guangzhou, China			
Testing location/ procedure	Full application of Harmonised standards ■			
	Partial application of Harmonised standards \square			
	Other standard testing method \square			
Applicant's name	SHARPVISION CO.,LTD.			
Address	5/F., #3 Building, Huangzhou Industrial Park, Chebei Rd., Tianhe Dist., 510665 Guangzhou, China			
Test specification				
Standard	47 CFR PART 15 OCT, 2013			
Test Report Form No	CTSEMC-1.0			
TRF Originator	CENTRE OF TESTING SERVICE CO., LTD.			
Master TRF	Dated 2009-01			
CENTRE OF TESTING SERVICE C	O., LTD. All rights reserved.			
CENTRE OF TESTING SERVICE C material. CENTRE OF TESTING SE	in whole or in part for non-commercial purposes as long as the O., LTD. is acknowledged as copyright owner and source of the RVICE CO., LTD takes no responsibility for and will not assume liability er's interpretation of the reproduced material due to its placement and			
Test item description	2.4G Digital Wireless System			
Trade Mark				
Manufacturer	SHARPVISION CO.,LTD.			
Model/Type reference	WT434			
Ratings	DC 12V, 2W			
Operating Frequency	2403.0 MHz ~2478.0 MHz			
Result	Positive			

MAD

Supervised by:

Approved by:

Kate zhang / Fileadministrators

Compiled by:

Duke yang / Technique principal

Vincent yao / Manager

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn





12 September 2014

FCCID-TEST REPORT

Test Report No.:	CGZ3140822-00945-EF	Date of issue
Type / Model	WT434	
EUT	2.4G Digital Wireless System	
Applicant	SHARPVISION CO.,LTD.	
Address	5/F., #3 Building, Huangzhou Industrial Park 510665 Guangzhou, China	, Chebei Rd.,Tianhe Dist.,
Telephone	+86-20-66670988-231	
Fax	+86-20-66670977	
Contact	Hongyuanzhang	
Manufacturer	SHARPVISION CO.,LTD.	
Address	5/F., #3 Building, Huangzhou Industrial Park 510665 Guangzhou, China	, Chebei Rd.,Tianhe Dist.,
Telephone	+86-20-66670988-231	
Fax	+86-20-66670977	
Contact	Hongyuanzhang	
Factory	/	

Test Result according to the standards on page 1:	PASSED
i det i tedenti according to the ciandarac on page 1.	

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway, Tianhe District, Guangzhou, China Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406 Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

Address...../ Telephone...../ Fax..... Contact..... /



TABLE OF CONTENTS

<u>Description</u>	Page
1.0 TEST STANDARDS	6
2.0 SUMMARY	6
2.1 GENERAL REMARKS	6
2.2 FINAL ASSESSMENT	6
3.0 EQUIPMENT UNDER TEST	6
3.1 POWER SUPPLY SYSTEM UNILISED	6
3.2 SHORT DESCRIPTION OF THE EQUIPMENT UNDER TEST (EUT)	6
3.3 EUT OPERATION MODE	
3.4 EUT CONFIGURATION	7
4.0 TEST ENVIRONMENT	8
4.1 ADDRESS OF THE TEST LABORATORY	8
4.2 TEST FACILITY	8
4.3 ENVIRONMENTAL CONDITIONS	8
4.4 DEFINITIONS OF SYMBOLS USED IN THIS TEST REPORT	
4.5 STATEMENT OF THE MEASUREMENT UNCERTAINTY	
4.6 MEASUREMENT UNCERTAINTY	
5.0 SUMMARY OF STANDARDS AND RESULTS	
5.1.DESCRIPTION OF STANDARDS AND RESULTS	10
6.0 POWER LINE CONDUCTED EMISSION TEST	11
6.1.TEST EQUIPMENTS	11
6.2. BLOCK DIAGRAM OF TEST SETUP	
6.3. POWER LINE CONDUCTED EMISSION TEST LIMITS	11
6.4.TEST PROCEDURE	11
6.5. POWER LINE CONDUCTED EMISSION TEST RESULTS	11
7.0 20DB BANDWIDTH	13
7.1 MEASUREMENT EQUIPMENT USED	
7.2 TEST CONFIGURATION	
7.3 TEST PROCEDURE	
7.4 TEST RESULTS	13
8.0 PEAK POWER	16
8.1 LIMIT	
8.2 MEASUREMENT EQUIPMENT USED	16
8.3 TEST CONDIGURATION	
8.4 TEST PROCEDURE	17
Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.	

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

FCC ID:2AAJ2-WT434





CENTRE OF TESTING SERVICE

8.5 TEST RESULTS	18
9.0 PEAK POWER SPECTRAL DENSITY	20
9.1 LIMIT	20
9.2 MEASUREMENT EQUIPMENT USED	20
9.5 TEST RESULTS	
10.0 100KHZ BANDWIDTH OF BAND EDGES MEASUREMENT	21
10.1 LIMIT	21
10.2 MEASUREMENT EQUIPMENT USED	21
10.3 TEST CONFIGURATION	
10.4 TEST PROCEDURE	21
9.0 PEAK POWER SPECTRAL DENSITY 9.1 LIMIT. 9.2 MEASUREMENT EQUIPMENT USED. 9.3 TEST CONFIGURATION. 9.4 TEST PROCEDURE. 9.5 TEST RESULTS. 10.0 100KHZ BANDWIDTH OF BAND EDGES MEASUREMENT. 10.1 LIMIT. 10.2 MEASUREMENT EQUIPMENT USED. 10.3 TEST CONFIGURATION. 10.4 TEST PROCEDURE. 10.5 TEST RESULTS. 11.0 FREQUENCY SEPARATION. 11.1 LIMIT. 11.2 MEASUREMENT EQUIPMENT USED. 11.3 TEST CONFIGURATION. 11.4 TEST PROCEDURE. 11.5 TEST RESULTS. 12.0 NUMBER OF HOPPING FREQUENCY. 12.1 LIMIT. 12.2 MEASUREMENT EQUIPMENT USED. 12.3 TEST CONFIGURATION. 12.4 TEST PROCEDURE. 12.5 TEST RESULTS. 12.6 TEST DATA. 13.1 LIMIT. 13.2 MEASUREMENT EQUIPMENT USED. 13.3 TEST CONFIGURATION. 13.4 TEST PROCEDURE. 12.5 TEST RESULTS. 13.6 TEST DATA. 14.1 LIMIT. 13.2 MEASUREMENT EQUIPMENT USED. 13.3 TEST CONFIGURATION. 13.4 TEST PROCEDURE. 13.5 TEST RESULTS. 13.6 TEST DATA. 14.0 TRANSMITTER UNWANTED EMISSIONS. 14.1 LIMIT. 14.2 TEST EQUIPMENT 14.3 TEST CONFIGURATION. 14.4 TEST PROCEDURE. 15.5 TEST RESULTS. 13.6 TEST DATA. 14.1 LIMIT. 14.2 TEST EQUIPMENT 14.3 TEST CONFIGURATION. 14.4 TEST PROCEDURE 14.5 TEST RESULTS. 15.0 CONDUCTED SPURIOUS EMISSIONS.	22
11.0 FREQUENCY SEPARATION	25
11.1 LIMIT	25
11.2 MEASUREMENT EQUIPMENT USED	25
11.3 TEST CONFIGURATION	
11.4 TEST PROCEDURE	25
11.5 TEST RESULTS	25
12.0 NUMBER OF HOPPING FREQUENCY	27
12.1 LIMIT	27
12.6 TEST DATA	
13.0 TIME OF OCCUPANCY (DWELL TIME)	29
· ·	
	_
14.0 TRANSMITTER UNWANTED EMISSIONS	31
14.1 LIMIT	
14.3 TEST CONFIGURATION	
14.4 TEST PROCEDURE	
14.5 TEST RESULTS	33
15.0 CONDUCTED SPURIOUS EMISSIONS	41
15.1 LIMIT	41
Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.	

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

Complaint line: +86-20-85533471 E-mail: cts@c

Report No.: CGZ3140822-00945-EF

FCC ID:2AAJ2-WT434

CENTRE OF TESTING SERVICE



CT5

15.2 TEST EQUIPMENT15.3 TEST CONFIGURATION	41
15.3 TEST CONFIGURATION	41
15.4 TEST PROCEDURE	41
15.4 TEST PROCEDURE	42
16.0 RECEIVER SUPRIOUS EMISSION	45
16.1 LIMIT	45
16.2 TEST EQUIPMENT	45
16.3 TEST CONFIGURATION	46
16.4 TEST PROCEDURE	46
16.2 TEST EQUIPMENT	46
17.0 ANTENNA REQUIREMENTS	47
17.1 STANDARD APPLICABLE	47
17.2 Antenna Construction and Directional Gain	47
18 0 DEVIATION TO TEST SPECIFICATIONS	47

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.





1.0 TEST STANDARDS

The tests were performed according to following standards:

- 47 CFR PART 15 OCT, 2013
- ANSI C63.4-2009

2.0 SUMMARY

2.1 GENERAL REMARKS

Date of receipt of test sample	22 August 2014
Testing commenced on	22 August~12 September 2014
_	
Testing concluded on	12 September 2014

2.2 FINAL ASSESSMENT

The IC requirements pertaining to the technical standards and tested operation modes are

 fulfilled.

□ - **not** fulfilled.

The equipment under test

fulfils the FCC requirements cited on page 1.

- does not fulfil the FCC requirements cited on page 1.

3.0 EQUIPMENT UNDER TEST

3.1 POWER SUPPLY SYSTEM UNILISED

Power supply voltage : ■ DC 12V

3.2 SHORT DESCRIPTION OF THE EQUIPMENT UNDER TEST (EUT)

Number of tested samples: 1

Serial number: Prototype

3.3 EUT OPERATION MODE

The equipment under test was operated during the measurement under the following conditions:

☐ TX- Y position

☐ TX- Zposition

■ TX- X position

Operation mode 1:TX-X Position Low (2403.0 MHz) , TX-X Position Middle (2442.0 MHz),

TX-X Position High (2478.0 MHz)

Note:Operation mode 1 TX -X position of EUT is the radiated test worst case. so only these test results be recorded in the test report.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn





3.4 EUT CONFIGURATION

3.4.1. Description of configuration (EUT)

Description	:	2.4G Digital Wireless System
Model Number	:	WT434
Operation frequency	:	2403.0 MHz~ 2478.0 MHz ISM Band
Modulation Technology	:	16QAM
Antenna	:	External antenna, met requirement of FCC 15.203

3.4.2. Tested Supporting System Details

N/A

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China
Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406
Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3140822-00945-EF Page 7 of 47





4.0 TEST ENVIRONMENT

4.1 ADDRESS OF THE TEST LABORATORY

A101, No.65, Zhuji Highway, Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

4.2 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L3394

CENTRE OF TESTING SERVICE CO., LTD has been assessed and proved to be in compliance with CNAS-CL01: 2006 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

IC-Registration No.: 8374A

The 3m Alternate Test Site of CENTRE OF TESTING SERVICE CO., LTD has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 8374A on May 22, 2014.

FCC-Registration No.: 971995

CENTRE OF TESTING SERVICE CO., LTD, EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration No.791995, July 13,2012.

4.3 ENVIRONMENTAL CONDITIONS

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35 ° C
Humidity:	25~75 %
Atmospheric pressure:	86~106 kPa

4.4 DEFINITIONS OF SYMBOLS USED IN THIS TEST REPORT

- - The black square indicates that the listed condition, standard or equipment is applicable for this report.
- The empty square indicates that the listed condition, standard or equipment is **not** applicable for this report.

4.5 STATEMENT OF THE MEASUREMENT UNCERTAINTY

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the CTS quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3140822-00945-EF Page 8 of 47







4.6 MEASUREMENT UNCERTAINTY

Test Item	Frequency Range	Uncertainty	Note
Conduction disturbance	150kHz~30MHz	±1.22dB	(1)
Power disturbance	30MHz~300MHz	±1.38dB	(1)
Radiation emission (3m)	30MHz~300MHz	±3.14dB	(1)
	300MHz~1000MHz	±3.18dB	(1)
	1GHz~26.5GHz	±3.54dB	(1)

^{(1).} This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service





5.0 SUMMARY OF STANDARDS AND RESULTS

5.1.DESCRIPTION OF STANDARDS AND RESULTS

The EUT have been tested according to the applicable standards as referenced below.

EMISSION					
Description of Test Item	Standard	Results			
Conducted Emission Test	FCC Part 15 : 15.207 ANSI C63.4-2009	PASSED			
20dB Bandwidth	FCC Part 15.247(a)(1) ANSI C63.4-2009	PASSED			
Peak Power	FCC Part 15.247(b)(1) ANSI C63.4-2009	PASSED			
Peak Power Spectral Density	15.247(e) Power Density ANSI C63.4-2009	N/A			
100KHz Bandwidth Band edges	FCC Part 15.247(d)	PASSED			
measurement	ANSI C63.4-2009	PASSED			
Conducted Spurious Emissions	FCC Part 15.247(d) ANSI C63.4-2009	PASSED			
Frequency Separation	FCC Part 15.247(a)(1)	PASSED			
Trequency Separation	ANSI C63.4-2009	FASSED			
Number of Hopping Frequency	FCC Part 15.247(a)(1)(iii)	PASSED			
Number of Tropping Frequency	ANSI C63.4-2009	FASSED			
Dwell Time	FCC Part 15.247(a)(1)(iii) ANSI C63.4-2009	PASSED			
Transmitter Unwanted Emissions	FCC Part 15: 15.209	PASSED			
Transmitter Unwanted Emissions	ANSI C63.4-2009	PASSED			
Reseiver Churisus Emissions	FCC Part 15: 15.209	NI/A			
Receiver Spurious Emissions	ANSI C63.4-2009	N/A			
Antonno Doguiromonto	FCC Part 15: 15.203	DACCED			
Antenna Requirements	ANSI C63.4-2009	PASSED			
N/A is an abbreviation for Not Applicable.					

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China
Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406
Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service





6.0 POWER LINE CONDUCTED EMISSION TEST

6.1.TEST EQUIPMENTS

Conduc	Conducted Disturbance						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.		
1	EMI Test Receiver	ROHDE & SCHWARZ	ESHS10	842884/012	2013/11		
2	Artificial Mains	ROHDE & SCHWARZ	ESH3-Z5	832479/025	2013/11		
3	Artificial Mains	ROHDE & SCHWARZ	ESH3-Z5	832479/026	2013/11		
4	Pulse Limiter	ROHDE & SCHWARZ	ESHSZ2	100301	2013/11		
5	EMI Test Software	EZ-EMC	Farad	N/A	N/A		

6.2. BLOCK DIAGRAM OF TEST SETUP

EUT

(EUT: 2.4G Digital Wireless System)

6.3. POWER LINE CONDUCTED EMISSION TEST LIMITS

Standard: FCC Part 15: 15.207, ANSI C63.4-2009

		Maximum RF Line Voltage		
Frequency		Quasi-Peak Level	Average Level	
	,	dB(μV)	dB(μV)	
150kHz	~ 500kHz	66 ~ 56*	56 ~ 46*	
500kHz	~ 5MHz	56	46	
5MHz	~ 30MHz	60	50	

Notes: 1. * Decreasing linearly with logarithm of frequency.

6.4.TEST PROCEDURE

The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N.#2). This provides a 50 ohm coupling impedance for the EUT. Please refer the block diagram of the test setup and photographs. The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N.#1). Power on the PC and let it work normally, we use a keyboard test soft ware, let EUT working in test mode, then test it. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC Part 15C on Conducted Emission Test.

6.5. POWER LINE CONDUCTED EMISSION TEST RESULTS PASSED.

The frequency range from 150KHz~30MHz is investigated. Please see the following pages.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3140822-00945-EF Page 11 of 47

^{2.} The lower limit shall apply at the transition frequencies.

FCC ID:2AAJ2-WT434








Test point:	DC Power Port	Result:	■ - passed
Frequency range:	0.15MHz~30MHz		□ - not passed

EUT	2.4G Digital Wireless System	
Operating Condition	TX	
Test Condition	Ambient Temperature: 25°C Humidity: 56%	
Test Date:	22 August ~ 12 September 2014	
Operator	Duke	
MODEL NO	WT434	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	0.3340	9.80	29.93	39.73	59.35	-19.62	QP
2	0.3340	9.80	27.02	36.82	49.35	-12.53	AVG
3	0.6580	9.84	11.35	21.19	56.00	-34.81	QP
4	0.6580	9.84	10.76	20.60	46.00	-25.40	AVG
5	1.0020	9.83	9.44	19.27	56.00	-36.73	QP
6	1.0020	9.83	7.30	17.13	46.00	-28.87	AVG
7	18.9220	9.99	31.95	41.94	60.00	-18.06	QP
8	18.9220	9.99	32.14	42.13	50.00	-7.87	AVG
9	23.9500	10.04	34.94	44.98	60.00	-15.02	QP
10	23.9500	10.04	24.92	34.96	50.00	-15.04	AVG
11	29.2220	10.10	23.83	33.93	60.00	-26.07	QP
12	29.2220	10.10	20.53	30.63	50.00	-19.37	AVG
Remark	Other frequen	icy mini ma	rgin all >6 dB	of Limit			

Note:Level=Reading+Factor. Margin= Level-Limit

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service






7.0 20dB BANDWIDTH

7.1 MEASUREMENT EQUIPMENT USED

20dB Bandwidth					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	Signal analyzer	ROHDE & SCHWARZ	FSIQ26	100311	2014/03

7.2 TEST CONFIGURATION



7.3 TEST PROCEDURE

- 1. Place the EUT on the table and set it in the transmitting mode.
- 2. Remove the antenna from the EUT, then connect a low loss RF cable from antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as RBW=100kHz, VBW=300kHz, Span=10MHz, Sweep = auto.
- 4. Mark the peak frequency and 20dB (upper and lower) frequency.
- 5. Repeat until all the test channels are investigated.

7.4 TEST RESULTS

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	Limit	Result
Low	2403	4.40		PASS
Middle	2442	4.46		PASS
High	2478	4.40		PASS

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn


See Reverse For Terms And Conditions of Service


Report No.: CGZ3140822-00945-EF Page 13 of 47





Test Plot





Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China


Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn









Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn





8.0 PEAK POWER

8.1 LIMIT


The maximum peak output power of the intentional radiator shall not exceed the following:

- 1. For frequency hopping systems operating in the band 902-928 MHz, the maximum peak conducted output power shall not exceed 1.0 W, and the e.i.r.p. shall not exceed 4 W if the hopset uses 50 or more hopping channels; the maximum peak conducted output power shall not exceed 0.25 W, and the e.i.r.p. shall not exceed 1 W if the hopset uses less than 50 hopping channels.
- 2. For frequency hopping systems operating in the band 2400-2483.5 MHz and employing at least 75 hopping channels, the maximum peak conducted output power shall not exceed 1 W; for all other frequency hopping systems in the band, the maximum peak conducted output power shall not exceed 0.125 W. Except as provided in Section A8.4 (5), the e.i.r.p. shall not exceed 4 W.
- 3. For frequency hopping systems operating in the band 5725-5850 MHz, the maximum peak conducted output power shall not exceed 1 W. Except as provided in Section A8.4 (5), the e.i.r.p. shall not exceed 4 W.
- 4. For systems employing digital modulation techniques operating in the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz, the maximum peak conducted output power shall not exceed 1 W. Except as provided in Section A8.4 (5), the e.i.r.p. shall not exceed 4 W.
- 5. Point-to-point systems in the bands 2400-2483.5 MHz and 5725-5850 MHz are permitted to have an e.i.r.p. higher than 4 W provided that the higher e.i.r.p. is achieved by employing higher gain directional antennas and not higher transmitter output powers. Point-to-multipoint systems, omnidirectional applications and multiple co-located transmitters transmitting the same information are prohibited from exceeding 4 W e.i.r.p. However, remote stations of point-to-multipoint systems shall be allowed to operate at greater than 4 W e.i.r.p. under the same conditions as for point-topoint systems.

8.2 MEASUREMENT EQUIPMENT USED

Peak	Peak Power						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.		
1	Signal analyzer	ROHDE & SCHWARZ	FSIQ26	100311	2014/03		
2	Power meter	ROHDE & SCHWARZ	NRVS	842856/049	2014/03		

8.3 TEST CONDIGURATION



Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3140822-00945-EF Page 16 of 47

CENTRE OF TESTING SERVICE





8.4 TEST PROCEDURE

- 1. Set span to encompass the entire emission bandwidth of the signal.
- 2. Set RBW = 1 MHz.
- 3. Set VBW = 3 MHz.
- 4. Use sample detector mode if bin width (i.e., span/number of points in spectrum display) < 0.5 RBW. Otherwise use peak detector mode.
- 5. Use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at full control power for entire sweep of every sweep. If the device transmits continuously, with no off intervals or reduced power Intervals, the trigger may be set to "free run".
- 6. Mark the peak frequency and channel power function on spectrum.
- 7. Repeat until all the test channels are investigated.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3140822-00945-EF Page 17 of 47






8.5 TEST RESULTS

Passed Test Data

Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Result
Low	2403	13.99	21	PASS
Middle	2442	14.34	21	PASS
High	2478	14.59	21	PASS



Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406


Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn


See Reverse For Terms And Conditions of Service











Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn





9.0 PEAK POWER SPECTRAL DENSITY


9.1 LIMIT

- 1. For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
- 2. The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section

9.2 MEASUREMENT EQUIPMENT USED

Peak	Peak Power Spectral Density					
Item	Test Equipment Manufacturer Model No. Serial No. Last Cal.					
1	Signal analyzer	ROHDE & SCHWARZ	FSIQ26	100311	2014/03	

9.3 TEST CONFIGURATION



9.4 TEST PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 300kHz, Sweep=100s
- 4. Record the max. reading.
- 5. Repeat the above procedure until the measurements for all frequencies are completed.

9.5 TEST RESULTS

Not applicable for frequency hopping systems device.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3140822-00945-EF Page 20 of 47





10.0 100KHz BANDWIDTH OF BAND EDGES MEASUREMENT


10.1 LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section A8.4 (4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

10.2 MEASUREMENT EQUIPMENT USED

Radiated disturbance (electric field)					
Item	Test Equipment Manufacturer Model No. Serial No. Last Cal.				
1	Signal analyzer	ROHDE & SCHWARZ	FSIQ26	100311	2014/03

10.3 TEST CONFIGURATION



10.4 TEST PROCEDURE

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- 3. Use the following spectrum analyzer settings:
 - Span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation

RBW = 100KHz(1% of the span)

VBW =3RBW

Sweep = auto

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3140822-00945-EF Page 21 of 47

FCC ID:2AAJ2-WT434





CENTRE OF TESTING SERVICE

Detector function = peak Trace = max hold

- 4. Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Plot the result on the screen of spectrum analyzer.
- 5. Repeat above procedures until all measured frequencies were complete.

10.5 TEST RESULTS

Refer to attach spectrum analyzer data chart.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service


Report No.: CGZ3140822-00945-EF Page 22 of 47






Band Edges (CH-Low)

Detector mode: Peak



Band Edges-Hopping on (CH-Low)

Detector mode: Peak



Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Complaint line: +86-20-85533471


E-mail: cts@cts-lab.com.cn






Band Edges (CH-High)

Detector mode: Peak



Band Edges (CH-High)

Detector mode: Peak



Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn





11.0 FREQUENCY SEPARATION


11.1 LIMIT

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

11.2 MEASUREMENT EQUIPMENT USED

Frequency Separation							
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.		
1	Signal analyzer	ROHDE & SCHWARZ	FSIQ26	100311	2014/03		

11.3 TEST CONFIGURATION



11.4 TEST PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set center frequency of spectrum analyzer = middle of hopping channel.
- 4. Set the spectrum analyzer as RBW=1MHz, VBW=1MHz, Adjust Span to 9 MHz, Sweep = auto.
- 5. Max hold. Mark 3 Peaks of hopping channel and record the 3 peaks frequency.

11.5 TEST RESULTS

PASSED

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3140822-00945-EF Page 25 of 47








Test Data

Channel Separation (MHz)	' JUGB Bandwigth		Result
3MHz	2.97	> Two-thirds of the 20 dB Bandwidth	PASSED



Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service





12.0 NUMBER OF HOPPING FREQUENCY


12.1 LIMIT

According to §15.247(a)(1)(ii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 15 hopping frequencies.

12.2 MEASUREMENT EQUIPMENT USED

Peak Power Spectral Density							
Item	Test Equipment Manufacturer Model No. Serial No. Last Ca						
1	Signal analyzer	ROHDE & SCHWARZ	FSIQ26	100311	2014/03		

12.3 TEST CONFIGURATION



12.4 TEST PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set spectrum analyzer Start=2400MHz, Stop = 2442 MHz, Sweep = 1ms and Start=2443MHz, Stop = 2483.5MHz, Sweep = 1ms.
- 4. Set the spectrum analyzer as RBW, VBW=1MHz,
- 5. Max hold, view and count how many channel in the band.

12.5 TEST RESULTS

PASSED

12.6 TEST DATA

Result(No. of CH)	Limit	Result
26	>15	Pass

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn


See Reverse For Terms And Conditions of Service


Report No.: CGZ3140822-00945-EF Page 27 of 47





Test Plot





Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn





13.0 TIME OF OCCUPANCY (DWELL TIME)


13.1 LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

13.2 MEASUREMENT EQUIPMENT USED

Frequency Separation							
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.		
1	Signal analyzer	ROHDE & SCHWARZ	FSIQ26	100311	2014/03		

13.3 TEST CONFIGURATION



13.4 TEST PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set center frequency of spectrum analyzer = operating frequency.
- 4. Set the spectrum analyzer as RBW=1MHz, VBW=3MHz, Span = 0Hz, Sweep = auto.
- 5. Repeat above procedures until all frequency measured were complete.

13.5 TEST RESULTS

PASSED

13.6 TEST DATA

Dwell time: 0.20*17*100= 340.00(ms)

Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
0.20	340.00	10.4(26*0.4)	400.00	PASS

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn


See Reverse For Terms And Conditions of Service


Report No.: CGZ3140822-00945-EF Page 29 of 47





Test Plot





Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China
Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406
Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn





14.0 TRANSMITTER UNWANTED EMISSIONS

14.1 LIMIT

According to §15.209.Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

FRE	QUEN	CY	DISTANCE	FIELD STREN	GTHS LIMIT	
1	MHz		Meters	μV/m	dB(μV)/m	
0.009	~	0.490	300	2400/F(kHz)		
0.490	~	1.705	30	24000/F(kHz)		
1.705	~	30	30	30		
30	~	88	3	100	40.0	
88	~	216	3	150	43.5	
216	~	960	3	200	46.0	
960	~	1000	3	500	54.0	
٨٨	Above 1000		3	Other:74.0 dB(μV)/m (Peak)		
AL	ove i	000	3	54.0 dB(μV)/m (Average)		

Note: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

14.2 TEST EQUIPMENT

Radia	Radiated disturbance (electric field)							
Item	Test Equipment	Manufacturer Model No.		Serial No.	Last Cal.			
1	EMI Test Receiver	ROHDE & SCHWARZ	ESCI	100868	2013/11			
2	Biconical Antenna	ROHDE & SCHWARZ	HK116	100221	2014/03			
3	Log per Antenna	ROHDE & SCHWARZ	HL223	100226	2014/03			
4	Log per Antenna	ROHDE & SCHWARZ	HL050	100186	2014/03			
5	Signal analyzer	ROHDE & SCHWARZ	FSIQ26	100311	2014/03			
6	Loop Antenna	A.R.A	PLA-1030/B	1030	2013/11			
7	EMI Test Software	EZ-EMC	Farad	N/A	N/A			

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Complaint line: +86-20-85533471

Fax: +86-20-38780406

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service


Report No.: CGZ3140822-00945-EF Page 31 of 47






14.3 TEST CONFIGURATION

Below 30MHz



Below 1 GHz



Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406


Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service





Above 1 GHz



14.4 TEST PROCEDURE

- 1. The EUT is placed on a turntable, which is 0.8m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Repeat above procedures until the measurements for all frequencies are complete.

14.5 TEST RESULTS

The frequency range from 9KHz~30MHz,30MHz to 230MHz, 230MHz to 1000MHz and above 1GHz. is investigated. Please see the following pages.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

FCC ID:2AAJ2-WT434







Test Mode: TX –X Position Mode Result: □ - passed Frequency range: 9KHz~30MHz □ - not passed

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
Rem	Remark: The test result reading value is to low, margin all > 10dB of the limit.						

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Page 34 of 47

FCC ID:2AAJ2-WT434








EUT 2.4G Digital Wireless System	
Operating Condition	DC 12V
Test Condition	Ambient Temperature: 25°C Humidity: 56%
Test distance	3 Meter
Operator	Duke
MODEL NO	WT434

Channel:	TX –X Position	Result:	■ - passed
Test point:	Horizontal		□ - not passed
Frequency range:	30MHz-1GHz		



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	
1	189.0782	-12.34	52.58	40.24	43.50	-3.26	QP	
2	217.7555	-12.35	53.11	40.76	46.00	-5.24	QP	
3	239.9399	-13.13	54.67	41.54	46.00	-4.46	QP	
4	273.4870	-10.91	53.16	42.25	46.00	-3.75	QP	
5	283.7675	-8.49	51.12	42.63	46.00	-3.37	QP	
6	291.3427	-6.86	49.55	42.69	46.00	-3.31	QP	
Remark	Remark: Other frequency mini margin all >6 dB of Limit							

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn


See Reverse For Terms And Conditions of Service

Report No.: CGZ3140822-00945-EF Page 35 of 47









No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	
1	358.9178	-13.85	49.03	35.18	46.00	-10.82	QP	
2	406.6132	-14.94	46.30	31.36	46.00	-14.64	QP	
3	479.5591	-9.77	39.75	29.98	46.00	-16.02	QP	
4	600.2004	-10.94	39.82	28.88	46.00	-17.12	QP	
5	720.8417	-10.94	43.31	32.37	46.00	-13.63	QP	
6	870.9419	-6.92	41.62	34.70	46.00	-11.30	QP	
Remark	Remark: Other frequency mini margin all >6 dB of Limit							

Channel:	Low Channel	Result:	■ - passed
Test point:	Horizontal		☐ - not passed
Frequency range:	1GHz-26.5GHz		,

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	
1	1947.896	-1.17	44.91	43.74	74.00	-30.26	peak	
2	1947.896	-1.17	29.82	28.65	54.00	-25.35	AVG	
3	2873.748	5.89	44.00	49.89	74.00	-24.11	peak	
4	2873.748	5.89	28.63	34.52	54.00	-19.48	AVG	
5	4659.319	11.36	38.14	49.50	74.00	-24.50	peak	
6	4659.319	11.36	23.82	35.18	54.00	-18.82	AVG	
Remark	Remark: Other frequency mini margin all >6 dB of Limit							

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3140822-00945-EF





CENTRE OF TESTING SERVICE

Channel:	Middle Channel	Result:	■ - passed
Test point:	Horizontal		□ - not passed
Frequency range:	1GHz-26.5GHz		

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.		
1	3689.379	8.81	39.97	48.78	74.00	-25.22	peak		
2	3689.379	8.81	24.21	33.02	54.00	-20.98	AVG		
3	4945.892	12.03	36.81	48.84	74.00	-25.16	peak		
4	4945.892	12.03	22.54	34.57	54.00	-19.43	AVG		
5	6114.229	15.66	40.40	56.06	74.00	-17.94	peak		
6	6114.229	15.66	25.62	41.28	54.00	-12.72	AVG		
Remark	Remark: Other frequency mini margin all >6 dB of Limit								

Channel:	High Channel	Result:	■ - passed
Test point:	Horizontal		☐ - not passed
Frequency range:	1GHz-26.5GHz		

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.		
1	3402.806	7.89	40.62	48.51	74.00	-25.49	peak		
2	3402.806	7.89	25.32	33.21	54.00	-20.79	AVG		
3	4372.746	10.69	36.94	47.63	74.00	-26.37	peak		
4	4372.746	10.69	21.95	32.64	54.00	-21.36	AVG		
5	5276.553	13.05	36.67	49.72	74.00	-24.28	peak		
6	5276.553	13.05	21.52	34.57	54.00	-19.43	AVG		
Remark	Remark: Other frequency mini margin all >6 dB of Limit								

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service


Report No.: CGZ3140822-00945-EF Page 37 of 47







Channel:TX –X PositionResult:■ - passedTest point:Vertical□ - not passedFrequency range:30MHz-1GHz



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	
1	132.2645	-16.91	41.72	24.81	43.50	-18.69	QP	
2	169.0581	-16.85	43.04	26.19	43.50	-17.31	QP	
3	189.0782	-12.34	42.02	29.68	43.50	-13.82	QP	
4	217.7555	-12.35	43.27	30.92	46.00	-15.08	QP	
5	226.9539	-12.37	40.65	28.28	46.00	-17.72	QP	
6	300.0000	-5.57	40.50	34.93	46.00	-11.07	QP	
Remark	Remark: Other frequency mini margin all >6 dB of Limit							

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn


See Reverse For Terms And Conditions of Service

Report No.: CGZ3140822-00945-EF

CENTRE OF TESTING SERVICE







No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	
1	329.4589	-15.68	40.66	24.98	46.00	-21.02	QP	
2	358.9178	-13.85	37.87	24.02	46.00	-21.98	QP	
3	406.6132	-14.94	39.91	24.97	46.00	-21.03	QP	
4	490.7816	-9.95	36.56	26.61	46.00	-19.39	QP	
5	643.6874	-8.21	35.03	26.82	46.00	-19.18	QP	
6	720.8417	-10.94	39.62	28.68	46.00	-17.32	QP	
Remark	Remark: Other frequency mini margin all >6 dB of Limit							

Channel:	Low Channel	Result:	■ - passed
Test point:	Vertical		□ - not passed
Frequency range:	1GHz-26.5GHz		

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	
1	1925.852	-1.18	45.35	44.17	74.00	-29.83	peak	
2	1925.852	-1.18	31.33	30.15	54.00	-23.85	AVG	
3	3887.776	9.45	41.05	50.50	74.00	-23.50	peak	
4	3887.776	9.45	26.17	35.62	54.00	-18.38	AVG	
5	5430.862	13.55	40.37	53.92	74.00	-20.08	peak	
6	5430.862	13.55	26.71	40.26	54.00	-13.74	AVG	
Remark	Remark: Other frequency mini margin all >6 dB of Limit							

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3140822-00945-EF







Channel:	Middle Channel	Result:	■ - passed
Test point:	Vertical		□ - not passed
Frequency range:	1GHz-26.5GHz		

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	1947.896	-1.17	46.59	45.42	74.00	-28.58	peak
2	1947.896	-1.17	31.31	30.14	54.00	-23.86	AVG
3	2895.792	6.01	44.37	50.38	74.00	-23.62	peak
4	2895.792	6.01	29.28	35.29	54.00	-18.71	AVG
5	4284.569	10.48	39.14	49.62	74.00	-24.38	peak
6	4284.569	10.48	24.26	34.74	54.00	-19.26	AVG
Remark: Other frequency mini margin all >6 dB of Limit							

Channel:	High Channel	Result:	■ - passed
Test point:	Vertical		□ - not passed
Frequency range:	1GHz-26.5GHz		

No.	Frequency	Factor	Reading	Level	Limit	Margin	Det.	
	(MHz)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1	3711.423	8.88	40.70	49.58	74.00	-24.42	peak	
2	3711.423	8.88	25.27	34.15	54.00	-19.85	AVG	
3	5364.730	13.33	38.12	51.45	74.00	-22.55	peak	
4	5364.730	13.33	23.25	36.58	54.00	-17.42	AVG	
5	7260.521	18.16	37.28	55.44	74.00	-18.56	peak	
6	7260.521	18.16	22.12	40.28	54.00	-13.72	AVG	
Remark:	Remark: Other frequency mini margin all >6 dB of Limit							

Note:Level=Reading+Factor. Margin=Level-Limit.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3140822-00945-EF Page 40 of 47





15.0 CONDUCTED SPURIOUS EMISSIONS


15.1 LIMIT

According to FCC Part 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section A8.4 (4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

15.2 TEST EQUIPMENT

Radiated disturbance (electric field)							
Item	Test Equipment Manufacturer Model No. Serial No. Last Cal.						
1	Signal analyzer	ROHDE & SCHWARZ	FSIQ26	100311	2014/03		

15.3 TEST CONFIGURATION



15.4 TEST PROCEDURE

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- 3. Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW = RBW

Sweep = auto

Detector function = peak

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China
Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406
Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3140822-00945-EF Page 41 of 47







Trace = max hold.

- 4. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. Plot the result on the screen of spectrum analyzer.
- 5. Repeat above procedures until all measured frequencies were complete.

15.5 TEST RESULTS

Low Channel:

30MHz to 26.6 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Middle Channel:

30MHz to 26.6 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

High Channel:

30MHz to 26.6 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.


Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.


Report No.: CGZ3140822-00945-EF Page 42 of 47





Test Plot:





Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406


Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

CENTRE OF TESTING SERVICE







Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China
Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406
Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn





16.0 RECEIVER SUPRIOUS EMISSION

16.1 LIMIT

According to FCC Part 15.247(d). Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

FREQUENCY			DISTANCE	FIELD STRENGTHS LIMIT		
MHz			Meters	μV/m	dB(μV)/m	
30	~	88	3	100	40.0	
88	~	216	3	150	43.5	
216	~	960	3	200	46.0	
960	~	1000	3	500	54.0	
Above 1000			3	Other:74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)		

16.2 TEST EQUIPMENT

Radiated disturbance (electric field)								
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.			
1	EMI Test Receiver	ROHDE & SCHWARZ	ESCI	100868	2013/11			
2	Biconical Antenna	ROHDE & SCHWARZ	HK116	100221	2014/03			
3	Log per Antenna	ROHDE & SCHWARZ	HL223	100226	2014/03			
4	Log per Antenna	ROHDE & SCHWARZ	HL050	100186	2014/03			
5	Signal analyzer	ROHDE & SCHWARZ	FSIQ26	100311	2014/03			
6	Loop Antenna	A.R.A	PLA-1030/B	1030	2013/11			
7	EMI Test Software	EZ-EMC	Farad	N/A	N/A			

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service


Report No.: CGZ3140822-00945-EF Page 45 of 47






16.3 TEST CONFIGURATION

Below 1 GHz



Above 1 GHz



16.4 TEST PROCEDURE

- 1. The EUT is placed on a turntable, which is 0.8m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Repeat above procedures until the measurements for all frequencies are complete.

16.5 TEST RESULTS

The EUT Only the transmitter, Not applicable.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3140822-00945-EF Page 46 of 47

CENTRE OF TESTING SERVICE





17.0 Antenna Requirements

17.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

17.2 Antenna Construction and Directional Gain

Antenna:

Antenna type: External Antenna

Antenna Gain: 3 dBi

18.0 DEVIATION TO TEST SPECIFICATIONS

The following identical model(s):

N/A

Belong to the tested device:

Product description: **2.4G Digital Wireless System**Model name: **WT434**

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Complaint line: +86-20-85533471

Fax: +86-20-38780406

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3140822-00945-EF Page 47 of 47