

TEST REPORT

Application No.: GZCR2505000725AT
Applicant: Guangzhou Robustel Co., Ltd.
Address of Applicant: 501, Building #2,63 Yongan Road, Huangpu District, Guangzhou, China
Manufacturer: Guangzhou Robustel Co., Ltd.
Address of Manufacturer: 501, Building #2,63 Yongan Road, Huangpu District, Guangzhou, China
Factory: Guangzhou Robustel Co., Ltd.
Address of Factory: 501, Building #2,63 Yongan Road, Huangpu District, Guangzhou, China
Product Name: High Speed Smart 5G Router
Model No.: R5020L-A-5G-A25GL
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2025-05-19
Date of Test: 2025-05-27 to 2025-06-06
Date of Issue: 2025-06-06

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Ricky Liu

Ricky Liu
Manager



SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Testing Center EEC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663 t (86-20) 82155555 www.sgsgroup.com.cn
 中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 sgs.china@sgs.com

Revision Record			
Version	Report No.	Date	Remark
01	GZCR250500072502	2025-06-06	Original

Authorized for issue by:			
		Jim Li	
		Jim Li/Project Engineer	
		Vico Cui	
		Vico Cui/Reviewer	



2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2013) Section 11.12	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2013) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2013) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Conducted Peak Output Power		ANSI C63.10 (2013) Section 11.9.2	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass

Note:

E.U.T./EUT means Equipment Under Test.

Pass means the test result passed the test standard requirement, please find the detailed decision rule in the report relative section.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch (EMC) EEC Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

3 Contents

	Page
1 Cover Page.....	1
2 Test Summary.....	3
3 Contents.....	4
4 General Information.....	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units.....	6
4.3 Measurement Uncertainty	7
4.4 Test Location.....	7
4.5 Test Facility.....	8
4.6 Deviation from Standards.....	8
4.7 Abnormalities from Standard Conditions	8
5 Equipment List.....	9
6 Radio Spectrum Technical Requirement	11
6.1 Antenna Requirement	11
6.1.1 Test Requirement:	11
6.1.2 Conclusion	11
7 Radio Spectrum Matter Test Results.....	12
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz).....	12
7.1.1 E.U.T. Operation	12
7.1.2 Test Mode Description	12
7.1.3 Test Setup Diagram	13
7.1.4 Measurement Procedure and Data	13
7.2 Radiated Emissions which fall in the restricted bands	16
7.2.1 E.U.T. Operation	16
7.2.2 Test Mode Description	16
7.2.3 Test Setup Diagram	17
7.2.4 Measurement Procedure and Data	18
7.3 Radiated Spurious Emissions Below 1GHz	43
7.3.1 E.U.T. Operation	43
7.3.2 Test Mode Description	43
7.3.3 Test Setup Diagram	44
7.3.4 Measurement Procedure and Data	44
7.4 Radiated Spurious Emissions Above 1GHz.....	47
7.4.1 E.U.T. Operation	47
7.4.2 Test Mode Description	47
7.4.3 Test Setup Diagram	48
7.4.4 Measurement Procedure and Data	49
7.5 Conducted Peak Output Power	86
7.5.1 E.U.T. Operation	86
7.5.2 Test Mode Description	86
7.5.3 Test Setup Diagram	86



7.5.4	Measurement Procedure and Data	87
7.6	Minimum 6dB Bandwidth	88
7.6.1	E.U.T. Operation	88
7.6.2	Test Mode Description	88
7.6.3	Test Setup Diagram	88
7.6.4	Measurement Procedure and Data	88
7.7	Power Spectrum Density	89
7.7.1	E.U.T. Operation	89
7.7.2	Test Mode Description	89
7.7.3	Test Setup Diagram	89
7.7.4	Measurement Procedure and Data	89
7.8	Conducted Band Edges Measurement	90
7.8.1	E.U.T. Operation	90
7.8.2	Test Mode Description	90
7.8.3	Test Setup Diagram	91
7.8.4	Measurement Procedure and Data	91
7.9	Conducted Spurious Emissions	92
7.9.1	E.U.T. Operation	92
7.9.2	Test Mode Description	92
7.9.3	Test Setup Diagram	93
7.9.4	Measurement Procedure and Data	93
8	Test Setup Photo	94
9	EUT Constructional Details (EUT Photos)	95
10	Appendix	96



4 General Information

4.1 Details of E.U.T.

Power supply: DC 12-36 V powered by AC/DC adapter as below:
Model:GQ24-120150-AX
Input: AC 100-240 V, 50/60Hz, 1.0A Max
Output: DC 12 V, 1.5 A, 18 W

Cable(s): DC input ports
LAN ports
Wi-Fi antenna ports*2
NR antenna ports*4

Test Voltage: AC 120 V, 60 Hz

Operation Frequency: 802.11b/g/n(HT20): 2412MHz to 2462MHz;
802.11n(HT40): 2422MHz to 2452MHz

Modulation Type: 802.11b: DSSS (DBPSK, DQPSK, CCK);
802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)

Number of Channels: 802.11b/g/n(HT20):11;
802.11n(HT40):7

Channel Spacing: 5MHz

Antenna Type: RP-SMA Connector with dedicated Dipole Antenna or Sucker Antenna
Option 1:
Dipole Antenna: Antenna 1: 2dBi and Antenna 2: 2dBi;

Antenna Gain: Option 2:
Sucker Antenna: Antenna 1: 3.1dBi and Antenna 2: 3.1dBi
(Refer to Remark)

Remark: Two antennas can simultaneous transmission

Antenna Number: 2

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
RJ45 Cable (1.2m length)	/	/	/
Note Book Computer	LENOVO	ThinkPad T490	PF1D1MVJ

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	±3.22dB
Radiated Emissions which fall in the restricted bands	±5.14dB (3m); ±4.90dB (10m); ±4.88dB (1GHz-6GHz); ±5.06dB (6GHz-18GHz); ±5.30dB (18GHz-40GHz)
Radiated Spurious Emissions Below 1GHz	±3.08dB (9kHz to 150kHz); ±3.19dB (150kHz to 30MHz); ±5.14dB (30MHz-1GHz) (3m); ±4.90dB (30MHz-1GHz) (10m)
Radiated Spurious Emissions Above 1GHz	±4.88dB (1GHz-6GHz); ±5.06dB (6GHz-18GHz); ±5.30dB (18GHz-40GHz)
Conducted Peak Output Power	± 0.75dB
Minimum 6dB Bandwidth	± 0.274%
Power Spectrum Density	± 2.84dB
Conducted Band Edges Measurement	± 0.75dB
Conducted Spurious Emissions	± 0.75dB
<p>Remark:</p> <p>The U_{lab} (lab Uncertainty) is less than U_{CISPR} (CISPR Uncertainty) or U_{ETSI} (ETSI Uncertainty).</p> <p>Emission decision rule:</p> <ul style="list-style-type: none"> – Compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit, marked as Pass in the report. – Non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit, marked as Fail in the report. 	

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory,
No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou,
Guangdong, China 510663

Tel: +86 20 82155555

No tests were sub-contracted.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch EMC Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● ACMA

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian/New Zealand Regulatory Compliance Mark (RCM).

● SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

● FCC Recognized Accredited Test Firm(Registration No.: 486818)

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: CN5016, Test Firm Registration Number: 486818.

● ISED (Registration No.: 4620B, CAB identifier: CN0052)

SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Innovation Science and Economic Development Canada for Wireless Device Testing laboratories to test to Canadian radio equipment requirements. Registration No. 4620B, CAB identifier: CN0052.

● VCCI (Registration No.: R-12460, C-12584, G-20107 and T-11179)

The 10m Semi-anechoic chamber, 966 Anechoic Chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-12460, C-12584, G-20107 and T-11179 respectively.

● CBTL (Lab Code: TL129)

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2017, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch EMC Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Coaxial Cable	HangTianXing	2m	EMC0107	2023-08-24	2025-08-23
Shielding Room	ChangZhou ZhongYu	8m x 3m x 3.8m	EMC0306	2022-10-16	2025-10-15
Two-Line V-Network-GZ	Rohde & Schwarz	ENV216	EMC2135	2024-09-02	2025-09-01
EMI Test Receiver (9kHz-3.6GHz)	Rohde & Schwarz	ESR3	EMC2221	2024-12-04	2025-12-03
Test Software E3r	Audix	Ver.6.191211	GZE100-77	N/A	N/A

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
1GHz-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2024-10-14	2025-10-13
EMI Test Receiver (10Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2024-09-02	2025-09-01
Chamber cable (Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2024-08-19	2026-08-18
Horn Antenna (1GHz-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2025-05-13	2027-05-12
Horn Antenna (14-40GHz)	SCHWARZBECK	BBHA 9170	EMC2041	2023-06-18	2026-06-17
EXA Signal Analyzer (10Hz-44GHz)	Keysight	N9010A	EMC2138	2024-08-19	2025-08-18
MXE EMI Receiver (10Hz-8.4GHz)	Keysight	N9038A	EMC2139	2024-10-14	2025-10-13
966 Anechoic Chamber	C.R.T	9m x 6m x 6m	EMC2142	2023-12-20	2026-12-19
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A

Radiated Spurious Emissions Below 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
966 Anechoic Chamber	Shenzhen C.R.T	CRTSGSSAC966	EMC2230	2025-03-22	2028-03-21
EMI Test Receiver(1Hz-8GHz)	Rohde & Schwarz	ESW8	EMC2229	2024-12-03	2025-12-02
Amplifier(9k-1000MHz)	SONOMA	310	EMC2237	2024-12-03	2025-12-02
Trilog Broadband Antenna (25MHz-2GHz)	Schwarzbeck Mess-Elektronik	VULB 9168	EMC2238	2025-03-24	2027-03-23
Coaxial Cable	Mirco-COAX UTIFLEX ve	LA2-C125-8000	EMC2239	2024-12-04	2026-12-03
Test Software E3	Audix	Ver.6.191211	GZE100-81	N/A	N/A
Active Loop Antenna-RED	ETS-Lindgren	6502	EMC2190	2024-04-08	2026-04-07



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663 t (86-20) 82155555 www.sgsgroup.com.cn
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 sgs.china@sgs.com

Radiated Spurious Emissions Above 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
1GHz-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2024-10-14	2025-10-13
EMI Test Receiver (10Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2024-09-02	2025-09-01
Chamber cable (Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2024-08-19	2026-08-18
Horn Antenna (1GHz-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2025-05-13	2027-05-12
Horn Antenna (14-40GHz)	SCHWARZBECK	BBHA 9170	EMC2041	2023-06-18	2026-06-17
2.4GHz Filter	Micro-Tronics	BRM 50702	EMC2069	2024-10-14	2025-10-13
EXA Signal Analyzer (10Hz-44GHz)	Keysight	N9010A	EMC2138	2024-08-19	2025-08-18
MXE EMI Receiver (10Hz-8.4GHz)	Keysight	N9038A	EMC2139	2024-10-14	2025-10-13
966 Anechoic Chamber	C.R.T	9m x 6m x 6m	EMC2142	2023-12-20	2026-12-19
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A

RF Conducted Test					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
MI CABLE	SGS-EMC	0.8M	EMC2137	2023-11-02	2025-11-01
4X4 Power sensor Unit	TST	TSPS2023R	EMC2226	2024-08-19	2025-08-18
Test Software	TST	V2.0	GZE100-78	N/A	N/A
EXA Signal Analyzer (10Hz-44GHz)	Keysight	N9010A	EMC2138	2024-08-19	2025-08-18

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DMM	Fluke	73	EMC0006	2024-06-13	2025-06-12



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch (EMC) EEC Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The Wi-Fi antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the Antenna 1: 2 dBi; Antenna 2: 2 dBi; the directional gain is: 5.01dBi or Antenna 1: 3.1 dBi; Antenna 2: 3.1 dBi; the directional gain is: 6.11dBi.

Antenna location: Refer to internal photo.

$$\text{Directional gain} = 10 \log \left[\left(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20} \right)^2 / N_{\text{ANT}} \right] \text{ dBi}$$

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		
Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz		

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 22.9 °C


Humidity: 53.3 % RH

Atmospheric Pressure: 1004 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report for ANT option 1.
Pre-scan	05	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report for ANT option 2.

7.1.3 Test Setup Diagram




7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark : Level=Read Level+ Cable Loss+ LISN Factor

Test Mode: 00; Line: Live line




Pol : LINE
Mode :
Model :
Power :

	Frequency MHz	Read Level dBuV	Cable Loss dB	LISN Factor dB	Measured Level dBuV	Limit Line dBuV	Over Limit dB	Remark
1	0.152	31.88	0.04	9.57	41.49	55.87	-14.38	Average
2	0.152	47.43	0.04	9.57	57.04	65.87	-8.83	QP
3	0.289	13.07	0.04	9.55	22.66	50.54	-27.88	Average
4	0.289	32.06	0.04	9.55	41.65	60.54	-18.89	QP
5	0.352	15.50	0.05	9.59	25.14	48.91	-23.77	Average
6	0.352	26.03	0.05	9.59	35.67	58.91	-23.24	QP
7	0.491	16.68	0.05	9.59	26.32	46.14	-19.82	Average
8	0.491	25.21	0.05	9.59	34.85	56.14	-21.29	QP
9	1.021	9.40	0.07	9.54	19.01	46.00	-26.99	Average
10	1.021	15.81	0.07	9.54	25.42	56.00	-30.58	QP
11	15.470	18.98	0.33	9.85	29.16	50.00	-20.84	Average
12	15.470	24.04	0.33	9.85	34.22	60.00	-25.78	QP



Test Mode: 00; Line: Neutral Line



Pol : NEUTRAL
Mode :
Model :
Power :

	Frequency MHz	Read Level dBuV	Cable Loss dB	LISN Factor dB	Measured Level dBuV	Limit Line dBuV	Over Limit dB	Remark
1	0.153	25.15	0.04	9.51	34.70	55.82	-21.12	Average
2	0.153	46.57	0.04	9.51	56.12	65.82	-9.70	QP
3	0.252	14.20	0.04	9.53	23.77	51.69	-27.92	Average
4	0.252	32.58	0.04	9.53	42.15	61.69	-19.54	QP
5	0.352	6.86	0.05	9.51	16.42	48.91	-32.49	Average
6	0.352	22.21	0.05	9.51	31.77	58.91	-27.14	QP
7	1.210	6.34	0.09	9.56	15.99	46.00	-30.01	Average
8	1.210	11.83	0.09	9.56	21.48	56.00	-34.52	QP
9	2.824	4.65	0.15	9.57	14.37	46.00	-31.63	Average
10	2.824	10.48	0.15	9.57	20.20	56.00	-35.80	QP
11	16.312	12.92	0.34	9.90	23.16	50.00	-26.84	Average
12	16.312	19.08	0.34	9.90	29.32	60.00	-30.68	QP



7.2 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 11.12

Limit:

Test Distance: 3 m

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 24.6 °C Humidity: 59.5 % RH Atmospheric Pressure: 1008 mbar

7.2.2 Test Mode Description

Pre-scan / Mode
Final test Code Description

Final test 00 TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report for ANT option 1.

Final test 05 TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report for ANT option 2.




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663 t (86-20) 82155555 www.sgsgroup.com.cn
Guangzhou Branch Inspection & Testing Services Laboratory 中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 sgs.china@sgs.com

7.2.3 Test Setup Diagram



30MHz-1GHz

Above 1GHz

7.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Remark 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.

Remark 4: For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.




Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	2389.242	60.05	27.68	3.44	37.77	53.40	74.00	-20.60	VERTICAL peak
2	2390.000	60.51	27.68	3.44	37.77	53.86	74.00	-20.14	VERTICAL peak
3 *	2412.000	113.35	27.74	3.46	37.77	106.78	74.00	32.78	VERTICAL peak




Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2389.242	55.63	27.68	3.44	37.77	48.98	74.00	-25.02	HORIZONTAL peak
2	2390.000	57.51	27.68	3.44	37.77	50.86	74.00	-23.14	HORIZONTAL peak
3 *	2412.000	108.05	27.74	3.46	37.77	101.48	74.00	27.48	HORIZONTAL peak




Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over	Pol/Phase	Remark
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	2462.000	110.26	27.82	3.48	37.76	103.80	74.00	29.80	VERTICAL peak
2	2483.500	52.85	27.85	3.49	37.76	46.43	74.00	-27.57	VERTICAL peak
3	2489.064	54.69	27.85	3.49	37.76	48.27	54.00	-5.73	VERTICAL Average
4	2489.064	64.43	27.85	3.49	37.76	58.01	74.00	-15.99	VERTICAL peak


Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over	Pol/Phase	Remark
	MHz	Level	Factor	Loss	Factor	Line	Limit		
		dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	2462.000	104.60	27.82	3.48	37.76	98.14	74.00	24.14	HORIZONTAL peak
2	2483.500	47.34	27.85	3.49	37.76	40.92	74.00	-33.08	HORIZONTAL peak
3	2491.680	55.66	27.86	3.49	37.76	49.25	74.00	-24.75	HORIZONTAL peak




Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over	Pol/Phase	Remark
	MHz	Level	Loss	Factor	dBuV/m	Line	Limit		
		dBuV	dB/m			dBuV/m	dB		
1	2389.000	59.27	27.68	3.44	37.77	52.62	74.00	-21.38	VERTICAL peak
2	2390.000	59.84	27.68	3.44	37.77	53.19	74.00	-20.81	VERTICAL peak
3 *	2412.000	107.43	27.74	3.46	37.77	100.86	74.00	26.86	VERTICAL peak




Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2389.242	56.18	27.68	3.44	37.77	49.53	74.00	-24.47	HORIZONTAL peak
2	2390.000	56.58	27.68	3.44	37.77	49.93	74.00	-24.07	HORIZONTAL peak
3 *	2412.000	101.45	27.74	3.46	37.77	94.88	74.00	20.88	HORIZONTAL peak




Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	2462.000	104.31	27.82	3.48	37.76	97.85	74.00	23.85	VERTICAL peak
2	2483.500	53.87	27.85	3.49	37.76	47.45	74.00	-26.55	VERTICAL peak
3	2489.064	53.23	27.85	3.49	37.76	46.81	54.00	-7.19	VERTICAL Average
4	2489.064	62.89	27.85	3.49	37.76	56.47	74.00	-17.53	VERTICAL peak




Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over	Pol/Phase	Remark
	MHz	Level	Factor	Loss	Factor	Line	Limit		
		dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	2462.000	98.38	27.82	3.48	37.76	91.92	74.00	17.92	HORIZONTAL peak
2	2483.500	48.62	27.85	3.49	37.76	42.20	74.00	-31.80	HORIZONTAL peak
3	2490.875	55.03	27.86	3.49	37.76	48.62	74.00	-25.38	HORIZONTAL peak


Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2389.211	55.53	27.68	3.44	37.77	48.88	54.00	-5.12	VERTICAL
2	2389.211	62.83	27.68	3.44	37.77	56.18	74.00	-17.82	VERTICAL
3	2390.000	55.79	27.68	3.44	37.77	49.14	54.00	-4.86	VERTICAL
4	2390.000	61.64	27.68	3.44	37.77	54.99	74.00	-19.01	VERTICAL
5 *	2422.000	100.14	27.75	3.46	37.77	93.58	74.00	19.58	VERTICAL




Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over	Pol/Phase	Remark
	MHz	Level	Factor	Loss	Factor	Line	Limit		
		dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2389.211	56.82	27.68	3.44	37.77	50.17	74.00	-23.83	HORIZONTAL peak
2	2390.000	58.50	27.68	3.44	37.77	51.85	74.00	-22.15	HORIZONTAL peak
3 *	2422.000	94.81	27.75	3.46	37.77	88.25	74.00	14.25	HORIZONTAL peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over	Pol/Phase	Remark
	MHz	Level	Factor	Loss	Factor	Line	Limit		
		dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	2452.000	100.98	27.80	3.47	37.76	94.49	74.00	20.49	VERTICAL peak
2	2483.500	53.86	27.85	3.49	37.76	47.44	74.00	-26.56	VERTICAL peak
3	2488.949	53.84	27.85	3.49	37.76	47.42	54.00	-6.58	VERTICAL Average
4	2488.949	62.92	27.85	3.49	37.76	56.50	74.00	-17.50	VERTICAL peak


Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over	Pol/Phase	Remark
	MHz	Level	Factor	Loss	Factor	Line	Limit		
		dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	2452.000	94.57	27.80	3.47	37.76	88.08	74.00	14.08	HORIZONTAL peak
2	2483.500	48.44	27.85	3.49	37.76	42.02	74.00	-31.98	HORIZONTAL peak
3	2491.990	54.88	27.86	3.49	37.76	48.47	74.00	-25.53	HORIZONTAL peak




Test Mode: 05; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over	Pol/Phase	Remark
	MHz	Level	Factor	Loss	Factor	Line	Limit		
		dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2389.242	55.79	27.68	3.44	37.77	49.14	54.00	-4.86	VERTICAL
2	2389.242	63.33	27.68	3.44	37.77	56.68	74.00	-17.32	VERTICAL
3	2390.000	57.15	27.68	3.44	37.77	50.50	54.00	-3.50	VERTICAL
4	2390.000	63.68	27.68	3.44	37.77	57.03	74.00	-16.97	VERTICAL
5 *	2412.000	116.91	27.74	3.46	37.77	110.34	74.00	36.34	VERTICAL




Test Mode: 05; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2389.242	49.85	27.68	3.44	37.77	43.20	74.00	-30.80	HORIZONTAL peak
2	2390.000	50.48	27.68	3.44	37.77	43.83	74.00	-30.17	HORIZONTAL peak
3 *	2412.000	102.95	27.74	3.46	37.77	96.38	74.00	22.38	HORIZONTAL peak



Test Mode: 05; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	2462.000	114.97	27.82	3.48	37.76	108.51	74.00	34.51	VERTICAL peak
2	2483.500	55.29	27.85	3.49	37.76	48.87	74.00	-25.13	VERTICAL peak
3	2488.762	58.94	27.85	3.49	37.76	52.52	54.00	-1.48	VERTICAL Average
4	2488.762	71.21	27.85	3.49	37.76	64.79	74.00	-9.21	VERTICAL peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch, Inspection & Testing Services

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com


Test Mode: 05; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over	Pol/Phase	Remark
	MHz	Level	Factor	Loss	Factor	Line	Limit		
		dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	2462.000	99.61	27.82	3.48	37.76	93.15	74.00	19.15	HORIZONTAL peak
2	2483.500	46.60	27.85	3.49	37.76	40.18	74.00	-33.82	HORIZONTAL peak
3	2495.408	57.79	27.86	3.49	37.76	51.38	74.00	-22.62	HORIZONTAL peak




Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over		
	MHz	Level	Loss	Factor	dBuV/m	Line	Limit	Pol/Phase	Remark
		dBuV	dB/m	dB	dB	dBuV/m	dB		
1	2389.121	56.92	27.68	3.44	37.77	50.27	54.00	-3.73	VERTICAL
2	2389.121	64.27	27.68	3.44	37.77	57.62	74.00	-16.38	VERTICAL
3	2390.000	58.35	27.68	3.44	37.77	51.70	54.00	-2.30	VERTICAL
4	2390.000	64.66	27.68	3.44	37.77	58.01	74.00	-15.99	VERTICAL
5 *	2412.000	111.37	27.74	3.46	37.77	104.80	74.00	30.80	VERTICAL




Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
		dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2389.242	50.08	27.68	3.44	37.77	43.43	74.00	-30.57	HORIZONTAL peak
2	2390.000	50.71	27.68	3.44	37.77	44.06	74.00	-29.94	HORIZONTAL peak
3 *	2412.000	97.94	27.74	3.46	37.77	91.37	74.00	17.37	HORIZONTAL peak




Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over	Pol/Phase	Remark
	MHz	Level	Loss	Factor	dBuV/m	Line	Limit		
		dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	2462.000	109.63	27.82	3.48	37.76	103.17	74.00	29.17	VERTICAL peak
2	2483.500	56.45	27.85	3.49	37.76	50.03	74.00	-23.97	VERTICAL peak
3	2489.165	58.43	27.86	3.49	37.76	52.02	54.00	-1.98	VERTICAL Average
4	2489.165	71.20	27.86	3.49	37.76	64.79	74.00	-9.21	VERTICAL peak




Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over	Pol/Phase	Remark
	MHz	Level	Loss	Factor	dBuV/m	dBuV/m	Limit		
		dBuV	dB/m	dB	dB	dBuV/m	dB		
1 *	2462.000	96.24	27.82	3.48	37.76	89.78	74.00	15.78	HORIZONTAL peak
2	2483.500	46.48	27.85	3.49	37.76	40.06	74.00	-33.94	HORIZONTAL peak
3	2498.384	58.22	27.87	3.49	37.76	51.82	74.00	-22.18	HORIZONTAL peak


Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over	Pol/Phase	Remark
	MHz	Level	Loss	Factor	dBuV/m	dBuV/m	Limit		
		dBuV	dB/m	dB	dB	dBuV/m	dB		
1	2389.211	57.11	27.68	3.44	37.77	50.46	54.00	-3.54	VERTICAL
2	2389.211	65.58	27.68	3.44	37.77	58.93	74.00	-15.07	VERTICAL
3	2390.000	59.16	27.68	3.44	37.77	52.51	54.00	-1.49	VERTICAL
4	2390.000	66.13	27.68	3.44	37.77	59.48	74.00	-14.52	VERTICAL
5 *	2422.000	105.38	27.75	3.46	37.77	98.82	74.00	24.82	VERTICAL




Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over	Pol/Phase	Remark
	MHz	Level	Factor	Loss	Factor	Line	Limit		
		dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2389.070	52.00	27.68	3.44	37.77	45.35	74.00	-28.65	HORIZONTAL peak
2	2390.000	51.49	27.68	3.44	37.77	44.84	74.00	-29.16	HORIZONTAL peak
3 *	2422.000	93.24	27.75	3.46	37.77	86.68	74.00	12.68	HORIZONTAL peak




Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over	Pol/Phase	Remark
	MHz	Level	Factor	Loss	Factor	Line	Limit		
		dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	2452.000	102.47	27.80	3.47	37.76	95.98	74.00	21.98	VERTICAL peak
2	2483.500	56.88	27.85	3.49	37.76	50.46	74.00	-23.54	VERTICAL peak
3	2488.949	58.63	27.85	3.49	37.76	52.21	54.00	-1.79	VERTICAL Average
4	2488.949	70.62	27.85	3.49	37.76	64.20	74.00	-9.80	VERTICAL peak

Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over	Pol/Phase	Remark
	MHz	Level	Factor	Loss	Factor	Line	Limit		
		dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	2452.000	89.38	27.80	3.47	37.76	82.89	74.00	8.89	HORIZONTAL peak
2	2483.500	47.52	27.85	3.49	37.76	41.10	74.00	-32.90	HORIZONTAL peak
3	2499.006	58.16	27.87	3.49	37.76	51.76	74.00	-22.24	HORIZONTAL peak

7.3 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5

Limit:

Test Distance: 3 m

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 24.7 °C

Humidity: 53.3 % RH

Atmospheric Pressure: 1004 mbar

7.3.2 Test Mode Description


Pre-scan / Mode
Final test Code Description

Final test 00 TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report for ANT 1.

Pre-scan 05 TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report for ANT 2.



7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch, EMC Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

Test Mode: 00; Polarity: Horizontal




Site : 966 Chamber
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	30.853	33.66	17.85	0.30	32.75	19.06	40.00	-20.94	HORIZONTAL	QP
2	50.586	34.85	19.66	0.39	32.79	22.11	40.00	-17.89	HORIZONTAL	QP
3	124.133	35.80	17.28	0.61	32.72	20.97	43.50	-22.53	HORIZONTAL	QP
4	240.830	34.22	17.32	0.85	32.83	19.56	46.00	-26.44	HORIZONTAL	QP
5	801.786	30.69	28.86	1.66	31.61	29.60	46.00	-16.40	HORIZONTAL	QP
6	958.794	26.16	30.10	1.81	30.73	27.34	46.00	-18.66	HORIZONTAL	QP



Test Mode: 00; Polarity: Vertical



Site : 966 Chamber
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	30.000	40.89	17.65	0.30	32.75	26.09	40.00	-13.91	VERTICAL	QP
2	49.533	38.51	19.65	0.39	32.79	25.76	40.00	-14.24	VERTICAL	QP
3	78.413	36.50	15.37	0.49	32.74	19.62	40.00	-20.38	VERTICAL	QP
4	118.186	41.90	16.79	0.60	32.71	26.58	43.50	-16.92	VERTICAL	QP
5	126.772	42.50	17.63	0.61	32.72	28.02	43.50	-15.48	VERTICAL	QP
6	574.626	34.98	24.99	1.41	32.79	28.59	46.00	-17.41	VERTICAL	QP



7.4 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.6

Limit:

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

7.4.1 E.U.T. Operation

Operating Environment:


Temperature: 24.6 °C Humidity: 59.5 % RH Atmospheric Pressure: 1008 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report for ANT option 1.
Final test	05	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report for ANT option 2.



7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
- 4: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
- 5:For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $\leq 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch (EMC) EEC Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com


Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1587.975	50.67	24.65	2.75	38.15	39.92	74.00	-34.08	VERTICAL	peak
2	4405.090	45.30	33.74	4.61	37.46	46.19	74.00	-27.81	VERTICAL	peak
3	4824.000	48.05	34.16	4.82	37.37	49.66	74.00	-24.34	VERTICAL	peak
4	5269.649	51.38	33.30	5.04	37.20	52.52	74.00	-21.48	VERTICAL	peak
5	7236.000	48.32	35.78	5.95	37.17	52.88	74.00	-21.12	VERTICAL	peak
6	9648.000	40.53	38.70	7.05	37.11	49.17	74.00	-24.83	VERTICAL	peak




Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1672.779	47.75	24.98	2.82	38.05	37.50	74.00	-36.50	HORIZONTAL peak
2	4456.315	44.73	34.00	4.61	37.45	45.89	74.00	-28.11	HORIZONTAL peak
3	4824.000	50.10	34.16	4.82	37.37	51.71	74.00	-22.29	HORIZONTAL peak
4	5300.200	45.53	33.17	5.07	37.19	46.58	74.00	-27.42	HORIZONTAL peak
5	7236.000	45.05	35.78	5.95	37.17	49.61	74.00	-24.39	HORIZONTAL peak
6	9648.000	42.55	38.70	7.05	37.11	51.19	74.00	-22.81	HORIZONTAL peak

Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:middle



		Freq	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
		MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1		1327.446	49.08	24.07	2.61	38.57	37.19	74.00	-36.81	VERTICAL peak
2		4456.315	44.79	34.00	4.61	37.45	45.95	74.00	-28.05	VERTICAL peak
3		4874.000	44.93	34.15	4.85	37.35	46.58	74.00	-27.42	VERTICAL peak
4		6756.708	45.13	34.56	5.77	37.13	48.33	74.00	-25.67	VERTICAL peak
5		7311.000	45.45	36.00	5.98	37.18	50.25	74.00	-23.75	VERTICAL peak
6		9748.000	41.33	38.81	7.11	37.11	50.14	74.00	-23.86	VERTICAL peak


Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1366.374	48.00	24.18	2.64	38.51	36.31	74.00	-37.69	HORIZONTAL peak
2	4495.125	44.55	34.17	4.62	37.44	45.90	74.00	-28.10	HORIZONTAL peak
3	4874.000	44.04	34.15	4.85	37.35	45.69	74.00	-28.31	HORIZONTAL peak
4	6954.852	44.28	35.04	5.86	37.14	48.04	74.00	-25.96	HORIZONTAL peak
5	7311.000	44.80	36.00	5.98	37.18	49.60	74.00	-24.40	HORIZONTAL peak
6	9748.000	40.36	38.81	7.11	37.11	49.17	74.00	-24.83	HORIZONTAL peak




Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High



		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1525.000	49.15	24.49	2.71	38.26	38.09	74.00	-35.91	VERTICAL	peak
2	4495.125	44.56	34.17	4.62	37.44	45.91	74.00	-28.09	VERTICAL	peak
3	4924.000	44.18	34.15	4.88	37.33	45.88	74.00	-28.12	VERTICAL	peak
4	6954.852	44.76	35.04	5.86	37.14	48.52	74.00	-25.48	VERTICAL	peak
5	7386.000	43.91	36.23	6.00	37.18	48.96	74.00	-25.04	VERTICAL	peak
6	9848.000	40.53	38.88	7.15	37.10	49.46	74.00	-24.54	VERTICAL	peak




Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1587.975	50.94	24.65	2.75	38.15	40.19	74.00	-33.81	HORIZONTAL	peak
2	4495.125	44.95	34.17	4.62	37.44	46.30	74.00	-27.70	HORIZONTAL	peak
3	4924.000	43.48	34.15	4.88	37.33	45.18	74.00	-28.82	HORIZONTAL	peak
4	7035.727	44.44	35.19	5.88	37.15	48.36	74.00	-25.64	HORIZONTAL	peak
5	7386.000	44.07	36.23	6.00	37.18	49.12	74.00	-24.88	HORIZONTAL	peak
6	9848.000	40.53	38.88	7.15	37.10	49.46	74.00	-24.54	HORIZONTAL	peak




Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1672.779	45.63	24.98	2.82	38.05	35.38	74.00	-38.62	VERTICAL	peak
2	4482.150	44.22	34.12	4.62	37.44	45.52	74.00	-28.48	VERTICAL	peak
3	4824.000	43.54	34.16	4.82	37.37	45.15	74.00	-28.85	VERTICAL	peak
4	5615.620	41.89	32.63	5.21	37.14	42.59	74.00	-31.41	VERTICAL	Peak
5	7236.000	44.63	35.78	5.95	37.17	49.19	74.00	-24.81	VERTICAL	peak
6	9648.000	41.62	38.70	7.05	37.11	50.26	74.00	-23.74	VERTICAL	peak




Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1702.042	47.98	25.15	2.85	38.03	37.95	74.00	-36.05	HORIZONTAL peak
2	4495.125	44.85	34.17	4.62	37.44	46.20	74.00	-27.80	HORIZONTAL peak
3	4824.000	45.23	34.16	4.82	37.37	46.84	74.00	-27.16	HORIZONTAL peak
4	6053.894	43.94	32.79	5.46	37.10	45.09	74.00	-28.91	HORIZONTAL Peak
5	7236.000	46.63	35.78	5.95	37.17	51.19	74.00	-22.81	HORIZONTAL peak
6	9648.000	41.92	38.70	7.05	37.11	50.56	74.00	-23.44	HORIZONTAL peak




Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle



		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1672.779	46.81	24.98	2.82	38.05	36.56	74.00	-37.44	VERTICAL	peak
2	4495.125	43.47	34.17	4.62	37.44	44.82	74.00	-29.18	VERTICAL	peak
3	4874.000	43.48	34.15	4.85	37.35	45.13	74.00	-28.87	VERTICAL	peak
4	6914.763	44.40	34.97	5.84	37.14	48.07	74.00	-25.93	VERTICAL	peak
5	7311.000	43.73	36.00	5.98	37.18	48.53	74.00	-25.47	VERTICAL	peak
6	9748.000	41.72	38.81	7.11	37.11	50.53	74.00	-23.47	VERTICAL	peak


Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1304.623	48.58	23.99	2.59	38.58	36.58	74.00	-37.42	HORIZONTAL peak
2	4354.454	44.54	33.43	4.60	37.46	45.11	74.00	-28.89	HORIZONTAL peak
3	4874.000	44.03	34.15	4.85	37.35	45.68	74.00	-28.32	HORIZONTAL peak
4	6602.265	45.19	34.07	5.69	37.12	47.83	74.00	-26.17	HORIZONTAL peak
5	7311.000	43.64	36.00	5.98	37.18	48.44	74.00	-25.56	HORIZONTAL peak
6	9748.000	40.92	38.81	7.11	37.11	49.73	74.00	-24.27	HORIZONTAL peak




Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1672.779	46.63	24.98	2.82	38.05	36.38	74.00	-37.62	VERTICAL	peak
2	4482.150	44.20	34.12	4.62	37.44	45.50	74.00	-28.50	VERTICAL	peak
3	4924.000	43.32	34.15	4.88	37.33	45.02	74.00	-28.98	VERTICAL	peak
4	6874.906	43.79	34.88	5.83	37.14	47.36	74.00	-26.64	VERTICAL	peak
5	7386.000	43.41	36.23	6.00	37.18	48.46	74.00	-25.54	VERTICAL	peak
6	9848.000	43.19	38.88	7.15	37.10	52.12	74.00	-21.88	VERTICAL	peak




Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1625.121	46.40	24.77	2.77	38.11	35.83	74.00	-38.17	HORIZONTAL peak
2	4495.125	44.27	34.17	4.62	37.44	45.62	74.00	-28.38	HORIZONTAL peak
3	4924.000	43.62	34.15	4.88	37.33	45.32	74.00	-28.68	HORIZONTAL peak
4	6954.852	44.83	35.04	5.86	37.14	48.59	74.00	-25.41	HORIZONTAL peak
5	7386.000	43.56	36.23	6.00	37.18	48.61	74.00	-25.39	HORIZONTAL peak
6	9848.000	41.14	38.88	7.15	37.10	50.07	74.00	-23.93	HORIZONTAL peak




Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1702.042	47.27	25.15	2.85	38.03	37.24	74.00	-36.76	VERTICAL peak
2	4482.150	44.12	34.12	4.62	37.44	45.42	74.00	-28.58	VERTICAL peak
3	4844.000	43.46	34.15	4.84	37.37	45.08	74.00	-28.92	VERTICAL peak
4	6756.708	44.87	34.56	5.77	37.13	48.07	74.00	-25.93	VERTICAL peak
5	7266.000	45.02	35.86	5.96	37.17	49.67	74.00	-24.33	VERTICAL peak
6	9688.000	40.73	38.75	7.08	37.11	49.45	74.00	-24.55	VERTICAL peak




Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1702.042	46.55	25.15	2.85	38.03	36.52	74.00	-37.48	HORIZONTAL	peak
2	4430.628	43.82	33.87	4.61	37.45	44.85	74.00	-29.15	HORIZONTAL	peak
3	4844.000	42.97	34.15	4.84	37.37	44.59	74.00	-29.41	HORIZONTAL	peak
4	6795.879	44.34	34.69	5.79	37.13	47.69	74.00	-26.31	HORIZONTAL	peak
5	7266.000	45.63	35.86	5.96	37.17	50.28	74.00	-23.72	HORIZONTAL	peak
6	9688.000	42.61	38.75	7.08	37.11	51.33	74.00	-22.67	HORIZONTAL	peak




Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1663.137	46.29	24.93	2.81	38.06	35.97	74.00	-38.03	VERTICAL peak
2	4456.315	44.39	34.00	4.61	37.45	45.55	74.00	-28.45	VERTICAL peak
3	4874.000	43.29	34.15	4.85	37.35	44.94	74.00	-29.06	VERTICAL peak
4	6835.278	44.51	34.79	5.81	37.13	47.98	74.00	-26.02	VERTICAL peak
5	7311.000	43.33	36.00	5.98	37.18	48.13	74.00	-25.87	VERTICAL peak
6	9748.000	40.84	38.81	7.11	37.11	49.65	74.00	-24.35	VERTICAL peak




Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1342.882	48.06	24.12	2.62	38.55	36.25	74.00	-37.75	HORIZONTAL peak
2	4456.315	45.64	34.00	4.61	37.45	46.80	74.00	-27.20	HORIZONTAL peak
3	4874.000	43.17	34.15	4.85	37.35	44.82	74.00	-29.18	HORIZONTAL peak
4	6954.852	44.25	35.04	5.86	37.14	48.01	74.00	-25.99	HORIZONTAL peak
5	7311.000	43.80	36.00	5.98	37.18	48.60	74.00	-25.40	HORIZONTAL peak
6	9748.000	42.23	38.81	7.11	37.11	51.04	74.00	-22.96	HORIZONTAL peak




Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1587.975	49.80	24.65	2.75	38.15	39.05	74.00	-34.95	VERTICAL	peak
2	4354.454	46.24	33.43	4.60	37.46	46.81	74.00	-27.19	VERTICAL	peak
3	4904.000	43.50	34.15	4.86	37.34	45.17	74.00	-28.83	VERTICAL	peak
4	5179.049	48.68	33.69	4.98	37.22	50.13	74.00	-23.87	VERTICAL	peak
5	7356.000	44.81	36.12	5.99	37.18	49.74	74.00	-24.26	VERTICAL	peak
6	9808.000	42.16	38.86	7.14	37.10	51.06	74.00	-22.94	VERTICAL	peak




Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1414.597	48.48	24.29	2.67	38.47	36.97	74.00	-37.03	HORIZONTAL peak
2	4495.125	44.43	34.17	4.62	37.44	45.78	74.00	-28.22	HORIZONTAL peak
3	4904.000	43.72	34.15	4.86	37.34	45.39	74.00	-28.61	HORIZONTAL peak
4	6954.852	44.78	35.04	5.86	37.14	48.54	74.00	-25.46	HORIZONTAL peak
5	7356.000	43.25	36.12	5.99	37.18	48.18	74.00	-25.82	HORIZONTAL peak
6	9808.000	41.14	38.86	7.14	37.10	50.04	74.00	-23.96	HORIZONTAL peak

Test Mode: 05; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1644.019	46.78	24.84	2.79	38.08	36.33	74.00	-37.67	VERTICAL peak
2	4495.125	43.90	34.17	4.62	37.44	45.25	74.00	-28.75	VERTICAL peak
3	4824.000	43.37	34.16	4.82	37.37	44.98	74.00	-29.02	VERTICAL peak
4	6914.763	44.07	34.97	5.84	37.14	47.74	74.00	-26.26	VERTICAL peak
5	7236.000	44.69	35.78	5.95	37.17	49.25	74.00	-24.75	VERTICAL peak
6	9648.000	40.45	38.70	7.05	37.11	49.09	74.00	-24.91	VERTICAL peak


Test Mode: 05; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1398.336	47.12	24.26	2.66	38.49	35.55	74.00	-38.45	HORIZONTAL peak
2	4405.090	44.33	33.74	4.61	37.46	45.22	74.00	-28.78	HORIZONTAL peak
3	4824.000	43.29	34.16	4.82	37.37	44.90	74.00	-29.10	HORIZONTAL peak
4	6954.852	44.78	35.04	5.86	37.14	48.54	74.00	-25.46	HORIZONTAL peak
5	7236.000	44.23	35.78	5.95	37.17	48.79	74.00	-25.21	HORIZONTAL peak
6	9648.000	41.42	38.70	7.05	37.11	50.06	74.00	-23.94	HORIZONTAL peak




Test Mode: 05; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over		
	MHz	Level	Factor	Loss	dB	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1358.498	47.94	24.16	2.63	38.53	36.20	74.00	-37.80	VERTICAL peak
2	4482.150	44.51	34.12	4.62	37.44	45.81	74.00	-28.19	VERTICAL peak
3	4874.000	43.28	34.15	4.85	37.35	44.93	74.00	-29.07	VERTICAL peak
4	6914.763	44.13	34.97	5.84	37.14	47.80	74.00	-26.20	VERTICAL peak
5	7311.000	43.97	36.00	5.98	37.18	48.77	74.00	-25.23	VERTICAL peak
6	9748.000	41.34	38.81	7.11	37.11	50.15	74.00	-23.85	VERTICAL peak




Test Mode: 05; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over		
	MHz	Level	Factor	Loss	dB	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1663.137	46.63	24.93	2.81	38.06	36.31	74.00	-37.69	HORIZONTAL peak
2	4495.125	44.34	34.17	4.62	37.44	45.69	74.00	-28.31	HORIZONTAL peak
3	4874.000	44.58	34.15	4.85	37.35	46.23	74.00	-27.77	HORIZONTAL peak
4	6679.040	44.97	34.28	5.72	37.12	47.85	74.00	-26.15	HORIZONTAL peak
5	7311.000	45.16	36.00	5.98	37.18	49.96	74.00	-24.04	HORIZONTAL peak
6	9748.000	40.09	38.81	7.11	37.11	48.90	74.00	-25.10	HORIZONTAL peak




Test Mode: 05; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1682.477	46.58	25.03	2.83	38.05	36.39	74.00	-37.61	VERTICAL	peak
2	4495.125	44.68	34.17	4.62	37.44	46.03	74.00	-27.97	VERTICAL	peak
3	4924.000	43.30	34.15	4.88	37.33	45.00	74.00	-29.00	VERTICAL	peak
4	6954.852	44.81	35.04	5.86	37.14	48.57	74.00	-25.43	VERTICAL	peak
5	7386.000	43.66	36.23	6.00	37.18	48.71	74.00	-25.29	VERTICAL	peak
6	9848.000	41.32	38.88	7.15	37.10	50.25	74.00	-23.75	VERTICAL	peak




Test Mode: 05; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1414.597	47.65	24.29	2.67	38.47	36.14	74.00	-37.86	HORIZONTAL	peak
2	4354.454	45.11	33.43	4.60	37.46	45.68	74.00	-28.32	HORIZONTAL	peak
3	4924.000	43.67	34.15	4.88	37.33	45.37	74.00	-28.63	HORIZONTAL	peak
4	6954.852	43.53	35.04	5.86	37.14	47.29	74.00	-26.71	HORIZONTAL	peak
5	7386.000	43.80	36.23	6.00	37.18	48.85	74.00	-25.15	HORIZONTAL	peak
6	9848.000	40.27	38.88	7.15	37.10	49.20	74.00	-24.80	HORIZONTAL	peak




Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1587.975	47.73	24.65	2.75	38.15	36.98	74.00	-37.02	VERTICAL	peak
2	4456.315	44.26	34.00	4.61	37.45	45.42	74.00	-28.58	VERTICAL	peak
3	4824.000	44.26	34.16	4.82	37.37	45.87	74.00	-28.13	VERTICAL	peak
4	6526.373	45.53	33.91	5.66	37.12	47.98	74.00	-26.02	VERTICAL	peak
5	7236.000	43.11	35.78	5.95	37.17	47.67	74.00	-26.33	VERTICAL	peak
6	9648.000	41.73	38.70	7.05	37.11	50.37	74.00	-23.63	VERTICAL	peak




Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1406.443	47.39	24.27	2.66	38.47	35.85	74.00	-38.15	HORIZONTAL peak
2	4482.150	44.71	34.12	4.62	37.44	46.01	74.00	-27.99	HORIZONTAL peak
3	4824.000	43.12	34.16	4.82	37.37	44.73	74.00	-29.27	HORIZONTAL peak
4	6756.708	44.32	34.56	5.77	37.13	47.52	74.00	-26.48	HORIZONTAL peak
5	7236.000	43.42	35.78	5.95	37.17	47.98	74.00	-26.02	HORIZONTAL peak
6	9648.000	41.15	38.70	7.05	37.11	49.79	74.00	-24.21	HORIZONTAL peak




Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1358.498	47.89	24.16	2.63	38.53	36.15	74.00	-37.85	VERTICAL	peak
2	4495.125	44.86	34.17	4.62	37.44	46.21	74.00	-27.79	VERTICAL	peak
3	4874.000	44.50	34.15	4.85	37.35	46.15	74.00	-27.85	VERTICAL	peak
4	6995.172	44.05	35.11	5.87	37.15	47.88	74.00	-26.12	VERTICAL	peak
5	7311.000	44.23	36.00	5.98	37.18	49.03	74.00	-24.97	VERTICAL	peak
6	9748.000	40.90	38.81	7.11	37.11	49.71	74.00	-24.29	VERTICAL	peak




Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1702.042	47.07	25.15	2.85	38.03	37.04	74.00	-36.96	HORIZONTAL	peak
2	4456.315	44.72	34.00	4.61	37.45	45.88	74.00	-28.12	HORIZONTAL	peak
3	4874.000	44.44	34.15	4.85	37.35	46.09	74.00	-27.91	HORIZONTAL	peak
4	6795.879	44.66	34.69	5.79	37.13	48.01	74.00	-25.99	HORIZONTAL	peak
5	7311.000	44.70	36.00	5.98	37.18	49.50	74.00	-24.50	HORIZONTAL	peak
6	9748.000	41.05	38.81	7.11	37.11	49.86	74.00	-24.14	HORIZONTAL	peak




Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamplifier	Level	Limit	Over	Pol/Phase	Remark
	MHz	Level	Factor	Loss	Factor	Line	Limit		
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1542.733	47.41	24.53	2.72	38.23	36.43	74.00	-37.57	VERTICAL peak
2	4379.699	45.54	33.59	4.60	37.46	46.27	74.00	-27.73	VERTICAL peak
3	4924.000	42.58	34.15	4.88	37.33	44.28	74.00	-29.72	VERTICAL peak
4	6954.852	44.53	35.04	5.86	37.14	48.29	74.00	-25.71	VERTICAL peak
5	7386.000	43.33	36.23	6.00	37.18	48.38	74.00	-25.62	VERTICAL peak
6	9848.000	40.08	38.88	7.15	37.10	49.01	74.00	-24.99	VERTICAL peak




Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1672.779	46.70	24.98	2.82	38.05	36.45	74.00	-37.55	HORIZONTAL	peak
2	4405.090	44.65	33.74	4.61	37.46	45.54	74.00	-28.46	HORIZONTAL	peak
3	4924.000	42.68	34.15	4.88	37.33	44.38	74.00	-29.62	HORIZONTAL	peak
4	6954.852	45.07	35.04	5.86	37.14	48.83	74.00	-25.17	HORIZONTAL	peak
5	7386.000	44.27	36.23	6.00	37.18	49.32	74.00	-24.68	HORIZONTAL	peak
6	9848.000	40.81	38.88	7.15	37.10	49.74	74.00	-24.26	HORIZONTAL	peak




Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1615.754	47.85	24.74	2.77	38.13	37.23	74.00	-36.77	VERTICAL	peak
2	4430.628	45.35	33.87	4.61	37.45	46.38	74.00	-27.62	VERTICAL	peak
3	4844.000	43.22	34.15	4.84	37.37	44.84	74.00	-29.16	VERTICAL	peak
4	6874.906	44.09	34.88	5.83	37.14	47.66	74.00	-26.34	VERTICAL	peak
5	7266.000	44.50	35.86	5.96	37.17	49.15	74.00	-24.85	VERTICAL	peak
6	9688.000	40.08	38.75	7.08	37.11	48.80	74.00	-25.20	VERTICAL	peak




Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1414.597	48.89	24.29	2.67	38.47	37.38	74.00	-36.62	HORIZONTAL	peak
2	4495.125	44.17	34.17	4.62	37.44	45.52	74.00	-28.48	HORIZONTAL	peak
3	4844.000	42.73	34.15	4.84	37.37	44.35	74.00	-29.65	HORIZONTAL	peak
4	6954.852	44.42	35.04	5.86	37.14	48.18	74.00	-25.82	HORIZONTAL	peak
5	7266.000	43.50	35.86	5.96	37.17	48.15	74.00	-25.85	HORIZONTAL	peak
6	9688.000	42.32	38.75	7.08	37.11	51.04	74.00	-22.96	HORIZONTAL	peak




Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1304.623	47.90	23.99	2.59	38.58	35.90	74.00	-38.10	VERTICAL peak
2	4495.125	44.18	34.17	4.62	37.44	45.53	74.00	-28.47	VERTICAL peak
3	4874.000	43.67	34.15	4.85	37.35	45.32	74.00	-28.68	VERTICAL peak
4	6756.708	44.46	34.56	5.77	37.13	47.66	74.00	-26.34	VERTICAL peak
5	7311.000	44.73	36.00	5.98	37.18	49.53	74.00	-24.47	VERTICAL peak
6	9748.000	40.44	38.81	7.11	37.11	49.25	74.00	-24.75	VERTICAL peak




Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1414.597	47.13	24.29	2.67	38.47	35.62	74.00	-38.38	HORIZONTAL peak
2	4482.150	45.11	34.12	4.62	37.44	46.41	74.00	-27.59	HORIZONTAL peak
3	4874.000	43.78	34.15	4.85	37.35	45.43	74.00	-28.57	HORIZONTAL peak
4	6995.172	44.36	35.11	5.87	37.15	48.19	74.00	-25.81	HORIZONTAL peak
5	7311.000	44.12	36.00	5.98	37.18	48.92	74.00	-25.08	HORIZONTAL peak
6	9748.000	40.32	38.81	7.11	37.11	49.13	74.00	-24.87	HORIZONTAL peak




Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1672.779	46.88	24.98	2.82	38.05	36.63	74.00	-37.37	VERTICAL	peak
2	4405.090	45.31	33.74	4.61	37.46	46.20	74.00	-27.80	VERTICAL	peak
3	4904.000	43.91	34.15	4.86	37.34	45.58	74.00	-28.42	VERTICAL	peak
4	6835.278	44.08	34.79	5.81	37.13	47.55	74.00	-26.45	VERTICAL	peak
5	7356.000	44.71	36.12	5.99	37.18	49.64	74.00	-24.36	VERTICAL	peak
6	9808.000	42.20	38.86	7.14	37.10	51.10	74.00	-22.90	VERTICAL	peak



Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1342.882	47.65	24.12	2.62	38.55	35.84	74.00	-38.16	HORIZONTAL peak
2	4405.090	45.00	33.74	4.61	37.46	45.89	74.00	-28.11	HORIZONTAL peak
3	4904.000	44.04	34.15	4.86	37.34	45.71	74.00	-28.29	HORIZONTAL peak
4	6914.763	43.79	34.97	5.84	37.14	47.46	74.00	-26.54	HORIZONTAL peak
5	7356.000	44.62	36.12	5.99	37.18	49.55	74.00	-24.45	HORIZONTAL peak
6	9808.000	40.78	38.86	7.14	37.10	49.68	74.00	-24.32	HORIZONTAL peak

7.5 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.2

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 22.5 °C

Humidity: 63.5 % RH

Atmospheric Pressure: 1004 mbar


7.5.2 Test Mode Description

Pre-scan / Mode	Description
Final test Code	

Final test 00

TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details



7.6 Minimum 6dB Bandwidth

Test Requirement	47 CFR Part 15, Subpart C 15.247a(2)
Test Method:	ANSI C63.10 (2013) Section 11.8.1
Limit:	≥500 kHz

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 22.5 °C Humidity: 63.5 % RH Atmospheric Pressure: 1004 mbar


7.6.2 Test Mode Description

Pre-scan / Mode	Description
Final test Code	

TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

Final test 00

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.7 Power Spectrum Density

Test Requirement	47 CFR Part 15, Subpart C 15.247(e)
Test Method:	ANSI C63.10 (2013) Section 11.10.2
Limit:	≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.7.1 E.U.T. Operation


Operating Environment:

Temperature: 22.5 °C Humidity: 63.5 % RH Atmospheric Pressure: 1004 mbar

7.7.2 Test Mode Description

Pre-scan / Mode	Description
Final test Code	
Final test 00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.8 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.1 E.U.T. Operation

Operating Environment:


Temperature: 22.5 °C Humidity: 63.5 % RH Atmospheric Pressure: 1004 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.9 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 22.5 °C

Humidity: 63.5 % RH

Atmospheric Pressure: 1004 mbar


7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
--------------------------	--------------	-------------

Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.
------------	----	--



7.9.3 Test Setup Diagram



7.9.4 Measurement Procedure and Data

Please Refer to Appendix for Details

8 Test Setup Photo

Refer to Appendix - Test Setup Photos for GZCR250500072502



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch, EMC Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

9 EUT Constructional Details (EUT Photos)

Refer to Appendix - External and Internal Photos for GZCR2505000725AT



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch, EMC Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

10 Appendix

1. Duty Cycle


1.1 Test Result

1.1.1 Ant1


Ant1							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11b	SISO	2412	8.417	8.437	99.76	0.01	0.04
		2437	8.416	8.436	99.76	0.01	0.04
		2462	8.417	8.437	99.76	0.01	0.04
802.11g	SISO	2412	1.397	1.421	98.31	0.07	0.03
		2437	1.397	1.422	98.24	0.08	0.03
		2462	1.396	1.421	98.24	0.08	0.00
802.11n (HT40)	MIMO	2422	0.649	0.673	96.43	0.16	0.04
		2437	0.649	0.674	96.29	0.16	0.07
		2452	0.649	0.673	96.43	0.16	0.07

1.2 Test Graph


1.2.1 Ant1




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (MIMO)_NTNV



802.11n(HT40)_MCH_2437MHz_Ant1 (MIMO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant1 (MIMO)_NTNV



2. Bandwidth

2.1 Test Result

2.1.1 6dB BW

Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
802.11b	SISO	2412	1	9.538	≥ 0.5	Pass
		2437	1	10.057	≥ 0.5	Pass
		2462	1	9.114	≥ 0.5	Pass
802.11g	SISO	2412	1	13.812	≥ 0.5	Pass
		2437	1	15.123	≥ 0.5	Pass
		2462	1	15.136	≥ 0.5	Pass
802.11n (HT40)	MIMO	2422	1	35.142	≥ 0.5	Pass
		2437	1	35.180	≥ 0.5	Pass
		2452	1	27.579	≥ 0.5	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch, EMC Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

2.2 Test Graph

2.2.1 6dB BW

