Report No.: AGC00610130705FE02 Page 1 of 48

# **FCC Test Report**

Report No.: AGC00610130705FE02

FCC ID : 2AAKT-HB030

**APPLICATION PURPOSE**: Original Equipment

**PRODUCT DESIGNATION**: Bluetooth keyboard

**BRAND NAME** : N/A

HB038, HB039

**CLIENT** : Shenzhen Hastech Technology Co.,Ltd

**DATE OF ISSUE** : Jul.09,2013

**STANDARD(S)** : FCC Part 15 Rules

**REPORT VERSION**: V1.0

## Attestation of Global Compliance (Shenzhen) Co., Ltd

#### **CAUTION:**

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

Report No.: AGC00610130705FE02 Page 2 of 48

### **Report Revise Record**

| Report Version | Revise Time | Issued Date | Valid Version | Notes           |
|----------------|-------------|-------------|---------------|-----------------|
| V1.0           | /           | Jul.09,2013 | Valid         | Original Report |

#### **TABLE OF CONTENTS**

| 1. VERIFICATION OF CONFORMITY                        | 5   |
|--|-----|
| 2. GENERAL INFORMATION                               | 6   |
| 2.1. PRODUCT DESCRIPTION                             | 6   |
| 2.2. TABLE OF CARRIER FREQUENCYS                     | 6   |
| 2.3. RECEIVER INPUT BANDWIDTH                        | 7   |
| 2.4. EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE      | 7   |
| 2.5. EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOU | R 7 |
| 2.6. RELATED SUBMITTAL(S) / GRANT (S)                | 8   |
| 2.7. TEST METHODOLOGY                                | 8   |
| 2.8. SPECIAL ACCESSORIES                             | 8   |
| 2.9. EQUIPMENT MODIFICATIONS                         | 8   |
| 3. MEASUREMENT UNCERTAINTY                           | 9   |
| 4. DESCRIPTION OF TEST MODES                         | 9   |
| 5. SYSTEM TEST CONFIGURATION                         | 10  |
| 5.1. CONFIGURATION OF EUT SYSTEM                     | 10  |
| 5.2. EQUIPMENT USED IN EUT SYSTEM                    | 10  |
| 5.3. SUMMARY OF TEST RESULTS                         | 10  |
| 6. TEST FACILITY                                     | 11  |
| 7. PEAK OUTPUT POWER                                 | 12  |
| 7.1. MEASUREMENT PROCEDURE                           | 12  |
| 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)    | 12  |
| 7.3. LIMITS AND MEASUREMENT RESULT                   |     |
| 8. 20DB BANDWIDTH                                    | 14  |
| 8.1. MEASUREMENT PROCEDURE                           | 14  |
| 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)    |     |
| 8.3. LIMITS AND MEASUREMENT RESULTS                  |     |
| 9. CONDUCTED SPURIOUS EMISSION                       |     |
| 9.1. MEASUREMENT PROCEDURE                           |     |
| 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)    | 17  |
| 9.3. MEASUREMENT EQUIPMENT USED                      | 17  |
| 9.4. LIMITS AND MEASUREMENT RESULT                   | 17  |
| 10. RADIATED EMISSION                                | 21  |
| 10.1. MEASUREMENT PROCEDURE                          |     |
| 10.2. TEST SETUP                                     | 23  |

| 10.3. TEST RESULT   | 24 |
|---|----|
| 11. BAND EDGE EMISSION                                      | 28 |
| 11.1. MEASUREMENT PROCEDURE                                 | 28 |
| 11.2. TEST SET-UP   | 28 |
| 11.3. TEST RESULT   | 29 |
| 12. NUMBER OF HOPPING FREQUENCY                             | 33 |
| 12.1. MEASUREMENT PROCEDURE                                 | 33 |
| 12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)           | 33 |
| 12.3. MEASUREMENT EQUIPMENT USED                            | 33 |
| 12.4. LIMITS AND MEASUREMENT RESULT                         | 33 |
| 13. TIME OF OCCUPANCY (DWELL TIME)                          | 34 |
| 13.1. MEASUREMENT PROCEDURE                                 | 34 |
| 13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)           | 34 |
| 13.3. MEASUREMENT EQUIPMENT USED                            | 34 |
| 13.4. LIMITS AND MEASUREMENT RESULT                         | 34 |
| 14. FREQUENCY SEPARATION                                    | 37 |
| 14.1. MEASUREMENT PROCEDURE                                 | 37 |
| 14.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)           | 37 |
| 14.3. MEASUREMENT EQUIPMENT USED                            | 37 |
| 14.4. LIMITS AND MEASUREMENT RESULT                         | 37 |
| 15. FCC LINE CONDUCTED EMISSION TEST                        | 38 |
| 15.1. LIMITS OF LINE CONDUCTED EMISSION TEST                | 38 |
| 15.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST         | 38 |
| 15.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST | 39 |
| 15.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST       | 39 |
| 15.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST           | 40 |
| APPENDIX A: PHOTOGRAPHS OF TEST SETUP                       | 42 |
| APPENDIX B: PHOTOGRAPHS OF EUT                              | 44 |

Page 5 of 48

#### 1. VERIFICATION OF CONFORMITY

| Shenzhen Hastech Technology Co.,Ltd   |  |  |
|---|--|--|
| G-A1 BLDG,Democracy West Industry Park, Shajing town,<br>Bao'an District ,Shenzhen, China |  |  |
| Shenzhen Hastech Technology Co.,Ltd   |  |  |
| G-A1 BLDG,Democracy West Industry Park, Shajing town,<br>Bao'an District ,Shenzhen, China |  |  |
| Bluetooth keyboard  |  |  |
| N/A   |  |  |
| HB030   |  |  |
| HB005, HB033, HB034, HB035,HB036,HB037, HB038, HB039                                      |  |  |
| Electrical identical except for the model name and appearance.                            |  |  |
| Jul.04~ Jul.06,2013   |  |  |
| None  |  |  |
| Normal  |  |  |
| AGCRT-US-BR/RF (2013-03-01)   |  |  |
|   |  |  |

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.247.

Wall Huang Jul.09,2013

Checked By

Forrest Lei Jul.09,2013

Authorized By

Solger Zhang Jul.09,2013

Page 6 of 48

#### 2. GENERAL INFORMATION

#### 2.1. PRODUCT DESCRIPTION

The EUT is a **Bluetooth keyboard** designed as a "Communication Device". It is designed by way of utilizing the FHSS technology to achieve the system operation.

A major technical description of EUT is described as following

| Operation Frequency | 2.402 GHz to 2.480GHz             |
|---------------------|-----------------------------------|
| RF Output Power     | 0.85dBm(Max)                      |
| Bluetooth Version   | V 3.0                             |
| Modulation          | GFSK                              |
| Number of channels  | 79                                |
| Antenna Designation | Integrated Antenna                |
| Antenna Gain        | 0dBi                              |
| Power Supply        | DC3.7V by Built-in Li-ion Battery |

Note: 1.BT is active when charging. The USB port is only used for charging and can't be used to transfer data with PC.

2. The EUT is equipped with the Bluetooth Chip BCM20730 which complies with Bluetooth V3.0. BUT for this device the functionality is limited to GFSK (1 MBit/s) by the firmware. End-user is not able to change the settings and enable any additional functionality by himself.

#### 2.2. TABLE OF CARRIER FREQUENCYS

| Frequency Band | Channel Number | Frequency |  |
|----------------|----------------|-----------|--|
|                | 0              | 2402MHZ   |  |
|                | 1              | 2403MHZ   |  |
|                | :              | :         |  |
|                | 38             | 2440 MHZ  |  |
| 2400~2483.5MHZ | 39             | 2441 MHZ  |  |
|                | 40             | 2442 MHZ  |  |
|                | ••             | :         |  |
|                | 77             | 2479 MHZ  |  |
|                | 78             | 2480 MHZ  |  |

Page 7 of 48

#### 2.3. RECEIVER INPUT BANDWIDTH

The input bandwidth of the receiver is 1.3MHZ,In every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally the type of connection(e.g. single of multislot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings.

Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

#### 2.4. EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE

Example of a 79 hopping sequence in data mode: 40,21,44,23,42,53,46,55,48,33,52,35,50,65,54,67 56,37,60,39,58,69,62,71,64,25,68,27,66,57,70,59 72,29,76,31,74,61,78,63,01,41,05,43,03,73,07,75 09,45,13,47,11,77,15,00,64,49,66,53,68,02,70,06 01, 51, 03, 55, 05, 04

#### 2.5. EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR

The generation of the hopping sequence in connection mode depends essentially on two input values:

- 1. LAP/UAP of the master of the connection.
- 2. Internal master clock

The LAP(lower address part) are the 24 LSB's of the 48 BD\_ADDRESS. The BD\_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP(upper address part) are the 24MSB's of the 48BD ADDRESS

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For ehavior zation with other units only offset are used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5us. The clock has a cycle of about one day(23h30). In most case it is implemented as 28 bit counter. For the deriving of the hopping sequence the entire. LAP(24 bits), 4LSB's (4bits) (Input 1) and the 27MSB's of the clock (Input 2) are used. With this input values different mathematical procedures (permutations, additions, XOR-operations) are performed to generate te Sequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following ehavior:

The first connection between the two devices is established, a hopping sequence was generated. For Transmitting the wanted data the complete hopping sequence was not used. The connection ended. The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmission is longer(and it Cannot be shorter) than the minimum resolution of the clock(312.5us). The hopping sequence will always Differ from the first one.

Page 8 of 48

#### 2.6. RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID**: **2AAKT-HB030** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

#### 2.7. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.4 (2003). Radiated testing was performed at an antenna to EUT distance 3 meters.

#### 2.8. SPECIAL ACCESSORIES

Refer to section 5.2.

#### 2.9. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

Page 9 of 48

#### 3. MEASUREMENT UNCERTAINTY

Conducted measurement: +/- 2.75dB Radiated measurement: +/- 3.2dB

#### 4. DESCRIPTION OF TEST MODES

|     | TEST MODE DESCRIPTION |       |  |  |  |  |
|-----|-----------------------|-------|--|--|--|--|
| NO. | TEST MODE DESCRIPTION | WORST |  |  |  |  |
| 1   | Low channel TX        |       |  |  |  |  |
| 2   | Middle channel TX     |       |  |  |  |  |
| 3   | High channel TX       |       |  |  |  |  |
| 4   | Normal Hopping        | V     |  |  |  |  |

#### Note:

- 1. V means EMI worst mode.
- 2. All the test modes can be supply by Built-in Li-ion battery and adapter, only the result of the worst case was recorded in the report, if no other cases.
- 3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.


Report No.: AGC00610130705FE02 Page 10 of 48

#### 5. SYSTEM TEST CONFIGURATION

#### **5.1. CONFIGURATION OF EUT SYSTEM**

#### Configuration:

Configure 1 (Normal hopping)



Configure 1 (Control continuous TX)



#### **5.2. EQUIPMENT USED IN EUT SYSTEM**

| Item                 | Equipment     | Mfr/Brand | Model/Type No. | Remark    |
|----------------------|---------------|-----------|----------------|-----------|
| 1 Bluetooth keyboard |               | N/A       | HB030          | EUT       |
| 2                    | Battery       | N/A       | 382035p        | Accessory |
| 3                    | PC            | Dell      | INSPIRON       | A.E       |
| 4                    | Control Board | N/A       | N/A            | A.E       |
| 5                    | Table PC      | N/A       | N/A            | A.E       |

#### **5.3. SUMMARY OF TEST RESULTS**

| FCC RULES | DESCRIPTION OF TEST         | RESULT    |
|-----------|-----------------------------|-----------|
| §15.247   | Peak Output Power           | Compliant |
| §15.247   | 20 dB Bandwidth             | Compliant |
| §15.247   | Spurious Emission           | Compliant |
| §15.209   | Radiated Emission           | Compliant |
| §15.247   | Band Edges                  | Compliant |
| §15.207   | Conduction Emission         | Compliant |
| §15.247   | Number of Hopping Frequency | Compliant |
| §15.247   | Time of Occupancy           | Compliant |
| §15.247   | Frequency Separation        | Compliant |

Report No.: AGC00610130705FE02 Page 11 of 48

#### **6. TEST FACILITY**

| Site        | Attestation of Global Compliance (Shenzhen) Co., Ltd   |  |  |
|-------------|--|--|--|
| Location    | 2/F., Building 2, No.1-No.4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen, Guangdong, China |  |  |
| Description | The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2003.                           |  |  |

#### **ALL TEST EQUIPMENT LIST**

| Description           | Manufacturer      | Model       | S/N        | Cal. Date  | Cal. Due   |
|-----------------------|-------------------|-------------|------------|------------|------------|
| Power Probe           | R&S               | NRP-Z23     | 100323     | 07/18/2012 | 07/17/2013 |
| RF attenuator         | N/A               | RFA20db     | 68         | N/A        | N/A        |
| Spectrum Analyzer     | Agilent           | E4440A      | US41421290 | 07/18/2012 | 07/17/2013 |
| Amplifier             | EM                | EM30180     | 0607030    | 02/28/2013 | 02/27/2014 |
| Horn Antenna          | EM                | EM-AH-10180 | 67         | 04/21/2012 | 04/20/2014 |
| Horn Antenna          | A.H. Systems Inc. | SAS-574     |            | 06/08/2013 | 06/07/2014 |
| EMI Test Receiver     | Rohde & Schwarz   | ESCI        | 100694     | 07/18/2012 | 07/17/2013 |
| Bilogical Antenna     | A.H. Systems Inc. | SAS-521-4   | 26         | 06/08/2013 | 06/07/2014 |
| Loop Antenna          | Daze              | ZN30900N    | SEL0097    | 07/18/2012 | 07/17/2013 |
| Isolation Transformer | LETEAC            | LTBK        |            | 07/18/2012 | 07/17/2013 |

Page 12 of 48

#### 7. PEAK OUTPUT POWER

#### 7.1. MEASUREMENT PROCEDURE

For peak power test:

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 3. Set the EUT Work on the top, middle and the bottom operation frequency individually.
- 4. Set the RBW greater than 6DB bandwidth of emission.
- 5. Record the maximum power from the Spectrum Analyzer.


#### For average power test:

- 1. The EUT was placed on a table which is 0.8m above ground plane.
- 2. Connect EUT RF output port to power probe through an RF attenuator.
- 3. Connect the power probe to the PC.
- 3. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 4. Record the maximum power from the software.
- 5. The maximum peak power shall be less 1 Watt (30dBm).


Note: The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

#### 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

#### **PEAK POWER TEST SETUP**



#### **AVERAGE POWER SETUP**



Report No.: AGC00610130705FE02 Page 13 of 48

#### 7.3. LIMITS AND MEASUREMENT RESULT

| PEAK OUTPUT POWER MEASUREMENT RESULT FOR GFSK MOUDULATION                              |       |      |    |      |  |  |
|--|-------|------|----|------|--|--|
| Frequency (GHz)  Average Power (dBm)  Peak Power Applicable Limits (dBm)  Pass or Fail |       |      |    |      |  |  |
| 2.402  | -1.82 | 0.76 | 30 | Pass |  |  |
| 2.441  | -1.89 | 0.85 | 30 | Pass |  |  |
| 2.480  | -1.76 | 0.71 | 30 | Pass |  |  |


Page 14 of 48

#### 8. 20DB BANDWIDTH

#### **8.1. MEASUREMENT PROCEDURE**

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 3, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 4. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hoping channel RBW ≥ 1% of the 20 dB bandwidth, VBW ≥ RBW; Sweep = auto; Detector function = peak
- 5. Set SPA Trace 1 Max hold, then View.

#### 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)




#### **8.3. LIMITS AND MEASUREMENT RESULTS**


| BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESUL |                    |          |      |  |  |  |  |  |
|--|--------------------|----------|------|--|--|--|--|--|
| Amaliachla Limita                            | Measurement Result |          |      |  |  |  |  |  |
| Applicable Limits                            | Test Da            | Criteria |      |  |  |  |  |  |
|  | Low Channel        | 0.956    | PASS |  |  |  |  |  |
| N/A  | Middle Channel     | 0.922    | PASS |  |  |  |  |  |
|  | High Channel       | 0.924    | PASS |  |  |  |  |  |

Page 15 of 48

#### TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




#### TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



Page 16 of 48

#### TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



Page 17 of 48

#### 9. CONDUCTED SPURIOUS EMISSION

#### 9.1. MEASUREMENT PROCEDURE

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 3. Set the EUT Work on the top, the Middle and the bottom operation frequency individually.
- 4. Set the Span = wide enough to capture the peak level of the in-band emission and all spurious emissions from the lowest frequency generated in the EUT up through the 10th harmonic.
  - RBW = 100 kHz; VBW ≥ RBW; Sweep = auto; Detector function = peak.
- 5. Set SPA Trace 1 Max hold, then View.

#### 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 8.2

#### 9.3. MEASUREMENT EQUIPMENT USED


The same as described in section 6


#### 9.4. LIMITS AND MEASUREMENT RESULT

| LIMITS AND MEASUREMENT RESULT                          |                                |          |  |  |  |  |  |  |
|--|--------------------------------|----------|--|--|--|--|--|--|
| Applicable Limite                                      | Measurement Result             |          |  |  |  |  |  |  |
| Applicable Limits                                      | Test Data                      | Criteria |  |  |  |  |  |  |
| In any 100 KHz Bandwidth Outside the                   | At least -20dBc than the limit |          |  |  |  |  |  |  |
| frequency band in which the spread spectrum            | Specified on the BOTTOM        | PASS     |  |  |  |  |  |  |
| intentional radiator is operating, the radio frequency | Channel                        |          |  |  |  |  |  |  |
| power that is produce by the intentional radiator      |                                |          |  |  |  |  |  |  |
| shall be at least 20 dB below that in 100KHz           |                                |          |  |  |  |  |  |  |
| bandwidth within the band that contains the highest    |                                |          |  |  |  |  |  |  |
| level of the desired power.                            | At least -20dBc than the limit | DACC     |  |  |  |  |  |  |
| In addition, radiation emissions which fall in the     | Specified on the TOP Channel   | PASS     |  |  |  |  |  |  |
| restricted bands, as defined in §15.205(a), must also  |                                |          |  |  |  |  |  |  |
| comply with the radiated emission limits specified     |                                |          |  |  |  |  |  |  |
| in§15.209(a))  |                                |          |  |  |  |  |  |  |

Page 18 of 48


## TEST PLOT OF OUT OF BAND EMISSIONS WITH THE WORST CASE OF GFSK MODULATION IN LOW CHANNEL






Page 19 of 48


## TEST PLOT OF OUT OF BAND EMISSIONS OF GFSK MODULATION IN MIDDLE CHANNEL






Page 20 of 48

## TEST PLOT OF OUT OF BAND EMISSIONS OF GFSK MODULATION IN HIGH CHANNEL





Page 21 of 48

#### 10. RADIATED EMISSION

#### 10.1. MEASUREMENT PROCEDURE

- 1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

Report No.: AGC00610130705FE02 Page 22 of 48

The following table is the setting of spectrum analyzer and receiver.


| Spectrum Parameter    | Setting                                   |
|-----------------------|---|
| Start ~Stop Frequency | 9KHz~150KHz/RB 200Hz for QP               |
| Start ~Stop Frequency | 150KHz~30MHz/RB 9KHz for QP               |
| Start ~Stop Frequency | 30MHz~1000MHz/RB 120KHz for QP            |
| Start ~Stop Frequency | 1GHz~26.5GHz                              |
| Start Stop Froquency  | 1MHz/1MHz for Peak, 1MHz/10Hz for Average |

| Receiver Parameter    | Setting                        |
|-----------------------|--------------------------------|
| Start ~Stop Frequency | 9KHz~150KHz/RB 200Hz for QP    |
| Start ~Stop Frequency | 150KHz~30MHz/RB 9KHz for QP    |
| Start ~Stop Frequency | 30MHz~1000MHz/RB 120KHz for QP |


Page 23 of 48

#### 10.2. TEST SETUP


#### RADIATED EMISSION TEST SETUP BELOW 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz




Page 24 of 48

#### 10.3. TEST RESULT

#### RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

#### RADIATED EMISSION BELOW 1GHZ-Horizontal



Site: site #1

Limit: FCC Class B 3M Radiation

EUT: Bluetooth keyboard

M/N: HB030

Mode: Normal Hopping

Note:


Polarization: *Horizontal* Temperature: 26
Power: Humidity: 60 %

Distance: 3m

| No. | Mk | Freq.    | Reading | Factor | Measurement | Limit  | Over   | Detector | Antenna<br>Height | Table<br>Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|-------------------|-----------------|---------|
|     |    | MHz      | dBuV    | dB/m   | dBuV/m      | dBuV/m | dB     |          | cm                | degree          |         |
| 1   |    | 47.7833  | 30.36   | 2.35   | 32.71       | 40.00  | -7.29  | peak     |                   |                 |         |
| 2   | *  | 96.2833  | 25.71   | 10.51  | 36.22       | 43.50  | -7.28  | peak     |                   |                 |         |
| 3   |    | 228.8500 | 23.23   | 12.53  | 35.76       | 46.00  | -10.24 | peak     |                   |                 |         |
| 4   |    | 395.3667 | 19.30   | 16.87  | 36.17       | 46.00  | -9.83  | peak     |                   |                 |         |
| 5   |    | 599.0667 | 5.77    | 24.90  | 30.67       | 46.00  | -15.33 | peak     |                   |                 |         |
| 6   |    | 839.9500 | 4.35    | 32.74  | 37.09       | 46.00  | -8.91  | peak     |                   |                 |         |

Page 25 of 48

#### RADIATED EMISSION BELOW 1GHZ-Vertical



Site: site #1 Limit: FCC Class B 3M Radiation

EUT: Bluetooth keyboard

M/N: HB030

Mode: Normal Hopping

Note:


Polarization: *Horizontal* Temperature: 26 Power: Humidity: 60 %

Distance: 3m

| No. | Mk | Freq.    | Reading | Factor | Measurement | Limit  | Over   | Detector | Antenna<br>Height | Table<br>Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|-------------------|-----------------|---------|
|     |    | MHz      | dBuV    | dB/m   | dBuV/m      | dBuV/m | dB     |          | cm                | degree          |         |
| 1   | *  | 47.7832  | 32.17   | 4.04   | 36.21       | 40.00  | -3.79  | peak     |                   |                 |         |
| 2   |    | 144.7831 | 30.80   | 5.47   | 36.27       | 43.50  | -7.23  | peak     |                   |                 |         |
| 3   |    | 333.9331 | 14.75   | 19.96  | 34.71       | 46.00  | -11.29 | peak     |                   |                 |         |
| 4   |    | 395.3666 | 15.89   | 19.17  | 35.06       | 46.00  | -10.94 | peak     |                   |                 |         |
| 5   |    | 599.0665 | 8.24    | 24.90  | 33.14       | 46.00  | -12.86 | peak     |                   |                 |         |
| 6   |    | 741.3333 | 6.14    | 29.05  | 35.19       | 46.00  | -10.81 | peak     |                   |                 |         |

Page 26 of 48

### RADIATED EMISSION ABOVE 1GHZ (1-10<sup>th</sup> Harmonics) -Horizontal



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth keyboard Distance: 3m

M/N: HB030


Mode: Normal Hopping

Note:

| No. | Mk | Freq.    | Reading | Factor | Measurement | Limit  | Over   | Detector | Antenna<br>Height | Table<br>Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|-------------------|-----------------|---------|
|     | -  | MHz      | dBuV    | dB/m   | dBuV/m      | dBuV/m | dB     |          | cm                | degree          |         |
| 1   |    | 1166.667 | 42.77   | -11.25 | 31.52       | 74.00  | -42.48 | peak     |                   |                 |         |
| 2   | *  | 2402.000 | 81.21   | -8.39  | 72.82       | 74.00  | -1.18  | peak     |                   |                 |         |
| 3   |    | 2480.000 | 80.89   | -8.08  | 72.81       | 74.00  | -1.19  | peak     |                   |                 |         |
| 4   |    | 3213.333 | 41.26   | -8.26  | 33.00       | 74.00  | -41.00 | peak     |                   |                 |         |

Page 27 of 48

### RADIATED EMISSION ABOVE 1GHZ (1-10<sup>th</sup> Harmonics) -Vertical



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth keyboard Distance: 3m

M/N: HB030

Mode: Normal Hopping

Note:

| No. | Mk | Freq.    | Reading | Factor | Measurement | Limit  | Over   | Detector | Antenna<br>Height |        | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|-------------------|--------|---------|
|     |    | MHz      | dBuV    | dB/m   | dBuV/m      | dBuV/m | dB     |          | cm                | degree |         |
| 1   |    | 1740.000 | 38.68   | -10.25 | 28.43       | 74.00  | -45.57 | peak     |                   |        |         |
| 2   | *  | 2402.000 | 80.21   | -8.39  | 71.82       | 74.00  | -2.18  | peak     |                   |        |         |
| 3   |    | 2480.000 | 79.89   | -8.08  | 71.81       | 74.00  | -2.19  | peak     |                   |        |         |
| 4   |    | 2986.667 | 39.09   | -8.73  | 30.36       | 74.00  | -43.64 | peak     |                   |        |         |

#### **RESULT: PASS**

**Note:** 5~25GHz at least have 20dB margin. No recording in the test report. Factor=Antenna Factor+ Cable loss-Amplifier gain, Margin=Measurement-Limit.

Page 28 of 48

#### 11. BAND EDGE EMISSION

#### 11.1. MEASUREMENT PROCEDURE

- 1. Set the EUT Work on the top, the bottom operation frequency individually.
- 2. Set SPA Start or Stop Frequency = Operation Frequency, RBW>=1%span, VBW>=RBW
- 3. The band edges was measured and recorded.


#### **11.2. TEST SET-UP**

Radiated same as 10.2

Page 29 of 48

#### 11.3. TEST RESULT

#### TEST PLOT OF BAND EDGE FOR LOW CHANNEL (3Mbps)-Horizontal



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth keyboard Distance: 3m

M/N: HB030


Mode: Low Channel TX

Note:

| No. | Mk | Freq.    | Reading | Factor | Measurement | Limit  | Over   | Detector | Antenna<br>Height | Table<br>Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|-------------------|-----------------|---------|
|     |    | MHz      | dBuV    | dB/m   | dBuV/m      | dBuV/m | dB     |          | cm                | degree          |         |
| 1   |    | 2386.833 | 39.61   | -8.45  | 31.16       | 74.00  | -42.84 | peak     |                   |                 |         |
| 2   |    | 2390.000 | 37.68   | -8.44  | 29.24       | 74.00  | -44.76 | peak     |                   |                 |         |
| 3   |    | 2398.125 | 40.76   | -8.41  | 32.35       | 74.00  | -41.65 | peak     |                   |                 |         |
| 4   | *  | 2402.069 | 78.71   | -8.39  | 70.32       | 74.00  | -3.68  | peak     |                   |                 |         |

Page 30 of 48

#### TEST PLOT OF BAND EDGE FOR LOW CHANNEL (3Mbps)-Vertical



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth keyboard Distance: 3m

M/N: HB030


Mode: Low Channel TX

Note:

| No. | Mk | Freq.    | Reading | Factor | Measurement | Limit  | Over   | Detector | Antenna<br>Height |        | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|-------------------|--------|---------|
|     |    | MHz      | dBuV    | dB/m   | dBuV/m      | dBuV/m | dB     |          | cm                | degree |         |
| 1   |    | 2381.417 | 38.06   | -8.47  | 29.59       | 74.00  | -44.41 | peak     |                   |        |         |
| 2   |    | 2390.000 | 37.99   | -8.44  | 29.55       | 74.00  | -44.45 | peak     |                   |        |         |
| 3   |    | 2391.625 | 40.77   | -8.43  | 32.34       | 74.00  | -41.66 | peak     |                   |        |         |
| 4   | *  | 2402.089 | 80.07   | -8.39  | 71.68       | 74.00  | -2.32  | peak     |                   |        |         |

Page 31 of 48

#### TEST PLOT OF BAND EDGE FOR HIGH CHANNEL (3Mbps)-Horizontal



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth keyboard Distance: 3m

M/N: HB030


Mode: High Channel TX

Note:

| No. | Mk | Freq.    | Reading | Factor | Measurement | Limit  | Over   | Detector | Antenna<br>Height | Table<br>Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|-------------------|-----------------|---------|
|     |    | MHz      | dBuV    | dB/m   | dBuV/m      | dBuV/m | dB     |          | cm                | degree          |         |
| 1   | *  | 2480.071 | 79.23   | -8.08  | 71.15       | 74.00  | -2.85  | peak     |                   |                 |         |
| 2   |    | 2483.500 | 37.24   | -8.07  | 29.17       | 74.00  | -44.83 | peak     |                   |                 |         |
| 3   |    | 2487.827 | 41.67   | -8.05  | 33.62       | 74.00  | -40.38 | peak     |                   |                 |         |
| 4   |    | 2496.810 | 41.40   | -8.01  | 33.39       | 74.00  | -40.61 | peak     |                   |                 |         |

Page 32 of 48

#### TEST PLOT OF BAND EDGE FOR HIGH CHANNEL (3Mbps)-Vertical



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth keyboard Distance: 3m

M/N: HB030

Mode: High Channel TX

Note:

| No. | Mk | Freq.    | Reading | Factor | Measurement | Limit  | Over   | Detector | Antenna<br>Height |        | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|-------------------|--------|---------|
|     | -  | MHz      | dBuV    | dB/m   | dBuV/m      | dBuV/m | dB     |          | cm                | degree |         |
| 1   | *  | 2480.092 | 79.42   | -8.08  | 71.34       | 74.00  | -2.66  | peak     |                   |        |         |
| 2   |    | 2483.500 | 35.61   | -8.07  | 27.54       | 74.00  | -46.46 | peak     |                   |        |         |
| 3   |    | 2485.040 | 38.71   | -8.06  | 30.65       | 74.00  | -43.35 | peak     |                   |        |         |
| 4   |    | 2491.420 | 38.27   | -8.03  | 30.24       | 74.00  | -43.76 | peak     |                   |        |         |

Page 33 of 48

#### 12. NUMBER OF HOPPING FREQUENCY

#### 12.1. MEASUREMENT PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer Start = 2.4GHz Stop = 2.4835GHz
- 4. Set the Spectrum Analyzer as RBW>=1%span, VBW>=RBW.

#### 12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 8.2


#### 12.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6

#### 12.4. LIMITS AND MEASUREMENT RESULT

| TOTAL NO. OF<br>HOPPING CHANNEL | LIMIT (NO. OF CH) | MEASUREMENT<br>(NO. OF CH) | RESULT |
|---------------------------------|-------------------|----------------------------|--------|
|                                 | >=15              | 79                         | PASS   |

#### TEST PLOT FOR NO. OF TOTAL CHANNELS



Page 34 of 48

#### 13. TIME OF OCCUPANCY (DWELL TIME)

#### 13.1. MEASUREMENT PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode
- 2. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer.
- 3. Set Span = zero span, centered on a hoping channel
- 4. Set the spectrum analyzer as RBW=1MHz, VBW>=RBW, Span = 0 Hz

#### 13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 8.2

#### 13.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6

#### 13.4. LIMITS AND MEASUREMENT RESULT


#### The Worst Case (1Mbps)

| Channel | Time of Pulse for DH5 (ms) | Period Time<br>(s) | Sweep Time<br>(ms) | Limit<br>(ms) |
|---------|----------------------------|--------------------|--------------------|---------------|
| Low     | 2.891                      | 31.6               | 308.37             | 400           |
| Middle  | 2.891                      | 31.6               | 308.37             | 400           |
| High    | 2.891                      | 31.6               | 308.37             | 400           |


Low Channel Time 2.891\*(1600/6)/79\*31.6=308.37ms Middle Channel Time 2.891\*(1600/6)/79\*31.6=308.37ms High Channel Time 2.891\*(1600/6)/79\*31.6=308.37ms

Page 35 of 48

#### **TEST PLOT OF LOW CHANNEL**




TEST PLOT OF MIDDLE CHANNEL



Page 36 of 48

#### TEST PLOT OF HIGH CHANNEL



Page 37 of 48

## 14. FREQUENCY SEPARATION

### 14.1. MEASUREMENT PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode
- 2. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer
- 3. Set Span = wide enough to capture the peaks of two adjacent channels Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span Video (or Average) Bandwidth (VBW) ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold

## 14.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 6.2


#### 14.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.3

#### 14.4. LIMITS AND MEASUREMENT RESULT

| CHANNEL   | CHANNEL SEPARATION | LIMIT                    | RESULT |  |  |
|-----------|--------------------|--------------------------|--------|--|--|
|           | KHz                | KHz                      | Pass   |  |  |
| CH00-CH01 | 1000               | >=25 KHz or 2/3 20 dB BW |        |  |  |

## TEST PLOT FOR FREQUENCY SEPARATION (1Mbps)



Page 38 of 48

## 15. FCC LINE CONDUCTED EMISSION TEST


## 15.1. LIMITS OF LINE CONDUCTED EMISSION TEST

| Francis       | Maximum RF Line Voltage |                |  |  |  |  |  |  |
|---------------|-------------------------|----------------|--|--|--|--|--|--|
| Frequency     | Q.P.( dBuV)             | Average( dBuV) |  |  |  |  |  |  |
| 150kHz~500kHz | 66-56                   | 56-46          |  |  |  |  |  |  |
| 500kHz~5MHz   | 56                      | 46             |  |  |  |  |  |  |
| 5MHz~30MHz    | 60                      | 50             |  |  |  |  |  |  |

## Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

## 15.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



Page 39 of 48

#### 15.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.

- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. All support equipments received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC5V charging voltage by PC which received 120V/60Hzpower by a LISN..
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

## 15.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST


- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

Humidity: 60 %

Page 40 of 48

## 15.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

## Line Conducted Emission Test Line 1-L



Site: Conduction

Limit: FCC Class B Conduction(QP)

EUT: Bluetooth keyboard

M/N: HB030

Mode: Normal Hopping


Note:

| No. Freq. (MHz) | Reading_Level<br>(dBuV) |       |     | Correct<br>Factor | Measurement<br>(dBuV) |       |     | Limit<br>(dBuV) |       | Margin<br>(dB) |        | P/F    | Comment |  |
|-----------------|-------------------------|-------|-----|-------------------|-----------------------|-------|-----|-----------------|-------|----------------|--------|--------|---------|--|
|                 | Peak                    | QP    | AVG | dB                | Peak                  | QP    | AVG | QP              | AVG   | QP             | AVG    |        |         |  |
| 1               | 0.4980                  | 41.30 |     | 28.50             | 10.40                 | 51.70 |     | 38.90           | 56.03 | 46.03          | -4.33  | -7.13  | Р       |  |
| 2               | 0.6100                  | 42.13 |     | 23.91             | 10.31                 | 52.44 |     | 34.22           | 56.00 | 46.00          | -3.56  | -11.78 | Р       |  |
| 3               | 0.8820                  | 38.50 |     | 24.78             | 10.39                 | 48.89 |     | 35.17           | 56.00 | 46.00          | -7.11  | -10.83 | Р       |  |
| 4               | 2.6580                  | 34.99 |     | 25.82             | 10.47                 | 45.46 |     | 36.29           | 56.00 | 46.00          | -10.54 | -9.71  | Р       |  |
| 5               | 5.2500                  | 34.78 |     | 24.10             | 10.25                 | 45.03 |     | 34.35           | 60.00 | 50.00          | -14.97 | -15.65 | Р       |  |
| 6               | 13.5180                 | 35.12 |     | 22.85             | 10.13                 | 45.25 |     | 32.98           | 60.00 | 50.00          | -14.75 | -17.02 | Р       |  |

Power:

Page 41 of 48

## Line Conducted Emission Test Line 2-N



Site: Conduction Phase: N Temperature: 26
Limit: FCC Class B Conduction(QP) Power: Humidity: 60 %

EUT: Bluetooth keyboard

M/N: HB030

Mode: Normal Hopping

Note:

| No. Freq. (MHz) | Reading_Level<br>(dBuV) |       |     | Correct<br>Factor | Measurement<br>(dBuV) |       |     | Limit<br>(dBuV) |       | Margin<br>(dB) |        | P/F    | Comment |  |
|-----------------|-------------------------|-------|-----|-------------------|-----------------------|-------|-----|-----------------|-------|----------------|--------|--------|---------|--|
|                 | Peak                    | QP    | AVG | dB                | Peak                  | QP    | AVG | QP              | AVG   | QP             | AVG    |        |         |  |
| 1               | 0.4820                  | 40.81 |     | 32.33             | 10.39                 | 51.20 |     | 42.72           | 56.30 | 46.30          | -5.10  | -3.58  | Р       |  |
| 2               | 0.5700                  | 40.81 |     | 27.49             | 10.34                 | 51.15 |     | 37.83           | 56.00 | 46.00          | -4.85  | -8.17  | Р       |  |
| 3               | 0.7100                  | 38.42 |     | 23.18             | 10.34                 | 48.76 |     | 33.52           | 56.00 | 46.00          | -7.24  | -12.48 | Р       |  |
| 4               | 0.8740                  | 37.70 |     | 21.35             | 10.38                 | 48.08 |     | 31.73           | 56.00 | 46.00          | -7.92  | -14.27 | Р       |  |
| 5               | 1.3700                  | 37.43 |     | 25.35             | 10.38                 | 47.81 |     | 35.73           | 56.00 | 46.00          | -8.19  | -10.27 | Р       |  |
| 6               | 13.9340                 | 39.08 |     | 25.98             | 10.12                 | 49.20 |     | 36.10           | 60.00 | 50.00          | -10.80 | -13.90 | Р       |  |


Report No.: AGC00610130705FE02 Page 42 of 48


# **APPENDIX A: PHOTOGRAPHS OF TEST SETUP**

FCC LINE CONDUCTED EMISSION TEST SETUP



FCC RADIATED EMISSION TEST SETUP






Page 44 of 48

# **APPENDIX B: PHOTOGRAPHS OF EUT**

TOP VIEW OF EUT



**BOTTOM VIEW OF EUT** 



# FRONT VIEW OF EUT



BACK VIEW OF EUT



LEFT VIEW OF EUT




RIGHT VIEW OF EUT




# **INTERNAL VIEW OF EUT-1**




INTERNAL VIEW OF EUT-2



## **INTERNAL VIEW OF EUT-3**



**INTERNAL VIEW OF EUT-4** 



----END OF REPORT----