





Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.

Mode: EDR
Transfer rate: 3 Mbps(Worst case)
Distance of measurement: 3 meter
Channel: 40
- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 000.10	49.84	Peak	H	-10.42	-	39.42	74.00	34.58
1 000.10	46.20	Peak	V	-10.42	-	35.78	74.00	38.22
1 241.08	46.03	Peak	V	-8.95	-	37.08	74.00	36.92
1 640.04	47.34	Peak	H	-5.96	-	41.38	74.00	32.62



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr


Mode: EDR
Transfer rate: 3 Mbps(Worst case)
Distance of measurement: 3 meter
Channel: 78

- **Spurious**


Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 000.10	50.33	Peak	H	-10.42	-	39.91	74.00	34.09
1 053.89	46.97	Peak	V	-10.09	-	36.88	74.00	37.12
1 640.04	48.52	Peak	H	-5.96	-	42.56	74.00	31.44
2 594.14	45.29	Peak	V	-1.39	-	43.90	74.00	30.10

- **Band edge**

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 483.55	50.22	Peak	V	-1.67	-	48.55	74.00	25.45
2 483.68	52.80	Peak	H	-1.67	-	51.80	74.00	22.20
2 483.76	49.29	Peak	V	-1.67	-	47.62	74.00	26.38
2 483.77	52.97	Peak	H	-1.67	-	51.30	74.00	22.70



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr




Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.

Test results (18 GHz to 30 GHz) – Worst case

Mode:	EDR
Transfer rate:	3 Mbps
Distance of measurement:	3 meter
Channel:	00(Worst case)



Note.

1. No spurious emission were detected above 18 GHz.

3.7. Conducted band edge and out of band emissions

Test procedure

KDB 558074 v05r02 & ANSI 63.10-2013

Test setup




Test setting

1. Span = wide enough to capture the peak level of the in-band emission and all spurious emissions(e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic.
2. RBW = 100 kHz
3. VBW $\geq$ 300 kHz
4. Detector = Peak
5. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize


Limit

According to 15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in section 15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section 15.205(a), must also comply the radiated emission limits specified in section 15.209(a) (see section 15.205(c))


Test results






This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr


EDR(3 Mbps)																																																	
2 480 MHz	-																																																
	BLANK																																																
	BLANK																																																
 <table><thead><tr><th>Marker</th><th>Ref</th><th>Freq</th><th>Value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td>2.4801 GHz</td><td>-9.21 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td>4.961 GHz</td><td>-26.05 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td>3.7193 GHz</td><td>-34.22 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td>7.4394 GHz</td><td>-37.39 dBm</td><td></td><td></td></tr><tr><td>M5</td><td>1</td><td>1.241 GHz</td><td>-36.81 dBm</td><td></td><td></td></tr><tr><td>M6</td><td>1</td><td>8.9203 GHz</td><td>-40.42 dBm</td><td></td><td></td></tr><tr><td>M7</td><td>1</td><td>14.8821 GHz</td><td>-50.92 dBm</td><td></td><td></td></tr></tbody></table>	Marker	Ref	Freq	Value	Function	Function Result	M1	1	2.4801 GHz	-9.21 dBm			M2	1	4.961 GHz	-26.05 dBm			M3	1	3.7193 GHz	-34.22 dBm			M4	1	7.4394 GHz	-37.39 dBm			M5	1	1.241 GHz	-36.81 dBm			M6	1	8.9203 GHz	-40.42 dBm			M7	1	14.8821 GHz	-50.92 dBm			BLANK
Marker	Ref	Freq	Value	Function	Function Result																																												
M1	1	2.4801 GHz	-9.21 dBm																																														
M2	1	4.961 GHz	-26.05 dBm																																														
M3	1	3.7193 GHz	-34.22 dBm																																														
M4	1	7.4394 GHz	-37.39 dBm																																														
M5	1	1.241 GHz	-36.81 dBm																																														
M6	1	8.9203 GHz	-40.42 dBm																																														
M7	1	14.8821 GHz	-50.92 dBm																																														

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr

Hopping mode_BDR(1Mbps)



Hopping mode_EDR(3Mbps)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr

3.8. AC conducted emissions

Limit


According to 15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohm line impedance stabilization network (LISN). Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequencies ranges.

Frequency of Emission (MHz)	Conducted limit (dB μ V/m)	
	Quasi-peak	Average
0.15 – 0.50	66 - 56*	56 - 46*
0.50 – 5.00	56	46
5.00 – 30.0	60	50

Test results

Mode:	BDR
Transfer rate:	1 Mbps
Distance of measurement:	3 meter
Channel:	78(Worst case)


Hot Line



Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.442000	---	10.01	47.02	37.01	1000.0	9.000	L1	19.8
0.442000	23.59	---	57.02	33.43	1000.0	9.000	L1	19.8
0.594000	---	7.84	46.00	38.16	1000.0	9.000	L1	20.0
0.594000	28.81	---	56.00	27.19	1000.0	9.000	L1	20.0
1.514000	---	7.14	46.00	38.86	1000.0	9.000	L1	20.4
1.514000	24.30	---	56.00	31.70	1000.0	9.000	L1	20.4
4.386000	---	17.11	46.00	28.89	1000.0	9.000	L1	20.1
4.386000	19.52	---	56.00	36.48	1000.0	9.000	L1	20.1
17.830000	---	26.43	50.00	23.57	1000.0	9.000	L1	20.7
17.830000	31.56	---	60.00	28.44	1000.0	9.000	L1	20.7
23.210000	---	8.86	50.00	41.14	1000.0	9.000	L1	20.9
23.210000	11.92	---	60.00	48.08	1000.0	9.000	L1	20.9

Neutral Line



Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.554000	24.82	---	56.00	31.18	1000.0	9.000	N	19.9
0.554000	---	9.49	46.00	36.51	1000.0	9.000	N	19.9
0.586000	26.55	---	56.00	29.45	1000.0	9.000	N	19.9
0.586000	---	10.81	46.00	35.19	1000.0	9.000	N	19.9
0.734000	19.71	---	56.00	36.29	1000.0	9.000	N	20.0
0.734000	---	6.91	46.00	39.09	1000.0	9.000	N	20.0
1.614000	---	8.86	46.00	37.14	1000.0	9.000	N	20.4
1.614000	23.02	---	56.00	32.98	1000.0	9.000	N	20.4
2.362000	---	9.90	46.00	36.10	1000.0	9.000	N	20.4
2.362000	24.17	---	56.00	31.83	1000.0	9.000	N	20.4
17.814000	---	10.56	50.00	39.44	1000.0	9.000	N	20.6
17.814000	19.61	---	60.00	40.39	1000.0	9.000	N	20.6

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Appendix A. Measurement equipment

Equipment	Manufacturer	Model	Serial No.	Calibration interval	Calibration due.
Spectrum analyzer	R&S	FSV3044	101272	1 year	2023.03.14
Spectrum analyzer	R&S	FSV40	101725	1 year	2023.06.16
SIGNAL GENERATOR	KEYSIGHT	N5182B	MY59100115	1 year	2023.04.27
SIGNAL GENERATOR	Anritsu	68369B	002118	1 year	2023.05.13
Power Meter	Anritsu	ML2495A	2010001	1 year	2023.04.27
Pulse Power Sensor	Anritsu	MA2411B	1911111	1 year	2023.04.27
Attenuator	Mini-Circuits	BW-S10-2W263+	2	1 year	2023.01.17
Loop Antenna	Schwarzbeck	FMZB1513	225	2 years	2023.01.18
BILOG ANTENNA	Schwarzbeck	VULB 9168	9168-461	2 years	2022.12.22
BAND REJECT FILTER	MICRO-TRONICS	BRM50702	G272	1 year	2023.01.14
Horn Antenna	A.H	SAS-571	414	1 year	2023.01.18
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA 9170550	1 year	2023.01.18
Amplifier	SONOMA INSTRUMENT	310N	401123	1 year	2023.06.02
PREAMPLIFIER	HP	8449B	3008A00538	1 year	2023.06.02
BROADBAND AMPLIFIER	SCHWARZBECK	BBV9721	PS9721-003	1 year	2023.01.17
Attenuator	HUBER+SHHNER	6806.17.A	NONE	1 year	2023.04.01
DC Power supply	Agilent	6632B	MY43004090	1 year	2023.06.21
EMI Test Receiver	R&S	ESU26	100552	1 year	2023.03.31
LISN	ENV216	R & S	101787	1 year	2022.12.27
EMI TEST RECEIVER	ESR3	R & S	101783	1 year	2022.12.28
PULSE LIMITER	ESH3-Z2	R & S	101915	1 year	2022.12.27

Peripheral devices

Device	Manufacturer	Model No.	Serial No.
Notebook computer	HP	TPN-I110	5CG32924MK
Test Jig Board	N/A	N/A	N/A

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr