





BUREAU
VERITAS

Curtis-Straus LLC, a wholly owned subsidiary of BV CPS

Test Report

Report No	EQ1779-1
Client	Ideal Industries, Inc.
Address	Becker Place Sycamore, IL 60178
Phone	(815) 895 - 1295
Items tested	ESCGRID1000 2AAMXESCGRID1000 11250A-ESCGRID1000 0002862225
Equipment Type	Digital Transmission System
Equipment Code	DTS
Emission Designator	795KG1D
FCC/IC Rule Parts	CFR Title 47 FCC Part 15.247, ISED Canada RSS-247 Issue 1
Test Dates	June 20, 23, 30, and July 1, 2016
Results	As detailed within this report
Prepared by	 Christopher Bramley – EMC Engineer
Authorized by	 Yunus Faziloglu – Sr. EMC Engineer
Issue Date	3/20/2017
Conditions of Issue	This Test Report is issued subject to the conditions stated in the 'Conditions of Testing' section on page 28 of this report.

Curtis-Straus LLC is accredited by the American Association for Laboratory Accreditation for the specific scope of accreditation under Certificate Number 1627-01. This report may contain data which is not covered by the A2LA accreditation.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Contents

Contents.....	2
Summary.....	3
Test Methodology.....	4
Product Tested - Configuration Documentation	5
Statement of Conformity.....	6
Test Results	7
<i>Bandwidth</i>	7
Fundamental Emission Output Power	10
<i>Radiated Spurious Emissions</i>	13
<i>Conducted Spurious Emissions</i>	16
Power Spectral Density	20
AC Line Conducted Emissions.....	23
Occupied Bandwidth	24
Measurement Uncertainty	27
Conditions Of Testing	28

Form Final Report REV 7-20-07 (DW)



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828

Summary

This test report supports an application for certification of a transmitter operating pursuant to:
CFR Title 47 FCC Part 15.247, ISED Canada RSS-247 Issue 1

The product is the ESCGRID1000. It is a digitally modulated transmitter that operates in the 902.7-927.3MHz frequency range. Product has an internal PCB trace antenna with 3dBi gain.

We found that the product met the above requirements without modification. The test samples were received in good condition.

Issue No.	Reason for change	Date Issued
1	Original Release	March 20, 2017

page 3 of 29



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Test Methodology

All testing was performed according to the following rules/procedures/documents:
CFR Title 47 FCC Part 15.247, ISED Canada RSS-247 Issue 1, ISED Canada RSS-Gen Issue 4, FCC KDB 558074 D01 DTS Measurement Guidance v03r05 and ANSI C63.10-2013.

Radiated Emissions were maximized by rotating the device around its axes as well as varying the test antenna's height and polarity. AC line conducted emissions testing was performed with a 50Ω/50µH LISN. AC side of the support AC/DC brick to the EUT was tested.

RF measurements were performed at the antenna port on 3 channels as follows:

Low channel = 902.7MHz

Mid channel = 915MHz

High channel = 927.3MHz

The following bandwidths were used during radiated spurious and AC line conducted emissions tests:

Frequency	RBW	VBW
0.15-30MHz	9kHz	30kHz
30-1000MHz	120kHz	1MHz
1-10GHz	1MHz	3MHz



Product Tested - Configuration Documentation

EUT Configuration																	
Work Order:	Q1779																
Company:	Ideal Industries, Inc.																
Company Address:	Becker Place																
	Sycamore, IL 60178																
Contact:	Tim Tunnell																
	MN			PN			SN										
EUT:	ESCGRID1000																
EUT Description:	Smart Connector																
EUT TX Frequency:	902.7-927.3 MHz																
Port Label	Port Type	# ports	# populated	cable type	shielded	ferrites	length (m)	in/out	under test	comment							
24VDC power	DC Power	1	1	Power	No	No	0	In	yes	Direct contact with power rail							
Load	DC Power	1	1	Power	No	No	1	Out	yes								
Software Operating Mode Description:																	
The EUT is clipped on to the power rail that carries 24VDC. EUT provides a DC load output.																	
For testing the EUT was configured to change between 3 channels by power cycling.																	
Low channel: 902.7MHz, Mid Channel: 915MHz, High Channel: 927.3MHz. Direct sequence spread spectrum.																	



Statement of Conformity

RSS-GEN	RSP-100	RSS 247	Part 15	Comments
6.3			15.15(b)	There are no controls accessible to the user that varies the output power to operate in violation of the regulatory requirements.
	3.1		15.19	The label is shown in the label exhibit.
	4		15.21	Information to the user is shown in the instruction manual exhibit.
			15.27	No special accessories are required for compliance.
3, 6.1			15.31	The EUT was tested in accordance with the measurement standards in this section.
6.13			15.33	Frequency range was investigated according to this section, unless noted in specific rule section under which the equipment operates.
8.1			15.35	The EUT emissions were measured using the measurement detector and bandwidth specified in this section, unless noted in specific rule section under which the equipment operates.
8.3			15.203	Product has an internal PCB trace antenna with 3dBi gain.
8.10			15.205 15.209	The fundamental is not in a Restricted band and the spurious and harmonic emissions in the Restricted bands comply with the general emission limits of 15.209 or RSS-Gen as applicable
8.8			15.207	EUT meets the AC Line conducted emissions requirements of this section.
			15.247	The unit complies with the requirements of 15.247
		RSS 247		The unit complies with the requirements of RSS-247
6.6				Occupied Bandwidth measurements were made.



Test Results

Bandwidth

LIMIT

The minimum 6 dB bandwidth shall be at least 500 kHz. [15.247(a) (2)]

MEASUREMENTS / RESULTS

6dB Bandwidth								
Date: 20-Jun-16	Company: Ideal Industries, Inc.		Work Order: Q1779					
Engineer: Yunus Faziloglu	EUT Desc: ESCGRID1000		EUT Operating Voltage/Frequency: 24VDC					
Temp: 24.5°C	Humidity: 44%		Pressure: 1008mBar					
Frequency Range: 902.7MHz - 927.3MHz								
Notes: Per FCC 558074 D01 DTS Meas Guidance v03r05 Section 8.2								
Frequency (MHz)	Measured DTS Bandwidth (kHz)			Minimum Limit (kHz)				
902.7	653.4			500.0				
915.0	653.6			500.0				
927.3	656.1			500.0				

Rev. 6/8/2016

Spectrum Analyzers / Receivers /Preselectors MXE EMI Receiver	Range 20Hz-26.5GHz	MN N9038A	Mfr Agilent	SN MY51210181	Asset 2093	Cat I	Calibration Due 7/21/2016	Calibrated on 7/21/2015
Preamps /Couplers Attenuators / Filters API - 30dB 20W Attenuator	Range 9KHz-40GHz	MN 89-30-11	Mfr API Weinschel	SN 703	Asset 2121	Cat I	Calibration Due 2/10/2017	Calibrated on 2/10/2016
Meteorological Meters Weather Clock (Pressure Only) TH A#2082		MN BA928 HTC-1	Mfr Oregon Scientific HDE	SN C3166-1	Asset 831 2082	Cat I II	Calibration Due 4/28/2017 4/5/2017	Calibrated on 4/28/2016 4/5/2016

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.




Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828




page 7 of 29

Testing Cert. No. 1627-01

PLOT(s)



Low Channel – 6dB Bandwidth




Mid Channel – 6dB Bandwidth



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828





High Channel – 6 dB Bandwidth



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 9 of 29

Fundamental Emission Output Power

LIMIT

Conducted Output Power

1 Watt

[15.247(b) (3)]

MEASUREMENTS / RESULTS

Maximum Conducted Output Power												
Date: 20-Jun-16	Company: Ideal Industries, Inc.				Work Order: Q1779							
Engineer: Yunus Faziloglu	EUT Desc: ESCGRID1000				EUT Operating Voltage/Frequency: 24VDC							
Temp: 24.5°C	Humidity: 44%				Pressure: 1008mBar							
Frequency Range: 902.7MHz - 927.3MHz												
Notes: Per FCC 558074 D01 DTS Meas. Guidance v03r05 Section 9.2.2.2 Method AVGSA-1												
Frequency (MHz)	Reading (dBm)	Attenuator Loss (dB)	Power (dBm)	Limit (dBm)	Margin (dB)	Result						
902.7	-10.74	29.44	18.70	30.00	-1.3	Pass						
915.0	-12.10	29.44	17.34	30.00	-12.66	Pass						
927.3	-13.05	29.44	16.39	30.00	-13.61	Pass						
Power(dBm) = Reading(dBm) + Attenuator Loss(dB)												

Rev. 6/8/2016

Spectrum Analyzers / Receivers / Preselectors	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
MXE EMI Receiver	20Hz-26.5GHz	N9038A	Agilent	MY51210181	2093	I	7/21/2016	7/21/2015
Preamps / Couplers Attenuators / Filters	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
API - 30dB 20W Attenuator	9KHz-40GHz	89-30-11	API Weinschel	703	2121	I	2/10/2017	2/10/2016
Meteorological Meters	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on	
Weather Clock (Pressure Only)	BA928	Oregon Scientific	C3166-1	831	I	4/28/2017	4/28/2016	
TH A#2082	HTC-1	HDE		2082	II	4/5/2017	4/5/2016	

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.




Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828




page 10 of 29

Testing Cert. No. 1627-01

PLOTS



Low Channel – Channel Power




Mid Channel – Channel Power



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828





High Channel – Channel Power



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 12 of 29

Testing Cert. No. 1627-01

Radiated Spurious Emissions

LIMITS

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).
[15.247(d)]

MEASUREMENTS / RESULTS

Radiated Emissions Table

Date: 30-Jun-16		Company: Ideal Industries, Inc.		Work Order: Q1779												
Engineer: Nirak So		EUT Desc: ESCGRID1000		EUT Operating Voltage/Frequency: 24VDC												
Temp: 25°C		Humidity: 40%		Pressure: 1007mBar												
Frequency Range: 30-1000MHz					Measurement Distance: 3 m											
Notes: Low channel and middle channel					EUT Tx Freq: 902.7-927.3MHz											
Antenna Polarization (H / V)	Frequency (MHz)	Reading (dB μ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dB μ V/m)				FCC 15.209						
										Limit (dB μ V/m)	Margin (dB)	Result (Pass/Fail)				
Low Channel 902.7MHz										46.0	-15.0	Pass				
V	546.0	36.6	25.6	18.2	1.8	31.0				46.0	-21.1	Pass				
V	439.0	32.4	25.7	16.7	1.5	24.9				40.0	-10.3	Pass				
V	78.5	46.7	25.5	7.9	0.6	29.7				43.5	-13.1	Pass				
V	163.375	42.8	25.5	12.1	1.0	30.4				46.0	-12.1	Pass				
V	287.0	44.9	25.7	13.4	1.3	33.9				40.0	-10.6	Pass				
V	30.5	33.5	25.5	21.0	0.4	29.4				43.5	-8.8	Pass				
H	110.0	46.9	25.6	12.6	0.8	34.7				46.0	-12.4	Pass				
Mid Channel 915MHz										46.0	-10.5	Pass				
H	546.7	39.2	25.6	18.2	1.8	33.6				43.5	-10.7	Pass				
H	284.0	46.5	25.7	13.4	1.3	35.5				40.0	-13.4	Pass				
H	110.0	45.0	25.6	12.6	0.8	32.8				43.5	-17.4	Pass				
V	78.5	43.6	25.5	7.9	0.6	26.6				46.0	-14.1	Pass				
V	146.4	38.1	25.6	12.6	1.0	26.1				40.0	-12.2	Pass				
V	545.0	37.5	25.6	18.2	1.8	31.9				43.5	-12.2	Pass				
V	30.0	31.5	25.5	21.4	0.4	27.8				40.0	-12.2	Pass				
Table Result: Pass by -8.8 dB										Worst Freq:	110.0 MHz					
Test Site: EMI Chamber 1		Cable 1: Asset #2051		Cable 2: Asset #1784												
Analyzer: Gold		Preamp: Green		Antenna: Red-Brown								Copyright Curtis-Straus LLC 2000				
CSsoft Radiated Emissions Calculator v 1.017.164																
Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor																

Rev. 6/29/2016

Spectrum Analyzers / Receivers /Preselectors	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Gold	100Hz-26.5 GHz	E4407B	Agilent	MY45113816	1284	I	1/13/2017	1/13/2016
Radiated Emissions Sites	FCC Code	IC Code	VCCI Code	Range	Cat	Calibration Due	Calibrated on	
EMI Chamber 1	719150	2762A-6	A-0015	30-1000MHz	II	3/21/2017	3/21/2015	
Preamps /Couplers Attenuators / Filters	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Green	0.009-2000MHz	ZFL-1000-LN	CS	N/A	802	II	9/17/2016	9/17/2015
Antennas	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Red-Brown Biolog	30-2000MHz	JB1	Sunol	A0032406	1218	I	12/4/2016	12/4/2014
Meteorological Meters		MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Weather Clock (Pressure Only)	BA928	Oregon Scientific	C3166-1	831	I		4/28/2018	4/28/2016
TH A#2080	HTC-1	HDE		2080	II		4/5/2017	4/5/2016
Cables	Range	Mfr			Cat	Calibration Due	Calibrated on	
Asset #1784	9kHz - 18GHz	Florida RF			II	3/7/2017	3/7/2016	
Asset #2051	9kHz - 18GHz	Florida RF			II	3/2/2017	3/2/2016	

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Radiated Emissions Table

Date: 23-Jun-16		Company: Powercast Corporation		Work Order: Q1779								
Engineer: Jason Haley		EUT Desc: ESCGRID1000		EUT Operating Voltage/Frequency: 24VDC								
Temp: 22C		Humidity: 37%		Pressure: 1005mbar								
Frequency Range: 30-1000MHz					Measurement Distance: 3m							
Notes: High Channel (927.3MHz)					EUT Max Freq: 927.3MHz							
Antenna Polarization (H/V)	Frequency (MHz)	Reading (dB μ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dB μ V/m)	--			FCC Class B		
							Limit (dB μ V/m)	Margin (dB)	Result (Pass/Fail)	Limit (dB μ V/m)	Margin (dB)	Result (Pass/Fail)
V	74.33	48.2	25.3	9.1	0.6	32.6	---	---	---	40.0	-7.4	Pass
V	112.4	43.3	25.2	13.2	0.8	32.1	---	---	---	43.5	-11.4	Pass
H	112.5	46.3	25.2	13.2	0.8	35.1	---	---	---	43.5	-8.4	Pass
Table Result: Pass		by	-7.4 dB					Worst Freq: 74.33 MHz				
Test Site: EMI Chamber 2		Cable 1: Asset #1507		Cable 2: Asset #2052		Cable 3: ---						
Analyzer: Rental SA#5		Preamp: Blue-Blk		Antenna: Red-Black		Preselector: ---						
CSsoft Radiated Emissions Calculator		v 1.017.164									Copyright Curtis-Straus LLC 2000	
Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor												

Rev. 9/25/2016

Spectrum Analyzers / Receivers/Preselectors		Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
MXE EMI Receiver		20Hz-26.5GHz	N9038A	Agilent	MY51210181	2093	I	8/9/2017	8/9/2016
Antennas	Red-Black BiLog	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
		30-2000MHz	JB1	Sunol	A091604-2	1106	I	2/9/2017	2/9/2015
Radiated Emissions Sites	EMI Chamber 2	FCC Code	719150	IC Code	VCCI Code	Range	Cat	Calibration Due	Calibrated on
				2762A-7	A-0015	1-18GHz	I	4/29/2017	4/29/2015
Preamps /Couplers Attenuators / Filters	Blue-Black	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
		0.009-2000MHz	ZFL-1000-LN	CS	N/A	800	II	12/27/2016	12/27/2015
Cables	Asset #1507	Range	Mfr			Cat	Calibration Due	Calibrated on	
		9kHz - 18GHz	Florida RF			II	2/14/2017	2/14/2016	
	Asset #2052	9kHz - 18GHz	Florida RF			II	3/2/2017	3/2/2016	

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.

Radiated Emissions Table

Date: 23-Jun-16		Company: Ideal Industries, Inc.		Work Order: Q1779										
Engineer: Jason Haley		EUT Desc: ESCGRID1000		EUT Operating Voltage/Frequency: 24VDC										
Temp: 22C		Humidity: 37%		Pressure: 1005mBar										
Frequency Range: 1-6GHz					Measurement Distance: 3m									
Notes: 1854.6MHz, 1805.4MHz and 1830MHz frequencies are not in a restricted band, therefore limit was set to 30dB down from the corresponding fundamental field strength level.					EUT Tx Freq: 902.7-927.3MHz									
Antenna Polarization (H/V)	Frequency (MHz)	Peak Reading (dB μ V)	Average Reading (dB μ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Peak Reading (dB μ V/m)	Adjusted Avg Reading (dB μ V/m)	FCC 15.209 High Frequency - Peak			FCC 15.209 High Frequency - Average		
									Limit (dB μ V/m)	Margin (dB)	Result (Pass/Fail)	Limit (dB μ V/m)	Margin (dB)	Result (Pass/Fail)
Vertical	1854.6	64.8	59.3	18.8	27.4	3.2	76.6	71.1	101.6	-25.0	Pass	81.6	-10.5	Pass
Vertical	2781.9	35.9	24.4	20.1	28.9	3.7	48.4	36.9	74.0	-25.6	Pass	54.0	-17.1	Pass
V, Noise Floor	3709.2	33.9	21.9	19.1	32.1	4.2	51.1	39.1	74.0	-22.9	Pass	54.0	-14.9	Pass
V, Noise Floor	4636.5	34.1	21.3	17.9	32.6	5.2	54.0	41.2	74.0	-20.0	Pass	54.0	-12.8	Pass
V, Noise Floor	5563.8	34.0	21.4	17.6	33.9	5.5	55.8	43.2	74.0	-18.2	Pass	54.0	-10.8	Pass
Horizontal	1854.6	65.6	60.2	18.8	27.4	3.2	77.4	72.0	101.6	-24.2	Pass	81.6	-9.6	Pass
Horizontal	2781.9	39.5	29.3	20.1	28.9	3.7	52.0	41.8	74.0	-22.0	Pass	54.0	-12.2	Pass
H, Noise Floor	3709.2	34.8	21.9	19.1	32.1	4.2	52.0	39.1	74.0	-22.0	Pass	54.0	-14.9	Pass
H, Noise Floor	4636.5	34.5	21.4	17.9	32.6	5.2	54.4	41.3	74.0	-19.6	Pass	54.0	-12.7	Pass
H, Noise Floor	5563.8	34.4	21.5	17.6	33.9	5.5	56.2	43.3	74.0	-17.8	Pass	54.0	-10.7	Pass
Horizontal	1805.4	50.7	46.1	18.8	27.2	3.2	62.3	57.7	103.9	-41.6	Pass	83.9	-26.2	Pass
H, Noise Floor	2708.1	35.2	21.8	20.3	28.8	3.6	47.3	33.9	74.0	-26.7	Pass	54.0	-20.1	Pass
H, Noise Floor	3610.8	34.7	22.1	19.1	31.5	4.5	51.6	39.0	74.0	-22.4	Pass	54.0	-15.0	Pass
H, Noise Floor	4513.5	32.5	21.2	17.9	32.4	5.0	52.0	40.7	74.0	-22.0	Pass	54.0	-13.3	Pass
H, Noise Floor	5416.2	32.2	20.8	17.6	33.9	5.5	54.0	42.6	74.0	-20.0	Pass	54.0	-11.4	Pass
Vertical	1805.4	47.1	40.2	18.8	27.2	3.2	58.7	51.8	103.9	-45.2	Pass	83.9	-32.1	Pass
V, Noise Floor	2708.1	34.2	21.8	20.3	28.8	3.6	46.3	33.9	74.0	-27.7	Pass	54.0	-20.1	Pass
V, Noise Floor	3610.8	34.0	22.0	19.1	31.5	4.5	50.9	38.9	74.0	-23.1	Pass	54.0	-15.1	Pass
V, Noise Floor	4513.5	33.1	21.2	17.9	32.4	5.0	52.6	40.7	74.0	-21.4	Pass	54.0	-13.3	Pass
V, Noise Floor	5416.2	32.9	20.9	17.6	33.9	5.5	54.7	42.7	74.0	-19.3	Pass	54.0	-11.3	Pass
Vertical	1830.0	51.0	45.2	18.8	27.3	3.2	62.7	56.9	103.9	-41.2	Pass	83.9	-27.0	Pass
V, Noise Floor	2745.0	34.8	21.6	20.2	28.8	3.7	47.1	33.9	74.0	-26.9	Pass	54.0	-20.1	Pass
V, Noise Floor	3660.0	33.9	22.0	19.1	31.9	4.3	51.0	39.1	74.0	-23.0	Pass	54.0	-14.9	Pass
V, Noise Floor	4575.0	33.9	21.2	17.9	32.5	5.1	53.6	40.9	74.0	-20.4	Pass	54.0	-13.1	Pass
V, Noise Floor	5490.0	33.5	21.3	17.6	33.9	5.5	55.3	43.1	74.0	-18.7	Pass	54.0	-10.9	Pass
Table Result: Pass		by	9.6 dB					Worst Freq: 1854.6 MHz						
Test Site: EMI Chamber 2		Cable 1: Asset #1507		Cable 2: Asset #2052		Antenna: Orange Horn								
Analyzer: Rental SA#5		Preamp: Asset #1517												
CSsoft Radiated Emissions Calculator		v 1.017.164												
Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor														



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Radiated Emissions Table

Date: 23-Jun-16	Company: Ideal Industries, Inc.	Work Order: Q1779												
Engineer: Jason Haley	EUT Desc: ESCGRID1000	EUT Operating Voltage/Frequency: 24Vdc												
Temp: 22°C	Humidity: 37%	Pressure: 1005mBar												
Frequency Range: 6-10GHz		Measurement Distance: 1m												
Notes:		EUT Tx Freq: 902.7-927.3MHz												
Antenna Polarization (H/V)	Frequency (MHz)	Peak Reading (dB μ V)	Average Reading (dB μ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Peak Reading (dB μ V/m)	Adjusted Avg Reading (dB μ V/m)	FCC 15.209 High Frequency - Peak			FCC 15.209 High Frequency - Average		
									Limit (dB μ V/m)	Margin (dB)	Result (Pass/Fail)	Limit (dB μ V/m)	Margin (dB)	Result (Pass/Fail)
V, Noise floor	6405.0	32.4	20.8	17.3	34.9	6.1	56.1	44.5	83.5	-27.4	Pass	63.5	-19.0	Pass
V, Noise floor	7320.0	32.0	20.7	17.0	37.6	6.7	59.3	48.0	83.5	-24.2	Pass	63.5	-15.5	Pass
V, Noise floor	8235.0	33.1	21.1	17.4	37.5	6.7	59.9	47.9	83.5	-23.6	Pass	63.5	-15.6	Pass
V, Noise floor	9150.0	34.2	21.6	17.2	37.8	7.1	61.9	49.3	83.5	-21.6	Pass	63.5	-14.2	Pass
H, noise floor	6405.0	32.6	20.8	17.3	34.9	6.1	56.3	44.5	83.5	-27.2	Pass	63.5	-19.0	Pass
H, noise floor	7320.0	33.5	20.8	17.0	37.6	6.7	60.8	48.1	83.5	-22.7	Pass	63.5	-15.4	Pass
H, noise floor	8235.0	33.0	21.0	17.4	37.5	6.7	59.8	47.8	83.5	-23.7	Pass	63.5	-15.7	Pass
H, noise floor	9150.0	33.1	21.7	17.2	37.8	7.1	60.8	49.4	83.5	-22.7	Pass	63.5	-14.1	Pass
H, noise floor	6318.9	31.8	20.8	17.2	35.0	6.0	55.6	44.6	83.5	-27.9	Pass	63.5	-18.9	Pass
H, noise floor	7221.6	33.2	21.7	16.6	37.1	6.6	60.3	48.8	83.5	-23.2	Pass	63.5	-14.7	Pass
H, noise floor	8124.3	31.9	21.1	16.9	37.4	6.7	59.1	48.3	83.5	-24.4	Pass	63.5	-15.2	Pass
H, noise floor	9027.0	32.9	21.2	17.2	37.9	7.1	60.7	49.0	83.5	-22.8	Pass	63.5	-14.5	Pass
V, Noise floor	6318.9	31.8	20.8	17.2	35.0	6.0	55.6	44.6	83.5	-27.9	Pass	63.5	-18.9	Pass
Vertical	7221.6	34.6	25.0	16.6	37.1	6.6	61.7	52.1	83.5	-21.8	Pass	63.5	-11.4	Pass
V, Noise floor	8124.3	33.4	21.2	16.9	37.4	6.7	60.6	48.4	83.5	-22.9	Pass	63.5	-15.1	Pass
V, Noise floor	9027.0	32.4	21.2	17.2	37.9	7.1	60.2	49.0	83.5	-23.3	Pass	63.5	-14.5	Pass
V, Noise floor	6491.1	31.7	21.0	17.4	34.9	6.2	55.4	44.7	83.5	-28.1	Pass	63.5	-18.8	Pass
Vertical	7418.4	36.2	28.8	17.2	37.5	6.7	63.2	55.8	83.5	-20.3	Pass	63.5	-7.7	Pass
V, Noise floor	8345.7	32.1	20.9	17.5	37.7	6.7	59.0	47.8	83.5	-24.5	Pass	63.5	-15.7	Pass
V, Noise floor	9273.0	33.3	21.1	17.3	37.9	7.1	61.0	48.8	83.5	-22.5	Pass	63.5	-14.7	Pass
H, noise floor	6491.1	32.3	20.9	17.4	34.9	6.2	56.0	44.6	83.5	-27.5	Pass	63.5	-18.9	Pass
H, noise floor	7418.4	33.1	21.0	17.2	37.5	6.7	60.1	48.0	83.5	-23.4	Pass	63.5	-15.5	Pass
H, noise floor	8345.7	31.4	20.9	17.5	37.7	6.7	58.3	47.8	83.5	-25.2	Pass	63.5	-15.7	Pass
H, noise floor	9273.0	32.6	21.1	17.3	37.9	7.1	60.3	48.8	83.5	-23.2	Pass	63.5	-14.7	Pass

Table Result:

Pass by -7.7 dB

Worst Freq: 7418.4 MHz

Test Site: EMI Chamber 2

Analyzer: Rental SA#5

Cable 1: Asset #1507

Preamp: Asset #1517

CSsoft Radiated Emissions Calculator v1.017.164

Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor

Cable 2: Asset #2052

Antenna: Orange Horn

Copyright Curtis-Straus LLC 2000

Rev. 9/25/2016

Spectrum Analyzers / Receivers /Preselectors MXE EMI Receiver	Range 20Hz-26.5GHz	MN N9038A	Mfr Agilent	SN MY5120181	Asset 2093	Cat I	Calibration Due 8/9/2017	Calibrated on 8/9/2016
Radiated Emissions Sites EMI Chamber 2	FCC Code 719150	IC Code 2762A-7	VCCI Code A-0015	Range 30-1000MHz		Cat II	Calibration Due 3/22/2017	Calibrated on 3/22/2015
Preamps/Couplers Attenuators / Filters 1517 HF Preamp	Range 1-20GHz	MN CS	Mfr CS	SN N/A	Asset 1517	Cat II	Calibration Due 8/14/2017	Calibrated on 8/14/2016
Antennas Orange Horn	Range 1-18GHz	MN 3115	Mfr EMCO	SN 0004-6123	Asset 390	Cat I	Calibration Due 10/13/2016	Calibrated on 10/13/2014
Meteorological Meters Weather Clock (Pressure Only) TH A#2081	MN BA928 HTC-1	Mfr Oregon Scientific HDE	SN C3166-1	Asset 831 2081	Cat I II	Calibration Due 4/28/2018 4/5/2017	Calibrated on 4/28/2016 4/5/2016	
Cables Asset #1507 Asset #2052	Range 9kHz - 18GHz 9kHz - 18GHz	Mfr Florida RF Florida RF			Cat II II	Calibration Due 2/14/2017 3/2/2017	Calibrated on 2/14/2016 3/2/2016	

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 15 of 29

Conducted Spurious Emissions

LIMITS

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth that contains the highest level of desired power based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB ...


[15.247(d)]

MEASUREMENTS / RESULTS

Engineer	Yunus Faziloglu
Date	June 20, 2016
Site	Wireless Test Room
Environmental Conditions	24.5°C, 44%, 1008mBar

Conducted Band Edge

Plot(s)



Lowest Channel Bandedge




Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 16 of 29

ACREDITED
Testing Cert. No. 1627-01



Highest Channel Bandedge

Rev. 6/8/2016

Spectrum Analyzers / Receivers/Preselectors		Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
MXE EMI Receiver		20Hz-26.5GHz	N9038A	Agilent	MY51210181	2093	I	7/21/2016	7/21/2015
Preamps/Couplers Attenuators / Filters		Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
API - 30dB 20W Attenuator		9KHz-40GHz	89-30-11	PI Weinschke	703	2121	I	2/10/2017	2/10/2016

Meteorological Meters		MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Weather Clock (Pressure Only)		BA928	Regon Scienti	C3166-1	831	I	4/28/2017	4/28/2016
TH A#2082		HTC-1	HDE		2082	II	4/5/2017	4/5/2016

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.




Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
 One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828




page 17 of 29

Testing Cert. No. 1627-01

Conducted Spurious Emission



Conducted Spurious – Low



Conducted Spurious – Mid




Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 18 of 29

ACREDITED
Testing Cert. No. 1627-01



Conducted Spurious - High

Conducted spurious emissions within 9kHz-10GHz frequency range were measured at the antenna port on 3 channels. No emissions observed within 30dB of the fundamental.

Rev. 6/8/2016

Spectrum Analyzers / Receivers /Preselectors	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
MXE EMI Receiver	20Hz-26.5GHz	N9038A	Agilent	MY51210181	2093	I	7/21/2016	7/21/2015
Preamps /Couplers Attenuators / Filters	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
API - 30dB 20W Attenuator	9KHz-40GHz	89-30-11	PI Weinsche	703	2121	I	2/10/2017	2/10/2016

Meteorological Meters	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Weather Clock (Pressure Only)	BA928	Regon Scienti	C3166-1	831	I	4/28/2017	4/28/2016
TH A#2082	HTC-1	HDE		2082	II	4/5/2017	4/5/2016

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 19 of 29

Testing Cert. No. 1627-01

Power Spectral Density

LIMIT

*...the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.
[15.247(e)]*

MEASUREMENTS / RESULTS

Power Spectral Density (Conducted)												
Date: 20-Jun-16	Company: Ideal Industries, Inc.				Work Order: Q1779							
Engineer: Yunus Faziloglu	EUT Desc: ESCGRID1000				EUT Operating Voltage/Frequency: 24VDC							
Temp: 24.5°C	Humidity: 44%				Pressure: 1008mBar							
Frequency Range: 902.7MHz - 927.3MHz												
Notes: Per FCC 558074 D01 DTS Meas Guidance v03r05 Section 10.3 Method AVGPSD-1												
Frequency (MHz)	Reading (dBm)	Attenuator Loss (dB)	PSD (dBm)	Limit (dBm)	Margin (dB)	Result						
902.7	-22.499	29.44	6.941	8.00	-1.059	Pass						
915.0	-23.503	29.44	5.937	8.00	-2.063	Pass						
927.3	-24.224	29.44	5.216	8.00	-2.784	Pass						
PSD(dBm) = Reading(dBm) + Attenuator Loss(dB)												

Rev. 6/8/2016

Spectrum Analyzers / Receivers /Preselectors	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
MXE EMI Receiver	20Hz-26.5GHz	N9038A	Agilent	MY51210181	2093	I	7/21/2016	7/21/2015
Preamps /Couplers Attenuators / Filters	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
API - 30dB 20W Attenuator	9KHz-40GHz	89-30-11	API Weinschel	703	2121	I	2/10/2017	2/10/2016
Meteorological Meters	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on	
Weather Clock (Pressure Only)	BA928	Oregon Scientific	C3166-1	831	I	4/28/2017	4/28/2016	
TH A#2082	HTC-1	HDE		2082	II	4/5/2017	4/5/2016	

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.




Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828




page 20 of 29

Testing Cert. No. 1627-01

PLOTS




Channel Low – PSD



Channel Mid – PSD





Channel High – PSD



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



AC Line Conducted Emissions

LIMITS

Frequency of emission (MHz)	Quasi-peak limit (dB μ V)	Average limit (dB μ V)
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

[47 CFR 15.207(a)]

MEASUREMENTS / RESULTS

AC side of DC Power Supply -- Conducted Emissions Data Table																
Date: 01-Jul-16 Engineer: Fatou Faye Temp: 24.1 °C		Company: Ideal Industries, Inc. EUT Desc: ESCGRID1000 Humidity: 46%			Work Order: Q1779 Pressure: 1007 mBar											
Notes: Tested the AC side of 24VDC power supply																
Frequency Range: 0.15-30MHz			EUT Input Voltage/Frequency: 120Vac/60Hz													
Frequency (MHz)	Quasi-Peak Readings	Average Readings	LISN Factors	Cable Factor	ATTN Factor	FCC 15.207		FCC 15.207								
	QP1 (dB μ V)	QP2 (dB μ V)	AVG1 (dB μ V)	AVG2 (dB μ V)	L1 (dB)	L2 (dB)	(dB)	QP Limit (dB μ V)	Margin (dB)	Result (Pass/Fail)						
0.15	26.1	25.9	15.9	16.7	-0.1	-0.1	-0.1	66.0	-19.3	Pass						
0.19	21.5	20.6	14.9	15.7	-0.1	-0.1	-0.1	64.2	-22.1	Pass						
0.31	20.4	20.9	17.8	18.2	0.0	-0.1	-0.1	60.0	-18.6	Pass						
0.44	11.9	11.6	7.9	7.5	0.0	0.0	-0.1	57.0	-24.6	Pass						
0.76	11.3	11.1	6.9	6.9	0.0	0.0	-0.1	56.0	-24.1	Pass						
1.05	10.4	10.1	6.3	5.6	0.0	0.0	-0.1	56.0	-25.1	Pass						

Result: Pass

Worst Margin: -11.3 dB

Frequency: 0.308 MHz

Measurement Device: LISN ASSET 1727(Line 1) LISN ASSET 1726(Line 2)

Cable: CEMI-02

Spectrum Analyzer: 1327

Attenuator: 20dB Attenuator-64

Site: CEMI 1

Equipment Factor Sheet rev: 5/11/2016

C-S CEMI Calculator Version 3.0.14

Adjusted Reading = Raw Reading + LISN Insertion Loss + Cable Loss + Attenuation

Rev. 9/25/2016										
Spectrum Analyzers / Receivers / Preselectors			Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
SA EMI Chamber (1327)		9kHz-13.2 GHz	E4405B	Agilent	MY45103416	1327	I	8/4/2017	8/4/2016	
LISNs/Measurement Probes	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on		
LISN Asset 1726	150kHz-30MHz	LI-150A	Com-Power	201092	1726	I	2/4/2017	2/4/2016		
LISN Asset 1727	150kHz-30MHz	LI-150A	Com-Power	201093	1727	I	2/4/2017	2/4/2016		
Conducted Test Sites (Mains / Telco)	FCC Code	VCCI Code			Cat	Calibration Due	Calibrated on			
CEMI 1	719150	A-0015			III	NA	N/A			
Meteorological Meters	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on		
Weather Clock (Pressure Only) TH A#2084	9kHz-13.2 GHz	BA928 HTC-1	Oregon Scientific HDE	C3166-1	831 2084	I II	4/28/2018 4/5/2017	4/28/2016 4/5/2016		
Cables	Range	Mfr			Cat	Calibration Due	Calibrated on			
CEMI-02	9kHz - 2GHz	C-S			II	4/10/2017	4/10/2016			
Attenuators	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on		
20dB Attenuator-64	9kHz-2GHz	N/A			II	11/15/2016	11/15/2015			

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 23 of 29



Testing Cert. No. 1627-01

Occupied Bandwidth

REQUIREMENT

When an occupied bandwidth is not specified in the applicable RSS, the transmitted signal bandwidth to be reported is its 99% emission bandwidth, as calculated or measured.
[RSS-GEN 6.6]

MEASUREMENTS / RESULTS

99% Occupied Bandwidth										
Date: 20-Jun-16	Company: Ideal Industries, Inc.		Work Order: Q1779							
Engineer: Yunus Faziloglu	EUT Desc: ESCGRID1000		EUT Operating Voltage/Frequency: 24VDC							
Temp: 24.5°C	Humidity: 44%		Pressure: 1008mBar							
Frequency Range: 902.7MHz - 927.3MHz										
Notes: Per RSS-Gen Section 6.6										
Frequency (MHz)	Occupied Bandwidth (kHz)									
902.7	789.09									
915.0	779.40									
927.3	794.78									

Rev. 6/8/2016

Spectrum Analyzers / Receivers /Preselectors	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
MXE EMI Receiver	20Hz-26.5GHz	N9038A	Agilent	MY51210181	2093	I	7/21/2016	7/21/2015
Preamps /Couplers Attenuators / Filters	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
API - 30dB 20W Attenuator	9KHz-40GHz	89-30-11	PI Weinschre	703	2121	I	2/10/2017	2/10/2016

Meteorological Meters	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Weather Clock (Pressure Only) TH A#2082	BA928 HTC-1	Egon Scienti HDE	C3166-1	831 2082	I II	4/28/2017 4/5/2017	4/28/2016 4/5/2016

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.




Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828




page 24 of 29

Testing Cert. No. 1627-01

Plot(s)



Low Channel – Occupied Bandwidth




Mid Channel – Occupied Bandwidth



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 25 of 29



High Channel – Occupied Bandwidth



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 26 of 29

Measurement Uncertainty

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

Measurement	Expanded Uncertainty k=2	Maximum allowable uncertainty
Radiated Emissions (30-1000MHz) NIST CISPR	5.6dB 4.6dB	N/A 5.2dB (Ucispr)
Radiated Emissions (1-26.5GHz)	4.6dB	N/A
Radiated Emissions (above 26.5GHz)	4.9dB	N/A
Magnetic Radiated Emissions	5.6dB	N/A
Conducted Emissions NIST CISPR	3.9dB 3.6dB	N/A 3.6dB (Ucispr)
Telco Conducted Emissions (Current)	2.9dB	N/A
Telco Conducted Emissions (Voltage)	4.4dB	N/A
Electrostatic Discharge	11.5%	N/A
Radiated RF Immunity (Uniform Field)	1.6dB	N/A
Electrical Fast Transients	23.1%	N/A
Surge	23.1%	N/A
Conducted RF Immunity	3dB	N/A
Magnetic Immunity	12.8%	N/A
Dips and Interrupts	2.3V	N/A
Harmonics	3.5%	N/A
Flicker	3.5%	N/A
Radio frequency (@ 2.4GHz)	3.23×10^{-8}	1×10^{-7}
RF power, conducted	0.40dB	0.75dB
Maximum frequency deviation:		
• Within 300Hz and 6kHz of audio frequency / Within 6kHz and 25kHz of audio frequency	3.4% 0.3dB	5% 3dB
Adjacent channel power	1.9dB	3dB
Conducted spurious emission of transmitter, valid up to 12.75GHz	2.39dB	3dB
Conducted emission of receivers	1.3dB	3dB
Radiated emission of transmitter, valid up to 26.5GHz	3.9dB	6dB
Radiated emission of transmitter, valid up to 80GHz	3.3dB	6dB
Radiated emission of receiver, valid up to 26.5GHz	3.9dB	6dB
Radiated emission of receiver, valid up to 80GHz	3.3dB	6dB
Humidity	2.37%	5%
Temperature	0.7°C	1.0°C
Time	4.1%	10%
RF Power Density, Conducted	0.4dB	3dB
DC and low frequency voltages	1.3%	3%
Voltage (AC, <10kHz)	1.3%	2%
Voltage (DC)	0.62%	1%
The above reflects a 95% confidence level		



Conditions Of Testing

[Bureau Veritas Consumer Products Services, Inc., a Massachusetts corporation], and/or its affiliates (collectively, the "Company") will conduct, at the request of the Submitter ("Client"), the tests specified on the submitted Test Request Form or equivalent in accordance with, and subject to, the following terms and conditions (collectively, "Conditions"):

1. All orders for tests are subject to acceptance by the Company, and no order will constitute a binding commitment of the Company unless and until such order is accepted by it, as evidenced by the issuance of a written report ("Test Report") by the Company. The Test Report is issued solely by the Company, is intended for the exclusive use of Client and shall not be published, used for advertising purposes, copied or replicated for distribution to any other person or entity or otherwise publicly disclosed without the prior written consent of the Company. By submitting a request for services to the Company, Client consents to the disclosure to accreditation bodies of those records of Client relevant to the accreditation body's assessment of the Company's competence and compliance with relevant accreditation criteria. The Company shall not be liable for any loss or damage whatsoever resulting from the failure of the Company to provide its services within any time period for completion estimated by the Company. If Client anticipates using the Test Report in any legal proceeding, arbitration, dispute resolution forum or other proceeding, it shall so notify the Company prior to submitting the Test Report in such proceeding. The Company has no obligation to provide a fact or expert witness at such proceeding unless the Company agrees in advance to do so for a separate and additional fee.
2. The Test Report will set forth the findings of the Company solely with respect to the test samples identified therein. Unless specifically and expressly indicated in the Test Report, the results set forth in such Test Report are not intended to be indicative or representative of the quality or characteristics of the lot from which a test sample is taken, and Client shall not rely upon the Test Report as being so indicative or representative of the lot or of the tested product in general. The Test Report will reflect the findings of the Company at the time of testing only, and the Company shall have no obligation to update the Test Report after its issuance. The Test Report will set forth the results of the tests performed by the Company based upon the written information provided to the Company. The Test Report will be based solely on the samples and written information submitted to the Company by Client, and the Company shall not be obligated to conduct any independent investigation or inquiry with respect thereto.
3. The Company may, in its sole discretion, destroy samples which have been furnished to the Company for testing and which have not been destroyed in the course of testing. The Company may delegate the performance of all or a portion of the services contemplated hereunder to an affiliate, agent or subcontractor of the Company, and Client consents to such delegation.
4. These Conditions and the Test Report represent the entire understanding of the parties hereto with respect to the subject matter hereof and of the Test Report, and no modification, variance or extrapolation with respect thereto shall be permitted without the prior written consent of the Company.
5. The names, service marks, trademarks and copyrights of the Company and its affiliates, including the names "**BUREAU VERITAS**," "**BUREAU VERITAS CONSUMER PRODUCTS SERVICES**," "**BVCPs**," "**MTL**," "**ACTS**," "**MTL-ACTS**" and **CURTIS-STRAUS** (collectively, the "Marks") are and shall remain the sole property of the Company or its affiliates and shall not be used by Client except solely to the extent that Client obtains the prior written approval of the Company and then only in the manner prescribed by the Company. Client shall not contest the validity of the Marks or take any action that might impair the value or goodwill associated with the Marks or the image or reputation of the Company or its affiliates.
6. Payment in full shall be due 30 days after the date of invoice. Interest shall be due on overdue amounts from the due date until paid at an interest rate of 1.5% per month or, if less, the maximum rate permitted by law. The Company reserves the right, at any time and from time to time, to revoke any credit extended to Client. Client shall reimburse the Company for any costs it incurs in collecting past due amounts, including court costs and fees and expenses of attorneys and collection agencies. The Test Report may not be used or relied upon by Client if and for so long as Client fails to pay when due any invoice issued by the Company or any affiliate of it to Client or any affiliate or subsidiary of Client together with interest and penalties, if any, accrued thereon.
7. The Company disclaims any and all responsibility or liability arising out of or in connection with e-mail transmissions of such information.
8. Client understands and agrees that the Company is neither an insurer nor a guarantor, that the Company does not take the place of Client or any designer, manufacturer, agent, buyer, distributor or transportation or shipping company, and that the Company disclaims all liability in such capacities. Client further understands that if it seeks assurance against loss or damage, it should obtain appropriate insurance.
9. Client agrees that the Company, by providing the services, does not take the place of Client nor any third party, nor does the Company release them from any of their obligations, nor does the Company otherwise assume, abridge, abrogate or undertake to discharge any duty of any third party to Client or any duty of Client or any third party to any other third party, and Client will not release any third party from its obligations and duties with respect to the tested goods.
10. Client shall, on a timely basis, (a) provide adequate instructions to the Company in order to enable the Company to perform properly its services, (b) provide, or cause Client's suppliers and contractors to provide, the Company with all documents necessary to enable the Company to perform its services, (c) furnish the Company with all relevant information regarding Client's intended use and purposes of the tested goods, (d) advise the Company of essential dates and deadlines relevant to the tested goods and (e) fully exercise all rights and remedies available to Client against third parties in respect of the tested goods.
11. The Company shall undertake due care and ordinary skill in the performance of its services to Client, and the Company shall accept responsibility only were such skill has not been exercised and, even in such event, only to the extent of the limitation of liability set forth herein.
12. If Client desires to assert a claim arising from or relating to (i) the performance, purported performance or non-performance of any services by the Company or (ii) the sale, resale, manufacture, distribution or use of any tested goods, it must submit that claim to the Company in a writing that sets forth with particularity the basis for such claim within 60 days from discovery of the potential claim and not more than six months after the date of issuance of the Test Report to Client. Client waives any and all such claims including, without limitation, claims that the Test Report is inaccurate, incomplete or misleading or that additional or different testing is required, unless and then only to the extent that Client submits a written claim to the Company within both such time periods.
13. CLIENT SHALL, EXCEPT TO THE EXTENT OF COMPANY'S LIABILITY TO CLIENT HEREUNDER (WHICH IN NO EVENT SHALL EXCEED THE LIMITATION OF LIABILITY HEREIN), HOLD HARMLESS AND INDEMNIFY THE COMPANY, ITS AFFILIATES AND THEIR RESPECTIVE DIRECTORS, OFFICERS, EMPLOYEES, AGENTS AND SUBCONTRACTORS AGAINST ALL ACTUAL OR ALLEGED THIRD PARTY CLAIMS FOR LOSS, DAMAGE OR EXPENSE OF WHATSOEVER NATURE AND HOWSOEVER ARISING FROM OR RELATING TO (i) THE PERFORMANCE, PURPORTED PERFORMANCE OR NON-PERFORMANCE OF ANY SERVICES BY THE COMPANY OR (ii) THE SALE, RESALE, MANUFACTURE, DISTRIBUTION OR USE OF ANY TESTED GOODS.
14. EXCEPT AS MAY OTHERWISE BE EXPRESSLY AGREED TO IN WRITING BY THE COMPANY AND NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN OR IN ANY TEST REPORT, NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR USE, IS MADE.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 28 of 29

Testing Cert. No. 1627-01

15. (A) IN NO EVENT WHATSOEVER SHALL THE COMPANY BE LIABLE FOR ANY CONSEQUENTIAL, SPECIAL, INCIDENTAL, EXEMPLARY OR PUNITIVE DAMAGES IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE TEST REPORT OR THE SERVICES PROVIDED BY THE COMPANY HEREUNDER, INCLUDING WITHOUT LIMITATION LOSS OF OR DAMAGE TO PROPERTY; LOSS OF INCOME, PROFIT OR USE; OR ANY CLAIMS OR DEMANDS MADE AGAINST CLIENT OR ANY OTHER PERSON BY ANY THIRD PARTY IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE SERVICES PROVIDED BY THE COMPANY HEREUNDER.

(B) NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN, AND IN RECOGNITION OF THE RELATIVE RISKS AND BENEFITS TO CLIENT AND THE COMPANY ASSOCIATED WITH THE TESTING SERVICES CONTEMPLATED HEREBY, THE RISKS HAVE BEEN ALLOCATED SUCH THAT UNDER NO CIRCUMSTANCES WHATSOEVER SHALL THE LIABILITY OF THE COMPANY TO CLIENT OR ANY THIRD PARTY IN RESPECT OF ANY CLAIM FOR LOSS, DAMAGE OR EXPENSE, OF WHATSOEVER NATURE OR MAGNITUDE, AND HOWSOEVER ARISING, EXCEED AN AMOUNT EQUAL TO FIVE (5) TIMES THE AMOUNT OF THE FEES PAID TO THE COMPANY FOR THE SPECIFIC SERVICES WHICH GAVE RISE TO SUCH CLAIM OR U.S.\$10,000, WHICHEVER IS THE LESSER AMOUNT.

16. The Company shall not be liable for any loss or damage resulting from any delay or failure in performance of its obligations hereunder resulting directly or indirectly from any event of force majeure or any event outside the control of the Company. If any such event occurs, the Company may immediately cancel or suspend its performance hereunder without incurring any liability whatsoever to Client.

17. Company's services, including these Conditions, shall be governed by, and construed in accordance with, the local laws of the country where the Company performs the tests or, in the case of tests performed in the United States of America, the laws of Massachusetts without regard to conflicts of laws principles. If any aspect(s) of these Conditions is found to be illegal or unenforceable, the validity, legality and enforceability of all remaining aspects of these Conditions shall not in any way be affected or impaired thereby. Any proceeding related to the subject matter hereof shall be brought, if at all, in the courts of the country where the Company performs the tests or, in the case of tests performed in the United States of America, in the courts of Massachusetts. Client waives the right to interpose any counterclaim or setoffs of any nature in any litigation arising hereunder.

The complete list of the Approved Subcontractors Curtis-Straus may use to delegate the performance of work can be provided upon request. Rev.160009121(2)_#684340 v14CS



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 29 of 29