



BUREAU
VERITAS

Curtis-Straus LLC, a wholly owned subsidiary of BV CPS

Test Report

Report No	ET0476-1
Client	Ideal Industries, Inc.
Address	Becker Place Sycamore, IL 60178
Phone	815-895-1295
Items tested	TS1200
FCC ID	2AAMXTS1200
IC	11250A-TS1200
FRN	0002862225
Equipment Type	Digital Transmission System
Equipment Code	DTS
FCC/IC Rule Parts	CFR Title 47 FCC Part 15.247, ISED Canada RSS-247 Issue 2
Test Dates	February 21 to March 1, 2019
Results	As detailed within this report
Prepared by	 Arik Zwirner – Test Engineer
Authorized by	 Yunus Faziloglu – Sr. Engineer
Issue Date	5/7/2019
Conditions of Issue	This Test Report is issued subject to the conditions stated in the 'Conditions of Testing' section on page 39 of this report.

Curtis-Straus LLC is accredited by the American Association for Laboratory Accreditation for the specific scope of accreditation under Certificate Number 1627-01. This report may contain data which is not covered by the A2LA accreditation.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Contents

Contents.....	2
Summary.....	3
Test Methodology.....	4
Product Tested - Configuration Documentation	5
Statement of Conformity.....	6
Modifications Required for Compliance	6
Test Results	7
<i>DTS (6dB) Bandwidth</i>	7
<i>Output Power</i>	11
<i>Band Edge (Conducted)</i>	15
<i>Radiated Spurious Emissions</i>	18
<i>Conducted Spurious Emissions</i>	26
<i>Power Spectral Density</i>	30
<i>Occupied Bandwidth</i>	34
Measurement Uncertainty.....	38
Conditions Of Testing	39

Form Final Report REV 7-20-07 (DW)



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828

Summary

This test report supports an application for certification of a transmitter operating pursuant to:
CFR Title 47 FCC Part 15.247, ISED Canada RSS-247 Issue 2.

The product is the TS1200. It is a digitally modulated transmitter that operates in the 902.7 – 927.3MHz frequency range.

Antenna: Non-detachable PCB antenna with 2.5dBi gain.

The product is battery powered. Fresh batteries were used for all testing. AC mains conducted emissions tests do not apply.

We found that the product met the above requirements without modification. Test samples were received in good condition.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828

page 3 of 40



Test Methodology

All testing was performed according to the following rules/procedures/documents; CFR Title 47 FCC Part 15.247, ISED Canada RSS-247 Issue 2, ISED Canada RSS-Gen Issue 5, FCC KDB 558074 D01 15.247 Measurement Guidance v05r01 and ANSI C63.10-2013.

Radiated emissions were maximized by rotating the device around three orthogonal planes (X, Y and Z) as well as varying the test antenna's height and polarity. Y orientation was found to be the worst and all radiated emissions tests were performed in this orientation. AC line conducted emissions testing was not applicable since device is battery-only powered.

RF measurements were performed at the antenna port on 3 channels as follows:

Low channel = 902.7MHz

Mid channel = 915MHz

High channel = 927.3MHz

Following bandwidths were used during radiated spurious emissions tests:

Frequency	RBW	VBW
30-1000MHz	120kHz	1MHz
1-10GHz	1MHz	3MHz



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Product Tested - Configuration Documentation

EUT Configuration			
Work Order:	T0476		
Company:	Ideal Industries Inc.		
Company Address:	1375 Park Ave		
	Sycamore, IL, 60178		
Contact:	Tim Tunnell		
	MN	PN	SN
EUT:	TS1200		1, 2 (conducted)
EUT Description:	Audacy Temperature Sensor		
EUT Max Frequency:	927.3 MHz		
EUT Components	MN		SN
Conducted sample	TS1200		2
Radiated Sample	TS1200		1
Software Operating Mode Description:			
Client supplied constant TX test mode. on low, mid and high channels.			



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 5 of 40

Statement of Conformity

RSS-GEN	RSP-100	RSS 247	Part 15	Comments
6.4			15.15(b)	There are no controls accessible to the user that varies the output power to operate in violation of the regulatory requirements.
	3.1		15.19	The label is shown in the label exhibit.
	3.2		15.21	Information to the user is shown in the instruction manual exhibit.
			15.27	No special accessories are required for compliance.
3.2			15.31	The EUT was tested in accordance with the measurement standards in this section.
6.13.2			15.33	Frequency range was investigated according to this section, unless noted in specific rule section under which the equipment operates.
6.13.1			15.35	The EUT emissions were measured using the measurement detector and bandwidth specified in this section, unless noted in specific rule section under which the equipment operates.
6.8			15.203	The antenna for this device is non-detachable PCB antenna with 2.5dBi gain
8.10			15.205 15.209	The fundamental is not in a Restricted band and the spurious and harmonic emissions in the Restricted bands comply with the general emission limits of 15.209 or RSS-Gen as applicable
8.8			15.207	EUT is not connected to AC mains. Battery powered only.
			15.247	The unit complies with the requirements of 15.247
		RSS 247		The unit complies with the requirements of RSS-247
6.7				Occupied Bandwidth measurements were made.

Modifications Required for Compliance

None.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828

page 6 of 40



Test Results

DTS (6dB) Bandwidth

LIMIT

The minimum 6 dB bandwidth shall be at least 500 kHz. [15.247(a) (2)]

MEASUREMENTS / RESULTS

6dB Bandwidth								
Date: 3/1/2019	Company: Ideal Industries		Work Order: T0476					
Engineer: AKZ			Operating Voltage/Frequency: Battery					
Temp: 19°C	Humidity: 28%	Pressure: 1021mBar						
Frequency Range: 902-928 MHz Measurement Type: Conducted Measurement Method: FCC KDB 558074 D01 Meas Guidance V05								
Notes:								
Frequency (MHz)	Reading (kHz)			6dB Bandwidth				
	902.7	915.0	927.3	Limit (kHz)	Margin (kHz)			
	661.9	662.0	661.1	≥500	161.9			
				≥500	162.0			
				≥500	161.1			
Test Site: CEMI-2	Cable: none		Attenuator: Asset #2121					
Analyzer: 1118472								

Rev. 2/25/2019

Spectrum Analyzers / Receivers /Preselectors Rental EXA Signal Analyzer(1118472)	Range 9KHz-26.5GHz	MN N9010A-526;K	Mfr AT	SN MY51170010	Asset 1118472	Cat I	Calibration Due 8/10/2019	Calibrated on 8/10/2018
Preamps/Couplers Attenuators / Filters API - 30dB 20W Attenuator	Range 9KHz-40GHz	MN 89-30-11	Mfr API Weinschel	SN 703	Asset 2121	Cat I	Calibration Due 3/23/2019	Calibrated on 3/23/2018
Meteorological Meters/Chambers Weather Clock (Pressure Only) TH A#2081	MN BA928 HTC-1	Mfr Oregon Scientific HDE	SN C3166-1	Asset 831 2081	Cat I II	Calibration Due 5/15/2020 3/23/2019	Calibrated on 5/15/2018 3/23/2018	

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.




Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 7 of 40

Testing Cert. No. 1627-01

PLOT(s)


6dB Bandwidth – Low Channel



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 8 of 40




6dB Bandwidth – Mid Channel



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 9 of 40



6dB Bandwidth – High Channel



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 10 of 40

Output Power**LIMIT**

Conducted Output Power

1 Watt

[15.247(b) (3)]

Per ANSI C63.10 – 2013 Section 11.9.2.2.2 Method AVGSA-1

MEASUREMENTS / RESULTS

Peak Output Power													
Date: 3/1/2019	Company: Ideal Industries				Work Order: T0476								
Engineer: AKZ					Operating Voltage/Frequency: Battery								
Temp: 19°C	Humidity: 28%				Pressure: 1021mBar								
Frequency Range: 902-928 MHz		Measurement Type: Conducted											
Notes:													
Frequency (MHz)	Peak Reading (dBm)	Cable Loss (dB)	Attenuator Loss (dB)	Peak Output Power (dBm)	Limit (dBm)	Margin (dB)	Result (Pass/Fail)						
902.7	-26.43	0.00	29.35	2.92	30.0	-27.08	Pass						
915.0	-27.45	0.00	29.35	1.90	30.0	-28.10	Pass						
927.3	-28.51	0.00	29.35	0.84	30.0	-29.16	Pass						
Test Site: CEMI-2		Cable: none				Attenuator: Asset #2121							
Analyzer: 1118472													
Peak Output Power (dBm)= Peak Reading (dBm) + Cable Loss (dB) + Attenuator Loss (dB)													

Rev. 2/25/2019

Spectrum Analyzers / Receivers/Preselectors	Range	MN	Mfr	SN	Asset	Calibration Due	Calibrated on
Rental EXA Signal Analyzer(1118472)	9KHz-26.5GHz	N9010A-526;K	AT	MY51170010	1118472	8/10/2019	8/10/2018
Preamps/Couplers Attenuators / Filters	Range	MN	Mfr	SN	Asset	Calibration Due	Calibrated on
API - 30dB 20W Attenuator	9KHz-40GHz	89-30-11	API Weinschel	703	2121	3/23/2019	3/23/2018
Meteorological Meters/Chambers	Range	MN	Mfr	SN	Asset	Calibration Due	Calibrated on
Weather Clock (Pressure Only) TH A#2081	BA928 HTC-1	Oregon Scientific HDE	C3166-1	831 2081	I II	5/15/2020 3/23/2019	5/15/2018 3/23/2018

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.




Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
 One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 11 of 40

Testing Cert. No. 1627-01

PLOTS




Channel Power – Low Channel



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 12 of 40




Channel Power – Mid Channel



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828





Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Band Edge (Conducted)

Band Edge readings must be more than 30dB below the value of the fundamental.

MEASUREMENTS / RESULTS

Conducted Bandedge								
Date: 3/1/2019	Company: Ideal Industries							
Engineer: AKZ								
Temp: 19°C	Humidity: 28%		Pressure: 1021mBar					
Frequency Range: 902-928 MHz		Measurement Type: Conducted Measurement Method: FCC KDB 558074 D01 Meas Guidance V05						
Notes:								
	Adjusted Bandedge (dBm)	Adjusted Fundamental (dBm)	Delta to Peak (dB)	Limit				
Low Bandedge	-40.35	-0.6	39.75	≥ 20	Pass			
High Bandedge	-45.69	-2.67	43.02	≥ 20	Pass			
Test Site: CEMI-2	Cable: none		Attenuator: Asset #2121					
Analyzer: 1118472								

Copyright Curtis-Straus LLC 2000

Rev. 2/25/2019

Spectrum Analyzers / Receivers /Preselectors	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Rental EXA Signal Analyzer(1118472)	9KHz-26.5GHz	N9010A-526;K	AT	MY51170010	1118472	I	8/10/2019	8/10/2018
Preamps/Couplers Attenuators / Filters	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
API - 30dB 20W Attenuator	9KHz-40GHz	89-30-11	API Weinschel	703	2121	I	3/23/2019	3/23/2018

Meteorological Meters/Chambers	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Weather Clock (Pressure Only) TH Af#2081	BA928 HTC-1	Oregon Scientific HDE	C3166-1	831 2081	I II	5/15/2020 3/23/2019	5/15/2018 3/23/2018

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.




Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828




page 15 of 40

Testing Cert. No. 1627-01

PLOTS



Low Band Edge



Radiated Spurious Emissions

LIMITS

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
[15.247(d)]

MEASUREMENTS / RESULTS

Curtis Straus - a Bureau Veritas Company	Work Order - T0476
Radiated Emissions Electric Field 3m Distance	EUT Power Input - 3.3V Battery
Top Peaks Horizontal 30-1000MHz	Test Site - CH2
Operator: ECH	Conditions - 22.5°C; 25%RH; 1010mBar
Notes:	Witnessed by - N/A
Low Channel	EUT Maximum Frequency - 928MHz

Data Taken at February 21, 2019

Frequency (MHz)	Peak Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	Lim1: FCC_pt15_209 (dB μ V/m)	Lim1 Margin (dB)	Lim1 Test Results (Pass/Fail)	Worst Margin Lim1 (dB)
30.073	32.6	-6.4	26.2	40	-13.8	PASS	-13.8
122.732	34.6	-13.9	20.8	43.5	-22.7	PASS	
171.814	36.6	-16	20.6	43.5	-22.9	PASS	
184.084	37.3	-16.4	21	43.5	-22.5	PASS	
466.354	39.7	-9.9	29.8	46	-16.2	PASS	
789.777	30.7	-1.8	28.9	46	-17.1	PASS	



Curtis Straus - a Bureau Veritas Company
 Radiated Emissions Electric Field 3m Distance
 Top Peaks Vertical 30-1000MHz
 Operator: ECH
 Notes:
 Low Channel

Work Order - T0476
 EUT Power Input - 3.3V Battery
 Test Site - CH2
 Conditions - 22.5°C; 25%RH; 1010mBar
 Witnessed by - N/A
 EUT Maximum Frequency - 928MHz

Data Taken at February 21, 2019

Frequency (MHz)	Peak Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	Lim1: FCC_pt15_2 09 (dB μ V/m)	Lim1 Margin (dB)	Lim1 Test Results (Pass/Fail)	Worst Margin Lim1 (dB)
31.261	33.4	-7.2	26.2	40	-13.8	PASS	-13.8
180.568	39.1	-16.3	22.8	43.5	-20.7	PASS	
182.46	39.3	-16.3	22.9	43.5	-20.6	PASS	
466.33	36.1	-9.9	26.2	46	-19.8	PASS	
661.615	32.9	-4.1	28.9	46	-17.1	PASS	
800.034	30.2	-1.4	28.8	46	-17.2	PASS	

30-1000MHz Low Channel

Curtis Straus - a Bureau Veritas Company
 Radiated Emissions Electric Field 3m Distance
 Top Peaks Horizontal 30-1000MHz
 Operator: ECH
 Notes:
 Middle Channel

Work Order - T0476
 EUT Power Input - 3.3V Battery
 Test Site - CH2
 Conditions - 22.5°C; 25%RH; 1010mBar
 Witnessed by - N/A
 EUT Maximum Frequency - 928MHz

Data Taken at February 21, 2019

Frequency (MHz)	Peak Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	Lim1: FCC_pt15_2 09 (dB μ V/m)	Lim1 Margin (dB)	Lim1 Test Results (Pass/Fail)	Worst Margin Lim1 (dB)
30	32.6	-6.3	26.3	40	-13.7	PASS	-13.7
122.708	34.8	-13.9	20.9	43.5	-22.6	PASS	
184.157	38.5	-16.4	22.1	43.5	-21.4	PASS	
201.399	35	-14.9	20.1	43.5	-23.4	PASS	
466.354	39.7	-9.9	29.8	46	-16.2	PASS	
657.517	33.2	-4.1	29	46	-17	PASS	



Curtis Straus - a Bureau Veritas Company
 Radiated Emissions Electric Field 3m Distance
 Top Peaks Vertical 30-1000MHz
 Operator: ECH
 Notes:
 Middle Channel

Work Order - T0476
 EUT Power Input - 3.3V Battery
 Test Site - CH2
 Conditions - 22.5°C; 25%RH; 1010mBar
 Witnessed by - N/A
 EUT Maximum Frequency - 928MHz

Data Taken at February 21, 2019

Frequency (MHz)	Peak Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	Lim1: FCC_pt15_2 09 (dB μ V/m)	Lim1 Margin (dB)	Lim1 Test Results (Pass/Fail)	Worst Margin Lim1 (dB)
30.17	31.9	-6.4	25.5	40	-14.5	PASS	-14.5
170.092	36.7	-15.9	20.8	43.5	-22.7	PASS	
171.79	37.7	-16	21.7	43.5	-21.8	PASS	
182.484	39.5	-16.3	23.2	43.5	-20.3	PASS	
466.403	35.8	-9.9	25.9	46	-20.1	PASS	
809.565	31	-1.5	29.5	46	-16.5	PASS	

30-1000MHz Mid Channel

Curtis Straus - a Bureau Veritas Company
 Radiated Emissions Electric Field 3m Distance
 Top Peaks Horizontal 30-1000MHz
 Operator: ECH
 Notes:
 High Channel

Work Order - T0476
 EUT Power Input - 3.3V Battery
 Test Site - CH2
 Conditions - 22.5°C; 25%RH; 1010mBar
 Witnessed by - N/A
 EUT Maximum Frequency - 928MHz

Data Taken at February 21, 2019

Frequency (MHz)	Peak Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	Lim1: FCC_pt15_2 09 (dB μ V/m)	Lim1 Margin (dB)	Lim1 Test Results (Pass/Fail)	Worst Margin Lim1 (dB)
30.509	32.5	-6.7	25.8	40	-14.2	PASS	-14.2
72.413	34.5	-19.8	14.7	40	-25.3	PASS	
122.732	33.8	-13.9	19.9	43.5	-23.6	PASS	
184.06	37.5	-16.4	21.1	43.5	-22.4	PASS	
466.354	39.5	-9.9	29.5	46	-16.5	PASS	
773.335	31.5	-1.9	29.6	46	-16.4	PASS	



Curtis Straus - a Bureau Veritas Company	Work Order - T0476
Radiated Emissions Electric Field 3m Distance	EUT Power Input - 3.3V Battery
Top Peaks Vertical 30-1000MHz	Test Site - CH2
Operator: CH	Conditions - 22.5°C; 25%RH; 1010mBar
Notes:	Witnessed by - N/A
High Channel	EUT Maximum Frequency - 928MHz

Data Taken at February 21, 2019

Frequency (MHz)	Peak Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	Lim1: FCC_pt15_2 09 (dB μ V/m)	Lim1 Margin (dB)	Lim1 Test Results (Pass/Fail)	Worst Margin Lim1 (dB)
30.024	32.4	-6.3	26.1	40	-13.9	PASS	-13.9
171.838	37.8	-16	21.9	43.5	-21.6	PASS	
185.855	36.4	-16.4	20.1	43.5	-23.4	PASS	
196.379	35.5	-15.1	20.4	43.5	-23.1	PASS	
466.33	35.5	-9.9	25.6	46	-20.4	PASS	
789.874	30.5	-1.8	28.7	46	-17.3	PASS	

30-1000MHz High Channel

Curtis Straus - a Bureau Veritas Company	Work Order - T0476
Radiated Emissions Electric Field 3m Distance	EUT Power Input - 3.3V Battery
1-6GHz Horizontal Data	Test Site - CH2
Operator: CH	Conditions - 22.5°C; 25%RH; 1010mBar
Notes:	Witnessed by - N/A
Low Channel	EUT Maximum Frequency - 928MHz

Data Taken at February 21, 2019

Frequency (MHz)	Raw Peak Reading (dB μ V)	Raw Avg Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	Pk Lim: FCC_pt15_2 09_Peak (dB μ V/m)	Peak Margin (dB)	Peak Results (Pass/Fail)	Worst Peak Margin (dB)	Adjusted Avg Amplitude (dB μ V/m)	Av Lim: FCC_pt15_2 09_Average (dB μ V/m)	Avg Margin (dB)	Avg Results (Pass/Fail)	Worst Average Margin (dB)
2781.5	42.4	34.7	-5.1	37.3	74	-36.7	PASS		29.6	54	-24.4	PASS	
3233.2	43.1	34.6	-2.1	41	74	-33	PASS		32.5	54	-21.5	PASS	
3610.8	48.4	43.8	-1.7	46.7	74	-27.3	PASS	-27.3	42.1	54	-11.9	PASS	-11.9
3949.5	42.4	33.3	-0.2	42.3	74	-31.7	PASS		33.1	54	-20.9	PASS	
5514.2	44.3	33.6	2.2	46.5	74	-27.5	PASS		35.8	54	-18.2	PASS	



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 3m Distance 1-6GHz Vertical Data Operator: CH Notes: Low Channel						Work Order - T0476 EUT Power Input - 3.3V Battery Test Site - CH2 Conditions - 22.5°C; 25%RH; 1010mBar Witnessed by - N/A EUT Maximum Frequency - 928MHz					
--	--	--	--	--	--	---	--	--	--	--	--

Data Taken at February 21, 2019

Frequency (MHz)	Raw Peak Reading (dB μ V)	Raw Avg Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	Pk Lim: FCC_pt15_2 09_Peak (dB μ V/m)	Peak Margin (dB)	Peak Results (Pass/Fail)	Worst Peak Margin (dB)	Adjusted Avg Amplitude (dB μ V/m)	Av Lim: FCC_pt15_2 09_Average (dB μ V/m)	Avg Margin (dB)	Avg Results (Pass/Fail)	Worst Avg Margin (dB)
1321.6	44.2	35.5	-9.8	34.4	74	-39.6	PASS		25.8	54	-28.2	PASS	
2103	44.2	34.9	-6.4	37.8	74	-36.2	PASS		28.5	54	-25.5	PASS	
3309.5	43.8	34.7	-2	41.8	74	-32.2	PASS		32.6	54	-21.4	PASS	
3610.7	52.3	49.4	-1.7	50.6	74	-23.4	PASS	-23.4	47.7	54	-6.3	PASS	-6.3
5407.9	42.2	32.8	2.3	44.4	74	-29.6	PASS		35.1	54	-18.9	PASS	

1-6GHz Low Channel

Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 3m Distance 1-6GHz Horizontal Data Operator: CH Notes: Middle Channel						Work Order - T0476 EUT Power Input - 3.3V Battery Test Site - CH2 Conditions - 22.5°C; 25%RH; 1010mBar Witnessed by - N/A EUT Maximum Frequency - 928MHz					
---	--	--	--	--	--	---	--	--	--	--	--

Data Taken at February 21, 2019

Frequency (MHz)	Raw Peak Reading (dB μ V)	Raw Avg Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	Pk Lim: FCC_pt15_2 09_Peak (dB μ V/m)	Peak Margin (dB)	Peak Results (Pass/Fail)	Worst Peak Margin (dB)	Adjusted Avg Amplitude (dB μ V/m)	Av Lim: FCC_pt15_2 09_Average (dB μ V/m)	Avg Margin (dB)	Avg Results (Pass/Fail)	Worst Average Margin (dB)
1709.5	45	35.5	-8.3	36.7	74	-37.3	PASS		27.2	54	-26.8	PASS	
2364.5	43.6	34.1	-5.7	37.9	74	-36.1	PASS		28.3	54	-25.7	PASS	
3660.1	49.7	46.1	-1.1	48.7	74	-25.3	PASS	-25.3	45	54	-9	PASS	-9
5561.4	42.4	33.8	2.2	44.6	74	-29.4	PASS		36	54	-18	PASS	

Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 3m Distance 1-6GHz Vertical Data Operator: CH Notes: Middle Channel						Work Order - T0476 EUT Power Input - 3.3V Battery Test Site - CH2 Conditions - 22.5°C; 25%RH; 1010mBar Witnessed by - N/A EUT Maximum Frequency - 928MHz					
---	--	--	--	--	--	---	--	--	--	--	--

Data Taken at February 21, 2019

Frequency (MHz)	Raw Peak Reading (dB μ V)	Raw Avg Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	Pk Lim: FCC_pt15_2 09_Peak (dB μ V/m)	Peak Margin (dB)	Peak Results (Pass/Fail)	Worst Peak Margin (dB)	Adjusted Avg Amplitude (dB μ V/m)	Av Lim: FCC_pt15_2 09_Average (dB μ V/m)	Avg Margin (dB)	Avg Results (Pass/Fail)	Worst Avg Margin (dB)
1101	44.4	36	-10.3	34.1	74	-39.9	PASS		25.8	54	-28.2	PASS	
1726	44.2	35.6	-8.3	35.9	74	-38.1	PASS		27.3	54	-26.7	PASS	
2877.2	42.7	33.8	-4.2	38.5	74	-35.5	PASS		29.6	54	-24.4	PASS	
3317.5	42.8	34.7	-2.1	40.7	74	-33.3	PASS		32.6	54	-21.4	PASS	
3660.1	52.6	49.6	-1.1	51.5	74	-22.5	PASS	-22.5	48.6	54	-5.4	PASS	-5.4
5566.5	43.7	33.6	2.2	45.9	74	-28.1	PASS		35.8	54	-18.2	PASS	

1-6GHz Mid Channel



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 22 of 40

ACREDITED
Testing Cert. No. 1627-01

Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 3m Distance 1-6GHz Horizontal Data Operator: CCH Notes: High Channel					Work Order - T0476 EUT Power Input - 3.3V Battery Test Site - CH2 Conditions - 22.5°C; 25%RH; 1010mBar Witnessed by - N/A EUT Maximum Frequency - 928MHz				
--	--	--	--	--	---	--	--	--	--

Data Taken at February 21, 2019

Frequency (MHz)	Raw Peak Reading (dB μ V)	Raw Avg Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	Pk Lim: FCC_pt15_209_Peak (dB μ V/m)	Peak Margin (dB)	Peak Results (Pass/Fail)	Worst Peak Margin (dB)	Adjusted Avg Amplitude (dB μ V/m)	Av Lim: FCC_pt15_209_Average (dB μ V/m)	Avg Margin (dB)	Avg Results (Pass/Fail)	Worst Average Margin (dB)
1276.6	44.8	37	-10	34.8	74	-39.2	PASS	27	54	-27	PASS		
3709.4	46.2	40.7	-0.7	45.5	74	-28.5	PASS	-28.5	40	54	-14	PASS	-14
5617.7	42.4	33.8	2.1	44.5	74	-29.5	PASS	36	54	-18	PASS		

Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 3m Distance 1-6GHz Vertical Data Operator: CCH Notes: High Channel					Work Order - T0476 EUT Power Input - 3.3V Battery Test Site - CH2 Conditions - 22.5°C; 25%RH; 1010mBar Witnessed by - N/A EUT Maximum Frequency - 928MHz				
--	--	--	--	--	---	--	--	--	--

Data Taken at February 21, 2019

Frequency (MHz)	Raw Peak Reading (dB μ V)	Raw Avg Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	Pk Lim: FCC_pt15_209_Peak (dB μ V/m)	Peak Margin (dB)	Peak Results (Pass/Fail)	Worst Peak Margin (dB)	Adjusted Avg Amplitude (dB μ V/m)	Av Lim: FCC_pt15_209_Average (dB μ V/m)	Avg Margin (dB)	Avg Results (Pass/Fail)	Worst Avg Margin (dB)
2232.8	43.4	35.1	-6.6	36.8	74	-37.2	PASS	28.4	54	-25.6	PASS		
3326.7	43.8	34.7	-2.1	41.7	74	-32.3	PASS	32.6	54	-21.4	PASS		
3709.2	52.4	49.4	-0.7	51.7	74	-22.3	PASS	-22.3	48.8	54	-5.2	PASS	-5.2
5638.2	43.4	34	2.1	45.5	74	-28.5	PASS	36.1	54	-17.9	PASS		

1-6GHz High Channel

Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 1m Distance Top Peaks Horizontal 6-18GHz Operator: CCH Notes: Low Channel					Work Order - T0476 EUT Power Input - 3.3V Battery Test Site - CH2 Conditions - 22.5°C; 25%RH; 1010mBar Witnessed by - N/A EUT Maximum Frequency - 928MHz				
---	--	--	--	--	---	--	--	--	--

Data Taken at February 26, 2019

Frequency (MHz)	Raw Peak Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	Pk Lim: FCC_pt15_209_Peak (dB μ V/m)	Margin to Peak Limit (dB)	Peak Limit Test Results (Pass/Fail)	Peak Limit Worst Margin (dB)	Av Lim: FCC_pt15_209_Average (dB μ V/m)	Margin to Avg Limit (dB)	Avg Limit Test Results (Pass/Fail)	Avg Limit Worst Margin (dB)
9946.4	47.7	8.9	56.6	83.5	-26.9	PASS	-26.9	63.5	-6.9	PASS	-6.9



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 1m Distance Top Peaks Vertical 6-18GHz Operator: CCH Notes: Low Channel	Work Order - T0476 EUT Power Input - 3.3V Battery Test Site - CH2 Conditions - 22.5°C; 25%RH; 1010mBar Witnessed by - N/A EUT Maximum Frequency - 928MHz
---	---

Data Taken at February 26, 2019

Frequency (MHz)	Raw Peak Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	Pk Lim: FCC_pt15_209_Peak (dB μ V/m)	Margin to Peak Limit (dB)	Peak Limit Test Results (Pass/Fail)	Peak Limit Worst Margin (dB)	Av Lim: FCC_pt15_209_Average (dB μ V/m)	Margin to Avg Limit (dB)	Avg Limit Test Results (Pass/Fail)	Avg Limit Worst Margin (dB)
9916.4	47.8	8.8	56.6	83.5	-26.9	PASS	-26.9	63.5	-6.9	PASS	-6.9

6-10GHz Low Channel

Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 1m Distance Top Peaks Horizontal 6-18GHz Operator: CCH Notes: Middle Channel	Work Order - T0476 EUT Power Input - 3.3V Battery Test Site - CH2 Conditions - 22.5°C; 25%RH; 1010mBar Witnessed by - N/A EUT Maximum Frequency - 928MHz
--	---

Data Taken at February 26, 2019

Frequency (MHz)	Raw Peak Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	Pk Lim: FCC_pt15_209_Peak (dB μ V/m)	Margin to Peak Limit (dB)	Peak Limit Test Results (Pass/Fail)	Peak Limit Worst Margin (dB)	Av Lim: FCC_pt15_209_Average (dB μ V/m)	Margin to Avg Limit (dB)	Avg Limit Test Results (Pass/Fail)	Avg Limit Worst Margin (dB)
9904.1	47.6	8.7	56.3	83.5	-27.2	PASS	-27.2	63.5	-7.2	PASS	-7.2

Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 1m Distance Top Peaks Vertical 6-18GHz Operator: CCH Notes: Middle Channel	Work Order - T0476 EUT Power Input - 3.3V Battery Test Site - CH2 Conditions - 22.5°C; 25%RH; 1010mBar Witnessed by - N/A EUT Maximum Frequency - 928MHz
--	---

Data Taken at February 26, 2019

Frequency (MHz)	Raw Peak Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	Pk Lim: FCC_pt15_209_Peak (dB μ V/m)	Margin to Peak Limit (dB)	Peak Limit Test Results (Pass/Fail)	Peak Limit Worst Margin (dB)	Av Lim: FCC_pt15_209_Average (dB μ V/m)	Margin to Avg Limit (dB)	Avg Limit Test Results (Pass/Fail)	Avg Limit Worst Margin (dB)
9923.6	48.3	8.9	57.1	83.5	-26.4	PASS	-26.4	63.5	-6.4	PASS	-6.4

6-10GHz Mid Channel



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 1m Distance Top Peaks Horizontal 6-18GHz Operator: CCH Notes: High Channel						Work Order - T0476 EUT Power Input - 3.3V Battery Test Site - CH2 Conditions - 22.5°C; 25%RH; 1010mBar Witnessed by - N/A EUT Maximum Frequency - 928MHz					
Data Taken at February 26, 2019											
Frequency (MHz)	Raw Peak Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	Pk Lim: FCC_pt15_209_Peak (dB μ V/m)	Margin to Peak Limit (dB)	Peak Limit Test Results (Pass/Fail)	Peak Limit Worst Margin (dB)	Av Lim: FCC_pt15_209_Average (dB μ V/m)	Margin to Avg Limit (dB)	Avg Limit Test Results (Pass/Fail)	Avg Limit Worst Margin (dB)
9916.2	47.4	8.8	56.3	83.5	-27.2	PASS	-27.2	63.5	-7.2	PASS	-7.2

Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 1m Distance Top Peaks Vertical 6-18GHz Operator: CCH Notes: High Channel						Work Order - T0476 EUT Power Input - 3.3V Battery Test Site - CH2 Conditions - 22.5°C; 25%RH; 1010mBar Witnessed by - N/A EUT Maximum Frequency - 928MHz					
Data Taken at February 26, 2019											
Frequency (MHz)	Raw Peak Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	Pk Lim: FCC_pt15_209_Peak (dB μ V/m)	Margin to Peak Limit (dB)	Peak Limit Test Results (Pass/Fail)	Peak Limit Worst Margin (dB)	Av Lim: FCC_pt15_209_Average (dB μ V/m)	Margin to Avg Limit (dB)	Avg Limit Test Results (Pass/Fail)	Avg Limit Worst Margin (dB)
9894.7	48.2	8.7	56.9	83.5	-26.6	PASS	-26.6	63.5	-6.6	PASS	-6.6

6-10GHz High Channel

Rev. 2/25/2019

Spectrum Analyzers / Receivers / Preselectors		Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Rental MXE EMI Receiver(1170725)		20Hz-26.5GHz	N9038A	Agilent	MY51210151	1170725	I	4/10/2019	4/10/2018
Radiated Emissions Sites		FCC Code	IC Code	VCCI Code	Range	Asset	Cat	Calibration Due	Calibrated on
EMI Chamber 2	719150	2762A-7	A-0015	30-1000MHz	1686	I		12/7/2020	12/7/2018
EMI Chamber 2	719150	2762A-7	A-0015	1-18GHz	1686	I		12/7/2020	12/7/2018
Preamps / Couplers Attenuators / Filters		Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
2310 PA	1-1000MHz	PAM-103	COM-POWER	441175	2310	II		10/29/2019	10/29/2018
8449B HF Preamp	1-18GHz	8449B	Agilent	1149055		II		11/26/2019	11/26/2018
Antennas		Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Red-White Biolog	30-2000MHz	JB1	Sunol	A091604-1	1105	I		8/21/2019	8/21/2017
Black Horn	1-18GHz	3115	EMCO	9703-5148	56	I		9/6/2020	9/6/2018
Meteorological Meters / Chambers		MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on	
Weather Clock (Pressure Only)	BA928	Oregon Scientific	C3166-1	831	I			5/15/2020	5/15/2018
TH A#2084	HTC-1	HDE		2084	II			3/23/2019	3/23/2018
Cables		Range		Mfr		Cat	Calibration Due	Calibrated on	
Asset #2051	9kHz - 18GHz		Florida RF			II	3/7/2019	3/7/2018	
Asset #2455	9KHz-18GHz		MegaPhase			II	10/29/2019	10/29/2018	
Asset #2467	9KHz-18GHz		MegaPhase			II	10/31/2019	10/31/2018	

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.

Test Equipment Used



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 25 of 40

Testing Cert. No. 1627-01

Conducted Spurious Emissions

LIMITS

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth that contains the highest level of desired power based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB ...

[15.247(d)]

Conducted spurious emissions at the antenna port were measured in accordance with ANSI C63.10-2013 Section 11.11.


Frequency range up to 10GHz was investigated for all 3 channels (low, middle and high) at the EUT antenna port. No emissions within 30dB of their corresponding fundamental were found.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 26 of 40




Low Channel



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 27 of 40




Mid Channel



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 28 of 40



High Channel

Rev. 2/25/2019

Spectrum Analyzers / Receivers/Preselectors	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Rental EXA Signal Analyzer(1118472)	9KHz-26.5GHz	N9010A-526;K	AT	MY51170010	1118472	I	8/10/2019	8/10/2018
Preamps/Couplers Attenuators / Filters	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
API - 30dB 20W Attenuator	9KHz-40GHz	89-30-11	API Weinschel	703	2121	I	3/23/2019	3/23/2018
Meteorological Meters/Chambers		MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Weather Clock (Pressure Only)		BA928	Oregon Scientific	C3166-1	831	I	5/15/2020	5/15/2018
TH A#2081		HTC-1	HDE		2081	II	3/23/2019	3/23/2018

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Power Spectral Density

LIMIT

*...the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.
[15.247(e)]*

Per ANSI C63.10-2013 Section 11.10.3 Method AVGPSD-1

MEASUREMENTS / RESULTS

Peak Power Spectral Density												
Date: 3/1/2019	Company: Ideal Industries		Work Order: T0476									
Engineer: AKZ			Operating Voltage/Frequency: Battery									
Temp: 19°C	Humidity: 28%		Pressure: 1021mBar									
Frequency Range: 902-928 MHz		Measurement Type: Conducted										
Notes:												
Frequency	Peak Reading	Cable Loss	Attenuator Loss	Peak PSD	Limit	Margin	Result					
(MHz)	(dBm)	(dB)	(dB)	(dBm)	(dBm)	(dB)						
902.7	-40.01	0.00	29.35	-10.66	8.0	-18.66	Pass					
915.0	-41.15	0.00	29.35	-11.80	8.0	-19.80	Pass					
927.3	-42.31	0.00	29.35	-12.96	8.0	-20.96	Pass					
Test Site: CEMI-2	Cable: none		Attenuator: Asset #2121									
Analyzer: 1118472												
PSD(dBm) = Reading (dBm) + Cable Loss (dB) + Attenuator Loss (dBm)												

Rev. 2/25/2019

Spectrum Analyzers / Receivers/Preselectors	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Rental EXA Signal Analyzer(1118472)	9KHz-26.5GHz	N9010A-526:K	AT	MY51170010	1118472	I	8/10/2019	8/10/2018
Preamps/Couplers Attenuators / Filters	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
API - 30dB 20W Attenuator	9KHz-40GHz	89-30-11	API Weinschel	703	2121	I	3/23/2019	3/23/2018
Meteorological Meters/Chambers		MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Weather Clock (Pressure Only)	BA928	Oregon Scientific	C3166-1	831	2081	I	5/15/2020	5/15/2018
TH A#2081	HTC-1	HDE		II		II	3/23/2019	3/23/2018

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.




Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 30 of 40

Testing Cert. No. 1627-01


PLOTS



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 31 of 40




PSD – Mid Channel



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828





Occupied Bandwidth

REQUIREMENT

When an occupied bandwidth is not specified in the applicable RSS, the transmitted signal bandwidth to be reported is its 99% emission bandwidth, as calculated or measured.
[RSS-GEN Issue 5 Section 6.7]

MEASUREMENTS / RESULTS

99% Occupied Bandwidth																
Date: 3/1/2019	Company: Ideal Industries					Work Order: T0476										
Engineer: AKZ						Operating Voltage/Frequency: Battery										
Temp: 19°C	Humidity: 28%					Pressure: 1021mBar										
Notes:																
Frequency (MHz)	99% OBW (kHz)															
902.7	764.30															
915.0	762.23															
927.3	761.59															
Test Site: CEMI-2	Cable: none			Attenuator: Asset #2121												
Analyzer: 1118472																
Rev. 2/25/2019	Copyright Curtis-Straus LLC 2000															
Spectrum Analyzers / Receivers /Preselectors Rental EXA Signal Analyzer(1118472)	Range 9KHz-26.5GHz	MN N9010A-526;K	Mfr AT	SN MY51170010	Asset 1118472	Cat I	Calibration Due 8/10/2019	Calibrated on 8/10/2018								
Preamps/Couplers Attenuators / Filters API - 30dB 20W Attenuator	Range 9KHz-40GHz	MN 89-30-11	Mfr API Weinschel	SN 703	Asset 2121	Cat I	Calibration Due 3/23/2019	Calibrated on 3/23/2018								
Meteorological Meters/Chambers Weather Clock (Pressure Only) TH A#2081	MN BA928 HTC-1	Mfr Oregon Scientific HDE	SN C3166-1	Asset 831 2081	Cat I II	Calibration Due 5/15/2020 3/23/2019	Calibrated on 5/15/2018 3/23/2018									

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.




Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828




page 34 of 40

Testing Cert. No. 1627-01

Plot(s)

Occupied Bandwidth – Low Channel






Occupied Bandwidth – Middle Channel



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 36 of 40



Occupied Bandwidth – High Channel



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 37 of 40

Measurement Uncertainty

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

Measurement	Expanded Uncertainty k=2	Maximum allowable uncertainty
Radiated Emissions (30-1000MHz) NIST CISPR	5.6dB 4.6dB	N/A 5.2dB (Ucispr)
Radiated Emissions (1-26.5GHz)	4.6dB	N/A
Radiated Emissions (above 26.5GHz)	4.9dB	N/A
Magnetic Radiated Emissions	5.6dB	N/A
Conducted Emissions NIST CISPR	3.9dB 3.6dB	N/A 3.6dB (Ucispr)
Telco Conducted Emissions (Current)	2.9dB	N/A
Telco Conducted Emissions (Voltage)	4.4dB	N/A
Electrostatic Discharge	11.5%	N/A
Radiated RF Immunity (Uniform Field)	1.6dB	N/A
Electrical Fast Transients	23.1%	N/A
Surge	23.1%	N/A
Conducted RF Immunity	3dB	N/A
Magnetic Immunity	12.8%	N/A
Dips and Interrupts	2.3V	N/A
Harmonics	3.5%	N/A
Flicker	3.5%	N/A
Radio frequency (@ 2.4GHz)	3.23×10^{-8}	1×10^{-7}
RF power, conducted	0.40dB	0.75dB
Maximum frequency deviation:		
• Within 300Hz and 6kHz of audio frequency / Within 6kHz and 25kHz of audio frequency	3.4% 0.3dB	5% 3dB
Adjacent channel power	1.9dB	3dB
Conducted spurious emission of transmitter, valid up to 12.75GHz	2.39dB	3dB
Conducted emission of receivers	1.3dB	3dB
Radiated emission of transmitter, valid up to 26.5GHz	3.9dB	6dB
Radiated emission of transmitter, valid up to 80GHz	3.3dB	6dB
Radiated emission of receiver, valid up to 26.5GHz	3.9dB	6dB
Radiated emission of receiver, valid up to 80GHz	3.3dB	6dB
Humidity	2.37%	5%
Temperature	0.7°C	1.0°C
Time	4.1%	10%
RF Power Density, Conducted	0.4dB	3dB
DC and low frequency voltages	1.3%	3%
Voltage (AC, <10kHz)	1.3%	2%
Voltage (DC)	0.62%	1%
The above reflects a 95% confidence level		



Conditions Of Testing

[Bureau Veritas Consumer Products Services, Inc., a Massachusetts corporation], and/or its affiliates (collectively, the "Company") will conduct, at the request of the Submitter ("Client"), the tests specified on the submitted Test Request Form or equivalent in accordance with, and subject to, the following terms and conditions (collectively, "Conditions"):

1. All orders for tests are subject to acceptance by the Company, and no order will constitute a binding commitment of the Company unless and until such order is accepted by it, as evidenced by the issuance of a written report ("Test Report") by the Company. The Test Report is issued solely by the Company, is intended for the exclusive use of Client and shall not be published, used for advertising purposes, copied or replicated for distribution to any other person or entity or otherwise publicly disclosed without the prior written consent of the Company. By submitting a request for services to the Company, Client consents to the disclosure to accreditation bodies of those records of Client relevant to the accreditation body's assessment of the Company's competence and compliance with relevant accreditation criteria. The Company shall not be liable for any loss or damage whatsoever resulting from the failure of the Company to provide its services within any time period for completion estimated by the Company. If Client anticipates using the Test Report in any legal proceeding, arbitration, dispute resolution forum or other proceeding, it shall so notify the Company prior to submitting the Test Report in such proceeding. The Company has no obligation to provide a fact or expert witness at such proceeding unless the Company agrees in advance to do so for a separate and additional fee.
2. The Test Report will set forth the findings of the Company solely with respect to the test samples identified therein. Unless specifically and expressly indicated in the Test Report, the results set forth in such Test Report are not intended to be indicative or representative of the quality or characteristics of the lot from which a test sample is taken, and Client shall not rely upon the Test Report as being so indicative or representative of the lot or of the tested product in general. The Test Report will reflect the findings of the Company at the time of testing only, and the Company shall have no obligation to update the Test Report after its issuance. The Test Report will set forth the results of the tests performed by the Company based upon the written information provided to the Company. The Test Report will be based solely on the samples and written information submitted to the Company by Client, and the Company shall not be obligated to conduct any independent investigation or inquiry with respect thereto.
3. The Company may, in its sole discretion, destroy samples which have been furnished to the Company for testing and which have not been destroyed in the course of testing. The Company may delegate the performance of all or a portion of the services contemplated hereunder to an affiliate, agent or subcontractor of the Company, and Client consents to such delegation.
4. These Conditions and the Test Report represent the entire understanding of the parties hereto with respect to the subject matter hereof and of the Test Report, and no modification, variance or extrapolation with respect thereto shall be permitted without the prior written consent of the Company.
5. The names, service marks, trademarks and copyrights of the Company and its affiliates, including the names "BUREAU VERITAS," "BUREAU VERITAS CONSUMER PRODUCTS SERVICES," "BVCPs", "MTL", "ACTS", "MTL-ACTS" and CURTIS-STRaus (collectively, the "Marks") are and shall remain the sole property of the Company or its affiliates and shall not be used by Client except solely to the extent that Client obtains the prior written approval of the Company and then only in the manner prescribed by the Company. Client shall not contest the validity of the Marks or take any action that might impair the value or goodwill associated with the Marks or the image or reputation of the Company or its affiliates.
6. Payment in full shall be due 30 days after the date of invoice. Interest shall be due on overdue amounts from the due date until paid at an interest rate of 1.5% per month or, if less, the maximum rate permitted by law. The Company reserves the right, at any time and from time to time, to revoke any credit extended to Client. Client shall reimburse the Company for any costs it incurs in collecting past due amounts, including court costs and fees and expenses of attorneys and collection agencies. The Test Report may not be used or relied upon by Client if and for so long as Client fails to pay when due any invoice issued by the Company or any affiliate of it to Client or any affiliate or subsidiary of Client together with interest and penalties, if any, accrued thereon.
7. The Company disclaims any and all responsibility or liability arising out of or in connection with e-mail transmissions of such information.
8. Client understands and agrees that the Company is neither an insurer nor a guarantor, that the Company does not take the place of Client or any designer, manufacturer, agent, buyer, distributor or transportation or shipping company, and that the Company disclaims all liability in such capacities. Client further understands that if it seeks assurance against loss or damage, it should obtain appropriate insurance.
9. Client agrees that the Company, by providing the services, does not take the place of Client nor any third party, nor does the Company release them from any of their obligations, nor does the Company otherwise assume, abridge, abrogate or undertake to discharge any duty of any third party to Client or any duty of Client or any third party to any other third party, and Client will not release any third party from its obligations and duties with respect to the tested goods.
10. Client shall, on a timely basis, (a) provide adequate instructions to the Company in order to enable the Company to perform properly its services, (b) provide, or cause Client's suppliers and contractors to provide, the Company with all documents necessary to enable the Company to perform its services, (c) furnish the Company with all relevant information regarding Client's intended use and purposes of the tested goods, (d) advise the Company of essential dates and deadlines relevant to the tested goods and (e) fully exercise all rights and remedies available to Client against third parties in respect of the tested goods.
11. The Company shall undertake due care and ordinary skill in the performance of its services to Client, and the Company shall accept responsibility only were such skill has not been exercised and, even in such event, only to the extent of the limitation of liability set forth herein.
12. If Client desires to assert a claim arising from or relating to (i) the performance, purported performance or non-performance of any services by the Company or (ii) the sale, resale, manufacture, distribution or use of any tested goods, it must submit that claim to the Company in a writing that sets forth with particularity the basis for such claim within 60 days from discovery of the potential claim and not more than six months after the date of issuance of the Test Report to Client. Client waives any and all



such claims including, without limitation, claims that the Test Report is inaccurate, incomplete or misleading or that additional or different testing is required, unless and then only to the extent that Client submits a written claim to the Company within both such time periods.

13. CLIENT SHALL, EXCEPT TO THE EXTENT OF COMPANY'S LIABILITY TO CLIENT HEREUNDER (WHICH IN NO EVENT SHALL EXCEED THE LIMITATION OF LIABILITY HEREIN), HOLD HARMLESS AND INDEMNIFY THE COMPANY, ITS AFFILIATES AND THEIR RESPECTIVE DIRECTORS, OFFICERS, EMPLOYEES, AGENTS AND SUBCONTRACTORS AGAINST ALL ACTUAL OR ALLEGED THIRD PARTY CLAIMS FOR LOSS, DAMAGE OR EXPENSE OF WHATSOEVER NATURE AND HOWSOEVER ARISING FROM OR RELATING TO (i) THE PERFORMANCE, PURPORTED PERFORMANCE OR NON-PERFORMANCE OF ANY SERVICES BY THE COMPANY OR (ii) THE SALE, RESALE, MANUFACTURE, DISTRIBUTION OR USE OF ANY TESTED GOODS.

14. EXCEPT AS MAY OTHERWISE BE EXPRESSLY AGREED TO IN WRITING BY THE COMPANY AND NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN OR IN ANY TEST REPORT, NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR USE, IS MADE.

15. (A) IN NO EVENT WHATSOEVER SHALL THE COMPANY BE LIABLE FOR ANY CONSEQUENTIAL, SPECIAL, INCIDENTAL, EXEMPLARY OR PUNITIVE DAMAGES IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE TEST REPORT OR THE SERVICES PROVIDED BY THE COMPANY HEREUNDER, INCLUDING WITHOUT LIMITATION LOSS OF OR DAMAGE TO PROPERTY; LOSS OF INCOME, PROFIT OR USE; OR ANY CLAIMS OR DEMANDS MADE AGAINST CLIENT OR ANY OTHER PERSON BY ANY THIRD PARTY IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE SERVICES PROVIDED BY THE COMPANY HEREUNDER.

(B)NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN, AND IN RECOGNITION OF THE RELATIVE RISKS AND BENEFITS TO CLIENT AND THE COMPANY ASSOCIATED WITH THE TESTING SERVICES CONTEMPLATED HEREBY, THE RISKS HAVE BEEN ALLOCATED SUCH THAT UNDER NO CIRCUMSTANCES WHATSOEVER SHALL THE LIABILITY OF THE COMPANY TO CLIENT OR ANY THIRD PARTY IN RESPECT OF ANY CLAIM FOR LOSS, DAMAGE OR EXPENSE, OF WHATSOEVER NATURE OR MAGNITUDE, AND HOWSOEVER ARISING, EXCEED AN AMOUNT EQUAL TO FIVE (5) TIMES THE AMOUNT OF THE FEES PAID TO THE COMPANY FOR THE SPECIFIC SERVICES WHICH GAVE RISE TO SUCH CLAIM OR U.S.\$10,000, WHICHEVER IS THE LESSER AMOUNT.

16. The Company shall not be liable for any loss or damage resulting from any delay or failure in performance of its obligations hereunder resulting directly or indirectly from any event of force majeure or any event outside the control of the Company. If any such event occurs, the Company may immediately cancel or suspend its performance hereunder without incurring any liability whatsoever to Client.

Company's services, including these Conditions, shall be governed by, and construed in accordance with, the local laws of the country where the Company performs the tests or, in the case of tests performed in the United States of America, the laws of Massachusetts without regard to conflicts of laws principles. If any aspect(s) of these Conditions is found to be illegal or unenforceable, the validity, legality and enforceability of all remaining aspects of these Conditions shall not in any way be affected or impaired thereby. Any proceeding related to the subject matter hereof shall be brought, if at all, in the courts of the country where the Company performs the tests or, in the case of tests performed in the United States of America, in the courts of Massachusetts. Client waives the right to interpose any counterclaim or setoffs of any nature in any litigation arising hereunder.

The complete list of the Approved Subcontractors Curtis-Straus may use to delegate the performance of work can be provided upon request.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 40 of 40