

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan
District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM150100010902
Page: 1 of 56

IC REPORT

Application No: SZEM1501000109CR (SGS GZ No.: GZEM1501000049CR)
Applicant: WOOX Innovations Limited
Manufacturer: WOOX Innovations Limited
Factory: Foshan City Nanhai Commtech Technology Co., Ltd
Product Name: Bluetooth Headset Trainer TH100
Model No.(EUT): TH100
Trade Mark: Trainer
IC ID: 11260A-TH100
Standards: RSS-210 Issue 8 Dec 2010
RSS-Gen Issue 4 Nov 2014
Date of Receipt: 2015-01-09
Date of Test: 2015-01-13 to 2015-01-15
Date of Issue: 2015-02-11

| | |
|----------------------|---------------|
| Test Result : | PASS * |
|----------------------|---------------|

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

2 Version

| Revision Record | | | | |
|-----------------|---------|------------|----------|----------|
| Version | Chapter | Date | Modifier | Remark |
| 00 | | 2015-02-11 | | Original |
| | | | | |
| | | | | |

| | | | |
|--------------------------|--|-----------------------------|------------|
| Authorized for issue by: | | | |
| | | Eric Fu | 2015-01-15 |
| Tested By | | (Eric Fu) /Project Engineer | Date |
| | | Hedy Wen | 2015-02-11 |
| Prepared By | | (Hedy Wen) /Clerk | Date |
| | | Owen Zhou | 2015-02-11 |
| Checked By | | (Owen Zhou) /Reviewer | Date |



3 Test Summary

| Test Item | Test Requirement | Test method | Result |
|--|-------------------|-------------------------------------|--------|
| Antenna Requirement | RSS-Gen Issue 4 | ANSI C63.10: 2009 | PASS |
| Conducted Emission | RSS-Gen Issue 4 | ANSI C63.10: 2009 | PASS |
| Conducted Peak Output Power | RSS 210 A 8.4(4) | RSS-Gen Issue 4 & ANSI C63.10: 2009 | PASS |
| 6dB Occupied Bandwidth | RSS 210 A 8.2 (a) | RSS-Gen Issue 4 | PASS |
| 99% Occupied Bandwidth | RSS-Gen Issue 4 | RSS-Gen Issue 4 | PASS |
| Power Spectral Density | RSS 210 A 8.2 (b) | ANSI C63.10: 2009 | PASS |
| Band-Edge for RF Transmit Conducted Emissions | RSS 210 A 8.5 | ANSI C63.10: 2009 | PASS |
| Spurious RF Transmit Conducted Emissions | RSS 210 A 8.5 | ANSI C63.10: 2009 | PASS |
| Radiated Transmit Spurious Emissions | RSS-Gen Issue 4 | RSS-Gen Issue 4 & ANSI C63.10: 2009 | PASS |
| Restricted bands around fundamental frequency (Radiated Emission) | RSS-Gen Issue 4 | RSS-Gen Issue 4 & ANSI C63.10: 2009 | PASS |

4 Contents

| | Page |
|--|------|
| 1 COVER PAGE..... | 1 |
| 2 VERSION | 2 |
| 3 TEST SUMMARY | 3 |
| 4 CONTENTS..... | 4 |
| 5 GENERAL INFORMATION | 5 |
| 5.1 CLIENT INFORMATION..... | 5 |
| 5.2 GENERAL DESCRIPTION OF EUT | 5 |
| 5.3 TEST ENVIRONMENT | 7 |
| 5.4 DESCRIPTION OF SUPPORT UNITS | 7 |
| 5.5 TEST LOCATION | 7 |
| 5.6 TEST FACILITY | 8 |
| 5.7 DEVIATION FROM STANDARDS..... | 8 |
| 5.8 ABNORMALITIES FROM STANDARD CONDITIONS | 8 |
| 5.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER..... | 8 |
| 5.10 EQUIPMENT LIST | 9 |
| 6 TEST RESULTS AND MEASUREMENT DATA | 12 |
| 6.1 ANTENNA REQUIREMENT..... | 12 |
| 6.2 CONDUCTED EMISSIONS..... | 13 |
| 6.3 CONDUCTED PEAK OUTPUT POWER | 17 |
| 6.4 6dB OCCUPY BANDWIDTH..... | 20 |
| 6.5 99% OCCUPY BANDWIDTH | 23 |
| 6.6 POWER SPECTRAL DENSITY | 26 |
| 6.7 BAND EDGE FOR RF CONDUCTED EMISSIONS | 29 |
| 6.8 RF ANTENNA CONDUCTED SPURIOUS EMISSIONS..... | 31 |
| 6.9 RADIATED SPURIOUS EMISSION | 38 |
| 6.9.1 <i>Radiated Spurious Emission</i> | 38 |
| 6.10 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY | 44 |
| 7 PHOTOGRAPHS - EUT TEST SETUP | 54 |
| 7.1 CONDUCTED EMISSIONS..... | 54 |
| 7.2 RADIATED EMISSION..... | 54 |
| 8 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS..... | 56 |

5 General Information

5.1 Client Information

| | |
|--------------------------|--|
| Applicant: | WOOX Innovations Limited |
| Address of Applicant: | 5/F, Philips Electronics Building, No.5 Science Park East Avenue, Hong Kong Science Park, Shatin, N.T., HONG KONG. |
| Manufacturer: | WOOX Innovations Limited |
| Address of Manufacturer: | 5/F, Philips Electronics Building, No.5 Science Park East Avenue, Hong Kong Science Park, Shatin, N.T., HONG KONG. |
| Factory: | Foshan City Nanhai Commtech Technology Co., Ltd |
| Address of Factory: | Yi Zhong, DaZhen, Da Li, Nan Hai District, FoShan City, Guangdong Province, P.R.C |

5.2 General Description of EUT

| | |
|-----------------------|--|
| Product Name: | Bluetooth Headset Trainer TH100 |
| Model No.: | TH100 |
| Trade Mark: | Trainer |
| Operation Frequency: | 2402MHz~2480MHz |
| Bluetooth Version: | V4.0 |
| | This test report is for BLE mode. |
| Modulation Type: | GFSK |
| Number of Channel: | 40 |
| Sample Type: | Portable production |
| EUT Function: | Bluetooth Headphone |
| Test Power Grade: | ClassII (manufacturer declare) |
| Test Software of EUT: | Blue test 3 (manufacturer declare) |
| Antenna Type: | Integral |
| Antenna Gain | 0dBi |
| Power Supply: | USB Charge DC 5V 0.5A |
| Battery: | DC 3.7V 190mAh Lithium ion Polymer Battery |
| USB Cable: | Unshielded 50cm |

| Operation Frequency each of channel | | | | | | | |
|-------------------------------------|-----------|---------|-----------|---------|-----------|---------|-----------|
| Channel | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 1 | 2402MHz | 11 | 2422MHz | 21 | 2442MHz | 31 | 2462MHz |
| 2 | 2404MHz | 12 | 2424MHz | 22 | 2444MHz | 32 | 2464MHz |
| 3 | 2406MHz | 13 | 2426MHz | 23 | 2446MHz | 33 | 2466MHz |
| 4 | 2408MHz | 14 | 2428MHz | 24 | 2448MHz | 34 | 2468MHz |
| 5 | 2410MHz | 15 | 2430MHz | 25 | 2450MHz | 35 | 2470MHz |
| 6 | 2412MHz | 16 | 2432MHz | 26 | 2452MHz | 36 | 2472MHz |
| 7 | 2414MHz | 17 | 2434MHz | 27 | 2454MHz | 37 | 2474MHz |
| 8 | 2416MHz | 18 | 2436MHz | 28 | 2456MHz | 38 | 2476MHz |
| 9 | 2418MHz | 19 | 2438MHz | 29 | 2458MHz | 39 | 2478MHz |
| 10 | 2420MHz | 20 | 2440MHz | 30 | 2460MHz | 40 | 2480MHz |

Note:

In RSS-Gen, regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

| Channel | Frequency |
|---------------------|-----------|
| The Lowest channel | 2402MHz |
| The Middle channel | 2440MHz |
| The Highest channel | 2480MHz |

5.3 Test Environment

| Operating Environment: | |
|------------------------|-----------|
| Temperature: | 24.0 °C |
| Humidity: | 52 % RH |
| Atmospheric Pressure: | 1020 mbar |

5.4 Description of Support Units

The EUT has been tested with associated equipment below.

| Description | Manufacturer | Model No. |
|---------------|---------------|-----------|
| RF test board | Supply by SGS | NONE |
| Adapter | Supply by SGS | R01100 |

5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,
No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1 & 4620C-2.

5.7 Deviation from Standards

None.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.

5.10 Equipment List

| Conducted Emission | | | | | |
|--------------------|---------------------------------|------------------------------------|-----------------|---------------|---------------------------|
| Item | Test Equipment | Manufacturer | Model No. | Inventory No. | Cal.Due date (yyyy-mm-dd) |
| 1 | Shielding Room | ZhongYu Electron | GB-88 | SEL0042 | 2015-06-10 |
| 2 | LISN | Rohde & Schwarz | ENV216 | SEL0152 | 2015-10-24 |
| 3 | LISN | ETS-LINDGREN | 3816/2 | SEL0021 | 2015-05-16 |
| 4 | 8 Line ISN | Fischer Custom Communications Inc. | FCC-TLISN-T8-02 | SEL0162 | 2015-08-30 |
| 5 | 4 Line ISN | Fischer Custom Communications Inc. | FCC-TLISN-T4-02 | SEL0163 | 2015-08-30 |
| 6 | 2 Line ISN | Fischer Custom Communications Inc. | FCC-TLISN-T2-02 | SEL0164 | 2015-08-30 |
| 7 | EMI Test Receiver | Rohde & Schwarz | ESCI | SEL0022 | 2015-05-16 |
| 8 | Coaxial Cable | SGS | N/A | SEL0025 | 2015-05-29 |
| 9 | DC Power Supply | Zhao Xin | RXN-305D | SEL0117 | 2015-10-24 |
| 10 | Humidity/ Temperature Indicator | Shanghai Qixiang | ZJ1-2B | SEL0103 | 2015-10-24 |
| 11 | Barometer | Chang Chun | DYM3 | SEL0088 | 2015-05-16 |

| RE in Chamber | | | | | |
|---------------|--------------------------------|------------------------------------|-----------|---------------|---------------------------|
| Item | Test Equipment | Manufacturer | Model No. | Inventory No. | Cal.Due date (yyyy-mm-dd) |
| 1 | 3m Semi-Anechoic Chamber | ETS-LINDGREN | N/A | SEL0017 | 2015-06-10 |
| 2 | EMI Test Receiver | Agilent Technologies | N9038A | SEL0312 | 2015-09-16 |
| 3 | EMI Test software | AUDIX | E3 | SEL0050 | N/A |
| 4 | BiConiLog Antenna (26-3000MHz) | ETS-LINDGREN | 3142C | SEL0015 | 2015-10-24 |
| 5 | Double-ridged horn (1-18GHz) | ETS-LINDGREN | 3117 | SEL0006 | 2015-10-24 |
| 6 | Horn Antenna (18-26GHz) | ETS-LINDGREN | 3160 | SEL0076 | 2015-10-24 |
| 7 | Pre-amplifier (0.1-1300MHz) | Agilent Technologies | 8447D | SEL0053 | 2015-05-16 |
| 8 | Pre-Amplifier (0.1-26.5GHz) | Compliance Directions Systems Inc. | PAP-0126 | SEL0168 | 2015-10-24 |
| 9 | Coaxial cable | SGS | N/A | SEL0027 | 2015-05-29 |
| 10 | Coaxial cable | SGS | N/A | SEL0189 | 2015-05-29 |
| 11 | Coaxial cable | SGS | N/A | SEL0121 | 2015-05-29 |
| 12 | Coaxial cable | SGS | N/A | SEL0178 | 2015-05-29 |
| 13 | Band filter | Amindeon | 82346 | SEL0094 | 2015-05-16 |
| 14 | Barometer | Chang Chun | DYM3 | SEL0088 | 2015-05-16 |
| 15 | DC Power Supply | Zhao Xin | RXN-305D | SEL0117 | 2015-10-24 |
| 16 | Humidity/Temperature Indicator | Shanghai Qixiang | ZJ1-2B | SEL0103 | 2015-10-24 |
| 17 | Signal Generator (10M-27GHz) | Rohde & Schwarz | SMR27 | SEL0067 | 2015-05-16 |
| 18 | Signal Generator | Rohde & Schwarz | SMY01 | SEL0155 | 2015-10-24 |
| 19 | Loop Antenna | Beijing Daze | ZN30401 | SEL0203 | 2015-06-04 |

| RF connected test | | | | | |
|-------------------|---------------------------------|----------------------|-----------|---------------|---------------------------|
| Item | Test Equipment | Manufacturer | Model No. | Inventory No. | Cal.Due date (yyyy-mm-dd) |
| 1 | DC Power Supply | Zhao Xin | RXN-305D | SEL0117 | 2015-10-24 |
| 2 | Humidity/ Temperature Indicator | HYGRO | ZJ1-2B | SEL0033 | 2015-10-24 |
| 3 | Spectrum Analyzer | Rohde & Schwarz | FSP | SEL0154 | 2015-10-24 |
| 4 | Coaxial cable | SGS | N/A | SEL0178 | 2015-05-29 |
| 5 | Coaxial cable | SGS | N/A | SEL0179 | 2015-05-29 |
| 6 | Barometer | ChangChun | DYM3 | SEL0088 | 2015-05-16 |
| 7 | Signal Generator | Rohde & Schwarz | SML03 | SEL0068 | 2015-05-16 |
| 8 | Band filter | amideon | 82346 | SEL0094 | 2015-05-16 |
| 9 | POWER METER | R & S | NRVS | SEL0144 | 2015-10-24 |
| 10 | Attenuator | Beijin feihang taida | TST-2-6dB | SEL0205 | 2015-05-16 |
| 11 | Power Divider(splitter) | Agilent Technologies | 11636B | SEL0130 | 2015-10-24 |

Note: The calibration interval is one year, all the instruments are valid.

6 Test Results and Measurement Data


6.1 Antenna Requirement

| | |
|---|-----------------|
| Standard Requirement: | RSS-Gen Issue 4 |
| EUT Antenna: | |
| The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi. | |



6.2 Conducted Emissions

| | | | |
|--|---|-----------|-------------------------|
| Test Requirement: | RSS-Gen Issue 4 | | |
| Test Method: | ANSI C63.10: 2009 | | |
| Test Frequency Range: | 150kHz to 30MHz | | |
| Limit: | Frequency range (MHz) | | Limit (dBuV) |
| | | | Quasi-peak Average |
| | 0.15-0.5 | 66 to 56* | 56 to 46* |
| | 0.5-5 | 56 | 46 |
| | 5-30 | 60 | 50 |
| * Decreases with the logarithm of the frequency. | | | |
| Test Procedure: | <ol style="list-style-type: none">1) The mains terminal disturbance voltage test was conducted in a shielded room.2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2009 on conducted measurement. | | |

Test Setup:


| | |
|--------------------------|---|
| Instruments Used: | Refer to section 5.10 for details |
| Test Mode: | Transmitting with GFSK modulation. AC charge +Transmitting mode. |
| Test Results: | Pass |

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.


Live Line:



Site : Shielding Room
 Condition : RSS-210 AV CE LINE
 Job.No : 0109CR
 Mode : Charge +TX mode

| Freq | Cable | LISN | Read | Limit | | Over | Remark |
|------|---------|--------|-------|-------|-------|-------|-------------|
| | Loss | Factor | Level | Level | Line | Limit | |
| | MHz | dB | dB | dBuV | dBuV | dB | |
| 1 | 0.19758 | 0.02 | 9.70 | 34.37 | 44.09 | 53.71 | -9.62 Peak |
| 2 | 0.46614 | 0.01 | 9.80 | 28.01 | 37.82 | 46.58 | -8.76 Peak |
| 3 | 1.049 | 0.02 | 9.80 | 27.28 | 37.10 | 46.00 | -8.90 Peak |
| 4 | 1.654 | 0.02 | 9.80 | 25.21 | 35.03 | 46.00 | -10.97 Peak |
| 5 | 5.867 | 0.01 | 9.90 | 24.05 | 33.96 | 50.00 | -16.04 Peak |
| 6 | 16.750 | 0.02 | 10.10 | 28.99 | 39.11 | 50.00 | -10.89 Peak |

Neutral Line:




Site : Shielding Room
 Condition : RSS-210 AV CE NEUTRAL
 Job.No : 0109CR
 Mode : Charge +TX mode

| | Freq | Cable | LISN | Read | Limit | Over | Remark |
|---|---------|-------|--------|-------|-------|-------|-------------|
| | | Loss | Factor | Level | Level | Line | |
| | MHz | dB | dB | dBuV | dBuV | dB | |
| 1 | 0.22201 | 0.02 | 9.70 | 30.29 | 40.01 | 52.74 | -12.73 Peak |
| 2 | 0.45636 | 0.01 | 9.80 | 28.46 | 38.27 | 46.76 | -8.49 Peak |
| 3 | 1.049 | 0.02 | 9.80 | 28.15 | 37.97 | 46.00 | -8.03 Peak |
| 4 | 2.707 | 0.02 | 9.83 | 29.27 | 39.13 | 46.00 | -6.87 Peak |
| 5 | 6.841 | 0.01 | 9.99 | 23.68 | 33.68 | 50.00 | -16.32 Peak |
| 6 | 13.695 | 0.01 | 10.00 | 27.29 | 37.30 | 50.00 | -12.70 Peak |

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.

6.3 Conducted Peak Output Power


| | |
|------------------------|---|
| Test Requirement: | RSS 210 A 8.4(4) |
| Test Method: | RSS-Gen Issue 4 & ANSI C63.10: 2009 |
| Limit: | 30dBm |
| Test Setup: |  |
| | <i>Remark:</i> <i>Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</i> |
| Instruments Used: | Refer to section 5.10 for details. |
| Exploratory Test Mode: | Transmitting with GFSK modulation. |
| Test Results: | Pass |

Measurement Data


| GFSK mode | | | |
|--------------|-------------------------|-------------|--------|
| Test channel | Peak Output Power (dBm) | Limit (dBm) | Result |
| Lowest | -4.73 | 30.00 | Pass |
| Middle | -0.60 | 30.00 | Pass |
| Highest | 0.02 | 30.00 | Pass |

Test plot as follows:


| | | | |
|------------|------|---------------|--------|
| Test mode: | GFSK | Test channel: | Lowest |
|------------|------|---------------|--------|




| | | | |
|------------|------|---------------|--------|
| Test mode: | GFSK | Test channel: | Middle |
|------------|------|---------------|--------|



| | | | |
|------------|------|---------------|---------|
| Test mode: | GFSK | Test channel: | Highest |
|------------|------|---------------|---------|



6.4 6dB Occupy Bandwidth


| | |
|-------------------|--|
| Test Requirement: | RSS 210 A 8.2(a) |
| Test Method: | RSS-Gen Issue 4 |
| Test Setup: |  |
| Instruments Used: | Refer to section 5.10 for details. |
| Limit: | ≥ 500 kHz |
| Test Mode: | Transmitting with GFSK modulation. |
| Test Results: | Pass |

Measurement Data


| GFSK mode | | | |
|--------------|----------------------------|-------------|--------|
| Test channel | 6dB Occupy Bandwidth (MHz) | Limit (kHz) | Result |
| Lowest | 0.697 | ≥ 500 | Pass |
| Middle | 0.697 | ≥ 500 | Pass |
| Highest | 0.697 | ≥ 500 | Pass |

Test plot as follows:


| | | | |
|------------|------|---------------|--------|
| Test mode: | GFSK | Test channel: | Lowest |
|------------|------|---------------|--------|




| | | | |
|------------|------|---------------|--------|
| Test mode: | GFSK | Test channel: | Middle |
|------------|------|---------------|--------|



| | | | |
|------------|------|---------------|---------|
| Test mode: | GFSK | Test channel: | Highest |
|------------|------|---------------|---------|



6.5 99% Occupy Bandwidth


| | |
|-------------------|--|
| Test Requirement: | RSS-Gen Issue 4 |
| Test Method: | RSS-Gen Issue 4 |
| Test Setup: |  |
| Instruments Used: | Refer to section 5.10 for details. |
| Limit: | NA |
| Test Mode: | Transmitting with GFSK modulation. |
| Test Results: | Pass |

Measurement Data


| GFSK mode | |
|--------------|----------------------------|
| Test channel | 99% Occupy Bandwidth (MHz) |
| Lowest | 1028.846 |
| Middle | 1024.038 |
| Highest | 1024.038 |

Test plot as follows:


| | | | |
|------------|------|---------------|--------|
| Test mode: | GFSK | Test channel: | Lowest |
|------------|------|---------------|--------|




| | | | |
|------------|------|---------------|--------|
| Test mode: | GFSK | Test channel: | Middle |
|------------|------|---------------|--------|



| | | | |
|------------|------|---------------|---------|
| Test mode: | GFSK | Test channel: | Highest |
|------------|------|---------------|---------|




6.6 Power Spectral Density

| | |
|-------------------|--|
| Test Requirement: | RSS 210 A 8.2(b) |
| Test Method: | ANSI C63.10: 2009 |
| Test Setup: |  |
| Instruments Used: | Refer to section 5.10 for details. |
| Test Mode: | Transmitting with GFSK modulation. |
| Limit: | $\leq 8\text{dBm}$ |
| Test Results: | Pass |


| GFSK mode | | | |
|--------------|------------------------------|-------------|--------|
| Test channel | Power Spectral Density (dBm) | Limit (dBm) | Result |
| Lowest | -5.49 | ≤ 8.00 | Pass |
| Middle | -1.37 | ≤ 8.00 | Pass |
| Highest | -0.73 | ≤ 8.00 | Pass |

Test plot as follows:


| | | | |
|------------|------|---------------|--------|
| Test mode: | GFSK | Test channel: | Lowest |
|------------|------|---------------|--------|




| | | | |
|------------|------|---------------|--------|
| Test mode: | GFSK | Test channel: | Middle |
|------------|------|---------------|--------|



| | | | |
|------------|------|---------------|---------|
| Test mode: | GFSK | Test channel: | Highest |
|------------|------|---------------|---------|




6.7 Band Edge for RF Conducted Emissions


| | |
|-------------------|--|
| Test Requirement: | RSS 210 A 8.5 |
| Test Method: | ANSI C63.10: 2009 |
| Test Setup: |  <p>Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane</p> <p><i>Remark:</i> <i>Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</i></p> |
| Instruments Used: | Refer to section 5.10 for details. |
| Limit: | RSS 210 A 8.5 In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. |
| Test Mode: | Transmitting with GFSK modulation. |
| Test Results: | Pass |

Test plot as follows:


| | | | |
|------------|------|---------------|--------|
| Test mode: | GFSK | Test channel: | Lowest |
|------------|------|---------------|--------|



| | | | |
|------------|------|---------------|---------|
| Test mode: | GFSK | Test channel: | Highest |
|------------|------|---------------|---------|







6.8 RF Antenna Conducted Spurious Emissions

| | |
|-------------------|---|
| Test Requirement: | RSS 210 A 8.5 |
| Test Method: | ANSI C63.10: 2009 |
| Test Setup: |  <p>Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane</p> <p><i>Remark:</i> Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</p> |
| Instruments Used: | Refer to section 5.10 for details. |
| Limit: | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. |
| Test Mode: | Transmitting with GFSK modulation. |
| Test Results: | Pass |



Test plot as follows:



| | | | |
|------------|------|---------------|--------|
| Test mode: | GFSK | Test channel: | Lowest |
|------------|------|---------------|--------|









| | | | |
|------------|------|---------------|--------|
| Test mode: | GFSK | Test channel: | Middle |
|------------|------|---------------|--------|





| | | | |
|------------|------|---------------|---------|
| Test mode: | GFSK | Test channel: | Highest |
|------------|------|---------------|---------|





**Remark:**

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

6.9 Radiated Spurious Emission

6.9.1 Radiated Spurious Emission

| Test Requirement: | RSS-Gen Issue 4 | | | | | | | | | | |
|--|--|----------------------------------|-------------------------|------------|--------------------------|--|--|--|--|--|--|
| Test Method: | ANSI C63.10: 2009 & RSS-Gen Issue 4 | | | | | | | | | | |
| Test Site: | Measurement Distance: 3m (Semi-Anechoic Chamber) | | | | | | | | | | |
| Receiver Setup: | Frequency | Detector | RBW | VBW | Remark | | | | | | |
| | 0.009MHz-0.015MHz | Quasi-peak | 200Hz | 1kHz | Quasi-peak | | | | | | |
| | 0.015MHz-30MHz | Quasi-peak | 9kHz | 30kHz | Quasi-peak | | | | | | |
| | 30MHz-1GHz | Quasi-peak | 120 kHz | 300kHz | Quasi-peak | | | | | | |
| | Above 1GHz | Peak | 1MHz | 3MHz | Peak | | | | | | |
| | | Peak | 1MHz | 10Hz | Average | | | | | | |
| Limit: | Frequency | Field strength (microvolt/meter) | Limit (dBuV/m) | Remark | Measurement distance (m) | | | | | | |
| | 0.009MHz-0.490MHz | 2400/F(kHz) | - | Quasi-peak | 300 | | | | | | |
| | 0.490MHz-1.705MHz | 24000/F(kHz) | - | Quasi-peak | 30 | | | | | | |
| | 1.705MHz-30MHz | 30 | - | Quasi-peak | 30 | | | | | | |
| | 30MHz-88MHz | 100 | 40.0 | Quasi-peak | 3 | | | | | | |
| | 88MHz-216MHz | 150 | 43.5 | Quasi-peak | 3 | | | | | | |
| | 216MHz-960MHz | 200 | 46.0 | Quasi-peak | 3 | | | | | | |
| | 960MHz-1GHz | 500 | 54.0 | Quasi-peak | 3 | | | | | | |
| | Above 1GHz | 500 | 54.0 | Average | 3 | | | | | | |
| | | | 74.0 | Peak | 3 | | | | | | |
| Test Setup: | | | | | | | | | | | |
|  | | | | | | | | | | | |
|  | | | | | | | | | | | |
| Figure 1. Below 30MHz | | | Figure 2. 30MHz to 1GHz | | | | | | | | |





Figure 3. Above 1 GHz

| | |
|------------------------|--|
| Test Procedure: | <ol style="list-style-type: none"> The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to height 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. Test the EUT in the lowest channel (2402MHz), the middle channel (2440MHz), the Highest channel (2480MHz). The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. Repeat above procedures until all frequencies measured was complete. |
| Instruments Used: | Refer to section 5.10 for details. |
| Exploratory Test Mode: | Transmitting with GFSK modulation. Transmitting mode. |
| Final Test Mode: | For below 1GHz part, through pre-scan, the worst case is the lowest channel. Transmitting mode. Only the worst case is recorded in the report. |
| Test Results: | Pass |

Radiated Emission below 1GHz**30MHz~1GHz (QP)**

Test mode: Transmitting Vertical




Condition: RSS 210 3m 3142C Vertical

Job No. : 0109CR

Test mode: TX mode

| Freq | Cable | Ant | Preamp | Read | Limit | Over | | |
|------|--------|--------|--------|-------|-------|--------|--------|--------|
| | Loss | Factor | Factor | Level | | | Line | Limit |
| | MHz | dB | dB/m | dB | dBuV | dBuV/m | dBuV/m | dB |
| 1 | 34.28 | 0.60 | 16.31 | 27.34 | 31.72 | 21.29 | 40.00 | -18.71 |
| 2 | 43.51 | 0.68 | 11.56 | 27.31 | 35.35 | 20.28 | 40.00 | -19.72 |
| 3 | 55.22 | 0.80 | 7.92 | 27.28 | 37.75 | 19.19 | 40.00 | -20.81 |
| 4 | 176.27 | 1.36 | 9.75 | 26.79 | 24.81 | 9.13 | 43.50 | -34.37 |
| 5 | 684.75 | 2.87 | 21.48 | 27.43 | 23.62 | 20.54 | 46.00 | -25.46 |
| 6 | 900.15 | 3.60 | 23.20 | 26.78 | 22.23 | 22.25 | 46.00 | -23.75 |

| | | |
|------------|--------------|------------|
| Test mode: | Transmitting | Horizontal |
|------------|--------------|------------|



Condition: RSS 210 3m 3142C Horizontal

Job No. : 0109CR

Test mode: TX mode

| Freq | Cable | Ant | Preamp | Read | Limit | Over | Limit |
|------|--------|------|--------|-------|-------|--------|--------------|
| | Freq | Loss | Factor | Level | | | |
| | MHz | dB | dB/m | dB | dBuV | dBuV/m | dB |
| 1 | 30.00 | 0.60 | 18.70 | 27.36 | 22.56 | 14.50 | 40.00 -25.50 |
| 2 | 470.52 | 2.49 | 17.64 | 27.56 | 23.49 | 16.06 | 46.00 -29.94 |
| 3 | 614.21 | 2.73 | 20.20 | 27.52 | 23.47 | 18.88 | 46.00 -27.12 |
| 4 | 706.70 | 2.92 | 21.60 | 27.41 | 24.25 | 21.36 | 46.00 -24.64 |
| 5 | 824.60 | 3.31 | 22.40 | 27.16 | 24.25 | 22.80 | 46.00 -23.20 |
| 6 | 958.79 | 3.66 | 23.30 | 26.51 | 24.86 | 25.31 | 46.00 -20.69 |

| Transmitter Emission above 1GHz | | | | | | | | | |
|---------------------------------|-----------------|-----------------------|--------------------|-------------------|----------------|---------------------|-----------------|--------------|------|
| Test mode: | | GFSK | | Test channel: | | Lowest | | Remark: | Peak |
| Frequency (MHz) | Cable Loss (dB) | Antenna Factor (dB/m) | Preamp Factor (dB) | Read Level (dBuV) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization | |
| 3527.774 | 6.95 | 32.92 | 38.75 | 47.81 | 48.93 | 74 | -25.07 | Vertical | |
| 4804.000 | 6.42 | 34.70 | 39.24 | 48.69 | 50.57 | 74 | -23.43 | Vertical | |
| 5982.226 | 8.05 | 36.27 | 39.19 | 47.87 | 53.00 | 74 | -21.00 | Vertical | |
| 7206.000 | 8.92 | 35.63 | 39.07 | 46.42 | 51.90 | 74 | -22.10 | Vertical | |
| 9608.000 | 9.99 | 37.33 | 37.93 | 42.87 | 52.26 | 74 | -21.74 | Vertical | |
| 11323.540 | 10.35 | 38.14 | 38.38 | 43.51 | 53.62 | 74 | -20.38 | Vertical | |
| 3663.017 | 6.87 | 33.05 | 38.81 | 48.20 | 49.31 | 74 | -24.69 | Horizontal | |
| 4804.000 | 6.42 | 34.70 | 39.24 | 50.05 | 51.93 | 74 | -22.07 | Horizontal | |
| 5956.314 | 8.01 | 36.22 | 39.19 | 48.74 | 53.78 | 74 | -20.22 | Horizontal | |
| 7206.000 | 8.92 | 35.63 | 39.07 | 45.18 | 50.66 | 74 | -23.34 | Horizontal | |
| 9608.000 | 9.99 | 37.33 | 37.93 | 43.40 | 52.79 | 74 | -21.21 | Horizontal | |
| 11323.540 | 10.35 | 38.14 | 38.38 | 43.22 | 53.33 | 74 | -20.67 | Horizontal | |

| Test mode: | | GFSK | | Test channel: | | Middle | | Remark: | Peak |
|-----------------|-----------------|------------------------|--------------------|----------------------------|-------------------------------|----------------------|-----------------|--------------|------|
| Frequency (MHz) | Cable loss (dB) | Antenna factors (dB/m) | Preamp factor (dB) | Reading Level (dB μ V) | Emission Level (dB μ V/m) | Limit (dB μ V/m) | Over limit (dB) | Polarization | |
| 3589.562 | 6.92 | 32.99 | 38.78 | 48.11 | 49.24 | 74 | -24.76 | Vertical | |
| 4880.000 | 6.58 | 34.78 | 39.26 | 48.31 | 50.41 | 74 | -23.59 | Vertical | |
| 6016.949 | 8.08 | 36.28 | 39.18 | 48.42 | 53.60 | 74 | -20.40 | Vertical | |
| 7320.000 | 9.07 | 35.51 | 39.06 | 47.66 | 53.18 | 74 | -20.82 | Vertical | |
| 9760.000 | 9.90 | 37.80 | 37.84 | 42.09 | 51.95 | 74 | -22.05 | Vertical | |
| 11128.630 | 10.31 | 38.11 | 38.29 | 42.13 | 52.26 | 74 | -21.74 | Vertical | |
| 3589.562 | 6.92 | 32.99 | 38.78 | 48.13 | 49.26 | 74 | -24.74 | Horizontal | |
| 4880.000 | 6.58 | 34.78 | 39.26 | 48.28 | 50.38 | 74 | -23.62 | Horizontal | |
| 6016.949 | 8.08 | 36.28 | 39.18 | 48.45 | 53.63 | 74 | -20.37 | Horizontal | |
| 7320.000 | 9.07 | 35.51 | 39.06 | 45.25 | 50.77 | 74 | -23.23 | Horizontal | |
| 9760.000 | 9.90 | 37.80 | 37.84 | 42.51 | 52.37 | 74 | -21.63 | Horizontal | |
| 11372.800 | 10.36 | 38.15 | 38.41 | 43.72 | 53.82 | 74 | -20.18 | Horizontal | |



| Test mode: | | GFSK | | Test channel: | | Highest | | Remark: | | Peak |
|-----------------|-----------------|------------------------|--------------------|----------------------------|-------------------------------|----------------------|-----------------|--------------|--|------|
| Frequency (MHz) | Cable loss (dB) | Antenna factors (dB/m) | Preamp factor (dB) | Reading Level (dB μ V) | Emission Level (dB μ V/m) | Limit (dB μ V/m) | Over limit (dB) | Polarization | | |
| 3620.861 | 6.90 | 33.02 | 38.79 | 47.90 | 49.03 | 74 | -24.97 | Vertical | | |
| 4960.000 | 6.76 | 34.86 | 39.29 | 48.30 | 50.63 | 74 | -23.37 | Vertical | | |
| 5982.226 | 8.05 | 36.27 | 39.19 | 48.31 | 53.44 | 74 | -20.56 | Vertical | | |
| 7440.000 | 9.23 | 35.43 | 39.05 | 44.71 | 50.32 | 74 | -23.68 | Vertical | | |
| 9920.000 | 9.81 | 38.27 | 37.75 | 41.93 | 52.26 | 74 | -21.74 | Vertical | | |
| 11323.540 | 10.35 | 38.14 | 38.38 | 43.44 | 53.55 | 74 | -20.45 | Vertical | | |
| 3678.952 | 6.87 | 33.06 | 38.82 | 47.78 | 48.89 | 74 | -25.11 | Horizontal | | |
| 4960.000 | 6.76 | 34.86 | 39.29 | 48.08 | 50.41 | 74 | -23.59 | Horizontal | | |
| 6016.949 | 8.08 | 36.28 | 39.18 | 48.42 | 53.60 | 74 | -20.40 | Horizontal | | |
| 7440.000 | 9.23 | 35.43 | 39.05 | 44.50 | 50.11 | 74 | -23.89 | Horizontal | | |
| 9920.000 | 9.81 | 38.27 | 37.75 | 41.96 | 52.29 | 74 | -21.71 | Horizontal | | |
| 11128.630 | 10.31 | 38.11 | 38.29 | 42.13 | 52.26 | 74 | -21.74 | Horizontal | | |

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

6.10 Restricted bands around fundamental frequency

| | | | |
|-------------------|--|--------------------|------------------|
| Test Requirement: | RSS-Gen Issue 4 | | |
| Test Method: | ANSI C63.10: 2009 & RSS-Gen Issue 4 | | |
| Test Site: | Measurement Distance: 3m (Semi-Anechoic Chamber) | | |
| Limit: | Frequency | Limit (dBuV/m @3m) | Remark |
| | 30MHz-88MHz | 40.0 | Quasi-peak Value |
| | 88MHz-216MHz | 43.5 | Quasi-peak Value |
| | 216MHz-960MHz | 46.0 | Quasi-peak Value |
| | 960MHz-1GHz | 54.0 | Quasi-peak Value |
| | Above 1GHz | 54.0 | Average Value |
| | | 74.0 | Peak Value |
| Test Setup: | | | |




Figure 1. 30MHz to 1GHz





Figure 2. Above 1 GHz

| | |
|-------------------|--|
| Test Procedure: | <ol style="list-style-type: none">a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel.g. Test the EUT in the lowest channel , the Highest channel.h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.i. Repeat above procedures until all frequencies measured was complete. |
| Instruments Used: | Refer to section 5.10 for details |
| Test Mode: | Transmitting with GFSK modulation. Transmitting mode. |
| Test Results: | Pass |

Test plot as follows:

| | | | | | | |
|------------|------|---------------|--------|---------|------|----------|
| Test mode: | GFSK | Test channel: | Lowest | Remark: | Peak | Vertical |
|------------|------|---------------|--------|---------|------|----------|

Data: 235



Site : chamber

Condition: RSS 210 PK 3m Vertical


Job No: : 0109CR

Mode: : 2402 Band edge BLE

| | Freq | Cable Loss | Ant Factor | Preamp Factor | Read Level | Limit Level | Limit Line | Over Limit |
|------|---------|------------|------------|---------------|------------|-------------|------------|------------|
| | MHz | dB | dB/m | dB | dBuV | dBuV/m | dBuV/m | dB |
| 1 | 2390.00 | 4.90 | 32.35 | 38.46 | 46.91 | 45.70 | 74.00 | -28.30 |
| 2 pp | 2402.29 | 4.92 | 32.41 | 38.46 | 76.99 | 75.86 | 74.00 | 1.86 |

| | | | | | | |
|------------|------|---------------|--------|---------|------|------------|
| Test mode: | GFSK | Test channel: | Lowest | Remark: | Peak | Horizontal |
|------------|------|---------------|--------|---------|------|------------|

Data: 237



Site : chamber

Condition: RSS 210 PK 3m Horizontal


Job No: : 0109CR

Mode: : 2402 Band edge BLE

| | Freq | Cable Loss | Ant Factor | Preamp Factor | Read Level | Limit Level | Limit Line | Over Limit |
|------|---------|------------|------------|---------------|------------|-------------|------------|------------|
| 1 | 2388.10 | 4.90 | 32.33 | 38.46 | 54.17 | 52.94 | 74.00 | -21.06 |
| 2 | 2390.00 | 4.90 | 32.35 | 38.46 | 48.51 | 47.30 | 74.00 | -26.70 |
| 3 pp | 2402.29 | 4.92 | 32.41 | 38.46 | 80.65 | 79.52 | 74.00 | 5.52 |

| | | | | | | |
|------------|------|---------------|--------|---------|---------|----------|
| Test mode: | GFSK | Test channel: | Lowest | Remark: | Average | Vertical |
|------------|------|---------------|--------|---------|---------|----------|

Data: 236



Site : chamber

Condition: RSS 210 AV 3m Vertical


Job No: : 0109CR

Mode: : 2402 Band edge BLE

| | Freq | Cable Loss | Ant Factor | Preamp Factor | Read Level | Limit Level | Limit Line | Over Limit |
|------|---------|------------|------------|---------------|------------|-------------|------------|------------|
| | MHz | dB | dB/m | | dBuV | dBuV/m | dBuV/m | dB |
| 1 | 2390.00 | 4.90 | 32.35 | 38.46 | 34.42 | 33.21 | 54.00 | -20.79 |
| 2 pp | 2402.19 | 4.92 | 32.41 | 38.46 | 62.19 | 61.06 | 54.00 | 7.06 |

| | | | | | | |
|------------|------|---------------|--------|---------|---------|------------|
| Test mode: | GFSK | Test channel: | Lowest | Remark: | Average | Horizontal |
|------------|------|---------------|--------|---------|---------|------------|

Data: 238



Site : chamber

Condition: RSS 210 AV 3m Horizontal


Job No: : 0109CR

Mode: : 2402 Band edge BLE

| | Freq | Cable Loss | Ant Factor | Preamp Factor | Read Level | Limit Level | Limit Line | Over Limit |
|------|---------|------------|------------|---------------|------------|-------------|------------|------------|
| 1 | 2390.00 | 4.90 | 32.35 | 38.46 | 33.94 | 32.73 | 54.00 | -21.27 |
| 2 pp | 2402.19 | 4.92 | 32.41 | 38.46 | 61.39 | 60.26 | 54.00 | 6.26 |

| | | | | | | |
|------------|------|---------------|---------|---------|------|----------|
| Test mode: | GFSK | Test channel: | Highest | Remark: | Peak | Vertical |
|------------|------|---------------|---------|---------|------|----------|

Data: 233



Site : chamber

Condition: RSS 210 PK 3m Vertical


Job No: : 0109CR

Mode: : 2480 Band edge BLE

| | | Cable Freq | Ant Loss | Preamp Factor | Read Level | Limit Level | Over Line | Over Limit | |
|------|---------|---------------|-------------|------------------|---------------|----------------|--------------|---------------|----|
| | | MHz | dB | dB/m | dB | dBuV | dBuV/m | dBuV/m | dB |
| 1 pp | 2479.71 | 5.02 | 32.44 | 38.47 | 81.42 | 80.41 | 74.00 | 6.41 | |
| 2 | 2483.50 | 5.03 | 32.44 | 38.47 | 46.15 | 45.15 | 74.00 | -28.85 | |

| | | | | | | |
|------------|------|---------------|---------|---------|------|------------|
| Test mode: | GFSK | Test channel: | Highest | Remark: | Peak | Horizontal |
|------------|------|---------------|---------|---------|------|------------|

Data: 231



Site : chamber

Condition: RSS 210 PK 3m Horizontal


Job No: : 0109CR

Mode: : 2480 Band edge BLE

| | Cable | Ant | Preamp | Read | Limit | Over | |
|------|---------|--------|--------|-------|-------|-------|--------------|
| Freq | Loss | Factor | Factor | Level | Level | Line | Limit |
| 1 pp | 2479.76 | 5.02 | 32.44 | 38.47 | 88.95 | 87.94 | 74.00 13.94 |
| 2 | 2483.50 | 5.03 | 32.44 | 38.47 | 48.31 | 47.31 | 74.00 -26.69 |

| | | | | | | |
|------------|------|---------------|---------|---------|---------|----------|
| Test mode: | GFSK | Test channel: | Highest | Remark: | Average | Vertical |
|------------|------|---------------|---------|---------|---------|----------|

Data: 234



Site : chamber

Condition: RSS 210 AV 3m Vertical

Job No: : 0109CR


Mode: : 2480 Band edge BLE

| | Freq | Cable Loss | Ant Factor | Preamp Factor | Read Level | Limit Level | Limit Line | Over Limit |
|------|---------|------------|------------|---------------|------------|-------------|------------|------------|
| | MHz | dB | dB/m | | dBuV | dBuV/m | dBuV/m | dB |
| 1 pp | 2480.01 | 5.02 | 32.44 | 38.47 | 63.84 | 62.83 | 54.00 | 8.83 |
| 2 | 2483.50 | 5.03 | 32.44 | 38.47 | 34.79 | 33.79 | 54.00 | -20.21 |



| | | | | | | |
|------------|------|---------------|---------|---------|---------|------------|
| Test mode: | GFSK | Test channel: | Highest | Remark: | Average | Horizontal |
|------------|------|---------------|---------|---------|---------|------------|

Data: 232



Site : chamber

Condition: RSS 210 AV 3m Horizontal

Job No: : 0109CR

Mode: : 2480 Band edge BLE

| | Cable | Ant | Preamp | Read | Limit | Over | | |
|------|---------|--------|--------|-------|-------|--------|--------|--------|
| Freq | Loss | Factor | Factor | Level | Level | Line | Limit | |
| | MHz | dB | dB/m | dB | dBuV | dBuV/m | dBuV/m | dB |
| 1 pp | 2480.06 | 5.02 | 32.44 | 38.47 | 69.64 | 68.63 | 54.00 | 14.63 |
| 2 | 2483.50 | 5.03 | 32.44 | 38.47 | 38.77 | 37.77 | 54.00 | -16.23 |

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

7 Photographs - EUT Test Setup

Test model No.: TH100

7.1 Conducted Emissions



7.2 Radiated Emission





8 Photographs - EUT Constructional Details

Test model No.: TH100

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1501000109CR