



Test Report No.: PBJ-NQN2411050214RF01



# TEST REPORT FOR WLAN TESTING

Report No.: PBJ-NQN2411050214RF01

Product Name: Edge Computing Gateway

Product Model: IG902-FQ39

Series Model: IG904-FQ39


Brand Name: inhand

Applicant: Beijing InHand Networks Technology Co., Ltd.

Manufacturer: Beijing InHand Networks Technology Co., Ltd.

Specification: FCC Part 15 Subpart C (2023)

FCC ID: 2AANY-IG902FQ39

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                                              |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| Prepared by Simon Wang<br>Engineer / Mobile Department                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Approved by Luke Lu<br>Manager / Mobile Department                                                           |
| <br>Date: Oct. 21, 2024                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | <br>Date: Oct. 21, 2024 |
| <small>This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <a href="http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/">http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/</a> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.</small> |                                                                                                              |

## CONTENTS

|                                                          |           |
|----------------------------------------------------------|-----------|
| <b>1. GENERAL INFORMATION.....</b>                       | <b>2</b>  |
| 1.1 NOTES OF THE TEST REPORT .....                       | 2         |
| 1.2 INFORMATION ABOUT THE TESTING LABORATORY .....       | 2         |
| 1.3 APPLICANT'S DETAILS .....                            | 2         |
| 1.4 MANUFACTURER'S DETAILS .....                         | 3         |
| 1.5 TEST ENVIRONMENT .....                               | 3         |
| <b>2. DESCRIPTION OF THE DEVICE UNDER TEST .....</b>     | <b>4</b>  |
| 2.1 FINAL EQUIPMENT BUILD STATUS .....                   | 4         |
| 2.2 DESCRIPTION OF TEST MODES .....                      | 6         |
| 2.3 EUT OPERATING CONDITIONS .....                       | 7         |
| 2.4 SUPPORT EQUIPMENT .....                              | 7         |
| <b>3. REFERENCE SPECIFICATION.....</b>                   | <b>8</b>  |
| <b>4. KEY TO NOTES AND RESULT CODES .....</b>            | <b>8</b>  |
| <b>5. RESULT SUMMARY .....</b>                           | <b>9</b>  |
| <b>6. TEST RESULT .....</b>                              | <b>10</b> |
| 6.1 PEAK POWER OUTPUT .....                              | 10        |
| 6.2 6DB BANDWIDTH.....                                   | 11        |
| 6.3 TRANSMITTER POWER SPECTRAL DENSITY .....             | 12        |
| 6.4 CONDUCTED OUT OF BAND EMISSION MEASUREMENT .....     | 13        |
| 6.5 BAND-EDGE MEASUREMENT .....                          | 14        |
| 6.6 SPURIOUS RADIATED EMISSIONS .....                    | 15        |
| 6.7 AC POWER LINE CONDUCTED EMISSION .....               | 20        |
| <b>7. MEASUREMENT UNCERTAINTIES .....</b>                | <b>22</b> |
| <b>8. TEST EQUIPMENTS .....</b>                          | <b>23</b> |
| <b>APPENDIX A – TEST DATA OF CONDUCTED EMISSION.....</b> | <b>24</b> |
| DUTY CYCLE .....                                         | 24        |
| CONDUCTED POWER.....                                     | 25        |
| 6DB BANDWIDTH .....                                      | 26        |
| 99% BANDWIDTH .....                                      | 30        |
| TRANSMITTER POWER SPECTRAL DENSITY .....                 | 34        |
| CONDUCTED OUT OF BAND EMISSION MEASUREMENT .....         | 38        |
| BAND EDGE MEASUREMENT .....                              | 41        |
| <b>APPENDIX B – TEST DATA OF RADIATED EMISSION .....</b> | <b>43</b> |



## **1. GENERAL INFORMATION**

### **1.1 Notes of the test report**

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of BV 7Layers Communications Technology (Shenzhen) Co., Ltd. The test results relate only to individual items of the samples which have been tested. The certification and accreditation identifiers used in this report shall not be applicable to the tested or calibrated samples thereof. The manufacturer shall not mark the tested samples or items (or a separate part of the item) with the identifiers of certification and accreditation to mislead relevant parties about the tested samples or items.

### **1.2 Information about the testing laboratory**

|                      |                                                                                                                                  |
|----------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Company:             | BV 7Layers Communications Technology (Shenzhen) Co., Ltd                                                                         |
| Address:             | Room B37, Warehouse A5, No.3 Chiwan 4th Road, Zhaoshang Street, Nanshan District Shenzhen, Guangdong, People's Republic of China |
| City:                | Shenzhen                                                                                                                         |
| Country or Region:   | P.R.China                                                                                                                        |
| Tel:                 | +86 755 8869 6566                                                                                                                |
| Fax:                 | +86 755 8869 6577                                                                                                                |
| Email:               | <a href="mailto:customerservice.sw@bureauveritas.com">customerservice.sw@bureauveritas.com</a>                                   |
| Designation Number:  | CN1171                                                                                                                           |
| Registration number: | 525120                                                                                                                           |

### **1.3 Applicant's details**

|                    |                                                                                |
|--------------------|--------------------------------------------------------------------------------|
| Company:           | Beijing InHand Networks Technology Co., Ltd.                                   |
| Address:           | Room 501, floor 5, building 3, yard 18, ziyue road, chaoyang district, Beijing |
| City:              | Beijing                                                                        |
| Country or Region: | China                                                                          |
| Contacted person:  | GuJichi                                                                        |
| Tel:               | 15281366255                                                                    |
| Email:             | <a href="mailto:gujc@inhand.com.cn">gujc@inhand.com.cn</a>                     |



## 1.4 Manufacturer's details

|                    |                                                                                |
|--------------------|--------------------------------------------------------------------------------|
| Company:           | Beijing InHand Networks Technology Co., Ltd.                                   |
| Address:           | Room 501, floor 5, building 3, yard 18, ziyue road, chaoyang district, Beijing |
| City:              | Beijing                                                                        |
| Country or Region: | China                                                                          |
| Contacted person:  | GuJichi                                                                        |
| Tel:               | 15281366255                                                                    |
| Email:             | gujc@inhand.com.cn                                                             |

## 1.5 Test Environment

|                                 |            |
|---------------------------------|------------|
| Date of Receipt of test sample: | 2024/9/13  |
| Testing Start Date:             | 2024/9/14  |
| Testing End Date:               | 2024/10/21 |

| Environmental Data: | Temperature (°C) | Humidity (%) |
|---------------------|------------------|--------------|
| Ambient             | 25               | 40           |
| Maximum Extreme     | 75               | ---          |
| Minimum Extreme     | -25              | ---          |

|                                          |    |
|------------------------------------------|----|
| Normal Supply Voltage (V d.c.):          | 12 |
| Maximum Extreme Supply Voltage (V d.c.): | 48 |
| Minimum Extreme Supply Voltage (V d.c.): | 12 |



## **2. DESCRIPTION OF THE DEVICE UNDER TEST**

### **2.1 Final Equipment Build Status**

|                              |                                           |
|------------------------------|-------------------------------------------|
| Frequency Band:              | 2.412GHz~2.462GHz                         |
| Number of Channel For 20MHz: | 11                                        |
| Number of Channel For 40MHz: | 7                                         |
| Modulation Type:             | 802.11b<br>802.11g<br>802.11n (HT20/HT40) |
| Power Supply:                | DC supply                                 |
| Antenna gain:                | For Power/PSD: 3.0dBi(max)                |
| Directional Gain:            | N/A                                       |
| Software Revision:           | V2.1                                      |
| Hardware Revision:           | V1.1                                      |
| SN/IMEI:                     | GL9022425014925/868517074320205           |
| Antenna type:                | Refer to Note                             |
| Antenna connector:           | Refer to Note                             |

NOTE1: Directional gain =  $10 \log[(10^{G1/10} + 10^{G2/10} + \dots + 10^{GN/10}) / N_{ANT}]$  dBi(Uncorrelated)



**Note: Antenna requirement (FCC Part 15.203)**

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

- The antenna(s) of the EUT are permanently attached.
- There are no provisions for connection to an external antenna.

Note: The antenna provides to the EUT, please refer to the following table:

| Brand | Model | Antenna gain | Frequency band   | Antenna type   | Connector Type |
|-------|-------|--------------|------------------|----------------|----------------|
| N/A   | N/A   | 3.0dBi       | 2.4GHz~2.4835GHz | Sucker antenna | RP-SMA-J1.5    |

NOTE1: The antenna gain is provided by the customer and involved in the calculation and influence of the test results. Our laboratory takes the value declared by the customer as the criterion, and the customer is responsible for the antenna gain value. Manufacturers ensure that their designs will not be modified by the user or third party's arbitrary antenna parameters and performance.

NOTE2: Refer to section F of 662911 D01, Categorization as Correlated or Completely Uncorrelated:

*Correlated* signals include, but are not limited to, signals transmitted in any of the following modes:

- *Any transmit beamforming mode*, whether fixed or adaptive (e.g., phased array modes, closed loop MIMO modes, Transmitter Adaptive Antenna modes, Maximum Ratio Transmission (MRT) modes, and Statistical Eigen Beamforming (EBF) modes).
- *Cyclic Delay Diversity (CDD) modes*, also known as *Cyclic Shift Diversity (CSD)* (including modes for 802.11n and later devices to communicate with legacy 802.11 devices). In CDD modes, the same digital data is carried by each transmit antenna, but with different cyclic delays. The signals are highly correlated at any one frequency, though not necessarily at zero time delay. In particular, correlations tend to be high over the bandwidths specified for in-band PSD measurements in FCC rule parts that require reductions in PSD when directional gain exceeds a threshold.

*Completely uncorrelated* signals include those transmitted in the following modes, if they are not combined with any correlated modes, such as beamforming:

- Space Time Block Codes (STBC) or Space Time Codes (STC) for which different digital data is carried by each transmit antenna during any symbol period (e.g., WiMAX Matrix A [Alamouti coding]).
- Spatial Multiplexing MIMO (SM-MIMO), for which independent data streams are sent to each transmit antenna (e.g., WiMAX Matrix B). WiMAX Matrix C, which adds diversity, also produces uncorrelated transmit signals.

EUT is STBC MODE. the output signals are Uncorrelated.

transmissions directional gain is calculated as:

a) For power, the directional gain calculation is following.

$$\text{Directional gain} = 10 \log[(10^{G^1}/10 + 10^{G^2}/10 + \dots + 10^{G^N}/10)^2/N_{\text{ANT}}] \text{ dBi}$$

b) For PSD, the directional gain calculation is following.

$$\text{Directional gain} = 10 \log[(10^{G^1}/10 + 10^{G^2}/10 + \dots + 10^{G^N}/10)^2/N_{\text{ANT}}] \text{ dBi}$$



## 2.2 Description of Test Modes

11 channels are provided to this EUT:

| CHANNEL | FREQ. (MHz) | CHANNEL | FREQ. (MHz) |
|---------|-------------|---------|-------------|
| 1       | 2412        | 7       | 2442        |
| 2       | 2417        | 8       | 2447        |
| 3       | 2422        | 9       | 2452        |
| 4       | 2427        | 10      | 2457        |
| 5       | 2432        | 11      | 2462        |
| 6       | 2437        | ---     | ---         |

### 2.2.1 Test Mode Applicability and Tested Channel Detail

| EUT CONFIGURE<br>MODE | APPLICABLE TO |       |     |      | DESCRIPTION |
|-----------------------|---------------|-------|-----|------|-------------|
|                       | RE≥1G         | RE<1G | PLC | APCM |             |
| -                     | √             | √     | √   | √    | -           |

Where

RE ≥ 1G: Radiated Emission above 1GHz

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

#### Radiated Emission Test (Above 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

| AVAILABLE<br>CHANNEL | TESTED CHANNEL | MODULATION TYPE | DATA RATE (Mbps) |
|----------------------|----------------|-----------------|------------------|
| 1 to 11              | 1,6,11         | 802.11b         | 1                |
| 1 to 11              | 1,6,11         | 802.11g         | 6                |
| 1 to 11              | 1,6,11         | 802.11n 20      | MCS0             |
| 3 to 9               | 3,6,9          | 802.11n 40      | MCS0             |

#### Radiated Emission Test (Below 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.



| AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TYPE | DATA RATE (Mbps) |
|-------------------|----------------|-----------------|------------------|
| 1 to 11           | 1,6,11         | 802.11b         | 1                |
| 1 to 11           | 1,6,11         | 802.11g         | 6                |
| 1 to 11           | 1,6,11         | 802.11n 20      | MCS0             |
| 3 to 9            | 3,6,9          | 802.11n 40      | MCS0             |

**Power Line Conducted Emission Test:**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

| AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TYPE | DATA RATE (Mbps) |
|-------------------|----------------|-----------------|------------------|
| 1 to 11           | 6              | 802.11b         | 1                |

**Antenna Port Conducted Measurement:**

This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

| AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TYPE | DATA RATE (Mbps) |
|-------------------|----------------|-----------------|------------------|
| 1 to 11           | 1,6,11         | 802.11b         | 1                |
| 1 to 11           | 1,6,11         | 802.11g         | 6                |
| 1 to 11           | 1,6,11         | 802.11n 20      | MCS0             |
| 3 to 9            | 3,6,9          | 802.11n 40      | MCS0             |

**2.3 EUT Operating conditions**

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

**2.4 Support Equipment**

The following support equipment was used to exercise the DUT during testing:N/A



### **3. REFERENCE SPECIFICATION**

| Specification           | Version          | Title                                                                                                                                                                                             |
|-------------------------|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FCC Part15<br>Subpart C | 2023             | Intentional radiators                                                                                                                                                                             |
| ANSI C63.10             | 2013             | Standard of Procedures for Compliance Testing of<br>Unlicensed Wireless Devices                                                                                                                   |
| KDB 558074D01<br>v05r02 | April 2,<br>2019 | Guidance for compliance measurements on Digital<br>transmission system, frequency hopping spread spectrum<br>system, and hybrid system devices operating under section<br>15.247 of the FCC rules |

### **4. KEY TO NOTES AND RESULT CODES**

| Code | Meaning                                                                                  |
|------|------------------------------------------------------------------------------------------|
| PASS | Test result shows that the requirements of the relevant specification have been met.     |
| FAIL | Test result shows that the requirements of the relevant specification have not been met. |
| N/T  | Test case is not tested.                                                                 |



## **5. RESULT SUMMARY**

| No. | Test case                                  | Reference     | Verdict                    | Test Lab |
|-----|--------------------------------------------|---------------|----------------------------|----------|
| 1   | Transmitter Output Power                   | 15.247(b)(3)  | Pass                       | A        |
| 2   | 6dB Bandwidth                              | 15.247(a)(2)  | Pass                       | A        |
| 3   | Transmitter Power Spectral Density         | 15.247(e)     | Pass                       | A        |
| 4   | Conducted Out of band emission measurement | 15.247(d)     | Pass                       | A        |
| 5   | Band Edge                                  | 15.247(d)     | Pass                       | A        |
| 6   | Antenna requirement                        | 15.203        | Pass(refer to section 2.1) | A        |
| 7   | Spurious Radiated Emissions                | 15.205/15.209 | Pass                       | A        |
| 8   | AC Power line Conducted Emission           | 15.207        | Pass                       | A        |

**Lab A:**

BV 7Layers Communications Technology (Shenzhen) Co. Ltd

**Lab Address:**Room B37, Warehouse A5, No.3 Chiwan 4th Road, Zhaoshang Street, Nanshan District  
Shenzhen, Guangdong, People's Republic of China**Accredited Test Lab Cert 3939.01**

The FCC Site Registration No. is 525120; The Designation No. is CN1171.



## **6. TEST RESULT**

### **6.1 Peak Power Output**

#### **6.2.1 Test limit**

Part15.247 (b) (3)

The maximum permissible conducted output power is 1 Watt.

#### **6.2.2 Test Procedure Used**

ANSI C63.10-2013 – Section 11.9.1.3

ANSI C63.10-2013 – Section 11.9.2.3.2

KDB 558074 D01 v05r02 – Section 8.3.1.3

#### **6.2.3 Test Settings**

Peak Power Measurement


The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

#### **6.2.4 Test Setup**

The EUT and measurement equipment were set up as shown in the diagram below.



#### **6.2.5 Test result**

The test results are shown in Appendix A.



## 6.2 6dB Bandwidth

### 6.1.1 Test limit

Part15.247 (a) (2)

The minimum permissible 6dB bandwidth is 500 kHz

### 6.1.2 Test Procedure Used

ANSI C63.10-2013 – Section 11.8.2 Option 2

KDB 558074 D01 v05r02 – Section 8.2

### 6.1.3 Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to  $X = 6$ . The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.

2. RBW = 100 kHz

3. VBW  $\geq 3 \times$  RBW

4. Detector = Peak


5. Trace mode = max hold

6. Sweep = auto couple

7. The trace was allowed to stabilize

### 6.1.4 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



### 6.1.5 Test result

The test results are shown in Appendix A.



## 6.3 Transmitter Power Spectral Density

### 6.3.1 Test limit

Part15.247 (e)

The maximum permissible power spectral density is 8.0dBm in any 3 kHz band.

### 6.3.2 Test Procedure Used

ANSI C63.10-2013 – Section 11.10.2 Method PKPSD


KDB 558074 D01 v05r02 – Section 8.4

### 6.3.3 Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 30 kHz
4. VBW = 100 kHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

### 6.3.4 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



### 6.3.5 Test result

The test results are shown in Appendix A.



## 6.4 Conducted Out of band emission measurement

### 6.4.1 Test limit

Part 15.247(d): The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth.

### 6.4.2 Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3

KDB 558074 D01 v05r02 – Section 8.5

### 6.4.3 Reference level measurement Settings

Establish a reference level by using the following procedure:


- Set instrument center frequency to DTS channel center frequency.
- Set the span to  $\geq 1.5$  MHz
- Set the RBW = 100 kHz.
- Set the VBW  $\geq 300$  kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum PSD level.

### 6.4.4 Test Settings

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW  $\geq 300$  kHz.
- Detector = peak.
- Set span to encompass the spectrum to be examined
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

### 6.4.5 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



### 6.4.6 Test result

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement. The test results are shown in Appendix A.



## 6.5 Band-edge measurement

### 6.5.1 Test limit

Part 15.247(d): The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth.

### 6.5.2 Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3

KDB 558074 D01 v05r02 – Section 8.7.2

### 6.5.3 Reference level measurement Settings

Establish a reference level by using the following procedure:


- Set instrument center frequency to DTS channel center frequency.
- Set the span to  $\geq 1.5$  MHz
- Set the RBW = 100 kHz.
- Set the VBW  $\geq 300$  kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum PSD level.

### 6.5.4 Test Settings

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW  $\geq 300$  kHz.
- Detector = peak.
- Set span to encompass the spectrum to be examined
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

### 6.5.5 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



### 6.5.6 Test result

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement. The test results are shown in Appendix A.



## 6.6 Spurious Radiated Emissions

### 6.6.1 Test Description

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

### 6.6.2 Test limit

Part15.205, 15.209, 15.247(d)

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in below Table per Section 15.209. The spectrum shall be investigated from the lowest radio frequency signal generated in the device

| Frequency [MHz] | Field strength<br>[ $\mu\text{V/m}$ ] | Measured Distance<br>[meters] |
|-----------------|---------------------------------------|-------------------------------|
| 0.009~0.490     | 2400/F(kHz)                           | 300                           |
| 0.490~1.705     | 24000/F(kHz)                          | 30                            |
| 1.705~30.0      | 30                                    | 30                            |
| 30~88           | 100                                   | 3                             |
| 88~216          | 150                                   | 3                             |
| 216~960         | 200                                   | 3                             |
| Above 960       | 500                                   | 3                             |

**Radiated Limits**

Part15.35(b):

There is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit

**Used conversion factor: Limit (dB $\mu\text{V/m}$ ) = 20 log (Limit ( $\mu\text{V/m}$ )/1 $\mu\text{V/m}$ )**

| Frequency [MHz]                                                            | Detector   | Unit (dB $\mu\text{V/m}$ ) |
|----------------------------------------------------------------------------|------------|----------------------------|
| 30~88                                                                      | Quasi-peak | 40.0                       |
| 88~216                                                                     | Quasi-peak | 43.5                       |
| 216~960                                                                    | Quasi-peak | 46.0                       |
| 960~1000                                                                   | Quasi-peak | 54.0                       |
| 1000~5th harmonic of the highest frequency<br>or 40GHz, whichever is lower | Average    | 54.0                       |
|                                                                            | Peak       | 74.0                       |

**Conversion Radiated limits**



### 6.6.3 Test Procedure Used

ANSI C63.10-2013

#### For Radiated emission below 30MHz

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Both X and Y axes of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and recorded the reading with Maximum Hold Mode.

#### NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer complied the following setting:

| Frequency  | RBW       |
|------------|-----------|
| 9-150kHz   | 200-300Hz |
| 0.15-30MHz | 9-10kHz   |

- Signals below 30MHz are not recorded in the report because they are lower than the limits by more than 20dB.

#### For Radiated emission above 30MHz

- The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground in chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to quasi-peak detect function and recorded the reading with Maximum Hold Mode when the test frequency is below 1 GHz.
- The test-receiver system was set to peak and average detector and recorded the reading with Maximum Hold Mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

**For the radiated emission test above 1GHz:**

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Average detection (AV) at frequency above 1GHz. If duty cycle of test signal is < 98%, the duty factor need added to measured value.
4. All modes of operation were investigated and the worst-case emissions are reported.

**6.6.4 Test Settings****Average Field Strength Measurements**

| Frequency | Detector         |
|-----------|------------------|
| <1000MHz  | Quasi-peak       |
| >1000MHz  | Peak and average |

**Peak Field Strength Measurements**

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW is set depending on measurement frequency, as specified in following table


| Frequency  | RBW        |
|------------|------------|
| 9-150kHz   | 200-300Hz  |
| 0.15-30MHz | 9-10kHz    |
| 30-1000MHz | 100-120kHz |
| >1000MHz   | 1MHz       |

3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize




## 6.6.5 Test Setup

### For Radiated emission below 30MHz




### For Radiated emission 30MHz to 1GHz





## For Radiated emission above 1GHz



### 6.6.6 Test result

The test results are shown in Appendix B.



## 6.7 AC Power line Conducted Emission

### 6.7.1 Test limit

FCC Part15.207

| Frequency of Emission<br>(MHz) | Conducted Limit (dBuV) |            |
|--------------------------------|------------------------|------------|
|                                | Quasi-peak             | Average    |
| 0.15-0.5                       | 66 to 56 *             | 56 to 46 * |
| 0.5-5                          | 56                     | 46         |
| 5-30                           | 60                     | 50         |

\* Decreases with the logarithm of the frequency.

The measurement is made according to ANSI C63.10-2013

### 6.7.2 Test Procedures

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.


c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

**NOTE:** The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

The EUT shall test under the power AC120V/240V/60Hz.



### 6.7.3 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 6.7.4 Test result

The test results are shown in AppendixB.



## **7. MEASUREMENT UNCERTAINTIES**

| Items                                      | Uncertainty    |        |
|--------------------------------------------|----------------|--------|
| 6dB Bandwidth                              | 3kHz           |        |
| Peak power output                          | 0.67dB         |        |
| Transmitter Power Spectral Density         | 0.75dB         |        |
| Band edge compliance                       | 1.20dB         |        |
| Conducted Out of band emission measurement | 30MHz~1GHz     | 2.83dB |
|                                            | 1GHz~12.75GHz  | 2.50dB |
|                                            | 12.75GHz~25GHz | 2.75dB |
| Spurious Radiated Emissions                | 30MHz~200MHz   | 4.88dB |
|                                            | 200MHz~1GHz    | 4.87dB |
|                                            | 1GHz~18GHz     | 4.58dB |
|                                            | 18GHz~40GHz    | 4.35dB |
| AC Power line Conducted Emission           | 3.92dB         |        |

Note 1: According to the test specification limit (The test results fully compliance with the test standard limit requirements)

Note 2: According to test specification limits plus uncertainties (The test results exceed the standard limit requirements and meet the standard requirements after adding the system uncertainty)

Note 3: Test operation mode is Note 1



## 8. TEST EQUIPMENTS

| No. | Name/ Model                                   | Manufacturer    | S/N              | Cal date   | Cal Due date |
|-----|-----------------------------------------------|-----------------|------------------|------------|--------------|
| 1.  | Spectrum Analyzer / FSV                       | ROHDE & SCHWARZ | 101065           | 2024.06.21 | 2025.06.20   |
| 2.  | Signal Analyzer / N9020A                      | Agilent         | MY48010771       | 2024.03.06 | 2025.03.05   |
| 3.  | Bluetooth Test Set / MT8852B                  | Anritsu         | 1329003          | 2024.06.21 | 2025.06.20   |
| 4.  | Power Divider / 11667A                        | HP              | 19632            | 2024.06.21 | 2025.06.20   |
| 5.  | Signal Generator / SMBV100A                   | R&S             | 260910           | 2024.06.21 | 2025.06.20   |
| 6.  | Power Meter E4416A                            | Agilent         | MY52370013       | 2024.03.06 | 2025.03.05   |
| 7.  | Power Sensor E9323A                           | Agilent         | MY52150008       | 2024.03.06 | 2025.03.05   |
| 8.  | Temperature chamber / SH241                   | ESPEC           | 92013758         | 2024.06.21 | 2025.06.20   |
| 9.  | Fully-Anechoic Chamber / 12.65m×8.03m×7.50m   | FRANKONIA       | -----            | -----      | -----        |
| 10. | Semi-Anechoic/Chamber / 23.18m×16.88m×9.60m   | FRANKONIA       | ---              | -----      | -----        |
| 11. | Turn table Diameter:1m                        | FRANKONIA       | -----            | -----      | -----        |
| 12. | Turn table Diameter:5m                        | FRANKONIA       | -----            | -----      | -----        |
| 13. | Antenna master FAC(MA4.0)                     | MATURO          | -----            | -----      | -----        |
| 14. | Antenna master SAC(MA4.0)                     | MATURO          | -----            | -----      | -----        |
| 15. | Shielding room / 9.080m×5.255m×3.525m         | FRANKONIA       | -----            | -----      | -----        |
| 16. | Double-Ridged Waveguide Horn Antenna / HF 907 | R&S             | 100512           | 2024.06.21 | 2025.06.20   |
| 17. | Double-Ridged Waveguide Horn Antenna / HF 907 | R&S             | 100513           | 2024.06.21 | 2025.06.20   |
| 18. | Ultra log antenna / HL562                     | R&S             | 100016           | 2024.06.21 | 2025.06.20   |
| 19. | Receive antenna /3160-09                      | SCHWARZ-BECK    | 002058-002       | 2024.06.21 | 2025.06.20   |
| 20. | EMI test receiver / ESI 40                    | R&S             | 100015           | 2024.06.21 | 2025.06.20   |
| 21. | EMI test receiver / ESCS30                    | R&S             | 100029           | 2024.06.21 | 2025.06.20   |
| 22. | Receive antenna / HL562                       | R&S             | 100167           | 2024.06.21 | 2025.06.20   |
| 23. | AMN / ENV216                                  | R&S             | 3560.6550.12     | 2024.06.21 | 2025.06.20   |
| 24. | WLAN AP WIA3300-20                            | SKSpruce        | 8152017060700339 | ---        | ---          |
| 25. | Notebook E470c                                | Lenovo          | PF10UZW7         | ---        | ---          |
| 26. | Loop Antenna                                  | R&S             | 100340           | 2024.08.21 | 2025.08.20   |
| 27. | FCC auto test system / RT9200BW-2             | Radiosky        | V2.05            | /          | /            |
| 28. | EMI test software / EMC32                     | R&S             | V10.20.01        | /          | /            |



## APPENDIX A – TEST DATA OF CONDUCTED EMISSION

Offset 1.2dB = Temporary antenna connector loss 0.2dB+ Cable loss 1.0dB

### Duty Cycle

| Modulation Type | Frequency (MHz) | Antenna | Plot  | Duty Cycle | Correction Factor(dB) |
|-----------------|-----------------|---------|-------|------------|-----------------------|
| 802.11b         | 2412            | Chain0  | Fig.1 | 99.91%     | 0                     |
| 802.11g         | 2412            | Chain0  | Fig.2 | 95.87%     | 0.18                  |
| 802.11n HT20    | 2412            | Chain0  | Fig.3 | 95.39%     | 0.21                  |
| 802.11n HT40    | 2422            | Chain0  | Fig.4 | 93.28%     | 0.30                  |

Note: Correction Factor=10\*log (1/Duty Cycle)




Fig.1




Fig.2




Fig.3




Fig.4

**Conducted power**

| Test Mode    | Tones/<br>RU Index | Frequency<br>(MHz) | Antenna | Peak power<br>output<br>(dBm) | Average<br>power output<br>(dBm) | EIRP<br>(dBm) |
|--------------|--------------------|--------------------|---------|-------------------------------|----------------------------------|---------------|
| 802.11b      | NA                 | 2412               | Chain0  | 18.37                         | 15.34                            | 18.34         |
| 802.11b      | NA                 | 2437               | Chain0  | 18.50                         | 15.49                            | 18.49         |
| 802.11b      | NA                 | 2462               | Chain0  | 18.59                         | 15.55                            | 18.55         |
| 802.11g      | NA                 | 2412               | Chain0  | 24.12                         | 15.31                            | 18.31         |
| 802.11g      | NA                 | 2437               | Chain0  | 24.26                         | 15.10                            | 18.10         |
| 802.11g      | NA                 | 2462               | Chain0  | 24.22                         | 15.17                            | 18.17         |
| 802.11n HT20 | NA                 | 2412               | Chain0  | 23.95                         | 15.20                            | 18.20         |
| 802.11n HT20 | NA                 | 2437               | Chain0  | 24.41                         | 15.38                            | 18.38         |
| 802.11n HT20 | NA                 | 2462               | Chain0  | 24.25                         | 15.45                            | 18.45         |
| 802.11n HT40 | NA                 | 2422               | Chain0  | 24.60                         | 15.10                            | 18.10         |
| 802.11n HT40 | NA                 | 2437               | Chain0  | 24.89                         | 15.60                            | 18.60         |
| 802.11n HT40 | NA                 | 2452               | Chain0  | 24.99                         | 15.53                            | 18.53         |





## 6dB Bandwidth

| Test Mode    | Antenna | 6 dB bandwidth(MHz) |              |               |
|--------------|---------|---------------------|--------------|---------------|
|              |         | Channel No.1        | Channel No.6 | Channel No.11 |
|              |         | 2412MHz             | 2437MHz      | 2462MHz       |
| 802.11b      | Chain0  | 8.53                | 9.60         | 8.52          |
| 802.11g      | Chain0  | 16.38               | 16.28        | 16.26         |
| 802.11n HT20 | Chain0  | 17.28               | 17.54        | 17.29         |


| Test Mode    | Antenna | 6 dB bandwidth(MHz) |              |              |
|--------------|---------|---------------------|--------------|--------------|
|              |         | Channel No.3        | Channel No.6 | Channel No.9 |
|              |         | 2422MHz             | 2437MHz      | 2452MHz      |
| 802.11n HT40 | Chain0  | 35.84               | 35.90        | 35.31        |

### Test Mode: 802.11b




Mode:802.11b Frequency:2412MHz Ant:Chain0

Mode:802.11b Frequency:2437MHz Ant:Chain0




Mode:802.11b Frequency:2462MHz Ant:Chain0

### Test Mode: 802.11g






Test Mode: 802.11n HT20



Mode:802.11n HT20 Frequency:2412MHz Ant:Chain0

Mode:802.11n HT20 Frequency:2437MHz Ant:Chain0




Mode:802.11n HT20 Frequency:2462MHz Ant:Chain0



BUREAU  
VERITAS


Test Report No.: PBJ-NQN2411050214RF01

Test Mode: 802.11n HT40



Mode:802.11n HT40 Frequency:2422MHz Ant:Chain0

Mode:802.11n HT40 Frequency:2437MHz Ant:Chain0



Mode:802.11n HT40 Frequency:2452MHz Ant:Chain0




## 99% Bandwidth


| Test Mode    | Antenna | 99% bandwidth(MHz) |              |               |
|--------------|---------|--------------------|--------------|---------------|
|              |         | Channel No.1       | Channel No.6 | Channel No.11 |
|              |         | 2412MHz            | 2437MHz      | 2462MHz       |
| 802.11b      | Chain0  | 14.823             | 14.779       | 14.789        |
| 802.11g      | Chain0  | 16.850             | 16.786       | 16.835        |
| 802.11n HT20 | Chain0  | 17.957             | 17.957       | 17.911        |

| Test Mode    | Antenna | 99% bandwidth(MHz) |              |              |
|--------------|---------|--------------------|--------------|--------------|
|              |         | Channel No.3       | Channel No.6 | Channel No.9 |
|              |         | 2422MHz            | 2437MHz      | 2452MHz      |
| 802.11n HT40 | Chain0  | 36.364             | 36.214       | 36.199       |


Test Mode: 802.11b



Mode:802.11b Frequency:2412MHz Ant:Chain0




Mode:802.11b Frequency:2437MHz Ant:Chain0



Mode:802.11b Frequency:2462MHz Ant:Chain0




Test Mode: 802.11g






Test Mode: 802.11n HT20



Mode:802.11n HT20 Frequency:2412MHz Ant:Chain0


Mode:802.11n HT20 Frequency:2437MHz Ant:Chain0



Mode:802.11n HT20 Frequency:2462MHz Ant:Chain0




Test Mode: 802.11n HT40



Mode:802.11n HT40 Frequency:2422MHz Ant:Chain0

Mode:802.11n HT40 Frequency:2437MHz Ant:Chain0



Mode:802.11n HT40 Frequency:2452MHz Ant:Chain0




## Transmitter Power Spectral Density

| Test Mode    | Antenna | Tones | Power Density(dBm/3KHz) |              |               |
|--------------|---------|-------|-------------------------|--------------|---------------|
|              |         |       | Channel No.1            | Channel No.6 | Channel No.11 |
|              |         |       | 2412MHz                 | 2437MHz      | 2462MHz       |
| 802.11b      | Chain0  | NA    | -6.624                  | -7.716       | -7.411        |
| 802.11g      | Chain0  | NA    | -8.338                  | -8.511       | -8.515        |
| 802.11n HT20 | Chain0  | NA    | -8.683                  | -8.407       | -8.322        |


| Test Mode    | Antenna | Tones | Power Density(dBm/3KHz) |              |              |
|--------------|---------|-------|-------------------------|--------------|--------------|
|              |         |       | Channel No.3            | Channel No.6 | Channel No.9 |
|              |         |       | 2422MHz                 | 2437MHz      | 2452MHz      |
| 802.11n HT40 | Chain0  | NA    | -10.453                 | -10.271      | -10.160      |

Test Mode: 802.11b



Mode:802.11b Frequency:2412MHz Ant:Chain0


Mode:802.11b Frequency:2437MHz Ant:Chain0



Mode:802.11b Frequency:2462MHz Ant:Chain0



Test Mode: 802.11g




Mode:802.11g Frequency:2412MHz Ant:Chain0

Mode:802.11g Frequency:2437MHz Ant:Chain0

Mode:802.11g Frequency:2462MHz Ant:Chain0




Test Mode: 802.11n HT20






Test Mode: 802.11n HT40






## Conducted Out of band emission measurement


Test Mode: 802.11b



Mode:802.11b Frequency:2412MHz Ant:Chain0




Mode:802.11b Frequency:2437MHz Ant:Chain0




Mode:802.11b Frequency:2462MHz Ant:Chain0

Test Mode: 802.11g



Mode:802.11g Frequency:2412MHz Ant:Chain0




Mode:802.11g Frequency:2437MHz Ant:Chain0





BUREAU  
VERITAS


Test Report No.: PBJ-NQN2411050214RF01



Test Mode: 802.11n HT20



Test Mode: 802.11n HT40






BUREAU  
VERITAS


Test Report No.: PBJ-NQN2411050214RF01

## Band edge measurement


Test Mode: 802.11b



Test Mode: 802.11g



Test Mode: 802.11n HT20






BUREAU  
VERITAS

Test Report No.: PBJ-NQN2411050214RF01

Test Mode: 802.11n HT40






## APPENDIX B – TEST DATA OF RADIATED EMISSION

Note: The worst channel results are reflected in the report.

Note: The scanned graph represents the maximum of both horizontal and vertical polarizations and is not a single horizontal or vertical polarization scan.

### Radiated Emission Band Edge




### Radiated Emission Band Edge

Channel No.:1

Test Mode: 802.11b

Polarization: V



### Radiated Emission Band Edge

Channel No.:1


Test Mode: 802.11b



BUREAU  
VERITAS

Test Report No.: PBJ-NQN2411050214RF01

Polarization: H




Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11b

Polarization: V




Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11b

Polarization: H




Radiated Emission Band Edge

Channel No.:1

Test Mode: 802.11g

Polarization: V



Radiated Emission Band Edge

Channel No.:1


Test Mode: 802.11g

Polarization: H



BUREAU  
VERITAS

Test Report No.: PBJ-NQN2411050214RF01




Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11g

Polarization: V



Radiated Emission Band Edge

Channel No.:11


Test Mode: 802.11g

Polarization: H




BUREAU  
VERITAS


Test Report No.: PBJ-NQN2411050214RF01



Radiated Emission Band Edge  
Channel No.:1  
Test Mode: 802.11n(HT20)  
Polarization: V



Radiated Emission Band Edge  
Channel No.:1  
Test Mode: 802.11n(HT20)  
Polarization: H




Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11n(HT20)

Polarization: V




Radiated Emission Band Edge


Channel No.:11

Test Mode: 802.11n(HT20)

Polarization: H



Radiated Emission Band Edge  
Channel No.:3  
Test Mode: 802.11n(HT40)  
Polarization: V




Radiated Emission Band Edge  
Channel No.:3  
Test Mode: 802.11n(HT40)  
Polarization: H



BUREAU  
VERITAS

Test Report No.: PBJ-NQN2411050214RF01




Radiated Emission Band Edge

Channel No.:9

Test Mode: 802.11n(HT40)

Polarization: V



Radiated Emission Band Edge

Channel No.:9

Test Mode: 802.11n(HT40)

Polarization: H

**Sample Calculations**

After comparison, the worst case attitude is EUT lay down.

**Determining Spurious Emissions Levels**

A “reference path loss” is established and the  $A_{Rpl}$  is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{mea}} + A_{Rpl}$$

Sample calculation:  $(19.42 \text{ dB}\mu\text{V/m}) = (38.32 \text{ dB}\mu\text{V}) + (-18.9 \text{ dB/m})$ , the corresponding frequency is 47.8965 MHz.

**For 802.11b Channel No.:1**

| Frequency(MHz) | Result(dBuV/m) | ARpl (dB) | Pmea (dBuV/m) | Polarity | Limit (dBuV/m) | Margin (dB) |
|----------------|----------------|-----------|---------------|----------|----------------|-------------|
| 47.8965        | 19.42          | -18.9     | 38.32         | Vertical | 40             | 20.58       |
| 86.0175        | 9.68           | -20.8     | 30.48         | Vertical | 40             | 30.32       |
| 96.5905        | 9.49           | -19.6     | 29.09         | Vertical | 43.5           | 34.01       |
| 199.9925       | 17.5           | -19.9     | 37.4          | Vertical | 43.5           | 26          |
| 436.3815       | 24.79          | -13.5     | 38.29         | Vertical | 46             | 21.21       |
| 696.002        | 19.34          | -8.8      | 28.14         | Vertical | 46             | 26.66       |

**For 802.11g Channel No.:1**

| Frequency(MHz) | Result(dBuV/m) | ARpl (dB) | Pmea (dBuV/m) | Polarity | Limit (dBuV/m) | Margin (dB) |
|----------------|----------------|-----------|---------------|----------|----------------|-------------|
| 47.8965        | 19.16          | -18.9     | 38.06         | Vertical | 40             | 20.84       |
| 85.581         | 9.9            | -20.9     | 30.8          | Vertical | 40             | 30.1        |
| 163.0355       | 8.21           | -22.1     | 30.31         | Vertical | 43.5           | 35.29       |
| 199.9925       | 17.57          | -19.9     | 37.47         | Vertical | 43.5           | 25.93       |
| 436.3815       | 24.84          | -13.5     | 38.34         | Vertical | 46             | 21.16       |
| 915.8525       | 16.16          | -5.3      | 21.46         | Vertical | 46             | 29.84       |

**For 802.11n(HT20) Channel No.:1**

| Frequency(MHz) | Result(dBuV/m) | ARpl (dB) | Pmea (dBuV/m) | Polarity | Limit (dBuV/m) | Margin (dB) |
|----------------|----------------|-----------|---------------|----------|----------------|-------------|
| 47.8965        | 19.12          | -18.9     | 38.02         | Vertical | 40             | 20.88       |
| 71.9525        | 8.97           | -22.2     | 31.17         | Vertical | 40             | 31.03       |
| 165.897        | 11.02          | -22       | 33.02         | Vertical | 43.5           | 32.48       |
| 199.9925       | 18.36          | -19.9     | 38.26         | Vertical | 43.5           | 25.14       |
| 436.333        | 19.11          | -13.5     | 32.61         | Vertical | 46             | 26.89       |
| 941.8          | 16.34          | -5.1      | 21.44         | Vertical | 46             | 29.66       |