

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	HOVER-1 CHARGER SELF BALANCING SCOOTER
Model Name	H1-RGPRO-BLK
Series Model	H1-RGPRO, H1-RGPRO-XXX, DSA-RGPRO-BLK, DSA-RGPRO, DSA-RGPRO-XXX, DSA-AH-RGPRO-BLK, DSA-AH-RGPRO, DSA-AH-RGPRO-XXX, H1-COL-BLK, H1-COL, H1-COL-XXX, DSA-COL-BLK, DSA-COL, DSA-COL-XXX, DSA-AH-COL-BLK, DSA-AH-COL, DSA-AH-COL-XXX
FCC ID	2AANZRANGERPRO

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

BLE:

$P_t = -0.029 \text{ dBm} = 0.99 \text{ mW}$

The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation $\text{SAR} = (0.99 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.480(\text{GHz})}] = 0.31 < 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

BR/EDR:

$P_t = -2.248 \text{ dBm} = 0.60 \text{ mW}$

The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation $\text{SAR} = (0.60 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.480(\text{GHz})}] = 0.19 < 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

4. CONCLUSION

The SAR evaluation is not required.