FCC ID: 2AAOE14BTH450

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] * $[\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is \leq 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

Transmit Frequency	Modulation Mode	Max Conducted Power	Result	1-g SAR
(GHz)		(mW)	calculation	
2.402	GFSK	1.94	0.60	3.0
2.441	GFSK	1.82	0.57	3.0
2.480	GFSK	1.67	0.53	3.0
2.402	π/4-DQPSK	1.37	0.42	3.0
2.441	π/4-DQPSK	1.29	0.40	3.0
2.480	π/4-DQPSK	1.17	0.37	3.0
2.402	8DPSK	1.51	0.47	3.0
2.441	8DPSK	1.41	0.44	3.0
2.480	8DPSK	1.29	0.41	3.0

Conclusion:

I noty wany

For the max result : 0.60≤ 3.0 for 1-g SAR extremity SAR, No SAR is required.

Signature

Company Name: NINGBO EMTEK CO., LTD.

1F Building 4, 1177#, Lingyun Road, National Hi-Tech Zone, Ningbo, Zhejiang, China