

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

```
eirp = pt x gt = (EXd)^2/30gt where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- 10^{((dBuV/m)/20)}/10^6

d = measurement distance in meters (m) ---0.2m

So pt = (EXd)^2/30 x gt

Field strength = 93.95dBuV/m @3m

Ant gain =0dBi, so Ant numeric gain= 1

So pt={ [10^{(93.95/20)}/10^6 x 3]^2/30x1 }x1000 mW = 0.74mW

So (0.74 \text{ mW}/5mm)x \sqrt{2.48} = 0.23 < 3
```

Then SAR evaluation is not required