

Report No.: BTEK231102001AE001
Page: 1 of 96
FCC ID: 2AAOSFLS-BASS

TEST REPORT

Application No.:	BTEK231102001AE
Applicant:	Shenzhen FLS Electronic Co., LTD
Address of Applicant:	4/F, Building 3, Xinxueziwei Industrial Area Shajing, Bao'an District, Shenzhen city Guangdong Province, China
Manufacturer:	Shenzhen FLS Electronic Co., LTD
Address of Manufacturer:	4/F, Building 3, Xinxueziwei Industrial Area Shajing, Bao'an District, Shenzhen city Guangdong Province, China
Factory:	Shenzhen FLS Electronic Co., LTD
Address of Factory:	4/F, Building 3, Xinxueziwei Industrial Area Shajing, Bao'an District, Shenzhen city Guangdong Province, China
Equipment Under Test (EUT):	
EUT Name:	Bluetooth Speaker
Model No.:	LFS-Bass
Trade Mark:	LFS
Standard(s) :	47 CFR Part 15, Subpart C 15.247
Date of Receipt:	2023-11-02
Date of Test:	2023-11-03 to 2023-11-16
Date of Issue:	2023-11-16
Test Result:	Pass*

* In the configuration tested, the EUT complied with the standards specified above.



Damon Su
EMC Laboratory Manager



Revision Record

Version	Chapter	Date	Modifier	Remark
01		2023-11-16		Original

Authorized for issue by

	Carl Yang /Project Engineer	
	David Zhuang /Reviewer	



2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass
Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence		N/A	47 CFR Part 15, Subpart C 15.247(a)(1),(g),(h)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Conducted Peak Output Power		ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(1)	Pass
20dB Bandwidth		ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.247(a)(1)	Pass
Carrier Frequencies Separation		ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass
Hopping Channel Number		ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Dwell Time		ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2013) Section 7.8.6	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2013) Section 7.8.8	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions (Below 1GHz)		ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions (Above 1GHz)		ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass

Note:

E.U.T./EUT means Equipment Under Test.

Pass means the test result passed the test standard requirement, please find the detailed decision rule in the report relative section.



3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information.....	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units	6
4.3 Measurement Uncertainty	6
4.4 Test Location.....	7
4.5 Deviation from Standards.....	7
4.6 Abnormalities from Standard Conditions	7
5 Equipment List.....	8
6 Radio Spectrum Technical Requirement	11
6.1 Antenna Requirement	11
6.1.1 Test Requirement:	11
6.1.2 Conclusion	11
6.2 Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence	12
6.2.1 Test Requirement:	12
6.2.2 Conclusion	13
7 Radio Spectrum Matter Test Results	15
7.1 Conducted Peak Output Power.....	19
7.1.1 E.U.T. Operation.....	19
7.1.2 Test Mode Description	19
7.1.3 Test Setup Diagram	19
7.1.4 Measurement Procedure and Data.....	20
7.2 20dB Bandwidth	21
7.2.1 E.U.T. Operation.....	21
7.2.2 Test Mode Description	21
7.2.3 Test Setup Diagram.....	21
7.2.4 Measurement Procedure and Data.....	21
7.3 Carrier Frequencies Separation	22
7.3.1 E.U.T. Operation.....	22
7.3.2 Test Mode Description	22
7.3.3 Test Setup Diagram	22
7.3.4 Measurement Procedure and Data.....	22
7.4 Hopping Channel Number.....	23
7.4.1 E.U.T. Operation.....	23
7.4.2 Test Mode Description	23
7.4.3 Test Setup Diagram	23
7.4.4 Measurement Procedure and Data.....	23
7.5 Dwell Time.....	24
7.5.1 E.U.T. Operation.....	24
7.5.2 Test Mode Description	24
7.5.3 Test Setup Diagram	24
7.5.4 Measurement Procedure and Data.....	24
7.6 Conducted Band Edges Measurement.....	25
7.6.1 E.U.T. Operation	25



7.6.2	Test Mode Description	25
7.6.3	Test Setup Diagram	26
7.6.4	Measurement Procedure and Data.....	26
7.7	Conducted Spurious Emissions	27
7.7.1	E.U.T. Operation.....	27
7.7.2	Test Mode Description	27
7.7.3	Test Setup Diagram	27
7.7.4	Measurement Procedure and Data.....	28
7.8	Radiated Emissions which fall in the restricted bands	29
7.8.1	E.U.T. Operation	29
7.8.2	Test Mode Description	29
7.8.3	Test Setup Diagram	30
7.8.4	Measurement Procedure and Data.....	30
7.9	Radiated Spurious Emissions (Below 1GHz).....	32
7.9.1	E.U.T. Operation	32
7.9.2	Test Mode Description	32
7.9.3	Test Setup Diagram	33
7.9.4	Measurement Procedure and Data.....	33
7.10	Radiated Spurious Emissions (Above 1GHz)	36
7.10.1	E.U.T. Operation	36
7.10.2	Test Mode Description	36
7.10.3	Test Setup Diagram	37
7.10.4	Measurement Procedure and Data	38
8	Test Setup Photo	44
9	EUT Constructional Details (EUT Photos)	44
10	Appendix.....	45



4 General Information

4.1 Details of E.U.T.

Power supply:	DC 3.7V by rechargeable lithium-ion battery(500mAh) and recharged by USB port.
Cable(s):	/
Frequency Range:	2402MHz to 2480MHz
Bluetooth Version:	V5.0
This test report is for classic mode.	
Spectrum Spread Technology:	Frequency Hopping Spread Spectrum(FHSS)
Hopping Channel Type:	Adaptive Frequency Hopping systems
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channels:	79
Channel Spacing:	1MHz
Sample Type:	Portable device
Antenna Type:	PCB Antenna
Antenna Gain:	1.9dBi
Hardware Version	LFS-TG-6965E--V1.0
Software and Firmware Version	V2.6.3
Sample No.:	BTEK231102001AE-01

Remark: The information in this section is provided by the applicant or manufacturer, BANTEK is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Adapter	JW	4441	/

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	± 3.12 dB
Conducted Peak Output Power	± 0.76 dB
20dB Bandwidth	$\pm 3\%$
Carrier Frequencies Separation	$\pm 7.3 \times 10^{-8}$
Hopping Channel Number	$\pm 7.3 \times 10^{-8}$
Dwell Time	$\pm 0.4\%$
Conducted Band Edges Measurement	± 0.8 dB
Conducted Spurious Emissions	± 0.8 dB
Radiated Emissions which fall in the restricted bands	± 5.1 dB (1GHz-6GHz); ± 5.2 dB(above 6GHz)
Radiated Spurious Emissions (Below 1GHz)	± 5.1 dB
Radiated Spurious Emissions (Above 1GHz)	± 5.1 dB (1GHz-6GHz); ± 5.2 dB(above 6GHz)



4.4 Test Location

All tests were performed at:

Shenzhen BANTEK Testing Co., Ltd.,

A5&A6, Building B1&B2, No.45 Gangtou Road, Bogang Community, Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Tel:0755-2334 4200 Fax: 0755-2334 4200

FCC Registration Number: 264293

Designation Number: CN1356

No tests were sub-contracted.

4.5 Deviation from Standards

None

4.6 Abnormalities from Standard Conditions

None



5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Shielding Room	YIHENG ENECLTRONIC	9*5*3.3	YH-BT-220304-04	2022-03-03	2025-03-02
EMI Test Receiver	Rohde&Schwarz	ESCI	101021	2023-06-12	2024-06-11
Measurement Software	Fara	EZ EMC Ver. FA-03A2	N/A	N/A	N/A
LISN	Rohde&Schwarz	ENV216	101472	2023-06-12	2024-06-11
LISN	Schwarzbeck	NSLK 8128	05127	2023-06-12	2024-06-11

RF Conducted					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
Shielding Room	YIHENG ENECLTRONIC	5.5*3.1*3	YH-BT-220304-03	2022-03-03	2025-03-02
EXA Signal Analyzer	KEYSIGHT	N9020A	MY54230486	2023-06-12	2024-06-11
DC Power Supply	E3632A	E3642A	KR75304416	2023-06-12	2024-06-11
Attenuator	RswTech	SMA-JK-6dB	N/A	2023-06-12	2024-06-11
Attenuator	RswTech	SMA-JK-3dB	N/A	2023-06-12	2024-06-11
RF Control Unit	Techy	TR1029-1	N/A	2023-06-12	2024-06-11
RF Sensor Unit	Techy	TR1029-2	N/A	2023-06-12	2024-06-11
WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW 500	141258	2023-06-12	2024-06-11
MXG Vector Signal Generator	Agilent	N5182A	US46240522	2023-06-12	2024-06-11
Programmable Temperature&Humidity Chamber	GRT	GR-HWX1000	GR22051001	2023-06-12	2024-06-11
Measurement Software	TACHOY	RF TestSoft	N/A	N/A	N/A

RSE					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	YIHENG ENECLTRONIC	966	YH-BT-220304-01	2022-03-03	2025-03-02
EMI Test Receiver	Rohde&Schwarz	ESCI	100694	2023-06-12	2024-06-11
TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	01324	2022-06-15	2025-06-14
Pre-Amplifier	Schwarzbeck	BBV 9745	#180	2023-06-12	2024-06-11
Measurement Software	Fara	EZ EMC Ver. FA-03A2	N/A	2023-06-12	2024-06-11
EXA Signal Analyzer	Keysight	N9020A	MY54440290	2023-06-12	2024-06-11
Horn Antenna	Schwarzbeck	BBHA 9120D	02695	2022-06-15	2025-06-14
Pre-Amplifier	Tonscend	TAP0118045	AP20K806109	2023-06-12	2024-06-11
Horn Antenna	SCHWARZBECK	BBHA9170	1157	2022-06-15	2025-06-14



Low Noise Pre-amplifier	SKET	LNPA-1840G-50	SK2022032902	2023-06-12	2024-06-11
Signal analyzer	ROHDE&SCHWARZ	FSQ40	100010	2023-06-12	2024-06-11
Loop Antenna	ETS	6502	00201177	2022-06-15	2025-06-14



General used equipment

Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
Humidity/Temperature/B arometric Pressure Indicator	KUMAR	F132	N/A	2023-06-12	2024-06-11
Humidity/Temperature/B arometric Pressure Indicator	KUMAR	F132	N/A	2023-06-12	2024-06-11



6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:


Testing shall be performed using the highest gain antenna of each combination of licence-exempt transmitter and antenna type, with the transmitter output power set at the maximum level. When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna manufacturer.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the Chip in PCB and no consideration of replacement. The best case gain of the antenna is 1.9dBi.



6.2 Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence

6.2.1 Test Requirement:

47 CFR Part 15, Subpart C 15.247(a)(1),(g),(h)

Limit:

Standard Requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.


Compliance for section 15.247(a)(1):

According to Technical Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- > Number of shift register stages: 9
- > Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- > Longest sequence of zeros: 8 (non-inverted signal)


Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

According to Technical Specification, the receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g):

According to Technical Specification, the system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h):

According to Technical specification, the system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

The system is designed not have the ability to coordinate with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

6.2.2 Conclusion

Standard Requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1):

According to Technical Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

> Number of shift register stages: 9

> Length of pseudo-random sequence: $2^9 - 1 = 511$ bits

> Longest sequence of zeros: 8 (non-inverted signal)

Linear Feedback Shift Register for Generation of the PRBS sequence

Each frequency used equally on the average by each transmitter.

According to Technical Specification, the receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any transmitters and shift frequencies in synchronization with the transmitted signals.



Compliance for section 15.247(g):

According to Technical Specification, the system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h):

According to Technical specification, the system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

The system is designed not have the ability to coordinate with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.



7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 22.2 °C


Humidity: 60.5 % RH

Atmospheric Pressure: 1010 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.1.3 Test Setup Diagram




7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50 μ H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor




Test Mode: 01; Line: Live line; Modulation:GFSK; ; Channel:Low



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2054	16.84	19.80	36.64	63.39	-26.75	QP	P	
2	0.2054	12.70	19.80	32.50	53.39	-20.89	AVG	P	
3	0.3141	17.67	19.82	37.49	59.86	-22.37	QP	P	
4	0.3141	13.95	19.82	33.77	49.86	-16.09	AVG	P	
5	0.4720	13.92	19.83	33.75	56.48	-22.73	QP	P	
6	0.4720	10.08	19.83	29.91	46.48	-16.57	AVG	P	
7	0.6584	13.28	19.90	33.18	56.00	-22.82	QP	P	
8	0.6584	9.65	19.90	29.55	46.00	-16.45	AVG	P	
9	0.7778	16.86	19.94	36.80	56.00	-19.20	QP	P	
10 *	0.7778	13.71	19.94	33.65	46.00	-12.35	AVG	P	
11	1.7746	11.23	20.06	31.29	56.00	-24.71	QP	P	
12	1.7746	7.94	20.06	28.00	46.00	-18.00	AVG	P	



Test Mode: 01; Line: Neutral Line; Modulation:GFSK; ; Channel:Low



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2031	16.90	19.81	36.71	63.48	-26.77	QP	P	
2	0.2031	12.53	19.81	32.34	53.48	-21.14	AVG	P	
3	0.3161	17.23	19.83	37.06	59.81	-22.75	QP	P	
4 *	0.3161	13.50	19.83	33.33	49.81	-16.48	AVG	P	
5	0.6384	13.17	19.90	33.07	56.00	-22.93	QP	P	
6	0.6384	9.55	19.90	29.45	46.00	-16.55	AVG	P	
7	0.9770	12.66	20.01	32.67	56.00	-23.33	QP	P	
8	0.9770	9.08	20.01	29.09	46.00	-16.91	AVG	P	
9	1.4977	12.02	20.05	32.07	56.00	-23.93	QP	P	
10	1.4977	8.52	20.05	28.57	46.00	-17.43	AVG	P	
11	2.2146	11.58	20.10	31.68	56.00	-24.32	QP	P	
12	2.2146	6.96	20.10	27.06	46.00	-18.94	AVG	P	



7.2 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(1)

Test Method: ANSI C63.10 (2013) Section 7.8.5

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.2.1 E.U.T. Operation


Operating Environment:

Temperature: 20.6 °C Humidity: 50.5 % RH Atmospheric Pressure: 1010 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

cable loss=0.83dB

Please Refer to Appendix for Details



7.3 20dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247(a)(1)
Test Method: ANSI C63.10 (2013) Section 7.8.7

7.3.1 E.U.T. Operation


Operating Environment:

Temperature: 20.6 °C Humidity: 50.5 % RH Atmospheric Pressure: 1010 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

cable loss=0.83dB

Please Refer to Appendix for Details



7.4 Carrier Frequencies Separation

Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)

Test Method: ANSI C63.10 (2013) Section 7.8.2

Limit:

2/3 of the 20dB bandwidth base on the transmission power is less than 0.125W.

7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 20.6 °C Humidity: 50.5 % RH Atmospheric Pressure: 1010 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

cable loss=0.83dB

Please Refer to Appendix for Details



7.5 Hopping Channel Number

Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)(iii)

Test Method: ANSI C63.10 (2013) Section 7.8.3

Limit:

Frequency range(MHz)	Number of hopping channels (minimum)
902-928	50 for 20dB bandwidth <250kHz
	25 for 20dB bandwidth ≥250kHz
2400-2483.5	15
5725-5850	75

7.5.1 E.U.T. Operation


Operating Environment:

Temperature: 20.6 °C Humidity: 50.5 % RH Atmospheric Pressure: 1010 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX_Hop mode _Keep the EUT in frequency hopping mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

cable loss=0.83dB

Please Refer to Appendix for Details



7.6 Dwell Time

Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)(iii)

Test Method: ANSI C63.10 (2013) Section 7.8.4

Limit:

Frequency(MHz)	Limit
902-928	0.4s within a 20s period(20dB bandwidth<250kHz)
	0.4s within a 10s period(20dB bandwidth≥250kHz)
2400-2483.5	0.4s within a period of 0.4s multiplied by the number of hopping channels
5725-5850	0.4s within a 30s period

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 20.6 °C


Humidity: 50.5 % RH

Atmospheric Pressure: 1010 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

cable loss=0.83dB

Please Refer to Appendix for Details



7.7 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 7.8.6

Limit:

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.7.1 E.U.T. Operation

Operating Environment:


Temperature: 20.6 °C Humidity: 50.5 % RH Atmospheric Pressure: 1010 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.
Final test	02	TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.



7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

cable loss=0.83dB

Please Refer to Appendix for Details



7.8 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 7.8.8

Limit:

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.1 E.U.T. Operation


Operating Environment:

Temperature: 20.6 °C Humidity: 50.5 % RH Atmospheric Pressure: 1010 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

cable loss=0.83dB

Please Refer to Appendix for Details



7.9 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.9.1 E.U.T. Operation

Operating Environment:


Temperature: 21.4 °C Humidity: 54.3 % RH Atmospheric Pressure: 1010 mbar

7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.



7.9.3 Test Setup Diagram



7.9.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Reading Level + Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Note: Level = Reading level + Factor

Test Mode: 01; Polarity: Horizontal; Modulation: GFSK; Channel: Low

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2310.000	67.40	-30.59	36.81	74.00	-37.19	peak	P
2	2390.000	69.68	-30.49	39.19	74.00	-34.81	peak	P
3	2400.000	77.94	-30.48	47.46	74.00	-26.54	peak	P

Test Mode: 01; Polarity: Vertical; Modulation: GFSK; Channel: Low

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2310.000	68.72	-30.59	38.13	74.00	-35.87	peak	P
2	2390.000	70.18	-30.49	39.69	74.00	-34.31	peak	P
3	2400.000	78.58	-30.48	48.10	74.00	-25.90	peak	P

Test Mode: 01; Polarity: Horizontal; Modulation: GFSK; Channel: High

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.500	80.16	-30.39	49.77	74.00	-24.23	peak	P
2	2500.000	71.58	-30.37	41.21	74.00	-32.79	peak	P

Test Mode: 01; Polarity: Vertical; Modulation: GFSK; Channel: High

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.500	80.17	-30.39	49.78	74.00	-24.22	peak	P
2	2500.000	70.17	-30.37	39.80	74.00	-34.20	peak	P



7.10 Radiated Spurious Emissions (Below 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.10.1 E.U.T. Operation

Operating Environment:


Temperature: 25.5 °C Humidity: 68.6 % RH Atmospheric Pressure: 1010 mbar

7.10.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.



7.10.3 Test Setup Diagram



7.10.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1) Through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.


2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Reading Level + Factor

3) Scan from 9kHz to 1 GHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.




Test Mode: 01; Polarity: Horizontal; Modulation: GFSK; Channel: High



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	120.6991	57.57	-18.88	38.69	43.50	-4.81	QP	300	122	P	
2 !	214.5141	59.27	-20.80	38.47	43.50	-5.03	QP	300	154	P	
3 !	267.5452	59.21	-18.63	40.58	46.00	-5.42	QP	100	145	P	
4	355.4272	54.54	-16.33	38.21	46.00	-7.79	QP	300	345	P	
5	483.9094	52.57	-13.85	38.72	46.00	-7.28	QP	300	86	P	
6	144.3345	52.88	-17.22	35.66	43.50	-7.84	QP	100	67	P	



Test Mode: 01; Polarity: Vertical; Modulation: GFSK; Channel: High



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	37.4164	53.17	-17.17	36.00	40.00	-4.00	QP	100	56	P	
2 !	119.8555	57.66	-18.91	38.75	43.50	-4.75	QP	100	49	P	
3 !	147.9214	56.27	-16.96	39.31	43.50	-4.19	QP	200	114	P	
4 !	215.2675	59.29	-20.71	38.58	43.50	-4.92	QP	100	332	P	
5 !	361.7137	57.82	-16.16	41.66	46.00	-4.34	QP	100	198	P	
6	485.6091	53.78	-13.84	39.94	46.00	-6.06	QP	300	166	P	



7.11 Radiated Spurious Emissions (Above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.11.1 E.U.T. Operation

Operating Environment:


Temperature: 21.4 °C Humidity: 54.3 % RH Atmospheric Pressure: 1010 mbar

7.11.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.



7.11.3 Test Setup Diagram



7.11.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

2) Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

3) The field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



TM01 / Polarization: Horizontal / Modulation: GFSK/ CH: L

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2915.407	69.36	-29.44	39.92	74.00	-34.08	peak	P
2	4276.588	67.52	-29.53	37.99	74.00	-36.01	peak	P
3	6086.090	65.07	-26.06	39.01	74.00	-34.99	peak	P
4	8644.981	70.76	-25.11	45.65	74.00	-28.35	peak	P
5	11046.690	68.31	-23.94	44.37	74.00	-29.63	peak	P
6	14218.192	70.00	-21.68	48.32	74.00	-25.68	peak	P

TM01 / Polarization: Vertical / Modulation: GFSK/ CH: L

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2972.395	66.86	-30.53	36.33	74.00	-37.67	peak	P
2	4312.977	67.92	-29.43	38.49	74.00	-35.51	peak	P
3	6352.661	68.09	-25.36	42.73	74.00	-31.27	peak	P
4	8577.139	70.40	-26.18	44.22	74.00	-29.78	peak	P
5	11285.823	67.10	-22.45	44.65	74.00	-29.35	peak	P
6	14956.137	71.63	-21.10	50.52	74.00	-23.48	peak	P

TM01 / Polarization: Horizontal / Modulation: GFSK/ CH: M

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2914.628	69.50	-29.20	40.29	74.00	-33.71	peak	P
2	4277.957	67.94	-29.18	38.76	74.00	-35.24	peak	P
3	6085.020	64.61	-24.49	40.13	74.00	-33.87	peak	P
4	8645.733	69.16	-24.85	44.31	74.00	-29.69	peak	P
5	11047.409	68.16	-23.96	44.21	74.00	-29.79	peak	P
6	14218.349	70.57	-21.71	48.87	74.00	-25.13	peak	P

TM01 / Polarization: Vertical / Modulation: GFSK/ CH: M

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2973.432	66.83	-30.24	36.59	74.00	-37.41	peak	P
2	4312.568	68.23	-28.18	40.05	74.00	-33.95	peak	P
3	6353.817	66.66	-25.70	40.96	74.00	-33.04	peak	P
4	8576.236	69.33	-25.95	43.38	74.00	-30.62	peak	P
5	11285.771	67.48	-23.31	44.18	74.00	-29.82	peak	P
6	14955.407	71.90	-20.84	51.06	74.00	-22.94	peak	P



TM01 / Polarization: Horizontal / Modulation: GFSK/ CH: H

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2915.405	70.52	-29.97	40.55	74.00	-33.71	peak	P
2	4277.968	68.52	-29.55	38.97	74.00	-35.24	peak	P
3	6085.995	64.57	-25.64	38.93	74.00	-33.87	peak	P
4	8646.877	69.89	-25.97	43.92	74.00	-29.69	peak	P
5	11046.555	67.78	-24.39	43.40	74.00	-29.79	peak	P
6	14218.861	71.20	-21.75	49.44	74.00	-25.13	peak	P

TM01 / Polarization: Vertical / Modulation: GFSK/ CH: H

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2972.789	67.42	-29.13	38.29	74.00	-35.71	peak	P
2	4314.062	68.12	-29.48	38.64	74.00	-35.36	peak	P
3	6354.188	67.20	-25.80	41.40	74.00	-32.60	peak	P
4	8576.503	69.27	-24.86	44.41	74.00	-29.59	peak	P
5	11286.329	68.07	-22.60	45.47	74.00	-28.53	peak	P
6	14955.237	70.00	-20.48	49.52	74.00	-24.48	peak	P

TM01 / Polarization: Horizontal / Modulation: $\pi/4$ DQPSK / CH: L

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2913.676	70.13	-28.87	41.26	74.00	-32.74	peak	P
2	4278.094	68.63	-29.02	39.61	74.00	-34.39	peak	P
3	6086.176	63.92	-25.66	38.26	74.00	-35.74	peak	P
4	8645.124	69.08	-25.50	43.58	74.00	-30.42	peak	P
5	11046.639	67.33	-23.88	43.44	74.00	-30.56	peak	P
6	14219.036	70.45	-20.14	50.31	74.00	-23.69	peak	P

TM01 / Polarization: Horizontal / Modulation: $\pi/4$ DQPSK / CH: L

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2972.513	66.53	-29.03	37.50	74.00	-36.50	peak	P
2	4313.882	68.84	-29.84	39.00	74.00	-35.00	peak	P
3	6353.489	68.41	-24.45	43.96	74.00	-30.04	peak	P
4	8576.472	70.62	-25.74	44.87	74.00	-29.13	peak	P
5	11285.948	67.84	-23.01	44.83	74.00	-29.17	peak	P
6	14956.087	71.71	-19.59	52.12	74.00	-21.88	peak	P



TM01 / Polarization: Horizontal / Modulation: π/4DQPSK / CH: M

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2913.849	70.53	-29.28	41.24	74.00	-32.76	peak	P
2	4277.223	67.56	-29.78	37.78	74.00	-36.22	peak	P
3	6084.667	65.47	-25.39	40.08	74.00	-33.92	peak	P
4	8644.897	69.37	-24.80	44.57	74.00	-29.43	peak	P
5	11047.793	68.85	-23.99	44.87	74.00	-29.13	peak	P
6	14217.633	70.36	-21.79	48.57	74.00	-25.43	peak	P

TM01 / Polarization: Vertical / Modulation: π/4DQPSK / CH: M

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2972.991	66.77	-30.23	36.54	74.00	-37.46	peak	P
2	4312.999	67.88	-29.21	38.67	74.00	-35.33	peak	P
3	6352.891	67.40	-24.42	42.99	74.00	-31.01	peak	P
4	8576.819	70.23	-24.47	45.76	74.00	-28.24	peak	P
5	11286.109	68.38	-22.73	45.65	74.00	-28.35	peak	P
6	14956.448	70.44	-19.64	50.80	74.00	-23.20	peak	P

TM01 / Polarization: Horizontal / Modulation: π/4DQPSK / CH: H

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2915.158	70.09	-29.10	40.98	74.00	-33.02	peak	P
2	4276.525	67.36	-28.20	39.16	74.00	-34.84	peak	P
3	6085.368	63.99	-24.82	39.17	74.00	-34.83	peak	P
4	8646.486	69.07	-24.81	44.26	74.00	-29.74	peak	P
5	11047.263	67.18	-24.05	43.13	74.00	-30.87	peak	P
6	14218.658	70.05	-21.12	48.93	74.00	-25.07	peak	P

TM01 / Polarization: Vertical / Modulation: π/4DQPSK / CH: H

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2972.312	66.78	-29.71	37.07	74.00	-36.93	peak	P
2	4313.122	69.18	-28.24	40.94	74.00	-33.06	peak	P
3	6353.145	67.51	-25.93	41.58	74.00	-32.42	peak	P
4	8576.418	70.22	-24.42	45.80	74.00	-28.20	peak	P
5	11286.920	67.32	-22.78	44.54	74.00	-29.46	peak	P
6	14955.883	70.85	-20.26	50.59	74.00	-23.41	peak	P



TM01 / Polarization: Horizontal / Modulation: 8DPSK / CH: L

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2914.993	68.67	-28.83	39.84	74.00	-34.16	peak	P
2	4277.666	68.64	-28.70	39.94	74.00	-34.06	peak	P
3	6085.103	65.59	-25.53	40.06	74.00	-33.94	peak	P
4	8645.756	69.10	-25.86	43.24	74.00	-30.76	peak	P
5	11046.470	67.94	-22.45	45.50	74.00	-28.50	peak	P
6	14218.816	70.49	-20.95	49.53	74.00	-24.47	peak	P

TM01 / Polarization: Horizontal / Modulation: 8DPSK / CH: L

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2972.330	67.85	-29.31	38.54	74.00	-35.46	peak	P
2	4312.847	68.97	-29.79	39.18	74.00	-34.82	peak	P
3	6352.999	68.40	-26.01	42.40	74.00	-31.60	peak	P
4	8577.105	69.12	-24.75	44.37	74.00	-29.63	peak	P
5	11286.356	67.91	-23.19	44.72	74.00	-29.28	peak	P
6	14956.156	71.44	-19.63	51.81	74.00	-22.19	peak	P

TM01 / Polarization: Horizontal / Modulation: 8DPSK / CH: M

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2914.043	70.56	-29.64	40.92	74.00	-33.08	peak	P
2	4277.291	67.26	-29.36	37.89	74.00	-36.11	peak	P
3	6085.619	64.55	-25.51	39.04	74.00	-34.96	peak	P
4	8645.188	70.35	-25.97	44.38	74.00	-29.62	peak	P
5	11047.341	68.42	-23.95	44.47	74.00	-29.53	peak	P
6	14218.948	70.73	-21.48	49.25	74.00	-24.75	peak	P

TM01 / Polarization: Vertical / Modulation: 8DPSK / CH: M

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2972.631	66.06	-30.34	35.72	74.00	-38.28	peak	P
2	4312.367	68.30	-28.99	39.31	74.00	-34.69	peak	P
3	6353.257	66.60	-24.40	42.19	74.00	-31.81	peak	P
4	8577.177	69.85	-24.44	45.41	74.00	-28.59	peak	P
5	11285.871	68.54	-23.97	44.56	74.00	-29.44	peak	P
6	14956.370	71.16	-20.68	50.48	74.00	-23.52	peak	P



TM01 / Polarization: Horizontal / Modulation: 8DPSK / CH: H

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2915.023	70.54	-29.26	41.28	74.00	-32.72	peak	P
2	4277.467	69.08	-28.91	40.17	74.00	-33.83	peak	P
3	6084.675	64.24	-25.42	38.82	74.00	-35.18	peak	P
4	8645.572	70.18	-25.32	44.86	74.00	-29.14	peak	P
5	11046.387	68.51	-22.48	46.03	74.00	-27.97	peak	P
6	14217.154	70.62	-21.33	49.30	74.00	-24.70	peak	P

TM01 / Polarization: Vertical / Modulation: 8DPSK / CH: H

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2973.399	67.52	-29.93	37.59	74.00	-36.41	peak	P
2	4313.057	69.35	-28.33	41.02	74.00	-32.98	peak	P
3	6352.749	68.09	-25.12	42.97	74.00	-31.03	peak	P
4	8576.712	69.43	-24.34	45.09	74.00	-28.91	peak	P
5	11287.131	67.50	-23.46	44.04	74.00	-29.96	peak	P
6	14955.012	70.31	-20.54	49.77	74.00	-24.23	peak	P



8 Test Setup Photo

Refer to Appendix – Test Setup Photos.

9 EUT Constructional Details (EUT Photos)

Refer to Appendix - External and Internal Appendix EUT Photos






10 Appendix



Cable loss=0.83 dB



1. Dwell Time (Hopping)



Condition	Antenna	Packet Type	Pulse Time(ms)	Hops	Dwell Time(ms)	Limit(s)	Result
NVNT	ANT1	1-DH1	0.377	319.00	120.263	0.40	Pass
NVNT	ANT1	1-DH3	1.633	160.00	261.280	0.40	Pass
NVNT	ANT1	1-DH5	2.881	105.00	302.505	0.40	Pass
NVNT	ANT1	2-DH1	0.387	320.00	123.840	0.40	Pass
NVNT	ANT1	2-DH3	1.639	157.00	257.323	0.40	Pass
NVNT	ANT1	2-DH5	2.887	110.00	317.570	0.40	Pass
NVNT	ANT1	3-DH1	0.388	318.00	123.384	0.40	Pass
NVNT	ANT1	3-DH3	1.638	171.00	280.098	0.40	Pass
NVNT	ANT1	3-DH5	2.889	130.00	375.570	0.40	Pass





































2. -20dB Bandwidth



Condition	Antenna	Modulation	Frequency (MHz)	-20dB BW(MHz)	if larger than CFS
NVNT	ANT1	1-DH5	2402.00	0.954	No
NVNT	ANT1	1-DH5	2441.00	0.960	No
NVNT	ANT1	1-DH5	2480.00	0.957	No
NVNT	ANT1	2-DH5	2402.00	1.283	Yes
NVNT	ANT1	2-DH5	2441.00	1.284	Yes
NVNT	ANT1	2-DH5	2480.00	1.282	Yes
NVNT	ANT1	3-DH5	2402.00	1.299	Yes
NVNT	ANT1	3-DH5	2441.00	1.300	Yes
NVNT	ANT1	3-DH5	2480.00	1.298	Yes


















3. 99% Occupied Bandwidth



Condition	Antenna	Modulation	Frequency (MHz)	99%BW(MHz)
NVNT	ANT1	1-DH5	2402.00	0.851
NVNT	ANT1	1-DH5	2441.00	0.854
NVNT	ANT1	1-DH5	2480.00	0.855
NVNT	ANT1	2-DH5	2402.00	1.167
NVNT	ANT1	2-DH5	2441.00	1.169
NVNT	ANT1	2-DH5	2480.00	1.174
NVNT	ANT1	3-DH5	2402.00	1.176
NVNT	ANT1	3-DH5	2441.00	1.180
NVNT	ANT1	3-DH5	2480.00	1.183


















4. Peak Output Power



Condition	Antenna	Modulation	Frequency (MHz)	Max. Conducted Power(dBm)	Max. Conducted Power(mW)	Limit(mW)	Result
NVNT	ANT1	1-DH5	2402.00	-2.33	0.59	1000	Pass
NVNT	ANT1	1-DH5	2441.00	-1.71	0.67	1000	Pass
NVNT	ANT1	1-DH5	2480.00	-1.89	0.65	1000	Pass
NVNT	ANT1	2-DH5	2402.00	-1.24	0.75	125	Pass
NVNT	ANT1	2-DH5	2441.00	-0.67	0.86	125	Pass
NVNT	ANT1	2-DH5	2480.00	-0.83	0.83	125	Pass
NVNT	ANT1	3-DH5	2402.00	-0.82	0.83	125	Pass
NVNT	ANT1	3-DH5	2441.00	-0.25	0.94	125	Pass
NVNT	ANT1	3-DH5	2480.00	-0.43	0.91	125	Pass















5. Spurious Emissions


Condition	Antenna	Modulation	TX Mode	Spurious MAX.Value(dBm)	Limit	Result
NVNT	ANT1	1-DH5	2402.00	-49.848	-22.501	Pass
NVNT	ANT1	1-DH5	2441.00	-52.548	-21.717	Pass
NVNT	ANT1	1-DH5	2480.00	-50.332	-22.266	Pass
NVNT	ANT1	2-DH5	2402.00	-36.060	-22.350	Pass
NVNT	ANT1	2-DH5	2441.00	-52.102	-21.732	Pass
NVNT	ANT1	2-DH5	2480.00	-50.766	-21.915	Pass
NVNT	ANT1	3-DH5	2402.00	-49.156	-22.597	Pass
NVNT	ANT1	3-DH5	2441.00	-52.509	-21.801	Pass
NVNT	ANT1	3-DH5	2480.00	-51.024	-21.991	Pass




























6. Bandedge


Condition	Antenna	Modulation	TX Mode	Bandedge MAX.Value	Limit	Result
NVNT	ANT1	1-DH5	2402.00	-51.074	-22.501	Pass
NVNT	ANT1	1-DH5	Hopping_LCH	-49.935	-21.589	Pass
NVNT	ANT1	1-DH5	2480.00	-50.068	-22.266	Pass
NVNT	ANT1	1-DH5	Hopping_HCH	-48.996	-22.032	Pass
NVNT	ANT1	2-DH5	2402.00	-51.631	-22.350	Pass
NVNT	ANT1	2-DH5	Hopping_LCH	-50.789	-21.523	Pass
NVNT	ANT1	2-DH5	2480.00	-49.531	-21.915	Pass
NVNT	ANT1	2-DH5	Hopping_HCH	-49.588	-21.707	Pass
NVNT	ANT1	3-DH5	2402.00	-50.230	-22.597	Pass
NVNT	ANT1	3-DH5	Hopping_LCH	-50.435	-21.463	Pass
NVNT	ANT1	3-DH5	2480.00	-49.958	-21.991	Pass
NVNT	ANT1	3-DH5	Hopping_HCH	-50.586	-21.904	Pass






































7. Carrier Frequencies Separation (Hopping)

Condition	Antenna	Modulation	Frequency(MHz)	Hopping NO.0 (MHz)	Hopping NO.1 (MHz)	Carrier Frequencies Separation(MHz)	Limit(MHz)	Result
NVNT	ANT1	1-DH5	2441.00	2440.810	2441.827	1.02	0.960	Pass
NVNT	ANT1	2-DH5	2441.00	2440.834	2441.824	0.99	0.856	Pass
NVNT	ANT1	3-DH5	2441.00	2440.837	2441.806	0.97	0.867	Pass






8. Number of Hopping Channel (Hopping)

Condition	Antenna	Modulation	Hopping Num	Limit	Result
NVNT	ANT1	1-DH5	79	15	Pass
NVNT	ANT1	2-DH5	79	15	Pass
NVNT	ANT1	3-DH5	79	15	Pass





- End of the Report -

