

FCC PART 15 B TEST REPORT

For

KBX GROUP

AVENIDA 1ERA. CALLE B Y C MANZANA 58,FRANCE FIELD,PANAMA,FL,United States

FCC ID: 2AAPW501QSWT

Product Type: Report Type: **3G MOBILE PHONE** Original Report Lion Nias Test Engineer: Lion Xiao Report Number: RSZ150930004-00D **Report Date: 2015-10-13** Some Hugof Sula Huang Reviewed By: RF Leader **Test Laboratory:** Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

Report No.: RSZ150930004-00D

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
TEST FACILITY	4
SYSTEM TEST CONFIGURATION	5
DESCRIPTION OF TEST CONFIGURATION	5
EUT Exercise Software	5
EQUIPMENT MODIFICATIONS	5
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	5
SUPPORT CABLE LIST AND DETAILS	
CONFIGURATION OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
FCC§15.107 - CONDUCTED EMISSIONS	8
MEASUREMENT UNCERTAINTY	8
EUT SETUP	8
EMI TEST RECEIVER SETUP	9
TEST EQUIPMENT LIST AND DETAILS.	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST RESULTS SUMMARY	
TEST DATA	10
FCC §15.109 - RADIATED SPURIOUS EMISSIONS	13
MEASUREMENT UNCERTAINTY	13
EUT Setup	
EMI TEST RECEIVER SETUP	14
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST RESULTS SUMMARY	
TEST DATA	15
DECLADATION LETTED	20

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The KBX GROUP's product, model number: QSP-501QS-WT (FCC ID: 2AAPW501QSWT) (the "EUT") in this report was a 3G MOBILE PHONE, which was measured approximately: 14.23 cm (L) x7.15 cm (W) x 0.97 cm (H), rated input voltage: DC 3.8V rechargeable Li-ion battery or DC5V charging from adapter. The highest operating frequency is 1.3GHz.

Report No.: RSZ150930004-00D

Adapter information: MODEL: SC050100-US

Input: AC 100-240V, 50/60Hz 0.4A

Output: DC5.0V, 1000mA

Note: The series product, model QSP-501QS-WT, QSP-501QS-BK, QSP-501QS-GD are electrically identical, the difference between them is model name, we selected QSP-501QS-WT for testing, the details was explained in the attached declaration letter.

All measurement and test data in this report was gathered from production sample serial number: 150930004 (Assigned by BACL, Dongguan). The EUT was received on 2015-10-08.

Objective

This test report is prepared on behalf of *KBX GROUP*. in accordance with Part 2, Subpart J, and Part 15-Subparts A and B of the Federal Communications Commission's rules.

The objective of the manufacturer is to determine the compliance of EUT with FCC Part 15 B Class B.

Related Submittal(s)/Grant(s)

FCC Part 15C DSS submissions with FCC ID: 2AAPW501QSWT.

FCC Part 15C DTS submissions with FCC ID: 2AAPW501QSWT.

FCC Part 22H, 24E PCE submissions with FCC ID: 2AAPW501QSWT.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Report No.: RSZ150930004-00D

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a typical fashion (as normally used by a typical user).

Report No.: RSZ150930004-00D

EUT Exercise Software

The software "winthrax.exe" was used during test.

Equipment Modifications

No modification was made to the EUT tested.

Local Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	Laptop	PP11L	QDS-BRCM1017
НР	Printer	C3941A	JPTVOB2337
DELL	Keyboard	L100	CNORH656658907BL05DC
SAST	Modem	AEM-2100	0293
Kingston	Micro SD card	4GB	/

Support Cable List and Details

		WINDLA VIOLE			
Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	То
Serial Cable	yes	no	1.2	Serial Port of Laptop	Modem
Parallel Cable	yes	no	1.2	Parallel Port of Laptop	Printer
Keyboard Cable	yes	no	1.8	USB Port of Laptop	Keyboard
USB Cable	yes	no	1.0	USB Port of Laptop	EUT
Earphone Cable	no	no	1.5	Audio Port of EUT	Earphone

FCC Part 15 B Page 5 of 20

Configuration of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§15.107	Conducted Emissions	Compliance
§15.109	Radiated Emissions	Compliance

Report No.: RSZ150930004-00D

FCC Part 15 B Page 7 of 20

FCC§15.107 - CONDUCTED EMISSIONS

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are Receiver, cable loss, and LISN.

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- -compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- -non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 1, then:

-compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit;

Report No.: RSZ150930004-00D


-non - compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cispr}

Measurement	$U_{ m cispr}$
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



Note: 1. Support units were connected to second LISN.

Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

FCC Part 15 B Page 8 of 20

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15 B Class B limits.

Report No.: RSZ150930004-00D

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter of laptop was connected to a 120V/60Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W	
150 kHz – 30 MHz	9 kHz	

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date				
R&S	EMI Test Receiver	ESCS 30	830245/006	2014-10-20	2015-10-20				
R&S	L.I.S.N	ESH2-Z5	892107/021	2015-07-16	2016-07-15				
R&S	Two-line V-network	ENV 216	3560.6550.12	2014-12-11	2015-12-11				
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A				

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

During the conducted emission test, the adapter of laptop was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

FCC Part 15 B Page 9 of 20

Herein,

V_C: corrected voltage amplitude

V_R: reading voltage amplitude

A_c: attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The "Margin" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

Report No.: RSZ150930004-00D

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15 B Class B, with the worst margin reading of:

13.6 dB at 0.272666 MHz in the Neutral conducted mode

Test Data


Environmental Conditions

Temperature:	26.3°C
Relative Humidity:	49%
ATM Pressure:	100.3 kPa

The testing was performed by Lion Xiao on 2015-10-08.

Test Mode: Downloading

AC120V, 60Hz, Line:




Report No.: RSZ150930004-00D

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.211298	45.5	9.000	L1	9.8	17.7	63.2	Compliance
0.219886	41.4	9.000	L1	9.8	21.4	62.8	Compliance
0.415949	41.1	9.000	L1	9.8	16.4	57.5	Compliance
0.426011	41.2	9.000	L1	9.8	16.1	57.3	Compliance
0.436318	38.1	9.000	L1	9.8	19.1	57.1	Compliance
0.515791	39.4	9.000	L1	9.8	16.6	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.211298	36.0	9.000	L1	9.8	17.2	53.2	Compliance
0.274848	34.2	9.000	L1	9.8	16.8	51.0	Compliance
0.302425	34.1	9.000	L1	9.8	16.1	50.2	Compliance
0.332770	31.4	9.000	L1	9.8	18.0	49.4	Compliance
0.515791	24.6	9.000	L1	9.8	21.4	46.0	Compliance
0.604902	25.6	9.000	L1	9.8	20.4	46.0	Compliance

FCC Part 15 B Page 11 of 20

AC120V, 60Hz, Neutral:



Report No.: RSZ150930004-00D

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.183065	48.7	9.000	N	9.8	15.6	64.3	Compliance
0.422630	38.7	9.000	N	9.8	18.6	57.4	Compliance
0.429420	38.4	9.000	N	9.8	18.9	57.3	Compliance
0.604902	35.8	9.000	N	9.8	20.2	56.0	Compliance
0.709407	32.1	9.000	N	9.8	23.9	56.0	Compliance
0.750100	34.2	9.000	N	9.8	21.8	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.186006	37.3	9.000	N	9.8	16.9	54.2	Compliance
0.207957	34.7	9.000	N	9.8	18.6	53.3	Compliance
0.272666	37.4	9.000	N	9.8	13.6	51.0	Compliance
0.302425	33.2	9.000	N	9.8	17.0	50.2	Compliance
0.335433	35.0	9.000	N	9.8	14.3	49.3	Compliance
0.604902	29.2	9.000	N	9.8	16.8	46.0	Compliance

FCC Part 15 B Page 12 of 20

FCC §15.109 - RADIATED SPURIOUS EMISSIONS

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- -compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- -non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If U_{lab} is greater than U_{cispr} of Table 1, then:
- -compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} U_{cispr})$, exceeds the disturbance limit;

Report No.: RSZ150930004-00D

-non - compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.


Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:30M~200MHz: 5.0 dB; 200M~1GHz: 6.2 dB; 1G~6GHz: 4.45 dB, 6G~18GHz: 5.23 dB

Table 1 – Values of U_{cispr}


Measurement					
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB				
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB				
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB				

EUT Setup

Below 1GHz:



Above 1GHz:



Report No.: RSZ150930004-00D

The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 6.5 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	Peak
Above I GHZ	1 MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The data was recorded in the Quasi-peak detection mode for below 1 GHz, peak and average detection mode above 1 GHz.

FCC Part 15 B Page 14 of 20

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-08-03	2016-08-02
Sunol Sciences	Antenna	ЈВ3	A060611-3	2014-11-06	2017-11-05
HP	Amplifier	8447E	2434A02181	2015-09-01	2016-09-01
Agilent	Spectrum Analyzer	E4440A	SG43360054	2014-12-04	2015-12-04
ETS-Lindgren	Horn Antenna	3115	9808-5557	2015-09-06	2018-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2015-02-19	2016-02-19
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

Report No.: RSZ150930004-00D

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Loss + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the data in the following table, the EUT complied with the <u>FCC Part 15 B Class B</u>, with the worst margin reading of:

0.70 dB at 165.8000 MHz in the Horizontal polarization

Test Data

Environmental Conditions

Temperature:	26.2 °C
Relative Humidity:	43 %
ATM Pressure:	100.3 kPa

The testing was performed by Lion Xiao on 2015-10-08.

Test Result: Compliance


FCC Part 15 B Page 15 of 20

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Mode: Downloading

1) Below 1GHz:

Horizontal




Report No.: RSZ150930004-00D

Frequency (MHz)	Receiver Reading (dBµV)	Detector (PK/QP/AVG)	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
53.2800	48.84	QP	-12.94	35.90	40.00	4.10*
165.8000	50.84	QP	-8.04	42.80	43.50	0.70*
195.8700	46.04	QP	-8.34	37.70	43.50	5.80
284.1400	44.90	QP	-6.50	38.40	46.00	7.60
313.2400	41.23	QP	-6.13	35.10	46.00	10.90
480.0800	39.43	QP	-2.63	36.80	46.00	9.20

^{*}within uncertainty measurement!

FCC Part 15 B Page 16 of 20

Vertical



Report No.: RSZ150930004-00D


Frequency (MHz)	Receiver Reading (dBµV)	Detector (PK/QP/AVG)	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
52.3100	49.22	QP	-12.82	36.40	40.00	3.60*
134.7600	43.60	QP	-6.50	37.10	43.50	6.40
165.8000	48.94	QP	-8.04	40.90	43.50	2.60*
195.8700	47.04	QP	-8.34	38.70	43.50	4.80*
284.1400	47.70	QP	-6.50	41.20	46.00	4.80*
475.2300	38.67	QP	-2.67	36.00	46.00	10.00

^{*}within uncertainty measurement!

FCC Part 15 B Page 17 of 20

2) Above 1GHz:

Horizontal




Report No.: RSZ150930004-00D

Frequency (MHz)	Receiver Reading (dBµV)	Detector (PK/QP/AVG)	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1065.000	47.98	peak	1.46	49.44	74.00	24.56
1065.000	35.57	AVG	1.46	37.03	54.00	16.97
1330.000	42.11	peak	1.88	43.99	74.00	30.01
1330.000	29.40	AVG	1.88	31.28	54.00	22.72
2127.500	40.51	peak	3.66	44.17	74.00	29.83
2127.500	27.88	AVG	3.66	31.54	54.00	22.46

For above 6 GHz, all spurious emissions are 20dB below the limit or are on the system noise floor level.

FCC Part 15 B Page 18 of 20

Vertical



Report No.: RSZ150930004-00D

Frequency (MHz)	Receiver Reading (dBµV)	Detector (PK/QP/AVG)	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1062.500	51.20	peak	1.46	52.66	74.00	21.34
1062.500	38.66	AVG	1.46	40.12	54.00	13.88
1330.000	47.85	peak	1.88	49.73	74.00	24.27
1330.000	35.36	AVG	1.88	37.24	54.00	16.76
2932.500	39.55	peak	9.35	48.90	74.00	25.10
2932.500	27.06	AVG	9.35	36.41	54.00	17.59

For above 6 GHz, all spurious emissions are 20dB below the limit or are on the system noise floor level.

FCC Part 15 B Page 19 of 20

DECLARATION LETTER

KBX GROUP
AVENIDA 1ERA. CALLE B Y C MANZANA 58,FRANCE FIELD,PANAMA,FL ,United States
TEL: 507-403-6677 FAX: 507-403-6677

Report No.: RSZ150930004-00D

10/21/2015

Product Similarity Declaration

To Whom It May Concern,

We, KBX GROUP, hereby declare that we have a product named as 3G MOBILE PHONE (Model no: QSP-501QS-WT) was tested by BACL, meanwhile, for our marketing purpose, we would like to list a series models (QSP-501QS-BK,QSP-501QS-GD) on reports and certificate, all the models are identical schematics, except for the differences as below,

1, Only different Model No.

No other changes are made to them.

We confirm that all information above is true, and we'll be responsible for all the consequences. Please contact me if you have any question.

Signature:

Daniel Laughlin Product Manager

***** END OF REPORT *****

FCC Part 15 B Page 20 of 20