FCC PART 15.247 TEST REPORT

Product: Bluetooth speaker

Model: BT-1069

FCC ID: 2AAQFBT-1069

Report No.: BZT-2013NT0821013F

Issued Date: August 25, 2013

Issued for:

CHINA ELECTRONICS SHENZHEN COMPANY

F35/F., Electronics Science& Technology Building, Shennan Zhong Road, shenzhen China

Issued By:

BZT Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community,Xixiang Street

Bao'an District, Shenzhen P.R. China

Tested By:

Apple Huang(EMC Engineer)

Approved By:

Bovey Yang(Technical Manager)

Report No.: BZT-2013NT0821013F

Note:

The results detailed in this test report relate only to the specific sample(s) tested. It is the Application's responsibility to ensure that all production units are manufactured with equivalent EMC characteristics. This report is not to be reproduced except in full, without written approval from BZT Technology.

Table of Contents

1.0	General Details	3
1.1	Test Lab Details.	3
1.2	Applicant Details.	3
1.3	Description of EUT	4
1.4	Submitted Sample.	4
1.5	Test By	4
2.0	List of Measurement Equipment.	5
3.0	Technical Details	6
4.0	EUT Modification.	6
5.0	Measurement Uncertainty	6
6.0	Power Line Conducted Emission Test.	7
6.1	Schematics of the test.	7
6.2	Test Method and Test Procedure.	7
6.3	EUT Operating Condition.	7
6.4	Test Equipment.	7
6.5	Conducted Emission Limit.	8
6.6	Photo documentation of the test set-up	8
6.7	Test specification.	8
6.8	Test result.	8
7.0	20 dB Bandwidth Measurement	11
7.1	Test Equipment.	11
7.2	Test Specification.	11
7.3	Limit	11
7.4	Test status.	11
7.5	Test Result.	11
8.0	Maximum Peak Output Power	15
9.0	Carrier Frequency Separation.	21
10.0	Number of Hopping Channels.	25
11.0	Time of Occupancy (Dwell Time)	27
12.0	Band age Measurement.	31
13.0	Spurious Emission Test.	40
14.0	Antenna Requirement	52
15.0	FCC ID Label	53

1.0 General Details

1.1 Test Lab Details

Name:	BZT Testing Technology Co., Ltd
Address:	1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District,
	Shenzhen P.R. China.

Report No.: BZT-2013NT0821013F

Site Listed with Federal Communication Commission

Registration Number: 701733

For 3m chamber

1.2 Applicant Details

Applicant: CHINA ELECTRONICS SHENZHEN COMPANY			
Address:	F35/F., Electronics Science& Technology Building, Shennan Zhong Road, shenzhen China		
Telephone:	0755-86253000		
Fax:	0755-86253100		

1.3 Description of EUT

Product:	Bluetooth Speaker	
Brand Name:	N/A	
Model No.:	BT-1069	
Additional Model No.	C8A, C8, C1, C2, C3, C5, C6, C7, C9	
Rating:	DC 3.7V Lithium battery or DC 5V from USB LINE	
Bluetooth Version:	BT 3.0	
Modulation Type:	GFSK, Pi/4QDPSK, 8DPSK	
Transfer Data Rate	1/2/3 Mbps	
Channel Number:	79	
Channel spacing:	1 MHz	
Operation Frequency	2402 MHz-2480 MHz	
Antenna Designation	An PCB printed antenna and the maximum gain is 0 dBi	
Product Dimensions	L*W*H=10.6cm*10.6cm*10.2cm	
Modes Statement:	All modes above are identical in interior structure, electrical circuits and	
	components; just model names are different for the marketing requirement.	

Report No.: BZT-2013NT0821013F

1.4 Submitted Sample

1 Sample(s)

2.0 Test equipments and Associated Equipment used during the test.

2.1 Test Equipments

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	Agilent	E4407B	160400005	Jul. 06. 2014
2	Test Receiver	R&S	ESPI	101318	Jul. 06. 2014
3	Bilog Antenna	TESEQ	CBL6111D	31216	Jul. 06. 2014
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	Jul. 06. 2014
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	Jul. 06. 2014
6	Horn Antenna	EM	EM-AH-10180	2011071402	Jul. 06. 2014
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	Jul. 06. 2014
8	Amplifier	EM	EM-30180	060538	Jul. 06. 2014
9	Loop Antenna	ARA	PLA-1030/B	1029	Jul. 06. 2014
10	Power Meter	R&S	NRVS	100696	Jul. 06. 2014
11	Power Sensor (Peak)	R&S	NRV-Z31	0396.0101.19	Jul. 06. 2014

Report No.: BZT-2013NT0821013F

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Test Receiver	R&S	ESCI	101160	Jul. 06. 2014
2	LISN	R&S	ENV216	101313	Jul. 06. 2014
3	LISN	EMCO	3816/2	00042990	Jul. 06. 2014
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	Jul. 06. 2014
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	Jul. 06. 2014
6	Absorbing clamp	R&S	MOS-21	100423	Jul. 06. 2014

2.2 AE used during the test

Equipment type	Manufacturer	Model
Notebook	acer	ZQ1A
N/A		
N/A		
N/A		

3.0 Technical Details

3.1 Summary of test results

The EUT has been tested according to the following specifications

Report No.: BZT-2013NT0821013F

Requirement	CFR 47 Section	Result
Power Line Conducted Emission Test	15.207(a)	PASS
20dB Channel Bandwidth	15.247 (a)(1), 15.215(c)	PASS
Maximum Peak Output Power	15.247(b)(1)	PASS
Carrier Frequency Separation	15.247 (a)(1)	PASS
Number of Hopping Channels	15.247(a)(iii)	PASS
Time of Occupancy (Dwell Time)	15.247(a)(iii)	PASS
Band age Measurement,	15 247 (d) 15 205 (a) 15 200 (a)	PASS
Spurious Emission Test	15.247 (d), 15.205 (a), 15.209 (a)	rass
Antenna Requirement	15.203	PASS

3.2 Test Standards

FCC Part 15:2012 Subpart C, Paragraph 15.247

4.0 EUT Modification

No modification by BZT Testing Technology Co., Ltd


5.0 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	MU
1.	Radio Frequency	±1×10 ⁻⁹
2.	Temperature	±0.1°C
3.	Humidity	±1.0%
4.	RF power, conducted	±0.34dB
5.	Spurious emissions, conducted	±3.70dB
6.	All emissions, radiated	±4.50dB

Report No.: BZT-2013NT0821013F

6. Power Line Conducted Emission Test

6.1 Schematics of the test




EUT: Equipment Under Test

6.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2003. The Frequency spectrum From 0.15MHz to 30MHz was investigated.

Test Voltage: 120V~, 60Hz Block diagram of Test setup



6.3 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2003

- 1) Setup the EUT and simulators as shown on the following
- 2) Enable AF signal and confirm EUT active to normal condition

6.4 Test Equipment

Please refer to the Section 2

Report No.: BZT-2013NT0821013F

6.5 Power line conducted Emission Limit according to Paragraph 15.207

Engage av (MHz)	Class A Lir	mits (dB μ V)	$(dB \mu V)$ Class B Limits $(dB \mu V)$	
Frequency(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0
5.00 ~ 30.00	73.0	60.0	60.0	50.0

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

6.6 Photo documentation of the test set-up

Please refer to the Section 12

6.7 Test specification:

Frequency range: 0.15 MHz – 30 MHz

The test was carried out in the following operation mode(s):

- Tx mode

6.8 Test result

Min. limit margin

8.22dB at 0.2600MHz

The requirements are FULFILLED

Remarks: According to FCC part 15.207(a)


Report No.: BZT-2013NT0821013F

A Conducted Emission on Line Terminal of the power line (150kHz to 30MHz)

EUT Description: Bluetooth Speaker

Operation Mode: Tx mode
Tested By: Apple Huang
Test date: August 24, 2013

Start Frequency	Stop Frequency	Step	IF BW	Detector	Final M-Time
0.15MHz	30MHz	4.5KHz	10KHz	QP+AV	1s



E		Reading	Limit				
Frequency	Line		Neutr	Neutral		$(dB \mu V)$	
(MHz)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average	
0.1547	54.68	32.35	-		65.74	55.74	
0.2600	49.66	43.21			61.43	51.43	
0.3608	47.56	36.39			58.71	48.71	
1.0947	44.72	31.56			56.00	46.00	
1.8680	44.77	33.53			56.00	46.00	
2.4546	45.28	34.31			56.00	46.00	


Report No.: BZT-2013NT0821013F

B Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT Description: Bluetooth Speaker

Operation Mode: Tx mode
Tested By: Apple Huang
Test Data: August 24, 2013

Start Frequency	Stop Frequency	Step	IF BW	Detector	Final M-Time
0.15MHz	30MHz	4.5KHz	10KHz	QP+AV	1s



Frequency		Reading	Limit			
	Live		Neutr	Neutral		$(dB \mu V)$
(MHz)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.1539			54.20	24.36	65.78	55.78
0.2575			50.63	40.19	63.53	53.53
0.5493			46.74	33.89	56.00	46.00
0.9684			44.88	32.68	56.00	46.00
1.6794			45.25	34.56	56.00	46.00
2.9305			44.97	32.33	56.00	46.00

7.0 20dB Bandwidth Measurement

7.1 Test Equipment

Please refer to the Section 2

7.2 Test Specification:

Environmental conditions: Temperature 23 °C Humidity: 51% Atmospheric pressure: 103kPa

Report No.: BZT-2013NT0821013F

7.3 Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

7.4 Test status:


Pre-tests were made in continuous transmitting mode at lowest (2402 MHz), middle (2441 MHz) and highest (2480MHz) channel with GFSK, Pi/4 QDPSK and 8DPSK mode, which indicates that the worst case is 8DPSK mode, so it is reported GFSK and 8DPSK mode only.

7.5 Test Result:

Modulation Type	Channel number	20dB Bandwidth (kHz)	Limit (kHz)	Conclusion
	Low	1034		PASS
GFSK	Middle	998		PASS
	High	1022		PASS
	Low	1323		PASS
8DPSK	Middle	1359		PASS
	High	1353		PASS


Modulation: GFSK

Low channel




Report No.: BZT-2013NT0821013F

Middle channel




Report No.: BZT-2013NT0821013F

High channel




Modulation: 8DPSK

Low channel




Report No.: BZT-2013NT0821013F

Middle channel



High channel



8.0 Maximum Peak Output Power

8.1 Test Equipment

Please refer to the Section 2

8.2 Test specification:

Environmental conditions: Temperature 23 °C Humidity: 51% Atmospheric pressure: 103kPa

Report No.: BZT-2013NT0821013F

8.3 Test Procedure

- 1) Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
- 2) Set the spectrum analyzer as follows: Span = approximately 5 times the 20 dB bandwidth, centred on a hopping channel; RBW > the 20 dB bandwidth of the emission being measured; VBW ≥RBW; Sweep = auto; Detector function = peak; Trace = max hold
- 3) Measure the highest amplitude appearing on spectral display and record the level to calculate results.
- 4) Repeat above procedures until all frequencies measured were complete.
- 5) Peak Power Output = Peak Power Reading + Cable loss + Attenuator

8.4 Limits


According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5MHz band: 0.125 watts. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

8.5 Test Result

Modulation Type	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (mW)	Peak Power Limit (dBm)	Pass/ Fail
	2402	-5.15	125	20.97	Pass
GFSK	2441	-4.69	125	20.97	Pass
	2480	-4.42	125	20.97	Pass
	2402	-2.58	125	20.97	Pass
Pi/4 QDPSK	2441	-2.05	125	20.97	Pass
	2480	-1.87	125	20.97	Pass
	2402	-2.00	125	20.97	Pass
8 DPSK	2441	-1.50	125	20.97	Pass
	2480	-1.33	125	20.97	Pass


Modulation: GFSK

Low channel




Report No.: BZT-2013NT0821013F

Middle channel




Report No.: BZT-2013NT0821013F

High channel




Modulation: Pi/4DQPSK

Low channel




Report No.: BZT-2013NT0821013F

Middle channel




High channel




Report No.: BZT-2013NT0821013F

Modulation: 8DPSK

Low channel




Middle channel



Report No.: BZT-2013NT0821013F

High channel



9.0 Carrier Frequency Separation

9.1 Test Equipment

Please refer to the Section 2

9.2 Test specification:

Environmental conditions: Temperature 23 °C Humidity: 51% Atmospheric pressure: 103kPa

Report No.: BZT-2013NT0821013F

9.3 Test Procedure

1. Set the spectrum analyzer as follows: Span = wide enough to capture the peaks of two adjacent channels: Resolution (or IF) Bandwidth (RBW) \geq 1% of the span; Video (or Average) Bandwidth (VBW) \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold

- 2. Measure the separation between the peaks of the adjacent channels using the marker-delta function.
- 3. Repeat above procedures until all frequencies measured were complete.

9.4 Limits

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

9.5 Test status:

Pre-tests were made in continuous transmitting mode at lowest (2402 MHz), middle (2441 MHz) and highest (2480MHz) channel with GFSK, Pi/4 QDPSK and 8DPSK mode, which indicates that the worst case is 8DPSK mode, so it is reported GFSK and 8DPSK mode only.


9.6 Test Result

Modulation Type	Channel number	Carrier Frequency	Limit	Pass/ Fail
		Separation		
	Low	1.002MHz	≥25 kHz or	Pass
GFSK	Middle	1.002MHz	two-thirds	Pass
	High	1.002MHz	20 dB bandwidth	Pass
	Low	1.007MHz	≥25 kHz or	Pass
8DPSK	Middle	1.002MHz	two-thirds 20 dB bandwidth	Pass
	High	1.002MHz	20 db bandwidth	Pass

Note: Two-thirds 20 dB bandwidth: GFSK: 689 kHz; 8DPSK: 906 kHz


Modulation: GFSK

Low channel




Report No.: BZT-2013NT0821013F

Middle channel




Report No.: BZT-2013NT0821013F

High channel




Modulation: 8DPSK

Low channel




Report No.: BZT-2013NT0821013F

Middle channel



High channel



10.0 Number of Hopping Channels

10.1 Test Equipment

Please refer to the Section 2

10.2 Test specification:

Environmental conditions: Temperature 22 °C Humidity: 51% Atmospheric pressure: 103kPa

Report No.: BZT-2013NT0821013F

10.3 Test Procedure

Set the spectrum analyzer as follows: Span = the frequency band of operation; RBW \ge 1% of the span;

VBW ≥RBW; Sweep = auto; Detector function = peak; Trace = max hold

10.4 Limits

According to \$15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

10.5 Test status:

Pre-tests were made in continuous transmitting mode at lowest (2402 MHz), middle (2441 MHz) and highest (2480MHz) channel with GFSK, Pi/4 QDPSK and 8DPSK mode, which indicates that the worst case is 8DPSK mode, so it is reported GFSK and 8DPSK mode only.


10.6 Test Result

Modulation Type	Operating	Number of	Limit	Pass/ Fail	
Wiodulation Type	Frequency	hopping channels	Limit	Fass/Tan	
GFSK	2402-2480MHz	79	≥ 15	Pass	
8-DPSK	2402-2480MHz	79	≥ 15	Pass	


Report No.: BZT-2013NT0821013F

Test Plot:

Modulation Type: GFSK



Modulation Type: 8DPSK



11.0 Time of Occupancy (Dwell Time)

11.1 Test Equipment

Please refer to the Section 2

11.2 Test specification:

Environmental conditions: Temperature 22 °C Humidity: 52% Atmospheric pressure: 103kPa

Report No.: BZT-2013NT0821013F

11.3 Test Procedure

Span = zero span, centred on a hopping channel; RBW = 1 MHz; VBW ≥RBW; Detector function = peak;

Sweep = as necessary to capture the entire dwell time per hopping channel; Trace = max hold

Measure the dwell time using the marker-delta function.

Repeat this test for different modes of operation (e.g., data rate, modulation format, etc.), if applicable.

11.4 Limits

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed

11.5 Test status:

Pre-tests were made in continuous transmitting mode at lowest (2402 MHz), middle (2441 MHz) and highest (2480MHz) channel with GFSK, Pi/4 QDPSK and 8DPSK mode, which indicates that the worst case is 8DPSK mode, so it is reported GFSK and 8DPSK mode only.

11.6 Test Result

Modulation Type	Packet	Reading (ms)	Hoping Rate	Actual (s)	Limit (s)
	DH1	0.433	800hop/s	0.1386	0.4
GFSK	DH3	1.702	400hop/s	0.2723	0.4
	DH5	2.958	266.667hop/s	0.3155	0.4
	DH1	0.431	800hop/s	0.1379	0.4
8DPSK	DH3	1.687	400hop/s	0.2688	0.4
	DH5	2.936	266.667hop/s	0.3132	0.4


Note: 1) The measurements were conducted in High, Middle, Low channel. The Low channel could represent the character of the other channels, so the low channel measurement was submitted in the report only.

- 2) Actual = Reading \times (Hopping rate / Number of channels) \times Test period
- 3) The EUT makes worst case 1600 hops per second or 1 time slot has a length of 625 µs with 79 channels. A DH5 Packet needs 5 time slot for transmitting and 1 time slot for receiving. So the EUT makes worst case 266.667 hops per second with 79 channels, and the DH5 is the worst case.


Report No.: BZT-2013NT0821013F

Modulation Type: GFSK

Packet Type: DH1




Packet Type: DH3




Report No.: BZT-2013NT0821013F

Packet Type: DH5




Modulation Type: 8DPSK


Packet Type: 3-DH1



Packet Type: 3-DH3



Packet Type: 3-DH5



12.0 Band age Measurement

12.1 Test Equipment

Please refer to the Section 2

12.2 Test specification:

Environmental conditions: Temperature 22 °C Humidity: 52% Atmospheric pressure: 103kPa

Report No.: BZT-2013NT0821013F

12.3 Test Procedure

For bandage test, the spectrum set as follows: RBW=VBW=100 kHz. A conducted measure method is used For signals allocated in the restricted bands above and below the 2.4-2.483GHz, a radiated measurement is made (Peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector)

12.4 Limit


Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth). Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

12.5 Test status:

Pre-tests were made in continuous transmitting mode at lowest (2402 MHz), middle (2441 MHz) and highest (2480MHz) channel with GFSK, Pi/4-QDPSK and 8-DPSK mode, which indicates that the worst case is 8-DPSK mode, so it is reported GFSK and 8-DPSK mode only.

Modulation: GFSK

EUT operation mode: Keep transmitting in low channel




Report No.: BZT-2013NT0821013F

- 2) The maximum emission was 46.21dBuv at 2350.7 MHz, which is less than the Average limit.
- 3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).

Report No.: BZT-2013NT0821013F


EUT operation mode: Keep transmitting in high channel



- 2) The maximum emission was 47.13dBuv at 2493.8MHz, which is less than the Average limit.
- 3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).

Report No.: BZT-2013NT0821013F


EUT operation mode: Keep hopping



- 2) The maximum emission was 46.91dBuv at 2326.2MHz, which is less than the Average limit.
- 3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).

Report No.: BZT-2013NT0821013F


EUT operation mode: Keep hopping



- 2) The maximum emission was 47.25dBuv at 2489.3MHz, which is less than the Average limit.
- 3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).

Modulation: 8DPSK

EUT operation mode: Keep transmitting in low channel




Report No.: BZT-2013NT0821013F

- 2) The maximum emission was 46.80dBuv at 2378.4MHz, which is less than the Average limit.
- 3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).

Report No.: BZT-2013NT0821013F

EUT operation mode: Keep transmitting in high channel




Remark: 1) The radiated measurement was made in horizontal and vertical polarity;

- 2) The maximum emission was 47.04dBuv at 2491.1 MHz, which is less than the Average limit.
- 3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).

Report No.: BZT-2013NT0821013F

EUT operation mode: Keep hopping




Remark: 1) The radiated measurement was made in horizontal and vertical polarity;

- 2) The maximum emission was 47.21dBuv at 2345.2 MHz, which is less than the Average limit.
- 3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).

Report No.: BZT-2013NT0821013F

EUT operation mode: Keep hopping



Remark: 1) The radiated measurement was made in horizontal and vertical polarity;

- 2) The maximum emission was 47.34dBuv at 2490.3MHz, which is less than the Average limit.
- 3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).

13.0 Spurious Emission Test


13.1 Radiated emissions

- 13.1.1 Test Method and test Procedure:
 - 1) The EUT was tested according to ANSI C63.10 –2009.
 - 2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2009.

Report No.: BZT-2013NT0821013F


- 3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz. Measurements were made at 3 meters.
- 4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- 5) The antenna polarization: Vertical polarization and Horizontal polarization.

13.1.2 Block diagram of Test setup for frequency 30MHz-1000MHz




Report No.: BZT-2013NT0821013F

Block diagram of Test setup for frequency below 30MHz



Block diagram of Test setup for frequency above 1GHz



13.1.3 EUT Operating Condition

Operating condition is according to ANSI C63.10 -2009

13.1.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Report No.: BZT-2013NT0821013F

Frequencies in restricted band are complied to limit on Paragraph 15.209.

Frequency Range (MHz)	Distance (m)	Field strength (dB μ V/m)
0.009-0.490	3	20log 2400/F (kHz) + 80
0.490-1.705	3	20log 24000/F (kHz) + 40
1.705-30	3	20log 30 + 40
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1) RF Voltage $(dBuV) = 20 \log RF \text{ Voltage } (uV)$
- 2) In the Above Table, the tighter limit applies at the band edges.
- 3) Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4) This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.
- 5) All scanning using PK detector. And the final emission level was get using QP detector for frequency range from 30-1000MHz.As to 1G-25G, the final emission level got using PK and AV detector.
- 6) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula Ld1 = Ld2 * (d2/d1)

13.1.5 Photo documentation of the test set-up

Please refer to the Section 16

13.1.6 Test Equipment:

Please refer to the Section 2

13.1.7 Test specification:

Environmental conditions: Temperature 23 °C Humidity: 50% Atmospheric pressure: 103kPa

Report No.: BZT-2013NT0821013F

13.1.8 Test result

A Radiated Emission (9 kHz----30 MHz)

Note:

- 1) Emission Level=Reading+ Cable loss+ Antenna factor-Amp factor
- 2) The emission levels are 20 dB below the limit value, which are not reported. It is deemed to comply with the requirement

Result: Pass

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB μ V/m)
		V	
		Н	
		V	
		Н	


Report No.: BZT-2013NT0821013F

B General Radiated Emissions Data

Radiated Emission In Horizontal (30MHz----1000MHz)

Please refer to following diagram for individual

High channel: 2480 MHz




Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB μ V/m)
78.5972	26.67	Н	40.00
98.0361	26.62	Н	43.50
298.2565	36.52	Н	46.00
399.3387	35.48	Н	46.00
465.4310	37.22	Н	46.00
663.7073	37.97	Н	46.00

Radiated Emission In Vertical (30MHz----1000MHz)

Please refer to following diagram for individual

High channel: 2480 MHz

667.5951



Note: Measurements were conducted in all three channels (high, middle, low), and the worst case (high channel) was submitted only.

34.77

46.00

C Fundamental & Harmonics Radiated Emission Data (1000MHz-25000MHz)

Pre-tests were made in continuous transmitting mode at lowest (2402 MHz), middle (2441 MHz) and highest (2480MHz) channel with GFSK, Pi/4 QDPSK and 8DPSK mode, which indicates that the worst case is 8DPSK mode, so it is reported GFSK and 8DPSK mode only.

Report No.: BZT-2013NT0821013F

Modulation Type: GFSK

lr										
Low chann	Low channel: 2402 MHz									
Freq.	Ant. Pol.	Peak reading	AV reading	Correction Factor	Emissio Peak	on Level AV	Peak limit	AV limit	Margin (dB)	
(MHz)	H/V	(dBuV)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(u2)	
1304.01	Н	49.35		-4.21	45.14		74.00	54.00	-8.86	
4804.00	Н	51.20		-3.94	47.26		74.00	54.00	-6.74	
5601.12	Н	49.37		-2.87	46.50		74.00	54.00	-7.50	
7206.00	Н	47.26		0.52	47.78		74.00	54.00	-6.22	
16814.00	Н	41.33		6.73	48.06		74.00	54.00	-5.94	
24020.00	Н	40.84		8.11	48.95		74.00	54.00	-5.05	
1302.33	V	52.39		-4.26	48.13		74.00	54.00	-5.87	
4804.00	V	52.24		-3.94	48.30		74.00	54.00	-5.70	
5640.82	V	48.33		-2.89	45.44		74.00	54.00	-8.56	
7206.00	V	45.01		0.52	45.53		74.00	54.00	-8.47	
16814.00	V	41.27		6.73	48.00		74.00	54.00	-6.00	
24020.00	V	40.36		8.11	48.47		74.00	54.00	-5.53	

- 2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.
 - 3) Average test would be performed if the peak readings were greater than the average limit.
 - 4) Data of measurement shown "---"in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
 - 5) Emission Level=Peak (AV) Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss - Pre-amplifier
 - 6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

ınnel: 2441	MHz							
Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emissio Peak (dBuV/m)	on Level AV (dBuV/m)	Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
Н	51.36		-4.21	47.15		74.00	54.00	-6.85
Н	50.32		-3.98	46.34		74.00	54.00	-7.66
Н	50.56		-2.86	47.70		74.00	54.00	-6.30
Н	46.52		0.57	47.09		74.00	54.00	-6.91
Н	41.88		6.79	48.67		74.00	54.00	-5.33
Н	40.47		8.16	48.63		74.00	54.00	-5.37
V	52.45		-4.25	48.20		74.00	54.00	-5.80
V	51.24		-3.98	47.26		74.00	54.00	-6.74
V	50.96		-2.83	48.13		74.00	54.00	-5.87
V	46.75		0.57	47.32		74.00	54.00	-6.68
V	40.89		6.79	47.68		74.00	54.00	-6.32
V	39.36		8.16	47.52		74.00	54.00	-6.48
	Ant. Pol. H/V H H H H V V V V V	H/V reading (dBuV) H 51.36 H 50.32 H 50.56 H 46.52 H 41.88 H 40.47 V 52.45 V 51.24 V 50.96 V 46.75 V 40.89	Ant. Pol. H/V reading (dBuV) H 51.36 H 50.32 H 50.56 H 46.52 H 41.88 V 52.45 V 51.24 V 50.96 V 46.75 V 40.89	Ant. Pol. H/V Peak reading (dBuV) AV reading (dBuV) Correction Factor (dB) H 51.36 -4.21 H 50.32 -3.98 H 50.56 -2.86 H 46.52 0.57 H 41.88 6.79 H 40.47 8.16 V 52.45 -4.25 V 51.24 -3.98 V 50.96 -2.83 V 46.75 6.79	Ant. Pol. H/V Peak reading (dBuV) AV reading (dBuV) Correction Factor (dB) Emission Peak (dBuV/m) H 51.36 -4.21 47.15 H 50.32 -3.98 46.34 H 50.56 -2.86 47.70 H 46.52 0.57 47.09 H 41.88 6.79 48.67 H 40.47 8.16 48.63 V 52.45 -4.25 48.20 V 51.24 -3.98 47.26 V 50.96 -2.83 48.13 V 46.75 0.57 47.32 V 40.89 6.79 47.68	Ant. Pol. H/V Peak reading (dBuV) AV reading (dBuV) Correction Factor (dB) Emission Level Peak (dBuV/m) AV (dBuV/m) H 51.36 -4.21 47.15 H 50.32 -3.98 46.34 H 50.56 -2.86 47.70 H 46.52 0.57 47.09 H 41.88 6.79 48.67 H 40.47 8.16 48.63 V 51.24 -3.98 47.26 V 50.96 -2.83 48.13 V 46.75 0.57 47.32 V 40.89 6.79 47.68	Ant. Pol. H/V Peak reading (dBuV) AV reading (dBuV) Correction Factor (dB) Emission Level (dBuV/m) Peak (dBuV/m) Peak (dBuV/m) AV (dbuV/m) AV (dbuV/m) Peak (dbuV/m) AV (dbuV/m) AV (dbuV/m) AV (dbuV/m	Ant. Pol. H/V Peak reading (dBuV) AV reading (dBuV) Correction Factor (dB) Emission Level Peak (dBuV/m) Peak Imit (dBuV/m) AV Imit (dBuV/m) H 51.36 -4.21 47.15 74.00 54.00 H 50.32 -3.98 46.34 74.00 54.00 H 50.56 -2.86 47.70 74.00 54.00 H 46.52 0.57 47.09 74.00 54.00 H 41.88 6.79 48.67 74.00 54.00 H 40.47 8.16 48.63 74.00 54.00 V 52.45 -3.98 47.26 74.00 54.00 V 50.96 -2.83 48.13 74.00 54.00 V 46.75 0.57 47.32 74.00 54.00

Report No.: BZT-2013NT0821013F

- 2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.
 - 3) Average test would be performed if the peak result were greater than the average limit.
 - 4) Data of measurement shown "---"in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
 - 5) Emission Level=Peak (AV) Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss - Pre-amplifier
 - 6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

High chans	nel: 2480 M	Hz							
Freq. (MHz)	Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emissio Peak (dBuV/m)	AV (dBuV/m)	Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
1300.14	Н	50.85		-4.19	46.66		74.00	54.00	-7.34
4960.00	Н	51.29		-3.98	47.31		74.00	54.00	-6.69
5606.52	Н	52.65		-2.84	49.81		74.00	54.00	-4.19
7440.00	Н	43.22		0.57	43.79		74.00	54.00	-10.21
17360.00	Н	40.85		6.79	47.64		74.00	54.00	-6.36
24800.00	Н	38.74		8.16	46.90		74.00	54.00	-7.10
1310.42	V	52.65		-4.24	48.41		74.00	54.00	-5.59
4960.00	V	54.45		-3.98	50.47		74.00	54.00	-3.53
5623.45	V	49.33		-2.88	46.45		74.00	54.00	-7.55
7440.00	V	46.22		0.57	46.79		74.00	54.00	-7.21
17360.00	V	39.57		6.79	46.36		74.00	54.00	-7.64
24800.00	V	41.89		8.16	50.05		74.00	54.00	-3.95

Report No.: BZT-2013NT0821013F

- 2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.
 - 3) Average test would be performed if the peak result were greater than the average limit.
 - 4) Data of measurement shown "---"in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
 - 5) Emission Level=Peak (AV) Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss - Pre-amplifier
 - 6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

Modulation Type: 8DPSK

()									
Low chann	nel: 2402 MI	Hz							
Freq. (MHz)	Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emissio Peak (dBuV/m)	on Level AV (dBuV/m)	Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
1302.11	Н	51.35		-4.20	47.15		74.00	54.00	-6.85
4804.00	Н	52.34		-3.94	48.40		74.00	54.00	-5.60
5601.23	Н	49.85		-2.83	47.02		74.00	54.00	-6.98
7206.00	Н	44.96		0.52	45.48		74.00	54.00	-8.52
16814.00	Н	39.99		6.73	46.72		74.00	54.00	-7.28
24020.00	Н	40.36		8.11	48.47		74.00	54.00	-5.53
1314.12	V	52.78		-4.27	48.51		74.00	54.00	-5.49
4804.00	V	51.69		-3.94	47.75		74.00	54.00	-6.25
5614.75	V	49.87		-2.86	47.01		74.00	54.00	-6.99
7206.00	V	44.75		0.52	45.27		74.00	54.00	-8.73
16814.00	V	42.31		6.73	49.04		74.00	54.00	-4.96
24020.00	V	40.67		8.11	48.78		74.00	54.00	-5.22
i									

Report No.: BZT-2013NT0821013F

- 2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.
 - 3) Average test would be performed if the peak readings were greater than the average limit.
 - 4) Data of measurement shown "---"in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
 - 5) Emission Level=Peak (AV) Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss - Pre-amplifier
 - 6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

Middle cha	annel: 2441	MHz							
Freq. (MHz)	Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emissio Peak (dBuV/m)	ON Level AV (dBuV/m)	Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
1310.45	Н	51.36		-4.21	47.15		74.00	54.00	-6.85
4882.00	Н	50.89		-3.98	46.91		74.00	54.00	-7.09
5600.25	Н	48.78		-2.83	45.95		74.00	54.00	-8.05
7323.00	Н	44.92		0.57	45.49		74.00	54.00	-8.51
17087.00	Н	40.84		6.79	47.63		74.00	54.00	-6.37
24410.00	Н	39.68		8.16	47.84		74.00	54.00	-6.16
1301.33	V	52.04		-4.20	47.84		74.00	54.00	-6.16
4882.00	V	51.78		-3.98	47.80		74.00	54.00	-6.20
5613.88	V	50.85		-2.88	47.97		74.00	54.00	-6.03
7323.00	V	47.91		0.57	48.48		74.00	54.00	-5.52
17087.00	V	40.37		6.79	47.16		74.00	54.00	-6.84
24410.00	V	38.66		8.16	46.82		74.00	54.00	-7.18
									•

Report No.: BZT-2013NT0821013F

- 2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.
 - 3) Average test would be performed if the peak result were greater than the average limit.
 - 4) Data of measurement shown "---"in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
 - 5) Emission Level=Peak (AV) Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss - Pre-amplifier
 - 6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

nel: 2480 M	Hz							
Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emissio Peak (dBuV/m)	on Level AV (dBuV/m)	Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
Н	50.36		-4.22	46.14		74.00	54.00	-7.86
Н	51.86		-3.98	47.88		74.00	54.00	-6.12
Н	50.76		-2.82	47.94		74.00	54.00	-6.06
Н	45.76		0.57	46.33		74.00	54.00	-7.67
Н	40.85		6.79	47.64		74.00	54.00	-6.36
Н	40.63		8.16	48.79		74.00	54.00	-5.21
V	51.32		-4.26	47.06		74.00	54.00	-6.94
V	50.64		-3.98	46.66		74.00	54.00	-7.34
V	49.65		-2.87	46.78		74.00	54.00	-7.22
V	48.32		0.57	48.89		74.00	54.00	-5.11
V	40.85		6.79	47.64		74.00	54.00	-6.36
V	38.64		8.16	46.80		74.00	54.00	-7.20
	Ant. Pol. H/V H H H H V V V V	H/V reading (dBuV) H 50.36 H 51.86 H 50.76 H 45.76 H 40.85 H 40.63 V 51.32 V 50.64 V 49.65 V 48.32 V 40.85	Ant. Pol. H/V Peak reading (dBuV) (dBuV) (dBuV) AV reading (dBuV) H 50.36 H 51.86 H 50.76 H 45.76 H 40.85 H 40.63 V 51.32 V 50.64 V 49.65 V 40.85	Ant. Pol. H/V Peak reading (dBuV) (dBuV) AV reading (dBuV) Correction Factor (dB) H 50.36 -4.22 H 51.86 -3.98 H 50.76 -2.82 H 45.76 0.57 H 40.85 6.79 H 40.63 8.16 V 51.32 -4.26 V 50.64 -3.98 V 49.65 -2.87 V 48.32 0.57 V 40.85 6.79	Ant. Pol. H/V Peak reading (dBuV) AV reading (dBuV) Correction Factor (dB) Emission Peak (dBuV/m) H 50.36 -4.22 46.14 H 51.86 -3.98 47.88 H 50.76 -2.82 47.94 H 45.76 0.57 46.33 H 40.85 6.79 47.64 H 40.63 8.16 48.79 V 50.64 -3.98 46.66 V 49.65 -2.87 46.78 V 48.32 0.57 48.89 V 40.85 6.79 47.64	Ant. Pol. H/V Peak reading (dBuV) AV reading (dBuV) Correction Factor (dB) Emission Level Peak (dBuV/m) AV (dBuV/m) H 50.36 -4.22 46.14 H 51.86 -3.98 47.88 H 50.76 -2.82 47.94 H 45.76 0.57 46.33 H 40.85 6.79 47.64 H 40.63 8.16 48.79 V 50.64 -3.98 46.66 V 49.65 -2.87 46.78 V 48.32 0.57 48.89 V 40.85 6.79 47.64	Ant. Pol. H/V Peak reading (dBuV) AV reading (dBuV) Correction Factor (dB) Emission Level Peak (dBuV/m) Peak limit (dBuV/m) H 50.36 -4.22 46.14 74.00 H 51.86 -3.98 47.88 74.00 H 50.76 -2.82 47.94 74.00 H 45.76 0.57 46.33 74.00 H 40.85 6.79 47.64 74.00 H 40.63 8.16 48.79 74.00 V 50.64 -3.98 46.66 74.00 V 49.65 -2.87 46.78 74.00 V 48.32 0.57 48.89 74.00 V 40.85 6.79 47.64 74.00	Ant. Pol. H/V Peak reading (dBuV) AV reading (dBuV) Correction (dB) Emission Level Peak (dBuV/m) Peak Imit (dBuV/m) AV limit (dBuV/m) H 50.36 -4.22 46.14 74.00 54.00 H 51.86 -3.98 47.88 74.00 54.00 H 50.76 -2.82 47.94 74.00 54.00 H 45.76 0.57 46.33 74.00 54.00 H 40.85 6.79 47.64 74.00 54.00 H 40.63 8.16 48.79 74.00 54.00 V 51.32 -4.26 47.06 74.00 54.00 V 50.64 -3.98 46.66 74.00 54.00 V 49.65 -2.87 46.78 74.00 54.00 <td< td=""></td<>

Report No.: BZT-2013NT0821013F

- 2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.
 - 3) Average test would be performed if the peak result were greater than the average limit.
 - 4) Data of measurement shown "---"in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
 - 5) Emission Level=Peak (AV) Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss - Pre-amplifier
 - 6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

14.0 Antenna Requirement


14.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

14.2 Antenna Specification

According to the manufacturer declared, the EUT has a PCB Printed antenna; the directional gain of antenna is 0 dBi, and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.



ANTENNA

Report No.: BZT-2013NT0821013F

Report No.: BZT-2013NT0821013F

15.0 FCC ID Label

FCC ID: QOGMP03

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



FCC ID Label

-- End of the report--