

FCC RF Exposure Report

Report No.: SA200306C24

FCC ID: 2AARNWLTPH-8M

Test Model: WLTPH-8M

Received Date: Mar. 06, 2020

Test Date: Mar. 18 ~ Apr. 16, 2020

Issued Date: Apr. 21, 2020

Applicant: PHIHONG TECHNOLOGY CO., LTD.

Address: No. 568, Fuxing 3rd Rd., Guishan Dist., Taoyuan City, 333 Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

FCC Registration / 788550 / TW0003
Designation Number:



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
3.1 Limits for Maximum Permissible Exposure (MPE).....	5
3.2 MPE Calculation Formula	5
3.3 Classification	5
3 Calculation Result of Maximum Density Power	6

Release Control Record

Issue No.	Description	Date Issued
SA200306C24	Original release	Apr. 21, 2020

1 Certificate of Conformity

Product: LTE Module

Brand: PHIHONG

Test Model: WLTPH-8M

Sample Status: Engineering Sample

Applicant: PHIHONG TECHNOLOGY CO., LTD.

Test Date: Mar. 18 ~ Apr. 16, 2020

Standards: FCC Part 2 (Section 2.1091)

References Test KDB 447498 D01 General RF Exposure Guidance v06

Guidance: IEEE C95.3 -2002

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :

Pettie Chen

Date:

Apr. 21, 2020

Pettie Chen / Senior Specialist

Approved by :

Bruce Chen

Date:

Apr. 21, 2020

Bruce Chen / Senior Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.
So, this device is classified as **Mobile Device**.

3 Calculation Result of Maximum Density Power

Function	Frequency Band (MHz)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA Band 2	1850.7-1909.3	25.12	20	0.065	1
WCDMA Band 4	1712.4-1752.6	24.82	20	0.060	1
LTE Band 2	1850.7-1909.3	24.99	20	0.063	1
LTE Band 4	1710.7-1754.3	25.35	20	0.068	1
LTE Band 66	1710.7-1779.3	25.20	20	0.066	1

Function	Frequency Band (MHz)	ERP (dBm)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA Band 5	826.4-846.6	23.32	25.47	20	0.070	0.551
LTE Band 5	824.7-848.3	23.52	25.67	20	0.073	0.550
LTE Band 12	699.7-715.3	23.58	25.73	20	0.074	0.466
LTE Band 13	779.5-784.5	23.90	26.05	20	0.080	0.520
LTE Band 14	790.5-795.5	23.30	25.45	20	0.070	0.527
LTE Band 71	665.5-695.5	23.44	25.59	20	0.072	0.444

EIRP = ERP + 2.15dB

*Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

--- END ---