



## 14. Radio Frequency Exposure

### 14.1 Applicable Standards

<input type="checkbox"/> §1.1307(b)(3)(i)(A)	The available maximum time-averaged power is no more than 1 mW, regardless of separation distance.																																										
<input checked="" type="checkbox"/> §1.1307(b)(3)(i)(c)	<p>ERP is below a threshold calculated based on the distance , R between the person and the antenna / radiating structure, where <math>R &gt; \lambda / 2\pi</math>.</p> <p style="text-align: center;">TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">RF Source Frequency</th> <th colspan="2"></th> <th colspan="2">Minimum Distance</th> <th>Threshold ERP</th> </tr> <tr> <th><math>f_L</math> MHz</th> <th></th> <th><math>f_H</math> MHz</th> <th><math>\lambda_L / 2\pi</math></th> <th><math>\lambda_H / 2\pi</math></th> <th>W</th> </tr> </thead> <tbody> <tr> <td>0.3</td> <td>—</td> <td>1.34</td> <td>159 m</td> <td>—</td> <td>1,920 <math>R^2</math></td> </tr> <tr> <td>1.34</td> <td>—</td> <td>30</td> <td>35.6 m</td> <td>—</td> <td>3,450 <math>R^2/f^2</math></td> </tr> <tr> <td>30</td> <td>—</td> <td>300</td> <td>1.6 m</td> <td>—</td> <td>3.83 <math>R^2</math></td> </tr> <tr> <td>300</td> <td>—</td> <td>1,500</td> <td>159 mm</td> <td>—</td> <td>0.0128 <math>R^2/f</math></td> </tr> <tr> <td>1,500</td> <td>—</td> <td>100,000</td> <td>31.8 mm</td> <td>0.5 mm</td> <td>19.2 <math>R^2</math></td> </tr> </tbody> </table> <p>Subscripts L and H are low and high; <math>\lambda</math> is wavelength. From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.</p>	RF Source Frequency			Minimum Distance		Threshold ERP	$f_L$ MHz		$f_H$ MHz	$\lambda_L / 2\pi$	$\lambda_H / 2\pi$	W	0.3	—	1.34	159 m	—	1,920 $R^2$	1.34	—	30	35.6 m	—	3,450 $R^2/f^2$	30	—	300	1.6 m	—	3.83 $R^2$	300	—	1,500	159 mm	—	0.0128 $R^2/f$	1,500	—	100,000	31.8 mm	0.5 mm	19.2 $R^2$
RF Source Frequency			Minimum Distance		Threshold ERP																																						
$f_L$ MHz		$f_H$ MHz	$\lambda_L / 2\pi$	$\lambda_H / 2\pi$	W																																						
0.3	—	1.34	159 m	—	1,920 $R^2$																																						
1.34	—	30	35.6 m	—	3,450 $R^2/f^2$																																						
30	—	300	1.6 m	—	3.83 $R^2$																																						
300	—	1,500	159 mm	—	0.0128 $R^2/f$																																						
1,500	—	100,000	31.8 mm	0.5 mm	19.2 $R^2$																																						
<input type="checkbox"/> § 1.1307(b)(3)(i)(B).	<p>Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, <math>\leq P_{th}</math></p> $P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$ <p>Where</p> $x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$ <p>and</p> $ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$ <p><math>d</math> = the separation distance (cm);</p>																																										



## 14.2 EUT Specification

<b>Frequency band (Operating)</b>	902MHz~928MHz
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>40cm separation)
<b>Antenna diversity</b>	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Evaluation applied</b>	<input type="checkbox"/> Blanket 1 mW Blanket Exemption <input checked="" type="checkbox"/> MPE-based Exemption <input type="checkbox"/> SAR-based Exemption

**Remark:**

1. *The maximum conducted output power is 27.54 dBm (567.545 mW) at 908.5MHz (with 8dBi antenna gain.) Lora 125K*

## 14.3 Results

Lora 125K

Channel Frequency (MHz)	Max. Conducted output power(dBm)	Max. Tune up power (dBm)	Antenna Gain(dBi)	Distance (cm)	EIRP (dBm)	ERP (dBm)	ERP (W)	ERP Limit (W)
908.5	27.54	28.04	8	50	36.04	33.89	2.45	2.91

No non-compliance noted.

-----THE END OF REPORT-----