FCC ID: 2AASC-81013

RF EXPOSURE EVALUATION METHOD

FCC ID: 2AASC-81013

SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and \leq 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [$\sqrt{f(GHz)}$] \leq 3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR,where f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation. The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is ≤ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Maximum measured transmitter power.

BT

1Mbps							
Test Channel	Frequency	Peak Output Power	Peak Output Power				
	(MHz)	(dBm)	(mW)				
CH00	2402	0.107	1.025				
CH39	2441	-0.739	0.844				
CH78	2480	0.130	1.030				
2Mbps							
CH00	2402	-0.444	0.903				
CH39	2441	-1.047	0.786				
CH78	2480	-0.440	0.904				
3Mbps							
CH00	2402	0.027	1.006				
CH39	2441	-0.751	0.841				
CH78	2480	-0.009	0.998				

Remark: The best case gain of the antenna is 1.0dBi.

FCC ID: 2AASC-81013

1.0 dBi logarithmic terms convert to numeric result is nearly 1.26

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by: [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance,mm)] • [$\sqrt{f(GHz)}$]

BT

Mode	[(max. power of channel, including tune-up tolerance, mW)	(min. test separation distance,mm)]	[√f(GHz)]	Result	Limit		
1Mbps							
CH00	1.025	5	2.402	0.318	3		
CH39	0.844	5	2.441	0.264	3		
CH78	1.030	5	2.480	0.325	3		
2Mbps							
CH00	0.903	5	2.402	0.280	3		
CH39	0.786	5	2.441	0.246	3		
CH78	0.904	5	2.480	0.285	3		
3Mbps							
CH00	1.006	5	2.402	0.312	3		
CH39	0.841	5	2.441	0.263	3		
CH78	0.998	5	2.480	0.314	3		

The test Result is less than 3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR.

Conclusion: No SAR is required.