

Report No.: AGC00200130801FE02 Page 1 of 61

FCC Test Report

Report No.: AGC00200130801FE02

FCC ID : 2AASJSMD-1770B

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION: GSM Mobile Phone

BRAND NAME : DAEWOO

MODEL NAME : SMD-1770B

CLIENT : Daewoo International Corp.

DATE OF ISSUE : Aug.12,2013

STANDARD(S) : FCC Part 22H & 24E Rules

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd.

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

Report No.: AGC00200130801FE02 Page 2 of 61

REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Aug.12,2013	Valid	Original Report

TABLE OF CONTENTS

1. GENERAL INFORMATION	7
1.1 PRODUCT DESCRIPTION	7
1.2 RELATED SUBMITTAL(S) / GRANT (S)	8
1.3 TEST METHODOLOGY	9
1.4 TEST FACILITY	9
1.5 MEASUREMENT INSTRUMENTS	9
1.6 SPECIAL ACCESSORIES	9
1.7 EQUIPMENT MODIFICATIONS	9
2. SYSTEM TEST CONFIGURATION	10
2.1 EUT CONFIGURATION	10
2.2 EUT EXERCISE	10
2.3 GENERAL TECHNICAL REQUIREMENTS	10
2.4 CONFIGURATION OF EUT SYSTEM	11
3. SUMMARY OF TEST RESULTS	12
4. DESCRIPTION OF TEST MODES	12
5. OUTPUT POWER	13
5.1 CONDUCTED OUTPUT POWER	13
5.2 RADIATED OUTPUT POWER	16
6. PEAK-TO-AVERAGE RATIO	20
6.1 MEASUREMENT METHOD	20
6.2 PROVISIONS APPLICABLE	20
6.3 MEASUREMENT RESULT	21
7. SPURIOUS EMISSION	22
7.1 CONDUCTED SPURIOUS EMISSION	22
7.2 RADIATED SPURIOUS EMISSION	24
8. MAINS CONDUCTED EMISSION	28

8.1 MEASUREMENT METHOD	28
8.2 PROVISIONS APPLICABLE	28
8.3 MEASUREMENT RESULT	29
9. FREQUENCY STABILITY	31
9.1 MEASUREMENT METHOD	31
9.2 PROVISIONS APPLICABLE	31
9.3 MEASUREMENT RESULT (WORST TEST)	32
10. OCCUPIED BANDWIDTH	34
10.1 MEASUREMENT METHOD	34
10.2 PROVISIONS APPLICABLE	34
10.3 MEASUREMENT RESULT	34
11. EMISSION BANDWIDTH	35
11.1 MEASUREMENT METHOD	35
11.2 PROVISIONS APPLICABLE	35
11.3 MEASUREMENT RESULT	35
12. BAND EDGE	36
12.1 MEASUREMENT METHOD	36
12.2 PROVISIONS APPLICABLE	36
12.3 MEASUREMENT RESULT	36
APPENDIX I	37
TEST PLOTS FOR CONDUCTED SPURIOUS EMISSION	37
APPENDIX II	45
TEST PLOTS FOR OCCUPIED BANDWIDTH (99%)	45
EMISSION BANDWIDTH (-26DBC)	45
APPENDIX III	49
TEST PLOTS FOR BAND EDGES	49

Page 5 of 61

APPENDIX IV	52
PHOTOGRAPHS OF TEST SETUP	52
110100174 110 01 1201 02101	02
APPENDIX V	5.1
AFFLINDIA V	54
	- 4
PHOTOGRAPHS	54

Page 6 of 61

VERIFICATION OF COMPLIANCE

Applicant	Daewoo International Corp.	
Address	84-11, Namdaemunno 5-ga, Jung-gu, Seoul 100-753 Korea	
Manufacturer	United Creation Technology Co., Ltd.	
Address	Room 201, Block A, Science and technology building phase-II, Nanhai Road 1057, Shekou, Nanshan district, Shenzhen, CN.	
Product Designation	GSM Mobile Phone	
Brand name	DAEWOO	
Test Model	SMD-1770B	
Date of Test	Aug.06, 2013 to Aug.09, 2013	
Deviation	None	
Condition of Test Sample	Normal	
Report Template	AGCRT-US-2.5G/RF (2013-03-01)	

WE HEREBY CERTIFY THAT:

The above equipment was tested by Attestation of Global Compliance(Shenzhen) Co., Ltd. The data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C 63.4:2003 and TIA/EIA 603. The sample tested as described in this report is in compliance with the FCC Rules Part 22H and 24E. The test results of this report relate only to the tested sample identified in this report.

Tested By :	East	Hie
	Bart Xie	Aug.12,2013
Reviewed By :	Jones.	
	Forrest Lei	Aug.12,2013
Approved By:	Solger	Zhang
	Solger Zhang	Aug.12,2013

Page 7 of 61

1. GENERAL INFORMATION

1.1 PRODUCT DESCRIPTION

A major technical description of EUT is described as following:

Product Designation:	GSM Mobile Phone		
Hardware Version:	92718_1_11		
Software Version:	N/A		
Frequency Bands:	☐GSM 850 ☐PCS 1900 (U.S. Bands)		
rrequerity Barids.	☐GSM 900 ☐DCS 1800 (Non-U.S. Bands)		
Antenna:	PIFA Antenna		
Antenna gain:	1.0dBi		
Battery parameter:	DC3.7V/700 mAh		
Adapter Input:	AC100-240V, 50-60Hz, 0.12A		
Adapter Output:	DC5.0V, 500mA		
	30.63 dBm Maximum ERP measured for GSM 850		
Outrat Barrer	31.55 dBm Maximum Average Burst Power for GSM 850		
Output Power:	28.37 dBm Maximum EIRP measured for PCS 1900		
	28.81 dBm Maximum Average Burst Power for PCS 1900		
Dual SIM Card:	The result for SIM1 is the worst case which was only recorded		
GPRS Class:	12		
Extreme Vol. Limits:	DC 3.4 V to DC4.2 V (Nominal DC 3.7 V)		
Extreme Temp. Tolerance:	-10℃ to +50℃		
** Note: The High Voltage DC 4.2V and Low Voltage DC 3.4V were declared by manufacturer, The			
EUT could not operate normally	with higher or lower voltage.		
Other functions have been perform	rmed according to verification procedure except for MS function.		
SIM1 can't transmit with SIM2 simultaneously.			

Page 8 of 61

1.2 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for FCC ID: 2AASJSMD-1770B filing to comply with the FCC Part 22H and 24E requirements.

Page 9 of 61

1.3 TEST METHODOLOGY

The radiated emission testing was performed according to the procedures of ANSI C 63.4: 2003; TIA/EIA 603 and FCC CFR 47 Rules of 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057.

1.4 TEST FACILITY

The test site used to collect the radiated data is located at:

Attestation of Global Compliance (Shenzhen) Co., Ltd.

2/F., Building 2, No.1-No.4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen, Guangdong, China

The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003.

FCC register No.: 259865

1.5 MEASUREMENT INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Calibration Date	Calibration Due.
SPECTRUM ANALYZER	AGILENT	E4440A	US41421290	July 17, 2013	July 16, 2014
TEST RECEIVER	R&S	ESCI	100694	July 17, 2013	July 16, 2014
COMMUNICATION TESTER	AGILENT	8960	GB46310822	Oct.22, 2012	Oct.21, 2013
COMMUNICATION TESTER	R&S	CMU200	122500166	Feb.28, 2013	Feb.27, 2014
TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100694	July 17, 2013	July 16, 2014
LISN	R&S	ESH3-Z5	8389791009	July 17, 2013	July 16, 2014
CLIMATE CHAMBER	ALBATROSS			July 17, 2013	July 16, 2014
Loop Antenna	Daze	ZN30900N	SEL0097	July 17, 2013	July 16, 2014
Bilogical Antenna	A.H. Systems Inc.	SAS-521-4	26	June 7, 2013	June 6, 2014
Horn Antenna	EM	EM-AH-10180	67	Apr.20, 2013	Apr.19, 2014
Horn Antenna	A.H. Systems Inc.	SAS-574		June 7, 2013	June 6, 2014

1.6 SPECIAL ACCESSORIES

The battery and the charger, earphone supplied by the applicant were used as accessories and being tested with EUT intended for FCC grant together.

1.7 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

Page 10 of 61

2. SYSTEM TEST CONFIGURATION

2.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT EXERCISE

The Transmitter was operated in the maximum output power mode through Communication Tester. The TX frequency was fixed which was for the purpose of the measurements.

2.3 GENERAL TECHNICAL REQUIREMENTS

Item Number	lte	FCC Rules		
4	Output Dawer	Conducted	22.913(a) / 24.232 (b)	
1	Output Power	Radiated		
2	Peak-to-Average	Dock to Average Datio	24 222(4)	
2	Ratio	Peak-to-Average Ratio	24.232(d)	
2	Spurious	Conducted Spurious Emission	2 4054 / 22 047 / 24 220	
3	Emission	Radiated Spurious Emission	2.1051 / 22.917 / 24.238	
4	Mains Conducted Emission		15.107 / 15.207	
5	Frequency Stability		2.1055 /24.235	
6	Occupied Bandwidth		2.1049 (h)(i)	
7	Emission Bandwidth		22.917(b) / 24.238 (b)	
8	Band Edge		22.917(b) / 24.238 (b)	

Page 11 of 61

2.4 CONFIGURATION OF EUT SYSTEM

Fig. 2-1 Configuration of EUT System



Table 2-1 Equipment Used in EUT System

Item	Equipment	Model No.	ID or Specification	Note
1	GSM Mobile Phone	SMD-1770B	FCC ID: 2AASJSMD-1770B	EUT
2	Adapter	SMD-1770B	DC5.0V /500mA	Accessory
3	Battery	SMD-1770B	DC3.7V/ 700 mAh	Accessory
4	Earphone	SMD-1770B	N/A	Accessory
5	USB Cable	N/A	N/A	Accessory

Note: All the accessories have been used during the test. The following "EUT" in setup diagram means EUT system.

Page 12 of 61

3. SUMMARY OF TEST RESULTS

Item Number	Item Description		FCC Rules	Result
4 0 4 4 5		Conducted Output Power	22.042(-) / 24.222 (b)	D
1	Output Power	Radiated Output Power	22.913(a) / 24.232 (b)	Pass
0	Peak-to-Average	Dook to Average Detic	24 222(4)	Pass
2	Ratio	Peak-to-Average Ratio	24.232(d)	
3	Caurious Emission	Conducted Spurious Emission	2 1051/22 017/ 24 229	Pass
3	Spurious Emission	Radiated Spurious Emission	2.1051/22.917/ 24.238	
4	Mains	Mains Conducted Emission		Pass
5	Frequency Stability		2.1055 /24.235	Pass
6	Occupied Bandwidth		2.1049 (h)(i)	Pass
7	Emission Bandwidth		22.917(b) / 24.238 (b)	Pass
8	Band Edge		22.917(b) / 24.238 (b)	Pass

4. DESCRIPTION OF TEST MODES

During the testing, the EUT (Quad-band GSM / GPRS Mobile Phone) was controlled via Rhode & Schwarz Digital Radio Communication Tester (CMU 200) to ensure max power transmission and proper modulation. Three channels (The top channel, the middle channel and the bottom channel) were chosen for testing on both GSM and PCS frequency band.

Note: GSM and GPRS modes have been tested during the test. The worst condition (GSM) be recorded in the test report if no other modes test data.

Page 13 of 61

5. OUTPUT POWER

5.1 CONDUCTED OUTPUT POWER

5.1.1 MEASUREMENT METHOD

The EUT was setup for the max output power with pseudo random data modulation. Power was measured with Spectrum Analyzer. The measurements were performed on all modes(GSM, GPRS,) at 3 typical channels(the Top Channel, the Middle Channel and the Bottom Channel) for both GSM band and PCS band.

5.1.2 PROVISIONS APPLICABLE

Conducted Output Power Limits for GSM 850 MHz				
Mode Power Step Nominal Peak Power Tolerance				
GSM	5	33 dBm (2W)	-1	
GPRS	3	33 dBm (2W)	-1	

Conducted Output Power Limits for PCS 1900 MHz				
Mode Power Step Nominal Peak Power Tolerance(dB				
GSM	0	30 dBm (1W)	-1	
GPRS	3	30 dBm (1W)	-1	

Page 14 of 61

5.1.3 MEASUREMENT RESULT

Test Result of Conducted Output Power for GSM 850 MHZ (SIM1)

Mede	Frequency	Reference	Peak	Toloronoo	Avg.Burst	Duty cycle	Frame
Mode	(MHz)	Power	Power	Tolerance	Power	Factor(dB)	Power(dBm)
	824.2	33	32.39	-0.61	31.55	-9	22.55
GSM(SIM1)	836.6	33	32.28	-0.72	31.46	-9	22.46
	848.8	33	32.34	-0.66	31.53	-9	22.53
GPRS850	824.2	33	32.37	-0.63	31.45	-9	22.45
(1 Slot)	836.6	33	32.24	-0.76	31.47	-9	22.47
	848.8	33	32.29	-0.71	31.37	-9	22.37
GPRS850	824.2	30	29.45	-0.55	28.55	-6	22.55
(2 Slot)	836.6	30	29.36	-0.64	28.52	-6	22.52
	848.8	30	29.32	-0.68	28.47	-6	22.47
GPRS850	824.2	28.23	27.49	-0.74	26.6	-4.26	22.34
(3 Slot)	836.6	28.23	27.58	-0.65	26.51	-4.26	22.25
	848.8	28.23	27.52	-0.71	26.58	-4.26	22.32
GPRS850	824.2	27	26.5	-0.5	25.7	-3	22.7
(4 Slot)	836.6	27	26.41	-0.59	25.56	-3	22.56
	848.8	27	26.36	-0.64	25.54	-3	22.54

Page 15 of 61

Test Result of Conducted Output Power for PCS 1900 MHZ (SIM1)

Mode	Frequency (MHz)	Reference Power	Peak Power	Tolerance	Avg.Burst Power	Duty cycle Factor(dB)	Frame Power(dBm)
	1850.2	30	29.56	-0.44	28.81	-9	19.81
GSM(SIM1)	1880	30	29.48	-0.52	28.55	-9	19.55
	1909.8	30	29.44	-0.56	28.66	-9	19.66
CDDC1000	1850.2	30	29.53	-0.47	28.63	-9	19.63
GPRS1900	1880	30	29.4	-0.6	28.43	-9	19.43
(1 Slot)	1909.8	30	29.35	-0.65	28.62	-9	19.62
GPRS1900	1850.2	27	26.32	-0.68	25.89	-6	19.89
(2 Slot)	1880	27	26.49	-0.51	25.82	-6	19.82
(2 3101)	1909.8	27	26.42	-0.58	25.76	-6	19.76
CDDC1000	1850.2	25.23	24.68	-0.55	24.63	-4.26	20.37
GPRS1900 (3 Slot)	1880	25.23	24.64	-0.59	24.6	-4.26	20.34
(3 3101)	1909.8	25.23	24.61	-0.62	24.54	-4.26	20.28
CDDC4000	1850.2	24	23.88	-0.12	22.66	-3	19.66
GPRS1900	1880	24	23.69	-0.31	22.57	-3	19.57
(4 Slot)	1909.8	24	23.58	-0.42	22.42	-3	19.42

Test Result of Conducted Output Power for GSM 850 MHZ and PCS 1900 MHz(SIM 2)					
Mode	Maximum Conducted Power(dBm)	Average Burst Power(dBm)	Duty cycle Factor (dB)	Frame Power (dBm)	
GSM 850 MHZ for (SIM2)	32.34	31.46	-9	22.46	
PCS 1900 MHZ for (SIM2)	29.51	28.77	-9	19.77	

Page 16 of 61

5.2 RADIATED OUTPUT POWER

5.2.1 MEASUREMENT METHOD

The measurements procedures specified in TIA-603C-2004 were applied.

- In an anechoic antenna test chamber, a half-wave dipole antenna for the frequency band of interest is placed at the reference centre of the chamber. An RF Signal source for the frequency band of interest is connected to the dipole with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A known (measured) power (Pin) is applied to the input of the dipole, and the power received (Pr) at the chamber's probe antenna is recorded.
- 2 The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established as ARpl=Pin + 2.15 Pr. The ARpl is the attenuation of "reference path loss", and including the gain of receive antenna, the cable loss and the air loss. The measurement results are obtained as described below: Power=PMea+ARpl
- 3 The EUT is substituted for the dipole at the reference centre of the chamber and a scan is performed to obtain the radiation pattern.
- 4 From the radiation pattern, the co-ordinates where the maximum antenna gain occurs are identified.
- 5 The EUT is then put into continuously transmitting mode at its maximum power level.
- Power mode measurements are performed with the receiving antenna placed at the coordinates determined in Step 3 to determine the output power as defined in Rule 24.232 (b) and (c). The "reference path loss" from Step1 is added to this result.
- 7 This value is EIRP since the measurement is calibrated using a half-wave dipole antenna of known gain (2.15 dBi) and known input power (Pin).
- 8 ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi..

5.2.2 PROVISIONS APPLICABLE

This is the test for the maximum radiated power from the EUT. Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 22.913(a) specifies "Maximum ERP. The effective radiated power (ERP) of base transmitters and cellular repeaters must not exceed 500 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

Report No.: AGC00200130801FE02 Page 17 of 61

Radiated Power Limits for GSM 850 MHZ (ERP)				
Mode Power Step Nominal Peak Power				
GSM	5	<=38.45 dBm (7W)		
GPRS	3	<=38.45 dBm (7W)		

Radiated Power Limits for PCS 1900 MHZ (E.I.R.P.)				
Mode Power Step Nominal Peak Power				
GSM	0	<=33 dBm (2W)		
GPRS	3	<=33 dBm (2W)		

Report No.: AGC00200130801FE02 Page 18 of 61

5.2.3 MEASUREMENT RESULT

	Radiated Power (ERP) for GSM 850 MHZ				
			Res	ult	
Mode	Frequency	Power Step	Max. Peak ERP	Polarization	Conclusion
			(dBm)	Of Max. ERP	
	824.2	5	30.63	Horizontal	Pass
GSM	836.6	5	30.52	Horizontal	Pass
	848.8	5	30.48	Horizontal	Pass
CDDC	824.2	3	30.57	Horizontal	Pass
GPRS 836.6	3	30.46	Horizontal	Pass	
1 5101	1 slot 848.8	3	30.42	Horizontal	Pass
GPRS	824.2	3		Horizontal	Pass
2 slots	836.6	3		Horizontal	Pass
2 51015	848.8	3		Horizontal	Pass
CDDC	824.2	2	Less than	Horizontal	Pass
GPRS 3 slots	836.6	2		Horizontal	Pass
3 81018	848.8	2	27 dBm	Horizontal	Pass
CDDC	824.2	2		Horizontal	Pass
GPRS	836.6	2		Horizontal	Pass
4 slots	848.8	2]	Horizontal	Pass

Page 19 of 61

	Radiated Power (E.I.R.P) for PCS 1900 MHZ				
			R	esult	
Mode	Frequency	Power Step	Max. Peak	Polarization	Conclusion
			E.I.R.P.(dBm)	Of Max. E.I.R.P.	
	1850.2	0	28.37	Horizontal	Pass
GSM	1880.0	0	28.29	Horizontal	Pass
	1909.8	0	28.23	Horizontal	Pass
GPRS	1850.2	3	28.26	Horizontal	Pass
1slot	1880.0	3	28.17	Horizontal	Pass
15101	1909.8	3	28.13	Horizontal	Pass
GPRS	1850.2	3		Horizontal	Pass
2 slots	1880.0	3		Horizontal	Pass
2 51015	1909.8	3		Horizontal	Pass
GPRS	1850.2	2	l coo than	Horizontal	Pass
3 slots	1880.0	2	Less than 27 dBm	Horizontal	Pass
3 81018	1909.8	2	27 dBm	Horizontal	Pass
CDDC	1850.2	2		Horizontal	Pass
4 slots	GPRS 1880.0 2		Horizontal	Pass	
4 51015	1909.8	2		Horizontal	Pass

Page 20 of 61

6. PEAK-TO-AVERAGE RATIO

6.1 MEASUREMENT METHOD

The following steps outline the procedure used to measure the Peak-to-Average Ratio from the EUT.

- 1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
- 2. For GSM/EGPRS operating modes:
- a. Set the RBW = 1MHz, VBW = 1MHz, Peak detector in spectrum analyzer.
- b. Set EUT in maximum power output, and triggered the burst signal.
- c. Measured respectively the Peak level and Mean level, and the deviation was recorded as Peak to Average Ratio.
- 3. For UMTS operating modes:
- a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
- b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.

6.2 PROVISIONS APPLICABLE

This is the test for the Peak-to-Average Ratio from the EUT.

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

Page 21 of 61

6.3 MEASUREMENT RESULT

Modes	GSM850(GSM)		
Channel	128	190	251
Shamer	(Low)	(Mid)	(High)
Frequency	824.2	836.6	848.8
(MHz)	024.2	030.0	040.0
Peak-To-Average Ratio (dB)	0.84	0.82	0.81

Modes	PCS 1900 (GSM)		
Channel	512	661	810
Shamer	(Low)	(Mid)	(High)
Frequency	1850.2	1880	1909.8
(MHz)	1030.2	1000	1303.0
Peak-To-Average Ratio (dB)	0.75	0.93	0.78

Page 22 of 61

7. SPURIOUS EMISSION

7.1 CONDUCTED SPURIOUS EMISSION

7.1.1 MEASUREMENT METHOD

The following steps outline the procedure used to measure the conducted emissions from the EUT.

- 1, Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM850, data taken from 30 MHz to 9 GHz.
- 2, Determine EUT transmit frequencies: the following typical channels were chosen to conducted emissions testing.

Typical Channels for testing of GSM 850 MHz			
Channel	Frequency (MHz)		
128	824.2		
190	836.6		
251	848.8		

Typical Channels for testing of PCS 1900 MHz			
Channel	Frequency (MHz)		
512	1850.2		
661	1880.0		
810	1909.8		

7.1.2 PROVISIONS APPLICABLE

On any frequency outside frequency band of the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log(P) dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.

Page 23 of 61

7.1.3 MEASUREMENT RESULT

	Conducted Spurious Emission for GSM 850 MHz										
Harmonic	Tx ch. 128 Freq. (MHz)	Level (dBm)	Tx ch. 190 Freq. (MHz)	Level (dBm)	Tx ch. Freq. (MHz) 251	Level (dBm)					
2	1648.4	B.I.N.F	1673.2	B.I.N.F	1697.6	B.I.N.F					
3	2472.6	B.I.N.F	2509.8	B.I.N.F	2546.4	B.I.N.F					
4	3296.8	B.I.N.F	3346.4	B.I.N.F	3395.2	B.I.N.F					
5	4121	B.I.N.F	4183	B.I.N.F	4244	B.I.N.F					
6	4945.2	B.I.N.F	5019.6	B.I.N.F	5092.8	B.I.N.F					
7	5769.4	B.I.N.F	5856.2	B.I.N.F	5941.6	B.I.N.F					
8	6593.6	B.I.N.F	6692.8	B.I.N.F	6790.4	B.I.N.F					
9	7417.8	B.I.N.F	7529.4	B.I.N.F	7639.2	B.I.N.F					
10	8242	B.I.N.F	8366	B.I.N.F	8488	B.I.N.F					
B.I.N.F	: Below Instrumen	ts Noise flo	or								

	Conducted Spurious Emission for PCS 1900 MHz										
Harmonic	Tx ch. 512 Freq. (MHz)	Level (dBm)	Tx ch. 661 Freq. (MHz)	Level (dBm)	Tx ch. 810 Freq. (MHz)	Level (dBm)					
2	3700.4	B.I.N.F	3760	B.I.N.F	3819.6	B.I.N.F					
3	5550.6	B.I.N.F	5640	B.I.N.F	5729.4	B.I.N.F					
4	7400.8	B.I.N.F	7520	B.I.N.F	7639.2	B.I.N.F					
5	9251.0	B.I.N.F	9400	B.I.N.F	9549.0	B.I.N.F					
6	11101.2	B.I.N.F	11280	B.I.N.F	11458.8	B.I.N.F					
7	12951.4	B.I.N.F	13160	B.I.N.F	13368.6	B.I.N.F					
8	14801.6	B.I.N.F	15040	B.I.N.F	15278.4	B.I.N.F					
9	16651.8	B.I.N.F	16920	B.I.N.F	17188.2	B.I.N.F					
10	18502.0	B.I.N.F	18800	B.I.N.F	19098.0	B.I.N.F					
B.I.N.F	: Below Instrumen	ts Noise flo	or								

Note: Below 30MHZ no Spurious found and The GSM modes is the worst condition.

Page 24 of 61


7.2 RADIATED SPURIOUS EMISSION

7.2.1 MEASUREMENT METHOD

The measurements procedures specified in TIA-603C-2004 were used for testing. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set 1MHz as outlined in Part 24.238. The measurements were performed on all modes(GSM, GPRS) at 3 typical channels(the Top Channel, the Middle Channel and the Bottom Channel) for both GSM band and PCS band.


The procedure of radiated spurious emissions is as follows:

a) Pre-calibration With pre-calibration method, the Radiated Spurious Emissions(RSE) is calculated as, RSE=Rx(dBuV)+CL(dB)+SA(dB)+Gain(dBi)-107(dBuV to dBm) The SA is calibrated using following setup.



b) EUT was placed on a 0.8 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the test item for emission measurements. The height of receiving antenna is 0.8m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the test item and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector and 1MHz bandwidth.

Page 25 of 61



Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS band (1850.2 MHz, 1880 MHz and 1909.8 MHz) ,GSM850 band (824.2MHz, 836.6MHz, 848.8MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900 ,GSM850 into any of the other blocks.

The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss and the air loss. The measurement results are obtained as described below: Power=P_{Mea}+A_{Rpl}

7.2.2 PROVISIONS APPLICABLE

(a) On any frequency outside a IMOBOnsee's frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log(P) dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Report No.: AGC00200130801FE02 Page 26 of 61

7.2.3 MEASUREMENT RESULT

The Worst Test Results for Channel 128 / 824.2 MHz								
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity			
1648.00	-34.23	-5.01	-39.24	-13.00	Horizontal			
1752.00	-36.24	-2.18	-38.42	-13.00	Vertical			
2472.00	-35.29	3.46	-31.83	-13.00	Horizontal			
9086.00	-36.59	2.79	-33.80	-13.00	Horizontal			

The Worst Test Results for Channel 190/836.6 MHz								
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity			
1673.00	-41.15	-3.22	-44.37	-13.00	Horizontal			
1903.00	-37.86	-0.24	-38.10	-13.00	Vertical			
9089.00	-39.82	3.98	-35.84	-13.00	Vertical			

The Worst Test Results for Channel 251/848.8 MHz								
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity			
1698.00	-37.58	-2.26	-39.84	-13.00	Horizontal			
1888.50	-36.64	-3.12	-39.76	-13.00	Vertical			
2131.00	-40.74	-1.74	-42.48	-13.00	Vertical			
9089.00	-38.56	8.46	-30.10	-13.00	Horizontal			

The Worst Test Results for Channel 512/1850.2 MHz								
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity			
1999.00	-42.74	9.5	-33.24	-13.00	Horizontal			
3700.00	-35.83	8.74	-27.09	-13.00	Horizontal			
12950.40	-32.27	11.56	-20.71	-13.00	Vertical			
17919.60	-41.92	17.89	-24.03	-13.00	Vertical			

Page 27 of 61

	The Worst Test Results for Channel 661/1880.0 MHz								
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity				
2000.50	-43.75	9.7	-34.05	-13.00	Vertical				
9399.00	-42.63	11.6	-31.03	-13.00	Vertical				
13160.40	-39.63	14.89	-24.74	-13.00	Horizontal				
15039.60	-38.61	13.87	-24.74	-13.00	Vertical				
17941.20	-39.58	19.76	-19.82	-13.00	Horizontal				
	The Worst Tes	t Results for	Channel 810/	1909.8 MHz					
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity				
2000.00	-40.36	10.02	-30.34	-13.00	Vertical				
9548.50	-37.75	11.3	-26.45	-13.00	Horizontal				
13367.40	-41.64	12.4	-29.24	-13.00	Horizontal				
15277.80	-38.77	18.03	-20.74	-13.00	Vertical				
17931.60	-39.56	19	-20.56	-13.00	Horizontal				

 $\textbf{Note:} \ \ \textbf{Below 30MHZ no Spurious found and The GSM modes is the worst condition}.$

Page 28 of 61

8. MAINS CONDUCTED EMISSION

8.1 MEASUREMENT METHOD

The measurement procedure specified in ANSI C63.4-2003 was used for testing. Conducted Emission was measured with travel charger.

8.2 PROVISIONS APPLICABLE

Frequency of Emission (MHz)	Conducted Limit(dBuV)				
	Quasi-Peak	Average			
0.15 – 0.5	66 to 56 *	56 to 46 *			
0.5 – 5	56	46			
5 – 30	60	50			


^{*}Decreases with the logarithm of the frequency.

^{*}The lower limit shall apply at the transition frequency.

Page 29 of 61

8.3 MEASUREMENT RESULT

LINE CONDUCTED EMISSION - L1



Site: Conduction Phase: L1 Temperature: 26
Limit: FCC Class B Conduction(QP) Power: AC 120V/60Hz Humidity: 60 %

EUT: GSM Mobile Phone


M/N: SMD-1770B

Mode: Call Note:

No.	Freq.		ding_L (dBuV)		Correct Factor	Me	asuren (dBuV)			nit uV)	Mai (d	rgin IB)	P/F	Comment
	(MHz)	Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.2220	37.34		20.15	10.24	47.58		30.39	62.74	52.74	-15.16	-22.35	Р	
2	0.5060	37.19		20.00	10.39	47.58		30.39	56.00	46.00	-8.42	-15.61	Р	
3	0.9340	29.38		16.97	10.40	39.78		27.37	56.00	46.00	-16.22	-18.63	Р	
4	1.9900	29.15		15.90	10.22	39.37		26.12	56.00	46.00	-16.63	-19.88	Р	
5	5.2619	32.16		14.36	10.25	42.41		24.61	60.00	50.00	-17.59	-25.39	Р	
6	20.9740	37.06		19.75	10.13	47.19		29.88	60.00	50.00	-12.81	-20.12	Р	

Page 30 of 61

LINE CONDUCTED EMISSION - N



Site: Conduction Phase: N Temperature: 26
Limit: FCC Class B Conduction(QP) Power: AC 120V/60Hz Humidity: 60 %

EUT: GSM Mobile Phone M/N: SMD-1770B

Mode: Call Note:

No.	Freq.	Rea	ding_L (dBuV)		Correct Factor	1	asuren (dBuV)		Lin (dB	nit uV)	Mai (d	rgin IB)	P/F	Comment
	(MHz)	Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.2460	40.75		22.69	10.27	51.02		32.96	61.89	51.89	-10.87	-18.93	Р	
2	0.5899	36.34		22.71	10.32	46.66		33.03	56.00	46.00	-9.34	-12.97	Р	
3	1.3740	33.22		17.11	10.38	43.60		27.49	56.00	46.00	-12.40	-18.51	Р	
4	2.4420	32.18		17.05	10.41	42.59		27.46	56.00	46.00	-13.41	-18.54	Р	
5	5.1060	34.78		19.05	10.24	45.02		29.29	60.00	50.00	-14.98	-20.71	Р	
6	22.3580	43.65		27.04	10.12	53.77		37.16	60.00	50.00	-6.23	-12.84	Р	

Note: The GSM850 mode is the worst condition.

Page 31 of 61

9. FREQUENCY STABILITY

9.1 MEASUREMENT METHOD

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

- 1 , Measure the carrier frequency at room temperature.
- 2 , Subject the EUT to overnight soak at -10 $^{\circ}$ C.
- 3 , With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 for PCS 1900 , channel 190 for GSM850 measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 4 , Repeat the above measurements at 10° C increments from - 10° C to + 50° C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 5 , Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
- Subject the EUT to overnight soak at +50℃.
- 7 , With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 8 , Repeat the above measurements at 10° C increments from +50°C to -10°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 9 , At all temperature levels hold the temperature to +/- 0.5° C during the measurement procedure.

9.2 PROVISIONS APPLICABLE

9.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.4VDC and 4.2VDC, with a nominal voltage of 3.7VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

Page 32 of 61

9.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

9.3 MEASUREMENT RESULT (WORST TEST)

Frequency Error Against Voltage for GSM 850 MHz(Test Channel 190)									
Voltage(V)	Frequency error(Hz)	Frequency error(ppm)							
3.4	32	0.038							
3.7	24	0.029							
4.2	26	0.031							

Frequency Error A	gainst Temperature for GSM	850 MHz(Test Channel 190)
temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	42	0.050
0	39	0.047
10	38	0.045
20	32	0.038
30	29	0.035
40	22	0.026
50	36	0.043

Note: The EUT doesn't work below -10℃

Page 33 of 61

Frequency Error Against Voltage for PCS 1900 MHz(Test Channel 661)		
Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.4	28	0.015
3.7	35	0.019
4.2	32	0.017

Frequency Error Against Temperature for PCS 1900 MHz(Test Channel 661)		
temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	44	0.023
0	37	0.020
10	35	0.019
20	32	0.017
30	31	0.016
40	43	0.023
50	44	0.023

Note: The EUT doesn't work below -10°C

Page 34 of 61

10. OCCUPIED BANDWIDTH

10.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

10.2 PROVISIONS APPLICABLE

The occupied bandwidth (99%) shall not exceed 300 KHz.

10.3 MEASUREMENT RESULT

Occupied Bandwidth (99%) for GSM 850 MHz			
Mode	Frequency(MHz)	Occupied Bandwidth (99%)(kHz)	
Low Channel	824.2	246.22	
Middle Channel	836.6	243.80	
High Channel	848.8	239.78	

Occupied Bandwidth (99%) for PCS 1900 MHz			
Mode	Frequency(MHz)	Occupied Bandwidth (99%)(kHz)	
Low Channel	1850.2	242.28	
Middle Channel	1880.0	244.81	
High Channel	1909.8	242.49	

Page 35 of 61

11. EMISSION BANDWIDTH

11.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

11.2 PROVISIONS APPLICABLE

The emission bandwidth is defined as two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26dB below the transmitter power

11.3 MEASUREMENT RESULT

Emission Bandwidth (-26dBc) for GSM 850 MHz			
Mode	Frequency(MHz)	Emission Bandwidth (-26dBc)(kHz)	
Low Channel	824.2	314.85	
Middle Channel	836.6	306.87	
High Channel	848.8	308.18	

Emission Bandwidth (-26dBc) for PCS 1900 MHz			
Mode	Frequency(MHz)	Emission Bandwidth (-26dBc)(kHz)	
Low Channel	1850.2	312.26	
Middle Channel	1880.0	310.52	
High Channel	1909.8	309.46	

Page 36 of 61

12. BAND EDGE

12.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

12.2 PROVISIONS APPLICABLE

as Specified in FCC rules of 22.917(b) and 24.238(b)

12.3 MEASUREMENT RESULT

Please refers to Appendix III for compliance test plots for band edges.

Page 37 of 61


APPENDIX I

TEST PLOTS FOR CONDUCTED SPURIOUS EMISSION


Page 38 of 61

CONDUCTED EMISSION IN GSM BAND

Conducted Emission Transmitting Mode CH 128 30MHz - 1GHz




Conducted Emission Transmitting Mode CH 128 1GHz – 9GHz




Report No.: AGC00200130801FE02 Page 39 of 61


Conducted Emission Transmitting Mode CH 190 30MHz - 1GHz




Conducted Emission Transmitting Mode CH 190 1GHz – 9GHz



Conducted Emission Transmitting Mode CH 251 30MHz - 1GHz




Conducted Emission Transmitting Mode CH 251 1GHz – 9GHz




Page 41 of 61

Conducted Emission Idle Mode 30MHz - 1GHz




Conducted Emission Idle Mode 1GHz – 9GHz




Page 42 of 61

CONDUCTED EMISSION IN PCS BAND

Conducted Emission Transmitting Mode CH 512 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 512 1GHz – 20GHz




Page 43 of 61

Conducted Emission Transmitting Mode CH 661 30MHz - 1GHz




Conducted Emission Transmitting Mode CH 661 1GHz – 20GHz




Report No.: AGC00200130801FE02 Page 44 of 61

Conducted Emission Transmitting Mode CH 810 30MHz - 1GHz



Conducted Emission Transmitting Mode CH 810 1GHz – 20GHz




Page 45 of 61

APPENDIX II


TEST PLOTS FOR OCCUPIED BANDWIDTH (99%) EMISSION BANDWIDTH (-26dBC)

Page 46 of 61

Occupied Bandwidth (99%) GSM 850 BAND CH 128




Occupied Bandwidth (99%) GSM 850 BAND CH 190




Page 47 of 61

Occupied Bandwidth (99%) GSM 850 BAND CH 251




Occupied Bandwidth (99%) PCS 1900 BAND CH 512




Page 48 of 61

Occupied Bandwidth (99%) PCS 1900 BAND CH 661



Occupied Bandwidth (99%) PCS 1900 BAND CH 810




Page 49 of 61


APPENDIX III

TEST PLOTS FOR BAND EDGES


Low Band Edge GSM 850 BAND CH 128




High Band Edge GSM 850 BAND CH 251



Low Band Edge PCS 1900 BAND CH 512



High Band Edge PCS 1900 BAND CH 810



Page 52 of 61

APPENDIX IV

PHOTOGRAPHS OF TEST SETUP

Report No.: AGC00200130801FE02 Page 53 of 61

CONDUCTED EMISSION



RADIATED SPURIOUS EMISSION



Page 54 of 61

APPENDIX V

PHOTOGRAPHS OF EUT

TOTAL VIEW OF EUT





Report No.: AGC00200130801FE02 Page 56 of 61


TOP VIEW OF EUT



BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



BACK VIEW OF EUT



Page 58 of 61

LEFT VIEW OF EUT



RIGHT VIEW OF EUT



Report No.: AGC00200130801FE02 Page 59 of 61


OPEN VIEW OF EUT-1




OPEN VIEW OF EUT-2




OPEN VIEW OF EUT-3




INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



INTERNAL VIEW OF EUT-3



----END OF REPORT----