Maximum Permissible Exposure: GWS-5002 Family

19th July 2019

Author: Dr. Michael Davies



Contents

Introduction	3
RF Exposure Risk: FCC Operation	4
MIMO	
Calculated maximum power density MIMO:	5
MPE Margin Calculation MIMO	6
SISO	7
Calculated maximum power density SISO:	7
MPE Margin Calculation SISO CPE	8
Summary of RF Exposure Risk	9
Explanation:	9
MPE Methodology	10
References	10
Expert Installer	11
Signature Page	11

Introduction

Radio-frequency (RF) sources (3 kHz - 300 GHz), electric and magnetic fields, are predominantly thermal hazards. The exposure limits in this range are for acute (short-term) exposures since there is no scientific evidence of adverse biological effects from chronic or cumulative exposure to electric and magnetic fields emitted at these frequencies. Exposure limits for this spectral range are based on specific absorption rates SAR (W/kg) which are the used to calculate the maximum permissible exposure (MPE).

The frequencies used by these radios are 470MHz to 698MHz and therefore the RF exposure risk is evaluated using the SAR and MPE methodology.

In the test report provided by Nemko the maximum conducted power allowed to meet all other requirements of Part 15 H is 27.73dBm/24MHz.

Given the measurement uncertainties and to be conservative we will assume that the maximum in these calculations is 29dBm/24MHz. This ensures an extra margin of permissible exposure beyond the calculations that follow.

The GWS-5002 is capable of transmitting with two spatial streams (MIMO). The GWS-5002E model variant can only transmit with on spatial stream (SISO).

RF Exposure Risk: FCC Operation

Page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

S=power density

P=power input

G=Power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the centre of radiation of the antenna.

If the antenna is directional; the power density maximum is assumed to be at the centre of the beam maximum in zenith and at the centre of the beam maximum in azimuth i.e. directly in front of the antenna.

If the antenna is omni directional; then the power density maximum is assumed to be at the centre of the beam maximum in zenith, and rotationally uniform.

MIMO

Calculated maximum power density MIMO:

Maximum peak power at radio terminal 29dBm/24MHz

Cable/connector loss/filters 1dB

Maximum peak power at each antenna input 28dBm/24MHz

Maximum peak power at each antenna input 0.631W (631mW)

Antenna gain (worst case) 12dBi

Numeric antenna gain 15.8

Number of antennas¹ 2

Prediction distance 75cm

S (mW/cm²)=
$$\frac{631*15.8*2}{4*\pi*75*75}$$

Calculated MPE at predicted distance & predicted frequency=0.282 mW/cm²

The estimated power density at 75cm from the transmitting antenna is 0.282 mWcm² which is 88% of the limit (0.321mW/cm²). We assume the device is operating continuously, the actual operation would not typically be continuous and therefore these estimates are conservative.

¹ The radio uses STBC and according to KDB 662911 D01 Multiple Transmitter Output v02r01, Section F, Part 1) on page 5, STBC transmissions are considered to be completely uncorrelated and as such there is no antenna array gain. However, to be conservative in this MPE calculation we assume that both transmitters are additive.

MPE Margin Calculation MIMO

Power density at predicted frequency f/1500 mW/cm²

Prediction frequency 482MHz

Power density MPE at predicted frequency 0.321mW/cm²

Tx on time 1msecond

Tx period time 1msecond

Duty factor² 100%

Maximum peak power at radio terminal 26dBm

Cable/connector loss 1dB

Maximum peak power at antenna input 25dBm

Maximum peak power at antenna input 0.321W (321mW)

Number of antennas 2

Prediction distance 75cm

Maximum allowable numeric gain:

$$\frac{S*4*\pi*R*R}{P*2}$$

$$G = \frac{0.321*4*\pi*75*75}{321}$$

Maximum numeric antenna gain allowed 35.35

Maximum antenna gain allowed 15.5dBi

Compliance margin with 12dBi antenna 3.5dB

Compliance margin numerical 2.2 times

-

² Worst case scenario

SISO

Calculated maximum power density SISO:

Maximum peak power at radio terminal 29dBm / 24MHz

Cable/connector loss 1dB

Maximum peak power at antenna input 28dBm / 24Mhz

Maximum peak power at antenna input 0.631W (631mW)

Antenna gain

(worst case, non-congested areas) 12dBi

Numeric antenna gain 15.8

Number of antennas 1

Prediction distance 75cm

S (mW/cm²)=
$$\frac{631*15.8*1}{4*\pi*75*75}$$

Calculated MPE at predicted distance & predicted frequency=0.141 mW/cm²

Power density at predicted frequency f/1500 mW/cm²

Prediction frequency 482MHz

Power density MPE at predicted frequency 0.321mW/cm²

The estimated power density at 75cm from the transmitting antenna is 0.141mWcm² which is 44% of the limit (0.321mW/cm²). We assume the device is operating continuously, the actual operation would not typically be continuous and therefore these estimates are conservative.

MPE Margin Calculation SISO CPE

Allowed power density at predicted frequency f/1500 mW/cm²

Prediction frequency 482MHz

Power density MPE at predicted frequency (S) 0.321mW/cm²

Tx on time 1msecond

Tx period time 1msecond

Duty factor³ 100%

Maximum peak power allowed at antenna input 0.321W (321mW)

Number of antennas 1

Prediction distance 75cm

Maximum allowable numeric gain:

$$G = \frac{S * 4 * \pi * R * R}{P}$$

$$G = \frac{0.321 * 4 * \pi * 75 * 75}{321}$$

Maximum numeric antenna gain allowed 70.77

Maximum antenna gain allowed 18.5dBi

Compliance margin with 12dBi antenna 6.6dB

Compliance margin numerical 4.6 times

_

³ Worst case scenario

Summary of RF Exposure Risk

Mode	Max Antenna Gain	Power per RF Port	Minimum distance to avoid exposure	Compliance margin numerical
MIMO	12dBi	29dBm	75cm	2.2 times
SISO	12dBi	29dBm	75cm	4.6 times

These are conservative estimates, and the actual exposure risk will be less.

Typically, these antennas are mounted on a roof which reduce exposure significantly.

In particular, the MIMO transmission scenario will occur on towers as high as 100m.

Explanation:

If a person was directly in front of the radiating antenna at a distance of 75cm then the radiation received would be 17.5% (1/4.6) of the maximum permissible exposure. This also assumes that the duty cycle is 100%, which it is not. The calculation also assumes direct line of sight, any obstructions such as a roof or wall will significantly reduce the signal strength further. Also, the MPE assumes that the person will be in place continuously for 30minutes in order to receive the MPE.

MPE Methodology

In order to calculate the maximum permissible exposure (MPE) we must know the Specific Absorption Rate (SAR) for the RF being used.

The maximum MPE (in mW/cm²) is defined as f/1500 where f is the frequency of the RF.

Prediction of MPE at a given distance

1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Frequency range (MHz)	Electric field strength (V/m rms)	Magnetic field strength (A/m rms)	Power density (mW/cm²)	Averaging time (minutes)
	(A) Limits for Oc	cupational/Controlled Exp	osures	
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f2)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
	(B) Limits for Gener	al Population/Uncontrolled	Exposure	
0.3 -1.34	614	1.63	*(100)	30
1.34 -30	824/:	2.19/1	*(180/f²)	30
30-300	27.5	0.073	0.2	30
300-1500			:/1500	30
1500-100,000			1	30

2. Test Procedure

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

References

- https://en.wikipedia.org/wiki/Specific absorption rate
- https://www.fcc.gov/general/oet-bulletins-line#65
- https://apps.fcc.gov/kdb/GetAttachment.html?id=f8lQgJxTTL5y0oRi0cpAuA%3D%3D&desc=447 498%20D01%20General%20RF%20Exposure%20Guidance%20v06&tracking_number=20676 specifically Section 4.

Expert Installer

For FCC an "expert installation" is required to ensure both electrical shock risk and RF exposure risk are minimal. In addition, the expert installer is responsible for regulatory compliance and to ensure that the radios do not cause interference.

Signature Page

Signed for and on behalf of 6Harmonics Inc

Place: Ottawa, Ontario, Canada

Date of issue: 19 July 2019

Name: Michael Davies

Function: Vice President, Business Development

Signature: