FCC ID: 2AATM-HXHP420

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] * [$\sqrt{f(GHz)}$] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation:

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

BT4.0 DSS:

Transmit Frequency	Mode	Max Conducted Power	Result	1-g SAR
(GHz)		(dBm)	calculation	1-y SAIX
2.402	GFSK	3.67	0.7216	3.0
2.441	GFSK	4.81	0.9458	3.0
2.480	GFSK	5.33	1.0746	3.0
2.402	π/4-DQPSK	0.79	0.3718	3.0
2.441	π/4-DQPSK	2.28	0.5282	3.0
2.480	π/4-DQPSK	2.76	0.5946	3.0
2.402	8-DPSK	1.01	0.3911	3.0
2.441	8-DPSK	2.75	0.5886	3.0
2.480	8-DPSK	3.23	0.6626	3.0

BT4.0 DTS:

Transmit Frequency (GHz)	Mode	Max Conducted Power (dBm)	Result calculation	1-g SAR
2.402	GFSK	6.12	1.2686	3.0
2.440	GFSK	6.14	1.2845	3.0
2.480	GFSK	6.3	1.3436	3.0

Conclusion:

For the max result : $1.34 \le 3.0$ for 1-g SAR extremity SAR, No SAR is required.

Sincerely,

Signature

Company Name: SHENZHEN EMTEK CO., LTD.

Address: Bldg 69, Majialong Industry Zone, NanshanDistrict, Shenzhen, China

david Lee/ Manager