

FCC 47 CFR PART 15 SUBPART C

CERTIFICATION TEST REPORT

For

Bluetooth Headphone

MODEL No.: HX-HP420A

FCC ID: 2AATM-HXHP420A

Trademark: Jam

REPORT NO.: ES141231435E1

ISSUE DATE: March 21, 2015

Prepared for

SHENZHEN YIYUN ELECTRONICS COMPANY LIMITED
Floor 6, Building C, Junxing industrial zone B, Haoye Road, Heping,
Fuyong, Baoan, Shenzheng, 518103, China

Prepared by

SHENZHEN EMTEK CO., LTD.

Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen,
Guangdong, China
TEL: 86-755-26954280
FAX: 86-755-26954282

Table of Contents

1	TEST RESULT CERTIFICATION	3
2	EUT TECHNICAL DESCRIPTION.....	4
3	SUMMARY OF TEST RESULT	5
4	TEST METHODOLOGY	6
4.1	GENERAL DESCRIPTION OF APPLIED STANDARDS	6
4.2	MEASUREMENT EQUIPMENT USED.....	6
4.3	DESCRIPTION OF TEST MODES	7
5	FACILITIES AND ACCREDITATIONS	8
5.1	FACILITIES	8
5.2	LABORATORY ACCREDITATIONS AND LISTINGS.....	8
6	TEST SYSTEM UNCERTAINTY	9
7	SETUP OF EQUIPMENT UNDER TEST	10
7.1	RADIO FREQUENCY TEST SETUP 1.....	10
7.2	RADIO FREQUENCY TEST SETUP 2.....	10
7.3	CONDUCTED EMISSION TEST SETUP	11
7.4	SUPPORT EQUIPMENT	11
8	FREQUENCY HOPPING SYSTEM REQUIREMENTS	12
8.1	STANDARD APPLICABLE.....	12
8.2	EUT PSEUDORANDOM FREQUENCY HOPPING SEQUENCE	12
8.3	EQUAL HOPPING FREQUENCY USE	13
8.4	FREQUENCY HOPPING SYSTEM	13
9	TEST REQUIREMENTS	14
9.1	20DB BANDWIDTH	14
9.2	CARRIER FREQUENCY SEPARATION	20
9.3	NUMBER OF HOPPING FREQUENCIES.....	26
9.4	AVERAGE TIME OF OCCUPANCY (DWELL TIME)	28
9.5	MAXIMUM PEAK CONDUCTED OUTPUT POWER	31
9.6	CONDUCTED SPURIOUS EMISSION	37
9.7	RADIATED SPURIOUS EMISSION	44
9.8	CONDUCTED EMISSION TEST	58
9.9	ANTENNA APPLICATION.....	61

1 TEST RESULT CERTIFICATION

Applicant:	SHENZHEN YIYUN ELECTRONICS COMPANY LIMITED Floor 6, Building C, Junxing industrial zone B, Haoye Road, Heping, Fuyong, Baoan, Shenzhen, 518103, China
Manufacturer:	SHENZHEN YIYUN ELECTRONICS COMPANY LIMITED Floor 6, Building C, Junxing industrial zone B, Haoye Road, Heping, Fuyong, Baoan, Shenzhen, 518103, China
Product Description:	Bluetooth Headphone
Model Number:	HX-HP420A
File Number:	ES141231435E1
Date of Test:	March 10, 2015 to March 21, 2015

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C	PASS

The above equipment was tested by SHENZHEN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2009) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247

The test results of this report relate only to the tested sample identified in this report

Date of Test :

March 10, 2015 to March 21, 2015



Test by :

KingKong /Tester



Prepared by :

Yaping Shen/Editor



Approve & Authorized Signer :

Lisa Wang/Manager

2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
Data Rate	DSS: 1Mbps for BT v3.0 BR GFSK modulation 2Mbps for BT v3.0 EDR pi/4-DQPSK modulation 3Mbps for BT v3.0 EDR 8DPSK modulation DTS: 1Mbps for BT v4.0 GFSK modulation
Modulation:	DSS: GFSK modulation for BT v3.0 BR(1Mbps) pi/4-DQPSK modulation for BT v3.0 EDR(2Mbps) 8DPSK modulation for BT v3.0 EDR (3Mbps) DTS: GFSK modulation for BT v4.0 (1Mbps)
Operating Frequency Range(s):	2402-2480MHz
Number of Channels:	79 channels for BT v3.0 BR; 79 channels for BT v3.0 EDR; 40 channels for BT v4.0
Transmit Power Max:	-0.572 dBm for BT v3.0; 0.698 dBm for BT v4.0;
Antenna Type :	PCB Antenna
Antenna Gain:	1.95 dBi;
Power supply:	<input checked="" type="checkbox"/> DC supply: DC 3.7V by battery or DC 5V by external power <input type="checkbox"/> Adapter supply:
Temperature Range	-10°C ~ +55°C

Note: for more details, please refer to the User's manual of the EUT.

3 SUMMARY OF TEST RESULT

FCC Part Clause	Test Parameter	Verdict	Remark
15.247(a)(1)	20 dB Bandwidth	PASS	
15.247(a)(1)	Carrier Frequency Separation	PASS	
15.247(a)(1)	Number of Hopping Frequencies	PASS	
15.247(a)(1)	Average Time of Occupancy (Dwell Time)	PASS	
15.247(b)(1)	Maximum Peak Conducted Output Power	PASS	
15.247(c)	Conducted Spurious Emissions	PASS	
15.247(d) 15.209	Radiated Spurious Emissions	PASS	
15.207	Conducted Emission	PASS	
15.247(b)	Antenna Application	PASS	
NOTE1: N/A (Not Applicable)			

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: 2AATM-HXHP420A filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

4 TEST METHODOLOGY

4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:
 FCC 47 CFR Part 2, Subpart J
 FCC 47 CFR Part 15, Subpart C
 DA 00-705

4.2 MEASUREMENT EQUIPMENT USED

4.2.1 Conducted Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/17/2014
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	05/17/2014
50Ω Coaxial Switch	Anritsu	MP59B	M20531	N/A
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	05/17/2014
Voltage Probe	Rohde & Schwarz	TK9416	N/A	05/17/2014
I.S.N	Rohde & Schwarz	ENY22	1109.9508.02	05/17/2014

4.2.2 Radiated Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	05/17/2014
Pre-Amplifier	HP	8447D	2944A07999	05/17/2014
Bilog Antenna	Schwarzbeck	VULB9163	142	05/17/2014
Loop Antenna	ARA	PLA-1030/B	1029	05/17/2014
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	05/17/2014
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/17/2014
Cable	Schwarzbeck	AK9513	ACRX1	05/17/2014
Cable	Rosenberger	N/A	FP2RX2	05/17/2014
Cable	Schwarzbeck	AK9513	CRPX1	05/17/2014
Cable	Schwarzbeck	AK9513	CRRX2	05/17/2014

4.2.3 Radio Frequency Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.
Spectrum Analyzer	Agilent	E4407B	88156318	05/17/2014
Power meter	Anritsu	ML2495A	0824006	05/17/2014
Power sensor	Anritsu	MA2411B	0738172	05/17/2014
Signal Analyzer	Agilent	N9010A	My53470879	05/17/2014

Remark: Each piece of equipment is scheduled for calibration once a year.

4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for Bluetooth v3.0 BR GFSK modulation; 2Mbps for Bluetooth v3.0 EDR pi/4-DQPSK modulation; 3Mbps for Bluetooth v3.0 EDR 8DPSK modulation) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for Bluetooth v3.0:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441
1	2403	40	2442	76	2478
2	2404	41	2443	77	2479
...	78	2480

Note: $fc = 2402\text{MHz} + (k-1) \times 1\text{MHz}$ k=1 to 79

Test Frequency and channel for Bluetooth v3.0:

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441	78	2480

5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at
Bldg 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China
The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR
Publication 22.

5.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab. : Accredited by CNAS, 2013.10.29
The certificate is valid until 2016.10.28
The Laboratory has been assessed and proved to be in compliance
with CNAS-CL01: 2006(identical to ISO/IEC17025: 2005)
The Certificate Registration Number is L2291

: Accredited by TUV Rheinland Shenzhen, 2010.5.25
The Laboratory has been assessed according to the requirements
ISO/IEC 17025.

: Accredited by FCC, July 24, 2013
The Certificate Registration Number is 406365.

: Accredited by FCC, April 17, 2013
The Certificate Registration Number is 709623.

: Accredited by Industry Canada, November 29, 2012
The Certificate Registration Number is 4480A-2

6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:


Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0 \text{dB}$
Conducted Emissions Test	$\pm 2.0 \text{dB}$
Radiated Emission Test	$\pm 2.0 \text{dB}$
Occupied Bandwidth Test	$\pm 1.0 \text{dB}$
Band Edge Test	$\pm 3 \text{dB}$
All emission, radiated	$\pm 3 \text{dB}$
Antenna Port Emission	$\pm 3 \text{dB}$
Temperature	$\pm 0.5^\circ\text{C}$
Humidity	$\pm 3\%$

Measurement Uncertainty for a level of Confidence of 95%

7 SETUP OF EQUIPMENT UNDER TEST

7.1 RADIO FREQUENCY TEST SETUP 1

The Bluetooth v3.0 component's antenna port(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.4. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.4-2009 and CAN/CSA-CEI/IEC CISPR 22.


Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.


Above 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




7.3 CONDUCTED EMISSION TEST SETUP

The mains cable of the EUT (Game fitness board) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.4-2009 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



7.4 SUPPORT EQUIPMENT

Item	Equipment	Mfr/Brand	Model/Type No.	Note
1.	iPhone	Apple	A1526	N/A

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

8 FREQUENCY HOPPING SYSTEM REQUIREMENTS

8.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.


8.2 EUT Pseudorandom Frequency Hopping Sequence

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The normal hop is 1 600 hops/s.


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage, and the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones. Number of shift register stages: 9

Length of pseudo-random sequence: $2^9 - 1 = 524$ bits

Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence



Each frequency used equally on the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

8.3 Equal Hopping Frequency Use

All Bluetooth units participating in the piconet are time and hop-synchronized to the channel.

Example of a 79 hopping sequence in data mode:

35, 27, 6, 44, 14, 61, 74, 32, 1, 11, 23, 2, 55, 65, 29, 3, 9, 52, 78, 58, 40, 25, 0, 7, 18, 26, 76, 60, 47, 50, 2, 5, 16, 37, 70, 63, 66, 54, 20, 13, 4, 8, 15, 21, 26, 10, 73, 77, 67, 69, 43, 24, 57, 39, 46, 72, 48, 33, 17, 31, 75, 19,

41, 62, 68, 28, 51, 66, 30, 56, 34, 59, 71, 22, 49, 64, 38, 45, 36, 42, 53

Each Frequency used equally on the average by each transmitter

8.4 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH- enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

9 TEST REQUIREMENTS

9.1 20DB BANDWIDTH

9.1.1 Applicable Standard

According to FCC Part 15.247(a)(1) and DA 00-705

9.1.2 Conformance Limit

No limit requirement.

9.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.1.4 Test Procedure

The EUT was operating in Bluetooth v3.0 mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 30 kHz.

Set the video bandwidth (VBW) =100 kHz.

Set Span= approximately 2 to 3 times the 20 dB bandwidth

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the markerdelta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

Measure and record the results in the test report.



Test Results


Temperature:	24°C	Test Date:	March 18, 2015
Humidity:	53 %	Test By:	KK

Modulation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (kHz)	Limit (kHz)	Verdict
GFSK	00	2402	867.925	N/A	PASS
	39	2441	873.056	N/A	PASS
	78	2480	867.715	N/A	PASS
pi/4-DQPSK	00	2402	1214	N/A	PASS
	39	2441	1213	N/A	PASS
	78	2480	1223	N/A	PASS
8DPSK	00	2402	1214	N/A	PASS
	39	2441	1233	N/A	PASS
	78	2480	1217	N/A	PASS
Note: N/A (Not Applicable)					

Test Model	20dB Bandwidth							
	Bluetooth v3.0							
	Channel 0: 2402MHz							
<p>Agilent</p> <p>Ch Freq 2.402 GHz Trig Free Occupied Bandwidth</p> <p>Center 2.402000000 GHz</p> <p>Ref 10 dBm Atten 20 dB #Peak Log 10 dB/ Offst 1 dB Center 2.402 GHz Span 3 MHz #Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</p> <table border="1"> <tr> <td>Occupied Bandwidth</td> <td>Occ BW % Pwr 99.00 %</td> </tr> <tr> <td>836.6698 kHz</td> <td>x dB -20.00 dB</td> </tr> <tr> <td>Transmit Freq Error</td> <td>-689.742 Hz</td> </tr> <tr> <td>x dB Bandwidth</td> <td>867.925 kHz</td> </tr> </table> <p>Freq/Channel</p> <p>Center Freq 2.402000000 GHz</p> <p>Start Freq 2.400500000 GHz</p> <p>Stop Freq 2.403500000 GHz</p> <p>CF Step 300.000000 kHz Auto Man</p> <p>Freq Offset 0.0000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>	Occupied Bandwidth	Occ BW % Pwr 99.00 %	836.6698 kHz	x dB -20.00 dB	Transmit Freq Error	-689.742 Hz	x dB Bandwidth	867.925 kHz
Occupied Bandwidth	Occ BW % Pwr 99.00 %							
836.6698 kHz	x dB -20.00 dB							
Transmit Freq Error	-689.742 Hz							
x dB Bandwidth	867.925 kHz							
<p>20dB Bandwidth</p> <p>Bluetooth v3.0</p> <p>Channel 39: 2441MHz</p> <p>GFSK Modulation</p>								
<p>Agilent</p> <p>Ch Freq 2.441 GHz Trig Free Occupied Bandwidth</p> <p>Center 2.441000000 GHz</p> <p>Ref 10 dBm Atten 20 dB #Peak Log 10 dB/ Offst 1 dB Center 2.441 GHz Span 3 MHz #Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</p> <table border="1"> <tr> <td>Occupied Bandwidth</td> <td>Occ BW % Pwr 99.00 %</td> </tr> <tr> <td>831.6650 kHz</td> <td>x dB -20.00 dB</td> </tr> <tr> <td>Transmit Freq Error</td> <td>-4.590 kHz</td> </tr> <tr> <td>x dB Bandwidth</td> <td>873.056 kHz</td> </tr> </table> <p>Freq/Channel</p> <p>Center Freq 2.441000000 GHz</p> <p>Start Freq 2.439500000 GHz</p> <p>Stop Freq 2.442500000 GHz</p> <p>CF Step 300.000000 kHz Auto Man</p> <p>Freq Offset 0.0000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>	Occupied Bandwidth	Occ BW % Pwr 99.00 %	831.6650 kHz	x dB -20.00 dB	Transmit Freq Error	-4.590 kHz	x dB Bandwidth	873.056 kHz
Occupied Bandwidth	Occ BW % Pwr 99.00 %							
831.6650 kHz	x dB -20.00 dB							
Transmit Freq Error	-4.590 kHz							
x dB Bandwidth	873.056 kHz							

Test Model	20dB Bandwidth	
	Bluetooth v3.0	
	Channel 78: 2480MHz	GFSK Modulation
 Agilent	<p>Ch Freq 2.48 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Center 2.480000000 GHz</p> <p>Ref 10 dBm Atten 20 dB</p> <p>#Peak Log 10 dB/Offst 1 dB</p>  <p>Center 2.48 GHz #Res BW 30 kHz #VBW 100 kHz Span 3 MHz Sweep 5 ms (401 pts)</p> <p>Occupied Bandwidth 829.4929 kHz</p> <p>Transmit Freq Error -7.284 kHz x dB Bandwidth 867.715 kHz</p>	<p>Freq/Channel</p> <p>Center Freq 2.480000000 GHz</p> <p>Start Freq 2.478500000 GHz</p> <p>Stop Freq 2.481500000 GHz</p> <p>CF Step 300.0000000 kHz Auto Man</p> <p>Freq Offset 0.000000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>
Test Model	20dB Bandwidth	
	Bluetooth v3.0	
	Channel 0: 2402MHz	pi/4-DQPSK Modulation
 Agilent	<p>Ch Freq 2.402 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Center 2.402000000 GHz</p> <p>Ref 10 dBm Atten 20 dB</p> <p>#Peak Log 10 dB/Offst 1 dB</p>  <p>Center 2.402 GHz #Res BW 30 kHz #VBW 100 kHz Span 3 MHz Sweep 5 ms (401 pts)</p> <p>Occupied Bandwidth 1.1603 MHz</p> <p>Transmit Freq Error -4.850 kHz x dB Bandwidth 1.214 MHz</p>	<p>Freq/Channel</p> <p>Center Freq 2.402000000 GHz</p> <p>Start Freq 2.400500000 GHz</p> <p>Stop Freq 2.403500000 GHz</p> <p>CF Step 300.0000000 kHz Auto Man</p> <p>Freq Offset 0.000000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>

Test Model	20dB Bandwidth
	Bluetooth v3.0
	Channel 39: 2441MHz
pi/4-DQPSK Modulation	
 <p>Agilent</p> <p>Ch Freq 2.441 GHz Occupied Bandwidth Center 2.441000000 GHz</p> <p>Ref 10 dBm Atten 20 dB</p> <p>#Peak Log 10 dB/Offst 1 dB</p> <p>Center 2.441 GHz #Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</p> <p>Span 3 MHz</p> <p>Occupied Bandwidth 1.1567 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -20.00 dB</p> <p>Transmit Freq Error -14.025 kHz x dB Bandwidth 1.213 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.44100000 GHz</p> <p>Start Freq 2.43950000 GHz</p> <p>Stop Freq 2.44250000 GHz</p> <p>CF Step 300.000000 kHz Auto</p> <p>Freq Offset 0.0000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>	
 <p>Agilent</p> <p>Ch Freq 2.48 GHz Occupied Bandwidth Center 2.480000000 GHz</p> <p>Ref 10 dBm Atten 20 dB</p> <p>#Peak Log 10 dB/Offst 1 dB</p> <p>Center 2.48 GHz #Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</p> <p>Span 3 MHz</p> <p>Occupied Bandwidth 1.1622 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -20.00 dB</p> <p>Transmit Freq Error -14.396 kHz x dB Bandwidth 1.223 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.48000000 GHz</p> <p>Start Freq 2.47850000 GHz</p> <p>Stop Freq 2.48150000 GHz</p> <p>CF Step 300.000000 kHz Auto</p> <p>Freq Offset 0.0000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>	





9.2 CARRIER FREQUENCY SEPARATION

9.2.1 Applicable Standard

According to FCC Part 15.247(a)(1) and DA 00-705

9.2.2 Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

In case of an output power less than 125mW, the frequency hopping system may have channels separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

9.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.2.4 Test Procedure

- According to FCC Part15.247(a)(1)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Set the RBW =100kHz. Set VBW =300kHz.

Set the span = wide enough to capture the peaks of two adjacent channels

Set Sweep time = auto couple.

Set Detector = peak. Set Trace mode = max hold.


Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.


Test Results



Temperature:	24°C	Test Date:	March 18, 2015
Humidity:	53 %	Test By:	KK



Modulation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (kHz)	Limit (kHz)	Verdict
GFSK	0	2402	1000	>578.617	PASS
	39	2441	1000	>582.037	PASS
	78	2480	1000	>578.477	PASS
pi/4-DQPSK	0	2402	1000	>809.333	PASS
	39	2441	1000	>808.667	PASS
	78	2480	1000	>815.333	PASS
8DPSK	0	2402	1000	>809.333	PASS
	39	2441	1000	>822.000	PASS
	78	2480	1000	>811.333	PASS


Note: Limit = 20dB bandwidth*2/3, if it is greater than 25kHz and the output power is less than 125mW (21dBm).





Test Model	Carrier Frequency Separation		
	Bluetooth v3.0		
	Channel 39: 2441MHz		pi/4-DQPSK Modulation
			
Test Model	Carrier Frequency Separation		
	Bluetooth v3.0		
	Channel 78: 2480MHz		pi/4-DQPSK Modulation
			

Test Model	Carrier Frequency Separation													
	Bluetooth v3.0													
	Channel 0: 2402MHz		8DPSK Modulation											
														
<table border="1"> <tr> <td colspan="3">Carrier Frequency Separation</td></tr> <tr> <td colspan="3">Bluetooth v3.0</td></tr> <tr> <td colspan="2">Channel 39: 2441MHz</td><td>8DPSK Modulation</td></tr> </table>				Carrier Frequency Separation			Bluetooth v3.0			Channel 39: 2441MHz		8DPSK Modulation		
Carrier Frequency Separation														
Bluetooth v3.0														
Channel 39: 2441MHz		8DPSK Modulation												
														



9.3 NUMBER OF HOPPING FREQUENCIES

9.3.1 Applicable Standard

According to FCC Part 15.247(a)(1) (iii)and DA 00-705

9.3.2 Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall use at least 15 channels.

9.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.3.4 Test Procedure

■ According to FCC Part15.247(a)(1)(iii)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation (2390-2440MHz) and(2440-2490MHz)

RBW \geq 1% of the span

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies.

Test Results

Temperature:

24°C

Test Date:

March 18, 2015


Humidity:

53 %

Test By:

KK

Hopping Channel Frequency Range	Quantity of Hopping Channel	Quantity of Hopping Channel limit
2402-2480	79	>15



9.4 AVERAGE TIME OF OCCUPANCY (DWELL TIME)

9.4.1 Applicable Standard

According to FCC Part 15.247(a)(1)(iii) and DA 00-705

9.4.2 Conformance Limit

For frequency hopping systems operating in the 2400-2483.5MHz band, the average time of occupancy on any channel shall not be greater than 0.4s within a period of 0.4s multiplied by the number of hopping channels employed.

9.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.4.4 Test Procedure

- According to FCC Part15.247(a)(1)(iii)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW = 1 MHz

VBW \geq RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

If possible, use the marker-delta function to determine the dwell time. If this value

varies with different modes of operation (e.g., data rate, modulation format, etc.),


repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section.

9.4.5 Test Results

Temperature:	24°C	Test Date:	March 18, 2015
Humidity:	53 %	Test By:	KK

Modulation Mode	Channel Number	Packet type	Pluse width (ms)	Number per channel in 31.6s	dwell time (ms)	Limit (ms)	Verdict
GFSK	0	DH1	0.4125	320.10	132.0	<400	PASS
	0	DH3	1.697	160.00	271.5	<400	PASS
	0	DH5	2.925	106.67	312.0	<400	PASS
Note:							

Test Model	Average Time Of Occupancy (Dwell Time)		
	Bluetooth v3.0		
	CH 0: 2402MHz	GFSK	DH1
Test Model	Average Time Of Occupancy (Dwell Time)		
	Bluetooth v3.0		
	CH 0: 2402MHz	GFSK	DH3



9.5 MAXIMUM PEAK CONDUCTED OUTPUT POWER

9.5.1 Applicable Standard

According to FCC Part 15.247(b)(1) and DA 00-705

9.5.2 Conformance Limit

The max For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

9.5.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.5.4 Test Procedure

■ According to FCC Part15.247(b)(1)

As an alternative to a peak power measurement, compliance with the limit can be based on a measurement of the maximum conducted output power.

Use the following spectrum analyzer settings:

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel (about 10MHz)

Set RBW > the 20 dB bandwidth of the emission being measured (about 3MHz)

Set VBW \geq RBW

Set Sweep = auto

Set Detector function = peak

Set Trace = max hold

Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission to determine the peak amplitude level.


Test Results



Temperature:	24°C	Test Date:	March 18, 2015
Humidity:	53 %	Test By:	KK



Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm)	Limit (dBm)	Verdict
GFSK	0	2402	-0.572	30	PASS
	39	2441	-0.679	30	PASS
	78	2480	-1.539	30	PASS
pi/4-DQPSK	0	2402	-2.925	30	PASS
	39	2441	-2.559	30	PASS
	78	2480	-3.341	30	PASS
8DPSK	0	2402	-2.383	30	PASS
	39	2441	-2.033	30	PASS
	78	2480	-2.778	30	PASS


Note: N/A

Test Model	Maximum Peak Conducted Output Power		
	Bluetooth v3.0		
	Channel 0: 2402MHz	GFSK	
<p>Agilent</p> <p>Ref 10 dBm Atten 20 dB Mkr1 2.402300 GHz -0.572 dBm</p> <p>Peak Log 10 dB/Offst 1 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.402000000 GHz</p> <p>Center 2.402 GHz #Res BW 3 MHz *VBW 3 MHz Sweep 4 ms (401 pts)</p> <p>R:\SCREEN146.GIF file deleted</p> <p>Freq/Channel</p> <p>Center Freq 2.40200000 GHz</p> <p>Start Freq 2.39700000 GHz</p> <p>Stop Freq 2.40700000 GHz</p> <p>CF Step 1.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>			
Maximum Peak Conducted Output Power			
Bluetooth v3.0			
Channel 39: 2441MHz		GFSK	
<p>Agilent</p> <p>Ref 10 dBm Atten 20 dB Mkr1 2.440875 GHz -0.679 dBm</p> <p>Peak Log 10 dB/Offst 1 dB</p> <p>M1 S2 S3 FC AA</p> <p>Marker 2.440875000 GHz -0.679 dBm</p> <p>Center 2.441 GHz #Res BW 3 MHz *VBW 3 MHz Sweep 4 ms (401 pts)</p> <p>Span 10 MHz</p> <p>Peak Search</p> <p>Meas Tools</p> <p>Next Peak</p> <p>Next Pk Right</p> <p>Next Pk Left</p> <p>Min Search</p> <p>Pk-Pk Search</p> <p>More 1 of 2</p>			



Test Model	Maximum Peak Conducted Output Power		
	Bluetooth v3.0		
	Channel 39: 2441MHz	pi/4-DQPSK	
 <div style="display: flex; justify-content: space-between;"> <div style="flex: 1;"> <p>Marker 2.441250000 GHz -2.559 dBm</p> <p>Center 2.441 GHz Span 10 MHz #Res BW 3 MHz *VBW 3 MHz Sweep 4 ms (401 pts)</p> </div> <div style="flex: 1; border-left: 1px solid black; padding-left: 10px;"> <p>Peak Search</p> <p>Meas Tools</p> <p>Next Peak</p> <p>Next Pk Right</p> <p>Next Pk Left</p> <p>Min Search</p> <p>Pk-Pk Search</p> <p>More 1 of 2</p> </div> </div>			
<p>Test Model</p> <p>Maximum Peak Conducted Output Power</p> <p>Bluetooth v3.0</p> <p>Channel 78: 2480MHz</p> <p>pi/4-DQPSK</p>  <div style="display: flex; justify-content: space-between;"> <div style="flex: 1;"> <p>Marker 2.480300000 GHz -3.341 dBm</p> <p>Center 2.48 GHz Span 10 MHz #Res BW 3 MHz *VBW 3 MHz Sweep 4 ms (401 pts)</p> </div> <div style="flex: 1; border-left: 1px solid black; padding-left: 10px;"> <p>Peak Search</p> <p>Meas Tools</p> <p>Next Peak</p> <p>Next Pk Right</p> <p>Next Pk Left</p> <p>Min Search</p> <p>Pk-Pk Search</p> <p>More 1 of 2</p> </div> </div>			

Test Model	Maximum Peak Conducted Output Power		
	Bluetooth v3.0		
	Channel 0: 2402MHz	8DPSK	
 <div style="display: flex; justify-content: space-between;"> <div style="flex: 1;"> <p>Marker 2.40210000 GHz -2.383 dBm</p> <p>Center 2.402 GHz #Res BW 3 MHz</p> <p>Atten 20 dB Span 10 MHz</p> <p>Ref 10 dBm Log 10 dB/ Offst 1 dB</p> <p>M1 S2 S3 FC AA</p> </div> <div style="flex: 1;"> <p>Mkr1 2.402100 GHz -2.383 dBm</p> <p>Span 10 MHz Sweep 4 ms (401 pts)</p> <p>*VBW 3 MHz</p> </div> <div style="flex: 1;"> <ul style="list-style-type: none"> Peak Search Meas Tools Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2 </div> </div>			
Test Model	Maximum Peak Conducted Output Power	Bluetooth v3.0	
	Channel 39: 2441MHz	8DPSK	
 <div style="display: flex; justify-content: space-between;"> <div style="flex: 1;"> <p>Marker 2.44095000 GHz -2.033 dBm</p> <p>Center 2.441 GHz #Res BW 3 MHz</p> <p>Atten 20 dB Span 10 MHz</p> <p>Ref 10 dBm Log 10 dB/ Offst 1 dB</p> <p>M1 S2 S3 FC AA</p> </div> <div style="flex: 1;"> <p>Mkr1 2.440950 GHz -2.033 dBm</p> <p>Span 10 MHz Sweep 4 ms (401 pts)</p> <p>*VBW 3 MHz</p> </div> <div style="flex: 1;"> <ul style="list-style-type: none"> Peak Search Meas Tools Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2 </div> </div>			



9.6 CONDUCTED SUPRIOUS EMISSION

9.6.1 Applicable Standard

According to FCC Part 15.247(d) and DA 00-705

9.6.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted, provided the transmitter demonstrates compliance with the peak conducted power limits.

9.6.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.6.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DSS channel center frequency.

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel.

Set the RBW = 100 kHz. Set the VBW \geq 3 x RBW.

Set Detector = peak. Set Sweep time = auto couple.

Set Trace mode = max hold. Allow trace to fully stabilize.

Use the peak marker function to determine the maximum Maximum conducted level.

Note that the channel found to contain the maximum conducted level can be used to establish the reference level.

■ Band-edge Compliance of RF Conducted Emissions

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products which fall outside of the authorized band of operation

Set RBW \geq 1% of the span=100kHz Set VBW \geq RBW

Set Sweep = auto Set Detector function = peak Set Trace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission.

The marker-delta value now displayed must comply with the limit specified in this Section.

Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.

■ Conducted Spurious RF Conducted Emission

Use the following spectrum analyzer settings:


Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic.(30MHz to 25GHz). Set RBW = 100 kHz Set VBW \geq RBW

Set Sweep = auto Set Detector function = peak Set Trace = max hold


Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this Section.


9.6.5 Test Results



Bluetooth (GFSK, pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:




Test Model	Band-edge Conducted Emissions		
	Bluetooth v3.0		
	Channel 0: 2402MHz	GFSK	
Test Model	Maximum Conducted Level RBW=100kHz	Bluetooth v3.0	GFSK
	Channel 39: 2441MHz		
Test Model	Conducted Spurious RF Conducted Emission		
	Bluetooth v3.0		
	Channel 39: 2441MHz	GFSK	





Test Model	Maximum Conducted Level RBW=100kHz		
	Bluetooth v3.0		
	Hopping	GFSK	
			
Test Model	Conducted Spurious RF Conducted Emission	Bluetooth v3.0	GFSK
	Hopping		
			



9.7 RADIATED SPURIOUS EMISSION

9.7.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and DA 00-705

9.7.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (μ V/m)	Field Strength (dB μ V/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (μ V/m)	300
0.490-1.705	2400/F(KHz)	20 log (μ V/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

9.7.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

9.7.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz(1GHz to 25GHz), 100 kHz for $f < 1$ GHz(30MHz to 1GHz)

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.4-2009 respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data. Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

9.7.5 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

Temperature:	24 °C	Test Date:	March 18, 2015
Humidity:	53 %	Test By:	KK
Test mode:	TX Mode		

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/ \text{test distance})(\text{dB})$;

Limit line=Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission Above 1GHz (1GHz to 25GHz)

Bluetooth (GFSK, pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:

Temperature:	24 °C	Test Date:	March 18, 2015
Humidity:	53 %	Test By:	KK
Test mode:	GFSK	Frequency:	Channel 0: 2402MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
1391.00	V	51.15	40.20	74.00	54.00	-22.85	-13.80
1595.00	V	49.45	39.60	74.00	54.00	-24.55	-14.40
1901.00	V	48.37	30.20	74.00	54.00	-25.63	-23.80
1204.00	H	51.55	35.20	74.00	54.00	-22.45	-18.80
1595.00	H	51.34	33.90	74.00	54.00	-22.66	-20.10
2547.00	H	48.62	31.60	74.00	54.00	-25.38	-22.40

Temperature: 24°C Test Date: March 18, 2015
 Humidity: 53 % Test By: KK
 Test mode: GFSK Frequency: Channel 39: 2441MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
1595.00	V	47.87	35.00	74.00	54.00	-26.13	-19.00
1986.00	V	43.55	34.60	74.00	54.00	-30.45	-19.40
2513.00	V	44.31	34.90	74.00	54.00	-29.69	-19.10
1595.00	H	48.21	32.90	74.00	54.00	-25.79	-21.10
1986.00	H	43.54	31.00	74.00	54.00	-30.46	-23.00
2581.00	H	45.23	36.10	74.00	54.00	-28.77	-17.90

Temperature: 24°C Test Date: March 18, 2015
 Humidity: 53 % Test By: KK
 Test mode: GFSK Frequency: Channel 78: 2480MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
1051.00	V	46.35	35.60	74.00	54.00	-27.65	-18.40
1272.00	V	45.58	37.00	74.00	54.00	-28.42	-17.00
1986.00	V	46.04	36.90	74.00	54.00	-27.96	-17.10
1017.00	H	52.09	35.30	74.00	54.00	-21.91	-18.70
1238.00	H	51.65	36.90	74.00	54.00	-22.35	-17.10
1748.00	H	51.39	33.90	74.00	54.00	-22.61	-20.10

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

Bluetooth (GFSK, pi/4-DQPSK, 8DPSK, Hopping) mode have been tested, and the worst result(GFSK, Hopping) was report as below:

Temperature:	24°C	Test Date:	March 18, 2015
Humidity:	53 %	Test By:	KK
Test mode:	GFSK	Frequency:	Channel 0: 2402MHz

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)
2350.24	H	48.00	74	39.60	54
2350.00	V	46.42	74	40.20	54

Temperature:	24°C	Test Date:	March 18, 2015
Humidity:	53 %	Test By:	KK
Test mode:	GFSK	Frequency:	Channel 78: 2480MHz

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)
2483.847	H	51.63	74	41.00	54
2483.880	V	51.24	74	40.90	54


Temperature:	24°C	Test Date:	March 18, 2015
Humidity:	53 %	Test By:	KK
Test mode:	GFSK	Frequency:	Hopping


Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)
2379.290	H	48.47	74	38.15	54
2374.220	V	51.59	74	39.64	54
2488.000	H	48.58	74	37.19	54
2492.200	V	52.17	74	39.16	54


Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).


(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.










■ Spurious Emission below 1GHz (30MHz to 1GHz)

Bluetooth (GFSK, pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:



Site: 3m Chamber #1

Polarization: **Horizontal**

Temperature: 24

Limit: (RE)FCC PART 15 C

Power:

Humidity: 53 %


Mode: TX(2402)

Note:

No	Mk	Freq	Roading	Correct	Measure	Limit	Over	Antenna	Table	Degree	
			Level	Factor	ment						
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		30.0000	7.86	11.98	19.84	40.00	-20.16	QP			
2		43.9904	2.83	15.17	18.00	40.00	-22.00	QP			
3		103.0610	8.25	12.87	21.12	43.50	-22.38	QP			
4		375.0962	11.14	17.35	28.49	46.00	-17.51	QP			
5		768.3814	8.58	24.82	33.40	46.00	-12.60	QP			
6	*	898.9503	8.12	26.10	34.22	46.00	-11.78	QP			


*:Maximum data x:Over limit !:over margin

Operator: KK



*:Maximum data x:Over limit !:over margin


Operator: KK



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
			Level						Height	Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	
1		30.0000	7.89	11.98	19.87	40.00	-20.13	QP			
2		288.0450	8.95	14.92	23.87	46.00	-22.13	QP			
3		323.7981	18.07	14.60	32.67	46.00	-13.33	QP			
4		375.0962	10.90	17.35	28.25	46.00	-17.75	QP			
5		407.7404	9.47	18.86	28.33	46.00	-17.67	QP			
6	*	766.8270	9.39	24.75	34.14	46.00	-11.86	QP			


*:Maximum data x:Over limit !:over margin

Operator: KK




*:Maximum data x:Over limit !:over margin

Operator: KK



*:Maximum data x:Over limit !:over margin

Operator: KK



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
			Level	Factor	ment						
		MHz	dBuV	dE	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		30.0000	8.71	11.98	20.69	40.00	-19.31	QP			
2		43.9904	4.01	18.17	22.18	40.00	-17.82	QP			
3		103.0610	12.32	12.87	25.19	43.50	-18.31	QP			
4		508.7821	11.09	20.99	32.08	46.00	-13.92	QP			
5		813.4615	7.94	24.68	32.62	46.00	-13.38	QP			
6	*	847.6603	10.63	24.48	35.11	46.00	-10.89	QP			

*:Maximum data x:Over limit !:over margin

Operator: KK

9.8 CONDUCTED EMISSION TEST

9.8.1 Applicable Standard

According to FCC Part 15.207(a)

9.8.2 Conformance Limit

Conducted Emission Limit		
Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.


9.8.3 Test Configuration

Test according to clause 7.3 conducted emission test setup

9.8.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.
Maximum procedure was performed on the highest emissions to ensure EUT compliance.
Repeat above procedures until all frequency measured were complete.

9.8.5 Test Results



Site Conduction #1

Phase: **L1**

Temperature: 26

Limit: (CE)FCC PART 15 C

Power: AC 120V/60Hz


Humidity: 60 %

Mode: BT ON

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.2000	25.79	0.00	25.79	63.61	-37.82	QP	
2		0.2000	11.22	0.00	11.22	53.61	-42.39	AVG	
3		0.2330	26.66	0.00	26.66	62.34	-35.68	QP	
4		0.2330	13.50	0.00	13.50	52.34	-38.84	AVG	
5		0.2500	29.01	0.00	29.01	61.76	-32.75	QP	
6		0.2500	12.38	0.00	12.38	51.76	-39.38	AVG	
7		0.3200	29.10	0.00	29.10	59.71	-30.61	QP	
8		0.3200	13.68	0.00	13.68	49.71	-36.03	AVG	
9 *		0.3600	29.15	0.00	29.15	58.73	-29.58	QP	
10		0.3600	14.53	0.00	14.53	48.73	-34.20	AVG	
11		0.4100	25.62	0.00	25.62	57.65	-32.03	QP	
12		0.4100	9.06	0.00	9.06	47.65	-38.59	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: csl



Site Conduction #1

Phase: **N**

Temperature: 26

Limit: (CE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 60 %

Mode: BT ON

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1		0.2000	31.94	0.00	31.94	63.61	-31.67	QP	
2		0.2000	20.36	0.00	20.36	53.61	-33.25	AVG	
3		0.2200	31.88	0.00	31.88	62.82	-30.94	QP	
4		0.2200	20.72	0.00	20.72	52.02	-32.10	AVG	
5		0.2350	35.72	0.00	35.72	62.27	-26.55	QP	
6		0.2350	24.96	0.00	24.96	52.27	27.31	AVG	
7		0.3450	34.94	0.00	34.94	59.08	-24.14	QP	
8	*	0.3450	25.03	0.00	25.03	49.08	-24.05	AVG	
9		0.4400	26.35	0.00	26.35	57.06	-30.71	QP	
10		0.4400	16.05	0.00	16.05	47.06	-31.01	AVG	
11		0.5150	25.33	0.00	25.33	56.00	-30.67	QP	
12		0.5150	14.10	0.00	14.10	46.00	-31.90	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: csl

9.9 ANTENNA APPLICATION

9.9.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

The EUT has 1 antenna: a PCB antenna for BT, the gain is 1.95 dBi;

Note:Antenna use a permanently attached antenna which is not replaceable.
which in accordance to section 15.203, please refer to the internal photos.

9.9.2 Result

PASS.