

Page:

Report No.: SZEM141000589302

1 of 8

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com

# **RF Exposure Evaluation Report**

Application No.: SZEM1410005893CR

Applicant:Flyingvoice Technology Co., Ltd.Manufacturer:Flyingvoice Technology Co., Ltd.FactoryFlyingvoice Technology Co., Ltd.

**Product Name:** VolP Wireless Router

Model No.(EUT): G802P

**Add Model No.:** G802, G801P, G801A, G800P, G800A

FCC ID: 2AATVG802

**Standards:** 47 CFR Part 1.1307(2014)

47 CFR Part 1.1310(2014)

**Date of Receipt:** 2014-11-04

**Date of Test:** 2014-11-13 to 2015-01-04

**Date of Issue:** 2015-02-11

Test Result : PASS\*

#### Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

<sup>\*</sup> In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEM141000589302

Page: 2 of 8

# 2 Version

Revision Record					
Version	Chapter	Date	Modifier	Remark	
00		2015-02-11		Original	

Authorized for issue by:		
Tested By	Chris-3hong	2015-01-04
	(Chris Zhong) /Project Engineer	Date
Prepared By	Hedy Wen	2015-02-11
	(Hedy Wen) /Clerk	Date
Checked By	Emen-Li	2015-02-11
	(Emen Li) /Reviewer	Date

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms.e-document.htm">www.sgs.com/terms.e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM141000589302

Page: 3 of 8

### 3 Contents

		Page
1	1 COVER PAGE	1
2	2 VERSION	2
3	3 CONTENTS	3
4		
	4.1 CLIENT INFORMATION	4
	4.2 GENERAL DESCRIPTION OF EUT	4
	4.3 TEST LOCATION	5
	4.4 Test Facility	6
	4.5 DEVIATION FROM STANDARDS	6
	4.6 ABNORMALITIES FROM STANDARD CONDITIONS	
	4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
5	5 RF EXPOSURE EVALUATION	
	5.1 RF Exposure Compliance Requirement	7
	5.1.1 Limits	
	5.1.2 Test Procedure	7
	5.1.3 EUT RF EXPOSURE EVALUATION	8

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms and conditions.htm">www.sgs.com/terms and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms e-document.htm">www.sgs.com/terms e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM141000589302

Page: 4 of 8

# 4 General Information

#### 4.1 Client Information

Applicant:	Flyingvoice Technology Co., Ltd.	
Address of Applicant:	Room 202, Chuangxin Bldg A#. No.12 Hongda North Rd, BDA, Beijing, China	
Manufacturer:	Flyingvoice Technology Co., Ltd.	
Address of Manufacturer:	Room 202, Chuangxin Bldg A#. No.12 Hongda North Rd, BDA, Beijing, China	
Factory:	Flyingvoice Technology Co., Ltd.	
Address of Factory:	Room 202, Chuangxin Bldg A#. No.12 Hongda North Rd, BDA, Beijing, China	

# 4.2 General Description of EUT

Product Name:	VoIP Wireless Router		
Model No.:	G802P		
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz		
	IEEE 802.11n(HT40): 2422MHz to 2452MHz		
Bluetooth Version:	IEEE 802.11b/g, IEEE 802.11n(HT20): 11 Channels		
	IEEE 802.11n(HT40): 7 Channels		
Modulation Technique:	5MHz		
Modulation Type:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK)		
	IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK)		
	IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)		
Sample Type:	Fixed production		
Antenna Type:	Integral		
Antenna Gain:	5dBi		
Power Supply:	M/N: WHF-1200300T3		
	Input: AC 100-240V; 50/60Hz, 1.0A		
	Output: DC 12V 3.0A		
	M/N: SW36-12003000-W		
	Input: AC 100-240V; 50/60Hz, 1.5A		
	Output: DC 12V, 3.0A		
	M/N: S24B12-120A200-Y4		
	Input: AC 100-240V; 50/60Hz, 0.7A		
	Output: DC 12V, 2A		
	M/N: F12W3-120100SPAU		
	Input: AC 100-240V; 50/60Hz, 0.3A		
	Output: DC 12V, 1A		
DC output cable:	140cm (Unshielded) (MODEL: S24B12-120A200-Y4)		

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM141000589302

Page: 5 of 8

DC output cable :	144cm Unshielded with a ferrite core (MODEL: SW36-12003000-W)
DC output cable:	148cm (Unshielded) (MODEL: F12W3-120100SPAU)
DC output cable :	146cm Unshielded (MODEL: WHF-1200300T3)

#### Remark:

Model No.: G802P, G802, G801P, G801A, G800P, G800A

Only the model G802P was tested, since the circuitry design, PCB layout, electrical components used, internal wiring and functions were identical for all above models. Only different on model number, color and decorations.

### 4.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch E&E Lab

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.



Report No.: SZEM141000589302

Page: 6 of 8

### 4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### • CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

#### VCCI

The 10m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

#### FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

#### Industry Canada (IC)

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1 & 4620C-2.

#### 4.5 Deviation from Standards

None

#### 4.6 Abnormalities from Standard Conditions

None.

### 4.7 Other Information Requested by the Customer

None.



Report No.: SZEM141000589302

Page: 7 of 8

# 5 RF Exposure Evaluation

# 5.1 RF Exposure Compliance Requirement

#### **5.1.1 Limits**

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

Table 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)		
(A) Limits for Occupational/Controlled Exposures						
0.3–3.0 3.0–30 30–300 300–1500 1500–100,000	614 1842/f 61.4	1.63 4.89/f 0.163	*(100) *(900/f²) 1.0 f/300 5	6 6 6 6		
(B) Limits for General Population/Uncontrolled Exposure						
0.3–1.34 1.34–30 30–300 300–1500 1500–100,000	614 824/f 27.5	1.63 2.19/f 0.073	*(100) *(180/f²) 0.2 f/1500 1.0	30 30 30 30 30		

F= Frequency in MHz

Friis Formula

Friis transmission formula: Pd = (Pout\*G)/(4\* Pi \* R 2)

Where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### 5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM141000589302

Page: 8 of 8

#### 5.1.3 EUT RF Exposure Evaluation

Antenna Gain: 5dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 5 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Frequency	Max Conducted	Output Power	Power Density	Limit	Result
	(MHz)	Peak Output	to Antenna	at R = 20 cm		
		Power (dBm)	(mW)	(mW/cm <sup>2</sup> )		
Lowest	2412	22.54	179.473	0.1129	1.0	PASS

Note: Refer to report No. SZEM141000589301 for EUT test Max Conducted Peak Output Power value. The distancer (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.