## User manual for Bluetooth module (Model: MY-DJAP-BD)

## **Features description**

- Use Bluetooth 2.1 + EDR specifications based on CLASS 2 power level
- Support L2CAP/A2DP (AVCTP / AVDTP / AVRCP to receive stereo audio signal and control the Prev/Next operation of the audio transmitter by agreement;
- Support Simple Pairing, without the pairing code, support automatic back even function Note:

SBC decode for Bluetooth audio streaming

- Easy to build using simple SMD
- Support Piconet

#### Note

- a. That module is limited to OEM installation ONLY
- b. That module is limited to installation in mobile or fixed applications, according to Part 2.1091(b).
- c. That separate approval is required for all other operating configurations, including portable configurations with respect to Part 2.1093 and different antenna configurations.
- d. The OEM integrator is responsible for ensuring that the end-user has no manual instructions to remove or install module.
- e. The module is limited to installation in mobile or fixed applications

# **Technical Specifications General Specification**

Number	Items	Description
1	Bluetooth Standard	Bluetooth v2.1+EDR
2	Chipset	CW6639E
3	Dimension	16.9mm x 14.2mm x 2mm
4	Voltage	3.3V
5	Temperature	-20∼+70 °C
6	Storage Temperature	-40∼+85 °C
7	Frequency Range	2402~2480MHz
8	Maximum RF Transmit Power	6dBm
9	Receive Sensitivity	-80dBm
10	Bluetooth® Profile Supported	A2DP,AVRCP,HFP,HSP,APTX

## **Power Consumption**

BMLE45	Item	Min	Тур	Max	Unit	Note
State	Working voltage		3.3		V	
	Working current		12		mA	Call and music
	Standby current		86		uA	
Power supply: 3.3V						

Operational Mode	Minimum	Typical	Maximum
Page scan, time internal 1.28s	-	1mA	-
Inquiry	-	55mA	-
Page scan and Inquiry	-	1.6mA	-
ACL no traffic	-	26mA	-
ACL with file transfer	-	47mA	-
SCO HV3	-	52mA	-
Sleep	-	80uA	_

# **Stereo Codec: Analogue to Digital Converter**

Analogue to Digital Converter								
Parameter	Conditions	Min	Тур	Max	Note			
Resolution	-		-	-	16	Bits		
Input Sample	-		8	-	48	kHz		
Rate,F <sub>SAMPLE</sub>								
	f <sub>in</sub> =1kHz	F <sub>SAMPLE</sub>						
SNR	B/W=20Hz-Fsample/2	8kHz	-	93.5	-	dB		
	(20kHz max)	16kHz		92.5		dB		
	A-Weighted	32kHz		91.4		dB		
	THD+N<0.1%	44.1kHz		90.4		dB		
	$1.6V_{pk-pk}$ input	48kHz		89.6		dB		
THD+N	f <sub>in</sub> =1kHz	F <sub>SAMPLE</sub>						
	B/W=20Hz- Fsample/2	8kHz	-	0.0041	-	%		
	(20kHz max)	48kHz	-	0.0072	-	%		
	1.6V <sub>pk-pk</sub> input							
Digital Gain	Digital Gain Resolution=	1/32dB	-24	-	21.5	dB		
Analogue Gain	Pre-amplifier setting = 0d	B, 9dB, 21dB	-3	-	42	dB		
	or30dB							
	Analogue setting = $-3dB$							
	3dB steps							
Stereo separation	(crosstalk)		_	-88.5	_	dB		

# **Stereo Codec: Digital to Analogue Converter**

Analogue to Digital Converter							
Parameter	Cond	itions		Min	Тур	Max	Note
Resolution	-			-	-	16	Bits
Output Sample	-		8	-	96	kHz	
Rate, F <sub>SAMPLE</sub>							
	f <sub>in</sub> =1kHz	F <sub>SAMPLE</sub>	Load				
SNR	B/W=20Hz-20kHz	48kHz	100kΩ	-	95.6	-	dB
	A-Weighted	48kHz	32Ω	-	95.8	-	dB
	THD+N<0.1%	48kHz	16Ω	-	95.6	-	dB
	0dBFS input						

THD+N	f <sub>in</sub> =1kHz	F <sub>SAMPLE</sub>	Load				
	B/W=20Hz-20kHz	8kHz	100kΩ	-	0.0025	-	%
	0dBFS input	8kHz	32Ω	-	0.0056	-	%
		8kHz	16Ω	-	0.0108		%
		48kHz	100kΩ	-	0.0027		%
		48kHz	32Ω	-	0.0067		%
		48kHz	16Ω	-	0.0122		%
Digital Gain	Digital Gain Resolut		-24	-	21.5	dB	
Analogue Gain	Analogue Gain Resolution = 3dB			-21	-	0	dB
Stereo separation	-	-87.5	-	dB			

# **Auxiliary ADC**

Auxiliary ADC	Min	Тур	Max	Unit	
Resolution		-	_	10	Bits
Input voltage range <sup>(a)</sup>		0	_	VDD_AUX	V
Accuracy	INL	-1	_	1	LSB
(Guaranteed monotonic)	DNL	0	_	1	LSB
Offset	-1	-	1	LSB	
Gain error	-0.8	-	0.8	%	
Input bandwidth	-	100		kHz	
Conversion time	1.38	1.69	2.75	μs	
Sample rate <sup>(b)</sup>		-	-	700	Samples/s

<sup>(</sup>a)LSB size = VDD AUX/1023


## **Auxiliary DAC**

Min	Тур	Max	Unit
-	-	10	Bits
1.30	1.35	1.40	V
0	-	VDD_AUX	V
1.30	1.35	1.40	
0	1.32 -	2.64	mV
-1.32	0	1.32	mV
-1	0	1	LSB
-	-	250	ns
	1.30 0 1.30 0 -1.32	1.30 1.35 0 - 1.30 1.35 0 1.32 - -1.32 0	- 10 1.30 1.35 1.40 0 - VDD_AUX 1.30 1.35 1.40 0 1.32 - 2.64 -1.32 0 1.32 -1 0 1


<sup>(</sup>a) The settling time does not i nclude any capacitive load

<sup>(</sup>b) The auxiliary ADC is accessed through a VM function. The sample rate given is achieved as part of this function.

## **Block Diagram**



# **Mechanical Dimensions and Electrical feature**



Pin number	Name	Electrical specific ation	State
1	TP1	Digital I/O	Test PIN
2	TP2	Digital I/O	Test PIN
3	TP3	Digital I/O	Test PIN
4	VIN	Power	Power Input
5	GND	Power	Digital Ground
6	GND	Power	Digital Ground
7	TXD	Digital I/O	CMD2026 CW6638 UART Transfer
8	RXD	Digital I/O	CMD2026 CW6638 UART Receiver
9	CTS	Digital I/O	APB8202 CW6638 UART Flow Control
10	TP6	Digital I/O	Test PIN
11	TP5	Digital I/O	Test PIN
12	TP4	Digital I/O	Test PIN

## Related recommended

- Module output audio is a differential signal
- If you want to use the MIC function, in order to achieve the best sound effects, please don't take MICAnd SPK is placed in the same plane, preferably vertically placed
- Full metal shell will greatly shorten the Bluetooth transmission distance
- Bluetooth antenna below PCB plate not copper

### **Disclaimer**

THESE MATERIALS AND INFORMATION ARE PROVIDED "AS IS" WITHOUT WARRANTYOF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THEIMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSEOR NON-INFRINGEMENT.

We use reasonable efforts to include accurate and up-to-date information on this document; it does not, however, make any representations as to its accuracy or completeness of the information, text, graphics, links or other items contained within these materials. Your use of this Document is at your own risk. Ogemaw, its suppliers, and other parties involved in creating and delivering this Document's contents shall not be liable for any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits.

## **OEM Labeling Requirements**

#### **USERS MANUAL OF THE END PRODUCT:**

In the user's manual of the end product, the end user has to be informed to keep at least 20cm separation with the antenna while this end product is installed and operated. The end user has to be informed that the FCC radio-frequency exposure guidelines for an uncontrolled environment can be satisfied. The end user has to also be informed that any changes or modifications not expressly approved by the manufacturer could void the user's authority to operate this equipment. If the size of the end product is smaller than 8x10cm, then additional FCC part 15.19 statement is required to be available in the user's manual:

This device complies with Part 15 of FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference and (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC Caution: Any changes or modifications not expressly approved by the party Responsible for compliance could void the user's authority to operate this equipment.

#### LABEL OF THE END PRODUCT:

The final end product must be labeled in a visible area with the following "Contains TX

FCC ID: 2AATW-20140913AP ". If the size of the end product is larger than 8x10cm, then the following FCC part 15.19 statement has to also be available on the label: This device complies with Part 15 of FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference and (2) this device must accept any interference received, including interference that may cause undesired operation.

## **Radiation Exposure Statement**

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled Environment. This equipment should be installed and operated with minimum distance 20cm. Between the radiator & your body.

### Attention

The OEM integrator is still responsible for the FCC compliance requirement of the end product, which integrates this module. Appropriate measurements (e.g. 15 B compliance) and if applicable additional equipment authorizations (e.g. Verification , Doc) of the host device to be addressed by the integrator/manufacturer.

This RF Module does not have an own shielding, so that a Limited Modular Approval (LMA) was granted: This RF module is strictly limited to the integration by the Grantee himself or the dedicated OEM integrators under the control of the Grantee. and This LMA with a Integral antenna, antenna gain is 0.0dBi.

Proper measurements of the host device including this RF module (radiated spurious emissions and bandage) are required to assure compliance with the FCC regulations.

Any other integrator must contact the Grantee to determine necessary compliance measurements and/or additional equipment authorizations (e.g. Class II Permissive Change or New Equipment Authorization) for his configuration. This RF Module must not be sold to the general public.

IMPORTANT NOTE: In the event that these conditions cannot be met (for example: certain laptop configurations or co-location with another transmitter), then the FCC authorization is no longer considered valid and the FCC ID cannot be used on the final product. In these circumstances, the OEM integrator will be responsible for re-evaluating the end product (including the transmitter) and obtaining a separate FCC authorization. Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.