# RF EXPOSURE REPORT



Report No.: 16070220-FCC-H2 Supersede Report No.: N/A

Applicant	NEG TECHNOLOGY CO., LIMITED		
Product Name	Mobile Phone		
Model No.	F1009		
Serial No.	N/A		
Test Standard	FCC 2.1093:2014		
Test Date	September 10 to September 24. 2015		
Issue Date	March 16,2016		
Test Result	Pass Fail		
Equipment complied with the specification			
Equipment did not comply with the specification			
Winnie Zhang		David Huang	
Winnie Zhang Test Engineer		David Huang Checked By	

This test report may be reproduced in full only

Test result presented in this test report is applicable to the tested sample only

#### Issued by:

#### SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park
South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn



Test Report	16070220-FCC-H2
Page	2 of 9

### **Laboratories Introduction**

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

#### **Accreditations for Conformity Assessment**

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety



Test Report	16070220-FCC-H2
Page	3 of 9

This page has been left blank intentionally.



Test Report	16070220-FCC-H2
Page	4 of 9

# **CONTENTS**

1.	REPORT REVISION HISTORY	.5
	CUSTOMER INFORMATION	
3.	TEST SITE INFORMATION	.5
4.	EQUIPMENT UNDER TEST (EUT) INFORMATION	.6
5.	FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES.	8
5.1	RF EXPOSURE	.8
52	TEST RESULT	Ç



Test Report	16070220-FCC-H2
Page	5 of 9

# 1. Report Revision History

Report No.	Report Version	Description	Issue Date
16070220-FCC-H2	NONE	Original	March 16,2016

# 2. Customer information

Applicant Name	NEG TECHNOLOGY CO., LIMITED
Applicant Add	Rm 1406, Block B, Jinsejiari, Jingtian south road, Futian district, Shenzhen, China
Manufacturer	NEG TECHNOLOGY CO., LIMITED
Manufacturer Add	Rm 1406, Block B, Jinsejiari, Jingtian south road, Futian district, Shenzhen, China

# 3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES	
	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park	
Lab Address	South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong	
	China 518108	
FCC Test Site No.	718246	
IC Test Site No.	4842E-1	
Test Software	Radiated Emission Program-To Shenzhen v2.0	



Test Report	16070220-FCC-H2
Page	6 of 9

## 4. Equipment under Test (EUT) Information

Description of EUT:	Mobile Phone
Main Model:	F1009
Serial Model:	N/A
Date EUT received:	September 09, 2015
Test Date(s):	September 10 to September 24. 2015
Antenna Gain:	GSM850:0.3dBi PCS1900:0.35dBi Bluetooth:0.1dBi
Type of Modulation:	GSM / GPRS: GMSK Bluetooth: GFSK, π /4DQPSK, 8DPSK
RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz Bluetooth: 2402-2480 MHz
Number of Channels:	GSM 850: 124CH PCS1900: 299CH Bluetooth: 79CH
Port:	Power Port, Earphone Port, USB Port
	AC Adapter:

AC Adapter:

Model:F1009

Input: AC 100-240V; 50/60Hz;150mA

Output: DC5.0V; 500mA

Input Power: Battery:

Model:F1009

Bateria Li-on:2.59Wh

Voltaje de carga limite:4.2V

Capacidad de bacteria:3.7V , 700mAh



Test Report	16070220-FCC-H2	
Page	7 of 9	

Trade Name : OWN

GPRS Multi-slot class 8/10/12

FCC ID: 2AAZ8-F1009

Date EUT received: September 09, 2015



Test Report	16070220-FCC-H2
Page	8 of 9

# 5. FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable devices.

#### 5.1 RF Exposure

#### Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot \sqrt{f_{(GHz)}} \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR,  $^{16}$  where

- f<sub>(GHz)</sub> is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $\leq 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

result =  $P\sqrt{F}/D$ 

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm



Test Report	16070220-FCC-H2
Page	9 of 9

### 5.2 Test Result

#### **Bluetooth Mode:**

Modulation	СН	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	-2.819	-3±1	-2	0.631	0.20	3
	Mid	2441	-3.945	-3±1	-2	0.631	0.20	3
	High	2480	-4.280	-4±1	-3	0.501	0.16	3
π /4 DQPSK	Low	2402	-1.267	-1±1	0	1.000	0.31	3
	Mid	2441	-2.053	-2±1	-1	0.794	0.25	3
	High	2480	-3.531	-3±1	-2	0.631	0.20	3
8-DPSK	Low	2402	-0.982	-1±1	-0	1.000	0.31	3
	Mid	2441	-1.642	-1±1	0	1.000	0.31	3
	High	2480	-3.049	-3±1	-2	0.631	0.20	3

Result: Compliance

No SAR measurement is required.