

## FCC SAR TEST REPORT

No. 140612

for

**NEG TECHNOLOGY CO., LIMITED** 

**Mobile Phone** 

**Model Name: OWN F1030** 

FCC ID: 2AAZ8-F1030

Issued Date: 2014-06-18



#### Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of GCCT.

#### **Test Laboratory:**

GCCT, Guangdong Telecommunications Terminal Products Quality Supervision and Testing Center Technology Road, High-tech Zone, He Yuan, Guang Dong, PR China 517001
Tel:+86(0)762-3607181, Fax:+86(0)762-3603336 Email: ncctmail@126.com. www.ncct.org.cn



## **CONTENTS**

GENERAL SUMMARY	4
1.Test Laboratory	5
1.1 Testing Location	5
1.2 Testing Environment	
1.3 Project Data	5
2. Client Information	6
2.1 Applicant Information	6
2.2 Manufacturer Information	6
3. Equipment Under Test (EUT) and Ancillary Equipment (AE)	7
3.1 About EUT	7
3.2 Internal Identification of EUT	
3.3 Internal Identification of AE	7
4. EUT Operational Conditions During Test	8
4.1 General Description of Test Procedures	8
4.2 GSM Test Configuration	8
5. SAR Measurements System Configuration	9
5.1 Measurement System Diagram	9
5.2 System Components	10
5.3 Equivalent Tissues	13
6. Evaluation Procedures	14
6.1 Data Evaluation	14
6.2 SAR Evaluation Procedures	
6.3 Spatial Peak SAR Evaluation	16
7. Conducted Output Power Measurement	18
8. SAR Measurement Results	19
8.1 Liquid Measurement Results	19
8.2 System Performance Check	
8.3 Measurement Results	21
9. Equipment List & Calibration Status	25
10. Measurement Uncertainty	26
ANNEX A: EUT Photos and Test Positions	27
ANNEX B: System Performance Check Plots	31
ANNEX C: SAR Test Plots	35
ANNEX D: Probe calibration report	56
ANNEX F: Dinole calibration report	68

ANNEX F: DAE calibration report	85
ANNEX G: Dipole Annual Check Result	89



## **GENERAL SUMMARY**

Product Name	Mobile Phone				
Model Name	OWN F1030				
Applicant	NEG TECHNOLOGY CO., LIMITED				
Manufacturer	1				
Test laboratory	GCCT, Guangdong Telecommunications Terminal Products Quality Supervision and Testing Center				
Reference Standards	IEEE Std C95.1, 1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz  IEEE 1528-2003: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques  FCC KDB 447498 D01 v05r02: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies  FCC KDB 865664 D01 v01r03: SAR Measurement Requirements for 100 MHz to 6 GHz  FCC KDB 648474 D04 Handset SAR v01r02: SAR Evaluation  Considerations for Wireless Handsets  IEC 62209-1: 2005: Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices — Human models, instrumentation, and procedures, Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)  IEC 62209-2: 2010: Human exposure to radio frequency fields from handheld and body-mounted wireless communication devices - Human models, instrumentation, and procedures, Part 2: Procedure to determine the specific absorption rate (SAR) for mobile wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)				
	This portable wireless equipment has been measured in all cases requested by the relevant standards. Test results in Chapter 8 of this test report are				
Test	below limits specified in the relevant standards.				
Conclusion	a seem milities opposition in the reservant standards.				
	General Judgment: Pass				
	Date of issue:2014.06.18				
Comment:	The test results in this report apply only to the tested sample of the stated device/equipment.				
Approved by:	Reviewed by: Tested by:				

luo jian	Dong Xrasbo	Ch Unflang
Luo Jian	Dong Xiaobo	Li Linqiang
Manager	Manager	Test Engineer

No. 140612 Page 5 of 89



## 1. Test Laboratory

## 1.1 Testing Location

Company Name:	me:  GCCT, Guangdong Telecommunications Terminal Products Qua Supervision and Testing Center	
CNAS Registration No.	CNAS L4992	
Address:	Technology Road, High-tech Zone, Heyuan, Guangdong Province,	
Address.	PR.China	
Postal Code:	517001	
Telephone:	+86-762-3607181	
Fax:	+86-762-3603336	

## 1.2 Testing Environment

Temperature	Min. = 20°C, Max. = 25 °C
Relative humidity	Min. = 30%, Max. = 70%
Ground system resistance	< 0.5 Ω
A salada at a sala a da sala a d	and found on the condition of the condition of

Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.

## 1.3 Project Data

Project Leader:	Dong Xiaobo
Project Engineer	Li Linqiang
Testing Start Date:	2014-06-17
Testing End Date:	2014-06-18

No. 140612 Page 6 of 89



## 2. Client Information

## 2.1 Applicant Information

Company Name:	NEG TECHNOLOGY CO., LIMITED		
Address:	Rm 1406, Block B, Jinsejiari, Jingtian south road, Futian district, Shenzhen, China		
City:	1		
Postal Code:	1		
Country:	1		
Telephone:	1		
Fax:	1		

## 2.2 Manufacturer Information

Company Name:	1
Address:	1
City:	1
Postal Code:	1
Country:	1
Telephone:	1
Fax:	1

No. 140612 Page 7 of 89



## 3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

## 3.1 About EUT

1	1			
Product Name	Mobile Phone			
Model Name	OWN F1030			
Exposure Category	Uncontrolled Environn	nent / General Popu	lation	
Device Type	Portable Device			
Supporting modes	GSM850 (tested) DCS1900 (tested) Bluetooth			
GPRS Class	Class 12			
	Mode	de 1g SAR(W/Kg)		
Max. SAR (1g)		Head	Body-worn	
inera or a t (1g)	GSM850	0.515	1.34	
	GSM1900	0.176	0.647	
Antenna Type	Fixed Internal Antenna			
Form factor	11.9cm*5.1cm			
Comment	The above EUT's information was declared by manufacture.			

Note: Photographs of EUT are shown in ANNEX A of this test report.

## 3.2 Internal Identification of EUT

EUT ID*	IMEI	HW Version	SW Version
M01	1	1	1

<sup>\*</sup>EUT ID: is used to identify the test sample in the lab internally.

## 3.3 Internal Identification of AE

AE ID*	Description	Туре	SN	Manufacture
B01	Battery	OWN F1030	1	1
CH01	Charger	OWN F1030D	1	1

<sup>\*</sup>AE ID: is used to identify the test sample in the lab internally.

No. 140612 Page 8 of 89



## 4. EUT Operational Conditions During Test

## 4.1 General Description of Test Procedures

A communication link is set up with a System Simulator (SS) by air link, and a call is established. The Absolute Radio Frequency Channel Number (ARFCN) is allocated to 128, 190 and 251 in the case of GSM850, allocated to 512, 661 and 810 in the case of PCS1900. The EUT is commanded to operate at maximum transmitting power by MT8820C

When we test, the EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output. The antenna connected to the output of the base station simulator shall be placed at least 50 cm away from the EUT. The signal transmitted by the simulator to the antenna feeding point shall be lower than the output power level of the EUT by at least 30 dB.

## 4.2 GSM Test Configuration

For the SAR tests for GSM850 and DCS1900, a communication link is set up with a System Simulator (SS) by air link. Using MT8820C the power lever is set to "5" of GSM850, set to "0" of PCS1900. The EUT is commanded to operate at maximum transmitting power. The GPRS class is 12 for this EUT. It has at most 4 timeslots in uplink and at most 4 timeslots in downlink, the maximum total timeslots is 5.

No. 140612 Page 9 of 89



## 5. SAR Measurements System Configuration

These measurements were performed with the automated near-field scanning system DASY5 from SPEAG. The system is based on a high precision robot, which positions the probes with a positional repeatability of better than  $\pm$  0.02 mm. Special E-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit. The SAR measurements were conducted with the dosimetric probe manufactured by SPEAG, designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure described in with accuracy of better than  $\pm$ 10%. The spherical isotropy was evaluated and found to be better than  $\pm$ 0.3 dB. The phantom used was the SAM Twin Phantom and ELI4 Phantom as described in IEC 62209-1, IEEE1528 and EN 62209-1.

## 5.1 Measurement System Diagram




Figure 1 System Diagram

## The DASY5 system consists of the following items:

- 1. A standard high precision 6-axis robot (TX90XL) with St"aubli CS8c robot controllers.
- 2. DASY5 Measurement Server.
- 3. Data Acquisition Electronics.
- 4. A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- 5. Light Beam Unit.
- 6. The SAM phantom enabling testing left-hand right-hand and the ELI4 phantom for body usage.
- 7. The Position device for handheld EUT.
- 8. Tissue simulating liquid mixed according to the given recipes.
- 9. System validation dipoles to validate the proper functioning of the system.
- 10. A computer operating Windows XP.

No. 140612 Page 10 of 89



## 5.2 System Components

The mobile phone under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The DASY5 software computes the results to give a SAR value in a 1g or 10 g mass.

#### 5.2.1 TX90XL

The TX90XL robot has six axes. The six axes are controlled by the St"aubli CS8c robot controllers. It offers the features important for our application:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchrony motors; no stepper motors)
- Low ELF

### 5.2.2 DASY5 Measurement Server

The DASY5 measurement server is based on a PC/104 CPU board with a 400MHz Intel ULV Celeron, 128MB chip disk and 128MB RAM. The necessary circuits for communication with either the DAE4 electronics box as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY5 I/O board, which is directly connected to the PC/104 bus of the CPU board.



Figure 2 TX90XL



Figure 3 Measurement Server

#### 5.2.3 Probe

For the measurements the specific dosimetric E-Field Probe ES3DV3 and EX3DV4 with following specifications is used.

Frequency: 10 MHz to 3 GHz; Linearity: ± 0.2 dB

Directivity: ± 0.3 dB in HSL (rotation around probe axis)

± 0.5 dB in tissue material (rotation normal to probe axis)

Dynamic Range: 10 μW/g to > 100 mW/g; Linearity: ± 0.2 dB

Tip Diameter: 5 mm; Distance between probe tip and sensor center: 2.5 mm

No. 140612 Page 11 of 89



Probe linearity: ±0.3 dB

Calibration range: 835 to 2500 MHz for head & body simulating liquid

#### 5.2.4 Device holder

The DASY device holder is designed to cope with the different positions given in the standard.

It has two scales for device rotation (with respect to the body axis) and device inclination (with respect to the line between the ear reference points). The rotation centers for both scales are the ear reference point (ERP). Thus the device needs no repositioning when changing the angles. The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity =3 and loss tangent =0.02. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.








Figure 5 Device Holder

## 5.2.5 Phontom

The SAM Twin Phantom and the ELI4 Phantom are constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is in compliance with the specification set in IEEE P1528 and CENELEC EN62209-1. The SAM Twin phantom enables the dosimetric evaluation of left and right hand phone usage and the ELI4 phantom enables the dosimetric evaluation of body mounted usage. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot.

Shell thickness: 2 mm +/-0.2 mm Filling Volume: Approx. 25 liters

Dimensions (H x L x W): 850 x 1000 x 500 mm

No. 140612 Page 12 of 89






Figure 6 SAM Twin Phantom and ELI Phantom

## 5.2.6 Data Acquisition Electronics

DAE4 consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock. The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

Input impedance: 200MOhm, symmetrical and floating.

Common mode rejection: > 80 dB.

## 5.2.7 Validation dipoles

SPEAG has a full range of dipoles corresponding to the frequencies defines by the standards: 835, 900,

1800, 1900, 2000, 2450MHz Maximum input Power: 100W

Connectors: SMA

Dimensions: (depends on the dipole frequency)

No. 140612 Page 13 of 89







Figure 7 DAE4

Figure 8 Validation Dipoles

## **5.3 Equivalent Tissues**

The relative permittivity and conductivity of the tissue material should be within  $\pm 5\%$  of the values given in the table below recommended by the FCC KDB 865664 D01 v01r03.

Target Frequency	Hea	ad	Вос	dy
(MHz)	٤r	σ (S/m)	٤r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800-2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

(  $\varepsilon r$  = relative permittivity,  $\sigma$  = conductivity and  $\rho$  = 1000 kg/m )



## 6. Evaluation Procedures

#### 6.1 Data Evaluation

The DASY5 software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters: - Sensitivity Normi, ai0, ai1, ai2

- Conversion factor ConvFi

- Diode compression point dcpi

Device parameters: - Frequency f

- Crest factor cf

Media parameters: - Conductivity σ

- Density p

These parameters must be set correctly in the software. They can be found in the component documents or be imported into the software from the configuration files issued for the DASY5 components. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \bullet \frac{cf}{dcpi}$$

with Vi = Compensated signal of channel i (i = x, y, z)

Ui = Input signal of channel i (i = x, y, z)

cf = Crest factor of exciting field (DASY5 parameter)

dcpi = Diode compression point (DASY5 parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

$$E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$
 E-field probes:

 $H_{i} = \sqrt{V_{i}} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^{2}}{f}$ 

With Vi = Compensated signal of channel i (i = x, y, z)

No. 140612 Page 15 of 89



Normi = Sensor sensitivity of channel i (i = x, y, z)

ConvF= Sensitivity enhancement in solution

aij = Sensor sensitivity factors for H-field probes

f = Carrier frequency (GHz)

Ei = Electric field strength of channel i in V/m

Hi = Magnetic field strength of channel i in A/m

The RSS value of the field components give the total field strength:

$$E_{\text{tot}} = \sqrt{E_{x}^{2} + E_{y}^{2} + E_{z}^{2}}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{\text{tot}}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

With SAR = local specific absorption rate in mW/g

Etot = total field strength in V/m

σ= conductivity in [mho/m] or [Siemens/m]

 $\rho$ = equivalent tissue density in g/ $cm^3$ 

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field as a free space field.

$$P_{\text{pwe}} = E_{\text{tot}}^2 / 3770 \text{ Or } P_{\text{pwe}} = H_{\text{tot}}^2 \cdot 37.7$$

With  $P_{\mathrm{pwe}}$  = Equivalent power density of a plane wave in mW/  $cm^2$ 

 $E_{tot}$  = total electric field strength in V/m

 $H_{tot}$  = total magnetic field strength in A/m

## **6.2 SAR Evaluation Procedures**

The procedure for assessing the peak spatial-average SAR value consists of the following steps:

#### Power Reference Measurement

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

### Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in DASY5 software can find the maximum locations even in relatively coarse grids. The scan area is defined by an editable grid. This grid is anchored at the grid reference point of the

No. 140612 Page 16 of 89



selected section in the phantom. When the area scan's property sheet is brought-up, grid was at to 15 mm by 15 mm and can be edited by a user.

#### Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default zoom scan measures 7 x 7 x 7 points within a cube whose base faces are centered around the maximum found in a preceding area scan job within the same procedure. If the preceding Area Scan job indicates more then one maximum, the number of Zoom Scans has to be enlarged accordingly (The default number inserted is 1).

#### Power Drift Measurement

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. In the properties of the Drift job, the user can specify a limit for the drift and have DASY5 software stop the measurements if this limit is exceeded.

## 6.3 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the IEC62209-1 standard. It can be conducted for 1 g and 10 g. The DASY5 system allows evaluations that combine measured data and robot positions, such as:

maximum search

extrapolation

boundary correction

#### Peak search for averaged SAR

During a maximum search, global and local maximum searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

#### **Extrapolation**

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation.

Extrapolation routines require at least 10 measurement points in 3-D space. They are used in the Cube Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the modified Quadratic Shepard's method for extrapolation. For a grid using 7x7x7 measurement points with 5mm resolution amounting to 343 measurement points, the uncertainty of the extrapolation routines is less than 1% for 1 g and 10 g cubes.

## **Boundary effect**

No. 140612 Page 17 of 89



For measurements in the immediate vicinity of a phantom surface, the field coupling effects between the probe and the boundary influence the probe characteristics. Boundary effect errors of different dosimetric probe types have been analyzed by measurements and using a numerical probe model. As expected, both methods showed an enhanced sensitivity in the immediate vicinity of the boundary. The effect strongly depends on the probe dimensions and disappears with increasing distance from the boundary. The sensitivity can be approximately given as:

$$S \approx S_o + S_b \exp(-\frac{z}{a})\cos(\pi \frac{z}{\lambda})$$

Since the decay of the boundary effect dominates for small probes (a<< $\lambda$ ), the cos-term can be omitted. Factors Sb (parameter Alpha in the DASY5 software) and a (parameter Delta in the DASY5 software) are assessed during probe calibration and used for numerical compensation of the boundary effect. Several simulations and measurements have confirmed that the compensation is valid for different field and boundary configurations.

This simple compensation procedure can largely reduce the probe uncertainty near boundaries. It works well as long as:

the boundary curvature is small

the probe axis is angled less than 30° to the boundary normal

the distance between probe and boundary is larger than 25% of the probe diameter

the probe is symmetric (all sensors have the same offset from the probe tip)

Since all of these requirements are fulfilled in a DASY5 system, the correction of the probe boundary effect in the vicinity of the phantom surface is performed in a fully automated manner via the measurement data extraction during post processing.

No. 140612 Page 18 of 89



## 7. Conducted Output Power Measurement

The following procedures had been used to prepare the EUT for the SAR test. To setup the desire channel frequency and the maximum output power. A Radio Communication Tester MT8820C was used to program the EUT.

		F	Power (dBm	1)		Avera	age power (	dBm)	
GSM	M 850	Channel	Channel	Channel		Channel	Channel	Channel	
		128	190	251		128	190	251	
G	SM	32.37	32.74	32.72					
	1TXslot	32.38	32.8	32.76	-9.03	23.35	23.77	23.73	
GPRS	2TXslots	30.98	31.07	32.21	-6.02	24.96	25.05	26.19	
GPRS	3TXslots	28.95	29.02	29.11	-4.26	24.69	24.76	24.85	
	4TXslots	26.95	27.02	27.07	-3.01	23.94	24.01	24.06	
		F	Power (dBm	n)		Average power (dBm)			
GSM	l 1900	Channel	Channel	Channel		Channel	Channel	Channel	
		512	661	810		512	661	810	
G	SM	30.55	30.53	30.47					
	1TXslot	30.63	30.61	30.55	-9.03	21.60	21.58	21.52	
GPRS	2TXslots	28.8	28.6	28.44	-6.02	22.78	22.58	22.42	
GPKS	3TXslots	27.26	27.01	26.87	-4.26	23.00	22.75	22.61	
	4TXslots	25.16	24.92	24.78	-3.01	22.15	21.91	21.77	

Note:

#### 1) Division Factors

To average the power, the division factor is as follows:

- 1 TX-slot = 1 transmit time slot out of 8 time slots
  - =>Conducted power divided by (8/1) => -9.03 dB
- 2 TX-slots = 2 transmit time slots out of 8 time slots
  - => Conducted power divided by (8/2) => -6.02 dB
- 3TX-slots = 3 transmit time slots out of 8 time slots
  - => Conducted power divided by (8/3) => -4.26 dB
- 4 TX-slots = 4 transmit time slots out of 8 time slots
  - => Conducted power divided by (8/4) => -3.01 dB

### 2) Average power

The maximum power are marks in bold. According to the conducted power as above, the 850MHz body measurements are performed with 2Txslots for GPRS and the 1900MHz body measurements are performed with 3Txslots for GPRS.

No. 140612 Page 19 of 89



## 8. SAR Measurement Results

## 8.1 Liquid Measurement Results

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine of the dielectric parameters are within the tolerances of the specified target values.

Freq. [MHz]	Date	Liquid Type	Liquid Temp. [°C]	Ambient Temp. [°C]	Relative Humidity	Para.	Target Value	Measured Value	Deviation [%]	Limit [%]
205	June		04.4	0.4	<b>50</b> 0/	εr	41.5	40.5	-2.41	±5
835	17, 2014	Head	21.4	21	56%	σ	0.90	0.89	-1.11	±5
	June			21	56%	εr	55.2	53.88	-2.39	±5
835	17, 2014	Body	21.4	21		σ	0.97	0.974	0.41	±5
4000	June			0.4	<b>-</b> 00/	εr	40	39.75	-0.63	±5
1900	17, 2014	Head	21.5	21	56%	σ	1.40	1.45	3.57	±5
1000	June		0.4 =		<b>-</b> 00/	εr	53.3	50.72	-4.84	±5
1900	17, 2014	Body	21.5	21	56%	σ	1.52	1.58	3.95	±5



## 8.2 System Performance Check

## **System Performance Check Measurement conditions**

- The measurements were performed in the flat section of the SAM twin phantom filled with head and body simulating liquid of the following parameters.
- The DASY5 system with an E-field probe was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 15 mm (below 1 GHz) and 10 mm (above 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 10mm was aligned with the dipole.
- Special 5x5x7 fine cube was chosen for cube integration (dx= 8 mm, dy= 8 mm, dz= 5 mm).
- Distance between probe sensors and phantom surface was set to 2.5 mm.



The depth of Liquid must above 15cm

## **System Performance Check Results**

Freq. [MHz]	Date	Liquid Type	Liquid Temp. [°C]	Amb. Temp . [°C]	Input Power (mW)	Measured SAR_1g (W/Kg)	250mW Target SAR_1g (W/Kg)	Dev. [%]	Limit [%]
925	June 17, 2014	Head	21.4	21	250	2.35	2.47	-4.86	±10
835	June 17, 2014	Body	21.4	21	250	2.59	2.52	2.78	±10
1900	June 17, 2014	Head	21.5	21	250	9.42	9.89	-4.75	±10
1900	June 17, 2014	Body	21.5	21	250	10.1	10.3	-1.94	±10



## 8.3 Measurement Results

	т	est			Freq.	Powe	r (dBm)	1g SAR (	W/Kg)	Power
Band		guration	Mode	Ch#.	[MHz]	Tune-up limit	Measured	Measured	Scaled	Drift (dB)
	Head	Left Cheek	voice	190	836.6	33	32.74	0.471	0.500	-0.10
	Head	Left Tilted	voice	190	836.6	33	32.74	0.252	0.268	-0.02
	Head	Right Cheek	voice	190	836.6	33	32.74	0.485	0.515	-0.05
	Head	Right Tilted	voice	190	836.6	33	32.74	0.283	0.301	-0.02
	Body	Back	GPRS 2 slots	251	848.8	32.5	32.21	1.19	1.27	-0.02
GSM 850	Body	Back	GPRS 2 slots	251	848.8	32.5	32.21	1.19	1.27	0.05
	Body	Back	GPRS 2 slots	190	836.6	32.5	31.07	0.966	1.34	-0.01
	Body	Back	GPRS 2 slots	128	824.2	32.5	30.98	0.658	0.935	-0.07
	Body	Front	GPRS 2 slots	251	848.8	32.5	32.21	0.780	0.834	0.01
	Body	Front	GPRS 2 slots	190	836.6	32.5	31.07	0.514	0.715	0.04
	Body	Front	GPRS 2 slots	128	824.2	32.5	30.98	0.313	0.445	-0.01
	Head	Left Cheek	voice	512	1850.2	31	30.55	0.159	0.176	-0.17
	Head	Left Tilted	voice	512	1850.2	31	30.55	0.091	0.101	-0.16
GSM	Head	Right Cheek	voice	512	1850.2	31	30.55	0.140	0.155	0.07
1900	Head	Right Tilted	voice	512	1850.2	31	30.55	0.087	0.097	0.18
	Body	Back	GPRS 3 slots	512	1850.2	28	27.26	0.545	0.647	0.07
	Body	Front	GPRS 3 slots	512	1850.2	28	27.26	0.214	0.254	-0.11

Note:

- 1) The body SAR was tested with separation distance 15mm.
- 2) Blue entries represent repeated test.

No. 140612 Page 22 of 89



## Measurement variability consideration

According to KDB 865664 D01v01r03 section 2.8.1, repeated measurements are required following the procedures as below:

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is  $\ge 1.45$  W/kg ( $\sim 10\%$  from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.

		<b>-</b> .			<b>-</b>	Measured SAR (W/Kg)					
Band	Test configuration	Mode	Ch#.	Freq. (MHz)	Oninin al	1 <sup>st</sup> Repeated		2 <sup>nd</sup> Repeated			
		comigaration				(**************************************	Original	Value	Ratio	Value	Ratio
	GSM1900	Body	Back	GPRS 2 slots	251	848.8	1.19	1.19	1.00	NA	NA



#### SAR consideration for unlicensed transmitters:

The EUT support Bluetooth function, the output power of Bluetooth is as follow:

		Conducted power ( dBm )	)
	GFSK	Pi/4DQPSK	8QPSK
Lowest	1.79	1.10	1.22
Middle	1.83	1.13	1.22
Highest	1.42	0.67	0.76
Tune-up limit	2	2	2

According to KDB 447498 section 4.3.1, the 1-g SAR test exclusion thresholds at test separation distances≤ 50 mm are determined by:

$$\frac{Max\ power\ of\ Channel(mW)}{Test\ Separation\ Dis\ tan\ ce(mm)}*\sqrt{Frequency(GHz)} \le 3.0$$

1) Bluetooth maximum tune-up limit power is 2dBm=1.6mW.

For the head and Body SAR, use 5mm and 10mm as the conservative minimum test separation distance respectively.

Mode	Frequency(MHz)	maximum Tune-up limit power(mW)	Separation Distance(mm)	≤3.0
Bluetooth (Head)	2480	1.6	5	0.50
Bluetooth (Body)	2480	1.6	15	0.17

So Bluetooth standalone SAR measurements are not required for both head and body.

3) According to KDB 447498 section 4.3.2.2, when standalone SAR test exclusion applies, the standalone SAR must be estimated according to following formula:

Estimated 
$$SAR = \frac{\sqrt{f(GHz)}}{7.5} * \frac{Max\ power\ of\ Channel(mW)}{Min\ Test\ Separation\ Dis\ tan\ ce(mm)}$$

Mode	Frequency(MHz)	maximum Tune-up limit power(mW)	Separation Distance(mm)	Estimated SAR(W/Kg)
Bluetooth (Head)	Bluetooth (Head) 2480		5	0.067
Bluetooth (Body)	2480	5	15	0.022

So the estimated Bluetooth head SAR is 0.067 W/kg and the body SAR is 0.022W/kg.

No. 140612 Page 24 of 89



## **Simultaneous SAR Consideration**

The simultaneous SAR scenarios are as follow.

No	Simultaneous Configuration	Sum. SAR (W/kg)
1	Cellular head + BT head	0.582
2	Cellular body + BT body	1.362

The maximum evaluation SAR of the simultaneous scenarios is 1.362 W/kg that less than 1.6 W/kg, so the simultaneous SAR measurement is not required.



## 9. Equipment List & Calibration Status

Name of Equipment	Manufacturer	Type/Model	Serial Number	Last Cal. Date	Calibration Due
PC	HP	d7900eC	CZC9312JJ4	N/A	N/A
E-field Probe	SPEAG	ES3DV3	SN 3221	2014-1-9	2015-1-9
DAE	SPEAG	DAE4-SD 000 D04 BJ	SN 893	2013-12-25	2014-12-24
Device Holder	Stäubli	N/A N/A		N/A	N/A
SAM Phantom	SPEAG	SAM Twin Phantom TP-1545/TP-1548		N/A	N/A
6 Axis Robot	Stäubli	Robot TX90XL	F09/5B9UA1/A/01	N/A	N/A
Dipole 835MHz	SPEAG	D835V2	4d150	2013-3-18	2016-3-17
Dipole 1900MHz	SPEAG	D1900V2	5d070	2012-10-1	2015-9-30
Wireless Communication Test Set	Anritsu	MT8820C	6201060976	2013-8-16	2014-8-15
Signal Generator	Agilent	5183A	MY49060563	2013-8-16	2014-8-15
Power Meter	Agilent	E4419B	MY45104719	2013-8-16	2014-8-15
Power Sensor	Agilent	N8481H	MY48100148	2013-8-16	2014-8-15
Directional couplers	Agilent	778D	MY48220223	N/A	N/A
Power amplifier	mini-circuits	ZHL-42W	QA0940002	N/A	N/A
Power supply	Topward	3303d	796708	2013-7-31	2014-7-30
Network Analyzer	Agilent	E5071C	MY46108263	2013-8-16	2014-8-15
Liquid Calibration Kit	Agilent	85070E	N/A	N/A	N/A

Note: Per KDB 450824 Dipole SAR Validation Verification, GCCT Lab has adopted 3 years calibration intervals. On annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

- 1. There is no physical damage on the dipole;
- 2. System validation with specific dipole is within 10% of calibrated value;
- 3. Return-loss is within 20% of calibrated measurement;
- 4. Impedance is within  $5\Omega$  of calibrated measurement.



## 10. Measurement Uncertainty

Uncertainty Component	Sec.	Tol (+-%)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	Vi
Measurement System		•		•					,
Probe calibration	E.2.1	6.55	N	1.0	1.0	1.0	6.55	6.55	8
Axial Isotropy	E.2.2	0.5	R	$\sqrt{3}$	1.0	1.0	0.29	0.29	∞
Hemispherical Isotropy	E.2.2	2.6	R	$\sqrt{3}$	1.0	1.0	1.5	1.5	∞
Boundary effect	E.2.3	0.8	R	$\sqrt{3}$	1.0	1.0	0.46	0.46	∞
Linearity	E.2.4	0.6	R	$\sqrt{3}$	1.0	1.0	0.35	0.35	∞
System detection limits	E.2.5	0.25	R	$\sqrt{3}$	1.0	1.0	0.14	0.14	∞
Readout Electronics	E.2.6	0.35	N	1	1.0	1.0	0.35	0.35	∞
Reponse Time	E.2.7	0	R	$\sqrt{3}$	1.0	1.0	0	0	∞
Integration Time	E.2.8	2.6	R	$\sqrt{3}$	1.0	1.0	1.5	1.5	∞
RF ambient Conditions-Noise	E.6.1	0	R	$\sqrt{3}$	1.0	1.0	0	0	∞
RF ambient Conditions-Reflections	E.6.1	3.0	R	$\sqrt{3}$	1.0	1.0	1.7	1.7	∞
Probe positioner Mechanical Tolerance	E.6.2	1.5	R	$\sqrt{3}$	1.0	1.0	0.87	0.87	∞
Probe positioning with respect to Phantom Shell	E.6.3	2.9	R	$\sqrt{3}$	1.0	1.0	1.67	1.67	∞
Extrapolation, interpolation and integration Algoritms for Max. SAR	E.5	1.0	R	$\sqrt{3}$	1.0	1.0	0.58	0.58	∞
Test sample Related									
Test Sample Positioning	E.4.2	4.6	N	1.0	1.0	1.0	4.6	4.6	N-1
Device Holder Uncertainty	E.4.1	5.2	N	1.0	1.0	1.0	5.2	5.2	N-1
Output Power Variation - SAR drift measurement	6.6.2	5	R	$\sqrt{3}$	1.0	1.0	2.89	2.89	∞
Phantom and Tissue Parameters		L		L	l	l			
Phantom Uncertainty (Shape and thickness tolerances)	E.3.1	4.0	R	$\sqrt{3}$	1.0	1.0	2.31	2.31	∞
Liquid conductivity - deviation from	E.3.2	5.0	R	$\sqrt{3}$	0.64	0.43	1.85	1.24	∞
Liquid conductivity - measurement	E.3.3	2.5	N	1.0	0.64	0.43	1.60	1.08	М
uncertainty Liquid permitivity - deviation from	E.3.2	5.0	R	$\sqrt{3}$	0.6	0.49	1.73	1.42	∞
target value Liquid permitivity - measurement									
uncertainty	E.3.3	2.5	N	1.0	0.6	0.49	1.5	1.23	M
Combined Standard Uncertainty			RSS				11.3	11.0	
Expanded Uncertainty (95% Confidence interval)			K				23	22	

## **ANNEX A: EUT Photos and Test Positions**

## **EUT Photos:**




**Mobile Phone** 



**Mobile Phone** 




**Mobile Phone** 




**Mobile Phone** 

## **Test Positions:**



No. 140612 Page 30 of 89

# **GCCT**



No. 140612 Page 31 of 89



## **ANNEX B: System Performance Check Plots**

Test Laboratory: GCCT Test Date: June.17, 2014

## System 835 MHz dipole (Head)

DUT: Dipole 835 MHz D835V2; Type: D835V2; Serial: D835V2

Communication System: CW; Communication System Band: D835 (835.0 MHz); Frequency: 835 MHz;

Communication System PAR: 0 dB

Medium parameters used: f = 835 MHz;  $\sigma$  = 0.89 mho/m;  $\varepsilon_r$  = 40.5;  $\rho$  = 1000 kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

## DASY5 Configuration:

Probe: ES3DV3 - SN3221; ConvF(6.23, 6.23, 6.23); Calibrated: 1/9/2014;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn893; Calibrated: 12/25/2013

Phantom: SAM\_1 with CRP v4.0; Type: QD000P40CC; Serial: TP:1586

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

835Head/System/Area Scan (31x181x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 87.272 V/m; Power Drift = -0.16 dB


Maximum value of SAR (interpolated) = 2.52 W/kg

835Head/System/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 87.272 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 3.432 mW/g

**SAR(1 g) = 2.35 mW/g; SAR(10 g) = 1.55 mW/g** Maximum value of SAR (measured) = 2.53 W/kg





Test Laboratory: GCCT Test Date: June.17, 2014

### System 835 MHz dipole (Body)

**DUT: Dipole 835 MHz D835V2; Type: D835V2; Serial: D835V2** 

Communication System: CW; Communication System Band: D835 (835.0 MHz); Frequency: 835 MHz;

Communication System PAR: 0 dB

Medium parameters used (interpolated): f = 835 MHz;  $\sigma = 0.974 \text{ mho/m}$ ;  $\epsilon_r = 53.879$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

#### DASY5 Configuration:

Probe: ES3DV3 - SN3221; ConvF(6.2, 6.2, 6.2); Calibrated: 1/9/2014;

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn893; Calibrated: 12/25/2013

Phantom: SAM\_2with CRP v4.0; Type: QD000P40CC; Serial: TP:1548

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**835Body/System/Area Scan (31x181x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm Reference Value = 54.162 V/m; Power Drift = 0.01 dB

Maximum value of SAR (interpolated) = 2.79 W/kg


835Body/System/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 54.162 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 3.776 mW/g

SAR(1 g) = 2.59 mW/g; SAR(10 g) = 1.72 mW/g

Maximum value of SAR (measured) = 2.81 W/kg





Test Date: June.17, 2014 Test Laboratory: GCCT

## System 1900 MHz dipole (Head)

## DUT: Dipole 1900 MHz D1900V2; Type: D1900V2; Serial: D1900V2

Communication System: CW; Communication System Band: D1900 (1900.0 MHz); Frequency: 1900

MHz; Communication System PAR: 0 dB

Medium parameters used: f = 1900 MHz;  $\sigma$  = 1.45 mho/m;  $\varepsilon_r$  = 39.75;  $\rho$  = 1000 kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

## DASY5 Configuration:

Probe: ES3DV3 - SN3221; ConvF(5.4, 5.4, 5.4); Calibrated: 1/9/2014;

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn893; Calibrated: 12/25/2013
- Phantom: SAM\_1 with CRP v4.0; Type: QD000P40CC; Serial: TP:1586
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

1900Head/System/Area Scan (21x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 87.272 V/m; Power Drift = -0.16 dB

Maximum value of SAR (interpolated) = 10.8 W/kg


1900Head/System/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 87.272 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 17.216 mW/g

SAR(1 g) = 9.42 mW/g; SAR(10 g) = 4.93 mW/g

Maximum value of SAR (measured) = 10.6 W/kg





Test Laboratory: GCCT Test Date: June.17, 2014

### System 1900 MHz dipole (Body)

DUT: Dipole 1900 MHz D1900V2; Type: D1900V2; Serial: D1900V2

Communication System: CW; Communication System Band: D1900 (1900.0 MHz); Frequency: 1900

MHz; Communication System PAR: 0 dB

Medium parameters used: f = 1900 MHz;  $\sigma = 1.578 \text{ mho/m}$ ;  $\varepsilon_r = 50.718$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

### DASY5 Configuration:

- Probe: ES3DV3 SN3221; ConvF(4.91, 4.91, 4.91); Calibrated: 1/9/2014;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn893; Calibrated: 12/25/2013
- Phantom: SAM\_1 with CRP v4.0; Type: QD000P40CC; Serial: TP:1586
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

1900Body/System/Area Scan (21x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 87.272 V/m; Power Drift = -0.16 dB

Maximum value of SAR (interpolated) = 11.6 W/kg


1900Body/System/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 87.272 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 17.958 mW/g

SAR(1 g) = 10.1 mW/g; SAR(10 g) = 5.34 mW/g

Maximum value of SAR (measured) = 11.4 W/kg



No. 140612 Page 35 of 89



## ANNEX C: SAR Test Plots

Test Date: June.17, 2014 Test Laboratory: GCCT

#### **GSM850 LEFT/CHEEK-Mid**

**DUT: Mobile Phone; Type: OWN F1030** 

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz);

Frequency: 836.6 MHz; Communication System PAR: 9.191 dB

Medium parameters used (interpolated): f = 836.6 MHz;  $\sigma = 0.89 \text{ mho/m}$ ;  $\varepsilon_r = 41.478$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Left Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

## DASY5 Configuration:

Probe: ES3DV3 - SN3221; ConvF(6.23, 6.23, 6.23); Calibrated: 1/9/2014;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn893; Calibrated: 12/25/2013

Phantom: SAM\_2with CRP v4.0; Type: QD000P40CC; Serial: TP:1548

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)


GSM850 LEFT/CHEEK-Mid/Area Scan (41x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm Reference Value = 7.130 V/m; Power Drift = -0.10 dB Maximum value of SAR (interpolated) = 0.501 W/kg

GSM850 LEFT/CHEEK-Mid/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm,

Reference Value = 7.130 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.601 mW/g

SAR(1 g) = 0.471 mW/g; SAR(10 g) = 0.344 mW/gMaximum value of SAR (measured) = 0.488 W/kg





Test Laboratory: GCCT Test Date: June.17, 2014

#### GSM850 LEFT/TILT-Mid

**DUT: Mobile Phone; Type: OWN F1030** 

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz);

Frequency: 836.6 MHz; Communication System PAR: 9.191 dB

Medium parameters used (interpolated): f = 836.6 MHz;  $\sigma = 0.89 \text{ mho/m}$ ;  $\epsilon_r = 41.478$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Left Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

## DASY5 Configuration:

Probe: ES3DV3 - SN3221; ConvF(6.23, 6.23, 6.23); Calibrated: 1/9/2014;

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn893; Calibrated: 12/25/2013

Phantom: SAM\_2with CRP v4.0; Type: QD000P40CC; Serial: TP:1548

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)


**GSM850 LEFT/TILT-Mid/Area Scan (41x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm Reference Value = 9.531 V/m; Power Drift = -0.02 dB


Maximum value of SAR (interpolated) = 0.264 W/kg

**GSM850 LEFT/TILT-Mid/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 9.531 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.315 mW/g

SAR(1 g) = 0.252 mW/g; SAR(10 g) = 0.190 mW/g Maximum value of SAR (measured) = 0.266 W/kg







#### **GSM850 RIGHT/CHEEK-Mid**

**DUT: Mobile Phone; Type: OWN F1030** 

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz);

Frequency: 836.6 MHz; Communication System PAR: 9.191 dB

Medium parameters used (interpolated): f = 836.6 MHz;  $\sigma = 0.89 \text{ mho/m}$ ;  $\varepsilon_r = 41.478$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

## DASY5 Configuration:

Probe: ES3DV3 - SN3221; ConvF(6.23, 6.23, 6.23); Calibrated: 1/9/2014;

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn893; Calibrated: 12/25/2013

Phantom: SAM 2with CRP v4.0; Type: QD000P40CC; Serial: TP:1548

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

GSM850 RIGHT/CHEEK-Mid/Area Scan (41x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 7.878 V/m; Power Drift = -0.05 dB


Maximum value of SAR (interpolated) = 0.508 W/kg

**GSM850 RIGHT/CHEEK-Mid/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 7.878 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.617 mW/g

SAR(1 g) = 0.485 mW/g; SAR(10 g) = 0.358 mW/g Maximum value of SAR (measured) = 0.509 W/kg







GSM850 RIGHT/CHEEK-Mid-axis scan



#### **GSM850 RIGHT/TILT-Mid**

**DUT: Mobile Phone; Type: OWN F1030** 

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz);

Frequency: 836.6 MHz; Communication System PAR: 9.191 dB

Medium parameters used (interpolated): f = 836.6 MHz;  $\sigma = 0.89 \text{ mho/m}$ ;  $\varepsilon_r = 41.478$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

## DASY5 Configuration:

Probe: ES3DV3 - SN3221; ConvF(6.23, 6.23, 6.23); Calibrated: 1/9/2014;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn893; Calibrated: 12/25/2013

Phantom: SAM\_2with CRP v4.0; Type: QD000P40CC; Serial: TP:1548

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**GSM850 RIGHT/TILT-Mid/Area Scan (41x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm Reference Value = 9.531 V/m; Power Drift = -0.02 dB


Maximum value of SAR (interpolated) = 0.299 W/kg

**GSM850 RIGHT/TILT-Mid/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.531 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.362 mW/g

SAR(1 g) = 0.283 mW/g; SAR(10 g) = 0.211 mW/g Maximum value of SAR (measured) = 0.294 W/kg





## GPRS 850/Back side High

**DUT: Mobile Phone; Type: OWN F1030** 

Communication System: GPRS(2slots); Communication System Band: GSM850; Frequency: 848.8 MHz;

Communication System PAR: 6.128 dB

Medium parameters used (interpolated): f = 848.8 MHz;  $\sigma = 0.951 \text{ mho/m}$ ;  $\epsilon_r = 53.603$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

## DASY5 Configuration:

Probe: ES3DV3 - SN3221; ConvF(6.2, 6.2, 6.2); Calibrated: 1/9/2014;

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn893; Calibrated: 12/25/2013
- Phantom: SAM\_2with CRP v4.0; Type: QD000P40CC; Serial: TP:1548
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

GPRS 850/Back side High/Area Scan (41x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 14.495 V/m; Power Drift = -0.02 dB


Maximum value of SAR (interpolated) = 1.25 W/kg

**GPRS 850/Back side High/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 14.495 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.535 mW/g

SAR(1 g) = 1.19 mW/g; SAR(10 g) = 0.870 mW/g Maximum value of SAR (measured) = 1.26 W/kg







GPRS 850/Back side High-axis scan



## GPRS 850/Back side High

**DUT: Mobile Phone; Type: OWN F1030** 

Communication System: GPRS(2slots); Communication System Band: GSM850; Frequency: 848.8 MHz;

Communication System PAR: 6.128 dB

Medium parameters used (interpolated): f = 848.8 MHz;  $\sigma = 0.951 \text{ mho/m}$ ;  $\epsilon_r = 53.603$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

## DASY5 Configuration:

Probe: ES3DV3 - SN3221; ConvF(6.2, 6.2, 6.2); Calibrated: 1/9/2014;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn893; Calibrated: 12/25/2013

Phantom: SAM\_2with CRP v4.0; Type: QD000P40CC; Serial: TP:1548

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

GPRS 850/Back side High 2/Area Scan (41x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 14.361 V/m; Power Drift = 0.05 dB


Maximum value of SAR (interpolated) = 1.26 W/kg

**GPRS 850/Back side High 2/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.361 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.545 mW/g

SAR(1 g) = 1.19 mW/g; SAR(10 g) = 0.869 mW/g Maximum value of SAR (measured) = 1.25 W/kg





#### GPRS 850/Back side Mid

**DUT: Mobile Phone; Type: OWN F1030** 

Communication System: GPRS(2slots); Communication System Band: GSM850; Frequency: 836.6 MHz;

Communication System PAR: 6.128 dB

Medium parameters used (interpolated): f = 836.6 MHz;  $\sigma = 0.939 \text{ mho/m}$ ;  $\epsilon_r = 53.719$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

## DASY5 Configuration:

Probe: ES3DV3 - SN3221; ConvF(6.2, 6.2, 6.2); Calibrated: 1/9/2014;

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn893; Calibrated: 12/25/2013

Phantom: SAM\_2with CRP v4.0; Type: QD000P40CC; Serial: TP:1548

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

GPRS 850/Back side Mid/Area Scan (41x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 12.888 V/m; Power Drift = -0.01 dB

Maximum value of SAR (interpolated) = 1.03 W/kg


GPRS 850/Back side Mid/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm,

dz=5mm

Reference Value = 12.888 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.242 mW/g

**SAR(1 g) = 0.966 mW/g; SAR(10 g) = 0.708 mW/g** Maximum value of SAR (measured) = 1.02 W/kg





#### GPRS 850/Back side Low

**DUT: Mobile Phone; Type: OWN F1030** 

Communication System: GPRS(2slots); Communication System Band: GSM850; Frequency: 824.2 MHz;

Communication System PAR: 6.128 dB

Medium parameters used (interpolated): f = 824.2 MHz;  $\sigma = 0.927 \text{ mho/m}$ ;  $\epsilon_r = 53.832$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

## DASY5 Configuration:

Probe: ES3DV3 - SN3221; ConvF(6.2, 6.2, 6.2); Calibrated: 1/9/2014;

Sensor-Surface: 4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn893; Calibrated: 12/25/2013

Phantom: SAM\_2with CRP v4.0; Type: QD000P40CC; Serial: TP:1548

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

GPRS 850/Back side Low/Area Scan (41x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 10.555 V/m; Power Drift = -0.07 dB


Maximum value of SAR (interpolated) = 0.699 W/kg

**GPRS 850/Back side Low/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.555 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.843 mW/g

SAR(1 g) = 0.658 mW/g; SAR(10 g) = 0.484 mW/g Maximum value of SAR (measured) = 0.697 W/kg





## **GPRS 850/Front side High**

**DUT: Mobile Phone; Type: OWN F1030** 

Communication System: GPRS(2slots); Communication System Band: GSM850; Frequency: 848.8 MHz;

Communication System PAR: 6.128 dB

Medium parameters used (interpolated): f = 848.8 MHz;  $\sigma = 0.951 \text{ mho/m}$ ;  $\epsilon_r = 53.603$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

## DASY5 Configuration:

Probe: ES3DV3 - SN3221; ConvF(6.2, 6.2, 6.2); Calibrated: 1/9/2014;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn893; Calibrated: 12/25/2013

Phantom: SAM\_2with CRP v4.0; Type: QD000P40CC; Serial: TP:1548

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

GPRS 850/Front side High/Area Scan (41x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 12.297 V/m; Power Drift = 0.01 dB


Maximum value of SAR (interpolated) = 0.821 W/kg

**GPRS 850/Front side High/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.297 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.998 mW/g

**SAR(1 g) = 0.780 mW/g; SAR(10 g) = 0.570 mW/g** Maximum value of SAR (measured) = 0.827 W/kg





#### **GPRS 850/Front side Mid**

**DUT: Mobile Phone; Type: OWN F1030** 

Communication System: GPRS(2slots); Communication System Band: GSM850; Frequency: 836.6

MHz; Communication System PAR: 6.128 dB

Medium parameters used (interpolated): f = 836.6 MHz;  $\sigma = 0.939 \text{ mho/m}$ ;  $\epsilon_r = 53.719$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

#### DASY5 Configuration:

Probe: ES3DV3 - SN3221; ConvF(6.2, 6.2, 6.2); Calibrated: 1/9/2014;

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn893; Calibrated: 12/25/2013

Phantom: SAM\_2with CRP v4.0; Type: QD000P40CC; Serial: TP:1548

• Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**GPRS 850/Front side Mid/Area Scan (41x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm Reference Value = 9.896 V/m; Power Drift = 0.04 dB


Maximum value of SAR (interpolated) = 0.545 W/kg

**GPRS 850/Front side Mid/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.896 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.656 mW/g

SAR(1 g) = 0.514 mW/g; SAR(10 g) = 0.377 mW/g Maximum value of SAR (measured) = 0.545 W/kg





#### **GPRS 850/Front side Low**

**DUT: Mobile Phone; Type: OWN F1030** 

Communication System: GPRS(2slots); Communication System Band: GSM850; Frequency: 824.2 MHz;

Communication System PAR: 6.128 dB

Medium parameters used (interpolated): f = 824.2 MHz;  $\sigma = 0.927 \text{ mho/m}$ ;  $\epsilon_r = 53.832$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

## DASY5 Configuration:

Probe: ES3DV3 - SN3221; ConvF(6.2, 6.2, 6.2); Calibrated: 1/9/2014;

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn893; Calibrated: 12/25/2013
- Phantom: SAM\_2with CRP v4.0; Type: QD000P40CC; Serial: TP:1548
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

GPRS 850/Front side Low/Area Scan (41x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 7.707 V/m; Power Drift = -0.01 dB


Maximum value of SAR (interpolated) = 0.333 W/kg

**GPRS 850/Front side Low/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.707 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.397 mW/g

SAR(1 g) = 0.313 mW/g; SAR(10 g) = 0.231 mW/g Maximum value of SAR (measured) = 0.329 W/kg





## PCS1900 LEFT/CHEEK-Low

**DUT: Mobile Phone; Type: OWN F1030** 

Communication System: Generic GSM; Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz);

Frequency: 1850.2 MHz; Communication System PAR: 9.191 dB

Medium parameters used: f = 1850.2 MHz;  $\sigma = 1.42 \text{ mho/m}$ ;  $\varepsilon_r = 39.87$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Left Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

## DASY5 Configuration:

Probe: ES3DV3 - SN3221; ConvF(5.4, 5.4, 5.4); Calibrated: 1/9/2014;

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn893; Calibrated: 12/25/2013
- Phantom: SAM\_1 with CRP v4.0; Type: QD000P40CC; Serial: TP:1586
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

PCS1900 LEFT/CHEEK-Low/Area Scan (41x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm Reference Value = 4.077 V/m; Power Drift = -0.17 dB


Maximum value of SAR (interpolated) = 0.190 W/kg

PCS1900 LEFT/CHEEK-Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 4.077 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 0.242 mW/g

SAR(1 g) = 0.159 mW/g; SAR(10 g) = 0.093 mW/g Maximum value of SAR (measured) = 0.163 W/kg







PCS1900 LEFT/CHEEK-Low- axis scan



#### PCS1900 LEFT/TILT-Low

**DUT: Mobile Phone; Type: OWN F1030** 

Communication System: Generic GSM; Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz);

Frequency: 1850.2 MHz; Communication System PAR: 9.191 dB

Medium parameters used: f = 1850.2 MHz;  $\sigma$  = 1.42 mho/m;  $\varepsilon_r$  = 39.87;  $\rho$  = 1000 kg/m<sup>3</sup>

Phantom section: Left Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

## DASY5 Configuration:

Probe: ES3DV3 - SN3221; ConvF(5.4, 5.4, 5.4); Calibrated: 1/9/2014;

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn893; Calibrated: 12/25/2013

Phantom: SAM\_1 with CRP v4.0; Type: QD000P40CC; Serial: TP:1586

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

PCS1900 LEFT/TILT-Low/Area Scan (41x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 5.307 V/m; Power Drift = -0.16 dB


Maximum value of SAR (interpolated) = 0.0998 W/kg

PCS1900 LEFT/TILT-Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.307 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 0.141 mW/g

**SAR(1 g) = 0.091 mW/g; SAR(10 g) = 0.055 mW/g** Maximum value of SAR (measured) = 0.0974 W/kg





#### PCS1900 RIGHT/CHEEK-Low

**DUT: Mobile Phone; Type: OWN F1030** 

Communication System: Generic GSM; Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz);

Frequency: 1850.2 MHz; Communication System PAR: 9.191 dB

Medium parameters used: f = 1850.2 MHz;  $\sigma$  = 1.42 mho/m;  $\varepsilon_r$  = 39.87;  $\rho$  = 1000 kg/m<sup>3</sup>

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

## DASY5 Configuration:

Probe: ES3DV3 - SN3221; ConvF(5.4, 5.4, 5.4); Calibrated: 1/9/2014;

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn893; Calibrated: 12/25/2013

Phantom: SAM\_1 with CRP v4.0; Type: QD000P40CC; Serial: TP:1586

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

PCS1900 RIGHT/CHEEK-Low/Area Scan (41x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm Reference Value = 4.774 V/m; Power Drift = 0.07 dB


Maximum value of SAR (interpolated) = 0.154 W/kg

PCS1900 RIGHT/CHEEK-Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.774 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.212 mW/g

SAR(1 g) = 0.140 mW/g; SAR(10 g) = 0.084 mW/g Maximum value of SAR (measured) = 0.147 W/kg





#### PCS1900 RIGHT/TILT-Low

**DUT: Mobile Phone; Type: OWN F1030** 

Communication System: Generic GSM; Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz);

Frequency: 1850.2 MHz; Communication System PAR: 9.191 dB

Medium parameters used: f = 1850.2 MHz;  $\sigma$  = 1.42 mho/m;  $\varepsilon_r$  = 39.87;  $\rho$  = 1000 kg/m<sup>3</sup>

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

## DASY5 Configuration:

Probe: ES3DV3 - SN3221; ConvF(5.4, 5.4, 5.4); Calibrated: 1/9/2014;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn893; Calibrated: 12/25/2013

Phantom: SAM\_1 with CRP v4.0; Type: QD000P40CC; Serial: TP:1586

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)


**PCS1900 RIGHT/TILT-Low/Area Scan (41x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm Reference Value = 6.875 V/m; Power Drift = 0.18 dB Maximum value of SAR (interpolated) = 0.101 W/kg

PCS1900 RIGHT/TILT-Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.875 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.128 mW/g

SAR(1 g) = 0.087 mW/g; SAR(10 g) = 0.054 mW/g Maximum value of SAR (measured) = 0.0923 W/kg





#### GPRS 1900/Back side Low

**DUT: Mobile Phone; Type: OWN F1030** 

Communication System: GPRS(3slots); Communication System Band: PCS 1900; Frequency: 1850.2

MHz; Communication System PAR: 4.44 dB

Medium parameters used (interpolated): f = 1850.2 MHz;  $\sigma = 1.525 \text{ mho/m}$ ;  $\varepsilon_r = 50.831$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

## DASY5 Configuration:

Probe: ES3DV3 - SN3221; ConvF(4.91, 4.91, 4.91); Calibrated: 1/9/2014;

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn893; Calibrated: 12/25/2013
- Phantom: SAM\_1 with CRP v4.0; Type: QD000P40CC; Serial: TP:1586
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

GPRS 1900/Back side Low/Area Scan (41x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 9.320 V/m; Power Drift = 0.07 dB


Maximum value of SAR (interpolated) = 0.594 W/kg

**GPRS 1900/Back side Low/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 9.320 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.854 mW/g

SAR(1 g) = 0.545 mW/g; SAR(10 g) = 0.337 mW/g Maximum value of SAR (measured) = 0.576 W/kg







GPRS 1900/Back side Low-axis scan



#### **GPRS 1900/Front side Low**

**DUT: Mobile Phone; Type: OWN F1030** 

Communication System: GPRS(3slots); Communication System Band: PCS 1900; Frequency: 1850.2

MHz; Communication System PAR: 4.44 dB

Medium parameters used (interpolated): f = 1850.2 MHz;  $\sigma = 1.525 \text{ mho/m}$ ;  $\varepsilon_r = 50.831$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

## DASY5 Configuration:

Probe: ES3DV3 - SN3221; ConvF(4.91, 4.91, 4.91); Calibrated: 1/9/2014;

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn893; Calibrated: 12/25/2013
- Phantom: SAM\_1 with CRP v4.0; Type: QD000P40CC; Serial: TP:1586
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

GPRS 1900/Front side Low/Area Scan (41x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 6.063 V/m; Power Drift = -0.12 dB


Maximum value of SAR (interpolated) = 0.240 W/kg

**GPRS 1900/Front side Low/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.063 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.348 mW/g

SAR(1 g) = 0.214 mW/g; SAR(10 g) = 0.126 mW/g Maximum value of SAR (measured) = 0.232 W/kg



No. 140612 Page 56 of 89

# **GCCT**

# **ANNEX D: Probe calibration report**

No. 140612 Page 57 of 89





In Collaboration with

S P @ A G

CALIBRATION LABORATORY



Add: No.52 Huayuanbei Road, Haidian District, Beijing, 100191, China Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504 Http://www.emcite.com

Client NCCT

Http://www.emcite.com

Certificate No: J14-2-0002

## CALIBRATION CERTIFICATE

Object ES3DV3 - SN:3221

Calibration Procedure(s) TMC-OS-E-02-195

Calibration Procedures for Dosimetric E-field Probes

Calibration date: January 09, 2014

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID#	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	101919	01-Jul-13 (TMC, No.JW13-044)	Jun-14
Power sensor NRP-Z91	101547	01-Jul-13 (TMC, No.JW13-044)	Jun-14
Power sensor NRP-Z91	101548	01-Jul-13 (TMC, No.JW13-044)	Jun-14
Reference10dBAttenuator	BT0520	12-Dec-12(TMC,No.JZ12-867)	Dec-14
Reference20dBAttenuator	BT0267	12-Dec-12(TMC,No.JZ12-866)	Dec-14
Reference Probe EX3DV4	SN 3846	03-Sep-13(SPEAG,No.EX3-3846_Sep13)	Sep-14
DAE4	SN 777	22-Feb-13 (SPEAG, DAE4-777_Feb13)	Feb -14
Secondary Standards	ID#	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
SignalGeneratorMG3700A	6201052605	01-Jul-13 (TMC, No.JW13-045)	Jun-14
Network Analyzer E5071C	MY46110673	15-Feb-13 (TMC, No.JZ13-781)	Feb-14
	Nama	Eupation	Cianatura

Name Function Signature

Calibrated by: Yu Zongying SAR Test Engineer

Reviewed by: Qi Dianyuan SAR Project Leader

Approved by: Lu Bingsong Deputy Director of the laboratory

Issued: January 10, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

No. 140612 Page 58 of 89





Add: No.52 Huayuanbei Road, Haidian District, Beijing, 100191, China Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504 E-mail: Info@emcite.com Http://www.emcite.com

Glossary:

TSL tissue simulating liquid
NORMx,y,z sensitivity in free space
ConvF sensitivity in TSL / NORMx,y,z
DCP diode compression point

CF crest factor (1/duty\_cycle) of the RF signal A,B,C,D modulation dependent linearization parameters

Polarization Φ rotation around probe axis

Polarization θ θ rotation around an axis that is in the plane normal to probe axis (at measurement center), i

θ=0 is normal to probe axis

Connector Angle information used in DASY system to align probe sensor X to the robot coordinate system Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300MHz to 3GHz)", February 2005

#### Methods Applied and Interpretation of Parameters:

- NORMx,y,z: Assessed for E-field polarization θ=0 (f≤900MHz in TEM-cell; f>1800MHz: waveguide). NORMx,y,z are only intermediate values, i.e., the uncertainties of NORMx,y,z does not effect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)x,y,z = NORMx,y,z\* frequency\_response (see Frequency Response Chart). This
  linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the
  frequency response is included in the stated uncertainty of ConvF.
- DCPx,y,z: DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics.
- Ax,y,z; Bx,y,z; Cx,y,z;VRx,y,z:A,B,C are numerical linearization parameters assessed based on the
  data of power sweep for specific modulation signal. The parameters do not depend on frequency nor
  media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for f≤800MHz) and inside waveguide using analytical field distributions based on power measurements for f >800MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty valued are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORMx,y,z\* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from±50MHz to±100MHz.
- Spherical isotropy (3D deviation from isotropy): in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle: The angle is assessed using the information gained by determining the NORMx (no uncertainty required).





# Probe ES3DV3

SN: 3221

Calibrated: January 09, 2014

Calibrated for DASY/EASY Systems

(Note: non-compatible with DASY2 system!)





Add: No.52 Huayuanbei Road, Haidian District, Beijing, 100191, China Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504 E-mail: Info@emcite.com Http://www.emcite.com

## DASY – Parameters of Probe: ES3DV3 - SN: 3221

## **Basic Calibration Parameters**

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm(µV/(V/m)²)A	1.04	1.30	1.03	±10.8%
DCP(mV) <sup>B</sup>	106.8	104.0	102.7	

## **Modulation Calibration Parameters**

UID	Communication System Name		A dB	B dBõV	С	D dB	VR mV	Unc <sup>E</sup> (k=2)
0 CW	0	X	0.0	0.0	1.0	0.00	244.0	±2.6%
		Y	0.0	0.0	1.0		270.1	
		Z	0.0	0.0	1.0		233.6	

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor k=2, which for a normal distribution Corresponds to a coverage probability of approximately 95%.

A The uncertainties of Norm X, Y, Z do not affect the E2-field uncertainty inside TSL (see Page 5 and Page 6).

<sup>&</sup>lt;sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>&</sup>lt;sup>E</sup> Uncertainly is determined using the max, deviation from linear response applying rectangular distribution and is expressed for the square of the field value.





Add: No.52 Huayuanbei Road, Haidian District, Beijing, 100191, China Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504 E-mail: Info@emcite.com Http://www.emcite.com

## DASY - Parameters of Probe: ES3DV3 - SN: 3221

## Calibration Parameter Determined in Head Tissue Simulating Media

f [MHz] <sup>C</sup>	Relative Permittivity F	Conductivity (S/m) <sup>F</sup>	ConvF X	ConvF Y	ConvF Z	Alpha <sup>G</sup>	Depth <sup>G</sup> (mm)	Unct. (k=2)
850	41.5	0.92	6.23	6.23	6.23	0.30	1.79	±12%
900	41.5	0.97	6.37	6.37	6.37	0.38	1.60	±12%
1750	40.1	1.37	5.44	5.44	5.44	0.52	1.46	±12%
1900	40.0	1.40	5.40	5.40	5.40	0.53	1.46	±12%
2000	40.0	1.40	5.32	5.32	5.32	0.52	1.52	±12%
2450	39.2	1.80	4.76	4.76	4.76	0.80	1.18	±12%

<sup>&</sup>lt;sup>c</sup> Frequency validity of ±100MHz only applies for DASY v4.4 and higher (Page 2), else it is restricted to ±50MHz. The uncertainty is the RSS of ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

FAt frequency below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ±10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ε and σ) is restricted to ±5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>&</sup>lt;sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for the frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.





Add: No.52 Huayuanbei Road, Haidian District, Beijing, 100191, China Tel: \*86-10-62304633-2079 Fax: \*86-10-62304633-2504 Http://www.emcite.com

## DASY – Parameters of Probe: ES3DV3 - SN: 3221

## Calibration Parameter Determined in Body Tissue Simulating Media

f [MHz] <sup>C</sup>	Relative Permittivity <sup>F</sup>	Conductivity (S/m) <sup>F</sup>	ConvF X	ConvF Y	ConvF Z	Alpha <sup>G</sup>	Depth <sup>G</sup> (mm)	Unct. (k=2)
850	55.2	0.99	6.20	6.20	6.20	0.45	1.51	±12%
900	55.0	1.05	6.16	6.16	6.16	0.51	1.41	±12%
1750	53.4	1.49	5.20	5.20	5.20	0.49	1.61	±12%
1900	53.3	1.52	4.91	4.91	4.91	0.49	1.65	±12%
2000	53.3	1.52	4.97	4.97	4.97	0.34	2.53	±12%
2450	52.7	1.95	4.48	4.48	4.48	0.84	1.19	±12%

<sup>&</sup>lt;sup>C</sup> Frequency validity of ±100MHz only applies for DASY v4.4 and higher (Page 2), else it is restricted to ±50MHz. The uncertainty is the RSS of ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

<sup>F</sup> At frequency below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ±10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ε and σ) is restricted to ±5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.


<sup>&</sup>lt;sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for the frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.





Add: No.52 Huayuanbei Road, Haidian District, Beijing, 100191, China Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504 E-mail: Info@emcite.com Http://www.emcite.com

# Frequency Response of E-Field (TEM-Cell: ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: ±7.5% (k=2)



E-mail: Info@emcite.com



## Receiving Pattern (Φ), θ=0°


## f=600 MHz, TEM f=1800 MHz, R22 10 0.5 Error[dB] 0.0 -0.5 -10 -150 -100 100 150 - 100MHz 600MHz 1800MHz 2500MHz

Uncertainty of Axial Isotropy Assessment: ±0.9% (k=2)





## Dynamic Range f(SAR<sub>head</sub>) (TEM cell, f = 900 MHz)








Add: No.52 Huayuanbel Road, Haidian District, Beijing, 100191, China Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504


## **Conversion Factor Assessment**

## f=900 MHz, WGLS R9(H\_convF)

## f=1750 MHz, WGLS R22(H\_convF)



## **Deviation from Isotropy in Liquid**



Uncertainty of Spherical Isotropy Assessment: ±2.8% (K=2)





Add: No.52 Huayuanbei Road, Haidian District, Beijing, 100191, China Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504 Http://www.emcite.com

## DASY - Parameters of Probe: ES3DV3 - SN: 3221

## Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	36.2
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disable
Probe Overall Length	337mm
Probe Body Diameter	10mm
Tip Length	10mm
Tip Diameter	4mm
Probe Tip to Sensor X Calibration Point	2mm
Probe Tip to Sensor Y Calibration Point	2mm
Probe Tip to Sensor Z Calibration Point	2mm
Recommended Measurement Distance from Surface	3mm

No. 140612 Page 68 of 89

# **GCCT**

# **ANNEX E: Dipole calibration report**

No. 140612 Page 69 of 89



Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland





C

S

Accreditation No.: SCS 108

Schweizerischer Kalibrierdienst Service suisse d'étalonnage Servizio svizzero di taratura Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Client

GCCT (Auden)

Certificate No: D835V2-4d150\_Mar13

## **CALIBRATION CERTIFICATE**

Object

D835V2 - SN: 4d150

Calibration procedure(s)

QA CAL-05.v9

Calibration procedure for dipole validation kits above 700 MHz

Calibration date:

March 18, 2013

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).

The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cai Date (Certificate No.)	Scheduled Calibration
Power mater EPM-442A	GB37480704	01-Nov-12 (No. 217-01640)	Oct-13
Power sensor HP 8481A	US37292783	01-Nov-12 (No. 217-01640)	Oct-13
Reference 20 dB Attenuator	SN: 5058 (20k)	27-Mar-12 (No. 217-01530)	Apr-13
Type-N mismatch combination	SN: 5047.3 / 06327	27-Mar-12 (No. 217-01533)	Apr-13
Reference Probe ES3DV3	SN: 3205	28-Dec-12 (No. ES3-3205_Dec12)	Dec-13
DAE4	SN: 601	27-Jun-12 (No. DAE4-601_Jun12)	Jun-13
Secondary Standards	ID#	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-11)	In house check: Oct-13
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-11)	In house check: Oct-13
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-12)	In house check: Oct-13

Name
Calibrated by: Leff Klysner

Function Laboratory Technician

and with

Approved by:

Katja Pokovic Technical Manager

issued: March 19, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory

## No. 140612 Page 70 of 89

## **GCCT**

Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland





S Schweizerischer Kalibrierdienst
Service suisse d'étalonnage
Servizio svizzero di taratura
S swiss Calibration Service

Accreditation No.: SCS 108

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

#### Glossary:

TSL

tissue simulating liquid

ConvF N/A sensitivity in TSL / NORM x,y,z not applicable or not measured

## Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

## Additional Documentation:

d) DASY4/5 System Handbook

#### Methods Applied and Interpretation of Parameters:

- Measurement Conditions: Further details are available from the Validation Report at the end
  of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL: The dipole is mounted with the spacer to position its feed
  point exactly below the center marking of the flat phantom section, with the arms oriented
  parallel to the body axis.
- Feed Point Impedance and Return Loss: These parameters are measured with the dipole
  positioned under the liquid filled phantom. The impedance stated is transformed from the
  measurement at the SMA connector to the feed point. The Return Loss ensures low
  reflected power. No uncertainty required.
- Electrical Delay: One-way delay between the SMA connector and the antenna feed point.
   No uncertainty required.
- SAR measured: SAR measured at the stated antenna input power.
- SAR normalized: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.



## Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.5
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz ± 1 MHz	

## **Head TSL parameters**

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	40.9 ± 6 %	0.94 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	****	***

## SAR result with Head TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.47 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	9.53 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.60 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	6.22 W/kg ± 16.5 % (k=2)

## **Body TSL parameters**

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.2	0.97 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	54.1 ± 6 %	1.02 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C		

## SAR result with Body TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.52 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	9.66 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.65 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	6.39 W/kg ± 16.5 % (k=2)

No. 140612 Page 72 of 89



## Appendix

## Antenna Parameters with Head TSL

Impedance, transformed to feed point	51.6 Ω - 2.8 jΩ	
Return Loss	- 30.0 dB	

## Antenna Parameters with Body TSL

Impedance, transformed to feed point	47.1 Ω - 5.2 jΩ
Return Loss	- 24.2 dB

## General Antenna Parameters and Design

Electrical Delay (one direction)	1.395 ns

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

#### Additional EUT Data

Manufactured by	SPEAG
Manufactured on	March 27, 2012



#### DASY5 Validation Report for Head TSL

Date: 18.03.2013

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d150

Communication System: CW; Frequency: 835 MHz

Medium parameters used: f = 835 MHz;  $\sigma = 0.94 \text{ S/m}$ ;  $\varepsilon_r = 40.9$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

#### DASY52 Configuration:

Probe: ES3DV3 - SN3205; ConvF(6.05, 6.05, 6.05); Calibrated: 28.12.2012;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn601; Calibrated: 27.06.2012

Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001

DASY52 52.8.5(1059); SEMCAD X 14.6.8(7028)

## Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 57.088 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 3.72 W/kg

SAR(1 g) = 2.47 W/kg; SAR(10 g) = 1.6 W/kg


Maximum value of SAR (measured) = 2.89 W/kg



0 dB = 2.89 W/kg = 4.61 dBW/kg



## Impedance Measurement Plot for Head TSL





## DASY5 Validation Report for Body TSL

Date: 18.03.2013

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d150

Communication System: CW; Frequency: 835 MHz

Medium parameters used: f = 835 MHz;  $\sigma = 1.02 \text{ S/m}$ ;  $\epsilon_r = 54.1$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

#### DASY52 Configuration:

Probe: ES3DV3 - SN3205; ConvF(6.04, 6.04, 6.04); Calibrated: 28.12.2012;

· Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn601; Calibrated: 27.06.2012

Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001

DASY52 52.8.5(1059); SEMCAD X 14.6.8(7028)

## Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 55.351 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 3.71 W/kg

SAR(1 g) = 2.52 W/kg; SAR(10 g) = 1.65 W/kg


Maximum value of SAR (measured) = 2.91 W/kg



0 dB = 2.91 W/kg = 4.64 dBW/kg



## Impedance Measurement Plot for Body TSL



No. 140612 Page 77 of 89

## **GCCT**

Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland





S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Client

GCCT (Auden)

Accreditation No.: SCS 108

Certificate No: D1900V2-5d070\_Oct12

## **CALIBRATION CERTIFICATE**

Object

D1900V2 - SN: 5d070

Calibration procedure(s)

QA CAL-05.v8

Calibration procedure for dipole validation kits above 700 MHz

Calibration date:

October 01, 2012

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID#	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	05-Oct-11 (No. 217-01451)	Oct-12
Power sensor HP 8481A	US37292783	05-Oct-11 (No. 217-01451)	Oct-12
Reference 20 dB Attenuator	SN: 5058 (20k)	27-Mar-12 (No. 217-01530)	Apr-13
Type-N mismatch combination	SN: 5047.2 / 06327	27-Mar-12 (No. 217-01533)	Apr-13
Reference Probe ES3DV3	SN: 3205	30-Dec-11 (No. ES3-3205_Dec11)	Dec-12
DAE4	SN: 601	27-Jun-12 (No. DAE4-601_Jun12)	Jun-13
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-11)	In house check: Oct-13
RF generator R&S SMT-05	100005	04-Aug-99 (in house check Oct-11)	In house check: Oct-13
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-11)	In house check: Oct-12
	Name	Function	Signature
Calibrated by:	Israe El-Naouq	Laboratory Technician	Osraer Ct Thous
Approved by:	Katja Pokovic	Technical Manager	Buc

Issued: October 2, 2012

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Calibration Laboratory of Schmid & Partner

Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland





C

S Schweizerischer Kalibrierdienst

Service suisse d'étalonnage Servizio svizzero di taratura

S Swiss Calibration Service

Accreditation No.: SCS 108

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

#### Glossary:

TSL

tissue simulating liquid

ConvF

sensitivity in TSL / NORM x,y,z

N/A

not applicable or not measured

#### Calibration is Performed According to the Following Standards:

 a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003

 b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

c) Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

#### Additional Documentation:

d) DASY4/5 System Handbook

#### Methods Applied and Interpretation of Parameters:

- Measurement Conditions: Further details are available from the Validation Report at the end
  of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL: The dipole is mounted with the spacer to position its feed
  point exactly below the center marking of the flat phantom section, with the arms oriented
  parallel to the body axis.
- Feed Point Impedance and Return Loss: These parameters are measured with the dipole
  positioned under the liquid filled phantom. The impedance stated is transformed from the
  measurement at the SMA connector to the feed point. The Return Loss ensures low
  reflected power. No uncertainty required.
- Electrical Delay: One-way delay between the SMA connector and the antenna feed point.
   No uncertainty required.
- · SAR measured: SAR measured at the stated antenna input power.
- SAR normalized: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.



#### Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.2
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1900 MHz ± 1 MHz	

## Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.0	1.40 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	40.6 ± 6 %	1.37 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C		

#### SAR result with Head TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	9.89 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	40.2 mW/g ± 17.0 % (k=2)

SAR averaged over 10 cm3 (10 g) of Head TSL	condition	
SAR measured	250 mW input power	5.22 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	21.1 mW/g ± 16.5 % (k=2)

## **Body TSL parameters**

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	53,3	1.52 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) "C	52.5 ± 6 %	1.54 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	- Section 1	

## SAR result with Body TSL

SAR averaged over 1 cm3 (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	10.3 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	40.7 mW / g ± 17.0 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.47 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	21.7 mW / g ± 16.5 % (k=2)



#### Appendix

#### Antenna Parameters with Head TSL

Impedance, transformed to feed point	52.7 $\Omega$ + 4.7 $j\Omega$
Return Loss	- 25.5 dB

#### Antenna Parameters with Body TSL

Impedance, transformed to feed point	$48.5 \Omega + 5.8 J\Omega$
Return Loss	- 24.4 dB

#### General Antenna Parameters and Design

ADDITION OF THE PROPERTY OF THE PROPERTY OF	Anning and Control
Electrical Delay (one direction)	1,196 ns

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

#### Additional EUT Data

Manufactured by	SPEAG	
Manufactured on	January 24, 2006	



#### DASY5 Validation Report for Head TSL

Date: 01.10.2012

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d070

Communication System: CW; Frequency: 1900 MHz

Medium parameters used: f = 1900 MHz;  $\sigma = 1.37 \text{ mho/m}$ ;  $\varepsilon_r = 40.6$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

#### DASY52 Configuration:

Probe: ES3DV3 - SN3205; ConvF(5.01, 5.01, 5.01); Calibrated: 30.12.2011;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn601; Calibrated: 27.06.2012

Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001

DASY52 52.8.2(969); SEMCAD X 14.6.6(6824)

#### Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 95.678 V/m; Power Drift = 0.07 dB Peak SAR (extrapolated) = 17.559 mW/g

SAR(1 g) = 9.89 mW/g; SAR(10 g) = 5.22 mW/g


Maximum value of SAR (measured) = 12.2 W/kg



0 dB = 12.2 W/kg = 21.73 dB W/kg



## Impedance Measurement Plot for Head TSL





Date: 01.10.2012

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d070

Communication System: CW; Frequency: 1900 MHz

Medium parameters used: f = 1900 MHz;  $\sigma = 1.54 \text{ mho/m}$ ;  $\varepsilon_r = 52.5$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/JEC/ANSI C63.19-2007)

#### DASY52 Configuration:

Probe: ES3DV3 - SN3205; ConvF(4.62, 4.62, 4.62); Calibrated: 30.12.2011;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn601; Calibrated: 27.06.2012

Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002

DASY52 52.8.2(969); SEMCAD X 14.6.6(6824)

#### Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 95.678 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 18.097 mW/g


SAR(1 g) = 10.3 mW/g; SAR(10 g) = 5.47 mW/g

Maximum value of SAR (measured) = 13.0 W/kg





## Impedance Measurement Plot for Body TSL



No. 140612 Page 85 of 89

# **GCCT**

# **ANNEX F: DAE calibration report**

No. 140612 Page 86 of 89

## **GCCT**



n Collaboration with



Add: No.52 Huayuanbei Road, Haidian District, Beijing, 100191, China Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504 E-mail: Info@emcite.com Http://www.emcite.com





Client :

NCCT

Certificate No: J13-2-3532

#### CALIBRATION CERTIFICATE

Object DAE4 - SN: 893

Calibration Procedure(s) TMC-OS-E-01-198

Calibration Procedure for the Data Acquisition Electronics

(DAEx)

Calibration date: December 25, 2013

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

ID# Cal Date(Calibrated by, Certificate No.)		Scheduled Calibration	
1971018	01-July-13 (TMC, No:JW13-049)	July-14	

Name

Function

Signature

Calibrated by:

Yu Zongying

SAR Test Engineer

Reviewed by:

Qi Dianyuan

SAR Project Leader

Approved by:

Lu Bingsong

Deputy Director of the laboratory

The way

Issued. December 26, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratoty.

No. 140612 Page 87 of 89





Add: No.52 Huayuanbei Road, Haidian District, Beijing, 100191, China Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504 Http://www.emcite.com

Glossary:

DAE

data acquisition electronics

Connector angle

information used in DASY system to align probe sensor X

to the robot coordinate system.

## Methods Applied and Interpretation of Parameters:

- DC Voltage Measurement: Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- Connector angle: The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The report provide only calibration results for DAE, it does not contain other performance test results.

No. 140612 Page 88 of 89





In Collaboration with

S P E A G
CALIBRATION LABORATORY

Add: No.52 Huayuanbei Road, Haidian District, Beijing, 100191, China Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504 Http://www.emcite.com

## DC Voltage Measurement

A/D - Converter Resolution nominal

Calibration Factors	x	Y	z	
High Range	406.166 ± 0.15% (k=2)	406.033 ± 0.15% (k=2)	405.072 ± 0.15% (k=2)	
Low Range	4.00811 ± 0.7% (k=2)	4.02146 ± 0.7% (k=2)	3.98338 ± 0.7% (k=2)	

## **Connector Angle**

Connector Angle to be used in DASY system	176° ± 1 °
Connector Angle to be used in DASY system	176° ± 1 °

No. 140612 Page 89 of 89



## **ANNEX G: Dipole Annual Check Result**

Per KDB 450824 Dipole SAR Validation Verification, GCCT Lab has adopted 3 years calibration intervals. On annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

- 1. There is no physical damage on the dipole;
- 2. System validation with specific dipole is within 10% of calibrated value;
- 3. Return-loss is within 20% of calibrated measurement;
- 4. Impedance is within  $5\Omega$  of calibrated measurement.

Date: June 17, 2014

Dipole	Liquid Type	Return-loss ( dB )		Impedance			
		Target Value	Measured Value	Deviation (%)	Target Value	Measured Value	Deviation ( $\Omega$ )
D835V2	Head	-30	-30.72	2.40	51.6Ω-2.8jΩ	50.5Ω-3.4 jΩ	1.1Ω+0.6jΩ
	Body	-24.2	-25.27	4.42	47.1Ω-5.2jΩ	46.9Ω-3.5 jΩ	0.2Ω-1.7jΩ
D1900V2	Head	-25.5	-22.78	-10.67	52.7Ω+4.7jΩ	49.9Ω+2.2jΩ	2.8Ω+2.5jΩ
	Body	-24.4	-26.94	10.41	48.5Ω+5.8jΩ	47.3Ω+3.7jΩ	1.2Ω+2.1jΩ