

Page 1 of 28

APPLICATION CERTIFICATION On Behalf of Carewell Electric Technology (Zhongshan) Co., Ltd.

REMOTE CONTROL Model No.: FAN61T-4SP1

FCC ID: 2AAZPFAN61T4SP1

Prepared for : Carewell Electric Technology (Zhongshan) Co., Ltd.

Address : Torch Development Zone, No.2, Ouya Road, Zhongshan,

Guangdong, China

Prepared by : ACCURATE TECHNOLOGY CO., LTD

Address : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.

Science & Industry Park, Nanshan, Shenzhen, Guangdong

P.R. China

Tel: (0755) 26503290 Fax: (0755) 26503396

Report Number : ATE20162255

Date of Test : Oct. 27, 2016-Nov. 24, 2016

Date of Report : Nov. 24,2015






TABLE OF CONTENTS

Γ	Descrij	ption	Page
т	Sest R	eport Certification	
1.		ENERAL INFORMATION	
	1.1.	Description of Device (EUT)	
	1.2.	Description of Test Facility	
_	1.3.	Measurement Uncertainty	
2.		EASURING DEVICE AND TEST EQUIPMENT	
3.	SU	MMARY OF TEST RESULTS	
4.	TH	IE FIELD STRENGTH OF RADIATION EMISSION	
	4.1.	Block Diagram of Test Setup	
	4.2.	The Field Strength of Radiation Emission Measurement Limits	9
	4.3.	Configuration of EUT on Measurement	10
	4.4.	Operating Condition of EUT	
	4.5.	Test Procedure	
	4.6.	The Field Strength of Radiation Emission Measurement Results	
5.		DB OCCUPIED BANDWIDTH	
	5.1.	Block Diagram of Test Setup	
	5.2.	The Bandwidth of Emission Limit According To FCC Part 15 Section 15.231(c)	
	5.3.	EUT Configuration on Measurement	
	5.4.	Operating Condition of EUT	
	5.5. 5.6.	Test Procedure	
_			
6.		ELEASE TIME MEASUREMENT	
	6.1.	Block Diagram of Test Setup	
	6.2. 6.3.	Release Time Measurement According To FCC Part 15 Section 15.231(a) EUT Configuration on Measurement	
	6.4.	Operating Condition of EUT	
	6.5.	Test Procedure	
	6.6.	Measurement Result	
7.	ΑV	VERAGE FACTOR MEASUREMENT	
· •	7.1.	Block Diagram of Test Setup	
	7.2.	Average factor Measurement according to ANSI C63.10-2013	13
	7.3.	EUT Configuration on Measurement	
	7.4.	Operating Condition of EUT	
	7.5.	Test Procedure	
	7.6.	Measurement Result	18
8.	AN	TENNA REQUIREMENT	19
	8.1.	The Requirement	19
	8.2.	Antenna Construction	



Page 3 of 28

Test Report Certification

Applicant : Carewell Electric Technology (Zhongshan) Co., Ltd.

Manufacturer : Carewell Electric Technology (Zhongshan) Co., Ltd.

EUT Description: **REMOTE CONTROL**

(A) MODEL NO.: FAN61T-4SP1

(B) SERIAL NO.: N/A

(C) POWER SUPPLY: DC 3V (Battery)

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.231a ANSI C63.10-2013

The device described above is tested by ACCURATE TECHNOLOGY CO., LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.231a. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO., LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO., LTD.

Date of Test:	Oct. 27, 2016-Nov. 24, 2016
Date of Report :	Nov. 24, 2016
Prepared by :	7 in Zhang
	(Tim.zhang, Engineer)
Approved & Authorized Signer :	Lemb
	(Sean Liu, Manager)





Page 4 of 28

1. GENERAL INFORMATION

1.1.Description of Device (EUT)

EUT : REMOTE CONTROL

Model Number : FAN61T-4SP1

Power Supply : DC 3V (powered by battery)

Modulation: : ASK

Operation Frequency : 315MHz

: PCB antenna Antenna type

Antenna gain : 0dBi

: Carewell Electric Technology (Zhongshan) Co., Ltd. **Applicant** Address Torch Development Zone, No.2, Ouya Road, Zhongshan,

Guangdong, China

Manufacturer Carewell Electric Technology (Zhongshan) Co., Ltd.

: Oct. 27, 2016-Nov. 24, 2016

Address Torch Development Zone, No.2, Ouya Road, Zhongshan,

Guangdong, China

: Oct. 27, 2016

Date of sample

Date of Test

received



Page 5 of 28

1.2.Description of Test Facility

EMC Lab : Accredited by TUV Rheinland Shenzhen

Listed by FCC

The Registration Number is 752051

Listed by Industry Canada

The Registration Number is 5077A-2

Accredited by China National Accreditation Committee

for Laboratories

The Certificate Registration Number is L3193

Name of Firm : ACCURATE TECHNOLOGY CO., LTD

Site Location : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.

Science & Industry Park, Nanshan, Shenzhen, Guangdong

P.R. China

1.3. Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty = 3.08dB, k=2


(9kHz-30MHz)

Radiated emission expanded uncertainty = 4.42dB, k=2

(30MHz-1000MHz)

Radiated emission expanded uncertainty = 4.06dB, k=2

(Above 1GHz)





2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Туре	S/N	Calibrated dates	Cal. Interval
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 09, 2016	One Year
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 09, 2016	One Year
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 09, 2016	One Year
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 09, 2016	One Year
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 14, 2016	One Year
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 14, 2016	One Year
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 14, 2016	One Year
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1067	Jan. 14, 2016	One Year
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 09, 2016	One Year
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 09, 2016	One Year
Highpass Filter	Wainwright Instruments	WHKX3.6/18 G-10SS	N/A	Jan. 09, 2016	One Year
Band Reject Filter	Wainwright Instruments	WRCG2400/2 485-2375/2510 -60/11SS	N/A	Jan. 09, 2016	One Year



Page 7 of 28

3. SUMMARY OF TEST RESULTS


FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission	N/A
Section 15.231(b)	Radiated Emission	Compliant
Section 15.231(c)	20dB Bandwidth	Compliant
Section 15.231(a)(1)	Release Time Measurement	Compliant
Section 15.203	Antenna Requirement	Compliant

The product is a manually operated transmitter.

Section 15.231 (a) (2), (3), (4) and (5) are not applicable.

Note: The power supply mode of the EUT is DC 3V, According to the FCC standard requirements, conducted emission is not applicable

All normal using modes of the normal function were tested but only the worst test data of the worst mode is recorded by this report.





4. THE FIELD STRENGTH OF RADIATION EMISSION

4.1.Block Diagram of Test Setup


4.1.1.Block diagram of connection between the EUT and simulators




(EUT: REMOTE CONTROL)

4.1.2.Semi-Anechoic Chamber Test Setup Diagram

(A)Radiated Emission Test Set-Up, Frequency below 30MHz



(B)Radiated Emission Test Set-Up, Frequency 30-1000MHz






ATC

Page 9 of 28

(C) Radiated Emission Test Set-Up, Frequency above 1GHz



GROUND PLANE
(EUT: REMOTE CONTROL)

4.2. The Field Strength of Radiation Emission Measurement Limits

4.2.1. Radiation Emission Measurement Limits According to FCC Part 15 Section 15.231(b)

Frequency Range of	Field Strength of Fundamental Emission	Field Strength of Spurious Emission
Fundamental	[Average]	[Average]
[MHz]	$[\mu V/m]$	[µV/m]
40.66-40.70	2250	225
70-130	1250	125
130-174	1250-3750	125-375
174-260	3750	375
260-470	3750-12500	375-1250
Above 470	12500	1250

Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, uV/m at 3 meters = 56.81818(F) - 6136.3636; for the band 260-470 MHz, uV/m at 3 meters = 41.6667(F) - 7083.3333. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.

4.2.2. Restricted Band Radiation Emission Measurement Limits According to FCC part 15 Section 15.205 and Section15.209.



Page 10 of 28

4.3. Configuration of EUT on Measurement

The following equipment is installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.3.1. REMOTE CONTROL (EUT)

Model Number : FAN61T-4SP1

Serial Number : N/A

Manufacturer : Carewell Electric Technology (Zhongshan) Co., Ltd.

4.4. Operating Condition of EUT

4.4.1. Setup the EUT and simulator as shown as Section 4.1.

4.4.2. Turn on the power of all equipment.

4.4.3. Let the EUT work in TX mode measure it.

4.5.Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground(Below 1GHz). The EUT and its simulators are placed on a turntable, which is 1.5 meter high above ground(Above 1GHz). The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI C63.10:2013 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

The bandwidth of test receiver is set at 120 kHz in 30-1000 MHz, and 1 MHz in 1000-4000 MHz.

The frequency range from 30 MHz to 4000 MHz is checked.



Report No.: ATE20162255 Page 11 of 28

4.6. The Field Strength of Radiation Emission Measurement Results **PASS.**

Note: The radiation emissions from 9KHz-30MHz are not reported, because the test values lower than the limits of 20dB.

EUT:	REMOTE CONTROL		
Model No.:	FAN61T-4SP1	Power Supply:	DC 3V
Test Mode:	TX	Test Engineer:	Star

Frequency (MHz)	Reading (dBµV/m)	Factor Corr.	Average Factor	$Result(dB\mu V/m) Limit(dB\mu V/m)$		Margi	n(dB)	Polarization		
	PEAK	(dB)	(dB)	AV	PEAK	AV	PEAK	AV	PEAK	
315.06	92.72	-16.05	-7.03	69.64	76.67	75.62	95.62	-5.92	-18.95	
630.12	64.21	-9.21	-7.03	47.97	55.00	55.62	75.62	-7.65	-20.62	
945.18	53.72	-3.56	-7.03	43.13	50.16	55.62	75.62	-12.49	-25.46	Horizontal
1260.25	45.67	-5.83	-7.03	32.81	39.84	55.62	75.62	-22.81	-35.78	
1890.65	39.94	-3.70	-7.03	29.21	36.24	55.62	75.62	-26.41	-39.38	
315.06	78.22	-16.05	-7.03	55.14	62.17	75.62	95.62	-20.48	-33.45	
630.12	63.68	-9.21	-7.03	47.44	54.47	55.62	75.62	-8.18	-21.15	
945.18	51.09	-3.56	-7.03	40.50	47.53	55.62	75.62	-15.12	-28.09	Vertical
1260.25	40.11	-5.83	-7.03	27.25	34.24	55.62	75.62	-28.37	-41.34	
1890.65	35.93	-3.70	-7.03	25.20	32.23	55.62	75.62	-30.42	-43.39	

Note:

- 1. Emissions attenuated more than 20 dB below the permissible value are not reported.
- 2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

Where Corrected Factor = Antenna Factor + Cable Loss + High Pass Filter Loss - Amplifier Gain

- 3. FCC Limit for Average Measurement = $41.6667(315)-7083.3333 = 6041.6772 \,\mu\text{V/m} = 75.62 \,\mu\text{V/m}$
- 4. The spectral diagrams in appendix I display the measurement of peak values.
- 5. Average value= PK value + Average Factor (duty factor)
- 6. If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.
- 7. The EUT is tested radiation emission in three axes(X,Y,Z). The worst emissions are reported in three axes.



Page 12 of 28

8. Pulse Desensitization Correction Factor

Pulse Width (PW) = 0.38ms

2/PW = 2/0.38ms = 5.26kHz

RBW (100 kHz) > 2/PW (5.26 kHz)

Therefore PDCF is not needed



Page 13 of 28

5. 20DB OCCUPIED BANDWIDTH

5.1.Block Diagram of Test Setup



(EUT: REMOTE CONTROL)

5.2. The Bandwidth of Emission Limit According To FCC Part 15 Section

15.231(c)

The bandwidth of emission shall be no wider than 0.25% of the center frequency. Therefore, the bandwidth of the emission limit is $315 \text{ MHz} \times 0.25\% = 787.5 \text{ kHz}$. Bandwidth is determined at the two points 20 dB down from the top of modulated carrier.

5.3.EUT Configuration on Measurement

The following equipment are installed on the bandwidth of emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.3.1.REMOTE CONTROL (EUT)


Model Number : FAN61T-4SP1

Serial Number : N/A

Manufacturer : Carewell Electric Technology (Zhongshan) Co., Ltd.

5.4. Operating Condition of EUT

- 5.4.1. Setup the EUT and simulator as shown as Section 5.1.
- 5.4.2. Turn on the power of all equipment.
- 5.4.3.Let the EUT work in TX mode measure it.





5.5.Test Procedure

- 5.5.1.Set SPA Center Frequency = Fundamental frequency, RBW = 10 kHz, VBW = 30 kHz, Span = 1MHz.
- 5.5.2.Set SPA Max hold, Mark peak, -20 dB.

5.6.Measurement Result

The EUT does meet the FCC requirement.

-20 dB bandwidth =60 kHz <787.5 kHz.


The spectral diagrams in appendix I.



Page 15 of 28

6. RELEASE TIME MEASUREMENT

6.1.Block Diagram of Test Setup



(EUT: REMOTE CONTROL)

6.2. Release Time Measurement According To FCC Part 15 Section 15.231(a)

Section 15.231(a) (1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

6.3.EUT Configuration on Measurement


The following equipment are installed on Release Time Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.3.1. REMOTE CONTROL (EUT)

Model Number : FAN61T-4SP1

Serial Number : N/A

Manufacturer : Carewell Electric Technology (Zhongshan) Co., Ltd.





6.4. Operating Condition of EUT

- 6.4.1. Setup the EUT and simulator as shown as Section 6.1.
- 6.4.2. Turn on the power of all equipment.
- 6.4.3.Let the EUT work in TX mode measure it.

6.5.Test Procedure

- 6.5.1.Set SPA Center Frequency = Fundamental frequency, RBW = 100 kHz, VBW = 300 kHz, Span = 0 Hz. Sweep time = 10 s.
- 6.5.2.Set EUT as normal operation and press Transmitter button.
- 6.5.3.Set SPA View. Delta Mark time.

6.6. Measurement Result

The release time less than 5 seconds.

Release Time = 3.18s

The spectral diagrams in appendix I.



Page 17 of 28

7. AVERAGE FACTOR MEASUREMENT

7.1.Block Diagram of Test Setup



(EUT: REMOTE CONTROL)

7.2. Average factor Measurement according to ANSI C63.10-2013

ANSI C63.10-2013 Section 7.5 Unless otherwise specified, when the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 s (100 ms). In cases where the pulse train exceeds 0.1 s, the measured field strength shall be determined during a 0.1 s interval.64 The following procedure is an example of how the average value may be determined. The average field strength may be found by measuring the peak pulse amplitude (in log equivalent units) and determining the duty cycle correction factor (in dB) associated with the pulse modulation as shown in Equation (10):

Average factor in $dB = 20 \log (duty \text{ cycle})$

7.3.EUT Configuration on Measurement

The following equipment are installed on average factor Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.3.1. REMOTE CONTROL

Model Number : FAN61T-4SP1

Serial Number : N/A

Manufacturer : Carewell Electric Technology (Zhongshan) Co., Ltd.



Page 18 of 28

7.4. Operating Condition of EUT

- 7.4.1. Setup the EUT and simulator as shown as Section 7.1.
- 7.4.2. Turn on the power of all equipment.
- 7.4.3.Let the EUT work in TX mode measure it.

7.5.Test Procedure

- 7.5.1.The time period over which the duty cycle is measured is 100 milliseconds, or the repetition cycle, whichever is a shorter time frame. The worst case (highest percentage on) duty cycle is used for the calculation.
- 7.5.2.Set SPA Center Frequency = Fundamental frequency, RBW = 100 kHz, VBW = 300 kHz, Span = 0 Hz.
- 7.5.3.Set EUT as normal operation.
- 7.5.4.Set SPA View. Delta Mark time.

7.6. Measurement Result

The duty cycle is simply the on time divided by the period:

The duration of one cycle = 34.3ms

Effective period of the cycle = $(0.68 \times 18) + (0.38 \times 8)$ ms = 15.28 ms

DC =15.28ms/34. 3ms=0.445

Therefore, the average factor is found by 20log0.445= -7.03dB

The spectral diagrams in appendix I.

Page 19 of 28




8. ANTENNA REQUIREMENT

8.1. The Requirement


According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2. Antenna Construction

Device is equipped with permanent attached antenna, which isn't displaced by other antenna. The Antenna gain of EUT is 0dBi. Therefore, the equipment complies with the antenna requirement of Section 15.203.




Antenna





APPENDIX I (Test Curves)



Site: 1# Chamber Tel:+86-0755-26503290

Fax:+86-0755-26503396





Job No.: DING #2828

ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd, Science & Industry Park,Nanshan Shenzhen,P.R.China

Polarization: Horizontal

Distance: 3m

Standard: FCC 15.231a 3M Radiated Power Source: DC 3V Test item: Radiation Test Date: 16/11/10/


Temp.(C)/Hum.(%) 25 C / 55 % Time: 8/56/39 EUT: REMOTE CONTROL Engineer Signature: DING

Mode: TX 315MHz


Model: FAN61T-4SP1

Manufacturer: CAREWELL

Note: Report NO.:ATE20162255



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	315.0601	92.72	-16.05	76.67			peak			
2	442.5722	32.77	-12.07	20.70	46.00	-25.30	QP			
3	544.5202	31.71	-9.83	21.88	46.00	-24.12	QP			
4	630.1205	64.21	-9.21	55.00			peak			
5	771.0475	32.52	-4.73	27.79	46.00	-18.21	QP			
6	945.1839	53.72	-3.56	50.16			peak			



Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396





ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd, Science & Industry Park,Nanshan Shenzhen,P.R.China

Polarization: Vertical

Power Source: DC 3V

Date: 16/11/10/ Time: 8/58/01

Engineer Signature: DING

Distance: 3m

Job No.: DING #2829

Standard: FCC 15.231a 3M Radiated


Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: REMOTE CONTROL

Mode: TX 315MHz


Model: FAN61T-4SP1

Manufacturer: CAREWELL

Note: Report NO.:ATE20162255



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	315.0601	78.22	-16.05	62.17			peak			
2	391.3601	33.62	-13.12	20.50	46.00	-25.50	QP			
3	514.7533	34.89	-10.55	24.34	46.00	-21.66	QP			
4	630.1205	63.68	-9.21	54.47			peak			
5	844.8028	30.94	-3.33	27.61	46.00	-18.39	QP			
6	945.1839	51.09	-3.56	47.53			peak			







ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd, Science & Industry Park,Nanshan Shenzhen,P.R.China Site: 1# Chamber Tel:+86-0755-26503290 Fax:+86-0755-26503396

Job No.: DING #2831

Standard: FCC 15.231a 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 % EUT: REMOTE CONTROL

Mode: TX 315MHz

Model: FAN61T-4SP1

Manufacturer: CAREWELL


Note: Report NO.:ATE20162255

Polarization: Horizontal Power Source: DC 3V


Date: 16/11/10/ Time: 9/04/11

Engineer Signature: DING

Distance: 3m



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	1260.250	45.67	-5.83	39.84			peak			
2	1575.441	42.91	-4.83	38.08			peak			
3	1890.646	39.94	-3.70	36.28			peak			
4	2276.982	34.35	-1.51	32.84	74.00	-41.16	peak			
5	2835.350	33.22	2.09	35.31			peak			
6	3290.507	31.24	4.52	35.76	74.00	-38.24	peak			



Site: 1# Chamber Tel:+86-0755-26503290

Fax:+86-0755-26503396





Job No.: DING #2830

ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd, Science & Industry Park,Nanshan Shenzhen,P.R.China

Polarization: Vertical
Power Source: DC 3V

Date: 16/11/10/ Time: 9/00/46

Engineer Signature: DING

Distance: 3m

Standard: FCC 15.231a 3M Radiated

Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %


EUT: REMOTE CONTROL

Mode: TX 315MHz


Model: FAN61T-4SP1

Manufacturer: CAREWELL


Note: Report NO.:ATE20162255




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	1260.250	40.11	-5.83	34.28			peak			
2	1575.441	38.41	-4.83	33.58			peak			
3	1890.646	35.93	-3.70	32.23			peak			
4	2367.658	34.30	-1.29	33.01	74.00	-40.99	peak			
5	2835.350	37.29	2.09	35.20			peak			
6	3341.377	42.00	4.68	37.32	74.00	-36.68	peak			








Date: 24.NOV.2016 17:39:51









Date: 07.Nov.2015 10:53:43

Release Time = 3.18s







The graph shows the pattern of coding during the signal transmission. The duration of one cycle = 34.3 ms.




Date: 24.NOV.2016 17:45:23







The graph shows the duration of 'on' signal. From marker 1 to marker 2, duration is 0.68ms.



The graph shows the duration of 'on' signal. From marker 1 to marker 2, duration is 0.38ms.