

**FCC/ISED**  
**RF**  
**TEST REPORT**

ISSUED BY  
Shenzhen BALUN Technology Co., Ltd.



FOR  
**Ring Keypad**

ISSUED TO  
LEEDARSON LIGHTING CO., LTD.

Xingtai Industrial Zone, Changtai County, Zhangzhou, Fujian, China



Tested by:	<u>Hu Chao</u>
	Hu Chao
	(Engineer)
Date	<u>Sep. 11. 2017</u>
Approved by:	<u>Wei Yanquan</u>
	Wei Yanquan
	(Chief Engineer)
Date	<u>Sep. 11. 2017</u>

Report No.:	BL-SZ1790048-601
EUT Name:	Ring Keypad
Model Name:	4AK1S70EN0
Brand Name:	LEEDARSON
Test Standard:	47 CFR Part 15 Subpart C RSS-210 Issue 9 (2016-8) RSS-Gen Issue 4 (2014-11)
FCC ID:	2AB2Q-BHAKP001
ISED Number:	10256A-BHAKP001
Test conclusion:	Pass
Test Date:	Sep. 04, 2017 ~ Sep. 06, 2017
Date of Issue:	Sep. 11, 2017

*NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. BALUN Laboratory. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.*

**Revision History**

Version	Issue Date	Revisions Content
Rev. 01	Sep. 11, 2017	Initial Issue

**TABLE OF CONTENTS**

1	ADMINISTRATIVE DATA (GENERAL INFORMATION) .....	5
1.1	Identification of the Testing Laboratory .....	5
1.2	Identification of the Responsible Testing Location .....	5
1.3	Laboratory Condition.....	5
1.4	Announce .....	5
2	PRODUCT INFORMATION .....	6
2.1	Applicant Information .....	6
2.2	Manufacturer Information .....	6
2.3	Factory Information .....	6
2.4	General Description for Equipment under Test (EUT) .....	6
2.5	Ancillary Equipment .....	7
2.6	Technical Information.....	7
2.7	Additional Instructions .....	8
3	SUMMARY OF TEST RESULTS.....	9
3.1	Test Standards .....	9
3.2	Verdict .....	9
4	GENERAL TEST CONFIGURATIONS .....	10
4.1	Test Environments .....	10
4.2	Test Equipment List .....	10
4.3	Measurement Uncertainty .....	11
4.4	Description of Test Setup .....	12
4.4.1	For Antenna Port Test .....	12
4.4.2	For AC Power Supply Port Test .....	12
4.4.3	For Radiated Test (Below 30 MHz) .....	13

4.4.4	For Radiated Test (30 MHz-1 GHz) .....	13
4.4.5	For Radiated Test (Above 1 GHz).....	14
5	TEST ITEMS.....	15
5.1	Antenna Requirements .....	15
5.1.1	Standard Applicable .....	15
5.1.2	Antenna Anti-Replacement Construction .....	15
5.1.3	Antenna Gain .....	15
5.2	20 dB and 99% Bandwidth .....	16
5.2.1	Limit.....	16
5.2.2	Test Setups .....	16
5.2.3	Test Procedure.....	16
5.2.4	Test Result .....	16
5.3	AC Conducted Emission .....	17
5.3.1	Limit.....	17
5.3.2	Test Setups .....	17
5.3.3	Test Procedure.....	17
5.3.4	Test Result .....	17
5.4	Radiated Spurious Emission .....	18
5.4.1	Limit.....	18
5.4.2	Test Setups .....	18
5.4.3	Test Procedure.....	18
5.4.4	Test Result .....	19
5.5	Band Edge (Restricted-band band-edge) .....	20
5.5.1	Limit.....	20
5.5.2	Test Setups .....	20
5.5.3	Test Procedure.....	20
5.5.4	Test Result .....	20
ANNEX A	TEST RESULT .....	21
A.1	<b>20 dB and 99% Bandwidth .....</b>	21
A.2	<b>AC Conducted Emission .....</b>	23

<b>A.3 Radiated Emission .....</b>	25
<b>A.4 Band Edge(Restricted-band band-edge) .....</b>	33
ANNEX B TEST SETUP PHOTOS .....	35
ANNEX C EUT EXTERNAL PHOTOS .....	35
ANNEX D EUT INTERNAL PHOTOS .....	35

# 1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

## 1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

## 1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1. The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The laboratory is a testing organization accredited by American Association for Laboratory Accreditation(A2LA) according to ISO/IEC 17025. The accreditation certificate is 4344.01. The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

## 1.3 Laboratory Condition

Ambient Temperature	20 to 25°C
Ambient Relative Humidity	45% - 55%
Ambient Pressure	100 kPa - 102 kPa

## 1.4 Announce

- (1) The test report reference to the report template version v2.2.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

## 2 PRODUCT INFORMATION

### 2.1 Applicant Information

Applicant	LEEDARSON LIGHTING CO., LTD.
Address	Xingtai Industrial Zone, Changtai County, Zhangzhou, Fujian, China

### 2.2 Manufacturer Information

Manufacturer	LEEDARSON LIGHTING CO., LTD.
Address	Xingtai Industrial Zone, Changtai County, Zhangzhou, Fujian, China

### 2.3 Factory Information

Factory	N/A
Address	N/A

### 2.4 General Description for Equipment under Test (EUT)

EUT Name	Ring Keypad
Model Name Under Test	4AK1S70EN0
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	N/A
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A
Network and Wireless connectivity	Z-Wave

## 2.5 Ancillary Equipment

Ancillary Equipment 1	Battery	
	Brand Name	Great Power
	Model No.	GSP454487
	Serial No.	N/A
	Capacitance	2200 mAh
	Rated Voltage	3.7 V
	Limit Charge Voltage	4.2 V
Ancillary Equipment 2	Adapter	
	Brand Name	INNOV
	Model No.	IVP0500-1000U
	Serial No.	N/A
	Rated Input	100-240 V~, 0.5 A, 50/60 Hz
Ancillary Equipment 3	Rated Output	
	USB Cable	5 V⎓, 1 A
	Length (Approx.)	2.0 m

## 2.6 Technical Information

The requirement for the following technical information of the EUT was tested in this report:

Modulation Type	FM
Product Type	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Frequency Range	902 MHz to 927 MHz
Tested Channel	Low (908.4 MHz), Middle (908.42 MHz), High (916 MHz)
Antenna Type	PCB Antenna
Antenna Gain	2.7 dBi (All involve the antenna gain test item, has been included in the final results)

## 2.7 Additional Instructions


EUT Software Settings:

Mode	<input checked="" type="checkbox"/> Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.
------	--

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power level setup in software			
Test Software Version	SSCOM3.2		
Support Units (Software installation media)	Description	Manufacturer	Model
	Laptop	Lenovo	E31-80
Mode	Channel	Frequency (MHz)	Soft Set
GFSK	High	916	Power parameter Settings is 63
	Middle	908.42	
	Low	908.4	

Run Software:



### 3 SUMMARY OF TEST RESULTS

#### 3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C (10-1-15 Edition)	Intentional Radiators
2	RSS-Gen (Issue 4, Nov. 2014)	General Requirements for Compliance of Radio Apparatus
3	RSS-210 (Issue 9, August 2016)	Licence-Exempt Radio Apparatus: Category I Equipment
4	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

#### 3.2 Verdict

No.	Description	FCC Part No.	ISED Part No.	Test Result	Verdict	Remark
1	Antenna Requirement	15.203	RSS-Gen 8.3	--	Pass	Note <sup>1</sup>
2	20 dB and 99% Bandwidth	15.215(c)	RSS-Gen 6.6	ANNEX A.1	Pass	--
3	AC Conducted Emission	15.207	RSS-Gen 8.8	ANNEX A.2	Pass	--
4	Radiated Spurious Emission	15.249(a)	RSS-210 B.10 RSS-Gen 8.9	ANNEX A.3	Pass	--
5	Band Edge(Restricted-band band-edge)	15.249(a)	RSS-210 B.10 RSS-Gen 8.10	ANNEX A.4	Pass	--

Note: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

## 4 GENERAL TEST CONFIGURATIONS

### 4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% - 55%		
Atmospheric Pressure	100 kPa - 102 kPa		
Temperature	NT (Normal Temperature)		+22°C to +25°C
Working Voltage of the EUT	NV (Normal Voltage)		5 V

### 4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2017.06.22	2018.06.21
Vector Signal Generator	ROHDE&SCHWARZ	SMBV100A	177746	2017.06.22	2018.06.21
Signal Generator	ROHDE&SCHWARZ	SMB100A	260592	2017.06.22	2018.06.21
Switch Unit with OSP-B157	ROHDE&SCHWARZ	OSP120	101270	2017.06.22	2018.06.21
Spectrum Analyzer	AGILENT	E4440A	MY45304434	2016.11.08	2017.11.07
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2017.06.22	2018.06.21
LISN	SCHWARZBECK	NSLK 8127	8127-687	2017.06.22	2018.06.21
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2017.06.22	2018.06.21
Power Splitter	KMW	DCPD-LDC	1305003215	--	--
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2017.06.22	2018.06.21
Attenuator (20 dB)	KMW	ZA-S1-201	110617091	--	--
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189	--	--
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2017.06.22	2018.06.21
Temperature Chamber	ANGELANTIONI SCIENCE	NTH64-40A	1310	2017.06.22	2018.06.21
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2017.06.22	2018.06.21
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2017.06.22	2018.06.21
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1148	2017.06.22	2018.06.21
Test Antenna-Horn(15-26.5 GHz)	SCHWARZBECK	BBHA 9170	9170-305	2017.06.22	2018.06.21
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2017.02.24	2019.02.23
Anechoic Chamber	EMC TECHNOLOGY LTD	21.1m*11.6m*7.35m	N/A	2016.08.09	2018.08.08
Shielded Enclosure	ChangNing	CN-130701	130703	--	--
Signal Generator	ROHDE&SCHWARZ	SMB100A	177746	2017.06.22	2018.06.21
Power Amplifier	OPHIR RF	5225F	1037	2017.02.17	2018.02.16

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Power Amplifier	OPHIR RF	5273F	1016	2017.02.17	2018.02.16
Directional Coupler	Werlantone	C5982-10	109275	N/A	N/A
Directional Coupler	Werlantone	CHP-273E	S00801z-01	N/A	N/A
Feld Strength Meter	Narda	EP601	511WX51129	2017.02.23	2018.02.22
Mouth Simulator	B&K	4227	2423931	2016.11.15	2017.11.14
Sound Calibrator	B&K	4231	2430337	2016.11.09	2017.11.08
Sound Level Meter	B&K	NL-20	00844023	2016.11.11	2017.11.10
Ear Simulator	B&K	4185	2409449	2016.11.15	2017.11.14
Ear Simulator	B&K	4195	2418189	2016.11.15	2017.11.14
Audio analyzer	B&K	UPL 16	100129	2016.11.08	2017.11.07

#### 4.3 Measurement Uncertainty


The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.


Measurement	Value
Occupied Channel Bandwidth	±4%
RF output power, conducted	±1.4 dB
Power Spectral Density, conducted	±2.5 dB
Unwanted Emissions, conducted	±2.8 dB
All emissions, radiated	±5.4 dB
Temperature	±1°C
Humidity	±4%

## 4.4 Description of Test Setup


### 4.4.1 For Antenna Port Test



### 4.4.2 For AC Power Supply Port Test




#### 4.4.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

#### 4.4.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

#### 4.4.5 For Radiated Test (Above 1 GHz)



**(Diagram 5)**

## 5 TEST ITEMS

### 5.1 Antenna Requirements

#### 5.1.1 Standard Applicable

FCC §15.203 & 15.247(b); RSS-Gen 8.3


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

#### 5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is An embedded-in	An embedded-in antenna design is used.

Reference Documents	Item
Photo	

#### 5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

## 5.2 20 dB and 99% Bandwidth

### 5.2.1 Limit

FCC §15.215(c);

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

RSS-Gen 6.6

The emission bandwidth ( $\times$ dB) is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated  $\times$  dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3 $\times$  the resolution bandwidth.

When the occupied bandwidth limit is not stated in the applicable RSS or reference measurement method, the transmitted signal bandwidth shall be reported as the 99% emission bandwidth, as calculated or measured

### 5.2.2 Test Setups

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.2.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW  $\geq$  1% of the 20 dB bandwidth

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

### 5.2.4 Test Result

Please refer to ANNEX A.1.

## 5.3 AC Conducted Emission

### 5.3.1 Limit

FCC §15.207; RSS-Gen 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB $\mu$ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

### 5.3.2 Test Setups

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.3.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

### 5.3.4 Test Result

Please refer to ANNEX A.2.

## 5.4 Radiated Spurious Emission

### 5.4.1 Limit

FCC §15.249(a); RSS-210 B.10& RSS-Gen 8.9

Except as provided in paragraph (a) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Frequency (MHz)	Field Strength of Fundamental (mV/m)	Field Strength of Harmonics (μV/m)
902-928	50	500
2400-2483.5	50	500
5725-5875	50	500

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.
2. For above 1000 MHz, limit field strength of harmonics: 54dB<sub>UV</sub>/m@3m (AV) and 74dB<sub>UV</sub>/m@3m (PK).

### 5.4.2 Test Setups

See section 4.4.2-4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.4.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented. The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1$  GHz, 100 kHz for  $f < 1$  GHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

#### 5.4.4 Test Result

Please refer to ANNEX A.3.

## 5.5 Band Edge (Restricted-band band-edge)

### 5.5.1 Limit

FCC §15.249(a); RSS-210 B.10&RSS-Gen 8.10

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

### 5.5.2 Test Setups

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.5.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1$  GHz, 100 kHz for  $f < 1$  GHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

### 5.5.4 Test Result

Please refer to ANNEX A.4.

## ANNEX A TEST RESULT


### A.1 20 dB and 99% Bandwidth

#### Test Data


Channel	Frequency (MHz)	20 dB Bandwidth (kHz)	99% Bandwidth (kHz)
High	916	2818	2656.9
Middle	908.42	96.54	93.231
Low	908.4	2731	2569.2

#### Test plots


##### Low Channel



## Middle Channel



## High Channel




## A.2 AC Conducted Emission

Note <sup>1</sup>: The EUT is working in the Normal link mode.


Note <sup>2</sup>: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz ) shown here.

### PHASE L



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.156	47.4	10.20	65.7	18.30	Peak	L Line	Pass
1**	0.156	27.3	10.20	55.7	28.40	AV	L Line	Pass
2	0.384	48.1	10.78	58.2	10.10	Peak	L Line	Pass
2**	0.384	36.2	10.78	48.2	12.00	AV	L Line	Pass
3	0.718	43.9	10.19	56.0	12.10	Peak	L Line	Pass
3**	0.718	28.7	10.19	46.0	17.30	AV	L Line	Pass
4	1.940	44.8	10.38	56.0	11.20	Peak	L Line	Pass
4**	1.940	30.3	10.38	46.0	15.70	AV	L Line	Pass
5	2.594	47.5	10.67	56.0	8.50	Peak	L Line	Pass
5**	2.594	34.4	10.67	46.0	11.60	AV	L Line	Pass
6	2.986	47.0	10.80	56.0	9.00	Peak	L Line	Pass
6**	2.986	33.2	10.80	46.0	12.80	AV	L Line	Pass

## PHASE N




No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.152	49.9	9.78	65.9	16.00	Peak	N Line	Pass
1**	0.152	27.9	9.78	55.9	28.00	AV	N Line	Pass
2	0.174	48.8	9.53	64.8	16.00	Peak	N Line	Pass
2**	0.174	28.6	9.53	54.8	26.20	AV	N Line	Pass
3	0.382	49.7	10.52	58.2	8.50	Peak	N Line	Pass
3**	0.382	37.3	10.52	48.2	10.90	AV	N Line	Pass
4	0.844	45.0	10.21	56.0	11.00	Peak	N Line	Pass
4**	0.844	29.0	10.21	46.0	17.00	AV	N Line	Pass
5	1.788	46.3	10.19	56.0	9.70	Peak	N Line	Pass
5**	1.788	32.4	10.19	46.0	13.60	AV	N Line	Pass
6	2.918	48.2	11.12	56.0	7.80	Peak	N Line	Pass
6**	2.918	34.3	11.12	46.0	11.70	AV	N Line	Pass

### A.3 Radiated Emission

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.


#### Test Data and Plots (30 MHz ~ 1 GHz)

Note: The bold frequency is the fundamental.




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	71.952	20.50	-18.37	30.0	9.50	Peak	165.00	200	Vertical	Pass
2	148.340	27.20	-18.67	33.5	6.30	Peak	2.00	200	Vertical	Pass
3	180.108	28.41	-16.89	33.5	5.09	Peak	1.00	100	Vertical	Pass
4	288.020	26.42	-12.52	36.0	9.58	Peak	5.00	100	Vertical	Pass
5	360.042	27.27	-10.53	36.0	8.73	Peak	5.00	100	Vertical	Pass
6	908.335	85.07	-0.74	36.0	-49.07	Peak	3.00	200	Vertical	N/A

## Low Channel 30 MHz to 1 GHz, ANT H




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	71.952	16.71	-18.37	30.0	13.29	Peak	344.00	100	Horizontal	Pass
2	95.960	26.38	-15.81	33.5	7.12	Peak	184.00	100	Horizontal	Pass
3	156.100	27.55	-18.23	33.5	5.95	Peak	337.00	100	Horizontal	Pass
4	240.005	27.06	-13.70	36.0	8.94	Peak	183.00	100	Horizontal	Pass
5	456.073	30.24	-8.57	36.0	5.76	Peak	29.00	100	Horizontal	Pass
6	908.335	100.04	-0.74	36.0	-64.04	Peak	2.00	100	Horizontal	N/A

## Middle Channel 30 MHz to 1 GHz, ANT V




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	71.952	21.18	-18.37	30.0	8.82	Peak	3.00	100	Vertical	Pass
2	95.960	26.38	-15.81	33.5	7.12	Peak	0.00	100	Vertical	Pass
3	108.085	26.27	-15.13	33.5	7.23	Peak	6.00	100	Vertical	Pass
4	180.108	27.68	-16.89	33.5	5.82	Peak	1.00	100	Vertical	Pass
5	360.042	26.88	-10.53	36.0	9.12	Peak	279.00	100	Vertical	Pass
6	908.335	81.24	-0.74	36.0	-45.24	Peak	3.00	100	Vertical	N/A

## Middle Channel 30 MHz to 1 GHz, ANT H




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	71.952	19.44	-18.37	30.0	10.56	Peak	66.00	100	Horizontal	Pass
2	95.960	26.77	-15.81	33.5	6.73	Peak	2.00	100	Horizontal	Pass
3	156.100	26.86	-18.23	33.5	6.64	Peak	4.00	100	Horizontal	Pass
4	240.005	27.66	-13.70	36.0	8.34	Peak	3.00	100	Horizontal	Pass
5	456.073	31.13	-8.57	36.0	4.87	Peak	3.00	100	Horizontal	Pass
6	908.335	100.54	-0.74	36.0	-64.54	Peak	1.00	100	Horizontal	N/A

## High Channel 30 MHz to 1 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	71.952	21.18	-18.37	30.0	8.82	Peak	321.00	100	Vertical	Pass
2	148.098	28.44	-18.68	33.5	5.06	Peak	5.00	100	Vertical	Pass
3	180.108	28.94	-16.89	33.5	4.56	Peak	2.00	100	Vertical	Pass
4	215.998	29.28	-14.97	33.5	4.22	Peak	5.00	100	Vertical	Pass
5	360.042	26.37	-10.53	36.0	9.63	Peak	190.00	100	Vertical	Pass
6	916.095	78.52	-0.67	36.0	-42.52	Peak	3.00	100	Vertical	N/A

## High Channel 30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	71.952	17.76	-18.37	30.0	12.24	Peak	295.00	100	Horizontal	Pass
2	95.960	27.17	-15.81	33.5	6.33	Peak	1.00	100	Horizontal	Pass
3	156.100	26.61	-18.23	33.5	6.89	Peak	0.00	100	Horizontal	Pass
4	240.005	27.32	-13.70	36.0	8.68	Peak	4.00	100	Horizontal	Pass
5	491.962	30.75	-7.78	36.0	5.25	Peak	5.00	100	Horizontal	Pass
6	915.610	98.82	-0.68	36.0	-62.82	Peak	1.00	100	Horizontal	N/A

Test Data and Plots (1 GHz ~ 10th Harmonic)

Note <sup>1</sup>: The marked is the harmonic signal.

Note <sup>2</sup>: Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Note <sup>3</sup>: Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Note <sup>4</sup>: Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20 dB from the applicable limit) and considered that's already beyond the background noise floor.

Note <sup>5</sup>: Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.

**LOW CHANNEL 1 GHz to 10 GHz, ANT V**

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1617.500	52.51	-5.56	74.0	21.49	Peak	153.70	150	Vertical	Pass
2	2126.500	48.46	-2.65	74.0	25.54	Peak	37.20	150	Vertical	Pass
3	3747.750	48.35	8.76	74.0	25.65	Peak	93.60	150	Vertical	Pass
4	5124.000	53.10	13.40	74.0	20.90	Peak	248.10	150	Vertical	Pass
5	6359.000	52.53	13.66	74.0	21.47	Peak	360.60	150	Vertical	Pass
6	9084.000	53.80	18.75	74.0	20.20	Peak	84.80	150	Vertical	Pass

**LOW CHANNEL 1 GHz to 10 GHz, ANT H**

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1816.500	47.84	-4.96	74.0	26.16	Peak	132.80	150	Horizontal	Pass
2	2258.500	46.26	-2.03	74.0	27.74	Peak	155.50	150	Horizontal	Pass
3	3709.500	48.15	8.45	74.0	25.85	Peak	326.60	150	Horizontal	Pass
4	4974.750	52.52	12.67	74.0	21.48	Peak	287.20	150	Horizontal	Pass
5	5986.500	52.24	13.13	74.0	21.76	Peak	359.60	150	Horizontal	Pass
6	9051.000	53.28	18.28	74.0	20.72	Peak	141.80	150	Horizontal	Pass

**MIDDLE CHANNEL 1 GHz to 10 GHz, ANT V**

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1652.000	51.91	-5.20	74.0	22.09	Peak	284.00	150	Vertical	Pass
2	2125.500	47.31	-2.67	74.0	26.69	Peak	3.00	150	Vertical	Pass
3	2934.500	47.50	0.41	74.0	26.50	Peak	6.00	150	Vertical	Pass
4	4542.000	50.71	10.56	74.0	23.29	Peak	1.00	150	Vertical	Pass
5	5983.500	53.30	13.14	74.0	20.70	Peak	4.00	150	Vertical	Pass
6	6359.000	52.66	13.66	74.0	21.34	Peak	83.00	150	Vertical	Pass

**MIDDLE CHANNEL 1 GHz to 10 GHz, ANT H**

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1687.500	46.03	-5.33	74.0	27.97	Peak	267.00	150	Horizontal	Pass
2	1816.500	48.34	-4.96	74.0	25.66	Peak	137.70	150	Horizontal	Pass
3	3440.250	47.07	7.12	74.0	26.93	Peak	197.20	150	Horizontal	Pass
4	5094.750	52.90	13.19	74.0	21.10	Peak	1.70	150	Horizontal	Pass
5	5923.500	52.60	13.37	74.0	21.40	Peak	52.80	150	Horizontal	Pass
6	9149.000	53.45	18.15	74.0	20.55	Peak	3.00	150	Horizontal	Pass

**HIGH CHANNEL 1 GHz to 10 GHz, ANT V**

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1654.000	53.11	-5.22	74.0	20.89	Peak	55.00	150	Vertical	Pass
2	2124.500	49.44	-2.71	74.0	24.56	Peak	4.00	150	Vertical	Pass
3	4575.750	51.63	10.55	74.0	22.37	Peak	0.00	150	Vertical	Pass
4	5040.000	52.54	13.23	74.0	21.46	Peak	2.00	150	Vertical	Pass
5	6409.000	51.63	13.18	74.0	22.37	Peak	1.00	150	Vertical	Pass
6	9494.000	53.36	17.55	74.0	20.64	Peak	3.00	150	Vertical	Pass

**HIGH CHANNEL 1 GHz to 10 GHz, ANT H**

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1682.000	46.21	-5.45	74.0	27.79	Peak	121.70	150	Horizontal	Pass
2	1830.500	49.24	-4.74	74.0	24.76	Peak	135.30	150	Horizontal	Pass
3	4569.000	50.52	10.52	74.0	23.48	Peak	128.20	150	Horizontal	Pass
4	5547.750	53.24	12.95	74.0	20.76	Peak	241.60	150	Horizontal	Pass
5	5972.250	53.48	13.14	74.0	20.52	Peak	13.90	150	Horizontal	Pass
6	9132.000	53.22	18.48	74.0	20.78	Peak	64.00	150	Horizontal	Pass


## A.4 Band Edge(Restricted-band band-edge)

### Test Data and Test Plots


Note: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Test Mode	Test Channel	Frequency (MHz)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Remark	Verdict
FM	Low	611.98	28.46	74	45.54	PEAK	Pass
		611.98	N/A	54	N/A	AVERAGE	Pass
FM	HIGH	1234.4	42.62	74	31.38	PEAK	Pass
		1234.4	N/A	54	N/A	AVERAGE	Pass

### LOW CHANNEL



## HIGH CHANNEL



## ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ1790048-DFS.PDF”.

## ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ1790048-AW.PDF”.

## ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ1790048-AI.PDF”.

--END OF REPORT--