

FCC 47 CFR MPE REPORT

ION Audio, LLC

15" GROUND-SHAKING SPEAKER SYSTEM WITH WIRELESS MICROPHONE

Model Number: Total PA™ Quake

Additional Model: TOTAL PA™ QUAKE, iPA180, TOTAL PA*****,

Total PA***** , iPA180***** ("**" can be "a-z", "A-Z", "0-9", blank, "-", "+" or any character, symbol, alphanumeric)

FCC ID: 2AB3E-IPA180

Applicant:	ION Audio, LLC
Address:	200 Scenic View Drive, Cumberland, RI 02864, USA
Prepared By:	EST Technology Co., Ltd.
Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China	
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2503170
Date of Test:	Jan. 06, 2025~ Mar. 13, 2025
Date of Report:	Mar. 17, 2025

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)
GFSK	2402	0.08	1.019
	2441	-1.35	0.733
	2480	-3.56	0.441
$\pi/4$ -DQPSK	2402	0.11	1.026
	2441	-1.38	0.728
	2480	-3.63	0.434
8-DPSK	2402	0.15	1.035
	2441	-1.02	0.791
	2480	-3.49	0.448
BLE 1M	2402	-0.20	0.955
	2440	-1.78	0.664
	2480	-4.11	0.388

3. Calculated Result and Limit

Mode	Peak output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW /cm ²)	Limited of Power Density (S) (mW /cm ²)	Test Result
				(dBi)	(Linear)			
GFSK	0.08	0±1	1	1.16	1.306	0.00033	1	Complies
π/4-DQPSK	0.11	0±1	1	1.16	1.306	0.00033	1	Complies
8-DPSK	0.15	0±1	1	1.16	1.306	0.00033	1	Complies
BLE 1M	-0.20	0±1	1	1.16	1.306	0.00033	1	Complies

End of Test Report