



RF EXPOSURE REPORT

Applicant	:	ION Audio LLC
Address of Applicant	:	200 Scenic View Drive, Suite 201 Cumberland, RI 02864, U.S.A.
Manufacturer	:	ION Audio LLC
Address of Manufacturer	:	200 Scenic View Drive, Suite 201 Cumberland, RI 02864, U.S.A.
Equipment under Test	:	BATTERY-POWERED PA SPEAKER WITH WIRELESS MICROPHONE AND DYNAMIC LIGHTS
FCC Model No.	:	TOTAL PA™ APEX, iPA185A, TOTAL PA***** iPA185***** (“*” can be “0-9”, “a-z”, “A-Z”, “blank”, “-”, “+” or any character, symbol, alphanumeric for marketing purpose)
Project Code	:	iPA185A
FCC ID	:	2AB3E-IPA185A
Test Standard(s)	:	KDB447498 D01 General RF Exposure Guidance v06
Report No.	:	DDT-RE24092711-1E03
Issue Date	:	2025/01/16
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1. General Test Information..... 5

1.1. Description of EUT..... 5

1.2. Accessories of EUT 5

1.3. Test laboratory 6

2. RF Exposure evaluation for FCC..... 7

2.1. Assessment procedure 7

2.2. Assess result..... 8

Test Report Declare

Applicant	:	ION Audio LLC
Address of Applicant	:	200 Scenic View Drive, Suite 201 Cumberland, RI 02864, U.S.A.
Equipment under Test	:	BATTERY-POWERED PA SPEAKER WITH WIRELESS MICROPHONE AND DYNAMIC LIGHTS
FCC Model No.	:	TOTAL PA™ APEX, iPA185A, TOTAL PA***** iPA185***** ("*" can be "0-9", "a-z", "A-Z", "blank", "-", "+" or any character, symbol, alphanumeric for marketing purpose)
Manufacturer	:	ION Audio LLC
Address of Manufacturer	:	200 Scenic View Drive, Suite 201 Cumberland, RI 02864, U.S.A.

Test Standard Used:

KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE24092711-1E03		
Date of Receipt:	2024/10/10	Date of Test:	2024/10/10~2025/01/16

Prepared By:**Johnson Huang/Engineer****Approved By:****Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2025/01/16	

1. General Test Information

1.1. Description of EUT

EUT Name	: BATTERY-POWERED PA SPEAKER WITH WIRELESS MICROPHONE AND DYNAMIC LIGHTS
Model Number	: TOTAL PA™ APEX, TOTAL PA™ APEX, TOTAL PA***** : iPA185***** (“*” can be “0-9”, “a-z”, “A-Z”, “blank”, “-”, “+” or any character, symbol, alphanumeric for marketing purpose)
Difference of model number	: All models are identical except the appearance colour and model number, therefore the test performed on the model TOTAL PA™ APEX.
EUT Function Description	: Please reference user manual of this device
Power Supply	: AC 100-240V~50/60Hz or DC 11.1V Li-ion built-in battery
Antenna Type	: PCB
Max Antenna Gain(dBi)	: 1.16

Note: This EUT support Bluetooth BR/EDR/LE .

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“☒” means to be chosen or applicable; “☐” means don't to be chosen or not applicable; This note applies to entire report.

1.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description	Other
AC cable	N/A	N/A	Length: 1.5m, unshielded	N/A
Wireless microphone	N/A	N/A	N/A	N/A
Support lever	N/A	N/A	N/A	N/A
Built-in battery	Shenzhen Hainengtong Eneregy Co., Ltd.	18650-11.1V-6000mAh-3S3P	11.1Vdc, 6000mAh, 66.6Wh, lithium-ion type	Optional
Built-in battery	Dongguan Wiliyoung Electronics Co., Ltd.	WLY 18650-3S3P	11.1Vdc, 6000mAh, 66.6Wh, lithium-ion type	
Built-in battery	Power7 Technology Co., Ltd.	B18650-201C-91	11.1Vdc, 6000mAh, 66.6Wh, lithium-ion type	
Transformer T1	Eaglerise Electric & Electronic (Ji An) Co., Ltd.	PSM-0100-022U	Input:100-240V~, 50/60Hz	Optional
Transformer T1	FOSHAN SHUNDE WECAN	PQ3220-2409192WK	Input:100-240V~, 50/60Hz	

	ELECTRONICS CO., LTD			
Transformer T1	Shenzhen Tianfuxiang Technology Co., Ltd.	PSM-0100- 022U	Input:100-240V~, 50/60Hz	

1.3. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2. RF Exposure evaluation for FCC

2.1. Assessment procedure

Requirement:

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100000			1.0	30

Note: f= frequency in MHz; *Plane-wave equivalent power density

Calculation method

$$E(\text{V/m}) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(\text{mW/cm}^2) = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (mW)

G = EUT Antenna numeric gain (numeric)=

d = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, $d=0.2$ m, as well as the gain of the used antenna, the RF power density can be obtained.

2.2. Assess result

Mode	Antenna	Output power (dBm)	Output power (mW)	tune up power (dBm)	tune up power (mW)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm ²)	MPE Limit (mW/cm ²)
BT	Ant1	-3.36	0.46	-3	0.50	1.16	1.31	0.00013	1
	Ant2	-4.18	0.38	-4	0.40	1.16	1.31	0.00010	1
BLE	Ant1	-3.67	0.43	-3	0.50	1.16	1.31	0.00013	1
	Ant2	-5.09	0.31	-5	0.32	1.16	1.31	0.00008	1

Simultaneous transmit evaluation result: BT Ant1+BT Ant2=0.00013+0.00010=0.00023<1.

Note: The estimation distance is 20 cm

Please refer to the test report "DDT-RE24092711-1E01 and DDT-RE24092711-1E02".

Conclusion: MPE evaluation required since transmitter power is below FCC threshold

-----End Report-----